

Building Technologies Program

Tax Deduction Qualified Software

Hourly Analysis Program (HAP) version 4.41.0.6

On this page you'll find information about the HAP version 4.41.0.6 <u>qualified computer software</u> (<u>buildings.energy.gov/qualified_software.html</u>), which calculates energy and power cost savings that meet federal tax incentive requirements for commercial buildings.

Date Documentation Received by DOE: 10 April 2009

Statements in quotes are from the software developer.

Internal Revenue Code §179D (c)(1) and (d) Regulations Notice 2006-52, Section 6 requirements as amplified by Notice 2008-40, Section 4 requirements. (1) The name, address, and (if applicable) web site of the software Carrier / United Technologies developer: Corporation Carrier Software Systems Bldg TR-4, Room 400A P. O. Box 4808 Syracuse, New York 13221 (2) The name, email address, and telephone number of the person to Carrier Software Systems contact for further information regarding the software; Software.systems@carrier.utc.com +1 (800) 253-1794 (3) The name, version, or other identifier of the software as it will Hourly Analysis Program version appear on the list; 4.41.0.6 Provided to DOE. (4) All test results, input files, output files, weather data, modeler reports, and the executable version of the software with which the tests were conducted; and (5) A declaration by the developer of the software, made under penalties of perjury, that-(a) The software has been tested according to ANSI/ASHRAE "The software has been tested Standard 140-2007 Standard Method of Test for the Evaluation of according to ANSI/ASHRAE Standard Building Energy Analysis Computer Programs; 140-2007 Standard Method of Test for the Evaluation of Building Energy Analysis Computer Programs." (b) The software can model explicitly— "Carrier HAP v4.41 complies." (i) 8,760 hours per year; (ii) Calculation methodologies for the building components being "Carrier HAP v4.41 complies." modeled; (iii) Hourly variations in occupancy, lighting power, miscellaneous "Carrier HAP v4.41 complies." equipment power, thermostat setpoints, and HVAC system operation, defined separately for each day of the week and holidays; (iv) Thermal mass effects; "Carrier HAP v4.41 complies."

(vi) Ten or more thermal zones: (vi) Part-load performance curves for mechanical equipment: (vii) Capacity and efficiency correction curves for mechanical heating and cooling equipment; and (viii) Air-side and water-side economizers with integrated control. (vii) Packaged Terminal Air Conditioner (PTAC) (air source), single-zone package (through the wail), multi-zone into your collection, air-to-air DX coll cooling, central boiler, hot water coll. (vii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coll cool, gas coil, constant-speed fan. (vi) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coll cool/heat, constant-speed fan. (vi) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coll, VAV fan, boller, hot water VAV boxes. (vii) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PPP boxes), multi-zone air, DX coll, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boller, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PPP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, vav fan, chiller, fan-powered induction boxes, electric reheat. (d) The software cane explicitly model for determining energy use by energy source suitable for determining energy and power costs or produce hourly	The state of the s	
(viii) Air-side and water-side economizers with integrated control. (viii) Air-side and water-side economizers with integrated control. (c) The software can explicitly model each of the following HVAC systems listed in Appendix G of Standard 90.1-2004: (i) Packaged Terminal Air Conditioner (PTAC) (air source), single-zone package (through the wall), multi-zone hydronic loop, air-to-air DX coil cooling, central boller, hot water coil. (ii) Packaged Single Zone Air Conditioner (PSAC) (air source), single-zone package (through the wall), air-to-air DX coil no water coil. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (vi) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV bern mind boxes. (vii) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power c	(v) Ten or more thermal zones;	"Carrier HAP v4.41 complies."
heating and cooling equipment: and (viii) Air-side and water-side economizers with integrated control. (c) The software can explicitly model each of the following HVAC systems listed in Appendix G of Standard 90.1-2004: (i) Packaged Terminal Air Conditioner (PTAC) (air source), singlezone package (through the wall), multi-zone hydronic loop, air-to-air DX coil cooling, central boiler, hot water coil. (ii) Packaged Terminal Heat Pump (PTHP) (air source), singlezone package (through the wall), air-to-air DX coil heat/cool. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Air Conditioner (PSZ-AFIP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV breminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (vi) Bither directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (i) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (ii) Natural ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation.	(vi) Part-load performance curves for mechanical equipment;	"Carrier HAP v4.41 complies."
(c) The software can explicitly model each of the following HVAC systems listed in Appendix G of Standard 90.1-2004: (i) Packaged Terminal Air Conditioner (PTAC) (air source), single-zone package (through the wail), multi-zone hydronic loop, air-to-air DX coil cooling, central boiler, hot water coil. (ii) Packaged Terminal Heat Pump (PTHP) (air source), single-zone package (through the wail), air-to-air DX coil heat/cool. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (iv) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, vAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-to-air DX coil, vAV fan, fan-powered induction boxes, electric reheat. (viii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, vAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, vAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately: and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation.		"Carrier HAP v4.41 complies."
(i) Packaged Terminal Air Conditioner (PTAC) (air source), single- zone package (through the wail), multi-zone hydronic loop, air-to- air DX coil cooling, central boiler, hot water coil. (ii) Packaged Terminal Heat Pump (PTHP) (air source), single- zone package (through the wail), air-to-air DX coil heat/cool. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, vAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi- zone hydronic loop, air-handling unit, chilled water coil, vAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, vav fan-volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software cam— (i) Elther directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately: and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) vent	(viii) Air-side and water-side economizers with integrated control.	"Carrier HAP v4.41 complies."
zone package (through the wall), multi-zone hydronic loop, air-to-air DX coil cooling, central boiler, hot water coil. (ii) Packaged Terminal Heat Pump (PTHP) (air source), single-zone package (through the wall), air-to-air DX coil heat/cool. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Air Conditioner (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software cam— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	1 3	ms listed in Appendix G of Standard
zone package (through the wall), air-to-air DX coil heat/cool. (iii) Packaged Single Zone Air Conditioner (PSZ-AC), single-zone air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, vav fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	zone package (through the wall), multi-zone hydronic loop, air-to-	
air, air-to-air DX coil cool, gas coil, constant-speed fan. (iv) Packaged Single Zone Heat Pump (PSZ-HP), single-zone air, air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, NAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air; multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, NAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, not water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation.		
air-to-air DX coil cool/heat, constant-speed fan. (v) Packaged Variable-Air-Volume (PVAV) with reheat, multi-zone hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (iv) Mixed mode (natural and mechanical) ventilation. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (VAV water coil, hot water		
hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV terminal boxes. (vi) Packaged Variable-Air-Volume with parallel fan powered boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (ivii) Mixed mode (natural and mechanical) ventilation. (ivii) Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."		
boxes (PVĀV with PFP boxes), multi-zone air, DX coil, VAV fan, fan-powered induction boxes, electric reheat. (vii) Variable-Air-Volume (VAV) with reheat, multi-zone air; multi-zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (iviii) Mixed mode (natural and mechanical) ventilation. (iviii) Mixed mode (natural and mechanical) ventilation. (iviii) Variable-Air-Volume vith parallel fan powered boxes (VAV water only of the system configuration." (Carrier HAP v4.41 models this system configuration." (Carrier HAP v4.41 complies." (Carrier HAP v4.41 complies." (Carrier HAP v4.41 complies." (Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	hydronic loop, air-to-air DX coil, VAV fan, boiler, hot water VAV	
zone hydronic loop, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, boiler, hot water VAV boxes. (viii) Variable-Air-Volume with parallel fan powered boxes (VAV with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology." "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	boxes (PVAV with PFP boxes), multi-zone air, DX coil, VAV fan,	
with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes, electric reheat. (d) The software can— (i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Mixed mode (natural and mechanical) ventilation. (iii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology." "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	zone hydronic loop, air-handling unit, chilled water coil, hot water	
(i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. (ii) Natural ventilation. (iii) Mixed mode (natural and mechanical) ventilation. (iv) Mixed mode (natural and mechanical) ventilation.	with PFP boxes), multi-zone air, air-handling unit, chilled water coil, hot water coil, VAV fan, chiller, fan-powered induction boxes,	
hourly reports of energy use by energy source suitable for determining energy and power costs separately; and (ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology." (ii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	(d) The software can—	
equipment capacities and air and water flow rates. (e) The software can explicitly model: (i) Natural ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology." (ii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	hourly reports of energy use by energy source suitable for	"Carrier HAP v4.41 complies."
(i) Natural ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology." (ii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."		"Carrier HAP v4.41 complies."
model this feature and shall not be used for projects with that technology." (ii) Mixed mode (natural and mechanical) ventilation. "Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."	(e) The software can explicitly model:	
model this feature and shall not be used for projects with that technology."	(i) Natural ventilation.	model this feature and shall not be used for projects with that
(iii) Earth tempering of outdoor air "Carrier HAP v4 41 does not explicitly	(ii) Mixed mode (natural and mechanical) ventilation.	model this feature and shall not be used for projects with that
(iii) Estati tempering of outdoor an.	(iii) Earth tempering of outdoor air.	"Carrier HAP v4.41 does not explicitly

	model this feature and shall not be used for projects with that technology."
(iv) Displacement ventilation.	"Carrier HAP v4.41 does not explicitly model this feature but can model by equivalent means."
(v) Evaporative cooling.	"Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."
(vi) Water use by occupants for cooking, cleaning or other domestic uses.	"Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."
(vii) Water use by heating, cooling, or other equipment, or for onsite landscaping.	"Carrier HAP v4.41 does not explicitly model this feature and shall not be used for projects with that technology."
(viii) Automatic interior or exterior lighting controls (such as occupancy, photocells, or time-clocks).	"Carrier HAP v4.41 can explicitly model automatic interior or exterior lighting controls such as occupancy sensors or time-clocks, but cannot model photocells."
(ix) Daylighting (sidelighting, skylights, or tubular daylight devices).	"Carrier HAP v4.41 does not explicitl model this feature and shall not be used for projects with that technology."
(x) Improved fan system efficiency through static pressure reset.	"Carrier HAP v4.41 does not explicitl model this feature and shall not be used for projects with that technology."
(xi) Radiant heating or cooling (low or high temperature).	"Carrier HAP v4.41 does not explicitl model this feature but can model by equivalent means."
(xii) Multiple or variable-speed control for fans, cooling equipment, or cooling towers.	"Carrier HAP v4.41 explicitly models these features."
(xiii) On-site energy systems (such as combined heat and power systems, fuel cells, solar photovoltaic, solar thermal, or wind).	"Carrier HAP v4.41 does not explicitly model these features and shall not be used for projects with that technology."