USAGE FACTORS FOR MAJOR HIGHWAY CONSTRUCTION MATERIALS AND LABOR 1/

U.S. WEIGHTED AVERAGES FOR ALL FEDERAL-AID HIGHWAY CONSTRUCTION CONTRACTS OVER \$1,000,000 ON THE NATIONAL HIGHWAY SYSTEM REPORTED AS COMPLETED DURING CALENDAR YEARS 1993, 1994, 1995

FEDERAL-AID AND DESIGN DIVISION OFFICE OF ENGINEERING

TABLE PT-4 OCTOBER 1996

TYPE OF MATERIALS AND LABOR	UNIT	NUMBER OF UNITS PER MILLION DOLLARS OF CONSTRUCTION COST 2/
Cement (excludes cement in concrete pipe)	Ton	1,274
Bituminous material	Ton	452
Aggregates 3/		
Purchased (by contractors)	Ton	15,504
Produced (by contractors)	Ton	3,999
Steel		
Structural (shapes, plates, H and sheet piling)	Ton	27
Reinforcing (pavement and structural reinforcement)	Ton	48
Culvert pipe (corrugated metal and structural		
plate, pipe arches and arches)	Ton	2
Miscellaneous (joint devices, tubular piling, etc.)	Ton	4
Concrete pipe (plain and reinforced)	Ton	79
Clay pipe and title (includes some pvc pipe)	Ton	1
Lumber (all lumber products except timber piling)	Board foot	7,451
Petroleum products 4/	Gallon	25,979
Guardrail (all types)	Linear foot	733
Bridge railing (all types)	Linear foot	204
Corrugated aluminum culvert	Pound	121
Signs (complete in place)	Dollar	10,188
Lighting (complete in place)	Dollar	11,103
Labor	Employee-hour	12,681

^{1/} For comparable standards of design, the usage of materials and labor on Federal-aid work is not appreciably different from their usage on non-Federal-aid work. The data in this table are obtained from Form FHWA-47.

- 2/ Right-of-way, preliminary engineering, and construction engineering costs excluded.
- 3/ Includes sand, gravel, clay gravel, slag, crushed stone, etc.; used for all highway construction including bases, subbases, concrete surfaces, bituminous surfaces, structural concrete, and drainage work.
- 4/ Fuel and lubricants for equipment and trucks. Grease converted to gallons on basis of 8 pounds per gallon.