

High Performance K-12 Building Design

Thomas Fernandez, Energy Manager Colorado Springs School District 11 (719)477-6011 fernatom@d11.org

EPA State Clean Energy-Environment Technical Forum December 8, 2005

D11's New Schools



- 4 different design teams
- Attractive designs
- Highly functional
- Excellent comfort levels
- D11's best student achievement scores

Energy Performance



- Trailblazer Elementary 68 KBTU/SF/YR
- Scott Elementary
- Jenkins Middle
- Tesla Middle

- D11 Average
- National K-12

71 KBTU/SF/YR

76 KBTU/SF/YR

101 KBTU/SF/YR

70 KBTU/SF/YR

80 KBTU/SF/YR

Energy Use Index




(Gas+Electric)/Total Sq. Ft. = KBTU/SF/YR





D11 Energy Cost & Use




Lessons Learned



- No clear understanding of HP buildings
- No clear understanding of HP design
- No specific building energy goals
- Traditional "architect down" design
- Passive during design

Traditional Design Hierarchy





Traditional Design Process



- Owner sets budget & functional scope
- Architect designs for form & function
- Mechanical & electrical systems must fit around architect's design
- Minimal interaction between disciplines
- Fixed design fees no incentive

High Performance Design Process



- Form & function designed around HVAC and lighting systems
- Maximizes use of natural lighting, heating, cooling, ventilation
- Reduced equipment sizing & run time
- Reduces energy use

Integrated Design Team



- All team members onboard from concept
- Energy goals clearly understood
- Architect allows team to interact freely & collaboratively to achieve energy goals
- The power of performance based fees
- Design process costs more

High Performance Energy Difference




- K-12 High Performance 25KBTU/SF/YR
- K-12 National average 80KBTU/SF/YR
- Does not have to cost more to build
- LEED certification doesn't guarantee high performance
- Higher design cost quick payback



The Lifecycle Cost Difference

Lifecycle Cummulitave Difference Trailbalzer Elementary



Owner Responsibilities



- Understands the HP concept
- Sets specific energy goals
- Finds the right design team
- Budgets for higher design fees
- Hire an integrated design process expert

D11 Building Performance Goals



- 25 KBTU/SF/YR total building energy
- 2.4 GAL/SF/YR domestic water
- 4.5 GAL/SF/YR irrigation
- Power factor > 0.95 lag
- Elementary school construction <\$110/SF

D11 Authored Documents



- Educational / Functional Specifications
- High Performance Design Specifications
- RFP for design services
- Performance based fee schedule


Finding The Right Team



- Ask for documented KBTU/SF/YR results for similar building type
- Demonstrated use of integrated design team approach
- Willing to accept performance based fees
- Don't rely on LEED certification

Owner Direct A New Alternative





Owner Direct Design Team Structure



- Owner direct HP expert project manager
- Owner direct all design disciplines
- Design team free to meet design goals collaboratively without traditional barriers
- Performance bonus for all members.

Useful Tools



- During design EPA Energy Star "Target Finder" tool - KBTU/SF/YR
- During verification EPA Energy Star "Portfolio Manager" benchmarking tool KBTU/SF/YR

Conclusion



- High performance buildings are achievable
- They don't have to cost more
- They already exist go visit them
- But it won't happen without a educated determined owner – at least not yet!
- It's the right thing to do for generations to come

Contact Information



Thomas Fernandez, Energy Manager Colorado Springs School District 11 (719) 477-6011 fernatom@d11.org