

## LIST OF TABLES

1.1	Main Performance Characteristics of the NSLS-II Storage Ring.....	1-2
2.1	Level 2 Cost Breakout for the NSLS-II Project .....	2-4
2.2	Preliminary Level 0 Milestone Schedule .....	2-4
3.2.1	Coherent Diffraction Measurement Considerations at NSLS-II.....	3-5
3.2.2	Required Coherent Flux Density, Equivalent Dose, and Measurement Times .....	3-6
4.1.1	Main Parameters of the NSLS-II Storage Ring .....	4-3
4.1.2	Main Parameters of the NSLS-II Injector .....	4-6
4.2.1	Goals for the NSLS-II Lattice .....	4-8
4.2.2	Restrictions on the NSLS-II Linear Lattice Design.....	4-8
4.2.3	Storage Ring Parameters for Number of DBA Lattice Cells Varying from 32 to 24 .....	4-10
4.1.1	Main Parameters of the NSLS-II Storage Ring.....	4-3
5.1	User Requirements.....	5-1
5.1.2	Storage Ring Parameters Related to the NSLS-II Injector .....	5-2
5.3.1	Magnet Characteristics.....	5-7
5.3.2	Linac-to-Booster Power Supplies .....	5-8
5.4.1	Linac Diagnostics .....	5-9
5.5.1	Field and Alignment Tolerance for the Booster Magnets .....	5-14
5.5.2	NSLS-II (3 GeV) Booster Lattice Parameters.....	5-15
5.6.1	Booster Magnet Parameters .....	5-16
5.6.2	Booster Dipole Parameters .....	5-18
5.6.3	Booster Quadrupole Magnet Parameters at 3 GeV .....	5-20
5.6.4	Booster Sextupole Parameters at 3 GeV .....	5-22
5.6.5	Power Supply Specifications.....	5-32
5.7.1	Vacuum Components for the Linac and Booster Vacuum Systems.....	5-37
5.8.1	RF and Beam Parameters for the Booster .....	5-37
5.8.2	Parameters for the Five-Cell PETRA Cavity .....	5-38
5.8.3	Tube Parameters for TH793 Inductive Output Tube Transmitter .....	5-38
5.9.1	Booster Pulsed Magnet Parameters .....	5-40
5.10.1	Magnet Parameters of the Booster-to-Storage Ring Transport Line .....	5-42
5.10.2	Booster-to-Storage Ring Transport Line Power Supplies.....	5-42
5.11.1	Beam Diagnostics for the Booster Ring .....	5-44
5.11.2	RF BPM Specifications.....	5-45
5.11.3	Booster current Monitor Specifications .....	5-45
5.11.4	Filling Pattern Specifications for the Fast Current Transformer .....	5-45
5.11.5	Beam Loss Monitor Specifications .....	5-46
6.1.1	Goals for the NSLS-II Design .....	6-1
6.1.2	Storage Ring Parameters.....	6-4
6.1.3	Effect of Three and Eight 7m Damping Wigglers on Beam Properties at 3 GeV.....	6-5
6.1.4	Magnets and BPMs for the NSLS-II Storage Ring.....	6-7
6.1.5	Dynamic Aperture Guidelines .....	6-8
6.1.6	Residual Normalized LIE Generators.....	6-15
6.1.7	Optics Tolerances for Robust DA of the NSLS-II Lattice.....	6-17
6.1.8	Transverse Magnet Alignment Tolerances .....	6-18
6.1.9	Tolerance Levels for MRS Normalized Multipole Errors .....	6-19
6.1.10	Insertion Device Parameters and Their Impact on the Vertical Tune .....	6-19

6.1.11	RMS Normalized Field Errors for Insertion Devices (CPMU, $R = 20\text{mm}$ ) .....	6-19
6.1.12	Effect of Mechanical Tolerances on the Magnetic Field Quality .....	6-24
6.1.13	Lie Generators from the Sextupole Scheme and a Single ID .....	6-29
6.1.14	Emittance Increase Due to Canting of the DW and the CPMU Undulator .....	6-31
6.2.1	Analytic Expressions for Impedance and Wakefield .....	6-37
6.2.2	Impedance Model .....	6-38
6.2.3	Parameters for Threshold Calculations .....	6-38
6.2.4	CESR-B Higher Order Longitudinal Modes .....	6-43
6.2.5	CESR-B Higher Order Transverse Modes .....	6-45
6.2.6	Calculated Impedance for Storage Ring Components .....	6-46
6.2.7	Description [includes drawings] of Components .....	6-47
6.2.1	Analytic Expressions for Impedance and Wakefield .....	6-37
7.1.1	Storage Ring Magnet Parameters at a 3 GeV Beam Energy, with Basic Tolerances .....	7-1
7.1.2	Storage Ring Magnet Specifications at 3.0 GeV .....	7-7
7.1.3	Dipole Magnet Conceptual Base Line Design Parameters .....	7-9
7.1.4	Quadrupole Magnet Conceptual Design Parameters .....	7-13
7.1.5	Sextupole Magnet Conceptual Design Parameters .....	7-14
7.1.5	Sextupole Magnet Conceptual Design Parameters .....	7-14
7.2.1	Beam Size at the Center of the ID Straights for 0.5 nm-rad (H) and 0.008 nm-rad (V) Emittance .....	7-29
7.2.2	Magnet Stability Tolerances for AC Closed-Orbit Stability, without Feedback Correction .....	7-32
7.2.3	RMS (4 – 50 Hz) Ground Motion near the NSLS-II Site .....	7-35
7.2.1	Beam Size at the Center of the ID Straights for 0.5 nm-rad (H) and 0.008 nm-rad (V) Emittance .....	7-29
7.3.1	Types and Numbers of Vacuum Chambers, Absorbers, and RF-Shielded Bellows in the SR at Start of Operations .....	7-45
7.3.2	Electron Storage Ring Chamber Materials and Their Critical Properties .....	7-51
7.3.3	Vacuum Pumps and gate Valves for the Storage Ring and Front Ends .....	7-54
7.3.4	Number of Gauges and Residual gas Analyzers in Various Areas of the Storage Ring .....	7-56
7.5.1	RF and Beam Parameters for the NSLS-II Storage Ring .....	7-67
7.5.2	RF Power Requirements for Dipole Losses and Various Example ID Configurations .....	7-68
7.5.3	CESR-B Cavity Parameters .....	7-70
7.5.4	Rating of Refrigeration System Unavailability .....	7-78
7.5.5	Cryogenic System Heat Loads Budget and Refrigeration Sizing .....	7-79
7.5.6	Cryogenic System Liquid Nitrogen Consumption Estimates .....	7-79
7.5.7	Cryogenic System Utility Requirements .....	7-88
7.5.8	ODH Control Measures .....	7-89
7.6.1	Parameters of the Septum Magnets .....	7-94
7.6.2	Parameters of the Injection Kickers .....	7-94
7.6.3	Input Beam Parameters .....	7-96
7.8.1	Beam Diagnostics and Instrumentation for Storage Ring .....	7-103
7.8.2	Complement of the Optical Diagnostics for the NSLS-II Storage Ring .....	7-110
7.8.3	C5860 Streak Camera Parameters .....	7-112
8.1.1	Electron Beam Size and Divergence at NSLS-II .....	8-1
8.1.2	Some Working SCWs Similar in Specifications to Proposed and Alternative NSLS-II Wigglers .....	8-4
8.1.3	Comparison of Bend Magnet Sources .....	8-4
8.3.1	Basic Parameters of NSLS-II Radiation Sources for SR Operation at 3.0 GeV and 500 mA .....	8-5
9.5.1	Diamond Version of the SLS Version of the APS Event System Specification .....	9-19
9.5.2	Fast Timing Hardware Options .....	9-19
9.5.3	Feedback System Comparisons .....	9-21
9.9.1	Typical Data Rates and Total Data Collected in Representative Experiments .....	9-34
10.1.1	NSLS-II Required Global Tolerances .....	10-2
10.1.2	NSLS-II Girder-to-Girder Positioning Tolerances .....	10-2
10.1.3	Magnet-to-Magnet Positioning Tolerances .....	10-8

11.2.1	Possible Distribution of Beamlines at NSLS-II by Beamline Type .....	11-4
11.3.1	NSLS-II Undulator-Based X-Ray Beamline Performance vs. Mirror Figure Error.....	11-15
11.4.1	Practical Parameters for Direct Scanning Mode, Wavelength 1A .....	11-20
11.4.2	Practical Parameters for Waveguide Scanning Mode .....	11-23
11.4.3	Summary of Characteristics of the Four Modes .....	11-27
11.6.1	Parameters for the Small Angle XPCS Branch of the Coherent X-Ray Scattering Beamline .....	11-51
11.6.2	Parameters for the CXD Branch of the Coherent X-Ray Scattering Beamline .....	11-52
11.6.3	Principal Components of the Coherent X-Ray Scattering Beamline at NSLS-II.....	11-56
11.7.1	Machine Parameters Used in the Calculations .....	11-64
11.7.2	ID Parameters Used in the Calculations .....	11-64
11.7.3	Attributes of the Optical Components for the XRMS/RIXS Beamline .....	11-65
11.7.4	Parameters of the Gratings for Beamline 1 .....	11-66
11.8.1	Machine Parameters Used in the Calculations .....	11-92
11.8.2	ID Parameters Used in the Calculations .....	11-92
11.8.3	Distance from the Source, Angle of Incidence, and Deflection of Optical Components for SXCS Beamline .....	11-93
11.8.4	Grating Parameters for Soft X-Ray Imaging and Coherent Scattering Beamline .....	11-94
11.9.1	Dose, Biomolecular Crystal Size, and Useful Lifetime for Different Photon Fluxes .....	11-105
11.9.2	KB System Parameters for an NSLS-II X-Ray Crystallography Beamline .....	11-107
11.9.3	NSLS-II Undulator-Based X-Ray Beamline Performance vs. Mirror Figure Error.....	11-108
11.17.1	Common Crystals in Medium Energy Monochromators.....	11-143
11.19.1	NSLS-II Fill Patterns Compatible with Mode-Locked Ti:Sapphire Laser Oscillators .....	11-153
12.2.1	Resolution Dependence of MLL Optics Parameters .....	12-21
12.3.1	Expected Specifications for the NSLS-II Nanoprobe Scanning Stages .....	12-38
12.3.2	Comparisons of Scanning Stages for STMs, AFMs, and a Hard X-Ray Nanoprobe.....	12-39
12.7.1	Period-Length vs. Maximum Flux Density and Effective K Value for IVU at Room Temperature and 150 K .....	12-63
12.7.2	Mechanical Tolerances.....	12-66
12.7.3	Characteristics of an APPLE-II Type EPU. Assumed Br of the Magnets is 1.35T .....	12-74
12.7.4	APPLE-II Type EPU45 Parameters .....	12-75
12.7.5	HiSOR-Type EPU50 Parameters .....	12-78
12.7.6	U100 Wiggler Parameters .....	12-82
12.7.7	Comparison of Peak $K_y$ and Effective $K_y$ with Varying Pole Width.....	12-82
13.1.1	NSLS-II Gross Area .....	13-2
13.2.1	Site Analysis Scoring Matrix .....	13-7
13.3.1	R-Values for High Fenestration Area Buildings - ECCNY .....	13-19
13.3.2	R-Values for Low Fenestration Area Buildings - ECCNY .....	13-20
13.3.3	Building Office Capacity.....	13-20
13.3.4	Parking Requirements .....	13-21
13.3.5	Acoustic Noise Criteria .....	13-22
13.3.6	Allowed Quantities of Hazardous Gas.....	13-22
13.3.7	Allowed Quantities of Hazardous Chemicals .....	13-23
13.3.8	Live Loads .....	13-26
13.3.9	Building Snow Loads .....	13-26
13.3.10	Building Wind Loads .....	13-26
13.3.11	Building Earthquake Loads.....	13-26
13.3.12	Mechanical Systems .....	13-27
13.3.13	Estimated Cooling Load.....	13-28
13.3.14	Existing Utilities .....	13-28
13.3.15	Process Systems .....	13-30
13.4.1	Summary Program of Spaces .....	13-39
13.4.2	Ring Building Program of Spaces .....	13-40
13.4.3	Central Lab Office Building Program of Spaces.....	13-44
13.4.4	Lab Office Buildings Program of Spaces .....	13-46
13.4.5	Service Buildings Program of Spaces .....	13-49

13.4.6	Linac and RF Buildings Program of Spaces .....	13-49
13.4.7	Building Floor Elevations .....	13-52
13.5.6.1.1	General HVAC .....	13-70
13.5.6.1.2	Accelerator Tunnel HVAC .....	13-71
13.5.6.1.3	Experimental Hall HVAC .....	13-76
13.5.6.1.4	Linac and RF Building HVAC .....	13-76
13.5.6.1.5	General Exhaust – Experimental Hall .....	13-77
13.5.6.1.6	General Exhaust – Lab Office Buildings .....	13-77
13.5.6.1.7	Chilled Water .....	13-78
13.5.6.1.8	Process Cooling Tower Water .....	13-80
13.5.6.1.9	Steam .....	13-80
13.5.6.1.10	Condensate .....	13-81
13.5.6.1.11	Heating Water .....	13-82
13.5.6.2.1	Potable Water .....	13-83
13.5.6.3.1	Nitrogen .....	13-85
13.5.6.3.2	Liquid Nitrogen .....	13-85
13.5.6.3.3	Compressed Air .....	13-86
13.5.6.3.4	Deionized Water .....	13-87
13.5.6.3.5	Deionized Water Make-Up .....	13-87
13.5.6.3.6	Process Cooling Water .....	13-88
13.5.6.4.1	Fire Water .....	13-88
13.5.1	LEED Certification Points .....	13-99
13.5.2	NSLS-II Preliminary LEED Points .....	13-102
13.6.2	Base Bid and Bid Alternate Components .....	13-104
13.7.1	Site/Civil Concept Design Drawing List .....	13-105
13.7.2	Architectural concept Design Drawing List .....	13-106
13.7.3	Mechanical Concept Design Drawing List .....	13-107
13.7.4	Electrical Concept Design Drawing List .....	13-107
14.1.1	Hazards Considered for PHA and Applicable Codes and Standards .....	14-3
15.2.1	Radiation Attenuation Factors of Shielding Materials .....	15-3
15.2.2	Dose Equivalent Factors ( $F_i$ ) Used for Shielding Calculations .....	15-3
15.2.3	Estimated Losses in the Linac System Components .....	15-4
15.2.4	Bulk Shielding Estimates for the Linac Tunnel .....	15-5
15.2.5	Electromagnetic Shower Parameters for Various Materials .....	15-5
15.2.6	Dose Rates at the Exterior of the Concrete Shield Wall around the Linac Beam Stop .....	15-6
15.2.7	Estimated Beam Losses in the Storage Ring – Booster Components .....	15-6
15.2.8	Bulk Shielding Estimates for the Storage Ring and Booster Synchrotron Enclosures .....	15-8
15.2.9	Dose Rates on Contact: Exterior Concrete Shield Walls near the Booster Beam Stop .....	15-9
15.3.1	Primary Bremsstrahlung Dose Rates at the NSLS-II ID Beamline .....	15-12
15.3.2	Shutter/Collimator Thickness for NSLS-II Insertion Device Beamlines .....	15-13
15.3.3	Shielding Estimates for the FOE for Bremsstrahlung Scattering .....	15-17
15.3.4	NSLS-II Insertion Device Parameters for Beamline Shielding Calculations .....	15-18
15.3.5	Preliminary Shielding Estimates for NSLS-II White Beam Stations (SR Only) .....	15-18
15.3.6	Summary Shielding Requirements for NSLS-II First Optics Enclosures .....	15-18
15.5.1	Activation Results for Various Accelerator Components at NSLS-II .....	15-24
15.5.2	Activity in the Soil Created by $^3\text{H}$ and $^{22}\text{Na}$ at Various Beam Loss Locations .....	15-25
15.5.3	Saturation Activity in Air at Various Beam Loss Locations .....	15-25
15.5.4	Saturation Activities of Radionuclides in the Cooling Water at the Storage Ring Septum .....	15-26
15.6.1	Estimates of Skyshine Created at the NSLS-II Linac Beam Stop .....	15-27
15.6.2	Estimates of Skyshine Created at the NSLS-II Booster Beam Stop .....	15-27