### High Performance, Low Cost Hydrogen Generation from Renewable Energy

P. I./Presenter Name: Dr. Katherine Ayers

Organization: Proton Energy Systems

Date: May 11, 2011

Project ID #PD071

### **Overview**

#### **Timeline**

- Project Start: Sept. 2009
- Project End: December 2013
- Percent complete: 25%

### **Budget**

- Total project funding
  - DOE share: \$3,186,826
  - Contractor share: \$849,206
- Funding for FY11
  - DOE share: \$762,610

Table 3.1.4 Source:
DOE Hydrogen, Fuel Cells & Infrastructure Technologies
Program Multi-Year Research, Development, and
Demonstration Plan, Updated April 2009

#### **Partners**

- Entegris, Inc. (Industry)
- Penn State (Academic)
- Oak Ridge (National Lab)

#### **Barriers**

Barriers addressed

G: Capital Cost

H: System Efficiency


J: Renewable Electricity
Generation Integration

Table 3.1.4. Technical Targets: Distributed Water Electrolysis Hydrogen Production <sup>a, b, c</sup>								
Characteristics	Units	2003 Status	2006 Status °	2012 Target	2017 Target			
Hydrogen Cost	\$/gge	5.15	4.80	3.70	<3.00			
Electrolyzer Capital Cost <sup>d</sup>	\$/gge \$/kW	N/A N/A	1.20 665	0.70 400	0.30 125			
Electrolyzer Energy Efficiency f	% (LHV)	N/A	62	69	74			



# Relevance Overall Cost of Hydrogen


- Cell stack largest contributor to system cost
  - Flowfields, separators and MEAs drive stack cost





### Relevance Proton Roadmap

- Detailed Technology Roadmap developed internally
  - High level outline shown below
- Over 15 projects completed or active to date
  - Funded by DOE, NSF, ARPA-E, ONR, DoD, and internal funds





### Relevance Project Objectives

- Improve electrolyzer cell stack manufacturability
  - Consolidation of components
  - Incorporation of alternative materials
  - Improved electrical efficiency
- Reduce cost in electrode fabrication
  - Reduction in precious metal content
  - Alternative catalyst application methods



### **Top Level Approach**

- Task 1.0: Catalyst Optimization
  - Control catalyst loading
  - Improve application
- Task 2.1: Computational Cell Model
  - Develop full model
  - Flex parameters, observe impact on performance
- Task 2.2: Implement New, Lower Cost Cell Design
  - Design and verify parts
  - Production release
- Task 2.3: Prototype Concepts
  - Test material compatibility
  - Fabricate test parts

- Task 2.4: Composite Bipolar Plates
  - Demonstrate functionality
- Task 3.0: Low Cost Manufacturing
  - Laminate concepts
  - Alternate processes
- Task 4.0: Operational Testing and Stack Scale Up
- Task 5.0: Manufacturing Development
- Task 6.0: Manufacturing Qualification
- Task 7.0: H2A Model Cost Analysis
  - Input design parameters
  - Assess impact of changes




Progress on Milestones


Tools		<b>Task Completion Date</b>	
Task Number	Project Milestones	Original Planned	Percent Complete
1	Catalyst Optimization	03/31/10	100%
2.2	Improved Flowfield Implementation	05/30/10	100%
2.1	Electrolyzer Cell Model	01/30/11	100%
2.3	Next Generation Flowfield Prototypes	05/30/10	100%
2.4	Metal-Composite Laminate Plate Fabrication	12/31/10	100%
3.1	Metal-Composite Plate Development	12/30/11	15%
3.2	All-Metal Laminate Plate Development	12/30/11	15%
3.3	Hydrogen Resistant Coating Development	12/30/11	10%
4.1	Sample Operational Tests	12/31/11	15%
4.2	Post Operational Testing Analysis	03/30/12	0%
4.3	Stack Scale Up	09/30/12	0%
5	Bipolar Plate Manufacturing Development	06/30/13	0%
6	Bipolar Plate Manufacturing Qualification	09/30/13	0%
7	H2A Cost Model Analysis	09/30/13	50%
8	Project Management	09/30/13	30%




# **Technical Accomplishments Task 1.0: Catalyst Optimization**

- Demonstrated new alternative application techniques
- Step 1: 55% reduction on anode
- Step 2: >90% reduction on cathode











# **Technical Accomplishments Task 1.0: Catalyst Optimization**


- Qualified non-proprietary test cell for collaborator use
- Enables rapid sample turnover and comparison between sites







## Relevance Task 1.0: Reduction of noble metals







# Technical Accomplishments Subtask 2.1: Computational Model

#### • Modeling goals:

- Current density distribution
- Electrical potential distributions
- Volume fraction of water and gases
- Heat distribution








## Relevance Task 2.1: Performance Prediction


- Cell component architecture can be refined in light of model predictions
- Use conclusions for iterations of next generation designs





# Technical Accomplishments Subtask 2.2: Cell Improvements


- Implemented first design step Oct. 2010
- Over 1200 cells manufactured to date
- 12% stack cost savings demonstrated





## Technical Accomplishments Subtask 2.3: Alternative Materials

- Built on previous work with test wafers
- Full bipolar plates show stable performance
  - >3000 hours demonstrated




Composite Bipolar Plate



Bipolar plate channels, nitrided plate



# Relevance Task 2: Flow Field Design





### **H2A Modeling Calculations – Year 1**

Highlighted items implemented in production


	Cost savings (\$/kg)	
Bipolar assembly	\$	0.24
Membrane	\$	0.30
Initial catalyst		
loading reduction	\$	0.06
Total	\$	0.60




# Technical Accomplishments: Subtask 2.4 Alternative Coatings


- Develop alternate protective coatings
  - Study with Oak Ridge on thermal nitriding and characterization

Nitride layer after 1300 hours operation





Oak Ridge alloy corrosion test







# **Technical Accomplishments Task 3: Alternative Concepts**

 Surveyed alternative manufacturing techniques in addition to Task 2 work

Diffusion bonding




Chemical/Electrochemical Etching





## Relevance Task 3: Alternative Concepts


- Over 30 concepts evaluated
- Ranked based on NRE cost, risk, and part cost
- Selected 2
   additional
   concepts for
   prototyping
- Potential for additional 50% cost savings





## Relevance Tasks 2 and 3: Cell Cost Reductions

Present program work impact on cell cost






#### Collaboration

#### Partners

- Entegris (Industry): Demonstrating alternative materials and coating techniques for reduced cost flowfields
- Penn State (Academic): Developing a full computational model of a functioning electrolyzer cell
- Oak Ridge National Laboratory: (Federal) Investigating advanced coating materials and deposition techniques





#### **Future Work**

- Task 2.3 Continue materials compatibility screening and evaluation of Entegris designs
- Task 2.4 Evaluate ORNL nitride coatings
- Task 3.0 Obtain and test alternate design concepts
- Task 4.0 Prototype testing in stacks and scale up
- Task 5.0 Final downselect and manufacturing process development
- Task 6.0 Manufacturing qualification
- Task 7.0 Perform H2A analysis for end design



### **Manufacturing Development**

- End goal of program to scale up new flow field
- Utilize existing stack design and system capability



0.6 ft<sup>2</sup> cell stack, >10,000 cell hours, ~1 kg/day/cell




65 kg/day system, operating Proton fueling station





### **Future Cell Stack Cost Reduction**


A pathway has been identified to significantly lower cell cost






### Future Cell Stack Efficiency Improvements

#### **Predicted and Measured Cell Potential vs Current Density**





### Resulting Hydrogen Cost Progression



<sup>\*</sup>Assumes volumes of 500 units/year



### **Summary**

- Relevance: Cost savings at the electrolyzer cell level directly impacts hydrogen production costs
- Approach: Reduce cost of largest contributors first
- Technical Accomplishments:
  - Catalyst: Demonstrated reduced catalyst loading (55% anode, 90% cathode reduction) while maintaining desired electrical performance
  - Flowfield: Implemented Phase 1 (25% part cost savings) and demonstrated new prototypes, evaluated new manufacturing methods with >50% savings
- Collaborations:
  - Cell Model: Will allow for optimization/verification of designs
  - Entegris: Concepts show good durability and >50% flow field cost savings
  - ORNL: Providing detailed information on nitrided layers, starting alloy work
- Proposed Future Work:
  - Continue development and verification of unitized flowfield architectures



#### **Team**

- Blake Carter
- Luke Dalton
- Brett Tannone
- Andy Roemer
- Mike Niedzwiecki
- Tom Mancino (Entegris)
- Mike Brady (ORNL)
- Todd Toops (ORNL)

