

Knowledge and Abilities Catalog for Nuclear Power Plant Operators

Boiling Water Reactors

Final Report

U.S. Nuclear Regulatory Commission Office of Nuclear Reactor Regulation Washington, DC 20555-0001



Knowledge and Abilities Catalog for Nuclear Power Plant Operators

Boiling Water Reactors

Final Report

Manuscript Completed: September 2007

Date Published: October 2007

Division of Inspection and Regional Support Office of Nuclear Reactor Regulation U.S. Nuclear Regulatory Commission Washington, DC 20555-0001

AVAILABILITY OF REFERENCE MATERIALS IN NRC PUBLICATIONS

NRC Reference Material

As of November 1999, you may electronically access NUREG-series publications and other NRC records at NRC's Public Electronic Reading Room at http://www.nrc.gov/reading-rm.html.

Publicly released records include, to name a few, NUREG-series publications; Federal Register notices; applicant, licensee, and vendor documents and correspondence; NRC correspondence and internal memoranda; bulletins and information notices; inspection and investigative reports; licensee event reports; and Commission papers and their attachments.

NRC publications in the NUREG series, NRC regulations, and *Title 10, Energy*, in the Code of *Federal Regulations* may also be purchased from one of these two sources.

- The Superintendent of Documents U.S. Government Printing Office Mail Stop SSOP Washington, DC 20402–0001 Internet: bookstore.gpo.gov Telephone: 202-512-1800 Fax: 202-512-2250
- The National Technical Information Service Springfield, VA 22161–0002 www.ntis.gov 1–800–553–6847 or, locally, 703–605–6000

A single copy of each NRC draft report for comment is available free, to the extent of supply, upon written request as follows:

Address: U.S. Nuclear Regulatory Commission

Office of Administration

Mail, Distribution and Messenger Team

Washington, DC 20555-0001,

E-mail: DISTRIBUTION@nrc.gov

Facsimile: 301-415-2289

Some publications in the NUREG series that are posted at NRC's Web site address http://www.nrc.gov/reading-rm/doc-collections/nuregs are updated periodically and may differ from the last printed version. Although references to material found on a Web site bear the date the material was accessed, the material available on the date cited may subsequently be removed from the site.

Non-NRC Reference Material

Documents available from public and special technical libraries include all open literature items, such as books, journal articles, and transactions, *Federal Register* notices, Federal and State legislation, and congressional reports. Such documents as theses, dissertations, foreign reports and translations, and non-NRC conference proceedings may be purchased from their sponsoring organization.

Copies of industry codes and standards used in a substantive manner in the NRC regulatory process are maintained at—

The NRC Technical Library Two White Flint North 11545 Rockville Pike Rockville, MD 20852–2738

These standards are available in the library for reference use by the public. Codes and standards are usually copyrighted and may be purchased from the originating organization or, if they are American National Standards, from—

American National Standards Institute 11 West 42nd Street New York, NY 10036–8002 www.ansi.org 212–642–4900

Legally binding regulatory requirements are stated only in laws; NRC regulations; licenses, including technical specifications; or orders, not in NUREG-series publications. The views expressed in contractor-prepared publications in this series are not necessarily those of the NRC.

The NUREG series comprises (1) technical and administrative reports and books prepared by the staff (NUREG-XXXX) or agency contractors (NUREG/CR-XXXX), (2) proceedings of conferences (NUREG/CP-XXXX), (3) reports resulting from international agreements (NUREG/IA-XXXX), (4) brochures (NUREG/BR-XXXX), and (5) compilations of legal decisions and orders of the Commission and Atomic and Safety Licensing Boards and of Directors' decisions under Section 2.206 of NRC's regulations (NUREG-0750).

Supplement 1 to Revision 2 of NUREG-1123 Record of Changes

Instructions: Remove the existing NUREG-1123, Revision 2, pages and insert replacement pages as noted below (corrections and clarifications have been made as indicated).

	•	1
Section	Remove Page(s)	Replacement Page(s) / Correction Summary
Cover pages	Cover pages	Cover pages / add Supp.1
Abstract	iii and blank	iii and iv / describe Supplement 1 changes in Abstract, add Paperwork Reduction Act page
Table of Contents	v-viii	v-viii / add Supplement 1, page number changes, add new APE (700000) for Generator Voltage and Electric Grid Disturbances to Section 4.2
Summary of	xi-xii	xi-xii / describe the replacement of Section 2
Significant Changes	xv and blank	xv and blank / discuss the study basis to reassess job safety and importance values
Organization of Catalog	1-1 to 1-6	1-1 to 1-6 / amend to conform with Revision 9 of NUREG-1021 and Section 2 changes
	1-9 to 1-12	1-9 to 1-12 / add new APE (700000) Generator Voltage and Electric Grid Disturbances
2.0 Generic Knowledges and Abilities	2-1 to 2-15	2-1 to 2-18 / revise Section 2
4.2 Generic Abnormal Plant Evolutions (APEs)	4.2-1 and blank	4.2-1 and blank / add new APE (700000) for Generator Voltage and Electric Grid Disturbances
Evolutions (Al Es)	4.2-43 and blank	4.2-43 to blank / add new APE 700000 Generator Voltage and Electric Grid Disturbances

ABSTRACT

The Knowledge and Abilities Catalog for Nuclear Power Plant Operators: Boiling Water Reactors (BWRs) (NUREG-1123, Revision 2, Supplement 1) provides the basis for the development of content-valid licensing examinations for reactor operators (ROs) and senior reactor operators (SROs). The examinations developed using the BWR Catalog along with the Operator Licensing Examination Standards for Power Reactors (NUREG-1021, Rev. 9, Supplement 1) will sample the topics listed under Title 10, Code of Federal Regulations, Part 55 (10 CFR 55).

The BWR Catalog contains approximately 7,000 knowledge and ability (K/A) statements for ROs and SROs at BWRs. The catalog is organized into six major sections: Organization of the Catalog, Generic Knowledge and Ability Statements, Plant Systems grouped by Safety Functions, Emergency and Abnormal Plant Evolutions, Components and Theory.

Revision 1 to the BWR Catalog modified the form and content of the original catalog. The K/As were linked to their applicable 10 CFR 55 item numbers. SRO level K/As were identified by 10 CFR 55.43 item numbers. The plant-wide generic and system generic K/As were combined in one section with approximately one hundred new K/As. Component Cooling Water and Instrument Air Systems were added to the Systems Section. Finally, High Containment Hydrogen Concentration and Plant Fire On Site evolutions were added to the Emergency and Abnormal Plant Evolutions section.

Revision 2 incorporated corrections to the Rev. 1 catalog that were identified during a pilot testing program associated with revision of 10 CFR 55 and implementation of NUREG-1021, Interim Rev. 8, "Operator Licensing Examination Standards for Power Reactors." Corrections to the catalog included:

- 1. addition of 7 K/As that had been omitted in Rev. 1.
- 2. correction of typographical errors.
- 3. addition of importance value modifiers that had been omitted in Rev. 1.

Revision 2, Supplement 1, includes the following changes:

- 1. total replacement of Section 2, "Generic Knowledges and Abilities"
- 2. inclusion of one additional Abnormal Plant Evolution (APE), 700000, "Generator Voltage and Electric Grid Disturbances," in Section 4.2 "Generic Abnormal Plant Evolutions"

Corrections and additions are identified by "redline" marking in the margins.

PAPERWORK REDUCTION ACT STATEMENT

This NUREG contains information collection requirements that are subject to the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 et seq.). These information collections were approved by the Office of Management and Budget, approval number 3150-0018.

Public Protection Notification

The NRC may neither conduct nor sponsor, and a person is not required to respond to, a request for information or an information collection requirement unless the requesting document displays a currently valid OMB approval number.

TABLE OF CONTENTS

ABSTRACT	page iii	
SUMMARY OF SIGNIFICANT CHANGES	xi	
1 ORGANIZATION OF THE CATALOG		
1.1 Introduction	1-1	
1.2 Part 55 of Title 10 of the Code of Federal Regulations	1-1	
1.3 RO Written Examination	1-1	
1.4 SRO Written Examination	1-2	
1.5 RO and SRO Operating Test Items	1-3	
1.6 Senior Operators Limited to Fuel Handling	1-4	
1.7 Organization of the BWR Catalog	1-4	
1.8 Generic Knowledge and Abilities	1-5	
1.9 Plant Systems	1-6	
1.10 Emergency And Abnormal Plant Evolutions	1-10	
1.11 Components	1-12	
1.12 Theory	1-13	
1.13 Importance Ratings	1-13	
1.14 Acronyms And Terms	1-14	
2 GENERIC KNOWLEDGES AND ABILITIES (120)		
2.1 Conduct Of Operations	2-1	
2.2 Equipment Control	2-6	
2.3 Radiation Control	2-11	
2.4 Emergency Procedures / Plan	2-13	
3 PLANT SYSTEMS		
3.1 Reactivity Control	3.1-1	
Control Rod Drive Hydraulic System	3.1-3	
Control Rod and Drive Mechanism	3.1-7	
Reactor Manual Control System	3.1-10	
Recirculation Flow Control System	3.1-13	
Recirculation System	3.1-17	
Rod Control and Information System	3.1-22	
Standby Liquid Control System	3.1-25	

ABLI	BLE OF CONTENTS (Continued)	
	3. 2 Reactor Water Inventory Control	3.2-1
	High Pressure Coolant Injection System	3.2-3
	High Pressure Core Spray System	3.2-8
	Low Pressure Core Spray System	3.2-12
	Reactor Condensate System	3.2-16
	Reactor Core Isolation Cooling System	3.2-21
	Reactor Feedwater System	3.2-25
	Reactor Water Cleanup System	3.2-29
	Reactor Water Level Control System	3.2-33
	Residual Heat Removal /Low Pressure Coolant Injection: Injection Mode (Plant Specific)	3.2-38
	3.3 Reactor Pressure Control	3.3-1
	Automatic Depressurization System	3.3-3
	Main and Reheat Steam System	3.3-6
	Reactor/Turbine Pressure Regulating System	3.3-11
	Relief/Safety Valves	3.3-18
	3. 4 Heat Removal From Reactor Core	3.4-1
	High Pressure Coolant Injection System	3.4-3
	High Pressure Core Spray System	3.4-8
	Isolation (Emergency) Condenser	3.4-12
	Low Pressure Core Spray System	3.4-16
	Main and Reheat Steam System	3.4-20
	Main Turbine Generator and Auxiliary Systems	3.4-25
	Reactor Core Isolation Cooling System	3.4-29
	Recirculation System	3.4-33
	Residual Heat Removal /Low Pressure Coolant Injection: Injection Mode Shutdown Cooling System (RHR Shutdown Cooling Mode)	3.4-38 3.4-42
	3.5 Containment Integrity	3.5-1
	Primary Containment System and Auxiliaries	3.5-3
	Primary Containment Isolation System / Nuclear Steam Supply Shut-Off	3.5-8
	Reactor Vessel Internals	3.5-12
	RHR/LPCI: Torus/Suppression Pool Cooling Mode	3.5-15
	RHR/LPCI: Containment Spray System Mode	3.5-19
	RHR/LPCI: Torus/Suppression Pool Spray Mode	3.5-23
	Secondary Containment	3.5-28
	3.6 Electrical	3.6-1
	A.C. Electrical Distribution	3.6-3
	D.C. Electrical Distribution	3.6-6
	Emergency Generators (Diesel/Jet)	3.6-9

TABLE OF CONTENTS (Continued)	
Uninterruptable Power Supply (A.C. /D.C.)	3.6-13
3.7 Instrumentation	3.7-1
Average Power Range Monitor/Local Power Range Monitor System	3.7-3
Intermediate Range Monitor System	3.7-7
Nuclear Boiler Instrumentation	3.7-10
Radiation Monitoring System	3.7-15
Reactor Protection System	3.7-19
Rod Block Monitor System	3.7-24
Rod Control and Information System	3.7-27
Rod Position Information System	3.7-30
Rod Sequence Control System (Plant Specific)	3.7-33
Rod Worth Minimizer System (Plant Specific)	3.7-35
Source Range Monitor System	3.7-38
Traversing In-Core Probe	3.7-41
3.8 Plant Service Systems	3.8-1
Fire Protection System	3.8-3
Fuel Handling	3.8-7
Instrument Air System	3.8-10
Component Cooling Water System	3.8-13
3.9 Radioactivity Release	3.9-1
Main Steam Isolation Valve Leakage Control System	3.9-3
Offgas System	3.9-7
Plant Ventilation Systems	3.9-11
Radiation Monitoring System	3.9-14
Radwaste	3.9-18
Reactor Vessel Internals	3.9-21
Fuel Pool Cooling and Clean-up	3.9-24
Standby Gas Treatment System	3.9-29
Control Room Heating, Ventilation and Air Conditioning	3.9-33
4 EMERGENCY AND ABNORMAL PLANT EVOLUTIONS	
4.1 Generic Emergency Plant Evolutions	4.1-1
High Drywell Pressure	4.1-3
High Reactor Pressure	4.1-5
Suppression Pool High Water Temperature	4.1-7
High Containment Temperature	4.1-8
High Drywell Temperature	4.1-9
High Suppression Pool Water Level	4.1-11

TABLE OF CONTENTS (Continued)	
Low Suppression Pool Water Level	4.1-12
Reactor Low Water Level	4.1-14
High Secondary Containment Area Temperature	4.1-16
High Secondary Containment Area Radiation Levels	4.1-18
Secondary Containment Ventilation High Radiation	4.1-20
Secondary Containment High Differential Pressure	4.1-22
Secondary Containment High Sump / Area Water Level	4.1-23
SCRAM Condition Present and Reactor Power Above APRM Downscale or unknown	4.1-24
High Off-Site Release Rate	4.1-26
High Containment Hydrogen Concentration.	4.1-28
4.2 Generic Abnormal Plant Evolutions	4.2-1
Partial or Complete Loss of Forced Core Flow Circulation	4.2-3
Loss of Main Condenser Vacuum	4.2-5
Partial or Complete Loss of A.C. Power	4.2-7
Partial or Complete Loss of D.C. Power	4.2-9
Main Turbine Generator Trip	4.2-10
SCRAM	4.2-12
High Reactor Pressure	4.2-14
High Reactor Water Level	4.2-16
Low Reactor Water Level	4.2-18
High Drywell Pressure	4.2-19
High Containment Temperature (Mark III Containment Only)	4.2-21
High Drywell Temperature	4.2-22
High Suppression Pool Temperature	4.2-23
Inadvertent Reactivity Addition	4.2-24
Incomplete SCRAM	4.2-26
Control Room Abandonment	4.2-28
High Off-Site Release Rate	4.2-29
Partial or Complete Loss of Component Cooling Water	4.2-31
Partial or Complete Loss of Instrument Air	4.2-33
Inadvertent Containment Isolation	4.2-35
Loss of Shutdown Cooling	4.2-37
Loss of Control Rod Drive Pumps	4.2-39
Refueling Accidents	4.2-40
Plant Fire On Site	4.2-42
Generator Voltage and Electric Grid Disturbances	4.2-44

TABLE OF CONTENTS (Continued)	page
5 COMPONENTS	5-1
Valves	5-3
Sensors and Detectors	5-4
Controllers and positioners	5-6
Pumps	5-7
Motors and Generators	5-9
Heat Exchangers and Condensers	5-10
Demineralizers and Ion Exchangers	5-11
Breakers, Relays and Disconnects	5-12
6 THEORY	6.1-1
DE A CHIOD HAVE ODAY	410
REACTOR THEORY	6.1-3
Neutrons	6.1-3
Neutron Life Cycle	6.1-4
Reactor Kinetics and Neutron Sources	6.1-5
Reactivity Coefficients	6.1-6
Control rods	6.1-7
Fission Product Poisons	6.1-8
Fuel Depletion and Burnable Poisons	6.1-10
Reactor Operational Physics	6.1-11
THERMODYNAMICS	6.2-1
Thermodynamic Units and Properties	6.2-1
Basic Energy Concepts	6.2-2
Steam	6.2-3
Thermodynamic Processes	6.2-4
Thermodynamic Cycles	6.2-5
Fluid Statics	6.2-6
Heat Transfer and Heat Exchanges	6.2-8
Thermal Hydraulics	6.2-9
Core Thermal Limits	6.2-12
Brittle Fracture and Vessel Thermal Stress	6.2-15

This page left blank

SUMMARY OF SIGNIFICANT CHANGES

The changes described in paragraphs 1 through 6, below, were incorporated in Revision 1 of the catalog in August, 1995. Paragraph 7 describes changes that are incorporated with Revision 2 of the catalog. Paragraph 8 describes Supplement 1 to Revision 2, which includes a replacement of Section 2, "Generic Knowledges and Abilities," and a new abnormal plant evolution (APE).

1 ORGANIZATION OF THE BWR CATALOG

1.1 The 10 CFR 55 items listed.

The content of the written examinations and operating licensing tests is dictated by Sections 55.41, 55.43, and 55.45 of Title 10 of the Code of Federal Regulations (10 CFR). The thirty four (34) items listed in 10 CFR 55 are listed in the catalog to reduce the need for cross referencing.

1.2 Knowledge and Abilities linked to 10 CFR 55

The linkage of K/As to the 10 CFR 55.41, 43 and 45 requirements was done to help ensure that the examinations include a representative sample from among the applicable items. Throughout the catalog, 10 CFR 55 section references are shown in parentheses following the appropriate K/A statement, such as (CFR: 41.x / 43.x / 45.x).

1.3 Senior Reactor Operator (SRO) K/As identified

NUREG-1021, Rev. 8, "Operator Licensing Examination Standards for Power Reactors," Section ES-401, required at least 25% of the site-specific written examination for SROs to evaluate K/As required for the higher license level. The original catalogs did not explicitly identify the K/As that represented the higher license level. Differences in RO and SRO importance ratings were sometimes used, but, the rating differences were not linked to the 10 CFR 55.43 SRO items. In this catalog revision, SRO license level K/As were linked to the items associated with the 10 CFR 55.43 SRO items. This is intended to remove subjectivity from selection of higher license level K/As.

1.4 Senior Reactor Operator Limited to Fuel Handling (LSRO) examination specifications added.

NUREG-1021, Rev. 8, Section 701 referred to the K/A catalog. In an effort to assure consistency between the Examination Standards and the catalog, a brief discussion of the use of the catalog for LSRO examinations was included.

1.5 An updated catalog organization was implemented.

1. ORGANIZATION OF BWR CATALOG

- 1. Added 10 CFR information
- 2 Generic Knowledge and Abilities
 - 1. Combined old plant-wide and system generic K/As in one section.
 - 2. Eliminated duplicate generic K/As.
 - 3. Organized the section into 4 topic areas.
 - 4. Added about 100 new generic K/As.
- 3 Plant Systems
 - 1. Moved System Generic K/As to new generic section
 - 2. Added Instrument Air System
 - 3. Added Component Cooling Water System
- 4 Emergency & Abnormal Plant Evolution Section
 - 1. Moved Generic K/As to Section 2
 - 2. Added High Containment Hydrogen Concentration
 - 3. Added Plant Fire On Site
- 5 Components

No change

6 Theory Section

No change

2 GENERIC KNOWLEDGE AND ABILITIES (132)

2.1 The System Generic K/As were combined with the Plant-Wide Generic K/As.

Many of the old system generic K/As had plant-wide applicability as well as local applicability. In addition, the old plant-wide generic section had relatively few K/As to draw upon to make up 13% of the RO examination or 17% of the SRO examination, per NUREG-1021. As a result, all generic K/As were merged into one section.

OLD SYSTEM GENERIC K/A	NEW K/A
1	2.1.2
2	2.1.14
3	2.4.30
4	2.1.27
5	2.2.22
6	2.2.25
7	2.1.28
8	2.4.31
9	2.1.30
10	2.1.32
11	2.1.33
12	2.4.50
13	2.1.23
14	2.4.49
15	2.4.4

These are generally administrative knowledge and abilities with broad application across systems and operations. The four (4) topic areas listed below.

- 2.1 Conduct of Operations K/As
- 2.2 Equipment Control K/As
- 2.3 Radiation Control K/As
- 2.4 Emergency Procedures /Plan K/As

The generic K/As for "Conduct of Operations," are used to evaluate the applicant's knowledge of the daily operation of the facility. The types of information covered under this category may include for example, shift turnover or temporary modification procedures.

- The generic K/As for "Equipment Control" are used to evaluate the administrative issues associated with the management and control of plant systems and equipment. Examples of the types of information evaluated under this topic include maintenance and temporary modifications of systems. Fuel handling and refueling K/As were also organized into this topic area because of the equipment control aspect of fuel handling.
- The generic K/As for "Radiation Control," are used to evaluate the applicant's knowledge and abilities with respect to radiation hazards and protection (personnel and public). Examples of the types of information that should be evaluated under this topic are knowledge of significant radiation hazards or radiation work permits.
- The generic K/As for "Emergency Procedures / Plan" are used to evaluate the applicant's general knowledge of emergency operations. The K/As are designed to evaluate knowledge of the emergency procedures use. The emergency plan K/As may be used to evaluate the applicant's knowledge of the plan, including, as appropriate, the RO's or SRO's responsibility to decide whether it should be executed and the duties assigned under the plan.
 - 2.2 Approximately one hundred (100) new generic K/As were added to the catalog.

The new K/As were identified through license examiner surveys and an independent review of the catalog, NUREG-1021, licensee event reports and inspection reports. All new K/As were directly linked to the applicable 10 CFR 55 requirements.

- 3 PLANT SYSTEMS (56) WITHIN 9 SAFETY FUNCTIONS
- 3.1 The old system generic K/As were combined with plant wide generic K/As in Section 2, Generic K/As.
- 3.2 Two systems were added because they were covered in the Abnormal Evolutions.
 - 1. Instrument Air System
 - 2. Component Cooling Water System
- 3.3 K/A stem statement K5, changed "operational applications" to "operational implications"
- 4 EMERGENCY & ABNORMAL PLANT EVOLUTIONS (40)
- 4.1 The original system generic K/As were combined with plant wide generic K/As in Section 2, Generic K/As. Duplicate generic K/As were combined into single K/As where applicable.
- **4.2.** High Containment Hydrogen Concentration was added to reflect Revision 4 changes to BWROG Emergency Procedures Guidelines (EPGs).
- 4.3 Plant Fire On Site was added as an abnormal plant evolution to achieve consistency with the Fire Protection System section.

4.4 Emergency and Abnormal Evolution K/As were linked to 10 CFR 55 item numbers at the stem statement level.

5 COMPONENTS

- 5.1 All component K/As were linked to 10 CFR 55 item numbers.
- 6 THEORY
- 6.1 Reactor Theory and Thermodynamics theory K/As were linked to 10 CFR, 55 item numbers.

7 REVISION 2 CHANGES

- 7.1 Approximately 7 K/As that had been omitted in Rev. 1 were added.
- 7.2 Typographical errors were corrected.
- 7.3 Importance value modifiers that had been omitted in Rev. 1 were added. Corrections and additions are identified by "redline" marking in the margins.

8 CHANGES IN SUPPLEMENT 1 TO REVISION 2

- **8.1** Regarding replacement of Section 2, the Pressurized Water Reactor Owners Group, with the endorsement of the U.S. Nuclear Regulatory Commission (NRC), first initiated a study to reassess the job relevance and importance-to-safety ratings of 129 K/As in Section 2 of NUREG-1122. The study was subsequently expanded to include the Boiling Water Reactor Owners Group to reassess its counterpart Section 2 of NUREG-1123.
- **8.2** Regarding the additional APE 700000, "Generator Voltage and Electric Grid Disturbances," the NRC requested that additional K/As related to degraded voltage be incorporated and validated during the study's second phase to address lessons learned from a major blackout in August 2003.

1 ORGANIZATION OF THE CATALOG

1.1 INTRODUCTION

The Knowledge and Abilities Catalog for Nuclear Power Plant Operators: Boiling Water Reactors (BWR) NUREG-1123, Revision 2, Supplement 1 provides the basis for development of content-valid written and operating licensing examinations for reactor operators (ROs) and senior reactor operators (SROs). The Catalog is designed to ensure equitable and consistent examinations.

1.2 PART 55 OF TITLE 10 OF THE CODE OF FEDERAL REGULATIONS

The catalog is used in conjunction with NUREG-1021, Revision 9, Supplement 1, "Operator Licensing Examination Standards for Power Reactors." NUREG-1021 provides policy and guidance and establishes the procedures and practices for examining licensees and applicants for RO and SRO licenses pursuant to Part 55 of Title 10 of the <u>Code of Federal Regulations</u> (10 CFR 55). All knowledge and abilities (K/As) in this catalog are directly linked by item number to 10 CFR 55.

1.3 RO WRITTEN EXAMINATION

The items for RO written examinations are specified in 10 CFR 55.41(b). The RO written examination questions should be generated from a representative sample of K/As derived from among the 10 CFR 55.41(b) items listed below:

- (1) Fundamentals of reactor theory, including fission process, neutron multiplication, source effects, control rod effects, criticality indications, reactivity coefficients, and poison effects.
- (2) General design features of the core, including core structure, fuel elements, control rods, core instrumentation, and coolant flow.
- (3) Mechanical components and design features of reactor primary system.
- (4) Secondary coolant and auxiliary systems that affect the facility.

- (5) Facility operating characteristics during steady state and transient conditions, including coolant chemistry, causes and effects of temperature, pressure and reactivity changes, effects of load changes, and operating limitations and reasons for these operating characteristics.
- (6) Design, components, and function of reactivity control mechanisms and instrumentation.
- (7) Design, components, and function of control and safety systems, including instrumentation, signals, interlocks, failure modes, and automatic and manual features.
- (8) Components, capacity, and functions of emergency systems.
- (9) Shielding, isolation, and containment design features, including access limitations.
- (10) Administrative, normal, abnormal, and emergency operating procedures for the facility.
- (11) Purpose and operation of radiation monitoring systems, including alarms and survey equipment.
- (12) Radiological safety principles and procedures.
- (13) Procedures and equipment available for handling and disposal of radioactive materials and effluents.
- (14) Principals of heat transfer, thermodynamics and fluid mechanics.

The RO written examination is administered in two sections, a generic fundamentals examination (GFE) section and a site-specific examination. The GFE covers those knowledge items that do not vary significantly among reactors of the same type (refer to NUREG-1021, ES-205). The GFE covers components, reactor theory, and thermodynamics knowledge. The component knowledge items are derived from 10 CFR 55.41(b) items 3 and 7. Reactor theory knowledge items are derived from 10 CFR 55.41(b)1. Thermodynamic knowledge items are derived from 10 CFR 55.41(b)14.

The site-specific RO written examination covers K/As that vary among reactors of the same type. The guidance for preparation of RO written examination is presented in NUREG-1021, ES-401. The RO examination includes a balanced mix of generic K/As, plant systems K/As, and emergency/abnormal evolution K/As. The K/As associated with the RO site-specific written examinations are derived from 10 CFR 55.41(b) items 2 through 13.

1.4 SRO WRITTEN EXAMINATION

The items for SRO written examinations are presented in 10 CFR 55.43(b). The guidance for

preparation of the SRO written examination is presented in NUREG-1021, ES-401. The examination for SROs includes 25 questions based on the higher license level K/As from the 7 items listed under 10 CFR 55.43(b), and 75 questions derived from the 10 CFR 55.41(b) RO K/As. The 7 SRO items listed under 10 CFR 55.43(b) include:

- (1) Conditions and limitations in the facility license.
- (2) Facility operating limitations in the technical specifications and their bases.
- (3) Facility licensee procedures required to obtain authority for design and operating changes in the facility.
- (4) Radiation hazards that may arise during normal and abnormal situations, including maintenance activities and various contamination conditions.
- (5) Assessment of facility conditions and selection of appropriate procedures during normal, abnormal, and emergency situations.
- (6) Procedures and limitations involved in initial core loading, alterations in core configuration, control rod programming, and determination of various internal and external effects on core reactivity.
- (7) Fuel handling facilities and procedures.

1.5 RO AND SRO OPERATING TEST ITEMS

The items for operating tests for ROs and SROs are presented in 10 CFR 55.45(a). The guidance for preparation of the operating tests is presented in NUREG-1021, ES-301. The operating test should include a representative selection of K/As derived from 13 items listed in 10 CFR 55.45(a). The 13 items listed in 10 CFR 55.45(a) are:

- (1) Perform pre-startup procedures for the facility, including operating of those controls associated with plant equipment that could affect reactivity.
- (2) Manipulate the console controls as required to operate the facility between shutdown and designated power levels.
- (3) Identify annunciators and condition-indicating signals and perform appropriate remedial actions where appropriate.
- (4) Identify the instrumentation systems and the significance of facility instrument readings.
- (5) Observe and safely control the operating behavior characteristics of the facility.

- (6) Perform control manipulations required to obtain desired operating results during normal, abnormal, and emergency situations.
- (7) Safely operate the facility's heat removal systems, including primary coolant, emergency coolant, and decay heat removal systems, and identify the relations of proper operation of these systems to the operation of the facility.
- (8) Safety operate the facility's auxiliary and emergency systems, including operation of those controls associated with plant equipment that could affect reactivity or the release of radioactive materials to the environment
- (9) Demonstrate or describe the use and function of the facility's radiation monitoring systems, including fixed radiation monitors and alarms, portable survey instruments, and personnel monitoring equipment.
- (10) Demonstrate a knowledge of significant radiation hazards, including permissible levels in excess of those authorized, and ability to perform other procedures to reduce excessive levels of radiation and to guard against personnel exposure.
- (11) Demonstrate knowledge of the emergency plan for the facility, including, as appropriate, the operator's or senior operator's responsibility to decide when the plan should be executed and the duties under the plan assigned.
- (12) Demonstrate the knowledge and ability as appropriate to the assigned position to assume the responsibilities associated with the safe operation of the facility.
- (13) Demonstrate the applicant's ability to function within the control room team as appropriate to the assigned position, in such a way that the facility licensee's procedures are adhered to and that the limitations in its license and amendments are not violated.

1.6 SENIOR OPERATORS LIMITED TO FUEL HANDLING

The specifications for examinations for Senior Operators Limited to Fuel Handling (LSRO) are provided in Examination Standard, NUREG 1021, Section ES-701. The LSRO examination process includes both a written examination and an operating test. This examination and test include, but are not limited to, items associated with 10 CFR 55.43(b) items 5 through 7, and 10 CFR 55.45(a) items 5 and 6.

1.7 ORGANIZATION OF THE BWR CATALOG

The Knowledge and Abilities Catalog for Nuclear Power Plant Operators: Boiling Water Reactors is organized into 6 major sections. Knowledge and ability statements (K/As) are grouped according to the major section to which they pertain. This organization is shown schematically below.

1 ORGANIZATION OF THE BWR CATALOG

2 GENERIC KNOWLEDGE AND ABILITIES (120)

Conduct of Operations K/As Equipment Control K/As Radiation Control K/As Emergency Procedures / Plan K/As

3 PLANT SYSTEMS (56) WITHIN 9 SAFETY FUNCTIONS

Knowledge Categories (K1 - K6) Ability Categories (A1 - A4)

4 EMERGENCY & ABNORMAL PLANT EVOLUTIONS (41)

Knowledge Categories (E/A K1 - E/A K3) Ability Categories (E/A A1 - E/A - A2)

5 COMPONENTS

Component Knowledge Categories (8)

6 THEORY

Reactor Theory Knowledge Categories (8) Thermodynamics Knowledge Categories (10)

1.8 GENERIC KNOWLEDGE AND ABILITIES

Generic knowledge and abilities are generally administrative knowledges and abilities with broad application across systems and operations. They are listed in Section 2 of the catalog. The four (4) categories of generic K/As are listed below:

- 1 Conduct of Operations K/As
- 2 Equipment Control K/As
- 3 Radiation Control K/As
- 4 Emergency Procedures /Plan K/As

The generic K/As for "Conduct of Operations," are used to evaluate the applicant's knowledge of the daily operation of the facility. The types of information covered under this category may include for example, shift turnover, operator responsibilities, and procedure usage.

The generic K/As for "Equipment Control" are used to evaluate the administrative requirements associated with the management and control of plant systems and equipment. Examples of the types of information evaluated under this topic include maintenance and temporary modifications of systems.

The generic K/As for "Radiation Control" are used to evaluate the applicant's knowledge and abilities with respect to radiation hazards and protection (personnel and public). Examples of

the types of information that should be evaluated under this topic are knowledge of significant radiation hazards or radiation work permits.

The generic K/As for "Emergency Procedures / Plan" are used to evaluate the applicant's general knowledge of emergency operations. The K/As are designed to evaluate knowledge of the emergency procedures use. The emergency plan K/As may be used to evaluate the applicant's knowledge of the plan, including, as appropriate, the RO's or SRO's responsibility to decide whether it should be executed and the duties assigned under the plan.

1.9 PLANT SYSTEMS

1.9.1 Plant System Organization by Safety Function

Nine (9) major safety functions must be maintained to ensure safe BWR nuclear power plant operation. The safety functions groups are:

- 1. Reactivity Control
- 2. Reactor Water Inventory Control
- 3. Reactor Pressure Control
- 4. Heat Removal From the Core
- 5. Containment Integrity
- 6. Electrical
- 7. Instrumentation
- 8. Plant Service Systems
- 9. Radioactivity Release.

Fifty six (56) plant systems have been included in the BWR Catalog based on their relationship and importance to safety functions. Table 1 contains a list of these plant systems, arranged within safety function. It should be noted that some plant systems contribute to more than one safety function.

Each plant system has a 6-digit code number. The words "Plant Specific" following the system title, indicates that the knowledge or ability does not apply to all plants.

See Section 3 of the BWR catalog for the delineation of K/As for the plant systems.

Table 1 Plant Systems by Safety Functions

Safety Function 1: Reactivity Control

201001	Control Rod Drive Hydraulic System
201003	Control Rod and Drive Mechanism
201002	Reactor Manual Control System

202002	Recirculation flow Control System
202001	Recirculation System
201005	Rod Control and Information System
211000	Standby Liquid Control System

Safety Function 2: Reactor Water Inventory Control

206000	High Pressure Coolant Injection System
209002	High Pressure Core Spray System
209001	Low Pressure Core Spray System
256000	Reactor Condensate System
217000	Reactor Core Isolation Cooling System
259001	Reactor Feedwater System
204000	Reactor Water Cleanup System
259002	Reactor Water Level Control System
203000	Residual Heat Removal /Low Pressure Coolant Injection: Injection Mode
	(Plant Specific)

Safety Function 3: Reactor Pressure Control

218000	Automatic Depressurization System
239001	Main and Reheat Steam System
241000	Reactor/Turbine Pressure Regulating System
239002	Safety Relief Valves

Safety Function 4: Heat Removal From Reactor Core

206000	High Pressure Coolant Injection System
209002	High Pressure Core Spray System
207000	Isolation (Emergency) Condenser
209001	Low Pressure Core Spray System
239001	Main and Reheat Steam System
245000	Main Turbine Generator and Auxiliary Systems
217000	Reactor Core Isolation Cooling System
202001	Recirculation System
203000	Residual Heat Removal /Low Pressure Coolant Injection: Injection Mode
205000	Shutdown Cooling System (RHR Shutdown Cooling Mode)

Safety Function 5: Containment Integrity

223001	Primary Containment System and Auxinaries
223002	Primary Containment Isolation System / Nuclear Steam Supply Shut-Off
290002	Reactor Vessel Internals
219000	RHR/LPCI: Torus/Suppression Pool Cooling Mode
226001	RHR/LPCI: Containment Spray System Mode

230000	RHR/LPCI:	Torus/Suppression	Pool Spray Mode
--------	-----------	-------------------	-----------------

290001 Secondary Containment

Safety Function 6: Electrical

262001	A.C. Electrical Distribution
263000	D.C. Electrical Distribution
264000	Emergency Generators (Diesel/Jet)
262002	Uninterruptable Power Supply (A.C. /D.C.)

Safety Function 7: Instrumentation

215005	Average Power Range Monitor/Local Power Range Monitor
215003	Intermediate Range Monitor System
216000	Nuclear Boiler Instrumentation
272000	Radiation Monitoring System
212000	Reactor Protection System
215002	Rod Block Monitor System
201005	Rod Control and Information System
214000	Rod Position Information System
201004	Rod Sequence Control System (Plant Specific)
201006	Rod Worth Minimizer System (Plant Specific)
215004	Source Range Monitor System
215001	Traversing In-Core Probe

Safety Function 8: Plant Service Systems

286000	Fire Protection System
234000	Fuel Handling
300000	Instrument Air System
400000	Component Cooling Water System

Safety Function 9: Radioactivity Release

239003	Main Steam Isolation Valve Leakage Control System
271000	Offgas System
288000	Plant Ventilation Systems
272000	Radiation Monitoring System
268000	Radwaste
290002	Reactor Vessel Internals
233000	Fuel Pool Cooling and Clean-up
261000	Standby Gas Treatment System
290003	Control Room Heating, Ventilation and Air Conditioning

1.9.2 Knowledge and Ability Stem Statements for Plant Systems

The information delineated within each plant system is organized into 6 different types of knowledge and 4 different types of ability. If there are no knowledge or ability statements following a stem statement there is no applicable K/A.

The applicable 10 CFR 55.41 / 43 / and 45 item numbers are included with each stem statement. In most cases the K/As associated with the stem statements can be used for both the written examination and the operating test. See Table 2 below:

Table 2 Knowledge and Ability Stem Statements for Plant Systems

- K1. Knowledge of the physical connections and/or cause-effect relationships between (SYSTEM) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)
- K2. Knowledge of electrical power supplies to the following: (CFR: 41.7)
- K3. Knowledge of the effect that a loss or malfunction of the (SYSTEM) will have on the following: (CFR: 41.7 / 45.4)
- K4. Knowledge of (SYSTEM) design feature(s) and or interlock(s) which provide for the following: (CFR: 41.7)
- K5. Knowledge of the operational implications of the following concepts as they apply to the (SYSTEM): (CFR: 41.5 / 45.3)
- K6 Knowledge of the effect that a loss or malfunction of the following will have on the (SYSTEM): (CFR: 41.7 / 45.7)
- A1. Ability to predict and/or monitor changes in parameters associated with operating the (SYSTEM) controls including: (CFR: 41.5 / 45.5)
- A2. Ability to (a) predict the impacts of the following on the (SYSTEM) and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal operation: (CFR: 41.5 / 45.6)

- A3. Ability to monitor automatic operations of the (SYSTEM) including: (CFR: 41.7 / 45.7)
- A4. Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)

1.10 EMERGENCY & ABNORMAL PLANT EVOLUTIONS

Section 4 of the BWR catalog contains emergency plant evolutions (EPEs) and abnormal plant evolutions (APEs). An emergency plant evolution is any condition, event or symptom which leads to entry into the plant-specific emergency operating procedures (EOPs). An abnormal plant evolution is any degraded condition, event or symptom not directly leading to an EOP entry condition, but, nonetheless, adversely affecting a safety function. The listing of EPEs and APEs was developed to include those integrative situations crossing several plant systems and/or safety functions.

The emergency plant evolution strategies described in Revision 4 to the Boiling Water Reactor Owners Group Emergency Procedures Guidelines, cover five broad areas:

- 1) Reactor Pressure Vessel Control
- 2) Reactor Pressure Vessel Control With SCRAM Condition Present and Reactor Power Above APRM Downscale or Unknown.
- 3) Primary Containment Control
- 4) Secondary Containment Control
- 5) Radioactivity Release Control.

If the operator controls the five broad areas of emergency plant evolutions listed above, the plant safety functions will be safely maintained. Table 3, below, contains a numerical list of the 16 emergency plant evolutions and the 25 abnormal plant evolutions covered by this catalog.

Table 3 Emergency and Abnormal Plant Evolutions

EPEs

295024	High Drywell Pressure
295025	High Reactor Pressure
295026	Suppression Pool High Water Temperature
295027	High Containment Temperature (Mark III Containment Only)
295028	High Drywell Temperature
295029	High Suppression Pool Water Level
295030	Low Suppression Pool Water Level
295031	Reactor Low Water Level
295032	High Secondary Containment Area Temperature

295033	High Secondary Containment Area Radiation Levels
295034	Secondary Containment Ventilation High Radiation
295035	Secondary Containment High Differential Pressure
295036	Secondary Containment High Sump / Area Water Level
295037	SCRAM Condition Present and Reactor Power Above APRM Downscale
	or unknown
295038	High Off-Site Release Rate
500000	High Containment Hydrogen Concentration.

APEs

295001	Partial or Complete Loss of Forced Core Flow Circulation
295002	Loss of Main Condenser Vacuum
295003	Partial or Complete Loss of A.C. Power
295004	Partial or Complete Loss of D.C. Power
295005	Main Turbine Trip
295006	SCRAM
295007	High Reactor Pressure
295008	High Reactor Water Level
295009	Low Reactor Water Level
295010	High Drywell Pressure
295011	High Containment Temperature (Mark III Containment Only)
295012	High Drywell Temperature
295013	High Suppression Pool Water Temperature
295014	Inadvertent Reactivity Addition
295015	Incomplete SCRAM
295016	Control Room Abandonment
295017	High Off-Site Release Rate
295018	Partial or Complete Loss of Component Cooling Water
295019	Partial or Complete Loss of Instrument Air
295020	Inadvertent Containment Isolation
295021	Loss of Shutdown Cooling
295022	Loss of Control Rod Drive Pumps
295023	Refueling Accidents
600000	Plant Fire On Site
700000	Generator Voltage and Electric Grid Disturbances

1.10.1 Knowledge and Ability Stem Statements for Emergency and Abnormal Plant Evolutions

The information delineated within each emergency or abnormal evolution is organized into three (3)different types of knowledge and two (2) different types of ability. If there are no knowledge or ability statements following a stem statement there is no applicable K/A.

The applicable 10 CFR 55.41, 43, and 45 item numbers are included with each stem statement. In most cases the K/As associated with the stem statements can be used for both

the written and operating examinations. See Table 4, below:

Table 4 Knowledge and Ability Stem Statements for Emergency and Abnormal Plant Evolutions

E/AK1 Knowledge of the operational applications of the following concepts as they apply to the (EMERGENCY OR ABNORMAL PLANT EVOLUTION):

(CFR: 41.8 to 41.10)

E/AK2 Knowledge of the interrelations between (EMERGENCY OR ABNORMAL

PLANT EVOLUTION) and the following:

(CFR: 41.7 / 45.8)

E/AK3 Knowledge of the reasons for the following responses as they apply to

(EMERGENCY OR ABNORMAL PLANT EVOLUTION):

(CFR: 41.5 / 45.6)

E/AA1 Ability to operate and / or monitor the following as they apply to (EMERGENCY

AND ABNORMAL PLANT EVOLUTION):

(CFR: 41.7 / 45.6)

E/AA2 Ability to determine and interpret the following as they apply to

(EMERGENCY AND ABNORMAL PLANT EVOLUTION):

(CFR: 41.10 / 43.5 / 45.13)

1.11 COMPONENTS

Basic components such as valves and pumps are found in many systems. NUREG-1021, section ES-205, "General Fundamentals Examination," lists 8 categories of components. The following eight (8) categories of components, for which additional knowledge statements are necessary are listed below and delineated in Section 5 of the BWR catalog.

The component knowledge statements are more detailed than those provided in the system listing, yet at the same time they are generic to the component types. Each component has a unique six (6) digit code number and 10 CFR 55.41 (b) item number. See Table 5, below.

Table 5 Components

291001	Valves (CFR: 41.3)
291002	Sensors and Detectors (CFR: 41.7)
291003	Controllers and positioners (CFR: 41.7)
291004	Pumps(CFR: 41.3)

291005	Motors and Generators (CFR: 41.7)
291006	Heat Exchangers and Condensers (CFR: 41.4)
291007	Demineralizers and Ion Exchangers (CFR: 41.3)
291008	Breakers, Relays and Disconnects (CFR: 41.7)

1.12 THEORY

NUREG-1021, Section ES-205, "General Fundamentals Examination," lists theory items. General fundamental knowledge which underlies safe performance on the job is delineated in Section 6 of the BWR Catalog. These theory topics represent general fundamental concepts related to plant operation. Each theory topic has a unique six (6) digit code number. The applicable 10 CFR 41(b) item number is provided for Reactor Theory and Thermodynamics Theory.

Reactor Theory (CFR: 41.1)

292001	Neutrons
292002	Neutron Life Cycle
292003	Reactor Kinetics and Neutron Sources
292004	Reactivity Coefficients
292005	Control rods
292006	Fission Product Poisons
292007	Fuel Depletion and Burnable Poisons
292008	Reactor Operational Physics

Thermodynamics Theory (CFR: 41.14)

293001	Thermodynamic Units and Properties
293002	Basic Energy Concepts
293003	Steam
293004	Thermodynamic Process
293005	Thermodynamic Cycles
293006	Fluid Statics
293007	Heat Transfer and Heat Exchangers
293008	Thermal Hydraulics
293009	Core Thermal Limits
293010	Brittle Fracture and Vessel Thermal Stress

1.13 IMPORTANCE RATINGS

Importance, in this context, considers direct and indirect impact of the K/A on safe plant operation in a manner ensuring personnel and public health and safety. Importance Ratings of the K/As are given for Reactor Operators and Senior Reactor Operators next to each knowledge and ability in the catalog. These ratings reflect average ratings of individual NRC and utility panel members. The rating scale is presented in Table 6, below.

Table 6 RO and SRO Importance Ratings

Rating	Importance for safe operation
5	Essential
4	Very important
3	Fairly important
2	Of limited importance
1	Insignificant Importance
*	Indicates variability in the responses

Therefore, the rating of 2.0 or below represents a statement of limited or insignificant importance for the safe operation of a plant. Such statements are generally considered as inappropriate content for NRC licensing examinations. (See below for qualifications of importance ratings related to variability of the ratings and plant specific data.)

1.13.1 Asterisk and Question Ratings

Some importance ratings are followed by an asterisk (*) or question mark (?). These marks indicate variability in the rating responses. An asterisk indicates that the rating spread was very broad. An asterisk can also signify that more than 15 percent of the raters indicated that the knowledge or ability is not required for the RO/SRO position at their plant, either because it refers to an inapplicable design feature or because it is the responsibility of someone else (e.g. SRO vs. RO). A question mark indicates that more than 15 percent of the raters felt that they were not familiar with the knowledge or ability as related to the particular system or design feature. These marks indicate a need for examination developers to review plant-specific materials to determine whether or not that knowledge or ability is indeed appropriate for inclusion in any given examination.

1.13.2 Difference Ratings

A dagger (†) to the left of an individual knowledge or ability statement indicates that more than 20 percent of the raters indicated that the <u>level</u> of knowledge or ability required by an SRO is different than the <u>level</u> of knowledge or ability required by an RO.

1.14 ACRONYMS AND TERMS

ADS automatic depressurization system

APE abnormal plant evolution AFW auxiliary feedwater system APRM average power range monitor

ARI alternate rod insertion system
ARM area radiation monitoring system

ACRONYMS AND TERMS (continued)

ATWS anticipated transient without scram code of federal regulations CFR

CRD control rod drive D/G diesel generator

ECCS emergency core cooling system emergency plant evolution EPE **HPCS** high pressure core spray

HVAC heating, ventilation and air conditioning

IAS instrument air system IRM intermediate range monitor K/A knowledge and ability

limiting condition for operation LCO low pressure coolant injection LPCI

LPCS low pressure core spray

LSRO senior reactor operator limited to fuel handling

MFW main feedwater M/G motor generator

MSIV main steam isolation valve **RCIC** reactor coolant isolation system

RCS reactor coolant system RHR residual heat removal RO reactor operator

RPS reactor protection system reactor pressure vessel **RPV** SRO senior reactor operator

SRV safety relief valve

2.0 GENERIC KNOWLEDGES AND ABILITIES

- 2.0.1 Technical Requirements Manual (TRM) For the purpose of this catalog, K/As that reference Technical Specifications (TS) may include the Technical Requirements Manual, where applicable.
- 2.0.2 K/A Clarifying Examples K/As that include the words "such as" list suggested topical areas as examples and are not intended to be all inclusive.
- 2.1 Conduct of Operations
- 2.1.1 Knowledge of conduct of operations requirements.

(CFR: 41.10 / 45.13)

IMPORTANCE

RO 3.8

SRO 4.2

2.1.2 Knowledge of operator responsibilities during all modes of plant operation.

(CFR: 41.10 / 45.13)

IMPORTANCE R

RO 4.1

SRO 4.4

2.1.3 Knowledge of shift or short-term relief turnover practices.

(CFR: 41.10 / 45.13)

IMPORTANCE

RO 3.7

SRO 3.9

2.1.4 Knowledge of individual licensed operator responsibilities related to shift staffing, such as medical requirements, "no-solo" operation, maintenance of active license status, 10CFR55, etc.

(CFR: 41.10 / 43.2)

IMPORTANCE

RO 3.3

SRO 3.8

2.1.5 Ability to use procedures related to shift staffing, such as minimum crew complement, overtime limitations, etc.

(CFR: 41.10 / 43.5 / 45.12)

IMPORTANCE

RO 2.9*

SRO 3.9

2.1.6 Ability to manage the control room crew during plant transients.

(CFR: 41.10 / 43.5 / 45.12 / 45.13)

IMPORTANCE

RO 3.8*

SRO 4.8

2.1.7 Ability to evaluate plant performance and make operational judgments based on operating characteristics, reactor behavior, and instrument interpretation.

2-1

(CFR: 41.5 / 43.5 / 45.12 / 45.13)

IMPORTANCE

RO 4.4

SRO 4.7

2.1 **Conduct of Operations (continued)** 2.1.8 Ability to coordinate personnel activities outside the control room. (CFR: 41.10 / 45.5 / 45.12 / 45.13) **IMPORTANCE** RO 3.4 SRO 4.1 2.1.9 Ability to direct personnel activities inside the control room. (CFR: 41.10 / 45.5 / 45.12 / 45.13) **IMPORTANCE** RO 2.9* **SRO 4.5** 2.1.10 Moved to 2.2.38 2.1.11 Moved to 2.2.39 2.1.12 **Moved to 2.2.40** 2.1.13 Knowledge of facility requirements for controlling vital/controlled access. (CFR: 41.10 / 43.5 / 45.9 / 45.10) **IMPORTANCE** RO 2.5 SRO 3.2 2.1.14 Knowledge of criteria or conditions that require plant-wide announcements, such as pump starts, reactor trips, mode changes, etc. (CFR: 41.10 / 43.5 / 45.12) **IMPORTANCE** RO 3.1 SRO 3.1 Knowledge of administrative requirements for temporary management 2.1.15 directives, such as standing orders, night orders, operations memos, etc. (CFR: 41.10 / 45.12) **IMPORTANCE** RO 2.7 SRO 3.4 2.1.16 **Deleted** 2.1.17 Ability to make accurate, clear, and concise verbal reports. (CFR: 41.10 / 45.12 / 45.13) **IMPORTANCE** RO 3.9 SRO 4.0 2.1.18 Ability to make accurate, clear, and concise logs, records, status boards, and reports. (CFR: 41.10 / 45.12 / 45.13) SRO 3.8 IMPORTANCE RO 3.6 2.1.19 Ability to use plant computers to evaluate system or component status. (CFR: 41.10 / 45.12) **IMPORTANCE** RO 3.9 SRO 3.8

- 2.1 Conduct of Operations (continued)
- 2.1.20 Ability to interpret and execute procedure steps.

(CFR: 41.10 / 43.5 / 45.12)

IMPORTANCE RO 4.6

SRO 4.6

2.1.21 Ability to verify the controlled procedure copy.

(CFR: 41.10 / 45.10 / 45.13)

IMPORTANCE RO 3.5*

SRO 3.6*

- 2.1.22 **Revised and moved to 2.2.35**
- 2.1.23 Ability to perform specific system and integrated plant procedures during all modes of plant operation.

(CFR: 41.10 / 43.5 / 45.2 / 45.6)

IMPORTANCE RO 4.3

SRO 4.4

- 2.1.24 Moved to 2.2.41
- 2.1.25 Ability to interpret reference materials, such as graphs, curves, tables, etc.

(CFR: 41.10 / 43.5 / 45.12)

IMPORTANCE

RO 3.9

SRO 4.2

2.1.26 Knowledge of industrial safety procedures (such as rotating equipment, electrical, high temperature, high pressure, caustic, chlorine, oxygen and hydrogen).

(CFR: 41.10 / 45.12)

IMPORTANCE

RO 3.4

SRO 3.6

2.1.27 Knowledge of system purpose and/or function.

(CFR: 41.7)

IMPORTANCE

RO 3.9

SRO 4.0

2.1.28 Knowledge of the purpose and function of major system components and controls.

(CFR: 41.7)

IMPORTANCE

RO 4.1

SRO 4.1

2.1.29 Knowledge of how to conduct system lineups, such as valves, breakers, switches, etc.

(CFR: 41.10 / 45.1 / 45.12)

IMPORTANCE

RO 4.1

SRO 4.0

2.1	Conduct of Operations (continued)
2.1.30	Ability to locate and operate components, including local controls. (CFR: 41.7 / 45.7)
 	IMPORTANCE RO 4.4 SRO 4.0
2.1.31	Ability to locate control room switches, controls, and indications, and to determine that they correctly reflect the desired plant lineup. (CFR: $41.10/45.12$)
 	IMPORTANCE RO 4.6 SRO 4.3
2.1.32	Ability to explain and apply system limits and precautions. (CFR: 41.10 / 43.2 / 45.12)
	IMPORTANCE RO 3.8 SRO 4.0
2.1.33	Moved to 2.2.42
2.1.34	Knowledge of primary and secondary plant chemistry limits. (CFR: 41.10 / 43.5 / 45.12)
	IMPORTANCE RO 2.7 SRO 3.5
2.1.35	Knowledge of the fuel-handling responsibilities of SROs. (CFR: 41.10 / 43.7)
 	IMPORTANCE RO 2.2 SRO 3.9
2.1.36	Knowledge of procedures and limitations involved in core alterations. (CFR: $41.10 / 43.6 / 45.7$)
 	IMPORTANCE RO 3.0 SRO 4.1
2.1.37	Knowledge of procedures, guidelines, or limitations associated with reactivity management. $(CFR: 41.1 / 43.6 / 45.6)$
 	IMPORTANCE RO 4.3 SRO 4.6
2.1.38	Knowledge of the station's requirements for verbal communications when implementing procedures. (CFR: $41.10 / 45.13$)
	IMPORTANCE RO 3.7* SRO 3.8
2.1.39	Knowledge of conservative decision making practices. (CFR: 41.10 / 43.5 / 45.12)
	IMPORTANCE RO 3.6 SRO 4.3
2.1.40	Knowledge of refueling administrative requirements. (CFR: 41.10 / 43.5 / 45.13)
 	IMPORTANCE RO 2.8 SRO 3.9

- 2.1 Conduct of Operations (continued)
- 2.1.41 Knowledge of the refueling process.

(CFR: 41.2 / 41.10 / 43.6 / 45.13) IMPORTANCE RO 2.8 SRO 3.7

2.1.42 Knowledge of new and spent fuel movement procedures.

(CFR: 41.10 / 43.7 / 45.13)

IMPORTANCE RO 2.5 SRO 3.4

2.1.43 Ability to use procedures to determine the effects on reactivity of plant changes, such as reactor coolant system temperature, secondary plant, fuel depletion, etc.

(CFR: 41.10 / 43.6 / 45.6)

IMPORTANCE RO 4.1 SRO 4.3

2.1.44 Knowledge of RO duties in the control room during fuel handling such as responding to alarms from the fuel handling area, communication with the fuel storage facility, systems operated from the control room in support of fueling operations, and supporting instrumentation.

(CFR: 41.10 / 43.7 / 45.12)

IMPORTANCE RO 3.9 SRO 3.8

2.1.45 Ability to identify and interpret diverse indications to validate the response of another indication.

(CFR: 41.7 / 43.5 / 45.4)

IMPORTANCE RO 4.3 SRO 4.3

2.2 Equipment Control

2.2.1 Ability to perform pre-startup procedures for the facility, including operating those controls associated with plant equipment that could affect reactivity.

(CFR: 41.5 / 41.10 / 43.5 / 43.6 / 45.1) IMPORTANCE RO 4.5 SRO 4.4

2.2.2 Ability to manipulate the console controls as required to operate the facility between shutdown and designated power levels.

(CFR: 41.6 / 41.7 / 45.2) IMPORTANCE RO 4.6 SRO 4.1

2.2.3 (multi-unit license) Knowledge of the design, procedural, and operational differences between units.

(CFR: 41.5 / 41.6 / 41.7 / 41.10 / 45.12) IMPORTANCE RO 3.8 SRO 3.9

2.2.4 (multi-unit license) Ability to explain the variations in control board/control room layouts, systems, instrumentation, and procedural actions between units at a facility.

(CFR: 41.6 / 41.7 / 41.10 / 45.1 / 45.13) IMPORTANCE RO 3.6 SRO 3.6

2.2.5 Knowledge of the process for making design or operating changes to the facility.

(CFR: 41.10 / 43.3 / 45.13) IMPORTANCE RO 2.2 SRO 3.2

2.2.6 Knowledge of the process for making changes to procedures.

(CFR: 41.10 / 43.3 / 45.13) IMPORTANCE RO 3.0 SRO 3.6

2.2.7 Knowledge of the process for conducting special or infrequent tests.

(CFR: 41.10 / 43.3 / 45.13) IMPORTANCE RO 2.9 SRO 3.6

2.2.8 **Deleted**

2.2.9 **Deleted**

2.2.10 **Deleted**

- 2.2 Equipment Control (continued)
- 2.2.11 Knowledge of the process for controlling temporary design changes.

(CFR: 41.10 / 43.3 / 45.13)

IMPORTANCE RO 2.3 SRO 3.3

2.2.12 Knowledge of surveillance procedures.

(CFR: 41.10 / 45.13)

IMPORTANCE RO 3.7 SRO 4.1

2.2.13 Knowledge of tagging and clearance procedures.

(CFR: 41.10 / 45.13)

IMPORTANCE RO 4.1 SRO 4.3

2.2.14 Knowledge of the process for controlling equipment configuration or status.

(CFR: 41.10 / 43.3 / 45.13)

IMPORTANCE RO 3.9 SRO 4.3

2.2.15 Ability to determine the expected plant configuration using design and configuration control documentation, such as drawings, line-ups, tag-outs, etc.

(CFR: 41.10 / 43.3 / 45.13)

IMPORTANCE RO 3.9 SRO 4.3

- 2.2.16 **Deleted**
- 2.2.17 Knowledge of the process for managing maintenance activities during power operations, such as risk assessments, work prioritization, and coordination with the transmission system operator.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 2.6 SRO 3.8

2.2.18 Knowledge of the process for managing maintenance activities during shutdown operations, such as risk assessments, work prioritization, etc.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 2.6 SRO 3.9

2.2.19 Knowledge of maintenance work order requirements.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 2.3 SRO 3.4

2.2 **Equipment Control (continued)** 2.2.20 Knowledge of the process for managing troubleshooting activities. (CFR: 41.10 / 43.5 / 45.13) **IMPORTANCE** RO 2.6 **SRO 3.8** Knowledge of pre- and post-maintenance operability requirements. 2.2.21 (CFR: 41.10 / 43.2) **IMPORTANCE** RO 2.9 SRO 4.1 2.2.22 Knowledge of limiting conditions for operations and safety limits. (CFR: 41.5 / 43.2 / 45.2) RO 4.0 **IMPORTANCE** SRO 4.7 Ability to track Technical Specification limiting conditions for operations. 2.2.23 (CFR: 41.10 / 43.2 / 45.13) **IMPORTANCE** RO 3.1 **SRO 4.6** 2.2.24 Moved to **2.2.36 Knowledge of the bases in Technical Specifications for limiting conditions** 2.2.25 for operations and safety limits. (CFR: 41.5 / 41.7 / 43.2) **IMPORTANCE** RO 3.2 SRO 4.2 2.2.26 Moved to **2.1.40** 2.2.27 Moved to 2.1.41 2.2.28 Moved to 2.1.42 2.2.29 Moved to 2.1.35 2.2.30 Moved to 2.1.44 2.2.31 Revised and moved to 2.1.36 2.2.32 **Deleted 2.2.33 Deleted** 2.2.34 Revised and moved to **2.1.43**

- **2.2** Equipment Control (continued)
- 2.2.35 Ability to determine Technical Specification Mode of Operation.

(CFR: 41.7 / 41.10 / 43.2 / 45.13)

IMPORTANCE RO 3.6 SRO 4.5

2.2.36 Ability to analyze the effect of maintenance activities, such as degraded power sources, on the status of limiting conditions for operations.

(CFR: 41.10 / 43.2 / 45.13)

IMPORTANCE RO 3.1 SRO 4.2

2.2.37 Ability to determine operability and/or availability of safety related equipment.

(CFR: 41.7 / 43.5 / 45.12)

IMPORTANCE RO 3.6 SRO 4.6

2.2.38 Knowledge of conditions and limitations in the facility license.

(CFR: 41.7 / 41.10 / 43.1 / 45.13)

IMPORTANCE RO 3.6 SRO 4.5

2.2.39 Knowledge of less than or equal to one hour Technical Specification action statements for systems.

(CFR: 41.7 / 41.10 / 43.2 / 45.13)

IMPORTANCE RO 3.9 SRO 4.5

2.2.40 Ability to apply Technical Specifications for a system.

(CFR: 41.10 / 43.2 / 43.5 / 45.3)

IMPORTANCE RO 3.4 SRO 4.7

2.2.41 Ability to obtain and interpret station electrical and mechanical drawings.

(CFR: 41.10 / 45.12 / 45.13)

IMPORTANCE RO 3.5 SRO 3.9

2.2.42 Ability to recognize system parameters that are entry-level conditions for Technical Specifications.

(CFR: 41.7 / 41.10 / 43.2 / 43.3 / 45.3)

IMPORTANCE RO 3.9 SRO 4.6

2.2.43 Knowledge of the process used to track inoperable alarms.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.0 SRO 3.3

2.2 Equipment Control (continued)

2.2.44 Ability to interpret control room indications to verify the status and operation of a system, and understand how operator actions and directives affect plant and system conditions.

(CFR: 41.5 / 43.5 / 45.12)

IMPORTANCE RO 4.2 SRO 4.4

- 2.3 Radiation Control
- 2.3.1 **Deleted**
- 2.3.2 **Deleted**
- **2.3.3 Deleted**
- 2.3.4 Knowledge of radiation exposure limits under normal or emergency conditions.

(CFR: 41.12 / 43.4 / 45.10)

IMPORTANCE RO 3.2

SRO 3.7

2.3.5 Ability to use radiation monitoring systems, such as fixed radiation monitors and alarms, portable survey instruments, personnel monitoring equipment, etc.

(CFR: 41.11 / 41.12 / 43.4 / 45.9)

IMPORTANCE RO 2.9

SRO 2.9

2.3.6 Ability to approve release permits.

(CFR: 41.13 / 43.4 / 45.10)

IMPORTANCE RO 2.0

SRO 3.8

2.3.7 Ability to comply with radiation work permit requirements during normal or abnormal conditions.

(CFR: 41.12 / 45.10)

IMPORTANCE RO 3.5 SRO 3.6

- **2.3.8 Deleted**
- **2.3.9 Deleted**
- 2.3.10 **Deleted**
- 2.3.11 Ability to control radiation releases.

(CFR: 41.11 / 43.4 / 45.10)

IMPORTANCE RO 3.8

SRO 4.3

2.3.12 Knowledge of radiological safety principles pertaining to licensed operator duties, such as containment entry requirements, fuel handling responsibilities, access to locked high-radiation areas, aligning filters, etc.

(CFR: 41.12 / 45.9 / 45.10)

IMPORTANCE RO 3.2

SRO 3.7

2.3 Radiation Control (continued)

2.3.13 Knowledge of radiological safety procedures pertaining to licensed operator duties, such as response to radiation monitor alarms, containment entry requirements, fuel handling responsibilities, access to locked high-radiation areas, aligning filters, etc.

(CFR: 41.12 / 43.4 / 45.9 / 45.10) IMPORTANCE RO 3.4 SRO 3.8

2.3.14 Knowledge of radiation or contamination hazards that may arise during normal, abnormal, or emergency conditions or activities.

(CFR: 41.12 / 43.4 / 45.10) IMPORTANCE RO 3.4 SRO 3.8

2.3.15 Knowledge of radiation monitoring systems, such as fixed radiation monitors and alarms, portable survey instruments, personnel monitoring equipment, etc.

(CFR: 41.12 / 43.4 / 45.9) IMPORTANCE RO 2.9 SRO 3.1 2.4 Emergency Procedures / Plan

2.4.1 Knowledge of EOP entry conditions and immediate action steps.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 4.6 SRO 4.8

2.4.2 Knowledge of system set points, interlocks and automatic actions associated with EOP entry conditions.

(CFR: 41.7 / 45.7 / 45.8)

IMPORTANCE RO 4.5 SRO 4.6

2.4.3 Ability to identify post-accident instrumentation.

(CFR: 41.6 / 45.4)

IMPORTANCE RO 3.7 SRO 3.9

2.4.4 Ability to recognize abnormal indications for system operating parameters that are entry-level conditions for emergency and abnormal operating procedures.

(CFR: 41.10 / 43.2 / 45.6)

IMPORTANCE RO 4.5 SRO 4.7

2.4.5 Knowledge of the organization of the operating procedures network for normal, abnormal, and emergency evolutions.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.7 SRO 4.3

2.4.6 Knowledge of EOP mitigation strategies.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.7 SRO 4.7

2.4.7 Deleted

2.4.8 Knowledge of how abnormal operating procedures are used in conjunction with EOPs.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.8 SRO 4.5

2.4.9 Knowledge of low power/shutdown implications in accident (e.g., loss of coolant accident or loss of residual heat removal) mitigation strategies.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.8 SRO 4.2

2.4	Emergency Procedures / Plan (continued)
2.4.10	Deleted
2.4.11	Knowledge of abnormal condition procedures. (CFR: 41.10 / 43.5 / 45.13) IMPORTANCE RO 4.0 SRO 4.2
2.4.12	Knowledge of general operating crew responsibilities during emergency operations. (CFR: $41.10 / 45.12$) IMPORTANCE RO 4.0 SRO 4.3
2.4.13	Knowledge of crew roles and responsibilities during EOP usage. (CFR: $41.10 / 45.12$) IMPORTANCE RO 4.0 SRO 4.6
2.4.14	Knowledge of general guidelines for EOP usage. (CFR: 41.10 / 45.13) IMPORTANCE RO 3.8 SRO 4.5
2.4.15	Revised and moved to 2.1.38
2.4.16	Knowledge of EOP implementation hierarchy and coordination with other support procedures or guidelines such as, operating procedures, abnormal operating procedures, and severe accident management guidelines. (CFR: 41.10 / 43.5 / 45.13) IMPORTANCE RO 3.5 SRO 4.4
2.4.17	Knowledge of EOP terms and definitions. (CFR: 41.10 / 45.13) IMPORTANCE RO 3.9 SRO 4.3
2.4.18	Knowledge of the specific bases for EOPs. (CFR: 41.10 / 43.1 / 45.13) IMPORTANCE RO 3.3 SRO 4.0
2.4.19	Knowledge of EOP layout, symbols, and icons. (CFR: 41.10 / 45.13) IMPORTANCE RO 3.4 SRO 4.1
2.4.20	Knowledge of the operational implications of EOP warnings, cautions, and notes. $ (\text{CFR:} \ 41.10 \ / \ 43.5 \ / \ 45.13) \\ \text{IMPORTANCE} \text{RO } 3.8 \qquad \text{SRO } 4.3 $

- 2.4 Emergency Procedures / Plan (continued)
- 2.4.21 Knowledge of the parameters and logic used to assess the status of safety functions, such as reactivity control, core cooling and heat removal, reactor coolant system integrity, containment conditions, radioactivity release control, etc.

(CFR: 41.7 / 43.5 / 45.12)

IMPORTANCE RO 4.0 SRO 4.6

2.4.22 Knowledge of the bases for prioritizing safety functions during abnormal/emergency operations.

(CFR: 41.7 / 41.10 / 43.5 / 45.12)

IMPORTANCE RO 3.6 SRO 4.4

2.4.23 Knowledge of the bases for prioritizing emergency procedure implementation during emergency operations.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.4 SRO 4.4

- 2.4.24 **Deleted**
- 2.4.25 Knowledge of fire protection procedures.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.3 SRO 3.7

2.4.26 Knowledge of facility protection requirements, including fire brigade and portable fire fighting equipment usage.

(CFR: 41.10 / 43.5 / 45.12)

IMPORTANCE RO 3.1 SRO 3.6

2.4.27 Knowledge of "fire in the plant" procedures.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.4 SRO 3.9

2.4.28 Knowledge of procedures relating to a security event (non-safeguards information).

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.2 SRO 4.1

2.4.29 Knowledge of the emergency plan.

(CFR: 41.10 / 43.5 / 45.11)

IMPORTANCE RO 3.1 SRO 4.4

2.4 Emergency Procedures / Plan (continued)

2.4.30 Knowledge of events related to system operation/status that must be reported to internal organizations or external agencies, such as the State, the NRC, or the transmission system operator.

(CFR: 41.10 / 43.5 / 45.11)

IMPORTANCE RO 2.7 SRO 4.1

2.4.31 Knowledge of annunciator alarms, indications, or response procedures.

(CFR: 41.10 / 45.3)

IMPORTANCE RO 4.2 SRO 4.1

2.4.32 Knowledge of operator response to loss of all annunciators.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.6 SRO 4.0

2.4.33 Moved to **2.2.43**

2.4.34 Knowledge of RO tasks performed outside the main control room during an emergency and the resultant operational effects.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 4.2 SRO 4.1

2.4.35 Knowledge of local auxiliary operator tasks during an emergency and the resultant operational effects.

(CFR: 41.10 / 43.5 / 45.13)

IMPORTANCE RO 3.8 SRO 4.0

2.4.36 **Deleted**

2.4.37 Knowledge of the lines of authority during implementation of the emergency plan.

(CFR: 41.10 / 45.13)

IMPORTANCE RO 3.0 SRO 4.1

2.4.38 Ability to take actions called for in the facility emergency plan, including supporting or acting as emergency coordinator if required.

(CFR: 41.10 / 43.5 / 45.11)

IMPORTANCE RO 2.4 SRO 4.4

2.4.39 Knowledge of RO responsibilities in emergency plan implementation.

(CFR: 41.10 / 45.11)

IMPORTANCE RO 3.9 SRO 3.8

2.4 **Emergency Procedures / Plan (continued)** 2.4.40 **Knowledge of SRO responsibilities in emergency plan implementation.** (CFR: 41.10 / 43.5 / 45.11) **IMPORTANCE** RO 2.7 SRO 4.5 Knowledge of the emergency action level thresholds and classifications. 2.4.41 (CFR: 41.10 / 43.5 / 45.11) **IMPORTANCE** RO 2.9 SRO 4.6 2.4.42 Knowledge of emergency response facilities. (CFR: 41.10 / 45.11) **IMPORTANCE** RO 2.6 **SRO 3.8** 2.4.43 **Knowledge of emergency communications systems and techniques.** (CFR: 41.10 / 45.13) **IMPORTANCE** RO 3.2 SRO 3.8 2.4.44 **Knowledge of emergency plan protective action recommendations.** (CFR: 41.10 / 41.12 / 43.5 / 45.11) **IMPORTANCE** RO 2.4 SRO 4.4 Ability to prioritize and interpret the significance of each annunciator or 2.4.45(CFR: 41.10 / 43.5 / 45.3 / 45.12) **IMPORTANCE** RO 4.1 SRO 4.3 2.4.46 Ability to verify that the alarms are consistent with the plant conditions. (CFR: 41.10 / 43.5 / 45.3 / 45.12) **IMPORTANCE** RO 4.2 SRO 4.2 2.4.47 Ability to diagnose and recognize trends in an accurate and timely manner utilizing the appropriate control room reference material. (CFR: 41.10 / 43.5 / 45.12) **IMPORTANCE** RO 4.2 SRO 4.2 2.4.48 Revised and moved to **2.2.44**

2.4.49 Ability to perform without reference to procedures those actions that require immediate operation of system components and controls.

(CFR: 41.10 / 43.2 / 45.6)

IMPORTANCE RO 4.6 SRO 4.4

- 2.4 Emergency Procedures / Plan (continued)
- 2.4.50 Ability to verify system alarm setpoints and operate controls identified in the alarm response manual.

(CFR: 41.10 / 43.5 / 45.3)

IMPORTANCE RO 4.2 SRO 4.0

3.1	Reactivity Control	page
201001	Control Rod Drive Hydraulic System	3.1-3
201003	Control Rod and Drive Mechanism	3.1-7
201002	Reactor Manual Control System	3.1-10
202002	Recirculation flow Control System	3.1-13
202001	Recirculation System	3.1-17
201005	Rod Control and Information System	3.1-22
211000	Standby Liquid Control System	3.1-25

This page left blank

TASK: Perform lineups on the CRD hydraulic system
Place the control rod drive system in service
Monitor the control rod Drive System
Remove Control Rod Drive System From Service

Vent the control rod drive system (write in)

Conduct CRD hydraulics valve testing during cold shutdown

	IMPORTAN	C E
K/A NO.	KNOWLEDGE RO	SRO
К1.	Knowledge of the physical connections and/or cause-effect relationships between CONTROL ROD DRIVE HYDRAULIC SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Condensate system	3.1
K1.02	Condensate storage tanks	3.0
K1.03	Recirculation pumps (seal purge): Plant-Specific	3.1
K1.04	Head spray: BWR-3	2.7
K1.05	Feedwater (or reactor water cleanup)-CRD return to	
	vessel: Plant-Specific	2.7
K1.06	Component cooling water systems: Plant-Specific	2.8
K1.07	Reactor protection system	3.4
K1.08	Reactor manual control system	3.4
K1.09	Plant air systems	3.2
K1.10	Control rod drive mechanisms	2.8
K1.11	Reactor water cleanup pumps: Plant-Specific	2.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Pumps	3.1
K2.02	Scram valve solenoids	3.7
K2.03	Backup SCRAM valve solenoids	3.6*
K2.04	Scram discharge volume vent and drain valve solenoids	3.3
K2.05	Alternate rod insertion valve solenoids: Plant-Specific	4.5*
K2.06	Motor operated valves	2.3*
K2.07	Breaker control	2.1*
К3.	Knowledge of the effect that a loss or malfunction of the CONTROL ROD DRIVE HYDRAULIC SYSTEM will have on following: (CFR: 41.7 / 45.4)	
K3.01 K3.02	Recirculation pumps: Plant-Specific 3.0 Reactor water level 2.6	3.1 2.6
K3.03	Control rod drive mechanisms	3.2
K3.04	Head spray: BWR-3	2.7
K3.05	Reactor water cleanup pumps: Plant-Specific	2.3

	IMPORTANCE	1
K/A NO.	KNOWLEDGE RO	
K4.	Knowledge of CONTROL ROD DRIVE HYDRAULIC SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR 41.7)	
K4.01	Protection against pump runout during SCRAM conditions (location of the CRD system flow element and a restricting orifice in the accumulator charging water line)	2.6
K4.02	Stable system flow when moving control rods (stabilizing valves)	2.6
K4.03	Control rod drive mechanism cooling water flow	2.7
K4.04	Scramming control rods with inoperative SCRAM solenoid	2.7
	valves (back-up SCRAM valves)	3.6
K4.05	Control rod SCRAM	3.8
K4.06	Isolation of the SCRAM discharge volumes during SCRAM	
	conditions	3.9
K4.07	Testing SCRAM discharge volume isolation valves	2.8
K4.08	Controlling control rod drive header pressure	3.0
K4.09	Controlling control rod drive cooling header pressure	2.8
K4.10	Control of rod movement (HCU directional control valves)	3.0
K4.11	Protection against filling the SDV during non-SCRAM conditions	3.6
K4.12	Controlling CRD system flow	2.9
K4.13	Motor cooling	2.3
K5.	Knowledge of the operational implications of the following concepts as they apply to CONTROL ROD DRIVE HYDRAULIC SYSTEM: (CFR::: 41.5 / 45.3)	
K5.01	Pump operation	2.4
K5.02	Flow indication	2.4
K5.02 K5.03	Pressure indication 2.7	2.0
K5.03 K5.04	Indications of pump cavitation 2.4	2.7
	1 1	2.4
K5.05	Indications of pump runout: Plant-Specific	
K5.06	Differential pressure indication	2.6
K5.07	Air operated control valves	2.4
K5.08	Solenoid operated valves	2.6
K5.09	System venting	* 2.2*
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the CONTROL ROD DRIVE HYDRAULIC System: (CFR: 41.7 / 45.7)	
K6.01 K6.02	Condensate system2.8Condensate storage tanks3.0	2.8 3.1

Tasks as noted			-
TZ/A NIO		RTANC	
K/A NO.	KNOWLEDGE	RO	SRO
K6.03	Plant air systems	3.0	2.9
K6.04	RPS		3.7
K6.05	A.C. power		3.3
K6.06	Component cooling water systems: Plant-Specific		2.8
110.00	Component cooming water systems. Thank specific	. 2.0	2.0
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the CONTROL ROD DRIVE HYDRAULIC SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	CRD drive water header pressure	. 3.1	2.9
A1.02	CRD cooling water header pressure		2.9
A1.03	CRD system flow		2.8
A1.04	Head spray flow: BWR-3		2.7
A1.05	SDV isolation valve position	. 3.5	3.4
A1.06	HCU pressure/level	. 3.4	3.4
A1.07	Reactor water level	. 3.3	3.2
A1.08	Pump amps	. 2.3	2.2
A1.09	CRD drive water flow		2.8
A1.10	CRD cooling water flow	. 2.8	2.6
A2.	Ability to (a) predict the impacts of the following on the CONTROL ROD DRIVE HYDRAULIC SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Pumps trips	. 3.2	3.3
A2.02	Valve closures		3.3
A2.03	Power supply failures		3.1
A2.04	†Scram conditions		3.9*
A2.05	Discharge strainer(s) becoming plugged		2.9
A2 06	Suction strainer(s) becoming plugged		2.9
A2.07	Flow control valve failure		3.1
A2.08	Inadequate system flow		2.8 3.1
A2.09 A2.10	Loss of applicable plant air systems		3.1
A2.10 A2.11	Valve openings		3.0 2.7
A2.11 A2.12	High cooling water flow		2.7
A2.12 A2.13	Low cooling water flow		2.9
A2.13 A2.14	Low drive header pressure		2.8
. 14.1 "	20 w diffe fledddi pressure	. 2.0	2.0

A3.	Ability to monitor automatic operations of the CONTROL ROD DRIVE HYDRAULIC SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01 A3.02	Valve operation	3.0 2.8
A3.03	System pressure	2.7
A3.04	System flow	2.7
A3.05	Reactor water level	2.8
A3.06	Reactor power	2.8
A3.07	HCU accumulator pressure/level	3.3
A3.08	Drive water flow	2.9
A3.09	Cooling water flow	2.8
A3.10	Lights and alarms	2.9
A3.11	SDV level	3.5
A4.	Ability to manually operate and/or monitor in the control room: CFR: 41.7 / 45.5 to 45.8)	
A4.01	CRD pumps	3.1
A4.02	CRD pump discharge valve	2.6
A4.03	CRD system flow control valve	2.8
A4.04	Drive water header pressure control valve	3.0
A4.05	Cooling water header pressure control valve	2.8
A4.06	SDV isolation valve test switch	2.7
A4.07	Stabilizing valve selector switch	2.1*

SYSTEM: 201003 Control Rod and Drive Mechanism

Conduct Control Rod Operability Test

TASK: Flush a CRD mechanism

	Perform control rod drive accumulator piston seal exercising		
	Perform the control rod drive timing test (write in)		
	Perform friction testing		
		IMPORTANC	
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between CONTROL ROD AND DRIVE MECHANISM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Control rod drive hydraulic system	3.2	3.3
K1.02	Reactor water		3.0
K1.03	RPIS		3.1
K1.04	Reactor vessel		2.9
K1.04 K1.05	CRD mechanism temperature monitor		2.6
K1.03	CKD mechanism temperature monitor	2.0	2.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
	None		
К3.	Knowledge of the effect that a loss or malfunction of the CONTROL ROD AND DRIVE MECHANISM will have on following: (CFR: 41.7 / 45.4)		
K3.01	Reactor power	3.2	3.4
K3.02	†Flux shaping		3.1
K3.03	†Shutdown margin		3.8
13.03	Shutdown margin		3.0
K4.	Knowledge of CONTROL ROD AND DRIVE MECHANISM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Limiting control rod speed in the event of a rod drop	2.9*	3.0*
K4.02	Detection of an uncoupled rod	3.8	3.9
K4.03	Slowing the drive mechanism near the end of its travel		
	following a SCRAM: Plant-Specific	2.1*	2.1*
K4.04	The use of either accumulator or reactor water to		
	SCRAM the control rod	3.6	3.7
K4.05	Rod position indication		3.3
K4.06	Uncoupling the control rod from the drive mechanism		2.6
K4.07	Maintaining the control rod at a given location		3.2
K4.07 K4.08	Monitoring CRD mechanism temperature		2.7
134.00	Monitoring CKD incchainsin temperature	2.0	∠.1

Conduct Control Rod Coupling Integrity Test
Perform Control Rod Drive Stall Flow Testing (CRD 18-Month Accumulator Operability Test)

SYSTEM: 201003 Control Rod and Drive Mechanism

		IMPORTANCE	
K/A NO.	KNOWLEDGE	RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to CONTROL ROD AND DRIVE MECHANISM: (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03 K5.04 K5.05 K5.06	Hydraulics †Flux shaping Reactor power control †Rod sequence patterns Reverse power effect How control rod worth varies with moderator temperature and voids How control rod movements affect core reactivity	2.8 3.3 3.1 3.0	2.7 3.3 3.4 3.4 3.1 2.9 3.6
K5.08	How control rods affect shutdown margin	3.1	3.5
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the CONTROL ROD AND DRIVE MECHANISM: (CFR: 41.7 / 45.7)		
K6.01 K6.02	Control rod drive hydraulic system		3.3 3.0
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the CONTROL ROD AND DRIVE MECHANISM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03	Reactor power CRD drive pressure CRD drive water flow	2.8	3.8 2.8 2.9
A2.	Ability to (a) predict the impacts of the following on the CONTROL ROD AND DRIVE MECHANISM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07	†Stuck rod Uncoupled rod †Drifting rod Single control rod SCRAM Reactor Scram Loss of CRD cooling water flow Loss of CRD drive water flow	3.7 3.4 3.5 4.1* 3.0	3.6 3.8 3.7 3.6 4.1 3.1

SYSTEM: 201003 Control Rod and Drive Mechanism

	IMPORTA		
K/A NO.	KNOWLEDGE	RO	SRO
A2.08	Low HCU accumulator pressure/high level	3.8	3.7
A2.09	Low reactor pressure	3.2	3.4
A2.10	†Excessive SCRAM time for a given drive mechanism	3.0	3.4
A3.	Ability to monitor automatic operations of the CONTROL ROD AND DRIVE MECHANISM including: (CFR: 41.7/45.7)		
A3.01	Control rod position	3.7	3.6
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	CRD mechanism temperature	2.6*	2.6*
A4.02	CRD mechanism position: Plant-Specific	3.5	3.5

SYSTEM: 201002 Reactor Manual Control System

TASK: Operate Control Rods Using "Single Notch" Mode
Operate Control Rods Using "Notch Override"
Conduct "Emergency Rod In" Control Rode Insertion
Operate The Control Rod Drive System To Bring The Reactor Critical
Operate the Control Rod Drive Manually At Power
Operate the Control Rod Drive System To Shutdown The Reactor
Conduct Refueling Interlocks Functional Test/Control Rod Drive

Maintenance Test
What if rod drift alarm occurs?

	IMPORTANO	E
K/A NO.	KNOWLEDGE RO	SRO
К1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR MANUAL CONTROL SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03	Control rod drive hydraulic system	3.2 2.9
K1.04 K1.05 K1.06 K1.07 K1.08	refueling	3.6 3.6 3.5 3.3 2.9 3.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02	Select matrix2.1*CRD HCU directional control valves2.1*	2.3* 2.3*
K3.	Knowledge of the effect that a loss or malfunction of the REACTOR MANUAL CONTROL SYSTEM will have on following: (CFR: 41.7 / 45.4)	
K3.01 K3.02 K3.03	Ability to move control rods	3.4 3.2 3.0
K4.	Knowledge of REACTOR MANUAL CONTROL SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02 K4.03	Detection of sequence timer malfunction2.7Control rod blocks3.5Detection of drifting control rods3.6	2.7 3.5 3.6

SYSTEM: 201002 Reactor Manual Control System

Tasks as noted previously			
K/A NO.	KNOWLEDGE	IMPORTANC RO	SRO
K4.04 K4.05 K4.06 K4.07	"Single notch" rod withdrawal and insertion "Notch override" rod withdrawal "Emergency In" rod insertion Timing of rod insert and withdrawal cycles (rod	3.3	3.3 3.3 3.5
K4.08	movement sequence timer)		2.5* 3.2
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR MANUAL CONTROL SYSTEM: (CFR: 41.5 / 45.3) None		
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR MANUAL CONTROL SYSTEM: (CFR: 41.7 / 45.7)		
K6.01	Select matrix power	2.5	2.6
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR MANUAL CONTROL SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05	CRD drive water flow Control rod position Rod movement sequence lights Overall reactor power Local reactor power	3.4 3.0 3.6	2.8 3.3 2.9 3.5 3.6
A2.	Ability to (a) predict the impacts of the following on the REACTOR MANUAL CONTROL SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04	Rod movement sequence timer malfunctions Rod drift alarm Select block Control rod block	3.2	2.8 3.3 2.8 3.1

SYSTEM: 201002 Reactor Manual Control System

		IMPORTANCE	
K/A NO.	ABILITY	RO	SRO
A3.	Ability to monitor automatic operations of the REACTOR MANUAL CONTROL SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	Control rod block actuation	3.2	3.1
A3.02	Rod movement sequence lights		2.7
A3.03	Rod drift alarm	3.2	3.2
A3.04	Rod movement sequence timer malfunction alarm:		
	Plant-Specific	2.8	2.8
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	Rod movement control switch	3.5	3.4
A4.02	Emergency in/notch override switch		3.5
A4.03	Rod drift test switch		2.8
A4.04	Timer malfunction test switch: Plant-Specific	2.8	2.8
A4.05	Rod select matrix		3.0
A4.06	Rod select matrix power switch	2.8	2.8

SYSTEM: 202002 Recirculation Flow Control System

TASK: Adjust the recirculation flow using manual control

Operate recirculation pumps in various control modes (adjust the recirculation flow using "master manual" control)

What if flow mismatch exceeds limits of daily surveillance log

What if power to flow is not in specified range?

**1	IMPORTANC	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO	
K1.	Knowledge of the physical connections and/or cause-effect relationships between RECIRCULATION FLOW CONTROL SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Recirculation system	3.6	
K1.02	Reactor power	4.2	
K1.03	Reactor core flow	3.7	
K1.04	Reactor/turbine pressure regulating system: Plant-		
	Specific	3.1	
K1.05	Recirculation MG set: Plant-Specific	3.5	
K1.06	A.C. electrical	3.0	
K1.07	D.C. electrical	2.8	
K1.08	Feedwater flow	3.2	
K1.09	Reactor water level	3.2	
Kl.10	Rod pattern	2.6	
K1.11	APRM system 3.4	3.4	
K1.12	Recirculation flow control valves: Plant-Specific	3.9	
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Recirculation flow control system	2.4*	
K2.02	Hydraulic power unit: Plant-Specific	2.6	
112.02	Trydraune power unit. Trant specific	2.0	
К3.	Knowledge of the effect that a loss or malfunction of the RECIRCULATION FLOW CONTROL SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01	Core flow	3.5	
K3.02	Reactor power	4.0	
K3.03	Reactor water level	3.4	
K3.04	Reactor/turbine pressure regulation system	3.1	
K3.05	Recirculation pump speed: Plant-Specific	3.3	
K3.06	Recirculation flow control valve position: Plant-		
	Specific	3.7	
	-		

SYSTEM: 202002 Recirculation Flow Control System

	K/A NO.	KNOWLEDGE	IMPORTANCI RO	E SRO
	K4.	Knowledge of RECIRCULATION FLOW CONTROL SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
	K4.01 K4.02 K4.03 K4.04 K4.05	Scoop tube break: Plant-Specific	3.0 3.0	3.1 3.0 3.0 2.4*
	K4.06 K4.07 K4.08 K4.09	Specific Recirculation pump adequate NPSH: Plant-Specific Minimum and maximum pump speed setpoints Automatic flow control valve positioning: BWR-5,6 Minimum and maximum flow control valve position setpoints: BWR-5,6	3.1 2.9 3.3	3.4 3.1 2.9 3.4
	K5.	Knowledge of the operational implications of the following concepts as they apply to RECIRCULATION FLOW CONTROL SYSTEM: (CFR: 41.5 / 45.3)	3.3	3.4
	K5.01 K5.02 K5.03	Fluid coupling: BWR-3,4 Feedback signals Error signals	2.6	2.8 2.6 2.4
	К6.	Knowledge of the effect that a loss or malfunction of the following will have on the RECIRCULATION FLOW CONTROL SYSTEM: (CFR: 41.7 / 45.7)		
	K6.01 K6.02 K6.03 K6.04 K6.05	A.C. power D.C. power Recirculation system Feedwater flow inputs: BWR-3,4,5,6 Reactor water level Reactor/turbine pressure regulating system: Plant-	2.6 2.8 3.5	2.9 2.6 2.8 3.5 3.1
	K6.06 K6.07	Specific		2.9 3.7

SYSTEM: 202002 Recirculation Flow Control System

****		IMPORTANCE SPO	
K/A NO.	ABILITY	RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RECIRCULATION FLOW CONTROL SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08	Recirculation pump speed: BWR-2,3,4,5,6 MG set drive motor amps: Plant-Specific MG set generator current, power, voltage Reactor water level Reactor power Reactor core flow Recirculation loop flow: Plant-Specific Recirculation FCV position: BWR-5,6	2.7 2.5* 2.9 3.6 3.4 3.1	3.2 2.7 2.4* 2.9 3.6 3.3 3.1 3.4
A2.	Ability to (a) predict the impacts of the following on the RECIRCULATION FLOW CONTROL SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04	Recirculation pump trip Loss of A.C. Loss of D.C. Recirculation pump speed mismatch between loops:	2.9	3.4 3.0 2.7
A2.05 A2.06 A2.07 A2.08 A2.09	Plant-Specific Scoop tube lockup: BWR-2,3,4 Low reactor water level: Plant-Specific Loss of feedwater signal inputs: Plant-Specific FCV lockup: BWR-5,6 †Recirculation flow mismatch: Plant-Specific	3.1 3.3 3.3	3.2 3.1 3.3 3.3 3.3 3.3
A3.	Ability to monitor automatic operations of the RECIRCULATION FLOW CONTROL SYSTEM including: (CFR: 41.7/45.7)		
A3.01 A3.02 A3.03	Flow control valve operation: BWR-5,6 Lights and alarms Scoop tube operation: BWR-2,3,4	3.4	3.4 3.4 3.0
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01 A4.02 A4.03	MG sets Hydraulic power unit: BWR-5,6 Lights and alarms	2.8	3.1 2.8 3.1

A4.04	Reactor power	3.8
A4.05	Reactor level	3.4
A4.06	Scoop tube power: BWR-2,3,4	2.6
A4.07	Recirculation pump speed: BWR-2,3,4,5,6	3.2
A4.08	Recirculation system flow	3.3
A4.09	Core flow	3.3

SYSTEM: 202001 Recirculation System

TASK: Perform lineups on the recirculation system

Vent recirculation pump seals

Startup a recirculation pump (startup a second recirculation pump)

Operate recirculation pumps in various control modes (adjust the recirculation flow using "master manual" control)

Monitor recirculation pumps in operation

Monitor jet pump operation

Secure a recirculation pump

Perform jet pump operability test

Conduct heatup and cooldown temperature checks

Conduct recirculation pump startup check of the delta temperature between the reactor coolant in the idle loop to the reactor vessel

Conduct recirculation pump trip logic system functional test

Conduct recirculation loop valve operability test

Conduct recirculation system valve testing

What if jet pumps not operating within required operating band

		IMPORTANC	Œ
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RECIRCULATION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Core flow	3.6	3.7
K1.02	Reactor power		4.1
K1.03	Reactor moderator temperature		3.3
K1.04	Reactor/turbine pressure regulating system: Plant-		- 10
	Specific	3.3	3.3
K1.05	Reactor pressure		3.4
K1.06	Jet pumps		3.6
K1.07	Component cooling water systems		3.2
K1.08	A.C. electrical	3.1	3.2
K1.09	D.C. electrical	2.7	2.9
K1.10	Control rod drive system: Plant-Specific	2.8	2.8
K1.11	Drywell equipment drain sump	2.7	2.8
K1.12	Recirculation system motor-generator sets: Plant-		
	Specific		3.6
K1.13	Jet pump ring header and risers: Plant-Specific	3.1	3.2
K1.14	Rod block monitor: Plant-Specific	3.0	3.2
K1.15	Nuclear boiler instrumentation (reactor water		
	level/pressure)		3.2
K1.16	Low pressure coolant injection logic: Plant-Specific		3.9
K1.17	Vessel bottom head drain temperature		3.3
K1.18	RHR shutdown cooling mode		3.3
K1.19	Feedwater flow	3.2	3.2
K1.20	Plant air systems: Plant-Specific		2.5
K1.21	Reactor water cleanup system	2.6	2.6

SYSTEM: 202001 Recirculation System

Tasks as noted	IN	IPORTANC	
K/A NO.	KNOWLEDGE	RO	SRO
K1.22	Reactor water level	3.5	3.6
K1.23	Average power range monitor flow converters: Plant-		
	Specific		3.5
K1.24	Isolation condenser: Plant-Specific		3.4
K1.25	Reactor water sampling system		2.7
K1.26	Recirculation flow control system: Plant-Specific		3.6
K1.27	ATWS circuitry: Plant-Specific	4.1	4.3*
K1.28	End-of-cycle recirculation pump trip circuitry:	2.0	4.4
	Plant-Specific	3.9	4.1
K2.	Knowledge of electrical power supplies to the following:		
	(CFR: 41.7)		
K2.01	Recirculation pumps: Plant-Specific	3.2*	3.2
K2.02	MG sets: Plant-Specific		3.3
K2.03	Recirculation system valves		2.8*
K2.04	Hydraulic power unit oil pumps: Plant-Specific		2.5*
K2.05	MG set oil pumps: Plant-Specific		2.3*
К3.	Knowledge of the effect that a loss or malfunction of the RECIRCULATION SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01	Core flow		3.6
K3.02	Load following capabilities: Plant-Specific		2.8
K3.03	Reactor power		3.9
K3.04	Reactor water level		3.7
K3.05	Recirculation system MG sets: Plant-Specific		3.3
K3.06	Low pressure coolant injection logic: Plant-Specific		3.9
K3.07	Vessel bottom head drain temperature		2.9
K3.08	Shutdown cooling system		2.9
K3.09	Reactor water cleanup system		2.5*
K3.10	Average power range monitor flow converters		3.4
K3.11	Component cooling water systems		2.3*
K3.12	Isolation condenser: Plant-Specific		3.0
K3.13	Reactor water sampling system		2.5
K3.14	Primary containment integrity: Plant-Specific	3.3	3.5
K4.	Knowledge of RECIRCULATION System design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	2/3 core coverage: Plant-Specific	3.9	3.9
K4.02	Adequate recirculation pump NPSH	3.1	3.2
K4.03	Recirculation pump motor cooling	2.8	2.8
K4.04	Controlled seal flow	3.0	3.1
K4.05	Seal cooling	2.9	2.9

SYSTEM: 202001 Recirculation System

V/A NO	WNOW! EDGE	IMPORTANCE SPO	
K/A NO.	KNOWLEDGE	RO	SRO
K4.06	Automatic voltage/frequency regulation: Plant-		
	Specific	2.6*	2.7
K4.07	Motor generator set trips: Plant-Specific		2.9
K4.08	Oil pump automatic starts: Plant-Specific		2.9
K4.09	Pump minimum flow limit: Plant-Specific		2.9
K4.10	Pump start permissives: Plant-Specific	3.3	3.4
K4.11	Limitation of recirculation pumps flow mismatch:		
	Plant-Specific	3.1	3.5
K4.12	Minimization of reactor vessel bottom head temperature		
TT 1 10	gradients: Plant-Specific		3.5
K4.13	†End of cycle recirculation pump trip: Plant-Specific		4.0*
K4.14	ATWS: Plant-Specific		4.1*
K4.15	Slow speed pump start: Plant-Specific		3.4
K4.16	Recirculation pump downshift/runback: Plant-Specific		3.6
K4.17	Fast speed pump start: Plant-Specific		3.5
K4.18	Automatic MG set start sequencing: Plant-Specific	2.8	3.0
K5.	Knowledge of the operational implications of the		
	following concepts as they apply to RECIRCULATION		
	SYSTEM:		
	(CFR: 41.5 / 45.3)		
K5.01	Indications of pump cavitation	2.7	2.8
K5.02	Jet pump operation: BWR-3,4,5,6		3.2
K5.03	Pump/motor cooling: Plant-Specific		2.7
K5.04	System venting		2.6
K5.05	End of cycle recirculation pump trip: Plant-Specific		3.6
K5.06	ATWS RPT: Plant-Specific	3.6	3.7
K5.07	Natural circulation: Plant-Specific	3.3	3.4
K5.08	E/P converters: Plant-Specific		2.1*
K5.09	Hydraulically operated valves: Plant-Specific		2.6*
K5.10	Motor generator set operation: Plant-Specific	2.8*	2.8
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the RECIRCULATION SYSTEM : $(CFR:\ 41.7/45.7)$		
K6.01	Jet pumps: Plant-Specific		3.7
K6.02	Component cooling water systems		3.2
K6.03	A.C. power: Plant-Specific		3.0
K6.04	D.C. power: Plant-Specific		2.8
K6.05	Control rod drive system: Plant-Specific	2.7	2.8
K6.06	Recirculation system motor-generator sets: Plant-Specific	3 1	3.1
K6.07	Feedwater flow		3.3
K6.08	Reactor water cleanup system		2.3
K6.09	Reactor water level		3.4

SYSTEM: 202001 Recirculation System

IZ/A NO	KNOWI EDGE	IMPORTANCE SPO	
K/A NO.	KNOWLEDGE	RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RECIRCULATION SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03	Recirculation pump flow: Plant-Specific	3.4	3.5 3.4 3.6
A1.04 A1.05	Reactor water level	3.3	3.3 3.9
A1.06	Reactor power Recirculation pump motor amps Recirculation pump motor amps	2.5	2.6
A1.07 A1.08 A1.09	Recirculation pump speed Recirculation FCV position: BWR-5,6 Recirculation pump seel pressures	3.7	2.8 3.7 3.3
A1.10 A1.11 A1.12	Recirculation pump seal pressures Recirculation seal purge flows Vessel bottom head drain temperature Recirculation pump differential pressure: Plant-	2.6	2.7 2.9
A1.13	Specific Recirculation loop temperatures: Plant-Specific		2.6 3.2
A1.14 A1.15	Recirculation drive motor temperature: Plant-Specific		2.4 2.4
A1.16 A1.17	Recirculation MG drive motor amps: Plant-Specific		2.3
	voltage: Plant-Specific	2.3*	2.3
A2.	Ability to (a) predict the impacts of the following on the RECIRCULATION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02	†Jet pump failure: Plant-Specific	3.7	3.9 3.9
A2.03 A2.04 A2.05	Single recirculation pump trip Multiple recirculation pump trip Inadvertent recirculation flow increase	3.7	3.7 3.8 4.0
A2.06 A2.07 A2.08	Inadvertent recirculation flow decrease Recirculation pump speed mismatch: Plant-Specific Recirculation flow mismatch: Plant-Specific	3.6 3.1	3.8 3.3 3.4
A2.09 A2.10 A2.11	Recirculation scoop tube lockup: Plant-Specific	3.5 3.7	3.4 3.9 3.9
A2.12 A2.13	Loss of reactor feedwater		3.8 2.8

SYSTEM: 202001 Recirculation System

****	IMPORTAN	
K/A NO.	KNOWLEDGE RO	SRO
A2.14	High reactor pressure (ATWS circuitry initiation):	
	Plant-Specific	4.2*
A2.15	End of cycle trip circuitry: Plant-Specific	3.9
A2.16	Loss of seal purge flow (CRD)	3.1
A2.17	Loss of seal cooling water	3.2
A2.18	Loss of motor cooling	3.1
A2.19	Loss of A.C. power: Plant-Specific	3.2
A2.20	Loss of D.C. power: Plant-Specific	2.9
A2.21	†Recirculation loop temperature out of spec: Plant-	
	Specific	3.7
A2.22	Loss of component cooling water	3.2
A2.23	Valve closures	3.2
A2.24	Valve opening	3.1
A2.25	Recirculation flow control valve lockup: Plant-	
	Specific	3.3
A2.26	Incomplete start sequence: Plant-Specific	3.1
A3.	Ability to monitor automatic operations of the	
110.	RECIRCULATION SYSTEM including:	
	(CFR: 41.7/45.7)	
	(CFR: 11.77 15.77)	
A3.01	Valve operation	3.1
A3.02	Pump/MG set start sequence: Plant-Specific	3.0
A3.03	System flow	3.2
A3.04	Lights and alarms	3.1
A3.05	Pump speed: Plant-Specific	2.9
A3.06	Flow control valve position: BWR-5,6	3.6
A3.07	Pump trips: Plant-Specific	3.3
A3.07 A3.08	Pump downshift: BWR-5,6	3.3
A3.09	MG set trip: Plant-Specific	3.3
A3.09	MO set trip. Frant-specific	3.3
A4.	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A 4 O1	Decimalation angula	2.7
A4.01	Recirculation pumps	3.7
A4.02	System valves	3.4
A4.03	Reactor power	4.1
A4.04	System flow	3.7
A4.05	Lights and alarms	3.3
A4.06	Oil pumps	2.7
A4.07	Vent fans: Plant-Specific	2.3
A4.08	Motor-generator sets: Plant-Specific	3.1
A4.09	Reactor water level	3.7
A4.10	Seal flow: Plant-Specific	2.8
A4.11	Seal pressures: Plant-Specific	3.3
A4.12	Core flow	3.8
A4.13	Core differential pressure	3.3

SYSTEM: 201005 Rod Control and Information System (RCIS)

TASK: Operate control rods using "single notch" mode Operate control rods using "notch override" Conduct "emergency rod in" control rod insertion Operate control rod drive system to bring the reactor critical Operate the control rod drive system manually at power Operate the control rod drive system to shutdown the reactor Conduct control rod operability test Conduct refueling interlocks functional test/control rod drive maintenance test Conduct CRD hydraulics valve testing during cold shutdown Conduct rod sequence control test Conduct rod sequence control integrity test Perform control rod drive stall flow testing (CRD 18-month accumulator operability test) Startup the rod position indication system Perform a position indication alignment during a reactor startup Monitor the rod position indication system Shutdown the rod position indication system (RPIS) **IMPORTANCE** K/A NO. KNOWLEDGE RO SRO K1. Knowledge of the physical connections and/or causeeffect relationships between ROD CONTROL AND **INFORMATION SYSTEM (RCIS) and the following:** (CFR: 41.2 to 41.9 / 45.7 to 45.8) K1.01 3.3 K1.023.5 K1.03 3.7 K1.04 3.7 K1.05 K1.06 3.3 K1.07 K2. Knowledge of electrical power supplies to the following: (CFR: 41.7) K2.01 2.6 K3. Knowledge of the effect that a loss or malfunction of the ROD CONTROL AND INFORMATION SYSTEM (RCIS) will have on following:

K3.01

K3.02

K3.03

K3.04

(CFR: 41.7 / 45.4)

3.7

3.5

3.2

3.3

SYSTEM: 201005 Rod Control and Information System (RCIS)

		IMPORTANCE		Ε
K/A NO.	KNOWLEDGE		RO	SRO
K4.	Knowledge of ROD CONTROL AND INFORMATION SYSTEM (RCI design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	S)		
K4.01	Limiting the effects of a control Rod accident: BWR-6		3.2	3.2
K4.02	Bank position withdrawal sequence (BPWS): BWR-6		3.3	3.3
K4.03	Rod withdrawal block signals: BWR-6		3.5	3.5
K4.04	Rod insertion block signals: BWR-6		3.5	3.5
K4.05	Rod withdrawal limiter: BWR-6			3.5
K4.06	Rod pattern controller rod blocks: BWR-6		3.5	3.5
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD CONTROL AND INFORMATION SYSTEM (RCIS): (CFR: 41.5 / 45.3)			
K5.01	†Rod pattern and program development: BWR-6		2.3	3.2
K5.02	Rod pattern controller (RPC): BWR-6		2.8	3.3
K5.03	Rod groups: BWR-6		2.3	2.7
K5.04	†Rod sequences: BWR-6			3.0
K5.05	Rod density: BWR-6			3.0
K5.06	Target rod pattern: BWR-6			2.8
K5.07	Low power alarm point: BWR-6			3.5
K5.08	Transition zone: BWR-6			3.5
K5.09	High power setpoints BWR-6			3.5
K5.10	Rod withdrawal limiter: BWR-6			3.3
K5.11	Control rod motion: BWR-6			3.3
K5.12	Command word generation and sequencing (operator			
	follow, scan and test): BWR-6		1.8*	2.2*
K5.13	Position indication probes: BWR-6			2.7
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the ROD CONTROL AND INFORMATION SYSTEM (RCIS): (CFR: 41.7 / 45.7)			
K6.01	First stage shell pressure or opening of a bypass			
	valve(s): BWR-6			3.2
K6.02	Rod position signal: BWR-6			3.3
K6.03	A.C. electrical power: BWR-6			2.8
K6.04	IRM channel: BWR-6		3.0	3.2
K6.05	SRM channel: BWR-6		3.0	3.2
K6.06	APRM channel: BWR-6		3.0	3.0

SYSTEM: 201005 Rod Control and Information System (RCIS)

K/A NO.	KNOWLEDGE	IMPORT		SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the ROD CONTROL AND INFORMATION SYSTEM (RCIS) controls including: (CFR: 41.5 / 45.5)			
A1.01	First stage shell pressure/turbine load: BWR-6		3.2	3.3
A2.	Ability to (a) predict the impacts of the following on the ROD CONTROL AND INFORMATION SYSTEM (RCIS); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)			
A2.01	High flow (CDM IDM ADDM), DWD 6		2.5	3.5
A2.01 A2.02	High flux (SRM, IRM, APRM): BWR-6			3.2
A2.02 A2.03	Insert block: BWR-6			3.2
A2.03 A2.04	Withdraw block: BWR-6			3.2
A2.04 A2.05				3.2
A2.06	Insert required: BWR-6			3.2
A2.00 A2.07	Withdraw inhibit: BWR-6			3.2
A2.07 A2.08				3.2
A2.08 A2.09	LPRM upscale/down scale: BWR-6			3.0
A2.09 A2.10	Data fault: BWR-6			
				3.0
A2.11	Accumulator fault: BWR-6			3.5
A2.12	Rod uncoupled: BWR-6			3.8
A2.13	Rod drift: BWR-6		3.8	3.8
A3.	Ability to monitor automatic operations of the ROD CONTROL AND INFORMATION System (RCIS) including: (CFR: 41.7 / 45.7)			
A3.01	Operator control module lights: BWR-6		3.5	3.5
A3.02	Rod display module lights: BWR-6			3.5
A3.03	†Verification of proper functioning/ operability:			
A 2 O 4	BWR-6 Annunciator and alarm signals: BWR-6			3.3
A3.04	Amuniciator and ararm signais: bwk-o		3.3	3.3
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)			
A4.01	Operator control module (lights and push buttons): BWR-6		3.7	3.7
A4.02	Rod display module (lights and push buttons): BWR-6			3.7
A4.03	Back panel indicating lights: BWR-6			3.3

TASK: Perform lineups on the standby liquid control system

Charge the standby liquid control tank

Place the standby liquid control system in standby readiness

Monitor the standby liquid control system

Inject poison solution into the reactor vessel

Purge the standby liquid control tank level indicator

Perform standby liquid control recirculation test

Perform standby liquid control relief valve test

Perform standby liquid control and demineralized water injection reactor vessel test

Perform standby liquid control explosive valve inspection

Perform standby liquid control component inoperable test

Per	Torin standby riquid control component moperable test	IMPORTANCE		
K/A NO.	KNOWLEDGE RO	SRO		
K1.	Knowledge of the physical connections and/or cause-effect relationships between STANDBY LIQUID CONTROL SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)			
K1.01	Core spray line break detection: Plant-Specific	3.3*		
K1.02	Core plate differential pressure indication	2.7		
K1.03	Plant air systems: Plant-Specific	2.6		
K1.04	Demineralized water/ condensate storage system	2.3*		
K1.05	RWCU	3.6		
K1.06	Reactor vessel	3.7		
K1.07	Jet pump differential pressure indication: Plant-	2.6		
K1.08	Specific	2.6		
K 1.00	indication	2.4*		
K1.09	Core spray system: Plant-Specific	3.4*		
K1.10	HPCI: Plant-Specific	3.0*		
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)			
K2.01	SBLC pumps	3.1*		
K2.02	Explosive valves	3.2*		
K2.03	Heater power	2.4*		
К3.	Knowledge of the effect that a loss or malfunction of the STANDBY LIQUID CONTROL SYSTEM will have on following: (CFR: 41.7 / 45.4)	2		
K3.01	†Ability to shutdown the reactor in certain conditions 4.3*	4.4*		
K3.02	Core spray line break detection system: Plant-			
	Specific	3.2*		
K3.03	Core plate differential pressure indication	2.7*		

K/A NO.	KNOWLEDGE IMPORTANCE RO	CE SRO
K3.04	Jet pump differential pressure indication: BWR-	2.5*
K3.05	3,4,5,6	2.5* 2.3*
	indication 2.3	2.3
K4.	Knowledge of STANDBY LIQUID CONTROL SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Zero leakage to the reactor (squib valves)	3.2
K4.02	Component and system testing	3.2
K4.03	Keeping sodium pentaborate in solution	3.9
K4.04	Indication of fault in explosive valve firing circuits	
		3.9
K4.05	Dispersal of boron upon injection into the vessel	3.6
K4.06	Core plate differential pressure indication	2.7
K4.07	RWCU isolation	3.9*
K4.08	System initiation upon operation of SBLC control switch	4.2*
K4.09	Dampening of positive displacement pump discharge	
	oscillations (accumulators): Plant-Specific	2.5*
K4.10	Over pressure protection	3.1
K5.	Knowledge of the operational implications of the following concepts as they apply to STANDBY LIQUID CONTROL SYSTEM: (CFR: 41.5 / 45.3)	
K5.01	Effects of the moderator temperature coefficient of	2.0
V5 02	reactivity on the boron	2.9
K5.02 K5.03	Chugging (as it pertains to boron mixing)	3.0 3.5
K5.03 K5.04	Explosive valve operation 3.1	3.3
K5.05	Accumulator operation: Plant-Specific	2.5
K5.06	Tank level measurement	3.2
K5.07	Tank heater operation 2.7	2.9
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the STANDBY LIQUID CONTROL SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Plant air systems: Plant-Specific	2.4*
K6.02	Demineralized water storage system	2.0*
K6.03	A.C. power	3.3
K6.04	Core spray system: Plant-Specific	2.8*
K6.05	HPCI system: Plant-Specific	2.7*

		IMPORTANCE	
K/A NO.	ABILITY	RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the STANDBY LIQUID CONTROL SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08 A1.09 A1.10	Tank level Explosive valve indication Pump discharge pressure Valve operations Pump amps: Plant-Specific Flow indication: Plant-Specific Reactor power RWCU system lineup SBLC system lineup Lights and alarms	3.8 3.6 3.6 2.7* 3.8 4.3* 3.7 4.0*	3.7 3.9 3.6 3.7 2.8* 3.9 4.4* 3.8 4.1 3.7
A2.	Ability to (a) predict the impacts of the following on the STANDBY LIQUID CONTROL SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08	Pump trip Failure of explosive valve to fire A.C. power failures Inadequate system flow Loss of SBLC tank heaters Valve openings Valve closures Failure to SCRAM	3.6 3.2 3.1* 3.1 3.1 3.9	3.8* 3.9* 3.4* 3.4* 3.3 3.2 4.2*
A3.	Ability to monitor automatic operations of the STANDBY LIQUID CONTROL SYSTEM including: (CFR: 41.7/45.7)		
A3.01 A3.02 A3.03 A3.04 A3.05 A3.06 A3.07 A3.08	Pump discharge pressure: Plant-Specific Tank level: Plant-Specific Explosive valves indicating lights: Plant-Specific Reactor power: Plant-Specific Flow indication: Plant-Specific RWCU system isolation: Plant-Specific Lights and alarms: Plant-Specific System initiation: Plant-Specific	3.9 3.8 4.3* 4.1* 4.0* 3.7	3.5 3.9 3.8 4.4* 4.2* 4.1* 3.6 4.2*

Tasks as noted previously

Ability to manually operate and/or monitor in the control room: (CFR: $41.7\,/\,45.5$ to 45.8)A4.

	IMPORTANO	ORTANCE	
K/A NO.	ABILITY RO	SRO	
A4.01	Tank level	3.9	
A4.02	SBLC control switch	4.2*	
A4.03	Explosive valves firing circuit status	4.1	
A4.04	Reactor power	4.6*	
A4.05	Flow indication: Plant-Specific	4.0	
A4.06	RWCU system isolation	3.9	
A4.07	Lights and alarms	3.6	
A4.08	System initiation: Plant-Specific	4.2*	

This page left blank

3.2	Reactor Water Inventory Control	page
206000	High Pressure Coolant Injection System	3.2-3
209002	High Pressure Core Spray System	3.2-8
209001	Low Pressure Core Spray System	3.2-12
256000	Reactor Condensate System	3.2-16
217000	Reactor Core Isolation Cooling System	3.2-21
259001	Reactor Feedwater System	3.2-25
204000	Reactor Water Cleanup System	3.2-29
259002	Reactor Water Level Control System	3.2-33
203000	Residual Heat Removal /Low Pressure Coolant Injection:	3.2-38
	Injection Mode (Plant Specific)	

This page left blank

TASK: Place the high pressure (Feedwater) coolant injection system (FWCI) in standby readiness

Monitor the high pressure (feedwater) coolant injection system operation

Return the high pressure (feedwater) coolant injection system to stand-by readiness after automatic initiation

Perform lineups of the high pressure coolant injection system (write in)

Manually initiate high pressure coolant injection

Perform high pressure coolant injection (HPCI) simulated automatic actuation test

Perform high pressure (feedwater) coolant injection flow rate test

Perform high pressure (feedwater) coolant injection (HPCI) pump operability test

Perform high pressure (feedwater) coolant injection motor operated valve operability test

Perform HPCI subsystem logic system functional test

Perform HPCI subsystem automatic isolation logic system functional test

Perform HPCI system inoperable test

Perform HPCI turbine overspeed test

Perform high pressure (feedwater) coolant injection operability test when reactor core isolation cooling is inoperable

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between HIGH PRESSURE COOLANT INJECTION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor vessel: BWR-2,3,4	3.9
K1.02	Reactor water level: BWR-2,3,4	4.1*
K1.03	Reactor pressure: BWR-2,3,4	3.8
K1.04	Reactor feedwater system: BWR-2,3,4	3.6
K1.05	Condensate storage system: BWR-2,3,4	3.7
K1.06	Suppression chamber: BWR-2,3,4	3.7
K1.07	D.C. power: BWR-2,3,4	3.8*
K1.08	A.C. power: BWR-2,3,4	3.1*
K1.09	ECCS keep fill system: BWR-2,3,4(P-Spec)	4.0
K1.10	Condensate storage and transfer system: BWR-2,3,4	3.4
K1.11	PCIS: BWR-2,3,4	3.5
K1.12	Nuclear boiler instrumentation: BWR-2,3,4	3.4
K1.13	Main condenser: BWR-2,3,4(P-Spec)	2.9*
K1.14	SBGT: BWR-2,3,4(P-Spec)	3.1
K1.15	Plant air systems: BWR-2,3,4	2.3*
K1.16	Containment/Torus pressure: BWR-2,3,4	3.5

	INFORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03 K2.04	System valves: BWR-2,3,4 System pumps: BWR-2,3,4 Initiation logic: BWR-2,3,4 Turbine control circuits: BWR-2,3,4	2.8*	3.3* 3.1* 2.9* 2.7*
К3.	Knowledge of the effect that a loss or malfunction of the HIGH PRESSURE COOLANT INJECTION SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03	Reactor water level control: BWR-2,3,4 Reactor pressure control: BWR-2,3,4 Suppression pool level control: BWR-2,3,4	3.8*	4.0 3.8* 3.5*
K4.	Knowledge of HIGH PRESSURE COOLANT INJECTION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Turbine trips: BWR-2,3,4	3.8	3.9
K4.02	System isolation: BWR-2,3,4		4.0
K4.03	Resetting turbine trips: BWR-2,3,4		4.1
K4.04	Resetting system isolations: BWR-2,3,4		3.9
K4.05	Preventing water hammer in turbine exhaust line		- 17
11.100	(procedural control): BWR-2,3,4	3.1	3.4
K4.06	Preventing water hammer in pump discharge line	5.1	5.1
111.00	(procedural control): BWR-2, 3, 4	3.2	3.4
K4.07	Automatic system initiation: BWR-2,3,4		4.3
K4.08	Manual system initiation: BWR-2,3,4		4.3
K4.09	Automatic flow control: BWR-2,3,4		3.9
K4.10	Surveillance for all operable components: BWR-2,3,4		3.8
K4.11	Turbine speed control: BWR-2,3,4		3.5
K4.12	Condensation of shaft sealing steam: BWR-2,3,4		3.0
K4.13	Turbine and pump lubrication: BWR-2,3,4		3.1
K4.14	Control oil to turbine speed controls: BWR-2,3,4		3.4
K4.15	Low speed turning of the turbine rotor: BWR-2,3,4(P-	5	5.1
111.10	Spec)	3.2	3.2
K4.16	Minimizing fission product concentration in the condensate storage tank (valve closures on system		3.2
	initiation): BWR-2,3,4(P-Spec)	3.1	3.3
K4.17	Protection against draining the condensate storage		
	tank to the suppression pool: BWR-2,3,4		3.4
K4.18	Pump minimum flow: BWR-2,3,4	3.2	3.3
K4.19	Automatic transfer of HPCI pump suction: BWR-2,3,4	3.7	3.8

K/A NO.	KNOWLEDGE	RO	SRO	
K5.	Knowledge of the operational implications of the following concepts as they apply to HIGH PRESSURE COOLANT INJECTION SYSTEM: (CFR: 41.5 / 45.3)			
K5.01 K5.02 K5.03 K5.04 K5.05 K5.06 K5.07 K5.08 K5.09	Turbine operation: BWR-2,3,4 Turbine shaft sealing: BWR-2,3,4 GEMAC controllers: BWR-2,3,4(P-Spec) Indications of pump cavitation: BWR-2,3,4 Turbine speed control: BWR-2,3,4 Turbine speed measurement: BWR-2,3,4 System venting: BWR-2,3,4 Vacuum breaker operation: BWR-2,3,4 Testable check valve operation: BWR-2,3,4 Assist core cooling: BWR-2,3,4	2.8 3.1 2.6* 3.3 2.6* 2.8 3.0 2.7*	3.4 2.9 3.1 2.7* 3.3 2.6 2.8 3.2 2.8 3.5	I
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the HIGH PRESSURE COOLANT INJECTION SYSTEM: (CFR: 41.7/45.7)			
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07 K6.08 K6.09 K6.10 K6.11	Plant air systems: BWR-2,3,4 D.C. power: BWR-2,3,4 A.C. power: BWR-2,3,4 Condensate storage tank level: BWR-2,3,4 Suppression pool level: BWR-2,3,4 SBGTS: BWR-2,3,4(P-Spec) ECCS keep fill system: BWR-2,3,4(P-Spec) Reactor pressure: BWR-2,3,4 Condensate storage and transfer system: BWR-2,3,4 PCIS: BWR-2,3,4 Nuclear boiler instrumentation: BWR-2,3,4 Reactor water level: BWR-2,3,4 ABILITY	3.3 2.9 3.5 3.5 3.1 3.4 3.8 3.5 3.8 3.5	2.3* 3.7* 3.1* 3.7 3.2 3.4 3.8 3.5 4.0 3.7 4.3*	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the HIGH PRESSURE COOLANT INJECTION SYSTEM controls including: (CFR: 41.5 / 45.5)			
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08	Reactor water level: BWR-2,3,4 Reactor pressure: BWR-2,3,4 Condensate storage tank level: BWR-2,3,4 Suppression pool level: BWR-2,3,4 Suppression pool temperature: BWR-2,3,4 System flow: BWR-2,3,4 System discharge pressure: BWR-2,3,4 System lineup: BWR-2,3,4	4.2* 3.5 3.7 4.1 3.8 3.7	4.4* 4.2 3.6 3.8 4.2 3.7 3.6 4.0	

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
A1.09	Turbine speed: BWR-2,3,4	3.4
A2.	Ability to (a) predict the impacts of the following on the HIGH PRESSURE COOLANT INJECTION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Turbing tring: DWD 2.2.4	4.0
	Turbine trips: BWR-2,3,4	
A2.02	Valve closures: BWR-2,3,4	3.5
A2.03	Valve openings: BWR-2,3,4	3.5
A2.04	A.C. failures: BWR-2,3,4	
A2.05	D.C. failures: BWR-2,3,4	3.8*
A2.06	Inadequate system flow: BWR-2,3,4	3.5
A2.07	Low suppression pool level: BWR-2,3,4	3.6
A2.08	†High suppression pool temperature: BWR-2,3,4	4.2
A2.09	†Low condensate storage tank level: BWR-2,3,4	3.7
A2.10		4.1
	System isolation: BWR-2,3,4	
A2.11	Low reactor water level: BWR-2,3,4	4.2
A2.12	Loss of room cooling: BWR-2,3,4	3.5
A2.13	Loss of applicable plant air systems: BWR-2,3,4	* 2.4*
A2.14	Flow controller failure: BWR-2,3,4	3.4
A2.15	Loss of control oil pressure: BWR-2,3,4	3.5
A2.16	High drywell pressure: BWR-2,3,4	4.1
A2.17	†HPCI inadvertent initiation: BWR-2,3,4	4.3*
A3.	Ability to monitor automatic operations of the HIGH PRESSURE COOLANT INJECTION SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Turbine speed: BWR-2,3,4	3.5
A3.02	System Flow: BWR-2,3,4	3.8
A3.03	System lineup: BWR-2,3,4	3.8
A3.04	Reactor pressure: BWR-2,3,4	
A3.05	Reactor water level: BWR-2,3,4	
A3.06	System discharge pressure: BWR-2,3,4	3.8
A3.07	Lights and alarms: BWR-2,3,4	3.8
A3.08	Condensate storage tank level: BWR-2,3,4	3.6
A3.09	Response to system isolation: BWR-2,3,4	* 4.1
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01 A4.02	Turbine speed controls: BWR-2,3,4	3.7 * 3.8
		2.0

Tasks as noted previously

E/A ORIM (CE		
K/A NO.	KNOWLEDGE RO	SRO
A4.03	Turbine temperatures: BWR-2,3,4	3.0
A4.04	Major system valves: BWR-2,3.4	3.7
A4.05	Reactor water level: BWR-2,3,4	4.4*
A4.06	Reactor pressure: BWR-2,3,4	4.3*
A4.07	Condensate storage tank level: BWR-2,3,4	3.5
A4.08	Suppression pool temperature: BWR-2,3,4	4.1
A4.09	Suppression pool level: BWR-2,3,4	3.7
A4.10	System pumps: BWR-2,3,4	3.5
A4.11	Turning gear: BWR-2,3,4(P-Spec)	3.0
A4.12	Turbine trip controls: BWR-2,3,4	3.9
A4.13	Turbine reset control: BWR-2,3,4	4.0
A4.14	System auto start control: BWR-2,3,4(P-Spec)	4.1

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

TASK: Perform lineups on the core spray system

Place core spray (CS) system in standby readiness

Monitor automatic operation of core spray system

Shutdown core spray cooling system

Perform core spray simulated automatic actuation test

Perform core spray pump operability test

Perform core spray system inop test

Conduct core spray - cold shutdown valve testing

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.05 K1.07 K1.08 K1.09 K1.10 K1.11 K1.12	Condensate transfer and storage system: BWR-5,6 Suppression Pool: BWR-5,6 Water leg (jockey) pump: BWR-5,6 HPCS diesel generator: BWR-5,6 Standby liquid control system: Plant-Specific Suppression pool cleanup system: BWR-5,6 ECCS room coolers: BWR-5,6 Component cooling water systems: BWR-5,6 Leak detection: BWR-5,6 Suppression pool suction strainers: BWR-5,6 Adequate core cooling: BWR-5,6 Reactor vessel: BWR-5,6 Instrument nitrogen: BWR-5,6 Plant air systems: BWR-5,6	. 3.5 . 3.0 . 3.8 . 2.8 . 2.0* . 2.4 . 2.4 . 2.5 . 2.1* . 3.8 . 3.4 . 2.7	3.4 3.5 3.0 3.8 2.8 2.0 2.4 2.6 2.5 2.1 4.0 3.6 2.7 2.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	. 2.0	2.0
K2.01 K2.02 K2.03	Pump electrical power: BWR-5,6 Valve electrical power: BWR-5,6 Initiation logic: BWR-5,6	. 2.8	3.3 2.9 2.9
K3.	Knowledge of the effect that a loss or malfunction of the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) will have on following: (CFR: 41.7/45.4)		
K3.01 K3.02 K3.03	Reactor water level: BWR-5,6	. 3.3	3.9 3.3 4.1

IMPORTANCE K/A NO. KNOWLEDGE RO SRO K4. **Knowledge of HIGH PRESSURE CORE SPRAY SYSTEM (HPCS)** design feature(s) and/or interlocks which provide for the following: (CFR: 41.7) K4.013.0 K4.02 3.5 K4.03 2.4 K4.04 2.3* K4.05 2.4 K4.06 2.4* K4.07 Override of reactor water level interlock: Plant-3.7 K5. Knowledge of the operational implications of the following concepts as they apply to HIGH PRESSURE CORE **SPRAY SYSTEM (HPCS):** (CFR: 41.5 / 45.3) K5.01 2.8 K5.02 2.7 K5.032.4 K5.04 4.0 K6. Knowledge of the effect that a loss or malfunction of the following will have on the HIGH PRESSURE CORE **SPRAY SYSTEM (HPCS):** (CFR: 41.7 / 45.7) K6.01 3.6 K6.02 3.4 K6.03 2.6 K6.04 Suppression pool suction strainer: BWR-5,6 2.5 2.5 **ABILITY** A1. Ability to predict and/or monitor changes in parameters associated with operating the HIGH PRESSURE **CORE SPRAY SYSTEM (HPCS) controls including:** (CFR: 41.5 / 45.5) A1.01 3.7 A1.023.6 A1.03 3.7 A1.04 3.3 A1.05 3.4 A1.06 2.3* A1.07 2.8 A1.08 3.3

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
A1.09	Condensate storage tank level: BWR-5,6	2.6	2.8
A2.	Ability to (a) predict the impacts of the following on the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08 A2.09 A2.10 A2.11 A2.12 A2.13 A2.14 A2.15	System initiation: BWR-5,6 Pump trips: BWR-5,6 Valve closures: BWR-5,6 A.C. electrical failure: BWR-5,6 D.C. electrical failure: BWR-5,6 Core spray line break: BWR-5,6 Pump seal failure: BWR-5,6 Inadequate system flow: BWR-5,6 Loss of room cooling: BWR-5,6 Valve openings: BWR-5,6 Low suppression pool level: BWR-5,6 High suppression pool level BWR-5,6 Low condensate storage tank level BWR-5,6 High suppression pool temperature: BWR-5,6 Clogged suppression pool suction strainers: BWR-5,6	3.6 3.2 3.1 2.8 3.4 2.6 3.1 2.4 2.7 3.3 3.3 3.4	3.8 3.7 3.4 3.2 2.9 3.6 3.0 3.2 2.6 3.5 3.5 3.5 3.5 3.5
A3.	Ability to monitor automatic operations of the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) including: (CFR: 41.7/45.7)		
A3.01 A3.02 A3.03 A3.04 A3.05 A3.06	Valve operation: BWR-5,6 Pump start: BWR-5,6 System pressure: BWR-5,6 System flow: BWR-5,6 Reactor water level BWR-5,6 Lights and alarms: BWR-5,6	3.8 3.6 3.7 3.7	3.3 3.8 3.6 3.7 3.7 2.8
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01 A4.02 A4.03 A4.04 A4.05	HPCS pump: BWR-5,6 Suction valves: BWR-5,6 Injection valve: BWR-5,6 Minimum flow valve: BWR-5,6 Manual Initiation controls: BWR-5,6	3.6 3.8 3.1	3.7 3.6 3.8 3.1 3.8

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A4.06	Testable check valve: BWR-5,6 2.6	2.6
A4.07	Line fill pump: BWR-5,6 2.8	2.8
A4.08	Reactor water level: BWR-5,6 3.6	3.7
A4.09	Suppression pool level: BWR-5,6 3.4	3.5
A4.10	Reactor pressure: BWR-5,6 3.3	3.3
A4.11	System flow: BWR-5,6 3.8	3.8
A4.12	System pressure: BWR-5,6	3.4
A4.13	Lights and alarms: BWR-5,6	2.6
A4.14	Test return valve: BWR-5,6	3.0
A4.15	Initiation reset: BWR-5,6	3.6

SYSTEM: 209001 Low Pressure Core Spray System

TASK: Fill the core spray systems

Perform lineups on the core spray systems

Place the core spray system in standby readiness

Monitor automatic operation of the core spray system

Shutdown the core spray cooling system

Fill the reactor cavity from the condensate storage tank with the core spray system

Perform core spray pump flow rate test

Perform core spray simulated automatic actuation test

Perform core spray pump operability test

Perform core spray subsys and low pressure coolant injection subsys discharge piping ventilation

Perform core spray system inop test

Conduct core spray motor operated valve operability test

	IVII ORTAINEE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause- effect relationships between LOW PRESSURE CORE SPRAY SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09 K1.10 K1.11 K1.12	Condensate storage tank: Plant-Specific 3.1 Torus/suppression pool 3.4 Keep fill system 2.9 condensate transfer system 2.3 Automatic depressurization system 3.7 Plant air systems 2.0* D.C. electrical power 2.5 A.C. electrical power 3.2 Nuclear boiler instrumentation 3.2 Emergency generator 3.7 Drywell coolers: Plant-Specific 2.4 ECCS room coolers 2.9 Leak detection 2.8 Reactor vessel 3.7	3.1 3.4 3.0 2.4 3.7 2.1* 2.7 3.3 3.4 3.8 2.6 3.1 3.0 3.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02 K2.03	Pump power 3.0* Valve power 2.5* Initiation logic 2.9*	3.1* 2.7* 3.1*

SYSTEM: 209001 Low Pressure Core Spray System

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the LOW PRESSURE CORE SPRAY SYSTEM will have on	
	following: (CFR: 41.7 / 45.4)	
K3.01	Reactor water level	3.9
K3.02	ADS logic	3.9
K3.03	Emergency generators	3.0
K3.04	Component cooling water systems	2.2
K3.05	Drywell cooling: Plant-Specific	2.7
K4.	Knowledge of LOW PRESSURE CORE SPRAY SYSTEM design	
	feature(s) and/or interlocks which provide for the	
	following:	
	(CFR: 41.7)	
K4.01	Prevention of overpressurization of core spray piping	3.4
K4.02	Prevents water hammer	3.2
K4.03	Motor cooling	2.5
K4.04	Line break detection	3.2
K4.05	Pump minimum flow	2.6
K4.06	Adequate pump net positive suction head	2.9
K4.07	Pump operability testing	3.0
K4.08	Automatic system initiation	4.0
K4.09	Load sequencing	3.5
K4.10	Testability of all operable components	2.9
K5.	Knowledge of the operational implications of the	
	following concepts as they apply to LOW PRESSURE CORE	
	SPRAY SYSTEM:	
	(CFR: 41.5 / 45.3)	
K5.01	Indications of pump cavitation	2.7
K5.02	Differential pressure indication	2.6
K5.03	Testable check valve operation	2.4
K5.04	Heat removal (transfer) mechanisms	2.9
K5.05	System venting	2.5
K5.06	Recirculation operation: Plant-Specific(BWR-1)	4.0
K6.	Knowledge of the effect that a loss or malfunction of	
	the following will have on the LOW PRESSURE CORE SPRAY	
	SYSTEM:	
	(CFR: 41.7 / 45.7)	
K6.01	A.C. power	3.4
K6.02	Emergency generators	3.9
K6.03	Torus/suppression pool water level	3.4

SYSTEM: 209001 Low Pressure Core Spray System

K/A NO. KNOWLEDGE K6.04 D.C. power K6.05 ECCS room cooler(s) K6.06 Pump motor cooler(s) K6.07 Pump seal cooler(s) K6.08 Keep fill system K6.09 Fire protection: BWR-1 K6.10 ECCS room integrity: Plant-Specific K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Pump trips	2.8 2.4 2.3 2.9 3.0* 2.3 3.6
K6.05 K6.06 Pump motor cooler(s) K6.07 Pump seal cooler(s) K6.08 Keep fill system K6.09 Fire protection: BWR-1 K6.10 ECCS room integrity: Plant-Specific K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	2.8 2.4 2.3 2.9 3.0* 2.3 3.6
K6.06 Pump motor cooler(s) K6.07 Pump seal cooler(s) K6.08 Keep fill system K6.09 Fire protection: BWR-1 K6.10 ECCS room integrity: Plant-Specific K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5/45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	2.4 2.3 2.9 3.0* 2.3 3.6
K6.07 Pump seal cooler(s) K6.08 Keep fill system K6.09 Fire protection: BWR-1 K6.10 ECCS room integrity: Plant-Specific K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5/45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	2.3 2.9 3.0* 2.3 3.6
K6.08 Keep fill system K6.09 Fire protection: BWR-1 K6.10 ECCS room integrity: Plant-Specific K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	2.9 3.0* 2.3 3.6
K6.09 K6.10 K6.10 K6.11 ECCS room integrity: Plant-Specific K6.11 ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	3.0* 2.3 3.6
K6.10 K6.11 ADS ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	2.3
ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	3.6
ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A1. Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	3.4
parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5/45.5) A1.01 Core spray flow A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	. 3.4
A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	. 3.4
A1.02 Core spray pressure A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	
A1.03 Reactor water level A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	3.2
A1.04 Reactor pressure A1.05 Torus/suppression pool water level A1.06 Motor amps A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	
A1.05 A1.06 A1.07 A1.07 Emergency generator loading A1.08 A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A1.06 Motor amps Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A1.07 Emergency generator loading A1.08 System lineup A2. Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	
A1.08 System lineup	
the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01 Pump trips	
	3.4
A2.02 Valve closures	
A2.03 A.C. failures	
A2.04 D.C. failures	
A2.05 Core spray line break	
A2.06 Inadequate system flow	
A2.07 Loss of room cooling	
A2.08 Valve openings	26
A2.09 Low suppression pool level	
A2.10 †High suppression pool temperature	3.1
A2.11 †Loss of fire protection: BWR-1	3.1

	IMPORTANCE	
K/A NO.	ABILITY RO	SRO
A3.	Ability to monitor automatic operations of the LOW	
	PRESSURE CORE SPRAY SYSTEM including:	
	(CFR: 41.7 / 45.7)	
A3.01	Valve operation	3.6
A3.02	Pump start	3.7
A3.03	System pressure	3.5
A3.04	System flow	3.6
A3.05	Reactor water level	3.9
A3.06	Lights and alarms	3.5
A4	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	Core spray pump	3.6
A4.02	Suction valves	3.4
A4.03	Injection valves	3.6
A4.04	Minimal flow valves	2.9
A4.05	Manual initiation controls	3.6
A4.06	Testable check valves	2.4
A4.07	Fill pump	2.8
A4.08	Reactor water level	3.9
A4.09	Suppression pool level	3.5
A4.10		3.8
A4.11	•	3.6
A4.12	System pressure	3.5
A4.13	v 1	3.4
A4.14	Containment level: BWR-1	3.6
A4.09 A4.10 A4.11 A4.12 A4.13	Suppression pool level3.6Reactor pressure3.9System flow3.7System pressure3.6Lights and alarms3.4	3.5 3.8 3.6 3.5 3.4

TASK: Perform lineups on condensate system

Fill the condensate storage tank

Deaerate condensate system prior to startup

Fill condenser hotwells

Fill the condenser system

Cleanup the condensate system

Startup the condensate systems

Operate condensate pumps in different combinations

Operate condensate booster pumps in different combinations

Operate hotwell pumps

Operate the hotwell dump and condensate transfer pump

Monitor condensate (and feedwater) system operation

Shut down the condensate system

Operate the low pressure heaters (operate the feedwater heaters)

Operate the low/intermediate pressure heaters

Operate the intermediate pressure heaters

Operate the feedwater heaters (write in)

Operate the condensate booster pumps forced lube oil pumps (write in)

What if hotwell level is high/low?

Perform lineups of the condenser air removal system

Monitor the condenser air removal system

Operate the mechanical vacuum pump(s)

Purge the offgas line

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR CONDENSATE SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Main turbine	2.6	2.6
K1.02	Reactor feedwater system	3.3	3.3
K1.03	HPCI: Plant-Specific	3.5	3.5
K1.04	RCIC: Plant-Specific	3.2	3.3
K1.05	CRD hydraulics system	3.1	3.1
K1.06	Extraction steam system	2.7	2.7
K1.07	SJAE condenser	2.9	2.9
K1.08	Gland seal steam condenser: Plant-Specific	2.7	2.7
K1.09	Offgas condenser: Plant-Specific	2.9	3.0
K1.10	Exhaust hood spray system		2.5
K1.11	Plant air systems: Plant-Specific		2.5
K1.12	Isolation condenser: Plant-Specific	3.3*	3.3*
K1.13	Reactor water level		3.5
K1.14	RHR (LPCI): Plant-Specific		3.0
K1.15	HPCS: Plant-Specific	3.6	3.6
K1.16	RWCU	2.6	2.6
K1.17	ECCS keep fill system: Plant-Specific	2.9*	2.9

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.18	Circulating water system	2.9	3.0
K1.19	Component cooling water (secondary equipment) systems:		
	Plant-Specific		2.7
K1.20	Demineralized water storage and makeup system		2.6
K1.21	Steam seal evaporator: Plant-Specific		2.4
K1.22	Offgas system		2.8
K1.23	Auxiliary steam system: Plant-Specific		2.5
K1.24	Radwaste system: Plant-Specific		2.4
K1.25	Main steam system: Plant-Specific	3.0	3.1
K2.	Knowledge of electrical power supplies to the following:		
	(CFR: 41.7)		
K2.01	System pumps	2.7*	2.8
K2.02	Motor operated valves		2.0*
K3.	Knowledge of the effect that a loss or malfunction of the REACTOR CONDENSATE SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01	Main turbine/main generator	3.2	3.2
K3.02	CRD hydraulics system		3.3
K3.03	Extraction steam system		2.6
K3.04	Reactor feedwater system		3.7
K3.05	HPCI: Plant-Specific		3.3
K3.06	RCIC: Plant-Specific		3.2
K3.07	Isolation condenser: Plant-Specific		3.0*
K3.08	SJAE		2.8
K3.09	Offgas		2.8
K3.10	Gland seal steam system: Plant-Specific		2.5
K3.11	Reactor water level		3.9
K3.12	HPCS: Plant-Specific		3.3
K3.13	Main steam system		3.3
K4.	Knowledge of REACTOR CONDENSATE SYSTEM design feature(s) and/or interlocks which provide for the following:		
	(CFR: 41.7)		
K4.01	Condensate and/or booster pump auto start: Plant-		
	Specific	3.4	3.4
K4.02	CRD pump suction		2.9
K4.03	Condensate and/or booster pump protection		2.8
K4.04	Maintenance of water quality		2.7
K4.05	Maintenance of 100% system flow if a feedwater string		
11.00	isolates: Plant-Specific	3.0	3.0

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K4.06	Control of extraction steam 2.8	2.8
K4.07	Cascading heater drains 2.4	2.4
K4.08	Dedicated ECCS water supply: Plant-Specific	3.6
K4.09	Initial main condenser vacuum	2.8
K4.10	Non-condensable gas removal	2.7
K4.11	Isolation of SJAE's on low flow: Plant-Specific	3.0
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR CONDENSATE SYSTEM: (CFR: 41.5 / 45.3)	
K5.01	System venting	2.5
K5.02	Water conductivity measurement	2.4
K5.03	Heat exchanger level operation	2.7
K5.04	Ion exchange process	2.1*
K5.05	Deaeration of condensate	2.2
K5.06	Air operated valve operation	2.4
K5.07	Level controller operation	2.7
K5.08	Heat removal (transfer) mechanisms	2.7
K5.09	Pump cavitation	2.6
K5.10	Air ejection operation	2.8
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR CONDENSATE SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Plant air systems	2.8
K6.02	Circulating water system	3.1
K6.03	Extraction steam system	2.9
K6.04	A.C. power	2.8
K6.05	Component cooling water systems	2.9
K6.06	Reactor feedwater system	3.3
K6.07	Demineralized water storage and makeup system	2.4
K6.08	Main turbine	2.9
K6.09	Offgas system	2.6
K6.10	Main steam system	2.9

****	IMPORTANCE	a n 0
K/A NO.	KNOWLEDGE RO	SRO
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR CONDENSATE SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	System flow	2.9
A1.02	Pump amps	2.3
A1.03	System pressure	2.8
A1.04	Hotwell level	2.9
A1.05	Condensate storage tank level	3.0
A1.06	Reactor water level	3.5
A1.07	System lineup	3.1
A1.08	System water quality	2.9
A1.09	Feedwater temperature	3.1
A1.10	Condenser vacuum	3.1
A2.	Ability to (a) predict the impacts of the following on the REACTOR CONDENSATE SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Pump trips	3.3
A2.02	Valve closures	2.9
A2.03	Valve openings	2.9
A2.04	A.C. power failures	3.0
A2.05	Inadequate system flow	2.9
A2.06	Low hotwell level	3.2
A2.07	High hotwell level	2.9
A2.08	High feedwater heater level	3.1
A2.09	Low feedwater heater level	2.8
A2.10	Main turbine trip	3.1
A2.11	Loss of circulating water system	3.2
A2.12	Loss of equipment component cooling water systems	3.1
A2.13	Loss of applicable plant air systems	3.0
A2.14	Low Condensate storage tank level	3.4
A2.15	Abnormal water quality	3.1
A2.16	High demineralizer differential pressure	2.8
A2.17	Feedwater heater string trip: Plant-Specific	2.9
A2.18	Loss of SIAE	2.9

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A3.	Ability to monitor automatic operations of the REACTOR CONDENSATE SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Valve operation	2.7
A3.02	Pump starts	2.9
A3.03	System pressure	2.9
A3.04	System flow	3.0
A3.05	Lights and alarms	2.9
A3.06	Hotwell level	2.9
A3.07	Feedwater heater level	2.9
A3.08	Feedwater temperature	3.1
A3.09	Feedwater heater drain tank level: Plant-Specific	2.9
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Hotwell condensate/ condensate booster pumps	3.3
A4.02	System motor operated valves	2.8
A4.03	Hotwell level controls	3.1
A4.04	Minimum flow valves	2.7
A4.05	System flow	3.1
A4.06	System pressure	3.0
A4.07	Lights and alarms	2.9
A4.08	Reactor water level	3.7
A4.09	System water quality	3.1
A4.10	Feedwater temperature	3.2
A4.11	Condensate storage tank level	3.4
A4.12	Feedwater heater level: Plant-Specific	3.0
A4.13	Condenser vacuum	3.4
A4.14	Feedwater heater drain tank level: Plant-Specific	2.7
A4.15	Air ejectors: Plant-Specific	3.0

TASK: Lineup the reactor core isolation cooling (RCIC) system

Manually operate and adjust reactor core isolation cooling system flow with the turbine governor

Manually initiate startup of the reactor core isolation cooling (RCIC) system

Operate RCIC pump in different modes

Monitor RCIC operation

Shutdown RCIC

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08	Condensate storage and transfer system Nuclear boiler system Suppression pool Main condenser Residual heat removal system Plant air systems: Plant-Specific Leak detection Line fill pump: Plant-Specific	3.5 3.6 2.6 2.6 2.3* 3.1	3.5 3.6 2.6 2.3* 3.2 3.4
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03 K2.04	Motor operated valves RCIC initiation signals (logic) RCIC flow controller Gland seal compressor (vacuum pump)	2.8*	2.8* 2.9* 2.8* 2.6*
K3.	Knowledge of the effect that a loss or malfunction of the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) will have on following: (CFR: 41.7/45.4)		
K3.01 K3.02 K3.03 K3.04	Reactor water level	3.6	3.7 3.6 3.5 3.6
K4.	Knowledge of REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02	Prevent water hammer: Plant-Specific		2.8 3.3

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K4.03	Prevents pump over heating	3.0
K4.04	Prevents turbine damage: Plant-Specific	3.1
K4.05	Prevents radioactivity release to auxiliary/reactor	
	building	3.5
K4.06	Manual initiation	3.5
K4.07	Alternate supplies of water	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR CORE ISOLATION COOLING SYSTEM (RCIC): (CFR: 41.5 / 45.3)	
K5.01	Indications of pump cavitation	2.6*
K5.02	Flow indication	3.1
K5.03	Differential pressure indication	2.6
K5.04	Testable check valve operation	2.7
K5.05	Centrifugal pump operation	
K5.06	Turbine operation	
K5.07	Assist core cooling	3.1
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC): (CFR: 41.7 / 45.7)	
K6.01	Electrical power	3.5
K6.02	Plant air systems	2.2*
K6.03	Suppression pool water supply	3.5
K6.04	Condensate storage and transfer system	3.5
	ABILITY	
Al.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) controls including: (CFR: 41.5 / 45.5)	
A1.01	RCIC flow	3.7
A1.02	RCIC pressure	3.3
A1.03	Reactor water level	4.0
A1.04	Reactor pressure	
A1.05	RCIC turbine speed	3.7
A1.06	Condensate storage tank level	3.3
A1.07	Suppression pool level	3.5
A1.08	Suppression pool temperature	3.6

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
A2.	Ability to (a) predict the impacts of the following on the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)		
A2.01	System initiation signal	. 3.8	3.7
A2.02	Turbine trips		3.7
A2.03	Valve closures		3.3
A2.04	A.C. power loss	. 2.3*	2.3*
A2.05	D.C. power loss		3.3
A2.06	Loss of applicable plant air systems		2.2*
A2.07	Loss of lube oil		3.1
A2.08	Loss of lube oil cooling		3.1
A2.09	Loss of vacuum pump		3.0
A2.10	Turbine control system failures		3.1
A2.11	Inadequate system flow		3.2
A2.12	Valve openings		3.0
A2.13	Loss of room cooling	. 2.9	3.0
A2.14	Rupture disc failure: Exhaust-Diaphragm	. 3.3	3.4
A2.15	Steam line break	. 3.8	3.8
A2.16	Low condensate storage tank level	. 3.5	3.4
A2.17	High suppression pool level	. 3.2	3.4
A2.18	Low suppression pool level	. 3.1	3.2
A2.19	High suppression pool temperature	. 3.5	3.6
A3.	Ability to monitor automatic operations of the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) including: (CFR: 41.7 / 45.7)		
A3.01	Valve operation	. 3.5	3.5
A3.02	Turbine startup	. 3.6	3.5
A3.03	System pressure	. 3.7	3.6
A3.04	System flow	. 3.6	3.5
A3.05	Reactor water level	. 3.9	3.9
A3.06	Lights and alarms	. 3.5	3.4
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	RCIC turbine speed	. 3.7	3.7
A4.02	Turbine trip throttle valve reset		3.9
A4.03	System valves		3.3
A4.04	Manually initiated controls		3.6

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
A4.05	Reactor water level	. 4.1	4.1
A4.06	Suppression pool level	. 3.6	3.7
A4.07	Reactor pressure	. 3.9	3.8
A4.08	System flow	. 3.7	3.6
A4.09	System pressure	. 3.7	3.6
A4.10	Lights and alarms	. 3.6	3.5
A4.11	Condensate storage tank level	. 3.5	3.5

SYSTEM: 259001 Reactor Feedwater System

TASK: Perform lineups on the reactor feedwater system

Fill the reactor feedwater system

Start a reactor feed pump

Monitor operation of a reactor feedwater pump

Secure a reactor feed pump

Operate feedwater manual/automatic transfer switch (for individual feed regulator valve)

Operate vessel level master control station

Operate feedwater low flow startup valve

Take local/manual control of feedwater regulating valves

Operate the reactor feed pump seal injection system

Secure the reactor feedwater system

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR FEEDWATER SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor vessel	3.7
K1.02	HPCI: Plant-Specific	3.8
K1.03	RWCU 2.7	2.9
K1.04	Extraction steam system	2.9
K1.05	Condensate system	3.2
K1.06	Plant air systems	3.0
K1.07	A.C. electrical power	2.9
K1.08	Reactor water level control system	3.7
K1.09	Reactor water level	3.8
K1.10	Component cooling water systems	2.7
K1.11	RFP lube oil system	2.7
K1.12	RFP turbine seal steam system: TDRFP's-Only	2.6
K1.13	Main turbine generator: Plant-Specific	2.5
K1.14	RCIC: Plant-Specific	3.1
K1.15	RHR: Plant-Specific	3.1
K1.16	Recirculation	3.1
K1.17	Heater drains: Plant-Specific	2.4
K1.18	Fire protection system (emergency cooling): Plant-	
	Specific	2.6
K1.19	†Redundant reactivity control system: Plant-Specific	3.3*
K1.20	Main steam system: TDRFPs-Only	3.2
K1.21	D.C. electric power	2.5
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Reactor feedwater pump(s): Motor-Driven-Only	3.3
K2.02	System motor operated valves	2.2*

SYSTEM: 259001 Reactor Feedwater System

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K2.03	RFP auxiliary oil pumps	2.4
К3.	Knowledge of the effect that a loss or malfunction of the REACTOR FEEDWATER SYSTEM will have on following: (CFR: 41.7 / 45.4)	
K3.01 K3.02 K3.03 K3.04 K3.05 K3.06 K3.07 K3.08 K3.09 K3.10 K3.11	Reactor water level 3.9 Reactor water level control system 3.8 HPCI: Plant-Specific 3.3 RWCU 2.5 Recirculation pump NPSH 2.9 Core inlet subcooling 3.1 Condensate system 3.0 RCIC 2.9 Extraction steam system 2.5 HPCS: Plant-Specific 3.2* RHR: Plant-Specific 3.3* Reactor power 3.8	3.9 3.8 3.3 2.5 2.9 3.1 3.0 2.9 2.6 3.2* 3.3* 3.9
K4.	Knowledge of REACTOR FEEDWATER SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06 K4.07 K4.08 K4.09	Auto start of the RFP's: Plant-Specific 3.8 Feedwater heating 2.8 RFP minimum flow 2.7 Dispersal of feedwater in the reactor vessel 2.5 RFP protection 2.7 RFP lubrication 2.5 RFP motor cooling: Motor-Driven-Only 2.5 RFP turbine seals: TDRFP's-Only 2.3 System isolation from the reactor vessel (check valves, double valve isolation inside/ outside containment) 3.2	4.0 2.9 2.7 2.6 2.8 2.6 2.6 2.4
K4.10 K4.11	Feedpump runbacks: Plant-Specific 3.1 Recirculation runbacks: Plant-Specific 3.5	3.4 3.5
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR FEEDWATER SYSTEM: (CFR: 41.5 / 45.3)	
K5.01 K5.02 K5.03	System venting2.4*Water hammer2.5Turbine operation: TDRFP's-Only2.8	2.4 2.5 2.8

SYSTEM: 259001 Reactor Feedwater System

K/A NO.	IMPORTANCE KNOWLEDGE RO) SRO
MA NO.	KNOWLEDGE) SKO
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR FEEDWATER SYSTEM: (CFR: 41.7/45.7)	
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07 K6.08	Plant air systems 3.0 Condensate system 3.3 A.C. electrical power 2.9 Extraction steam 2.8 Component cooling water systems 2.7 Plant service water 2.7 Reactor water level control system 3.8 Reactor feedwater pump motor ventilation: Motor-	3.4 3.1 3.2.9 7 2.7 7 2.7
K6.09 K6.10 K6.11 K6.12 K6.13 K6.14	Driven-Only 2.7 Reactor feedwater pump lube oil system 2.8 RFP turbine seal system: TDRFP's-Only 2.5 Main steam: TDRFP's-Only 2.6 D.C. electrical power 2.7 †Redundant reactivity control: Plant-Specific 3.6 Heater drains: Plant-Specific 2.5	3 2.9 5 2.5 8 2.8 3 2.4 0 3.3*
A1.	ABILITY Ability to predict and/or monitor changes in parameters associated with operating the REACTOR FEEDWATER SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01 A1.02 A1.03 A1.04 A1.05	Feedwater flow/pressure 3. Feedwater inlet temperature 3. RFP motor amps: Motor-Driven-Only 2. RFP turbine speed: Turbine-Driven-Only 2. RFP turbine control valve position: Turbine-Driven-Only 2. Feedwater heater level 2.	2 3.3 8 2.8 8 2.7 8 2.7
A2.	Ability to (a) predict the impacts of the following on the REACTOR FEEDWATER SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01 A2.02 A2.03 A2.04	Pump trip3.Feedwater heater isolation3.Loss of condensate pump(s)3.Loss of extraction steam3.	1 3.3 6 3.6

SYSTEM: 259001 Reactor Feedwater System

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
A 2 05	Loss of applicable plant sin systems	3.0	3.0
A2.05 A2.06	Loss of applicable plant air systems	3.0	3.0
A2.00 A2.07	Loss of A.C. electrical power		3.8
A2.07 A2.08	Reactor water level control system malfunctions		2.6
A2.09	†TDRFP steam inlet pressure flow: Plant-Specific		2.7
A2.09	TDRFF steam fillet pressure flow. Flam-specific	. 2.0	2.7
A3.	Ability to monitor automatic operations of the REACTOR FEEDWATER SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	RFP auto start: Plant-Specific	3 3	3.5
A3.02	Motor amps: Motor-Driven-Only		2.5
A3.03	System flow		3.2
A3.04	Reactor water level		3.7
A3.05	Feedwater inlet temperature		3.2
A3.06	Pump discharge pressure		3.1
A3.07	FWRV position		3.2
A3.08	Turbine speed: TDRFP'S-Only		2.7
A3.09	Lights and alarms		3.0
A3.10	Pump trips		3.4
A3.11	Reactor feedpump runbacks: Plant-Specific		3.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	System flow	. 3.6	3.5
A4.02	Manually start/control a RFP/TDRFP		3.7
A4.03	Feedwater heater/drain controls	. 2.9	3.0
A4.04	System valves	. 3.1	2.9
A4.05	Reactor water level	. 4.0	3.9
A4.06	Feedwater inlet temperature	. 3.4	3.5
A4.07	Pump discharge pressure	. 3.3	3.2
A4.08	FWRV position	. 3.3	3.3

TASK: Perform lineups on the reactor water cleanup system

Startup the reactor cleanup system

Operate the reactor cleanup system while reducing reactor pressure

Place the reactor water cleanup system in operation with the reactor at rated pressure

Remove the reactor cleanup (RWCU) system from service with the reactor at rated pressure

Return drained system to service with the reactor at rated pressure

Route primary system water to the main condenser hotwell

Operate the reactor cleanup system to conduct blowdowns

Route primary system water to radwaste

Drain the reactor cavity and equipment pool to the hotwell via the reactor cleanup system

Monitor the reactor water cleanup system (write in)

Place the reactor water cleanup system in operation with the

()reactor at rated temperature (write in)

Remove the reactor cleanup system from service with the reactor at rated temperature (write in)

Return drained system to service with the reactor at rated temperature (write in)

Perform reactor cleanup simulated automatic actuation test

Perform reactor cleanup isolation logic system functional test

Conduct reactor cleanup valve testing

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR WATER CLEANUP SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Reactor vessel	3.1	3.3
K1.02	Recirculation system: Plant-Specific	2.9	3.0
K1.03	Reactor feedwater system	3.1	3.1
K1.04	Component cooling water systems	2.9	2.9
K1.05	Plant air systems		2.7
K1.06	Main condenser		2.8
K1.07	Radwaste	2.6	2.7
K1.08	SBLC	3.7	3.8
K1.09	Reactor water level	3.2	3.3
K1.10	Reactor water quality	3.3	3.5
K1.11	PCIS/NSSSS		3.7
K1.12	Condensate storage and transfer system: Plant-		
	Specific	2.6	2.6
K1.13	RHR system: Plant-Specific	2.5	2.5
K1.14	Process sample system		2.5
K1.15	Leak detection: Plant-Specific		3.2
K1.16	CRD system: Plant-Specific		2.8

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02	Pumps		2.4* 2.1*
К3.	Knowledge of the effect that a loss or malfunction of the REACTOR WATER CLEANUP SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04 K3.05 K3.06 K3.07 K3.08	Reactor water quality Reactor water level Component cooling water systems Reactor water temperature Area temperature Area radiation levels Drywell temperature Drywell pressure	. 3.1 . 2.4 . 2.6 . 2.4* . 2.6 . 2.1*	3.6 3.1 2.4 2.6 2.4* 2.7 2.2* 2.3*
K4.	Knowledge of REACTOR WATER CLEANUP SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06	Pump protection Piping over-pressurization protection: Plant-Specific Over temperature protection for system components System isolation upon-receipt of isolation signals Double valve isolation from the reactor Maximize plant efficiency (use of regenerative heat	. 2.7 . 2.9 . 3.5 . 3.0	2.5 2.9 2.9 3.6 3.1
K4.07 K4.08	exchanger) Draining of reactor water to various locations Reducing reactor pressure upstream of low pressure piping: LP-RWCU	. 2.9	2.82.93.4
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR WATER CLEANUP SYSTEM: (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03 K5.04 K5.05	Electro/ pneumatic converter operation Control device operation Demineralizer operation Heat exchanger operation Flow controllers	. 2.2* . 2.4 . 2.7	2.1* 2.2* 2.5 2.7 2.6

K/A NO.	IMPORTANCE KNOWLEDGE RO	SRO
K5.06	Pressure controllers	2.6
K5.07	Conductivity measurement	2.6
K5.08	Temperature measurement	2.6
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR WATER CLEANUP SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Component cooling water systems	3.3
K6.02	Main condenser	2.4
K6.03	Radwaste	2.4
K6.04	Plant air systems	2.8
K6.05	A. C. power	2.6
K6.06	Reactor feedwater system	2.4*
K6.07	SBLC logic	3.5
K6.08	PCIS/NSSSS	3.5
K6.09	CRD hydraulics: Plant-Specific	2.9
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR WATER CLEANUP SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	Reactor water level	3.2
A1.02	Component cooling water temperature 2.9	2.9
A1.03	Reactor water temperature	2.9
A1.04	System flow	2.8
A1.05	System pressure	2.6
A1.06	System temperature	2.8
A1.07	RWCU drain flow	2.9
A1.08	Main condenser hotwell level	2.3
A1.09	Reactor water conductivity	3.2
A2.	Ability to (a) predict the impacts of the following on the REACTOR WATER CLEANUP SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Loss of component cooling water 3.2	3.4
A2.02	Pressure control valve failure: LP-RWCU	3.2
A2.03	Flow control valve failure	2.9
A2.04	Pump trips	2.9

Tasks as noted previously

IMPORTANCE K/A NO. **ABILITY** RO SRO A2.05 2.8 A2.06 2.6 A2.07 2.6 A2.08 RWCU pump seal failure 2.9 3.1 A2.09 2.8 A2.10 2.8 A2.11 2.7 A2.12 2.8 A2.13 3.4 A2.14 3.2 A2.15 2.9 Ability to monitor automatic operations of the REACTOR A3. WATER CLEANUP SYSTEM including: (CFR: 41.7 / 45.7) A3.01 System pressure downstream of the pressure regulating 3.3 A3.02 3.2 A3.03 3.6 A3.04 Response to interlocks and trips designed to protect 3.5 A3.05 2.8 A3.06 3.1 A4. Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) A4.01 3.0 A4.02 2.9 A4.03 3.1 A4.04 2.8 A4.05 2.8 A4.06 2.9 A4.07 3.1 A4.08 3.4

A4.09

2.9

SYSTEM: 259002 Reactor Water Level Control System

TASK: Operate feedwater manual/automatic transfer switch (for individual feed regulator valve)

Operate vessel level master control station

Operate feedwater low flow startup valve

Place the high pressure (feedwater) coolant injection system (FWCI) in standby readiness

Monitor the high pressure (feedwater) coolant injection system operation

Return the high pressure (feedwater) coolant injection system to standby readiness after automatic initiation

Perform high pressure (feedwater) coolant injection operability test when reactor core isolation coolant is inoperable

	IMORIANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR WATER LEVEL CONTROL SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	RPS	3.9
K1.02	Main steam flow	3.3
K1.03	Reactor water level 3.8	3.9
K1.04	Reactor feedwater flow	3.6
K1.05	Reactor feedwater system	3.7
K1.06	Plant air systems	3.1
K1.07	Rod worth minimizer: Plant-Specific	2.7
K1.08	Recirculation system: Plant-Specific	3.2
K1.09	P sat/T sat (compensation)	3.0
K1.10	Emergency generator(s): FWCI/HPCI	3.0
K1.11	Drywell pressure: FWCI/HPCI	3.2
K1.12	Emergency condensate transfer pump: FWCI/HPCI	2.6*
K1.13	Condensate system	3.2
K1.14	Main turbine	3.0
K1.15	Recirculation flow control system	3.2
K1.16	HPCI: Plant-Specific	3.5
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02	Reactor water level control system circuits	2.7
	FWCI/HPCI	3.5*

SYSTEM: 259002 Reactor Water Level Control System

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the REACTOR WATER LEVEL CONTROL SYSTEM will have on following: (CFR: 41.7 / 45.4) (CFR: 41.7 / 45.5 to 45.8)	
K3.01 K3.02 K3.03 K3.04 K3.05 K3.06 K3.07	Reactor water level3.8Reactor feedwater system3.7Rod worth minimizer: Plant-Specific2.7Recirculation system: Plant-Specific2.9Recirculation flow control system2.8Main turbine2.8Reactor water level indication3.4*	3.8 3.7 2.9 3.0 2.9 2.8 3.4
K4.	Knowledge of REACTOR WATER LEVEL CONTROL SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Ensuring adequate NPSH for recirculation pumps:	
	Plant-Specific	3.1
K4.02	Bypassing of the RWM: Plant-Specific	3.0
K4.03	Reactor feedpump runout protection: MDFP	2.8
K4.04	Reactor water level setpoint setdown following a reactor scram	2.9
K4.05	P sat/T sat (compensation)	2.9
K4.06	Control signal failure	3.2
K4.07	TDRFP 20% power interlock: TDRFP	3.3
K4.08	TDRFP speed control: TDRFP	3.0
K4.09	Single element control (reactor water level provides	
	the only input)	3.1
K4.10	Three element control (main steam flow, reactor	
	feedwater flow and reactor water level provide input)	3.4
K4.11	DP control: Plant-Specific	3.3
K4.12	Manual and automatic control of the system	3.4
K4.13	FWRV lockup	3.6
K4.14	Selection of various instruments to provide reactor	
	water level input 3.4	3.4
K4.15	Automatic initiation of the feedwater system upon	
	receipt of an ECCS initiation signal: FWCI/HPCI	4.5*
K4.16	Dedication of feedwater string(s) to ECCS: FWCI/HPCI	4.5*
K4.17	Simultaneous Manual and Auto operation of the system	
	(i.e. 1 FP in Auto, 1 FP in Manual)	3.0

SYSTEM: 259002 Reactor Water Level Control System

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR WATER LEVEL CONTROL SYSTEM: (CFR: 41.5 / 45.3)	
K5.01	GEMAC/Foxboro/Bailey controller operation: Plant-Specific	3.1
K5.02	Electro/ Pneumatic converter operation	2.4
K5.03	Water level measurement	3.2
K5.04	Moisture carryover	2.3
K5.05	Moisture carryunder	2.3
K5.06	Pump runout	2.4
K5.07	Turbine speed control mechanisms: TDRFP	2.7
K5.08	Heat removal mechanisms: FWCI	3.8
K5.09	†Adequate core cooling: FWCI	4.2*
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR WATER LEVEL CONTROL SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Plant air systems	3.2
K6.02	A.C. power	3.4
K6.03	Main steam flow input	3.1
K6.04	Reactor feedwater flow input	3.1
K6.05	Reactor water level input	3.5
K6.06	Reactor pressure/temperature input (for water level	0.7
17.6.07	input compensation)	2.7
K6.07	Drywell pressure input: FWCI	3.0*
K6.08	Loss of dP across startup level control bypass valve: Plant-Specific	2.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR WATER LEVEL CONTROL SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	Reactor water level	3.8
A1.02	Reactor feedwater flow	3.5
A1.03	Reactor power	3.8
A1.04	Reactor water level control controller indications	3.6
A1.05	FWRV/startup level control position: Plant-Specific 2.9	2.9
A1.06	Feedwater string(s) selected for FWCI: FWCI	3.3*
A1.07	TDRFP speed: TDRFP	2.6

	K/A NO.	KNOWLEDGE	RO	SRO
	MA NO.	KNOWLEDGE	KO	SKO
	A2.	Ability to (a) predict the impacts of the followin the REACTOR WATER LEVEL CONTROL SYS on those predictions, use procedures to correct,		
		control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
	A2.01	Loss of any number of main steam flow inputs	3.3	3.4
	A2.02	Loss of any number of reactor feedwater flow inputs	3	3.4
	A2.03	Loss of reactor water level input		
	A2.04	RFP runout condition: Plant-Specific		
	A2.05	Loss of applicable plant air systems		
	A2.06	Loss of controller signal output		
	A2.07	Loss of comparator bias signal		
	A2.08	Receipt of an ECCS initiation signal: FWCI		
	A2.09	FWCI system failure alarm: FWCI	4.0	4.0
	A3.	Ability to monitor automatic operations of the R		
		WATER LEVEL CONTROL SYSTEM including: (CFR: 41.7 / 45.7)		
l	A3.01	Runout flow control: Plant-Specific		* 3.0*
•	A3.02	Changes in reactor water level		3.4
	A3.03	Changes in main steam flow	3.2	3.2
	A3.04	Changes in reactor feedwater flow		3.2
	A3.05 A3.06	Changes in reactor power		3.4
	113.00	reactor scram: Plant-Specific	3.0	3.0
	A3.07	FWRV lockup		
	A3.08	FWCI system initiation: FWCI		
	A3.09	Transfer of system from flow control to level control		4.0
ı	113.07	mode: FWCI		* 4.3
I	A3.10	TDRFP lockup: TDRFP		
		•		
	A4.	Ability to manually operate and/or monitor in th control room:	e	
		(CFR: 41.7 / 45.5 to 45.8)		
	A4.01	All individual component controllers in the manual		
		mode		3.6
	A4.02	All individual component controllers in the automati mode		3.6
	A4.03	All individual component controllers when transferri		3.0
	117.03	from manual to automatic modes	C	3.6
	A4.04	FWRV lockup reset controls		
	A4.05	Runout flow control reset controls: Plant-Specific		
	A4.06	DP/Single/three element control selector switch:		5.5
	111100	Plant-Specific	31	3.2
		Tame operate		5.2

K/A NO.	KNOWLEDGE	RO	SRO	
A4.07	All individual component controllers when transferring			
	from automatic to manual mode	3.8	3.6	
A4.08	Manually initiate FWCI: FWCI	4.5*	4.5*	
A4.09	TDRFP lockout reset: TDRFP	3.4	3.1	
A4.10	Setpoint setdown reset controls: Plant-Specific	3.1	2.9	
A4.11	High level lockout reset controls: Plant-Specific	3.5	3.3	

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

TASK: Perform lineups on the low pressure coolant injection system

Place the low pressure coolant injection system in standby readiness

Monitor operational sequence of low pressure coolant injection (LPCI) system

Secure the low pressure coolant injection system

Perform LPCI subsystem logic system functional test

Perform LPCI mode inoperable test

Perform LPCI mov power supply simulated auto. act test and battery serv. tests

Conduct LPCI independent power supply weekly battery test

Conduct LPCI independent power supply performance discharge test

Perform low pressure coolant injection sound analysis and flow test (write in)

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Condensate storage and transfer system: Plant-Specific	. 2.8	2.8
K1.02	Suppression pool		3.9
K1.03	Condensate transfer		2.6*
K1.04	Keep fill system		3.4
K1.05	Recirculation system: BWR-3,4		3.8
K1.06	Automatic depressurization		3.9
K1.07	D.C. electrical power		3.3
K1.08	A.C. electrical power		3.5
K1.09	Emergency generators		3.8
K1.10	ECCS room coolers	. 3.2	3.2
K1.11	Nuclear boiler instrumentation	. 3.7	3.7
K1.12	Plant air systems: Plant-Specific	. 2.6*	2.7*
K1.13	Drywell pressure	. 3.9	4.0
K1.14	Shutdown cooling system: Plant-Specific	. 3.6	3.7
K1.15	Reactor building drain system: Plant-Specific		2.6
K1.16	Component cooling water systems	. 3.1	3.2
K1.17	Reactor pressure		4.0
K1.18	Reactor vessel: Plant-Specific		3.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Pumps	. 3.5*	3.5*
K2.02	Valves		2.7*
K2.03	Initiation logic		2.9*

SYSTEM 203000 RHR/LPCI: Injection Mode (Plant Specific)

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) will have on following: (CFR: 41.7 / 45.4)	
K3.01 K3.02 K3.03 K3.04	Reactor water level4.3*Suppression pool level3.5Automatic depressurization logic4.2*Adequate core cooling4.6*	4.4* 3.5 4.3* 4.6*
K4.	Knowledge of RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Automatic system initiation/injection	4.2
K4.02	Prevention of piping overpressurization	3.4
K4.03	Pump minimum flow protection	3.3
K4.04	Pump motor cooling: Plant-Specific	2.7
K4.05	Prevention of water hammer	3.3
K4.06	Adequate pump net positive suction head (interlock	3.5
K4.07	suction valve open): Plant-Specific	3.5 3.9
K4.07 K4.08	Emergency generator load sequencing	3.9 .4*
K4.09	Pump operability testing	3.4
K4.10	Dedicated injection system during automatic system	3.4
K4.10	initiation (injection valve interlocks)	4.1
K4.11	Loop selection logic: Plant-Specific	4.1
K4.11 K4.12	System redundancy	3.6
K4.12 K4.13	The prevention of leakage to the environment through	
	LPCI/RHR heat exchanger: Plant-Specific	3.7
K4.14	†Operation from remote shutdown panel	3.7
K4.15	Pump runout protection: Plant-Specific	2.5
K5.	Knowledge of the operational implications of the following concepts as they apply to RHR/LPCI: INJECTION MODE (PLANT SPECIFIC): (CFR: 41.5 / 45.3)	
K5.01	Testable check valve operation	2.9
K5.02	†Core cooling methods	3.7
	-	

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

		IMPORTANCE	
	K/A NO.	KNOWLEDGE RO	SRO
	K6.	Knowledge of the effect that a loss or malfunction of the following will have on the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC): (CFR: 41.7 / 45.7)	
	K6.01	A.C. electrical power	3.7
	K6.02	D.C. electrical power	3.0*
	K6.03	Emergency generator	3.9
	K6.04	Keep fill system	3.5
	K6.05	Condensate storage and transfer system: Plant-Specific	2.5
l	K6.06	Suppression pool	3.9
ı	K6.07	Plant air systems: Plant-Specific	2.7
	K6.08	ECCS room cooling	3.1
	K6.09	Nuclear boiler instrumentation	3.4
	K6.10	Component cooling water systems	3.1
l	K6.11	ADS	4.1
!	K6.12	†ECCS room integrity	2.9
		ABILITY	
	A1.	Ability to predict and/or monitor changes in parameters associated with operating the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) controls including: (CFR: 41.5 / 45.5)	
l	A1.01	Reactor water level	4.3*
	A1.02	Reactor pressure	4.0*
•	A1.03	System flow	3.7
	A1.04	System pressure	3.6
	A1.05	Suppression pool level	3.7
	A1.06	Condensate storage tank level: Plant-Specific	2.5*
	A1.07	Motor amps: Plant-Specific	2.5*
•	A1.08	†Emergency generator loading	3.8
	A1.09	Component cooling water systems	2.9
	A2.	Ability to (a) predict the impacts of the following on the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
	A2.01	Inadequate net positive suction head	3.4
	A2.02	Pump trips	3.5
	A2.03	Valve closures	3.3
	A2.04	A.C. failures	3.6
	A2.05	D.C. failures	3.2

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
A2.06	Emergency generator failure	3.9
A2.07	Pump seal failure	3.1
A2.08	Inadequate room cooling	3.0
A2.09	Inadequate system flow	3.4
A2.10	Nuclear boiler instrument failures	3.5
A2.11	Motor operated valve failures	3.6
A2.12	Pump runout	2.7*
A2.13	Valve openings	3.3
A2.14	Initiating logic failure	3.9*
A2.15	Loop selection logic failure: Plant-Specific	4.2*
A2.16	Loss of coolant accident	4.5*
A2.17	Keep fill system failure	3.5
A3.	Ability to monitor automatic operations of the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) including: (CFR: 41.7 / 45.7)	
A3.01	Valve operation	3.7
A3.02	Pump start	3.9
A3.03	Pump discharge pressure	3.6
A3.04	System flow	3.7
A3.05	Reactor water level	4.4*
A3.06	Indicating lights and alarms	3.6
A3.07	Loop selection: Plant-Specific	4.6*
A3.08	System initiation sequence	4.1
A3.09	Emergency generator load sequencing	3.9*
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Pumps	4.1*
A4.02	System valves	4.1*
A4.03	Keep fill system	3.4
A4.04	Heat exchanger cooling flow	3.6
A4.05	Manual initiation controls	4.1*
A4.06	System reset following automatic initiation: Plant-Specific	3.9
A4.07	Reactor water level	4.5*
A4.08	Reactor pressure	4.3*
A4.09	System flow	4.0
A4.10	Pump/system discharge pressure: Plant-Specific	3.6
A4.11	Indicating lights and alarms	3.5*
A4.12	Condensate storage tank level: Plant-Specific	2.6
A4.13	Suppression pool level/temperature	3.9
A4.14	Testable check valves	2.7*

3.3	Reactor Pressure Control	page
218000	Automatic Depressurization System	3.3-3
239001	Main and Reheat Steam System	3.3-6
241000	Reactor/Turbine Pressure Regulating System	3.3-11
239002	Safety Relief Valves	3.3-18

This page left blank

SYSTEM: 218000 Automatic Depressurization System

TASK: Monitor the automatic depressurization system (ADS)
Manually operate the automatic depressurization system

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between AUTOMATIC DEPRESSURIZATION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06	RHR/LPCI: Plant-Specific Low pressure core spray: Plant-Specific Nuclear boiler instrument system Drywell/containment pressure: Plant-Specific Remote shutdown system: Plant-Specific Safety/relief valves	. 4.0 . 3.7 . 3.9 . 3.9	4.1 4.1 3.8 4.2 3.9 3.9*
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	ADS logic	. 3.1*	3.3*
К3.	Knowledge of the effect that a loss or malfunction of the AUTOMATIC DEPRESSURIZATION SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01	Restoration of reactor water level after a break that	4 4*	4.4*
K3.02	does not depressurize the reactor when required		4.6*
K4.	Knowledge of AUTOMATIC DEPRESSURIZATION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Prevent inadvertent initiatior of ADS logic		3.9
K4.02 K4.03	Allows manual initiation of ADS logic		4.0 4.0
K4.04	Insures adequate air supply to ADS valves: Plant-Specific	. 3.5	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to AUTOMATIC DEPRESSURIZATION SYSTEM: (CFR: 41.5 / 45.3)		
K5.01	ADS logic operation	. 3.8	3.8

SYSTEM: 218000 Automatic Depressurization System

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the AUTOMATIC DEPRESSURIZATION SYSTEM: (CFR: 41.7/45.7)		
K6.01 K6.02	RHR/LPCI system pressure: Plant-Specific	. 3.9	4.1
	Specific		4.1
K6.03	Nuclear boiler instrument system (level indication)		3.9
K6.04	Air supply to ADS valves: Plant-Specific		3.7
K6.05 K6.06	A.C. power: Plant-Specific		3.1* 3.6*
K6.07	D.C. power: Plant-Specific		3.5
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the AUTOMATIC DEPRESSURIZATION SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	ADS valve tail pipe temperatures	. 3.4	3.6
A1.02	ADS valve acoustical monitor noise: Plant-Specific	. 3.7	4.0
A1.03	ADS valve Air supply pressure: Plant-Specific		3.4*
A1.04	Reactor pressure		4.2*
A1.05	Reactor water level		4.1
A1.06	Suppression pool temperature	. 4.1	4.3*
A2.	Ability to (a) predict the impacts of the following on the AUTOMATIC DEPRESSURIZATION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Small steam line break L0CA	. 4.1	4.3*
A2.02	Large break LOCA		3.6*
A2.03	Loss of air supply to ADS valves: Plant-Specific	. 3.4	3.6
A2.04	ADS failure to initiate		4.2*
A2.05	Loss of A.C. or D.C. power to ADS valves	. 3.4*	3.6*
A2.06	ADS initiation signals present	. 4.2	4.3*
A3.	Ability to monitor automatic operations of the AUTOMATIC DEPRESSURIZATION SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	ADS valve operation	. 4.2*	4.3

SYSTEM: 218000 Automatic Depressurization System

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
MILIO.	ROWLEDGE	DICO
A3.02	ADS valve tail pipe temperatures	3.7
A3.03	ADS valve acoustical monitor noise: Plant-Specific	3.8
A3.04	Primary containment pressure	3.8
A3.05	Suppression pool level	3.7
A3.06	Suppression pool temperature	3.9
A3.07	Lights and alarms	3.6
A3.08	Reactor pressure	4.3*
A3.09	Reactor vessel water level	4.2*
A4.	Ability to manually operate and/or monitor in the control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	ADS valves	4.4*
A4.02	ADS logic initiation	4.2*
A4.03	ADS logic reset	4.2*
A4.04	ADS inhibit: Plant-Specific	4.1*
A4.05	ADS timer reset	4.2*
A4.06	ADS valve tail pipe temperature	3.6
A4.07	ADS valve acoustical monitor noise: Plant-Specific	3.8
A4.08	Suppression pool level	3.8
A4.09	Suppression pool temperature	3.9
A4.10	Lights and alarms	3.8
A4.11	Reactor pressure	4.3*
A4.12	Reactor vessel water level	4.3*

TASK: Perform lineups on the main steam system

Startup the main steam system (cold)

Operate the main steam isolation valves

Place the automatic pressure relief valves in service

Monitor the main steam system

Perform main steam isolation valve (MSIV) fast closure test (MSIV operability testing)

Perform main steam line high radiation functional test perform MSIV's, steam line drain valves and reactor sample valves logic functional test

Perform main mechanical vacuum pump and valve

Isolation system functional test

Perform main steam isolation valve, main steam drain valve and reactor water sample valve simulated automatic isolation test

Perform main steam isolation valves limit switch instrument functional test

Perform main steam line closure scram (MSLCS) operational test

Perform one train MSLCS inop surveillance

Perform main steam leakage control system operational test (write in)

Perform one train main steam leakage control system operability surveillance (write in)

Perform monthly main steam leakage control system division 1 and division 2 fan and heater tests (write in)

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between MAIN AND REHEAT STEAM SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor vessel	3.4
K1.02	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8
K1.03	Main turbine	3.4
K1.04	Moisture separators	2.9
K1.05	Moisture separator reheaters: Plant-Specific	2.8
K1.06	Steam bypass system	3.4
K1.07	Offgas system	3.1
K1.08	Condenser air removal system	3.1
K1.09	Steam seal/gland seal system	2.8
K1.10	Extraction steam system	2.8
K1.11	High pressure heater drains and vents	2.5
K1.12	Plant air systems	2.6
K1.13	Main steam isolation valve leakage control: Plant-	
	Specific	2.8
K1.14	Positive leakage control system: Plant Specific	3.1
K1.15	Process computer/ performance monitor system	2.1
K1.16	Process radiation monitoring system	3.4

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K1.17	Containment system		3.2
K1.18 K1.19	High pressure coolant injection: Plant-Specific	3.3	3.6
IZ1 20	Plant-Specific		3.2
K1.20 K1.21	Residual heat removal system: Plant-Specific		2.9 3.7
K1.22	Feedwater system		3.2
K1.23	Reactor water level control system		3.3
K1.24	Head vent		2.7
K1.25 Kl.26	Relief valves		3.5 3.8
K1.27	Reactor protection system		4.1
K2.	Knowledge of electrical power supplies to the		
	following:		
	(CFR: 41.7)		
K2.01	Main steam isolation valve solenoids	3.2*	3.3*
K2.02	Main steam line shutoff valves (guard valves):	0.04	2 24
	Plant-Specific	2.3*	2.3*
K3.	Knowledge of the effect that a loss or malfunction of		
	the MAIN AND REHEAT STEAM SYSTEM will have on following:		
	(CFR: 41.7 / 45.4)		
K3.01	Turbine generator	3.2	3.3
K3.02	Condenser		3.2
K3.03	Reactor feedpump turbines: Plant-Specific		3.3
K3.04	Offgas system		2.8
K3.05	Condenser air removal		2.9
K3.06	Seal steam/gland and seal system		2.7
K3.07	Containment		3.3
K3.08 K3.09	Decay heat removal		3.5 3.7
K3.10	High pressure coolant injection system: Plant-	3.0	3.7
K3.10	Specific	3.5	3.5
K3.11	Reactor core isolation cooling system: Plant-Specific		
			3.3
K3.12	Isolation condenser: Plant-Specific		3.7
K3.13	Moisture separator reheaters: Plant-Specific		2.4
K3.14 K3.15	Residual heat removal system: Plant-Specific		2.7
K3.15 K3.16	Reactor water level control		3.5 3.6
K3.10 K3.17	Relief/safety valves		3.3
12.0.17	Reactor resser and internals	J.L	٠.٠

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
K4.	Knowledge of MAIN AND REHEAT STEAM SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Automatic isolation of steam lines	3.8
K4.02	Automatic isolation and opening of drain valves: Plant-Specific	3.2
K4.03	Insures that steam released from a steam line break will not bypass suppression pool; BWR-6	3.3
K4.04	Limits steam flow during a steam line rupture to 200%	3.5
K4.05	Steam flow measurement	3.3
K4.06	Allows for removal or prevents escape of radioactive	3.2
	steam from systems that have leaky MSIV's	3.2
K4.07	Over pressure control	3.7
K4.08	Removal of non condensable gases from reactor head	
	area	2.6
K4.09	Equalization of pressure across the MSIV's before	
TT 4 10	opening	3.3
K4.10	Moisture removal from steam lines prior to admitting	2.0
17 / 11	steam	3.0
K4.11	Positive sealing of the MSIV's when shutdown: Plant-Specific	3.1
	2p	0.1
K5.	Knowledge of the operational implications of the following concepts as they apply to MAIN AND REHEAT STEAM SYSTEM: (CFR: 41.5 / 45.3)	
K5.01	Constant enthalpy expansion through a valve	2.2*
K5.02	Definition and causes of steam/water hammer	3.1
K5.03	Definition and causes of thermal stress	2.9
K5.04	Definition and reason for steam blanketing of moisture	,
	separator reheater: Plant-Specific	1.9*
K5.05	Flow indication	2.8
K5.06	Air operated MSIV's	2.9
K5.07	Hydraulic operated MSIV's	2.7
K5.08	Solenoid operated valves	2.7
K5.09	Decay heat removal	3.5
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the MAIN AND REHEAT STEAM SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Electrical power	3.3
K6.02	Plant air systems	3.2
K6.02 K6.03	Safety valve operability	3.2 3.6
10.03	barcty varyo operating	5.0

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K6.04	Relief valve operability: Plant-Specific	3.4	3.5
K6.05	Steam line integrity	3.6	3.7
K6.06	MSIV isolation signal	3.8	3.9
K6.07	MSIV leakage control		3.2
K6.08	Main condenser vacuum		3.4
K6.09	PCIS/NSSSS		4.1*
K6.10	ADS/low low set: Plant-Specific	3.6	3.7
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the MAIN AND REHEAT STEAM SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Main steam pressure	3.6	3.6
A1.02	Main steam temperature		2.6
A1.03	Reheat steam pressure: Plant-Specific		2.2*
A1.04	Reheater temperature: Plant-Specific		2.3
A1.05	Main steam line radiation monitors	3.6	3.6
A1.06	Air ejector process radiation monitor	3.4	3.4
A1.07	Reactor water level	3.7	3.7
A1.08	Reactor pressure	3.8	3.8
A1.09	Main steam flow	3.5	3.4
A1.10	Reactor power	3.8	3.8
A2.	Ability to (a) predict the impacts of the following on		
	the MAIN AND REHEAT STEAM SYSTEM; and (b) based on		
	those predictions, use procedures to correct, control,		
	or mitigate the consequences of those abnormal		
	conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Malfunction of reactor turbine pressure regulating	2 0	3.9
A2.02	system	3.0	3.9
	pressure and power		3.8
A2.03	MSIV closure	4.0	4.2
A2.04	Main steam line low pressure		3.6
A2.05	†Main steam line high radiation		4.2*
A2.06	Turbine trip without bypass valves	4.1	4.3*
A2.07	Main steam area high temperature or differential	2.0	2.0
A 2 00	temperature high		3.9
A2.08	Low condenser vacuum	3.0	3.6
A2.09	Opening of head vent to drywell equipment sump with	3 /	3.7
A2.10	pressure in the reactor vessel		3.7 3.9
A2.10	Closure of one of more wish v s at power	3.0	3.7

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
A2.11	Steam line break	4.3*
A2.12	PCIS/NSSSS actuation	4.3*
A2.13	High reactor water level	3.7
A2.14	Inadvertent initiation of HPCI/HPCS/RCIC (steam	
	quality and steam flow): Plant-Specific	3.5
A3.	Ability to monitor automatic operations of the MAIN AND REHEAT STEAM SYSTEM including: (CFR: 41.7/45.7)	
A3.01	Isolation of main steam system	4.1*
A3.02	Opening and closing of drain valves as turbine load	
	changes: Plant-Specific	2.9
A3.03	Moisture separator reheat steam supply: Plant-	
	Specific	2.8
A3.04	Isolation of moisture separator reheater: Plant-	
	Specific	2.7
A4.	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	MSIV's	4.0
A4.02	Maim steam line drain valves	3.2
A4.03	System flow	3.5
A4.04	System pressure	3.7
A4.05	System temperature	2.7
A4.06	System radiation levels	3.8
A4.07	Lights and alarms	3.3
A4.08	Reactor water level	3.7
A4.09	Reactor pressure	3.9
A4.10	Reactor power	3.8
A4.11	Alternate methods of verifying valve positions	3.3

TASK: Manually operate the steam dump/turbine bypass control systems

Monitor steam dump/turbine bypass control system

Lineup reactor pressure control system for auto operation (write in)

Test control system prior to auto operation (write in)

Perform lineups of the electro-hydraulic control hydraulic power unit

Fill the hydraulic power unit when shutdown

Startup the electro-hydraulic control hydraulic power unit

Operate EHC hydraulic pumps

Shift EHC hydraulic coolers

Operate polishing filters (fuller earth filters)

Replace electro-hydraulic control system filters

Fill the hydraulic power unit reservoir during normal operations

Sample EHC hydraulic fluid

Change accumulators during operation

Monitor electro-hydraulic control hydraulic unit operation

Adjust turbine load limits

Operate the turbine governor test mechanism (test for operation of the overspeed trip device and mechanical trip valve)

Shutdown the electro-hydraulic control power unit

Discharge hydraulic fluid while shutdown

Perform test of the turbine overspeed protection controller (write in)

Test the turbine overspeed trip by actual turbine overspeed (write in)

Perform manual trip of turbine at front standard (write in)

Adjust turbine load limits

Operate the turbine governor test mechanism

Operate the reactor turbine pressure regulating system using manual control mode

Shift control modes (mechanical [manual]/electrical) of the reactor/turbine pressure regulating system

Monitor the reactor/turbine pressure regulating system

What if reactor pressure is high?

Shift control modes (manual/automatic) of the reactor/turbine pressure regulating system

Adjust the reactor/turbine pressure regulating system pressure

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR/TURBINE PRESSURE REGULATING SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor power	3.9
K1.02	Reactor pressure	4.1
K1.03	Reactor water level	3.7
K1.04	Reactor steam flow 3.7	3.7

		IMPORTANCE		
	K/A NO.	KNOWLEDGE RO	SRO	
	K1.05	Main turbine steam flow	3.6	
	K1.06	Bypass valves	3.9	
	K1.07	Main stop/throttle valves	3.6	
	K1.08	Control/governor valves	3.7	
	K1.09	Combined intermediate valves: Plant-Specific	3.4	
•	K1.10	Front standard trip system	3.3	
	K1.11	RPS 3.7	3.8	
	K1.12	FW extraction non-return valves	2.6	
	K1.13	Bearing oil	2.6	
	K1.14	A.C. electrical power	2.9	
	K1.15	D.C. electrical power	2.7	
	K1.16	Component cooling water systems	2.6	
	K1.17	Turbine chest warming: EHC-Only	2.5	
	K1.18	Turbine shell warming: EHC-Only	2.5	
	K1.19	Turbine acceleration	2.6	
	K1.20	Turbine speed	2.7	
	K1.21	Turbine inlet pressure	2.7	
	K1.22	Turbine trip	3.5	
	K1.23	Recirculation flow control system: Plant-Specific	3.1	
	K1.24	Main generator	2.8	
	K1.25	Stator water cooling: Plant-Specific	2.8	
	K1.26	Main turbine PMG: Plant-Specific	2.6	
	K1.27	Condenser vacuum	3.1	
	K1.28	Reactor startup	3.2	
	K1.29	Reactor heatup	3.4	
	K1.30	Reactor cooldown	3.3	
	K1.31	Turbine protection	3.2	
	K1.32	Turbine monitoring	2.8	
	K1.32 K1.33	FW extraction steam valves	2.6	
	K1.34	EGC system: Plant-Specific	3.3	
	K1.34 K1.35	Low pressure stop and control valves: Plant-Specific	2.6	
ı	K1.35	Primary water system: Plant-Specific	2.0*?	
I	K1.30 K1.37	Turbine stress evaluator: Plant-Specific	1.8*	
	K1.37 K1.38	PCIS/NSSSS: Plant-Specific	2.8	
	K1.30	PCIS/NSSSS: Plant-Specific	2.8	
	K2.	Knowledge of electrical power supplies to the		
		following: (CFR: 41.7)		
		(CIR. 41.7)		
	K2.01	Pumps	2.2*	
	K2.02	Controls	2.1*	
	К3.	Knowledge of the effect that a loss or malfunction of the REACTOR/TURBINE PRESSURE REGULATING SYSTEM will have on following: (CFR: 41.7 / 45.4)		
	K3.01	Reactor power	4.1	

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K3.02	Reactor pressure	. 4.2*	4.3*
K3.03	Reactor water level	. 3.7	3.8
K3.04	Reactor steam flow	. 3.8	3.9
K3.05	Main turbine steam flow	. 3.7	3.7
K3.06	Bypass valves	. 4.1*	4.1
K3.07	Main stop/throttle valves	. 3.3	3.3
K3.08	Control/governor valves	. 3.7	3.7
K3.09	Combined intermediate valves: Plant-Specific	. 3.2	3.3
K3.10	Front standard trip system	. 2.9	3.0
K3.11	RPS	. 3.8	3.8
K3.12	FW extraction steam valves: Plant-Specific	. 2.4	2.4
K3.13	FW extraction non-return valves		2.4
K3.14	Component cooling water systems: Plant-Specific		2.3
K3.15	Turbine chest warming: EHC-Only		2.8
K3.16	Turbine shell warming: EHC-Only		2.8
K3.17	Turbine acceleration		2.8
K3.18	Turbine speed		2.9
K3.19	Turbine inlet pressure		2.7
K3.20	Turbine trip		3.4
K3.21	Recirculation flow control system: Plant-Specific		2.8
K3.22	Main generator		2.6
K3.23	Turbine trip testing: Plant-Specific		2.9
K3.24	Reactor heatup		3.2
K3.25	Reactor cooldown		3.3
K3.26	Turbine protection		3.2
K3.27	Turbine monitoring		2.6
K3.28	Low pressure stop and control valves: Plant-Specific.		2.5
K3.29	PCIS/NSSSS		3.1
K3.29 K3.30	EGC: Plant-Specific		3.0
K4.	Knowledge of REACTOR/TURBINE PRESSURE REGULATING SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Reactor pressure control	3.8	3.8
K4.02	Turbine inlet pressure control		3.3
K4.03	Turbine speed control		3.1
K4.04	Turbine acceleration control		2.8
K4.05	Reactor scram		3.8*
K4.06	Turbine trip		3.7*
K4.07	Generator runback: Plant-Specific		3.7
K4.07 K4.08	Feedwater heater isolation: Plant-Specific		2.9
K4.09	Turbine chest warming: EHC-Only		2.9
K4.09 K4.10			2.4
K4.10 K4.11	Turbine shell warming: EHC-Only		
K4.11 K4.12	Load following: Plant-Specific		2.6 2.9
N4.12	Recirculation flow control. Flaint-specific	. ∠.9	۷.9

Tasks as noted previously

	K/A NO.	KNOWLEDGE	RO	SRO
	K4.13	Turbine trip testing: Plant-Specific	2.9	3.0
	K4.14	Reactor/turbine pressure regulating system oil		
		cooling: Plant-Specific		2.4
	K4.15	Automatic pump start		2.6
	K4.16	Reactor cooldown		3.4
	K4.17	Turbine monitoring		2.6
	K4.18	Turbine protection		2.8
	K4.19	Steam bypass valve control	3.6	3.7
	K5.	Knowledge of the operational Implications of the		
		following concepts as they apply to REACTOR/TURBINE		
		PRESSURE REGULATING SYSTEM:		
		(CFR: 41.5 / 45.3)		
	K5.01	Accumulator operation: Plant-Specific	2.0*	2.1*
	K5.02	Limit switch operation	2.1*	2.2*
	K5.03	Reactor power vs. reactor pressure	3.5	3.6
	K5.04	Turbine inlet pressure vs. reactor pressure	3.3	3.3
	K5.05	Turbine inlet pressure vs. turbine load	2.8	2.9
	K5.06	Turbine speed measurement		2.3
	K5.07	Unitized actuator operation: Fermi-Only	2.5	3.0
	K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR/TURBINE PRESSURE REGULATING SYSTEM: (CFR: 41.7 / 45.7)		
	K6.01	A.C. electrical power	2.8	2.9
	K6.02	D.C. electrical power		2.7
	K6.03	Component cooling water systems	2.5	2.5
	K6.04	Recirculation flow control system: Plant-Specific	3.0	3.0
	K6.05	Condenser vacuum	3.4	3.4
	K6.06	Reactor pressure	3.8*	3.9*
	K6.07	Turbine inlet pressure		3.4
	K6.08	Reactor power		3.7
	K6.09	Main turbine steam flow		3.1
	K6.10	Bypass valves		3.7
	K6.11	Main stop/throttle valves		3.4
	K6.12	Control/governor valves		3.4
	K6.13	Combined intermediate valves: Plant-Specific		3.2
	K6.14	Bearing oil		2.8
	K6.15	Turbine speed signal		2.4
	K6.16	Stator water cooling system: Plant-Specific		3.1
	K6.17	Main turbine PMG: Plant-Specific		2.8
ı	K6.18	Low pressure stop and control valves: Plant-Specific		2.7
l	K6.19	Primary water system: Plant-Specific		2.3*
	K6.20	Main generator	2.8	3.0

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR/TURBINE PRESSURE REGULATING SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Reactor pressure	. 3.9	3.8
A1.02	Reactor power		3.9
A1.03	Reactor water level		3.7
A1.04	Main turbine inlet pressure	. 3.1	3.1
A1.05	Reactor steam flow	. 3.5	3.6
A1.06	Ma in turbine steam flow	. 3.2	3.2
A1.07	Bypass valve position	. 3.8	3.7
A1.08	control/governor valve position	. 3.3	3.2
A1.09	Main stop throttle valve position	. 3.3	3.3
A1.10	Combined intermediate valve position: Plant-Specific	. 3.3	3.2
A1.11	Reactor/turbine pressure regulating system oil		
	pressure: Plant-Specific	. 2.7	2.7
A1.12	Reactor/turbine pressure regulating system load		
	set/reference: Plant-Specific	. 2.9	2.8
A1.13	Main turbine speed	. 2.7	2.7
A1.14	Pressure setpoint/pressure demand	. 3.4	3.4
A1.15	Maximum combined flow limit		3.1
A1.16	Load limit set: Plant-Specific	. 3.3	3.3
A1.17	Reactor/turbine pressure regulating system oil pump		
	current: Plant-Specific	. 1.9*	1.9*
A1.18	Reactor/turbine pressure regulating system reservoir		
	oil level: Plant-Specific	. 2.1*	2.0*
Al.19	Reactor/turbine pressure regulating system reservoir		
	oil temperature: Plant-Specific	. 2.0*	1.9*
A1.20	Servo valve currents: Plant-Specific	. 2.2*	2.1*
A1.21	Main condenser vacuum	. 3.4	3.4
A1.22	Reactor cooldown	. 3.4	3.3
A1.23	Main turbine vibration	. 2.8	2.8
A1.24	Main turbine eccentricity	. 2.6	2.7
A1.25	Main turbine expansion	. 2.6	2.6
A1.26	Governor valve limit: Plant-Specific	. 2.4	2.4
A2.	Ability to (a) predict the impacts of the following on the REACTOR/TURBINE PRESSURE REGULATING SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02	Loss of turbine inlet pressure signal		3.7 3.7

Tasks as noted previously

K/A NO.	ABILITY RO	SRC
A2.03	Failed open/closed bypass valve(s)	4.2*
A2.04	Failed open/closed control/governor valve(s)	3.8
A2.05	Failed open/closed main stop valve(s)	3.9
A2.06	Low reactor/turbine pressure regulating system oil	
	pressure: Plant-Specific	3.2
A2.07	Loss of condenser vacuum	3.6
A2.08	Main turbine overspeed	3.3
A2.09	Loss of generator load	3.5
A2.10	Loss of stator water cooling: Plant-Specific	3.2
A2.11	Loss of A.C. electrical power	3.1
A2.12	Loss of D.C. electrical power	2.8
A2.13	Loss of component cooling water systems	2.7
A2.14	Loss of main turbine PMG: Plant-Specific	2.7
A2.15	Loss of main turbine speed feedback: Plant-Specific	2.4
A2.16	Low turbine inlet pressure (loss of pressure signal)	3.4
A2.17	Turbine trip: Plant-Specific	3.8
A2.18	Generator trip: Plant-Specific	3.5
A2.19	Reactor scram	3.8
A2.20	Low reactor/turbine pressure regulating system oil level: Plant-Specific	2.6
A2.21	Reactor/turbine pressure regulating system pump trip:	2.0
A2.21	Plant-Specific	2.8
A2.22	Turbine high vibration	2.9
A2.23	Turbine high eccentricity	2.6
A2.24	Turbine high differential expansion	2.5
A2.25	Loss of primary water system: Plant-Specific	2.3
A3.	Ability to monitor automatic operations of the REACTOR/TURBINE PRESSURE REGULATING SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Turbine speed control: Plant-Specific	2.7
A3.02	Turbine acceleration control: Plant-Specific	2.6
A3.03	Turbine inlet pressure control	2.7
A3.04	Reactor/turbine pressure regulating system pump start: Plant-Specific	2.5
A3.05	Reactor/turbine pressure regulating system low	
	pressure turbine trip: Plant-Specific	2.8
A3.06	Reactor/turbine pressure regulating system low	
	pressure reactor scram: Plant-Specific	3.3
A3.07	Reactor/turbine pressure regulating system oil	
	temperature control: Plant-Specific	2.3
A3.08	Steam bypass valve operation	3.8
A3.09	Control/governor valve operation	3.2
A3.10	Main stop/throttle valve operation	3.3
A3.11	Combined intermediate valve operation: Plant-Specific	3.1
A3.12	Turbine trip testing	2.9

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO	
A 2 12	FW hastonicalstian, Plant Specific	2.0	
A3.13 A3.14	FW heater isolation: Plant-Specific	2.8	
A3.14 A3.15	Grid load following: Plant-Specific 2.6 Recirculation pump flow control: Plant-Specific 2.8	2.7 2.9	
A3.15 A3.16	Lights and alarms	2.9	
A3.17	Turbine runback 3.3	3.4	
A3.17 A3.18		3.4	- 1
A3.16	Turbine startup: Plant-Specific	3.0	I
A4.	Ability to manually operate and/or monitor in the		
	control room:		
	(CFR: 41.7 / 45.5 to 45.8)		
A4.01	Reactor power	4.0	
A4.02	Reactor pressure	4.1*	
A4.03	Reactor water level	3.9	'
A4.04	Reactor steam flow	3.7	
A4.05	Main turbine steam flow	3.3	
A4.06	Bypass valves (operation)	3.9	
A4.07	Main stop/throttle valves (operation)	3.4	
A4.08	Control/governor valves (operation)	3.4	
A4.09	Combined intermediate valves (operation): Plant-		
	Specific	3.1	
A4.10	Reactor/turbine pressure regulating system pumps:		
	Plant-Specific	2.9	
A4.11	Turbine speed	3.1	
A4.12	Turbine acceleration	3.0	
A4.13	Turbine inlet pressure	2.9	
A4.14	Turbine trip	3.7	
A4.15	Generator load	3.2	
A4.16	Lights and alarms	3.2	
A4.17	Turbine chest warming: Plant-Specific	2.8	
A4.18	Turbine shell warming: Plant-Specific	2.8	
A4.19	Turbine panel controls	3.4	

SYSTEM: 239002 Relief/Safety Valves

TASK: Place the automatic pressure relief valves in service

	K/A NO.	KNOWLEDGE RO	SRO
	K1.	Knowledge of the physical connections and/or cause-effect relationships between RELIEF/SAFETY VALVES and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
ı	K1.01 K1.02 K1.03	Nuclear boiler3.8SPDS/ERIS/CRIDS/GDS: Plant-Specific2.5*Nuclear boiler instrument system3.5	3.9 2.9 3.6
1	K1.04 K1.05 K1.06	Main steam	3.7 3.3
	K1.07 K1.08 K1.09	Specific	3.6 3.8 4.1
	K1.09	the drywell airspace): Plant-Specific	4.0
	K 2.	following: (CFR: 41.7)	
	K2.01	SRV solenoids	3.2*
	К3.	Knowledge of the effect that a loss or malfunction of the RELIEF/SAFETY VALVES will have on following: (CFR: 41.7 / 45.4)	
	K3.01 K3.02 K3.03	Reactor pressure control3.9Reactor over pressurization4.2*Ability to rapidly depressurize the reactor4.3*	4.0 4.4* 4.4*
	K4.	Knowledge of RELIEF/SAFETY VALVES design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
	K4.01	Insures that only one or two safety/relief valves reopen following the initial portion of a reactor isolation event (LLS logic): Plant-Specific	4.0
	K4.02	Minimizes containment fatigue duty cycles resulting from relief valve cycling during decay-heat-dominant period late in an isolation transient (LLS logic):	
	K4.03	Plant-Specific	3.6
	K4.04	and limits loads on subsequent actuation of SRV's	3.3

SYSTEM: 239002 Relief/Safety Valves

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRC
K4.05	Allows for SRV operation from more than one location:		
	Plant-Specific	3.6	3.7
K4.06	Detection of valve leakage	3.5	3.7
K4.07	Minimum steam pressure required to keep SRV open or to		
	open SRV	3.1	3.2
K4.08	Opening of the SRV from either an electrical or		
TT 4 00	mechanical signal .,		3.7
K4.09	Manual opening of the SRV	3.7	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to RELIEF/SAFETY VALVES: (CFR: 41.5 / 45.3)		
K5.01	Relief function of SRV operation	3.4	3.5
K5.02	Safety function of SRV operation		3.8
K5.03	Acoustical monitoring: Plant-Specific		3.8
K5.04	Tail pipe temperature monitoring		3.5
K5.05	Discharge line quencher operation		2.9
K5.06	Vacuum breaker operation		3.0
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the RELIEF/SAFETY VALVES: (CFR: 41.7 / 45.7)		
K6.01	Nuclear boiler instrument system (pressure indication)	3.2	3.4
K6.02	Air (Nitrogen) supply: Plant-Specific	3.4	3.5
K6.03	A.C. power: Plant-Specific		2.9*
K6.04	D.C. power: Plant-Specific	3.0	3.2
K6.05	Discharge line vacuum breaker	3.0	3.2
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RELIEF/SAFETY VALVES controls including: (CFR: 41.5 / 45.5)		
A1.01	Tail pipe temperature	3.3	3.4
1 1 00	A	~ -	• •

A1.01	Tail pipe temperature	3.4
A1.02	Acoustical monitor noise: Plant-Specific	3.8
A1.03	Air supply: Plant-Specific	2.9
A1.04	Reactor pressure	3.8
A1.05	Reactor water level	3.8
A1.06	Reactor power	3.8
A1.07	Turbine load	3.0
A1.08	Suppression pool water temperature	4.1
A1.09	Indicated vs. actual steam flow: Plant-Specific	3.3

SYSTEM: 239002 Relief/Safety Valves

Tasks as noted previously

TZ/A NIO	ADWWW	DO.	CD C
K/A NO.	ABILITY	RO	SRO
A2.	Ability to (a) predict the impacts of the following on the RELIEF/SAFETY VALVES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06	Stuck open vacuum breakers Leaky SRV Stuck open SRV ADS actuation Low reactor pressure Reactor high pressure	. 3.1 . 4.1 . 4.1* . 3.2	3.3 3.2 4.2* 4.2* 3.4 4.3*
A3.	Ability to monitor automatic operations of the RELIEF/SAFETY VALVES including: (CFR: 41.7 / 45.7)		
A3.01 A3.02 A3.03 A3.04 A3.05 A3.06 A3.07 A3.08 A3.09	SRV operation after ADS actuation SRV operation on high reactor pressure Tail pipe temperatures Acoustical monitor noise: Plant-Specific Suppression pool temperature Reactor pressure Reactor water level Lights and alarms Low low set logic: Plant-Specific	. 4.3* . 3.6 . 3.6 . 4.1* . 4.1* . 3.8 . 3.6	3.9* 4.3* 3.6 3.7 4.2* 4.1* 3.9 3.6 3.9
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01 A4.02 A4.03 A4.04 A4.05 A4.06 A4.07 A4.08	SRV's Tail pipe temperatures Acoustical monitor noise: Plant-Specific Suppression pool temperature Reactor pressure Reactor water level Lights and alarms Plant air system pressure: Plant-Specific	. 3.6 . 3.8 . 4.3* . 4.3* . 3.9 . 3.6	4.4* 3.7 3.9 4.3* 4.3* 4.1 3.6 3.2

3.4	Heat Removal from Reactor Core	page
206000	High Pressure Coolant Injection System	3.4-3
209002	High Pressure Core Spray System	3.4-8
207000	Isolation (Emergency) Condenser	3.4-12
209001	Low Pressure Core Spray System	3.4-16
239001	Main and Reheat Steam System	3.4-20
245000	Main Turbine Generator and Auxiliary Systems	3.4-25
217000	Reactor Core Isolation Cooling System	3.4-29
202001	Recirculation System	3.4-33
203000	Residual Heat Removal /Low Pressure Coolant Injection:	3.4-38
	Injection Mode	
205000	Shutdown Cooling System (RHR Shutdown Cooling Mode)	3.4-42

This page left blank

TASK: Place the high pressure (Feedwater) coolant injection system (FWCI) in standby readiness

Monitor the high pressure (feedwater) coolant injection system operation

Return the high pressure (feedwater) coolant injection system to stand-by readiness after automatic initiation

Perform lineups of the high pressure coolant injection system (write in)

Manually initiate high pressure coolant injection

Perform high pressure coolant injection (HPCI) simulated automatic actuation test

Perform high pressure (feedwater) coolant injection flow rate test

Perform high pressure (feedwater) coolant injection (HPCI) pump operability test

Perform high pressure (feedwater) coolant injection motor operated valve operability test

Perform HPCI subsystem logic system functional test

Perform HPCI subsystem automatic isolation logic system functional test

Perform HPCI system inoperable test

Perform HPCI turbine overspeed test

Perform high pressure (feedwater) coolant injection operability test when reactor core isolation cooling is inoperable

	INFORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between HIGH PRESSURE COOLANT INJECTION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Reactor vessel: BWR-2,3,4	3.8	3.9
K1.02	Reactor water level: BWR-2,3,4		4.1*
K1.03	Reactor pressure: BWR-2,3,4		3.8
K1.04	Reactor feedwater system: BWR-2,3,4	3.6	3.6
K1.05	Condensate storage system: BWR-2,3,4	3.7	3.7
K1.06	Suppression chamber: BWR-2,3,4	3.7	3.7
K1.07	D.C. power: BWR-2,3,4		3.8*
K1.08	A.C. power: BWR-2,3,4		3.1*
K1.09	ECCS keep fill system: BWR-2,3,4(P-Spec)	4.0*	4.0
K1.10	Condensate storage and transfer system: BWR-2,3,4	3.4	3.4
K1.11	PCIS: BWR-2,3,4	3.5	3.5
K1.12	Nuclear boiler instrumentation: BWR-2,3,4		3.4
K1.13	Main condenser: BWR-2,3,4(P-Spec)		2.9*
K1.14	SBGT: BWR-2,3,4(P-Spec)		3.1
K1.15	Plant air systems: BWR-2,3,4	2.3*	2.3*
K1.16	Containment/Torus pressure: BWR-2,3,4		3.5

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03 K2.04	System valves: BWR-2,3,4 System pumps: BWR-2,3,4 Initiation logic: BWR-2,3,4 Turbine control circuits: BWR-2,3,4	2.8* 2.8*	3.3* 3.1* 2.9* 2.7*
К3.	Knowledge of the effect that a loss or malfunction of the HIGH PRESSURE COOLANT INJECTION SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03	Reactor water level control: BWR-2,3,4	3.8*	4.0 3.8* 3.5*
K4.	Knowledge of HIGH PRESSURE COOLANT INJECTION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Turbine trips: BWR-2,3,4	3.8	3.9
K4.02	System isolation: BWR-2,3,4		4.0
K4.03	Resetting turbine trips: BWR-2,3,4		4.1
K4.04	Resetting system isolations: BWR-2,3,4		3.9
K4.05	Preventing water hammer in turbine exhaust line	4.0	3.9
K4.03		2 1	3.4
K4.06	(procedural control): BWR-2,3,4		3.4
K4.07	Automatic system initiation: BWR-2,3,4		4.3
K4.08	Manual system initiation: BWR-2,3,4		4.3
K4.09	Automatic flow control: BWR-2,3,4		3.9
K4.10	Surveillance for all operable components: BWR-2,3,4		3.8
K4.11	Turbine speed control: BWR-2,3,4		3.5
K4.12	Condensation of shaft sealing steam: BWR-2,3,4		3.0
K4.13	Turbine and pump lubrication: BWR-2,3,4		3.1
K4.14	Control oil to turbine speed controls: BWR-2,3,4		3.4
K4.15	Low speed turning of the turbine rotor: BWR-2,3,4(P-	5.1	5.1
K4.16	Spec)	3.2	3.2
K4.17	initiation): BWR-2,3,4(P-Spec)		3.3
17.4.10	tank to the suppression pool: BWR-2,3,4		3.4
K4.18	Pump minimum flow: BWR-2,3,4		3.3
K4.19	Automatic transfer of HPCI pump suction: BWR-2,3,4	3.7	3.8

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO	
K5.	Knowledge of the operational implications of the following concepts as they apply to HIGH PRESSURE COOLANT INJECTION SYSTEM: (CFR: 41.5 / 45.3)			
K5.01 K5.02 K5.03 K5.04 K5.05 K5.06 K5.07 K5.08 K5.09 K5.10	Turbine operation: BWR-2,3,4 Turbine shaft sealing: BWR-2,3,4 GEMAC controllers: BWR-2,3,4(P-Spec) Indications of pump cavitation: BWR-2,3,4 Turbine speed control: BWR-2,3,4 Turbine speed measurement: BWR-2,3,4 System venting: BWR-2,3,4 Vacuum breaker operation: BWR-2,3,4 Testable check valve operation: BWR-2,3,4 Assist core cooling: BWR-2,3,4	2.8 3.1 2.6* 3.3 2.6* 2.8 3.0 2.7*	3.4 2.9 3.1 2.7* 3.3 2.6 2.8 3.2 2.8 3.5	
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the HIGH PRESSURE COOLANT INJECTION SYSTEM: (CFR: 41.7 / 45.7)			
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07 K6.08 K6.09 K6.10 K6.11	Plant air systems: BWR-2,3,4 D.C. power: BWR-2,3,4 A.C. power: BWR-2,3,4 Condensate storage tank level: BWR-2,3,4 Suppression pool level: BWR-2,3,4 SBGTS: BWR-2,3,4(P-Spec) ECCS keep fill system: BWR-2,3,4(P-Spec) Reactor pressure: BWR-2,3,4 Condensate storage and transfer system: BWR-2,3,4 PCIS: BWR-2,3,4 Nuclear boiler instrumentation: BWR-2,3,4 Reactor water level: BWR-2,3,4	3.3 2.9 3.5 3.5 3.1 3.4 3.8 3.8 3.5	2.3* 3.7* 3.1* 3.7 3.7 3.2 3.4 3.8 3.5 4.0 3.7 4.3*	
	ABILITY			
A1.	Ability to predict and/or monitor changes in parameters associated with operating the HIGH PRESSURE COOLANT INJECTION SYSTEM controls including: (CFR: 41.5 / 45.5)			
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06	Reactor water level: BWR-2,3,4 Reactor pressure: BWR-2,3,4 Condensate storage tank level: BWR-2,3,4 Suppression pool level: BWR-2,3,4 Suppression pool temperature: BWR-2,3,4 System flow: BWR-2,3,4 System flow: BWR-2,3,4	4.2* 3.5 3.7 4.1	4.4* 4.2 3.6 3.8 4.2 3.7	

IMPORTAN	ICE
-----------------	------------

K/A NO.	KNOWLEDGE	RO	SRO
A1.07	System discharge pressure: BWR-2,3,4	3.7	3.6
A1.08	System lineup: BWR-2,3,4	4.1*	4.0
A1.09	Turbine speed: BWR-2,3,4	. 3.5	3.4
A2.	Ability to (a) predict the impacts of the following on the HIGH PRESSURE COOLANT INJECTION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Turbine trips: BWR-2,3,4	. 4.0	4.0
A2.02	Valve closures: BWR-2,3,4	. 3.5	3.5
A2.03	Valve openings: BWR-2,3,4	. 3.5	3.5
A2.04	A.C. failures: BWR-2,3,4	. 2.7*	3.0*
A2.05	D.C. failures: BWR-2,3,4	. 3.5	3.8*
A2.06	Inadequate system flow: BWR-2,3,4	. 3.3	3.5
A2.07	Low suppression pool level: BWR-2,3,4		3.6
A2.08	†High suppression pool temperature: BWR-2,3,4		4.2
A2.09	†Low condensate storage tank level: BWR-2,3,4		3.7
A2.10	System isolation: BWR-2,3,4		4.1
A2.11	Low reactor water level: BWR-2,3,4		4.2
A2.12	Loss of room cooling: BWR-2,3,4		3.5
A2.13	Loss of applicable plant air systems: BWR-2,3,4		2.4*
A2.14	Flow controller failure: BWR-2,3,4		3.4
A2.15	Loss of control oil pressure: BWR-2,3,4		3.5
A2.16	High drywell pressure: BWR-2,3,4		4.1
A2.17	†HPCI inadvertent initiation: BWR-2,3,4		4.3*
A2.17		. 3.9	4.3
AS.	Ability to monitor automatic operations of the HIGH PRESSURE COOLANT INJECTION SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	Turbine speed: BWR-2,3,4	. 3.6	3.5
A3.02	System Flow: BWR-2,3,4	. 3.8	3.8
A3.03	System lineup: BWR-2,3,4	. 3.9	3.8
A3.04	Reactor pressure: BWR-2,3,4		4.1
A3.05	Reactor water level: BWR-2,3,4		4.3
A3.06	System discharge pressure: BWR-2,3,4		3.8
A3.07	Lights and alarms: BWR-2,3,4		3.8
A3.08	Condensate storage tank level: BWR-2,3,4		3.6
A3.09	Response to system isolation: BWR-2,3,4		4.1
	,,		

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	Turbine speed controls: BWR-2,3,4	3.8	3.7
A4.02	Flow controller: BWR-2,3,4		3.8
A4.03	Turbine temperatures: BWR-2,3,4	3.1	3.0
A4.04	Major system valves: BWR-2,3.4		3.7
A4.05	Reactor water level: BWR-2,3,4	4.4*	4.4*
A4.06	Reactor pressure: BWR-2,3,4	4.3*	4.3*
A4.07	Condensate storage tank level: BWR-2,3,4	3.5	3.5
A4.08	Suppression pool temperature: BWR-2,3,4	4.1*	4.1
A4.09	Suppression pool level: BWR-2,3,4	3.8	3.7
A4.10	System pumps: BWR-2,3,4		3.5
A4.11	Turning gear: BWR-2,3,4(P-Spec)	3.0	3.0
A4.12	Turbine trip controls: BWR-2,3,4		3.9
A4.13	Turbine reset control: BWR-2,3,4		4.0
A4.14	System auto start control: BWR-2,3,4(P-Spec)	4.2*	4.1

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

TASK: Perform lineups on the core spray system

Place core spray (CS) system in standby readiness

Monitor automatic operation of core spray system

Shutdown core spray cooling system

Perform core spray simulated automatic actuation test

Perform core spray pump operability test

Perform core spray system inop test

Conduct core spray - cold shutdown valve testing

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Condensate transfer and storage system: BWR-5,6	3.4	3.4
K1.02	Suppression Pool: BWR-5,6	3.5	3.5
K1.03	Water leg (jockey) pump: BWR-5,6		3.0
K1.04	HPCS diesel generator: BWR-5,6		3.8
K1.05	Standby liquid control system: Plant-Specific		2.8
K1.05	Suppression pool cleanup system: BWR-5,6		2.0
K1.07	ECCS room coolers: BWR-5,6		2.4
K1.08	Component cooling water systems: BWR-5,6		2.6
K1.09	Leak detection: BWR-5,6		2.5
K1.10	Suppression pool suction strainers: BWR-5,6		2.1
K1.11	Adequate core cooling: BWR-5,6		4.0
Kl.12	Reactor vessel: BWR-5,6		3.6
K1.13	Instrument nitrogen: BWR-5,6	2.7	2.7
K1.14	Plant air systems: BWR-5,6	2.6	2.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Pump electrical power: BWR-5,6	3.2	3.3
K2.02	Valve electrical power: BWR-5,6		2.9
K2.03	Initiation logic: BWR-5,6		2.9
K3.	Knowledge of the effect that a loss or malfunction of the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) will have on following: (CFR: 41.7 / 45.4)		
K3.01	Reactor water level: BWR-5,6	3.9	3.9
K3.02	Standby liquid control system: Plant-Specific		3.3
K3.03	Adequate core cooling: BWR-5,6		4.1

K/A NO.	KNOWLEDGE	RO	SRO
K4.	Knowledge of HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06 K4.07	Prevents water hammer: BWR-5,6 Prevents over filling reactor vessel: Plant-Specific. Prevents pump over heating: BWR-5,6 Testable check valve operation: BWR-5,6 Motor operated valve operation: BWR-5,6 Centrifugal pump operation: BWR-5,6 Override of reactor water level interlock: Plant-Specific	. 3.4 . 2.3* . 2.3* . 2.4 . 2.3*	3.0 3.5 2.4 2.3* 2.4 2.4*
K5.	Knowledge of the operational implications of the following concepts as they apply to HIGH PRESSURE CORE SPRAY SYSTEM (HPCS): (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03 K5.04	Indications of pump cavitation: BWR-5,6. Heat removal (transfer) mechanism: BWR-5,6. System venting: BWR-5,6. Adequate core cooling: BWR-5,6.	. 2.6 . 2.4	2.8 2.7 2.4 4.0
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS): (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04	Electrical power: BWR-5,6	. 3.4	2.6 3.4 2.6 2.5
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08	HPCS flow: BWR-5,6 HPCS pressure: BWR-5,6 Reactor water level: BWR-5,6 Reactor pressure: BWR-5,6 Suppression pool water level: BWR-5,6 Motor amps: BWR-5,6 Diesel loading: BWR-5,6 System lineup: BWR-5,6	. 3.4 . 3.7 . 3.3 . 3.3 . 1.9* . 2.5*	3.7 3.6 3.7 3.3 3.4 2.3* 2.8 3.3

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

Tasks as noted previously

K/A NO.	KNOWLEDGE	SRO
A1.09	Condensate storage tank level: BWR-5,6	5 2.8
A2.	Ability to (a) predict the impacts of the following on the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08 A2.09 A2.10 A2.11 A2.12 A2.13 A2.14 A2.15	System initiation: BWR-5,6	6 3.7 2 3.4 1 3.2 8 2.9 4 3.6 6 3.0 1 3.2 4 2.6 7 3.0 3 3.5 3 3.5 4 3.5 0 3.3
A3.	Ability to monitor automatic operations of the HIGH PRESSURE CORE SPRAY SYSTEM (HPCS) including: (CFR: 41.7 / 45.7)	4 2.0
A3.01 A3.02 A3.03 A3.04 A3.05 A3.06	Valve operation: BWR-5,6 3. Pump start: BWR-5,6 3. System pressure: BWR-5,6 3. System flow: BWR-5,6 3. Reactor water level BWR-5,6 3. Lights and alarms: BWR-5,6 2.	8 3.8 6 3.6 7 3.7 7 3.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01 A4.02 A4.03 A4.04 A4.05	HPCS pump: BWR-5,6 3. Suction valves: BWR-5,6 3. Injection valve: BWR-5,6 3. Minimum flow valve: BWR-5,6 3. Manual Initiation controls: BWR-5,6 3.	6 3.6 8 3.8 1 3.1

SYSTEM: 209002 High Pressure Core Spray System (HPCS)

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
A4.06	Testable check valve: BWR-5,6.	. 2.6	2.6
A4.07	Line fill pump: BWR-5,6	. 2.8	2.8
A4.08	Reactor water level: BWR-5,6	. 3.6	3.7
A4.09	Suppression pool level: BWR-5,6	. 3.4	3.5
A4.10	Reactor pressure: BWR-5,6	. 3.3	3.3
A4.11	System flow: BWR-5,6	. 3.8	3.8
A4.12	System pressure: BWR-5,6	. 3.4	3.4
A4.13	Lights and alarms: BWR-5,6		2.6
A4.14	Test return valve: BWR-5,6	. 3.0	3.0
A4.15	Initiation reset: BWR-5,6	. 3.6	3.6

TASK: Perform lineups on the isolation condenser system

Fill and add makeup to the isolation condenser system Place the isolation condenser (Iso-Cond) in standby

Place the isolation condenser system in service from a standby readiness condition

Remove the isolation condenser system from service

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between ISOLATION (EMERGENCY) CONDENSER and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Reactor vessel: BWR-2,3	. 3.8	4.0
K1.02	Reactor pressure: BWR-2,3		4.2
K1.03	Reactor water level: BWR-2,3		3.8
K1.04	Condensate transfer system: BWR-2,3	. 3.5	3.8
K1.05	Demineralized water system: BWR-2,3(P-Spec)		3.6
K1.06	Fire protection/service water: BWR-2,3		3.7
K1.07	LPCI: BWR-2,3(P-Spec)		3.3*
K1.08	Recirculation system: BWR-2,3	. 3.0	3.2
K1.09	Main steam system: BWR-2,3		3.2
K1.10	Plant air systems: BWR-2,3	. 3.0*	3.2
K1.11	Primary containment isolation system: BWR-2,3	. 3.4	3.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Motor operated valves: BWR-2,3	. 3.6	3.8
K2.02	Initiation logic: BWR-2,3	. 3.5	3.7
К3.	Knowledge of the effect that a loss or malfunction of the ISOLATION (EMERGENCY) CONDENSER will have on following: (CFR: 41.7/45.4)		
K3.01	Reactor pressure control during conditions in which		
	the reactor vessel is isolated: BWR-2,3	. 4.2*	4.3*
K3.02	†Reactor water level (EPG's address the isolation condenser as a water source): BWR-2,3	. 3.8*	4.0*
K4.	Knowledge of ISOLATION (EMERGENCY) CONDENSER design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Isolation of the system in the event of a line break:	4.24	4 7 4
K4.02	BWR2,3		4.5* 4.2

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K4.03	Filling of the system: BWR-2,3	3.3	3.5
K4.04	Steam and condensate flow indication: BWR-2,3		3.4
K4.05	Detection of a tube bundle leak: BWR-2,3		4.2
K4.06	Throttling of system flow: BWR-2,3		4.0
K4.07	Manual operation of the system: BWR-2,3		4.0
K4.08	Protection against incomplete steam condensation		
	(condensate outlet valve does not fully open): BWR-		
	2,3,(P-Spec)	3.4	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to ISOLATION (EMERGENCY) CONDENSER: (CFR: 41.5 / 45.3)		
K5.01	Flow measurement across an elbow using differential		
	pressure: BWR-2,3		3.0*
K5.02	Heat exchanger operation: BWR-2,3		3.3
K5.03	Heat transfer: BWR-2,3		3.0
K5.04	Latent heat of vaporization: BWR-2,3		2.7*
K5.05	Saturated steam: BWR-2,3		2.7
K5.06	Saturated liquid: BWR-2,3		2.7
K5.07	Temperature sensing: BWR-2,3		2.8
K5.08	Level indicator operation: BWR-2,3		3.0
K5.09	Cooldown rate: BWR-2,3		4.0
K5.10	System venting: BWR-2,3	3.0	3.2
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the ISOLATION (EMERGENCY) CONDENSER: (CFR: 41.7 / 45.7)		
K6.01	Demineralized water system: BWR-2,3(P-Spec)	3.3	3.7
K6.02	Fire protection/service water system: BWR-2,3		3.7
K6.03	Condensate transfer system: BWR-2,3		3.8
K6.04	Plant air systems: BWR-2,3		3.3*
K6.05	Primary containment isolation system: BWR-2,3		3.8
K6.06	Recirculation system: BWR-2,3		3.2
K6.07	A.C. power: BWR-2,3		3.2
K6.08	D.C. power: BWR-2,3	3.5	3.7

Tasks as noted previously

IMPORTANCE RO K/A NO. KNOWLEDGE **SRO** ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the ISOLATION (EMERGENCY) CONDENSER controls including: (CFR: 41.5 / 45.5) A1.01 3.8 A1.023.4 A1.03 3.5 A1.04 3.5 A1.05 4.2 A1.06 3.7 A1.07 3.7 A1.08 4.0 A1.09 3.7 A1.10 3.4 **A2.** Ability to (a) predict the impacts of the following on the ISOLATION (EMERGENCY) CONDENSER; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 4.5* A2.02 4.7* A2.03 PCIS signal resulting in system isolation: BWR-2,3 3.8* 4.0 A2.04 4.0 A2.05 4.0 A2.063.3 A2.07 3.5 A2.08 3.8* **A3.** Ability to monitor automatic operations of the **ISOLATION (EMERGENCY) CONDENSER including:** (CFR: 41.7 / 45.7) A3.01 3.7 A3.02 4.0 A3.03 3.7 A3.04 4.2 A3.05 3.8 A3.06 3.3 A3.07 3.3 A3.08 3.4

Tasks as noted previously

K/A NO. A4.	KNOWLEDGE Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	SRO
A4.01	Isolation condenser level: BWR-2,3	3.8
A4.02	Steam line pressure: BWR-2,3	3.3
A4.03	Primary and shell side temperatures: BWR-2,3	3.2
A4.04	Vent line radiation levels: BWR-2,3	4.0
A4.05	Major system valves: BWR-2,3	3.7
A4.06	Shell side makeup valves: BWR-2,3	4.0
A4.07	Manually initiate the isolation condenser: BWR-2,3	4.3*

TASK: Fill the core spray systems

Perform lineups on the core spray systems

Place the core spray system in standby readiness

Monitor automatic operation of the core spray system

Shutdown the core spray cooling system

Fill the reactor cavity from the condensate storage tank with the core spray system

Perform core spray pump flow rate test

Perform core spray simulated automatic actuation test

Perform core spray pump operability test

Perform core spray subsys and low pressure coolant injection subsys discharge piping ventilation

Perform core spray system inop test

Conduct core spray motor operated valve operability test

	INFORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between LOW PRESSURE CORE SPRAY SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Condensate storage tank: Plant-Specific	3.1
K1.02	Torus/suppression pool	3.4
K1.03	Keep fill system	3.0
K1.04	condensate transfer system	2.4
K1.05	Automatic depressurization system	3.7
K1.06	Plant air systems	2.1*
K1.07	D.C. electrical power	2.7
K1.08	A.C. electrical power	3.3
K1.09	Nuclear boiler instrumentation	3.4
K1.10	Emergency generator	3.8
K1.11	Drywell coolers: Plant-Specific	2.6
K1.12	ECCS room coolers	3.1
K1.13	Leak detection	3.0
K1.14	Reactor vessel	3.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Pump power	3.1*
K2.02	Valve power	2.7*
K2.03	Initiation logic	3.1*

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K3.	Knowledge of the effect that a loss or malfunction of the LOW PRESSURE CORE SPRAY SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04 K3.05	Reactor water level ADS logic Emergency generators Component cooling water systems Drywell cooling: Plant-Specific	. 3.8 . 2.9 . 2.1*	3.9 3.9 3.0 2.2 2.7
K4.	Knowledge of LOW PRESSURE CORE SPRAY SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06 K4.07 K4.08 K4.09	Prevention of overpressurization of core spray piping Prevents water hammer Motor cooling Line break detection Pump minimum flow Adequate pump net positive suction head Pump operability testing Automatic system initiation Load sequencing Testability of all operable components	. 3.0 . 2.4 . 3.0 . 2.6 . 2.6 . 2.8 . 3.8 . 3.3	3.4 3.2 2.5 3.2 2.6 2.9 3.0 4.0 3.5 2.9
K5.	Knowledge of the operational implications of the following concepts as they apply to LOW PRESSURE CORE SPRAY SYSTEM: (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03 K5.04 K5.05 K5.06	Indications of pump cavitation Differential pressure indication Testable check valve operation Heat removal (transfer) mechanisms System venting Recirculation operation: Plant-Specific(BWR-1)	. 2.4 . 2.3 . 2.8 . 2.5	2.7 2.6 2.4 2.9 2.5 4.0
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the LOW PRESSURE CORE SPRAY SYSTEM: (CFR: 41.7/45.7)		
K6.01 K6.02 K6.03	A.C. power Emergency generators Torus/suppression pool water level	. 3.8	3.4 3.9 3.4

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K6.04	D.C. power	2.9
K6.05	ECCS room cooler(s)	2.9
K6.06	Pump motor cooler(s)	2.4
K6.07	Pump seal cooler(s)	2.3
K6.08	Keep fill system	3.0
K6.09	Fire protection: BWR-1	3.3
K6.10	ECCS room integrity: Plant-Specific	2.5
K6.11	ADS	3.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the LOW PRESSURE CORE SPRAY SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	Core spray flow	3.6
A1.02	Core spray pressure	3.4
A1.03	Reactor water level 3.8	3.9
A1.04	Reactor pressure 3.7	3.7
A1.05	Torus/suppression pool water level	3.6
A1.06	Motor amps	2.4
A1.07	Emergency generator loading	3.1
A1.08	System lineup	3.2
A2.	Ability to (a) predict the impacts of the following on the LOW PRESSURE CORE SPRAY SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Pump trips	3.4
A2.02	Valve closures	3.2
A2.03	A.C. failures	3.6
A2.04	D.C. failures	3.0
A2.05	Core spray line break	3.6
A2.06	Inadequate system flow	3.2
A2.07	Loss of room cooling	2.8
A2.08	Valve openings	3.1
A2.09	Low suppression pool level	3.3
A2.10	†High suppression pool temperature	3.4
A2.11	†Loss of fire protection: BWR-1	3.3

Tasks as noted previously

IMPORTANCE K/A NO. **ABILITY** RO SRO **A3.** Ability to monitor automatic operations of the LOW PRESSURE CORE SPRAY SYSTEM including: (CFR: 41.7 / 45.7) A3.01 3.6 A3.02 3.7 A3.03 3.5 A3.04 3.6 A3.05 3.9 A3.06 3.5 A4. Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) A4.01 3.6 A4.02 3.4 A4.03 3.6 A4.04 Minimal flow valves 2.9 2.9 A4.05 3.6 A4.06 2.4 2.8 A4.07 A4.08 3.9 A4.09 3.5 A4.10 3.8 A4.11 3.6 A4.12 3.5 A4.13 3.4 A4.14 3.6

TASK: Perform lineups on the main steam system

Startup the main steam system (cold)

Operate the main steam isolation valves

Place the automatic pressure relief valves in service

Monitor the main steam system

Perform main steam isolation valve (MSIV) fast closure test (MSIV operability testing)

Perform main steam line high radiation functional test perform MSIV's, steam line drain valves and reactor sample valves logic functional test

Perform main mechanical vacuum pump and valve

Isolation system functional test

Perform main steam isolation valve, main steam drain valve and reactor water sample valve simulated automatic isolation test

Perform main steam isolation valves limit switch instrument functional test

Perform main steam line closure scram (MSLCS) operational test

Perform one train MSLCS inop surveillance

Perform main steam leakage control system operational test (write in)

Perform one train main steam leakage control system operability surveillance (write in)

Perform monthly main steam leakage control system division 1 and division 2 fan and heater tests (write in)

K/A NO.	KNOWLEDGE RO	SRC
K1.	Knowledge of the physical connections and/or cause-effect relationships between MAIN AND REHEAT STEAM SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor vessel	3.4
K1.02	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8
K1.03	Main turbine	3.4
K1.04	Moisture separators	2.9
K1.05	Moisture separator reheaters: Plant-Specific	2.8
K1.06	Steam bypass system 3.4	3.4
K1.07	Offgas system	3.1
K1.08	Condenser air removal system	3.1
K1.09	Steam seal/gland seal system	2.8
K1.10	Extraction steam system	2.8
K1.11	High pressure heater drains and vents	2.5
K1.12	Plant air systems	2.6
K1.13	Main steam isolation valve leakage control: Plant-	
	Specific	2.8
K1.14	Positive leakage control system: Plant Specific	3.0
K1.15	Process computer/ performance monitor system	2.1
K1.16	Process radiation monitoring system	3.4

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K1.17 K1.18 K1.19	Containment system High pressure coolant injection: Plant-Specific Reactor core isolation cooling system: Plant-Specific		3.2 3.6
K1.20 K1.21 K1.22 K1.23 K1.24 K1.25 K1.26 K1.27	Residual heat removal system: Plant-Specific Isolation condenser system: Plant-Specific Feedwater system Reactor water level control system Head vent Relief valves Safety valves Reactor protection system	. 2.9 . 3.7 . 3.1 . 3.2 . 2.7 . 3.5 . 3.7	3.2 2.9 3.7 3.2 3.3 2.7 3.5 3.8 4.1
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02	Main steam isolation valve solenoids Main steam line shutoff valves (guard valves): Plant-Specific		3.3* 2.3*
K3.	Knowledge of the effect that a loss or malfunction of the MAIN AND REHEAT STEAM SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04	Turbine generator Condenser Reactor feedpump turbines: Plant-Specific Offgas system	. 3.1	3.3 3.2 3.3 2.9
K3.04 K3.05 K3.06 K3.07 K3.08	Condenser air removal Seal steam/gland and seal system Containment Decay heat removal	. 2.8 . 2.6 . 3.1	2.9 2.9 2.7 3.3 3.5
K3.09 K3.10	Steam bypass capability High pressure coolant injection system: Plant- Specific Reactor core isolation cooling system: Plant-Specific	. 3.6	3.7 3.5
K3.12 K3.13 K3.14 K3.15 K3.16 K3.17	Isolation condenser: Plant-Specific Moisture separator reheaters: Plant-Specific Residual heat removal system: Plant-Specific Reactor water level control Relief/safety valves Reactor vessel and internals	. 3.7 . 2.4 . 2.7 . 3.5 . 3.6	3.3 3.7 2.4 2.7 3.5 3.6 3.3

Tasks as noted previously

K/A NO.	KNOWLEDGE INFORTANCE	RO	SRO
K4.	Knowledge of MAIN AND REHEAT STEAM SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02	Automatic isolation of steam lines	3.8	3.8
	Plant-Specific	3.1	3.2
K4.03	Insures that steam released from a steam line break will not bypass suppression pool; BWR-6	3.2	3.3
K4.04	Limits steam flow during a steam line rupture to 200%		3.5
K4.05	Steam flow measurement		3.2
K4.06	Allows for removal or prevents escape of radioactive	5.1	3.2
14.00	steam from systems that have leaky MSIV's	3 1	3.2
K4.07			3.7
K4.07 K4.08	Over pressure control	3.7	3.7
K4.09	area	2.5	2.6
	opening	3.3	3.3
K4.10	Moisture removal from steam lines prior to admitting steam	2.9	3.0
K4.11	Positive sealing of the MSIV's when shutdown: Plant-		
	Specific	2.9	3.1
K5.	Knowledge of the operational implications of the following concepts as they apply to MAIN AND REHEAT STEAM SYSTEM: (CFR: 41.5 / 45.3)		
K5.01	Constant anthology armonaion through a valva	2.0*	2.2*
	Constant enthalpy expansion through a valve		
K5.02	Definition and causes of steam/water hammer		3.1
K5.03	Definition and causes of thermal stress	2.7	2.9
K5.04	Definition and reason for steam blanketing of moisture		
	separator reheater: Plant-Specific	1.8*	1.9*
K5.05	Flow indication	2.8	2.8
K5.06	Air operated MSIV's	2.8	2.9
K5.07	Hydraulic operated MSIV's		2.7
K5.08	Solenoid operated valves		2.7
K5.09	Decay heat removal		3.5
113.07	Boody near removal	J. 1	3.3
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the MAIN AND REHEAT STEAM SYSTEM: (CFR: 41.7/45.7)		
K6.01	Electrical power	3 1	3.3
K6.02	•		3.3
	Plant air systems		
K6.03	Safety valve operability	3.0	3.6

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
K6.04	Relief valve operability: Plant-Specific		3.5
K6.05	Steam line integrity		3.7
K6.06	MSIV isolation signal		3.9
K6.07	MSIV leakage control	2.8	3.2
K6.08	Main condenser vacuum		3.4
K6.09	PCIS/NSSSS		4.1*
K6.10	ADS/low low set: Plant-Specific	3.6	3.7
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the MAIN AND REHEAT STEAM SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Main steam pressure	3.6	3.6
A1.02	Main steam temperature		2.6
A1.03	Reheat steam pressure: Plant-Specific		2.2*
A1.04	Reheater temperature: Plant-Specific		2.3
A1.05	Main steam line radiation monitors		3.6
A1.06	Air ejector process radiation monitor		3.4
A1.07	Reactor water level		3.7
A1.08	Reactor pressure		3.8
A1.09	Main steam flow		3.4
A1.10	Reactor power		3.8
A2.	Ability to (a) predict the impacts of the following on the MAIN AND REHEAT STEAM SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Malfunction of reactor turbine pressure regulating		
	system	3.8	3.9
A2.02	Change in steam demand and its effect on reactor pressure and power	3.6	3.8
A2.03	MSIV closure		4.2
A2.03 A2.04	Main steam line low pressure		3.6
A2.05	†Main steam line high radiation		4.2*
A2.06	Turbine trip without bypass valves		4.3*
A2.00 A2.07		4.1	4.5
A4.07	Main steam area high temperature or differential temperature high	3.8	3.9
A2.08	Low condenser vacuum		3.6
A2.09	Opening of head vent to drywell equipment sump with		
	pressure in the reactor vessel	3.4	3.7
A2.10	Closure of one or more MSIV's at power		3.9

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
A2.11 A2.12 A2.13 A2.14	Steam line break 4.1 PCIS/NSSSS actuation 4.2* High reactor water level 3.5 Inadvertent initiation of HPCI/HPCS/RCIC (steam	4.3* 4.3* 3.7
112.11	quality and steam flow): Plant-Specific	3.5
A3.	Ability to monitor automatic operations of the MAIN AND REHEAT STEAM SYSTEM including: (CFR: 41.7/45.7)	
A3.01	Isolation of main steam system	4.1*
A3.02	Opening and closing of drain valves as turbine load	2.0
A3.03	changes: Plant-Specific	2.9
A3.03	Specific	2.8
A3.04	Isolation of moisture separator reheater: Plant-Specific	2.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	MSIV's	4.0
A4.02	Maim steam line drain valves	3.2
A4.03	System flow	3.5
A4.04	System pressure	3.7
A4.05	System temperature	2.7
A4.06	System radiation levels	3.8
A4.07	Lights and alarms	3.3
A4.08	Reactor water level	3.7
A4.09	Reactor pressure	3.9
A4.10	Reactor power 3.8	3.8
A4.11	Alternate methods of verifying valve positions	3.3

TASK: Perform lineups of the main turbine generator

Start up the turbine to rated speed

Perform generator excitation

Operate generator voltage regulator

Synchronize turbine generator with output grid at minimum load

Increase load on the turbine generator

Monitor the turbine generator

Secure the amplidyne (generator in service)

Return the amplidyne to service

Unload the turbine generator electrically to minimum load

Secure generator output and excitation

Shut down the turbine generator

Operate the turbine turning gear

Operate the turbine bearing lift oil pumps (jacking oil pumps)

Synchronize turbine generator with output grid at minimum load

Increase load on the turbine generator

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	A. C. electrical distribution	2 3.3
K1.02	Condensate system	5 2.5
K1.03	Main steam system	2 3.3
K1.04	Reactor protection system	3.7
K1.05	Extraction steam system	7 2.7
K1.06	Component cooling water systems 2.6	
K1.07	Plant air systems	
K1.08	Reactor/turbine pressure control system: Plant-	
	Specific	4 3.5
K1.09	D. C . electrical distribution	
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Stator water cooling pumps: Plant-Specific	* 2.4
K2.02	Main lubricating oil pumps	
K2.03	Amplidyne: Plant-Specific	
K2.04	Hydrogen seal oil pumps	
K2.05	Air seal oil pumps: Plant-Specific	
K2.06	Turbine supervisory instrumentation	

IMPORTANO K/A NO.		RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS will have on following: (CFR: 41.7 / 45.4)		
K3.01	A.C. electrical distribution	3.4	3.7
K3.02	Reactor pressure		4.0
K3.03	Reactor power		4.0
K3.04	Reactor feedwater system (feedwater heaters)		3.5
K3.05	Reactor feedwater pump: Plant-Specific		2.8
K3.06	Condensate system		2.5
K3.07	Reactor protection system		3.7
K3.08	Reactor/turbine pressure control system: Plant-		
	Specific	3.7	3.8
K4.	Knowledge of MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Bearing lubrication	2.4	2.5
K4.02	Generator cooling		2.5
K4.03	Sealing to prevent hydrogen leakage		2.8
K4.04	Hydrogen cooling		2.5
K4.05	Turbine protection		3.0
K4.06	Generator protection		2.8
K4.07	Generator voltage regulation		2.6
K4.08	Moisture removal from turbine steam		2.4
K4.09	Turbine control		3.2
K4.10	Extraction steam		2.7
K5.	Knowledge of the operational implications of the following concepts as they apply to MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS: (CFR: 41.5 / 45.3)		
K5.01	Heat exchanger operation	2.3*	2.3*
K5.02	Turbine operation and limitations		3.1
K5.03	Hydraulically operated valve operation		2.6
K5.04	Turbine speed measurement		2.0*
K5.05	Relief valve operation		2.4
K5.06	Turbine shaft sealing		2.6
K5.07	Generator operations and limitations		2.9
K5.08	Generator cooling		2.6
110.00	200000000000000000000000000000000000000		2.0

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS: (CFR: 41.7/45.7)	
K6.01	Gland seal	2.9
K6.02	Reactor/turbine pressure control system: Plant-Specific	3.7
K6.03	Hydrogen seal oil	3.1
K6.04	Hydrogen cooling	2.7
K6.05	Stator water cooling	2.9
K6.06	Electrical distribution	3.2
K6.07	Extraction steam	2.5
K6.08	Main steam	3.1
K6.09	Voltage regulation	2.5*
K6.10	Lube oil system	2.9
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS controls including: (CFR: 41.5/45.5)	
A1.01	Generator megawatts	2.7
A1.02	Turbine speed	2.5
A1.03	Turbine valve position	2.7
A1.04	Steam flow	2.8
A1.05	Reactor pressure	3.4
A1.06	Condenser vacuum	3.2
A1.07	First stage turbine pressure	2.8
A1.08	Generator output voltage/reactive load	2.7
A2.	Ability to (a) predict the impacts of the following on the MAIN TURBINE GENERATOR AND AUXILIARY SYSTEMS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Turbine trip	3.9
A2.02	Loss of lube oil	3.5
A2.03	Loss of condenser vacuum	3.6
A2.04	Reactor scram	3.8
A2.05	Generator trip	3.8
A2.06	Loss of extraction steam	3.1

IMPORTANCE			
K/A NO.	ABILITY	RO	SRO
A2.07	Loss of reactor/turbine pressure control system:		
		3.8	3.9
A2.08	Turbine rotor bow	2.3	2.6
A2.09	Turbine vibration	2.5	2.8
A3.	Ability to monitor automatic operations of the MAIN		
	TURBINE GENERATOR AND AUXILIARY SYSTEMS including:		
	(CFR: 41.7 / 45.7)		
A3.01	Turbine trip	3.6	3.6
A3.02	Turbine roll to rated speed	2.8	2.8
A3.03	Generator megawatt output	2.8	2.9
A3.04	Turbine speed	2.7*	2.8
A3.05	Control valve operation	3.0	3.1
A3.06	Turbine lube oil pressure	2.5	2.6
A3.07	Hydrogen seal oil pressure	2.5	2.6
A3.08	Hydrogen gas pressure	2.5	2.6
A3.09	Hydrogen gas temperature	2.4	2.5
A3.10	Generator output voltage/reactive load	2.5	2.6
A3.11	Generator power factor: Plant-Specific	1.8*	2.1*
A3.12	Automatic turbine control: Plant-Specific	3.3	3.5
A4.	Ability to manually operate and/or monitor in the		
	control room:		
	(CFR: 41.7 / 45.5 to 45.8)		
A4.01	Turbine lube oil pumps	2.7	2.7
A4.02	Generator controls	3.1	2.9
A4.03	Stator water cooling pumps: Plant-Specific	2.7	2.8
A4.04	Hydrogen seal oil pumps	2.7	2.7
A4.05	Generator megawatt output	2.7	2.7
A4.06	Turbine speed	2.7	2.6
A4.07	Turbine valve position	2.9	2.9
A4.08	Turbine oil pressure	2.7	2.7
A4.09	Hydrogen seal oil pressure	2.6	2.6
A4.10	Hydrogen gas pressure	2.6	2.6
A4.11	Hydrogen gas temperature	2.4	2.4*
A4.12	Generator output voltage	2.6	2.6
A4.13	Generator power factor: Plant-Specific	1.9*	2.1*
A4.14	Generator megavar output	2.5	2.5

TASK: Lineup the reactor core isolation cooling (RCIC) system

Manually operate and adjust reactor core isolation cooling system flow with the turbine governor

Manually initiate startup of the reactor core isolation cooling (RCIC) system

Operate RCIC pump in different modes

Monitor RCIC operation Shutdown RCIC

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08	Condensate storage and transfer system3.5Nuclear boiler system3.5Suppression pool3.6Main condenser2.6Residual heat removal system2.6Plant air systems: Plant-Specific2.3*Leak detection3.1Line fill pump: Plant-Specific3.3	3.5 3.5 2.6 2.6 2.3* 3.2 3.4
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02 K2.03 K2.04	Motor operated valves2.8*RCIC initiation signals (logic)2.8*RCIC flow controller2.7*Gland seal compressor (vacuum pump)2.6*	2.8* 2.9* 2.8* 2.6*
K3.	Knowledge of the effect that a loss or malfunction of the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) will have on following: (CFR: 41.7 / 45.4)	
K3.01 K3.02 K3.03 K3.04	Reactor water level3.7Reactor vessel pressure3.6Decay heat removal3.5Adequate core cooling3.6	3.7 3.6 3.5 3.6
K4.	Knowledge of REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02	Prevent water hammer: Plant-Specific	2.8 3.3

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K4.03	Prevents pump over heating	2.9	3.0
K4.04	Prevents turbine damage: Plant-Specific		3.1
K4.05	Prevents radioactivity release to auxiliary/reactor		
	building	3.2	3.5
K4.06	Manual initiation		3.5
K4.07	Alternate supplies of water	3.6	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR CORE ISOLATION COOLING SYSTEM (RCIC): (CFR: 41.5 / 45.3)		
K5.01	Indications of pump cavitation	2.6*	2.6*
K5.02	Flow indication		3.1
K5.03	Differential pressure indication		2.6
K5.04	Testable check valve operation		2.7
K5.05	Centrifugal pump operation		2.4*
K5.06	Turbine operation		2.7
K5.07	Assist core cooling		3.1
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC): (CFR: 41.7 / 45.7)		
K6.01	Electrical power	3.4	3.5
K6.02	Plant air systems		2.2*
K6.03	Suppression pool water supply		3.5
K6.04	Condensate storage and transfer system		3.5
	ABILITY		
Al.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) controls including: (CFR: 41.5 / 45.5)		
A1.01	RCIC flow	3.7	3.7
A1.02	RCIC pressure	3.3	3.3
A1.03	Reactor water level	4.0	4.0
A1.04	Reactor pressure		3.6*
A1.05	RCIC turbine speed	3.7	3.7
A1.06	Condensate storage tank level	3.2	3.3
A1.07	Suppression pool level		3.5
A1.08	Suppression pool temperature	3.5	3.6

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
A2.	Ability to (a) predict the impacts of the following on the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)		
A 2 O1	System initiation signal	2.0	27
A2.01	System initiation signal		3.7
A2.02	Turbine trips		3.7
A2.03	Valve closures		3.3
A2.04	A.C. power loss		2.3*
A2.05	D.C. power loss		3.3
A2.06	Loss of applicable plant air systems		2.2*
A2.07	Loss of lube oil		3.1
A2.08	Loss of lube oil cooling		3.1
A2.09	Loss of vacuum pump		3.0
A2.10	Turbine control system failures		3.1
A2.11	Inadequate system flow		3.2
A2.12	Valve openings		3.0
A2.13	Loss of room cooling		3.0
A2.14	Rupture disc failure: Exhaust-Diaphragm	3.3	3.4
A2.15	Steam line break	3.8	3.8
A2.16	Low condensate storage tank level	3.5	3.4
A2.17	High suppression pool level	3.2	3.4
A2.18	Low suppression pool level	3.1	3.2
A2.19	High suppression pool temperature	3.5	3.6
A3.	Ability to monitor automatic operations of the REACTOR CORE ISOLATION COOLING SYSTEM (RCIC) including: (CFR: 41.7 / 45.7)		
A3.01	Valve operation	3.5	3.5
A3.02	Turbine startup		3.5
A3.03	System pressure		3.6
A3.04	System flow		3.5
A3.05	Reactor water level		3.9
A3.06	Lights and alarms		3.4
A3.00	Lights and drains	3.3	5.4
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	RCIC turbine speed	3 7	3.7
A4.02	Turbine trip throttle valve reset		3.7
A4.02 A4.03	•		3.9
A4.03 A4.04	System valves		3.5 3.6
A4.04	Manually initiated controls	5.0	3.0

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRC
A4.05	Reactor water level	4.1	4.1
A4.06	Suppression pool level	3.6	3.7
A4.07	Reactor pressure	3.9	3.8
A4.08	System flow		3.6
A4.09	System pressure	3.7	3.6
A4.10	Lights and alarms	3.6	3.5
A4.11	Condensate storage tank level	3.5	3.5

TASK: Perform lineups on the recirculation system

Vent recirculation pump seals

Startup a recirculation pump (startup a second recirculation pump)

Operate recirculation pumps in various control modes (adjust the recirculation flow using "master manual" control)

Monitor recirculation pumps in operation

Monitor jet pump operation

Secure a recirculation pump

Perform jet pump operability test

Conduct heatup and cooldown temperature checks

Conduct recirculation pump startup check of the delta temperature between the reactor coolant in the idle loop to the reactor vessel

Conduct recirculation pump trip logic system functional test

Conduct recirculation loop valve operability test

Conduct recirculation system valve testing

What if jet pumps not operating within required operating band

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RECIRCULATION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Core flow	3.7
K1.02	Reactor power	
K1.03	Reactor moderator temperature	
K1.04	Reactor/turbine pressure regulating system: Plant-	3.3
111.01	Specific	3.3
K1.05	Reactor pressure	
K1.06	Jet pumps	
K1.07	Component cooling water systems	
K1.08	A.C. electrical	
K1.09	D.C. electrical	
K1.10	Control rod drive system: Plant-Specific	
K1.11	Drywell equipment drain sump	
K1.12	Recirculation system motor-generator sets: Plant-	
	Specific	3.6
K1.13	Jet pump ring header and risers: Plant-Specific	3.2
K1.14	Rod block monitor: Plant-Specific	3.2
K1.15	Nuclear boiler instrumentation (reactor water	
	level/pressure)	3.2
K1.16	Low pressure coolant injection logic: Plant-Specific	3.9
K1.17	Vessel bottom head drain temperature	3.3
K1.18	RHR shutdown cooling mode	3.3
K1.19	Feedwater flow	3.2
K1.20	Plant air systems: Plant-Specific	
K1.21	Reactor water cleanup system	2.6

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.22	Reactor water level	3.6
K1.23	Average power range monitor flow converters: Plant-	
	Specific 3.4	3.5
K1.24	Isolation condenser: Plant-Specific	
K1.25	Reactor water sampling system	
K1.26	Recirculation flow control system: Plant-Specific	2.7
	ATWIC circuitant Digit Charific	4.2*
K1.27	ATWS circuitry: Plant-Specific	4.3*
K1.28	End-of-cycle recirculation pump trip circuitry:	
	Plant-Specific	4.1
K2.	Knowledge of electrical power supplies to the	
	following:	
	(CFR: 41.7)	
K2.01	Recirculation pumps: Plant-Specific	
K2.02	MG sets: Plant-Specific	3.3
K2.03	Recirculation system valves	* 2.8*
K2.04	Hydraulic power unit oil pumps: Plant-Specific	* 2.5*
K2.05	MG set oil pumps: Plant-Specific	
K3.	Knowledge of the effect that a loss or malfunction of	
	the RECIRCULATION SYSTEM will have on following:	
	(CFR: 41.7/45.4)	
	(CILC TITT IST)	
K3.01	Core flow	3.6
K3.02	Load following capabilities: Plant-Specific	
K3.03	Reactor power	
K3.04	Reactor water level	
K3.05	Recirculation system MG sets: Plant-Specific	
K3.06	Low pressure coolant injection logic: Plant-Specific	
K3.07	Vessel bottom head drain temperature	
K3.08	Shutdown cooling system	
K3.09	Reactor water cleanup system	* 2.5*
K3.10	Average power range monitor flow converters	3.4
K3.11	Component cooling water systems	* 2.3*
K3.12	Isolation condenser: Plant-Specific	3.0
K3.13	Reactor water sampling system	
K3.14	Primary containment integrity: Plant-Specific	
110.11	Timaly comminent integrity. Train specific	3.3
K4.	Knowledge of RECIRCULATION System design feature(s)	
	and/or interlocks which provide for the following:	
	(CFR: 41.7)	
K4.01	2/3 core coverage: Plant-Specific	3.9
K4.02	Adequate recirculation pump NPSH	
K4.03	Recirculation pump motor cooling	
K4.04	Controlled seal flow	
K4.05	Seal cooling	
IX+.UJ	Scar cooming 2.9	. 4.3

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K4.06	Automatic voltage/frequency regulation: Plant-	2 64	2.7
TT 1 0 5	Specific		2.7
K4.07	Motor generator set trips: Plant-Specific		2.9
K4.08	Oil pump automatic starts: Plant-Specific		2.9
K4.09	Pump minimum flow limit: Plant-Specific		2.9
K4.10	Pump start permissives: Plant-Specific	. 3.3	3.4
K4.11	Limitation of recirculation pumps flow mismatch:		
	Plant-Specific	. 3.1	3.5
K4.12	Minimization of reactor vessel bottom head temperature		
	gradients: Plant-Specific		3.5
K4.13	†End of cycle recirculation pump trip: Plant-Specific	. 3.7	4.0*
K4.14	ATWS: Plant-Specific	. 4.0	4.1*
K4.15	Slow speed pump start: Plant-Specific		3.4
K4.16	Recirculation pump downshift/runback: Plant-Specific		3.6
K4.17	Fast speed pump start: Plant-Specific		3.5
K4.18	Automatic MG set start sequencing: Plant-Specific	. 2.8	3.0
	5	. =	
K5.	Knowledge of the operational implications of the		
	following concepts as they apply to RECIRCULATION		
	SYSTEM:		
	(CFR: 41.5/45.3)		
	(CIR. 41.5/ 45.5)		
K5.01	Indications of pump cavitation	2.7	2.8
K5.02	Jet pump operation: BWR-3,4,5,6		3.2
K5.03	Pump/motor cooling: Plant-Specific		2.7
K5.04	System venting		2.6
K5.05	End of cycle recirculation pump trip: Plant-Specific		3.6
	• • • • • •		
K5.06	ATWS RPT: Plant-Specific		3.7
K5.07	Natural circulation: Plant-Specific		3.4
K5.08	E/P converters: Plant-Specific		2.1*
K5.09	Hydraulically operated valves: Plant-Specific		2.6*
K5.10	Motor generator set operation: Plant-Specific	. 2.8*	2.8

K6.	Knowledge of the effect that a loss or malfunction of		
	the following will have on the RECIRCULATION SYSTEM:		
	(CFR: 41.7 / 45.7)		
K6.01	Jet pumps: Plant-Specific		3.7
K6.02	Component cooling water systems		3.2
K6.03	A.C. power: Plant-Specific		3.0
K6.04	D.C. power: Plant-Specific		2.8
K6.05	Control rod drive system: Plant-Specific	. 2.7	2.7
K6.06	Recirculation system motor-generator sets: Plant-		
	Specific	. 3.1	3.1
K6.07	Feedwater flow		3.3
K6.08	Reactor water cleanup system		2.3
K6.09	Reactor water level		3.4

SYSTEM: 202001 Recirculation System Tasks as noted previously

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RECIRCULATION SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	Recirculation pump flow: Plant-Specific	3.5
A1.02	Jet pump flow	3.4
A1.03	Core flow	3.6
A1.04	Reactor water level	3.3
A1.05	Reactor power	3.9
A1.06	Recirculation pump motor amps	2.6
A1.07	Recirculation pump speed	2.8
A1.08	Recirculation FCV position: BWR-5,6	3.7
A1.09	Recirculation pump seal pressures	3.3
A1.10	Recirculation seal purge flows	2.7
A1.11	Vessel bottom head drain temperature	2.9
A1.12	Recirculation pump differential pressure: Plant-	2.7
111.12	Specific	2.6
A1.13	Recirculation loop temperatures: Plant-Specific	3.2
A1.14	Recirculation drive motor temperature: Plant-Specific	3.2
711.14		2.4
A1.15	Recirculation MG set temperatures: Plant-Specific	2.4
A1.16	Recirculation MG drive motor amps: Plant-Specific	2.3
A1.17	Recirculation MG set generator current, power,	2.3
A1.17	voltage: Plant-Specific	2.3
	voltage. Frant-specific	2.3
A2.	Ability to (a) predict the impacts of the following on the RECIRCULATION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	†Jet pump failure: Plant-Specific	3.9
A2.02	Recirculation system leak	3.9
A2.03	Single recirculation pump trip	3.7
A2.04	Multiple recirculation pump trip	3.8
A2.05	Inadvertent recirculation flow increase	4.0
A2.06	Inadvertent recirculation flow decrease	3.8
A2.07	Recirculation pump speed mismatch: Plant-Specific	3.3
A2.08	Recirculation flow mismatch: Plant-Specific	3.4
A2.09	Recirculation scoop tube lockup: Plant-Specific	3.4
A2.10	†Recirculation pump seal failure	3.9
A2.11	Low reactor water level 3.7	3.9
A2.12	Loss of reactor feedwater	3.8
A2.13	Carryunder	2.8
112.13	2.0	2.0

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
A 2 14	High master anasona (ATWC singuitan initiation).	
A2.14	High reactor pressure (ATWS circuitry initiation): Plant-Specific	4.2*
A2.15	End of cycle trip circuitry: Plant-Specific	3.9
A2.13 A2.16	, , , , ,	3.9
	Loss of seal purge flow (CRD)	
A2.17	Loss of seal cooling water	3.2
A2.18	Loss of motor cooling	3.1
A2.19	Loss of A.C. power: Plant-Specific	3.2
A2.20	Loss of D.C. power: Plant-Specific	2.9
A2.21	†Recirculation loop temperature out of spec: Plant-	
	Specific	3 7
A2.22	Loss of component cooling water	3.2
A2.23	Valve closures	3.2
A2.24	Valve opening	3.1
A2.25	Recirculation flow control valve lockup: Plant-	
	Specific	3.3
A2.26	Incomplete start sequence: Plant-Specific	3.1
A3.	Ability to monitor automatic operations of the	
	RECIRCULATION SYSTEM including:	
	(CFR: 41.7 / 45.7)	
A3.01	Valve operation	3.1
A3.02	Pump/MG set start sequence: Plant-Specific	3.0
A3.03	System flow	3.2
A3.04	Lights and alarms	3.1
A3.05	Pump speed: Plant-Specific	2.9
A3.06	Flow control valve position: BWR-5,6	3.6
A3.07	Pump trips: Plant-Specific	3.3
A3.08	Pump downshift: BWR-5,6	3.3
A3.09	MG set trip: Plant-Specific	3.3
	r	
A4.	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	Recirculation pumps	3.7
A4.02	System valves	3.4
A4.03	Reactor power	4.1
A4.04	System flow	3.7
A4.05	Lights and alarms	3.3
A4.06	Oil pumps	2.7
A4.07		2.7
	Vent fans: Plant-Specific	
A4.08	Motor-generator sets: Plant-Specific	3.1
A4.09	Reactor water level	3.7
A4.10	Seal flow: Plant-Specific	2.8
A4.11	Seal pressures: Plant-Specific	3.3
A4.12	Core flow	3.8
A4.13	Core differential pressure	3.3

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

TASK: Perform lineups on the low pressure coolant injection system

Place the low pressure coolant injection system in standby readiness

Monitor operational sequence of low pressure coolant injection (LPCI) system

Secure the low pressure coolant injection system

Perform LPCI subsystem logic system functional test

Perform LPCI mode inoperable test

Perform LPCI mov power supply simulated auto. act test and battery serv. tests

Conduct LPCI independent power supply weekly battery test

Conduct LPCI independent power supply performance discharge test

Perform low pressure coolant injection sound analysis and flow test (write in)

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Condensate storage and transfer system: Plant-	
	Specific	2.8
K1.02	Suppression pool	3.9
K1.03	Condensate transfer	2.6*
K1.04	Keep fill system	3.4
K1.05	Recirculation system: BWR-3,4	3.8
K1.06	Automatic depressurization	3.9
K1.07	D.C. electrical power	3.3
K1.08	A.C. electrical power	3.5
K1.09	Emergency generators	3.8
K1.10	ECCS room coolers	3.2
K1.11	Nuclear boiler instrumentation	3.7
K1.12	Plant air systems: Plant-Specific	2.7*
K1.13	Drywell pressure	4.0
K1.14	Shutdown cooling system: Plant-Specific	3.7
K1.15	Reactor building drain system: Plant-Specific	2.6
K1.16	Component cooling water systems	3.2
K1.17	Reactor pressure	4.0
K1.18	Reactor vessel: Plant-Specific	3.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Pumps	3.5*
K2.02	Valves	2.7*
K2.03	Initiation logic	2.9*

SYSTEM 203000 RHR/LPCI: Injection Mode (Plant Specific)

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K3.	Knowledge of the effect that a loss or malfunction of the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04	Reactor water level Suppression pool level Automatic depressurization logic Adequate core cooling	. 3.5 . 4.2*	4.4* 3.5 4.3* 4.6*
K4.	Knowledge of RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03 K4.04 K4.05	Automatic system initiation/ injection Prevention of piping overpressurization Pump minimum flow protection Pump motor cooling: Plant-Specific Prevention of water hammer	. 3.3 . 3.2 . 2.6	4.2 3.4 3.3 2.7 3.3
K4.06 K4.07 K4.08	Adequate pump net positive suction head (interlock suction valve open): Plant-Specific	. 3.7 . 3.3	3.5 3.9 3.4*
K4.09 K4.10	Surveillance for all operable components	. 3.9	3.4 4.1
K4.11 K4.12 K4.13	Loop selection logic: Plant-Specific System redundancy The prevention of leakage to the environment through LPCI/RHR heat exchanger: Plant-Specific	. 3.5	4.0 3.6 3.7
K4.14 K4.15	†Operation from remote shutdown panel Pump runout protection: Plant-Specific	. 3.6	3.7 2.5
K5.	Knowledge of the operational implications of the following concepts as they apply to RHR/LPCI: INJECTION MODE (PLANT SPECIFIC): (CFR: 41.5 / 45.3)		
K5.01 K5.02	Testable check valve operation		2.9 3.7
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC): (CFR: 41.7/45.7)		

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

Tasks as noted previously

K/A NO.	IMPORTANCE KNOWLEDGE RO) SRO
K6.01	A.C. electrical power	3.7
K6.02	D.C. electrical power	
K6.03	Emergency generator 3.7	
K6.04	Keep fill system	
K6.05	Condensate storage and transfer system: Plant-	3.3
	Specific	2.5
K6.07	Plant air systems: Plant-Specific	2.7
K6.08	ECCS room cooling	3.1
K6.09	Nuclear boiler instrumentation	3.4
K6.10	Component cooling water systems	3.1
K6.11	ADS 4.1	
K6.12	†ECCS room integrity	
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) controls including: (CFR: 41.5 / 45.5)	
A1.01	Reactor water level	2* 4.3
A1.02	Reactor pressure	* 4.0
A1.03	System flow	
A1.04	System pressure	
A1.05	Suppression pool level	
A1.06	Condensate storage tank level: Plant-Specific	
A1.07	Motor amps: Plant-Specific	
A1.08	†Emergency generator loading	
A1.09	Component cooling water systems	
A2.	Ability to (a) predict the impacts of the following on the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Inadequate net positive suction head	2 3.4
A2.02	Pump trips	
A2.03	Valve closures	2 3.3
A2.04	A.C. failures	5 3.6
A2.05	D.C. failures	3.2
A2.06	Emergency generator failure	3.9
A2.07	Pump seal failure	
A2.08	Inadequate room cooling	
A2.09	Inadequate system flow	
A2.10	Nuclear boiler instrument failures	

SYSTEM: 203000 RHR/LPCI: Injection Mode (Plant Specific)

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A2.11	Motor operated valve failures	3.6
A2.12	Pump runout	2.7*
A2.13	Valve Openings	3.3
A2.14	Initiating logic failure	3.9*
A2.15	Loop selection logic failure: Plant-Specific	4.2*
A2.16	Loss of coolant accident	4.5*
A2.17	Keep fill system failure	3.5
A3.	Ability to monitor automatic operations of the RHR/LPCI: INJECTION MODE (PLANT SPECIFIC) including: (CFR: 41.7 / 45.7)	
A3.01	Valve operation	3.7
A3.02	Pump start	3.9
A3.03	Pump discharge pressure	3.6
A3.04	System flow	3.7
A3.05	Reactor water level	4.4*
A3.06	Indicating lights and alarms	3.6
A3.07	Loop selection: Plant-Specific	4.6*
A3.08	System initiation sequence	4.1
A3.09	Emergency generator load sequencing	3.9*
A4.	Ability to manually operate and/or monitor in the	
	control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Pumps	4.1
A4.02	System valves	4.1
A4.03	Keep fill system	3.4
A4.04	Heat exchanger cooling flow	3.6
A4.05	Manual initiation controls	4.1
A4.06	System reset following automatic initiation: Plant-	• •
	Specific	3.9
A4.07	Reactor water level	4.5
A4.08	Reactor pressure	4.3
A4.09	System flow	4.0
A4.10 A4.11	Pump/system discharge pressure: Plant-Specific	3.6 3.5
A4.11 A4.12	Condensate storage tank level: Plant-Specific	2.6
A4.12 A4.13	Suppression pool level/temperature	3.9
A4.14	Testable check valves	2.7

TASK: Perform lineups of the residual heat removal (RHR) system

Fill and vent the residual heat removal system

Start up the residual heat removal system

Operate a residual heat removal heat exchanger

Perform purification of the residual heat removal system during shutdown cooling

Operate residual heat removal system with fuel pool cooling system

Monitor the residual heat removal system

Add chemicals to the residual heat removal system

Operate the residual heat removal system using the high pressure safety injection pumps

Shutdown the residual heat removal system

Drain the residual heat removal system

Fill the refueling cavity and/or dryer-separator using the residual heat removal system

Drain the refueling cavity and/or dryer-separator using the residual heat removal system

Perform RHR pump flow rate test

Perform residual heat removal pump operability test

Perform RHR service water pump flow rate test

Perform one RHR service water pump inoperable test

Perform one RHR pump inoperable test

Perform residual heat removal isolation valves, shutdown cooling valves and head spray simulated automatic actuation test

Perform residual heat removal service water pump and motor operated valve operability test

Conduct RHR valve testing

Conduct RHR isolation valve control logic system functional test

Monitor the residual heat removal system

Shutdown the residual heat removal system

Fill the refueling cavity and/or dryer-separator using the residual heat removal system

Drain the refueling cavity and/or dryer-separator using the residual heat removal system

Perform one residual heat removal service water pump inoperable test

Perform one residual heat removal pump inoperable test

Perform residual heat removal isolation valves, shutdown cooling valves and head spray simulated automatic actuation test

Conduct residual heat removal isolation valve control logic system functional test

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09 K1.10 K1.11 K1.12 K1.13 K1.14	Reactor pressure Reactor water level Recirculation loop temperature Fuel pool cooling assist: Plant-Specific Component cooling water systems A.C. electrical power D.C. electrical power LPCI Auxiliary steam supply: Plant-Specific RWCU Nitrogen: Plant-Specific Isolation Condenser: Plant-Specific Floor drain system: Plant-Specific Reactor temperatures (moderator, vessel, flange) RHR service water: Plant-Specific	. 3.6 . 3.4 . 2.7 . 3.1 . 3.2 . 2.4 . 3.9 . 2.2* . 1.8* . 2.4* . 1.7* . 3.6	3.6 3.6 3.5 2.7 3.1 3.3 2.6 3.9 2.2* 2.3* 1.8* 2.4* 1.7* 3.6 3.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K3.	Pump motors		3.1* 2.7*
K3.01 K3.02 K3.03 K3.04 K3.05	(CFR: 41.7/45.4) Reactor pressure Reactor water level: Plant-Specific Reactor temperatures (moderator, vessel, flange) Recirculation loop temperatures Fuel pool cooling assist: Plant-Specific	. 3.2 . 3.8 . 3.7	3.3 3.3 3.9 3.7 2.7
K4.	Knowledge of SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03	High temperature isolation: Plant-Specific High pressure isolation: Plant-Specific Low reactor water level: Plant-Specific	. 3.7	3.4 3.8 3.8

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K4.04	Adequate pump NPSH	2.6
K4.05	Reactor cooldown rate	3.7
K4.06	Motor cooling: Plant-Specific	2.3
K4.07	Pump minimum flow	2.8
K5.	Knowledge of the operational implications of the following concepts as they apply to SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE): (CFR: 41.5 / 45.3)	
K5.01	NPSH	2.4
K5.02	Valve operation	2.9
K5.03	Heat removal mechanisms	3.1
K5.04	System venting	2.4
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE): (CFR: 41.7/45.7)	
K6.01	A.C. electrical power	3.4
K6.02	D.C. electrical power	2.9
K6.03	Recirculation system	3.2
K6.04	Reactor water level	3.6
K6.05	Component cooling water systems	3.3
K6.06	Auxiliary steam supply: Plant-Specific	2.0*
K6.07	Nitrogen: Plant-Specific	1.8*
K6.08	RHR service water: Plant-Specific	3.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE) controls including: (CFR: 41.5 / 45.5)	
A1.01	Heat exchanger cooling flow	3.2
A1.02	SDC/RHR pump flow	3.2
A1.03	Recirculation loop temperatures	3.3
A1.04	SDC/RHR pump suction pressure	2.7
A1.05	Reactor water level	3.4
A1.06	Reactor temperatures (moderator, vessel, flange)	3.7
A1.07	Motor amps: PlantSpecific	2.1*
A1.08	Heat exchanger temperatures	2.9
A1.09	SDC/RHR pump/system discharge pressure	2.8

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
A1.10	Throttle valve position	2.9
A2.	Ability to (a) predict the impacts of the following on the SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08 A2.09 A2.10 A2.11 A2.12	Recirculation loop high temperature: Plant-Specific3.1Low shutdown cooling suction pressure: Plant-Specific2.6A.C. failure3.2D.C. failure2.5System isolation3.5SDC/RHR pump trips3.4Loss of motor cooling: Plant-Specific2.7Loss of heat exchanger cooling3.3Reactor low water level3.6Valve operation2.9Recirculation pump trips: Plant-Specific2.5Inadequate system flow2.9	3.3 2.7 3.2 2.6 3.7 3.5 2.7 3.5 2.9 2.7 3.0
A3.	Ability to monitor automatic operations of the SHUTDOWN COOLING SYSTEM (RHR SHUTDOWN COOLING MODE) including: (CFR: 41.7/45.7)	
A3.01 A3.02	Valve operation 3.2 Pump trips 3.2	3.1 3.2
A3.03	Lights and alarms	3.3
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	SDC/RHR pumps	3.7
A4.02	SDC/RHR suction valves	3.5
A4.03	SDC/RHR discharge valves	3.5
A4.04	Heat exchanger cooling water valves	3.3
A4.05	Minimum flow valves	3.2
A4.06	Reactor water level	3.7
A4.07	Reactor temperatures (moderator, vessel, flange)	3.7
A4.08	Reactor power: Plant-Specific	3.2
A4.09	System flow	3.1
A4.10	System pressures	3.0

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
A4.11	Heat exchanger cooling flow	3.2	3.2
A4.12	Recirculation loop temperatures	3.4	3.4

3.5	Containment Integrity	page
223001	Primary Containment System and Auxiliaries	3.5-3
223002	Primary Containment Isolation System	3.5-8
	/Nuclear Steam Supply Shut-Off	
290002	Reactor Vessel Internals	3.5-12
219000	RHR/LPCI: Torus/Suppression Pool Cooling Mode	3.5-15
226001	RHR/LPCI: Containment Spray System Mode	3.5-19
230000	RHR/LPCI: Torus/Suppression Pool Spray Mode	3.5-23
290001	Secondary Containment	3.5-28

This page left blank

TASK: Conduct lineups on the containment system

Conduct containment inerting-normal purge on startup

Conduct containment inerting-makeup operation

Ventilate the containment during heatup and startup

Conduct containment de-inerting Monitor the containment system in standby readiness

Pump torus water to radwaste (pump suppression pool water to radwaste)

Refill the torus/suppression pool from the condensate storage tank

Startup the suppression pool cleanup system (write in)

Shutdown the suppression pool cleanup system (write in)

Perform external visual inspection of suppression chamber after relief valve operation

Conduct pressure suppression chamber (PSC)-drywell vacuum breaker visual inspection

K/A NO.	KNOWLEDGE RO	SRC
K1.	Knowledge of the physical connections and/or cause-effect relationships between PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Containment isolation/integrity: Plant-Specific	3.9
K1.02	Drywell isolation/integrity: Plant-Specific	3.8
K1.03	Containment/drywell atmosphere control	3.3
K1.04	Drywell floor and equipment floor drain system	3.2
K1.05	Suppression pool makeup system: Mark-III	3.5
K1.06	RHR/LPCI 3.4	3.6
K1.07	Suppression pool cleanup system: Plant-Specific	2.5
K1.08	Relief/safety valves	3.8
K1.09	SBGT/FRVS: Plant-Specific	3.6
K1.10	Plant air systems	3.1
K1.11	Post accident sampling system	2.9
K1.12	LPCS: Plant-Specific	3.6
K1.13	HPCS: Plant-Specific	3.5
K1.14	RCIC: Plant-Specific	3.6
K1.15	HPCI: Plant-Specific	3.9
K1.16	Containment and drywell atmosphere monitoring:	
	Plant-Specific 3.3	3.4
K1.17	Reactor building HVAC: Plant-Specific	3.1
K1.18	Drywell pneumatic compressors: Plant-Specific 2.6	2.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Atmosphere containment/ atmospheric dilution compressors: Plant-Specific	2.1
K2 02	Drywell compressors 1.8*	1.1

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K2.03	Pumpback compressors: Plant-Specific	1.8*	1.8*
K2.04	Combustible gas mixing compressors: Mark-III		2.4
K2.05	Hydrogen recombiners: Plant-Specific		2.4*
K2.06	Hydrogen igniters: Plant-Specific		2.4
K2.07	Containment atmosphere monitoring system	. 2.3*	2.6*
K2.08	Containment cooling air handling units: Plant-		
	Specific	. 2.7	3.0*
K2.09	Drywell cooling fans: Plant-Specific		2.9*
K2.10	Drywell chillers: Plant-Specific		2.9*
K2.10	Dryweit enimers. Traint-specific	. 2.1	2.9
К3.	Knowledge of the effect that a loss or malfunction of		
	the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES will		
	have on following:		
	(CFR: 41.7 / 45.4)		
K3.01	Secondary containment		3.8
K3.02	Containment/drywell temperature: Plant-Specific	. 3.3	3.4
K3.03	Containment/drywell pressure: Plant-Specific	3.4	3.5
K3.04	Containment/drywell hydrogen gas concentration		3.5
K3.05	Containment/drywell oxygen gas concentration		3.2
K3.06		. 3.1	3.2
K3.00	Differential pressure between secondary and primary	2.2	2.6
	containment	. 3.3	3.6
K3.07	Differential pressure between suppression pool and		
	drywell/containment	3.1	3.2
K3.08	Pneumatically operated valves internal to		
	containment/drywell: Plant-Specific	2.7	2.9
K3.09	Nuclear boiler instrumentation		3.1
K3.10	Containment/drywell moisture content	. 2.4	2.6
K4.	Knowledge of PRIMARY CONTAINMENT SYSTEM AND		
11.7.	AUXILIARIES design feature(s) and/or interlocks which		
	provide for the following:		
	(CFR: 41.7)		
K4.01	Allows for absorption of the energy released during a		
	LOCA	3.7	3.8
K4.02	Contains fission products after a LOCA	3.6	3.7
K4.03	Containment/drywell isolation		3.8
K4.04	Prevents hydrogen from reaching an explosive mixture		3.8
		. 3.3	3.6
K4.05	Maintains proper suppression pool to drywell	2.6	2.1
	differential pressure	. 2.9	3.1
K4.06	Maintains proper containment/secondary containment to		
	drywell differential pressure	3.1	3.3
K4.07	Prevents localized heating of suppression pool (SRV		
	steam quenchers)	3 1	3.3
	scam quenemoto)	. 5.1	5.5

Tasks as noted previously

K6.14

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K5. Knowledge of the operational implications of the following concepts as they apply to PRIMARY **CONTAINMENT SYSTEM AND AUXILIARIES:** (CFR: 41.5 / 45.3) K5.01 3.3 K5.02 2.4 K5.03 2.9 K5.04 2.6 K5.05 3.0 K5.06 2.9 K5.07 2.4 K5.08 2.8 K5.09 2.9* K5.10 Hydrogen combustibility versus hydrogen concentration 3.1 K5.11 2.7 K5.12 2.8 K5.13 2.8 K5.14 2.8* K5.15 2.6 Knowledge of the effect that a loss or malfunction of K6. the following will have on the PRIMARY CONTAINMENT **SYSTEM AND AUXILIARIES:** (CFR: 41.7 / 45.7) K6.01 3.8 K6.02 3.6 K6.03 3.1 K6.04 2.8 K6.05 3.3 K6.06 3.0 K6.07 K6.08 3.4 K6.09 K6.10 3.2 K6.11 3.2 K6.12 3.0 K6.13 3.4

3.8

A2.02Steam bypass of suppression pool3.94.1A2.03Safety/relief valve leaking or stuck open4.04.2*A2.04High containment/drywell hydrogen concentration3.73.8A2.05High containment/drywell oxygen concentration3.53.6		IMPORTANCE		
Al. Ability to predict and/or monitor changes in parameters associated with operating the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES controls including: (CFR: 41.5/45.5) 3.6 A1.01 Drywell temperature 3.5 3.6 A1.02 Drywell pressure 3.6 3.7 A1.03 Containment pressure: Mark-III 3.3 3.4 A1.04 Containment temperature: Mark-III 3.3 3.4 A1.05 Hydrogen concentration 3.1 3.3 A1.06 Oxygen concentration 3.1 3.3 A1.07 Drywell/suppression chamber differential pressure (drywell to containment building): Plant-Specific 3.2 3.4 A1.08 Suppression pool level 3.5 3.6 A1.09 Suppression pool temperature 3.5 3.6 A1.10 Drywell/suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.11 A1.11 A5.11 A5.11	K/A NO	D. KNOWLEDGE	RO	SRO
Parameters associated with operating the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES controls including: (CFR: 41.5 / 45.5)		ABILITY		
A1.02 Drywell pressure	Al.	parameters associated with operating the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES controls including:		
A1.02 Drywell pressure	A1 01	Drywell temperature 3.5	3.6	
A1.03 Containment pressure: Mark-III				
A1.04 Containment temperature: Mark-III 3.3 3.4 A1.05 Hydrogen concentration 3.1 3.3 3.4 A1.06 Oxygen concentration 3.1 3.3 A1.07 Drywell/suppression chamber differential pressure (drywell to containment building): Plant-Specific 3.2 3.4 A1.08 Suppression pool level 3.5 3.6 A1.09 Suppression pool temperature 3.5 3.6 A1.10 Drywell leak detection system: Plant-Specific 3.4 3.6 A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6) A2.01 Loss of coolant accident 4.2* 4.4* A2.02 Steam bypass of suppression pool 3.9 4.1 A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.5 3.6 A2.05 High containment/drywell bydrogen concentration 3.5 3.6 A2.06 High containment/drywell bydrogen concentration 3.5 3.6 A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool tevel 3.6 3.8 A2.12 Abnormal suppression pool tevel 3.7 3.8 Bigh containment temperature: Mark-III 3.3 3.4 A2.13 High containment temperature: Mark-III 3.3 3.4 A2.11 Abnormal suppression pool temperature: Mark-III 3.3 3.4 A2.13 High containment temperature: Mark-III 3.3 3.4 A2.14 A2.15 ADATE A2.15 ADATE A2.16 ADATE A2.17 ADATE A2.18 ADA				
A1.05 Hydrogen concentration A1.06 Oxygen concentration A1.07 Drywell/suppression chamber differential pressure (drywell to containment building): Plant-Specific A1.08 Suppression pool level A1.09 Suppression pool level A1.00 Drywell leak detection system: Plant-Specific A1.10 Drywell leak detection system: Plant-Specific A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific A1.12 Moisture concentration A1.13 Again Abhormal suppression chamber differential pressure: Plant-Specific A1.14 Moisture concentration A1.15 Moisture concentration A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident A2.02 Steam bypass of suppression pool A2.03 Safety/relief valve leaking or stuck open A2.04 High containment/drywell hydrogen concentration A2.05 High containment/drywell oxygen concentration A2.06 High containment pressure: Mark-III A2.07 High drywell pressure A2.08 Compressor trips (loss of air): Plant-Specific A2.10 High drywell temperature A2.11 Abnormal suppression pool level A3.6 A3.8 A2.11 Abnormal suppression pool level A3.7 A8.8 A2.12 Abnormal suppression pool level A3.1 A3.2 A3.4 A3.6 A3.8 A3.1 A3.6 A3.1 A3.1 A3.1 A3.6 A3.1 A3.1 A3.1 A3.1 A3.1 A3.1 A3.2 A3.1 A3.1 A3.1 A3.2 A3.1 A3.1 A3.1 A3.2 A3.1 A3.1 A3.2 A3.1 A3.1 A3.2 A3.1 A3.2 A3.1 A3.2 A3.1 A3.2 A3.1 A3.2 A3		•		
A1.06 Oxygen concentration A1.07 Drywell/suppression chamber differential pressure (drywell to containment building): Plant-Specific A1.08 Suppression pool level A1.09 Suppression pool temperature A1.10 Drywell leak detection system: Plant-Specific A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific A1.12 Moisture concentration A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6) A2.01 Loss of coolant accident A2.02 Steam bypass of suppression pool A2.03 Safety/relief valve leaking or stuck open A2.04 High containment/drywell hydrogen concentration A2.05 High containment/drywell oxygen concentration A2.06 High containment pressure: Mark-III A2.07 High drywell pressure A2.08 Compressor trips (loss of air): Plant-Specific A2.09 Vacuum breaker malfunction A2.09 Vacuum breaker malfunction A2.10 High drywell temperature A2.11 Abnormal suppression pool level A3.10 Abnormal suppression pool level A3.11 Abnormal suppression pool level A3.12 Abnormal suppression pool lemperature A3.13 A4.14 Abnormal suppression pool lemperature A3.14 Abnormal suppression pool lemperature A3.15 High containment temperature: Mark-III A3.16 High containment temperature: Mark-III A3.17 A3.18 A3.19 A3.1				
A1.07 Drywell/suppression chamber differential pressure (drywell to containment building): Plant-Specific 3.2 3.4 A1.08 Suppression pool level 3.5 3.6 A1.10 Drywell leak detection system: Plant-Specific 3.4 3.6 A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident A2.02 Steam bypass of suppression pool A2.03 Safety/relief valve leaking or stuck open A2.04 High containment/drywell hydrogen concentration A2.05 High containment/drywell oxygen concentration A2.06 High containment pressure: Mark-III A2.07 High drywell pressure A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool temperature 3.7 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4				
Al.08 Suppression pool level 3.5 3.6 Al.09 Suppression pool temperature 3.5 3.6 Al.10 Drywell leak detection system: Plant-Specific 3.4 3.6 Al.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 Al.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident 4.3* 4.4* A2.02 Steam bypass of suppression pool 3.9 4.1 A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool temperature 3.7 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4 A2.14 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4 A2.14 Abnormal suppression pool temperature 3.7 3.8 A2.15 A2.16 A3 A3 A3 A4 A3.16 A4 A4 A4 A4 A4.17 A4 A4 A4 A4 A4.18 A4 A4 A4 A4.18 A4 A4 A4 A4.18 A4		• •	3.3	
A1.08 Suppression pool level 3.5 3.6 A1.09 Suppression pool temperature 3.5 3.6 A1.10 Drywell leak detection system: Plant-Specific 3.4 3.6 A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident 4.3* 4.4* A2.02 Steam bypass of suppression pool 3.9 4.1 A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.11 Abnormal suppression pool temperature 3.7 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A1.07		2.4	
A1.09 Suppression pool temperature A1.10 Drywell leak detection system: Plant-Specific A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific A1.12 Moisture concentration A1.13 Moisture concentration A1.14 Moisture concentration A1.15 Moisture concentration A1.16 Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6) A2.01 Loss of coolant accident A2.02 Steam bypass of suppression pool A2.03 Safety/relief valve leaking or stuck open A2.04 High containment/drywell hydrogen concentration A2.05 High containment/drywell oxygen concentration A2.06 High containment pressure: Mark-III A2.07 High drywell pressure A2.08 Compressor trips (loss of air): Plant-Specific A2.09 Vacuum breaker malfunction A2.10 High drywell temperature A2.11 Abnormal suppression pool level A3.6 A8.11 Abnormal suppression pool level A3.7 3.8 High containment temperature: Mark-III A3.3 3.4	A 1 00			
A1.10 Drywell leak detection system: Plant-Specific A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific A1.12 Moisture concentration A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident				
A1.11 Reactor building to suppression chamber differential pressure: Plant-Specific 3.1 3.2 A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident 4.3* 4.4* A2.02 Steam bypass of suppression pool 3.9 4.0 4.2* A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool temperature 3.7 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4				
Pressure: Plant-Specific 3.1 3.2 A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)			3.0	
A1.12 Moisture concentration 2.5 2.6 A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations:	A1.11		2.2	
A2. Ability to (a) predict the impacts of the following on the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident	A 1 10			
the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Loss of coolant accident	A1.12	Moisture concentration 2.5	2.6	
A2.02 Steam bypass of suppression pool 3.9 4.1 A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.	the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations:		
A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.01	Loss of coolant accident	4.3*	4.4*
A2.03 Safety/relief valve leaking or stuck open 4.0 4.2* A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.02	Steam bypass of suppression pool	3.9	4.1
A2.04 High containment/drywell hydrogen concentration 3.7 3.8 A2.05 High containment/drywell oxygen concentration 3.5 3.6 A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.03	Safety/relief valve leaking or stuck open	4.0	4.2*
A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.04			3.8
A2.06 High containment pressure: Mark-III 4.1* 4.1* A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.05	High containment/drywell oxygen concentration	3.5	3.6
A2.07 High drywell pressure 4.2* 4.3* A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.06			4.1*
A2.08 Compressor trips (loss of air): Plant-Specific 3.1 3.1 A2.09 Vacuum breaker malfunction 3.4 3.6 A2.10 High drywell temperature 3.6 3.8 A2.11 Abnormal suppression pool level 3.6 3.8 A2.12 Abnormal suppression pool temperature 3.7 3.8 A2.13 High containment temperature: Mark-III 3.3 3.4	A2.07			4.3*
A2.09Vacuum breaker malfunction3.43.6A2.10High drywell temperature3.63.8A2.11Abnormal suppression pool level3.63.8A2.12Abnormal suppression pool temperature3.73.8A2.13High containment temperature: Mark-III3.33.4				3.1
A2.10High drywell temperature3.63.8A2.11Abnormal suppression pool level3.63.8A2.12Abnormal suppression pool temperature3.73.8A2.13High containment temperature: Mark-III3.33.4				
A2.11Abnormal suppression pool level3.63.8A2.12Abnormal suppression pool temperature3.73.8A2.13High containment temperature: Mark-III3.33.4				
A2.12 Abnormal suppression pool temperature		Abnormal suppression pool level	3.6	
A2.13 High containment temperature: Mark-III		Abnormal suppression pool temperature	3.7	
A2.14 Low containment to annulus pressure: Mark-III				
		Low containment to annulus pressure: Mark-III	3.4	

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
АЗ.	Ability to monitor automatic operations of the PRIMARY CONTAINMENT SYSTEM AND AUXILIARIES including: (CFR: 41.7 / 45.7)	
A3.01	Suppression pool level	3.5
A3.02	Vacuum breaker/relief valve operation	3.4
A3.03	System indicating light and alarms	3.3
A3.04	Containment/drywell response during LOCA	* 4.3*
A3.05	Drywell pressure	
A3.06	Drywell/suppression chamber differential pressure:	
	Mark-I,II	3.3
A3.07	Containment/drywell differential pressure: Mark-III	3.6
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Containment relief valves: Mark-III	3.5
A4.02	ACAD compressors: Plant-Specific	2.6
A4.03	Air dilution valves to drywell and suppression pool:	
	Plant-Specific	3.4
A4.04	Containment/drywell hydrogen concentration	3.6
A4.05	Containment/drywell oxygen concentration	
A4.06	Containment pressure: Mark-III	* 4.0*
A4.07	Drywell pressure	
A4.08	System indicating lights and alarms	3.3
A4.09	SPDS/CRIDS/ERIS/GDS: Plant-Specific	2.9*
A4.10	Drywell nitrogen makeup: Mark-I,II	3.2
A4.11	Drywell pneumatics	3.0
A4.12	Drywell coolers/chillers	3.6
A4.13	Hydrogen recombiners: Plant-Specific	
A4.14	Hydrogen igniters: Plant-Specific	3.7

TASK: Conduct lineups on the containment system

Monitor the containment system in standby readiness

Perform primary containment isolation valve simulated automatic initiation and closure test

Conduct reactor building isolation logic system functional test

Perform drywell isolation, atmosphere control, and sump drain valves logic system test

Perform drywell isolation valves, atmosphere control valves, sump drain valves simulated auto actuation

test

	INFORTANCE		
K/A NO.	KNOWLEDGE	O	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF and the following:		
	(CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Main steam system	8	3.9
K1.02	Reactor water cleanup	3	3.5
K1.03	Plant ventilation	0	3.2
K1.04	High pressure coolant injection: Plant-Specific	5	3.8
K1.05	Isolation Condenser: Plant-Specific	8	3.8
K1.06	Recirculation system		3.2
K1.07	Reactor core isolation cooling; Plant-Specific		3.6
K1.08	Shutdown cooling system/RHR		3.5
K1.09	Reactor vessel head spray: Plant-Specific		3.2
K1.10	Containment ventilation		3.2
K1.11	Containment atmosphere sampling		3.2
K1.12	Standby gas treatment system		3.3
K1.13	Traversing in-core probe system		2.9
K1.14	Containment drainage system		3.1
K1.15	High pressure core spray: Plant-Specific		3.4
K1.16	Process computer		2.2*
K1.17	SPDS/ERIS/CRIDS/GDS: Plant-Specific		2.6
K1.18	Reactor building drainage system: Plant-Specific		2.6
K1.19	Component cooling water systems		2.9
K1.20	A.C. distribution: Plant-Specific		3.0
K1.21	Circulating water: Plant-Specific		2.3*
K1.22	Containment nitrogen inerting system: Plant-Specific		3.0
K1.23	River water makeup: Plant-Specific		2.1
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Logic power supplies	4*	2.7*

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF will have on following:		
	(CFR: 41.7 / 45.4)		
K3.01	Reactor water level	. 3.7	3.7
K3.02	Fuel cladding temperature	. 3.6	3.7
K3.03	†Off-site radioactive release rates		3.8
K3.04	Reactor building radiation level	. 3.4	3.6
K3.05	Drainage sump levels		2.8
K3.06	Turbine building radiation		2.9
K3.07	Reactor pressure		3.8
K3.08	Reactor vessel temperature		3.5
K3.09	Main steam system		3.6
K3.10	Reactor water cleanup		3.1
K3.11	Plant ventilation		2.9
K3.12	High pressure coolant injection: Plant-Specific	. 3.6	3.6
K3.13	Isolation Condenser: Plant-Specific		3.7
K3.14	Recirculation system: Plant-Specific		3.0
K3.15	Reactor core isolation cooling: Plant-Specific		3.5
K3.16	Shutdown cooling system/RHR		3.3
K3.17	Reactor vessel head spray: Plant-Specific		2.9
K3.18	Containment ventilation		3.1
K3.19	Containment atmosphere sampling		3.0
K3.20	Standby gas treatment system		3.4
K3.21	Traversing in-core probe system		2.7
K3.22	Containment drainage system		2.6
K3.23	High pressure core spray: Plant-Specific		3.6
K3.24	Reactor building drainage system		2.6
K3.25	Component cooling water systems		2.3
K3.26	A.C. distribution		2.2*
K3.27	Circulating water		1.8*
K3.28	Containment nitrogen inerting system		2.8
K3.29	River water makeup		1.8*
K4.	Knowledge of PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Redundancy	. 3.0	3.2
K4.02	Testability		2.9
K4.03	Manual initiation capability: Plant-Specific		3.6
K4.04	†Automatic bypassing of selected isolations during		
	specified plant conditions	. 3.2	3.6

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRC
K4.05	Single failures will not impair the function ability	
K4.06	of the system	3.1
110	operator action	3.5
K4.07	Physical separation of system components (to prevent localized environmental factors, electrical faults,	
	and physical events from impairing system response)	2.9
K4.08	†Manual defeating of selected isolations during specified emergency conditions	3.7
K5.	Knowledge of the operational implications of the following concepts as they apply to PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF: (CFR: 41.5 / 45.3)	
	None	
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF: (CFR: 41.7 / 45.7)	
K6.01	A.C. electrical distribution	3.3
K6.02	D.C. electrical distribution	3.2
K6.03	Process radiation monitoring system	3.1
K6.04	Nuclear boiler instrumentation	3.5
K6.05	Containment instrumentation	3.3
K6.06	Various process instrumentation	2.9
K6.07	Essential A.C. power	3.3
K6.08	Reactor protection system	3.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF controls including: (CFR: 41.5 / 45.5)	
A1.01	System indicating lights and alarms	3.5
A1.02	Valve closures	3.7
A1.03	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8*
A1.04	Individual system relay status	2.8

Tasks as noted previously

IMPORTANCE ABILITY RO K/A NO. **SRO** Ability to (a) predict the impacts of the following on A2. the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY SHUT-OFF; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 3.5 A2.02 3.2 A2.03 3.3 A2.04 Process radiation monitoring system failures 2.9 3.2 A2.05 A2.06 3.2 A2.07 2.9 A2.08 3.1 A2.09 3.7 A2.10 4.2 A2.11 3.9 A3. Ability to monitor automatic operations of the PRIMARY CONTAINMENT ISOLATION SYSTEM/NUCLEAR STEAM SUPPLY **SHUT-OFF** including: (CFR: 41.7 / 45.7) A3.01 3.4 A3.02 3.5 A3.03 2.8* A3.04 2.5 A4. Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) A4.01 3.5 A4.02 3.8 A4.03 3.5 A4.04 3.6 A4.05 2.8* A4.06 3.7

SYSTEM: 290002 Reactor Vessel Internals

TASK: Perform heatup/cooldown of reactor vessel

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR VESSEL INTERNALS and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05	Main steam system Recirculation system Reactor feedwater system HPCI: Plant-Specific RHR: Plant-Specific	3.2 3.2 3.4	3.2 3.2 3.2 3.5 3.2
K1.06 K1.07 K1.08 K1.09	HPCS: Plant-Specific Isolation condenser: Plant-Specific RCIC: Plant-Specific LPCI: Plant-Specific	3.1 3.4 3.1 3.2	3.1 3.4 3.1 3.3
K1.10 K1.11 K1.12 K1.13 K1.14	CRD hydraulic system CRD mechanism SBLC Relief/safety valves RWCU	2.9 3.4 3.4	3.1 2.9 3.5 3.5 3.1
K1.15 K1.16 K1.17 K1.18 K1.19	Nuclear boiler instrumentation LPCS ADS Loss parts monitoring: Plant-Specific TIP	3.2 3.3 2.1*	3.5 3.4 3.4 2.2* 2.6
K1.20	Nuclear instrumentation Knowledge of electrical power supplies to the following: (CFR: 41.7)		3.3
	None		
K3.	Knowledge of the effect that a loss or malfunction of the REACTOR VESSEL INTERNALS will have on following: $(CFR:\ 41.7/45.4)$		
K3.01 K3.02 K3.03 K3.04 K3.05 K3.06 K3.07	Reactor water level Reactor pressure Reactor power Plant radiation levels Off-site radiation levels PCIS/NSSSS Nuclear boiler instrumentation	2.9 3.3 2.9 2.9 3.1	3.3 3.0 3.4 3.2 3.2 3.1 3.1

SYSTEM: 290002 Reactor Vessel Internals

Tasks as noted previously

K6.17

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** Knowledge of REACTOR VESSEL INTERNALS design K4. feature(s) and/or interlocks which provide for the following: (CFR: 41.7) K4.01 3.9 K4.02 3.2 K4.03 3.3 K4.04 Moisture removal from generated steam 2.8 2.8 K4.05 3.5 K5. **Knowledge of the operational implications of the** following concepts as they apply to REACTOR VESSEL **INTERNALS:** (CFR: 41.5 / 45.3) K5.01 3.9 Fission product poisons 2.9 K5.02 3.1 K5.033.0 K5.04 3.7 K5.05 3.3 K5.06 3.2 4.4* K5.07 K6. Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR VESSEL **INTERNALS:** (CFR: 41.7 / 45.7) K6.01 CRD hydraulic system 2.8 2.9 K6.02 2.9 K6.03 3.2 K6.04 3.1 K6.05 3.4 K6.06 3.2 K6.07 2.7 K6.08 3.2 K6.09 3.3 K6.10 3.3 K6.11 3.2 K6.12 3.2 K6.13 2.8 K6.14 3.3 K6.15 3.4 K6.16 2.0*

2.5

SYSTEM: 290002 Reactor Vessel Internals

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K6.18	Nuclear instrumentation	3.1
K6.19	HPCS: Plant-Specific(BWR-5&6)	3.1
K6.20	Main steam system	3.1
A1.	ABILITY Ability to predict and/or monitor changes in parameters associated with operating the REACTOR VESSEL INTERNALS controls including: (CFR: 41.5 / 45.5)	
	None	
A2.	Ability to (a) predict the impacts of the following on the REACTOR VESSEL INTERNALS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	LOCA	4.0
A2.02	†Overpressurization transient	3.9
A2.03	†Control rod drop accident	3.9
A2.04	Excessive heatup/cooldown rate	4.1
A2.05	†Exceeding thermal limits	4.2
A2.06	†Exceeding safety limits	4.5*
A3.	Ability to monitor automatic operations of the REACTOR VESSEL INTERNALS including: (CFR: 41.7 / 45.7)	
	None	
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
	None	

TASK: Startup the torus cooling system

Shutdown the torus (cooling system) Monitor the torus cooling system

Lineup torus/suppression pool cooling system for different modes (cooling, spray)

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Suppression pool	3.9
K1.01 K1.02	Condensate storage tank	2.4
K1.02 K1.03	LPCI/RHR piping	3.8
K1.04	LPCI/RHR pumps	3.9
K1.05	A.C. electrical power	3.6
K1.06	Keep fill system	3.3
K1.07	Condensate transfer	2.6
K1.08	D.C. electrical power	2.8
K1.09	Nuclear boiler instrumentation	3.4
K1.10	Reactor building drain system: Plant-Specific	1.9*
K1.11	Component cooling water systems	3.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	†Valves	2.9*
K2.02	Pumps 3.1*	3.3*
K2.03	Valve control logic: Plant-Specific	2.6*
K3.	Knowledge of the effect that a loss or malfunction of the RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE will have on following: (CFR: 41.7 / 45.4)	
K3.01	Suppression pool temperature control	4.1
K4.	Knowledge of RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Surveillance for all operable components	3.4
K4.02	Redundancy	3.5
K4.03	Unintentional reduction in vessel injection flow	2.0
	during accident conditions: Plant-Specific	3.8
K4.04	Prevention of piping overpressurization: Plant-	2.0
	Specific	3.4
		•

IMPORTANCE	IMP	OR'	ΓΑΝ	CE
------------	-----	-----	-----	----

K/A NO.	KNOWLEDGE	RO	SRO
K4.05	Pump minimum flow protection	3.0	3.2
K4.06	Pump motor cooling: Plant-Specific	2.7	2.7
K4.07	Prevention of water hammer: Plant-Specific	3.0	3.1
K4.08	Adequate pump net positive suction head	2.9	3.0
K4.09	Heat exchanger cooling		3.4
K4.10	Prevention of leakage to the environment through		
	system heat exchanger: Plant-Specific	3.3	3.6
K5.	Knowledge of the operational implications of the following concepts as they apply to RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE: (CFR: 41.5 / 45.3)		
K5.01	System venting	2.6	2.7
K5.02	Pump cavitation	2.7	2.8
K5.03	Pressure measurement	2.7*	2.8*
K5.04	Heat exchanger operation	2.9	2.9
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE: (CFR: 41.7/45.7)		
K6.01	A.C. electrical power	3.2	3.3
K6.02	D.C. electrical power		2.8*
K6.03	Emergency generator		3.5
K6.04	Keep fill system		3.0
K6.05	Condensate storage tank: Plant-Specific		2.2*
K6.06	Suppression pool		3.7
K6.07	Condensate transfer		2.2*
K6.08	ECCS room cooling	2.7*	2.7
K6.09	Nuclear boiler instrumentation		3.1
K6.10	Component cooling water systems	2.9	2.9
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02	Suppression pool temperature System flow	3.5	4.0 3.5
A1.03	System pressure		2.9
A1.04	Suppression pool level		3.2
A1.05	Condensate storage tank level: Plant-Specific	2.1*	2.1*

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
A1.06	Motor amps: Plant-Specific	2.3*	2.4*
A1.07	Emergency generator loading		3.3
A1.08	System lineup		3.6
A1.09	Suppression chamber air temperature: Plant-Specific		3.3
A1.10	Containment air temperature: Mark-III		3.1
A2.	Ability to (a) predict the impacts of the following on the RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: $(CFR:\ 41.5/45.6)$		
A2.01	Inadequate net positive suction head	3.0	3.1
A2.02	Pumps trips		3.3
A2.03	Valve closures		3.2
A2.04	Valve openings		3.2
A2.05	A.C. electrical failures		3.5
A2.06	D.C. electrical failures		2.9*
A2.07	Emergency generator failure		3.7
A2.07 A2.08	Pump seal failure		3.1
A2.08 A2.09	Inadequate room cooling		2.9
A2.10	Nuclear boiler instrument failures		3.2
A2.10 A2.11	Motor operated valve failures		3.3
A2.11 A2.12	Valve logic failure: Plant-Specific		3.3*
A2.12 A2.13	•		3.7
A2.13 A2.14	High suppression pool temperature		4.3*
A2.14 A2.15			3.4
	Loss of, or inadequate, heat exchanger cooling flow		3.4
A2.16	High suppression pool level	2.9	3.2
A3.	Ability to monitor automatic operations of the RHR/LPCI: TORUS/SUPPRESSION POOL COOLING MODE including: (CFR: 41.7 / 45.7)		
A3.01	Valve operation	3.3	3.3
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
	D.	2.61	0 E.t.
A4.01	Pumps		3.7*
A4.02	Valve lineup		3.5
A4.03	Keep fill system		2.9
A4.04	Minimum flow valves		2.9
A4.05 A4.06	Heat exchanger cooling flow	3.4	3.4
	LPCI/RHR in injection mode	3.9	3.7

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A4.07	System flow	3.4
A4.08	Pump/system discharge pressure: Plant-Specific	2.9
A4.09	Indicating lights and alarms	3.3
A4.10	Condensate storage tank level: Plant-Specific	2.2*
A4.11	System venting	2.4
A4.12	Suppression pool temperature	4.1
A4.13	Suppression pool level	3.8
A4.14	The overrides for suppression pool cooling valve	
	logic: Plant-Specific	3.5

TASK: Lineup the containment spray system

Manually initiate containment spray

Shutdown the containment spray system

Monitor the containment spray system

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RHR/LPCI: CONTAINMENT SPRAY SYSTEM MODE and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09 K1.10 K1.11 K1.12 K1.13	Suppression pool LPCI/RHR piping LPCI/RHR pumps A.C. electrical power Keep fill system Condensate Transfer D.C. electrical power Nuclear boiler instrumentation Drywell (spray penetration): Mark-I-II Containment (spray penetration): Mark-III Component cooling water systems Suppression pool (spray penetration): Plant-Specific. Containment instrumentation	. 3.5 . 3.5 . 3.1 . 2.9 . 2.5 . 2.4 . 3.2 . 3.0 . 2.8 . 3.0	3.6 3.7 3.6 3.3 2.9 2.5 2.5 3.4 3.1 3.0 3.0 3.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03	Valves Pumps Valve control logic	. 2.9*	2.3* 2.9* 2.5*
K3.	Knowledge of the effect that a loss or malfunction of the RHR/LPCI: CONTAINMENT SPRAY SYSTEM MODE will have on following: (CFR: 41.7/45.4)		
K3.01 K3.02 K3.03	Containment/drywell/suppression chamber pressure	. 3.5	3.7 3.5
K4.	Knowledge of RHR/LPCI: CONTAINMENT SPRAY SYSTEM MODE design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Testability of all operable components	. 2.6	2.8

Tasks as noted previously

	INFORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K4.02	Redundancy	2.8	2.9
K4.03	Reduction in vessel injection flow during accident		
	conditions	2.9	3.1
K4.04	Prevention of piping overpressurization		2.6
K4.05	Pump minimum flow protection		2.5
K4.06	Pump motor cooling		2.3
K4.07	Prevention of water hammer		2.8
K4.08	Adequate pump net positive suction head		2.4
K4.09	Automatic containment spray initiation: BWR-6		3.4
K4.10	Spray flow cooling	2.9	3.0
K4.11	Prevention of leakage to the environment through		
	system heat exchanger	2.7	2.9
K4.12	Prevention of inadvertent containment spray activation		2.9
K5.	Knowledge of the operational implications of the		
133.	following concepts as they apply to RHR/LPCI:		
	CONTAINMENT SPRAY SYSTEM MODE:		
	(CFR: 41.5 / 45.3)		
K5.01	System venting		2.2*
K5.02	Water hammer	2.6	2.7
K5.03	Pump cavitation	2.3	2.5
K5.04	Evaporative cooling	2.1*	2.1*
K5.05	Convective cooling		2.1*
K5.06	Vacuum breaker operation		2.8
113.00	racadin ofcaker operation	2.0	2.0
K6.	Vnoviladge of the effect that a loss or malfunction of		
No.	Knowledge of the effect that a loss or malfunction of		
	the following will have on the RHR/LPCI: CONTAINMENT		
	SPRAY SYSTEM MODE:		
	(CFR: 41.7 / 45.7)		
K6.01	A.C. electrical power	3.0	3.3
K6.02	D.C. electrical power	2.6	2.9
K6.03	Emergency generator	3.4	3.6
K6.04	Keep fill system		2.7
K6.05	Suppression pool (temperature level and pressure)		3.6
K6.06	Condensate transfer		2.4
K6.07	ECCS room cooling		2.6
K6.08			2.8
	Nuclear boiler instrumentation	2.1	2.8
K6.09	†Reactor building to suppression chamber vacuum		
	breakers: Plant-Specific	3.3	3.5
K6.10	†Suppression chamber to drywell vacuum breakers:		
	Mark-1-II	3.3	3.5
K6.11	Component cooling water systems	2.8	2.8
K6.12	Containment integrity		3.5

		TM/DOT	OTANCE
K/A NO.	KNOWLEDGE	RO	RTANCE SRO
K6.13	Suction flow path	. 3.2	3.2
	ABILITY		
A1.	Ability to predict and/or monitor changes in		
	parameters associated with operating the RHR/LPCI:		
	CONTAINMENT SPRAY SYSTEM MODE controls including: (CFR: 41.5 / 45.5)		
	(CFR. 41.57 45.5)		
A1.01	Containment/drywell pressure	. 3.6	3.8
A1.02	Containment/drywell temperature		3.5
A1.03	†Suppression chamber pressure: Mark-I-II		3.8
A1.04	Suppression pool temperature: Mark-I-II		3.6
A1.05	System lineup	. 3.1	3.4
A1.06	System flow	. 3.2	3.2
A1.07	System pressure	. 3.1	3.1
A1.08	Suppression pool level	. 3.1	3.4
A1.09	Motor amps	. 2.1*	2.1*
A1.10	Emergency generator loading	. 3.0	3.2
A2.	Ability to (a) predict the impacts of the following on the RHR/LPCI: CONTAINMENT SPRAY SYSTEM MODE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Inadequate net positive suction head	. 2.4	2.6
A2.02	Pumps trips		3.2
A2.03	Valve closures		3.1
A2.04	Valve openings		3.0
A2.05	A.C. electrical failures		3.4
A2.06	D.C. electrical failures		2.9
A2.07	Emergency generator failure		3.6
A2.08	Pump seal failure		2.5
A2.09	Inadequate room cooling		2.7
A2.10	Nuclear boiler instrument failures		3.1
A2.11	Motor operated valve failures		3.0
A2.12	Pump runout		2.6
A2.13	Valve logic failure		2.9
A2.14	High suppression pool level		3.1
A2.15	High containment / drywell pressure		3.8
A2.16	Loss of, or inadequate heat exchanger cooling flow		3.1
A2.17	†High containment / drywell temperature		3.2
A2.18	†Low (or negative) containment/drywell pressure during		
	system operation	. 3.3	3.5

	K/A NO.	KNOWLEDGE	IMPOR RO	TANCE SRO
	A2.19	†Low (or negative) suppression chamber pressure during		
		system operation: Mark-I-II		3.8
	A2.20	†Loss of coolant accident		4.1
	A2.21	Loss of containment/drywell cooling system(s)	3.3	3.4
	A3.	Ability to monitor automatic operations of the RHR/LPCI: CONTAINMENT SPRAY SYSTEM MODE including: (CFR: 41.7 / 45.7)		
	A3.01	Valve operation: Plant-Specific	3.0	3.0
	A3.02	System pressure		2.8
	A3.03	System flow		2.8
	A3.04	Lights and alarms		3.1
Ι	A3.05	Containment pressure		4.0*
'	A3.06	Containment temperature		3.5
	A3.07	Pump start		3.5
	A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
	A4.01	Pumps	3.5	3.4
	A4.02	Suction valves		3.1
	A4.03	Spray valves		3.4
	A4.04	Keep fill system		2.7
	A4.05	Minimum flow valves		2.8
	A4.06	Heat exchanger cooling flow		2.8
	A4.07	Valve logic reset/ bypass/ override		3.5
	A4.08	System flow		3.1
	A4.09	Pump discharge pressure		2.7
	A4.10	Indicating lights and alarms		3.2
	A4.11	System venting	2.2*	2.2*
	A4.12	Containment/drywell pressure		3.8
	A4.13	Containment/drywell temperature		3.3
	A4.14	Suppression pool temperature	3.5	3.6
•	A4.15	Suppression chamber pressure: Mark-I-II		3.6
	A4.16	The override for suppression pool spray valve logic		3.5
	A4.17	Manual initiation controls: BWR-6		3.8
	A4.18	Automatic system initiation reset: BWR-6		3.8
	A4.19	Drywell temperature		3.4
	A4.20	Drywell pressure		3.8

TASK: Lineup the torus spray system

Manually initiate torus spray

Monitor the torus spray system

	1 7 7	IMPO	RTANCE
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RHR/LPCI: TORUS/SUPPRESSION POOL SPRAY MODE and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09 K1.10	Suppression pool Condensate storage and transfer system LPCI/RHR piping LPCI/RHR pumps A.C. electrical Keep fill system D.C. electrical Nuclear boiler instrumentation Reactor building drain system Component cooling water systems	. 2.4* . 3.3 . 3.4 . 3.2 . 3.0 . 2.4* . 3.1 . 2.3*	3.7 2.5 3.5 3.6 3.3 3.1 2.6* 3.2 2.4* 2.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02	Valves		2.3* 2.9*
К3.	Knowledge of the effect that a loss or malfunction of the RHR/LPCI: TORUS/SUPPRESSION POOL SPRAY MODE will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04	Suppression chamber pressure Suppression pool temperature Drywell pressure Suppression chamber air temperature	. 3.3	3.9 3.5 3.6 3.8
K4.	Knowledge of RHR/LPCI: TORUS/SUPPRESSION POOL SPRAY MODE design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06	Surveillance for all operable components Redundancy Unintentional reduction in vessel injection flow during accident conditions Prevention of piping overpressurization Pump minimum flow protection Pump motor cooling	. 3.1* . 3.5 . 3.0 . 2.8	3.3 3.2 3.6 3.2 3.1 2.8

K/A NO. KNOWLEDGE RO SR K4.07 Prevention of water hammer 3.1 3.2 K4.08 Adequate pump net positive suction head 2.9 3.2 K4.09 Spray flow cooling 3.0 3.1	O
K4.08 Adequate pump net positive suction head	
K4.08 Adequate pump net positive suction head	
- 1x 110/ Dpiny 110 tt 00011115 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
K4.10 Prevention of leakage to the environment through	
system heat exchanger	
K5. Knowledge of the operational implications of the	
following concepts as they apply to RHR/LPCI:	
TORUS/SUPPRESSION POOL SPRAY MODE:	
(CFR: 41.5 / 45.3)	
K5.01 System venting	,
K5.02 Pump cavitation	
K5.03 Pressure measurement	*
K5.04 Evaporative cooling	*
K5.05 Convective cooling	*
K5.06 Heat exchanger operation	j
K5.07 Vacuum breaker operation	
K6. Knowledge of the effect that a loss or malfunction of	
the following will have on the RHR/LPCI:	
TORUS/SUPPRESSION POOL SPRAY MODE:	
(CFR: 41.7 / 45.7)	
K6.01 A.C. electrical	
K6.02 D.C. electrica	
K6.03 Emergency generator	
K6.04 Keep fill system	
K6.05 Suppression pool 3.3 3.4	
K6.06 Condensate storage and transfer system	
K6.07 ECCS room cooling	
K6.08 Nuclear boiler instrumentation	
K6.09 Reactor building to suppression pool vacuum breakers	
K6.10 Component cooling water systems	1
ABILITY	
A1. Ability to predict and/or monitor changes in parameters	
associated with operating the RHR/LPCI:	
TORUS/SUPPRESSION POOL SPRAY MODE controls including: (CFR: 41.5 / 45.5)	
A1.01 Suppression chamber pressure	
A1.02 Suppression pool temperature	
A1.03 Drywell pressure	
A1.04 System flow	

1 a	isks as noteu p	IMPORTANCE		
K/	A NO.	ABILITY	RO	SRO
A 1	1.05	System pressure	2.8*	2.9
	1.06	Suppression pool level		3.3
	1.07	Condensate storage tank level		2.3*
	1.08	Motor amps		2.5*
	1.09	Emergency generator loading		3.5
	1.10	System lineup		3.7
	1.11	Suppression chamber air temperature		3.6
A2	2.	Ability to (a) predict the impacts of the following on		
		the RHR/LPCI: TORUS/SUPPRESSION POOL SPRAY MODE; and		
		(b) based on those predictions, use procedures to		
		correct, control, or mitigate the consequences of		
		those abnormal conditions or operations:		
		(CFR: 41.5 / 45.6)		
	3.01		2.0	2.2
	2.01	Inadequate net positive suction head		3.2
	2.02	Pump trips		3.4
	2.03	Valve closures		3.2
	2.04	Valve openings		3.1
	2.05	A.C. electrical failures		3.6
	2.06	D.C. electrical failures		2.9*
	2.07	Emergency generator failure		3.8
	2.08	Pump seal failure		3.2
	2.09	Inadequate room cooling		3.0
	2.10	Nuclear boiler instrument failures		3.0
	2.11	Motor operated valve failures		3.3
	2.12	Valve logic failure		3.3
	2.13	High suppression pool level	2.9	3.2
ΑZ	2.14	Low (or negative) suppression pool pressure during	2.2	2.5
	. 15	system operation		3.5
	2.15	Loss of coolant accident		4.1
ΑZ	2.16	Loss of, or inadequate, heat exchanger cooling flow	3.1	3.3
A3	3.	Ability to monitor automatic operations of the		
		RHR/LPCI: TORUS/SUPPRESSION POOL SPRAY MODE including: (CFR: 41.7 / 45.7)		
A3	3.01	Valve operation	3.4	3.3
A	1.	Ability to manually operate and/or monitor in the		
		control room:		
		(CFR: 41.7 / 45.5 to 45.8)		
A۷	4.01	Pumps	3.7*	3.5
Α	4.02	Spray valves	3.8	3.6
Α	4.03	Keep fill system	3.1	3.0
Α	4.04	Minimum flow valves	3.1	2.9
Α	4.05	Heat exchanger cooling flow	3.2	3.1

K/A NO.	ABILITY	IMPORTANCE	RO	SRO
A4.06	Valve logic reset following automatic initiation of			
	LPCI/RHR in injection mode		4.0	3.9
A4.07	System flow		3.6	3.4
A4.08	Pump/system discharge pressure		3.0	2.9

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
A4.09	Indicating lights and alarms	. 3.6	3.3
A4.10	Condensate storage tank level	. 2.4*	2.4
A4.11	System venting	. 2.5	2.4
A4.12	Suppression pool level	. 3.8	3.8
A4.13	Suppression chamber pressure	. 4.0	3.9
A4.14	Suppression pool temperature	. 3.8	3.8
A4.15	Drywell pressure	. 3.9	4.0
A4.16	The override for suppression pool spray valve logic	. 3.8	3.8

K/A NO.	KNOWLEDGE	IMPOI RO	RTANCE SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between SECONDARY CONTAINMENT and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07	Reactor building ventilation: Plant-Specific Primary containment system: Plant-Specific Radwaste building ventilation: Plant-Specific SBGT Auxiliary building ventilation: Plant-Specific Auxiliary building isolation: BWR-6 Turbine building ventilation (steam tunnel): Plant-Specific Exhaust stack: BWR-2,3,4 Plant air systems	. 3.4 . 2.4 . 3.7 . 3.1 . 3.4	3.5 3.6 2.7 3.9 3.3 3.6 3.1 3.3 2.9
K1.10 K2.	Auxiliary boiler system: BWR-2,3,4		1.6*
К3.	None Knowledge of the effect that a loss or malfunction of the SECONDARY CONTAINMENT will have on following: (CFR: 41.7 / 45.4)		
K3.01 K4.	†Off-site radioactive release rates Knowledge of SECONDARY CONTAINMENT design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	. 4.0	4.4*
K4.01 K4.02 K4.03 K4.04	Personnel access without breaching secondary containment: Plant-System	. 3.4	3.8 3.5 2.9 3.4
K5.	Knowledge of the operational implications of the following concepts as they apply to SECONDARY CONTAINMENT: (CFR: 41.5 / 45.3)		
K5.01 K5.02	Vacuum breaker operation: BWR-4		3.4* 2.2

SYSTEM: 290001 Secondary Containment

Tasks as noted previously

K/A NO.	KNOWLEDGE	IMPOI RO	RTANCE SRO
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the SECONDARY CONTAINMENT: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07 K6.08 K6.09	Reactor building ventilation: Plant-Specific Radwaste building ventilation: Plant-Specific SBGT Primary containment system Auxiliary building ventilation: Plant-Specific Turbine building ventilation: Plant-Specific Auxiliary boiler system: BWR-3,4 Plant air systems A.C. power: BWR-6	. 2.4 . 3.8 . 3.9 . 2.9 . 2.2* . 1.9* . 2.7	3.6 2.6 4.0 4.1 3.0 2.3 2.0* 2.8 3.6
ABILIT	Y		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the SECONDARY CONTAINMENT controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02	System lineups		3.1 3.6
A2.	Ability to (a) predict the impacts of the following on the SECONDARY CONTAINMENT; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06	†Personnel airlock failure †Excessive outleakage High area radiation High airborne radiation High area temperature Auxiliary building isolation: BWR-6	. 3.5 . 3.4 . 3.4 . 3.1	3.7 3.7 3.6 3.7 3.3 4.0
A3.	Ability to monitor automatic operations of the SECONDARY CONTAINMENT including: (CFR: 41.7 / 45.7)		
A3.01 A3.02	Secondary containment isolation		4.0 3.5

SYSTEM: 290001 Secondary Containment

Tasks as noted previously

	IMPO	ORTANCE
K/A NO.	ABILITY RO	SRO
A4.	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	Reactor building differential pressure: Plant-	
	Specific 3.3	3.4
A4.02	Reactor building area temperatures: Plant-Specific	3.4
A4.03	Auxiliary building differential pressure: Plant-	
	Specific	2.7
A4.04	Auxiliary building area temperature: Plant-Specific	2.7
A4.05	Fuel building differential pressure: Plant-Specific	3.5
A4.06	Fuel building area temperature: Plant-Specific	3.5
A4.07	Radwaste building differential pressure: Plant-	
	Specific	2.5
A4.08	Radwaste building area temperature: Plant-Specific	
A4.09	System status lights and alarms: Plant-Specific	3.2
A4.10	System lineups: Plant-Specific	
A4.11	System reset: Plant-Specific	
A4.12	Surveillance testing: Plant-Specific	3.2

3.6	Electrical	page
262001	A.C. Electrical Distribution	3.6-3
263000	D.C. Electrical Distribution	3.6-6
264000	Emergency Generators (Diesel/Jet)	3.6-9
262002	Uninterruptable Power Supply (A.C. /D.C.)	3.6-13

This page left blank

SYSTEM: 226001 A.C. Electrical Distribution

TASK: Lineup the electrical distribution system (from station power to reserve station power)

Shift auxiliary buses between the unit auxiliary XFMR and the service/startup XFMR

Monitor the A.C. electrical distribution system (monitor the 416V A.C. power distribution system)

Deenergize a motor control center bus from service

Restore a motor control center bus to service

Deenergize an engineering safeguards (4160V vital) bus from service

Restore an engineering safeguards bus

Backfeed unit auxiliary transformer from main transmission switchyard (main turbine generator links removed)

Transfer a vital (120V)/instrument bus power supply

Operate a vital motor-generator set

Perform ground isolation

Lineup the electrical distribution system (from normal power to startup power) (write in)

Perform equipment/bus testing for ground faults

Perform operation of circuit breakers and disconnects

Perform emergency A.C. load sequencing and 4KV emergency systems volt relays instrumentation function tests

Perform circuit or equipment grounding using built-in devices

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between A.C. ELECTRICAL DISTRIBUTION and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Emergency generators (diesel/jet)	4.3*
K1.02	D.C. electrical distribution	3.6
K1.03	Off-site power sources	3.8
K1.04	Uninterruptible power supply	3.4
K1.05	Main turbine/generator	3.2
K1.06	Alternate shutdown system: Plant-Specific	3.9
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Off-site sources of power	3.6
К3.	Knowledge of the effect that a loss or malfunction of the A.C. ELECTRICAL DISTRIBUTION will have on following: (CFR: 41.7 / 45.4)	
K3.01	Major system loads	3.7
K3.02	Emergency generators	4.2

SYSTEM: 262001 A.C. Electrical Distribution

Tasks as noted previously

K/A NO.	IMPORTANCE KNOWLEDGE RO	SRO
K3.03	D.C. electrical distribution	3.2
K3.04	Uninterruptible power supply	3.3
K3.05	Off-site power system	3.5
K3.06	Reactor protection system	4.1*
K4.	Knowledge of A.C. ELECTRICAL DISTRIBUTION design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Bus lockouts	3.4
K4.02	Circuit breaker automatic trips	3.3
K4.03	Interlocks between automatic bus transfer and breakers	3.4
K4.04	Protective relaying	3.1
K4.05	Paralleling of A.C. sources (synchroscope)	3.6
K4.06	Redundant power sources to vital buses	3.9
K5.	Knowledge of the operational implications of the following concepts as they apply to A.C. ELECTRICAL DISTRIBUTION: (CFR: 41.5 / 45.3)	
K5.01	Principle involved with paralleling two A.C. sources	3.4
K5.02	Breaker control	2.9
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the A.C. ELECTRICAL DISTRIBUTION: (CFR: 41.7 / 45.7)	
K6.01	D.C. power	3.4
K6.02	Off-site power	3.9
K6.03	Generator trip	3.7
ABIL	ПҮ	
A1.	Ability to predict and/or monitor changes in	
parai	meters associated with operating the A.C. ELECTRICAL DISTRIBUTION controls including: (CFR: 41.5 / 45.5)	
A1.01	Effect on instrumentation and controls of switching	2.4
A 1 02	power supplies	3.4
A1.02	Effects of loads when energizing a bus	3.5
A1.03	Bus voltage	3.1

SYSTEM: 262001 A.C. Electrical Distribution

Tasks as noted previously

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** A1.04 2.9 A1.05 3.5 A2. Ability to (a) predict the impacts of the following on the A.C. ELECTRICAL DISTRIBUTION; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 3.6 A2.02 3.9 A2.034.3* A2.04 Types of loads that, if deenergized, would degrade or 4.2 A2.05 A2.06 2.9 A2.07 3.2 A2.08 3.6 A2.09 3.4 A2.10 3.4 A2.11 3.6 **A3.** Ability to monitor automatic operations of the A.C. **ELECTRICAL DISTRIBUTION including:** (CFR: 41.7 / 45.7) A3.01 3.2 A3.02 3.3 A3.03 3.5 A3.04 36 A4. Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) A4.01 All breakers and disconnects (including available 3.7 A4.02 Synchroscope, including understanding of running and 3.4 A4.03 3.4 A4.04 Synchronizing and paralleling of different A.C. 3.7 A4.05 3.3

SYSTEM: 263000 D.C. Electrical Distribution

TASK: Startup a battery charger

Shift battery chargers

Monitor the D.C. electrical distribution system (battery, chargers, distribution and PWR panels)

Monitor the D.C. electrical distribution system for grounds

Energize D.C. switchboards Deenergize D.C. switchboards Energize D.C. equipment Deenergize D.C. equipment Secure a battery charger

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between D.C. ELECTRICAL DISTRIBUTION and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04	A.C. electrical distribution Battery charger and battery Battery ventilation Ground detection	. 3.2 . 2.6	3.5 3.3 2.8 2.9
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02	Major D.C. loads		3.4 2.2*
К3.	Knowledge of the effect that a loss or malfunction of the D.C. ELECTRICAL DISTRIBUTION will have on following: (CFR: 41.7/45.4)		
K3.01 K3.02 K3.03	Emergency generators: Plant-Specific Components using D.C. control power (i.e. breakers) Systems with D.C. components (i.e. valves, motors, solenoids, etc.)	. 3.5	3.8 3.8 3.8
K4.	Knowledge of D.C. ELECTRICAL DISTRIBUTION design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02	Manual/ automatic transfers of control: Plant- Specific		3.4
	ties: Plant-Specific	. 3.1	3.5

SYSTEM: 263000 D.C. Electrical Distribution

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to D.C. ELECTRICAL DISTRIBUTION: (CFR: 41.5 / 45.3)		
K5.01	Hydrogen generation during battery charging	2.6	2.9
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the D.C. ELECTRICAL DISTRIBUTION: (CFR: 41.7 / 45.7)		
K6.01 K6.02	A.C. electrical distribution		3.5 2.6
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the D.C. ELECTRICAL DISTRIBUTION controls including: (CFR: 41.5 / 45.5)		
A1.01	Battery charging/discharging rate	2.5	2.8
A2.	Ability to (a) predict the impacts of the following on the D.C. ELECTRICAL DISTRIBUTION; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02	Grounds		3.2 2.9
A3.	Ability to monitor automatic operations of the D.C. ELECTRICAL DISTRIBUTION including: (CFR: 41.7 / 45.7)		
A3.01	Meters, dials, recorders, alarms, and indicating lights	3.2	3.3
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	Major breakers and control power fuses: Plant- Specific	3.3	3.5

SYSTEM: 263000 D.C. Electrical Distribution

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
A4.02	Battery voltage indicator: Plant-Specific	3.2	3.1
A4.03	Battery discharge rate: Plant-Specific	2.7	2.8
A4.04	Ground detection circuit: Plant-Specific	3.0	3.2

TASK: Perform a lineup of the diesel generator system

Start a diesel generator (D/G)

Load the diesel generator (D/G)

Monitor the diesel generator

Unload the diesel generator

Shutdown the diesel generator (D/G)

Transfer fuel oil from main storage tanks to various system tanks

Operate the diesel starting air compressor

Restart a diesel generator (D/G) with an automatic start signal present

Perform emergency diesel generator (EDG) load tests

Perform lineups on the gas turbine generator

Start the gas turbine generator remotely

Monitor gas turbine generator emergency start

Monitor the gas turbine generator during operation

Conduct normal shutdown of the gas turbine generator

Conduct emergency shutdown of the gas turbine generator

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between EMERGENCY GENERATORS (DIESEL/JET) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	A.C. electrical distribution	3.8	4.1
K1.02	D.C. electrical distribution	3.3	3.4
K1.03	Fire protection system	2.9	3.2
K1.04	Emergency generator cooling water system	3.2	3.3
K1.05	Emergency generator fuel oil supply system	3.2	3.3
K1.06	Starting system	3.2	3.2
K1.07	Emergency core cooling systems	3.9	4.1
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Air compressor	2.2*	2.4*
K2.02	Fuel oil pumps	2.2*	2.4*
K2.03	Turning gear (jet engine): Plant-Specific	2.0*	2.3*
K2.04	Ignition system (jet engine): Plant-Specific	2.3*	2.7*
K2.05	Lube oil pumps	2.3*	2.4*
K2.06	Battery charger	2.2*	2.2*
K2.07	Emergency generator field flash	2.1*	2.3*

Tasks as noted previously

IZ/A NO	ENOWI FROE	D/) CT	20
K/A NO.	KNOWLEDGE	RO) SR	RO
К3.	Knowledge of the effect that a loss or malfunction of the EMERGENCY GENERATORS (DIESEL/JET) will have on following: (CFR: 41.7 / 45.4)			
K3.01	Emergency core cooling systems	4.2*	4.4*	
K3.02	A.C. electrical distribution	3.9	4.0	
K3.03	Major loads powered from electrical buses fed by the emergency generator(s)	4.1*	4.2*	
K4.	Knowledge of EMERGENCY GENERATORS (DIESEL/JET) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)			
K4.01	Emergency generator trips (normal)	3	5 3.7	7
K4.02	Emergency generator trips (emergency/LOCA)			
K4.03	Speed droop control			
K4.04	Field flashing			
K4.05	Load shedding and sequencing			
K4.06	Governor control			
K4.07	Local operation and control			
K4.08	Automatic startup			7
K5.	Knowledge of the operational implications of the following concepts as they apply to EMERGENCY GENERATORS (DIESEL/JET): (CFR: 41.5 / 45.3)			
K5.01	Definition of frequency and synchronous frequency	2.0)* 2.1	1*
K5.02	Reactive power control			1*
K5.03	Real power control	2.4	1* 2.4	4*
K5.04	Governor control	2.4	2.5	5
K5.05	Paralleling A.C. power sources	3.4	1 3.4	4
K5.06	Load sequencing	3.4	3.5	5
K5.07	Speed droop	2.3	3 2.4	4
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the EMERGENCY GENERATORS (DIESEL/JET): (CFR: 41.7 / 45.7)			
K6.01	Starting air	3	8 3.9	9
K6.02	Fuel oil pumps			
K6.03	Lube oil pumps			
K6.04	Turning gear (jet engine): Plant-Specific			
K6.05	Ignition system (jet engine): Plant-Specific			

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K6.06	Battery charger	2.9	3.1
K6.07	Cooling water system		3.9
K6.08	A.C. power		3.7
K6.09	D.C. power		3.5
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the EMERGENCY GENERATORS (DIESEL/JET) controls including: (CFR: 41.5 / 45.5)		
A1.01	Lube oil temperature	3.0*	3.0*
A1.02	Fuel consumption rate	2.2*	2.3
A1.03	Operating voltages, currents, and temperatures	2.8	2.9
A1.04	Crank case temperature and pressure	2.6	2.7
A1.05	Cylinder temperature differential	2.4*	2.4*
A1.06	Emergency generator room temperature	2.3	2.4
A1.07	Gas generator temperature: Plant-Specific	2.0*	2.5
A1.08	Gas generator speed: Plant-Specific	2.0*	2.5
A1.09	Maintaining minimum load on emergency generator (to		
	prevent reverse power)	3.0	3.1
A2.	Ability to (a) predict the impacts of the following on the EMERGENCY GENERATORS (DIESEL/JET); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Parallel operation of emergency generator	3.5	3.6
A2.02	Unloading prior to securing emergency generator	3.1	3.1
A2.03	Operating unloaded, lightly loaded, and highly loaded	3.4	3.4
A2.04	Consequences of operating under/over excited	2.9	3.0
A2.05	Synchronization of the emergency generator with other		
	electrical supplies		3.6
A2.06	Opening normal and/or alternate power to emergency bus	3.4	3.4
A2.07	Loss of off-site power during full-load testing	3.5	3.7
A2.08	Initiation of emergency generator room fire protection		
	system	3.3	3.7
A2.09	Loss of A.C. power	3.7	4.1
A2.10	LOCA	3.9	4.2*

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A3.	Ability to monitor automatic operations of the EMERGENCY GENERATORS (DIESEL/JET) including: (CFR: 41.7/45.7)	
A3.01	Automatic starting of compressor and emergency	
	generator	3.1
A3.02	Minimum time for load pick up	
A3.03	Indicating lights, meters, and recorders	3.4
A3.04	Operation of the governor control system on frequency	
	and voltage control 3.1	
A3.05	Load shedding and sequencing	3.5
A3.06	Cooling water system operation	3.2
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Adjustment of exciter voltage	3.4
A4.02	Synchroscope	
A4.03	Transfer of emergency control between manual and	
	automatic	3.4
A4.04	Manual start, loading, and stopping of emergency	
	generator: Plant-Specific	3.7
A4.05	Transfer of emergency generator (with load) to grid	
A4.06	Droop setting	

SYSTEM: 262002 Uninterruptable Power Supply (A.C./D.C.)

TASK: Operate a static inverter

K3.07

K3.08

IMPORTANCE RO K/A NO. **KNOWLEDGE SRO** K1. Knowledge of the physical connections and/or causeeffect relationships between UNINTERRUPTABLE POWER **SUPPLY (A.C./D.C.)** and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8) K1.01 3.0 K1.02 3.0 K1.03 2.9 K1.043.0 Reactor/turbine pressure control system control unit: K1.05Plant-Specific 2.7 2.9 K1.06 2.7 K1.07 2.9 K1.08 3.1 K1.09 2.7 K1.10 2.8 K1.11 2.6 K1.12 Generator hydrogen and stator cooling water controls: Plant-Specific 2.1* 2.3* K1.13 2.6 K1.14 3.0 K1.15 3.0 K1.16 3.2 K1.17 3.3 K1.18 2.7 K1.19 3.1* K1.20 2.7 K2. Knowledge of electrical power supplies to the following: (CFR: 41.7) None K3. Knowledge of the effect that a loss or malfunction of the UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.) will have on following: (CFR: 41.7 / 45.4) K3.01 3.3 K3.02 2.9 K3.033.1 K3.04 2.7 K3.05 3.0 K3.06 2.9

2.8

SYSTEM: 262002 Uninterruptable Power Supply (A.C./D.C.)

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K3.09	Drywell ventilation control: Plant-Specific	2.4	2.7
K3.10	Containment isolation: Plant-Specific		2.8
K3.11	MSIV's: Plant-Specific		2.9
K3.12	Control rod drive mechanism: Plant-Specific		2.5
K3.13	Rx pressure: Plant-Specific		2.9
K3.14	Rx power: Plant-Specific		3.1
K3.15	Main turbine operation: Plant-Specific		2.7
K3.16	Control room recorders: Plant-Specific	2.4	2.6
K3.17	Process monitoring: Plant-Specific	. 2.9	3.1
K4.	Knowledge of UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Transfer from preferred power to alternate power		
	supplies	. 3.1	3.4
K5.	Knowledge of the operational implications of the following concepts as they apply to UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.): (CFR: 41.5 / 45.3)		
K5.01	General principles of static inverter operation	. 2.3*	2.3
K5.02	General principles of motor generator operation:		
	Plant-Specific	. 2.4	2.5
K5.03	General principles of inertia fly wheel operation:		
TT 0.4	Plant-Specific		2.4*
K5.04	General principles of static switch operation	. 2.1*	2.2*
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.): (CFR: 41.7 / 45.7)		
K6.01	A.C. electrical power	2.7	2.9
K6.02	D.C. electrical power		3.1
K6.03	Static inverter	. 2.7	2.9

SYSTEM: 262002 Uninterruptable Power Supply (A.C./D.C.)

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.) controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02	Inverter electrical outputs		2.6 2.9
A2.	Ability to (a) predict the impacts of the following on the UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Under voltage	. 2.6	2.8
A2.02	Over voltage		2.7
A2.03	Frequency changes in the system		2.6
A2.04	Abnormal battery operation: BWR-1	. 3.2	3.4
A3.	Ability to monitor automatic operations of the UNINTERRUPTABLE POWER SUPPLY (A.C./D.C.) including: (CFR: 41.7/45.7)		
A3.01	Transfer from preferred to alternate source	. 2.8	3.1
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	Transfer from alternative source to preferred source	. 2.8	3.1

3.7	Instrumentation	page
215005	Average Power Range Monitor/Local Power Range Monitor	3.7-3
215003	Intermediate Range Monitor System	3.7-7
216000	Nuclear Boiler Instrumentation	3.7-10
272000	Radiation Monitoring System	3.7-15
212000	Reactor Protection System	3.7-19
215002	Rod Block Monitor System	3.7-24
201005	Rod Control and Information System	3.7-27
214000	Rod Position Information System	3.7-30
201004	Rod Sequence Control System (Plant Specific)	3.7-33
201006	Rod Worth Minimizer System (Plant Specific)	3.7-35
215004	Source Range Monitor System	3.7-38
215001	Traversing In-Core Probe	3.7-41

This page left blank

TASK: Perform lineups of the nuclear instrumentation system

Monitor the nuclear instrumentation system

Startup the nuclear instrumentation system

Place a source range module in/out of service

Place power range instruments in/out of service

Operate the nuclear instrumentation system

Secure the nuclear instrumentation system

Place transversing incore probe in/out of service

Operate range switches on IRM on power increase and decrease (write in)

Conduct average power range meter (APRM) instrument functional test

Conduct intermediate range monitor - average power range monitor instrument range overlap check

Conduct IRM-inoperative functional test and IRM-high flux functional instrument check

Conduct APRM-high flux in start up or refuel functional test

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between AVERAGE POWER RANGE MONITOR/LOCAL POWER RANGE MONITOR SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	RPS	4.0
K1.02	IRM	3.7
K1.03	RBM: Plant-Specific	3.5
K1.04	LPRM channels	3.6
K1.05	Four rod display: Plant-Specific	3.2
K1.06	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8*
K1.07	Process computer, performance monitoring system	2.9
K1.08	Display control system: Plant-Specific	3.0
K1.09	Reactor recirculation system: BWR-5,6	3.6
K1.10	Reactor manual control system: Plant-Specific	3.3
K1.11	Rod control and information system: Plant-Specific	3.4
K1.12	Full core display 3.2	3.2
K1.13	Traversing incore probe system	3.0
K1.14	Reactor vessel	2.9
K1.15	Redundant reactivity control system: Plant-Specific	4.0
K1.16	Flow converter/comparator network: Plant-Specific	3.4
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	LPRM channels	2.6
K2 02	APRM channels	2.8

Tasks as noted previously

		IMPORTANCE		
K/A NO.	KNOWLEDGE		RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the AVERAGE POWER RANGE MONITOR/LOCA MONITOR SYSTEM will have on following: (CFR: 41.7 / 45.4)			
K3.01	RPS		4.0	4.0
K3.02	Reactor recirculation system: BWR-5,6		3.5	3.5
K3.03	Reactor manual control system: Plant-Specific			3.3
K3.04	Rod control and information system: Plant-Specific 3	.4	3.4	
K3.05	Reactor power indication			3.8
K3.06	IRM: Plant-Specific			3.6
K3.07	Rod block monitor: Plant-Specific			3.3
K3.08	†core thermal calculations		3.0	3.4
K4.	Knowledge of AVERAGE POWER RANGE MONIT RANGE MONITOR SYSTEM design feature(s) and/ interlocks which provide for the following: (CFR: 41.7)		X	
K4.01	Rod withdrawal blocks		. 3.7	3.7
K4.02	Reactor SCRAM signals		4.1*	4.2
K4.03	Eliminates the necessity of running signal leads from each LPRM channel to the operator's console full core			
	display		2.1?*	2.2?*
K4.04	Individual LPRM detector replacement		2.0*	2.4*
K4.05	Alarm seal-in		2.4	2.4
K4.06	Effects of detector aging on LPRM/APRM readings		2.6	2.8
K4.07	Flow biased trip setpoints		3.7	3.7
K4.08	Sampling of overall core power in each APRM			
	(accomplished through LPRM assignments and symmet	rical		
	rod patterns)		2.7	3.1
K5.	Knowledge of the operational implications of the following concepts as they apply to AVERAGE POW RANGE MONITOR/LOCAL POWER RANGE MON (CFR: 41.5 / 45.3)			
K5.01	LPRM detector operation		2.8	2.9
K5.02	Effects of voids on LPRM indication		2.7	2.8
K5.03	Control rod symmetrical patterns		2.9	3.3
K5.04	LPRM detector location and core symmetry		2.9	3.2
K5.05	Core flow effects on APRM trip setpoints		3.6	3.6
K5.06	Assignment of LPRM's to specific APRM channels		2.5*	2.6*

Tasks as noted previously

		IMPORTANCE	
K/A NO.	KNOWLEDGE	RO	SRO
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the AVERAGE POWER I MONITOR/LOCAL POWER RANGE MONITOR SY (CFR: 41.7 / 45.7)	RANGE	
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07	RPS		3.8 2.8 3.3 3.2 3.1 2.4 3.3
A1.	ABILITY Ability to predict and/or monitor changes in parameters associated with operating the AVERAGI RANGE MONITOR/LOCAL POWER RANGE MON controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06	Reactor power indication RPS status Control rod block status SCRAM and rod block trip setpoints Lights and alarms Recirculation flow control valve position: Plant- Specific APRM (gain adjustment factor)		4.0 4.0 3.6 4.1 3.2 3.3 3.4
A2.	Ability to (a) predict the impacts of the following or the AVERAGE POWER RANGE MONITOR/LOCAL MONITOR SYSTEM; and (b) based on those predic use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)	L POWER RANGE	
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08 A2.09	Power supply degraded Upscale or downscale trips Inoperative trip (all causes) SCRAM trip signals Loss of recirculation flow signal Recirculation flow channels upscale Recirculation flow channels flow mismatch Faulty or erratic operation of detectors/systems Failed recorder		3.1 3.7 3.8 3.9 3.6 3.5 3.4 3.4 2.4

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A2.10	Changes in void concentration	2.9
A3.	Ability to monitor automatic operations of the AVERAGE POWER RANGE MONITOR/LOCAL POWER RANGE MONITOR SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Four rod display: Plant-Specific	3.5
A3.02	Full core display	3.5
A3.03	Meters and recorders	3.3
A3.04	Annunciator and alarm signals	3.2
A3.05	Flow converter/comparator alarms	3.3
A3.06	Maximum disagreement between flow comparator channels:	
	Plant-Specific	3.1
A3.07	RPS status	3.8
A3.08	Control rod block status	3.6
A4.	Ability to manually operate and/or monitor in the control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	IRM/APRM recorder	3.1
A4.02	CRT display indicators: Plant-Specific	2.8
A4.03	APRM back panel switches, meters and indicating lights	3.3
A4.04	LPRM back panel switches, meters and indicating lights	3.2
A4.05	Trip bypasses	3.4
A4.06	Verification of proper functioning/ operability	3.8

SYSTEM: 215003 Intermediate Range Monitor (IRM) System

TASK: Perform lineups of the nuclear instrumentation system

Monitor the nuclear instrumentation system

Startup the nuclear instrumentation system

Place an intermediate range module in/out of service

Operate the nuclear instrumentation system

Secure the nuclear instrumentation system

Operate range switches on IRM on power increase and decrease (write in)

Conduct source range meter, intermediate range meter detector not in startup rod block functional test

Conduct intermediate range monitor - average power range monitor instrument range overlap check

Conduct IRM-inoperative functional test and IRM-high flux functional instrument check

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between INTERMEDIATE RANGE MONITOR (IRM) SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	RPS	3 9	3.9
K1.02	Reactor manual control		3.6
K1.03	Rod control and information system: Plant-Specific		3.1
K1.04	Process computer/ performance monitoring system	3.1	5.1
11110	(SPDS/ERIS/CRIDS/GDS): Plant-Specific	2.5	2.8
K1.05	Display control system: Plant-Specific		3.3
K1.06	APRM SCRAM signals: Plant-Specific		4.0
K1.07	Reactor vessel		3.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	IRM channels/detectors	2.5*	2.7
К3.	Knowledge of the effect that a loss or malfunction of the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM will have on following: (CFR: 41.7/45.4)		
K3.01	RPS	3.9	4.0
K3.02	Reactor manual control		3.6
K3.03	Rod control and information system: Plant-Specific	3.7	3.7
K3.04	Reactor power indication		3.6
K3.05	APRM: Plant-Specific	3.7	3.8

SYSTEM: 215003 Intermediate Range Monitor (IRM) System

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K4.	Knowledge of INTERMEDIATE RANGE MONITOR (IRM) SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02 K4.03 K4.04 K4.05 K4.06	Rod withdrawal blocks3.7Reactor SCRAM signals4.0Gamma compensation2.4Varying system sensitivity levels using range switches2.9Changing detector position2.9Alarm seal-in2.6 Knowledge of the operational implications of the	3.7 4.0 2.4 2.9 3.0 2.6
	following concepts as they apply to INTERMEDIATE RANGE MONITOR (IRM) SYSTEM: (CFR: 41.5 / 45.3)	
K5.01	Detector operation	2.7
K5.02	Gamma discrimination	2.3
K5.03	Changing detector position	3.1
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM: (CFR: 41.7 / 45.7)	
K6.01	Reactor protection system (power supply): Plant- Specific	3.8
K6.02	24/48 volt D.C. power: Plant-Specific	3.8
K6.03	Detector drive motor	2.9
K6.04	Detectors	3.0
K6.05	Trip units	3.2
K6.06	APRM	3.4
K6.07	Recorder	2.3
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	Detector position	3.3
A1.02	Reactor power indication response to rod position	
	changes	3.7
A1.03	RPS status	3.7
A1.04	Control rod block status	3.4

SYSTEM: 215003 Intermediate Range Monitor (IRM) System

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
A1.05	SCRAM and rod block trip setpoints	3.9
A1.06	Lights and alarms	3.2
A2.	Ability to (a) predict the impacts of the following on the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Power supply degraded 2.8	3.2
A2.02	IRM inop condition	3.7
A2.03 A2.04	Stuck detector	3.1 3.8
A2.04 A2.05	Up scale or down scale trips	3.6 3.5
A2.06	Faulty range switch	3.2
A2.07	Failed recorder	2.7
A3.	Ability to monitor automatic operations of the INTERMEDIATE RANGE MONITOR (IRM) SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Meters and recorders	3.3
A3.02	Annunciator and alarm signals	3.3
A3.03	RPS status	3.6
A3.04	Control rod block status	3.5
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	IRM recorder indication	3.3
A4.02	CRT display indications: Plant-Specific	2.8
A4.03	IRM range switches	3.4
A4.04	IRM back panel switches, meters, and indicating lights	3.3
A4.05	Trip bypasses	3.4
A4.06	Detector drives	2.9
A4.07	Verification of proper functioning/ operability	3.6

TASK: Perform lineups of the non-nuclear instrumentation system Monitor the non-nuclear instrumentation system

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause- effect relationships between NUCLEAR BOILER INSTRUMENTATION and the following:	
	(CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Reactor protection system	4.1
K1.02	PCIS/NSSSS	4.0
K1.03	Reactor core isolation cooling system: Plant-Specific	
		3.6
K1.04	High pressure core spray system: Plant-Specific	4.0
K1.05	Residual heat removal: Plant-Specific	3.9
K1.06	Low pressure core spray	3.9
K1.07	Automatic depressurization system	4.1
K1.08	Relief/safety valves	3.9
K1.09	Redundant reactivity control/ alternate rod insertion;	
	Plant-Specific	4.0
K1.10	Recirculation flow control system	3.4
K1.11	MSIV leakage control system: Plant-Specific	2.8
K1.12	Reactor water level control system	3.7
K1.13	Feedwater system 3.4	3.5
K1.14	High pressure coolant injection: Plant-Specific	4.1*
K1.15	Isolation condenser: Plant-Specific	4.1*
K1.16	Main turbine	3.1
K1.17	Emergency generators	3.7
K1.18	Analog trip system: Plant-Specific	3.1
K1.19	Anticipated transient without scram system: Plant-	
	Specific	3.9
K1.20	Process computer: Plant-Specific	2.8
K1.21	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.9*
K1.22	Reactor vessel	3.8
K1.23	Recirculation system	3.4
K2.	Vnowledge of electrical newer complice to the	
KZ.	Knowledge of electrical power supplies to the following:	
	(CFR: 41.7)	
	(CFR. 41.7)	
K2.01	Analog trip system: Plant-Specific	2.8
K3.	Knowledge of the effect that a loss or malfunction of	
	the NUCLEAR BOILER Instrumentation will have on	
	following:	
	(CFR: 41.7 / 45.4)	
K3.01	Reactor protection system	4.3*
K3.02	PCIS/NSSSS	4.3*
123.02	1 CID/110000 4.U	4.5

Tasks as noted previously

	INFORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K3.03	Decetor core icaletion cooling systems Plant Specific		
K3.03	Reactor core isolation cooling system: Plant-Specific	3.5	3.8
K3.04	High pressure core spray system: Plant-Specific		4.0
K3.05	Residual heat removal: Plant-Specific		3.9
K3.06	•		3.9
K3.07	Low pressure core spray		3.9 4.1
	Automatic depressurization system		3.7
K3.08 K3.09	Relief/safety valves	3.0	3.7
K3.09	Redundant reactivity control/ alternate rod insertion:	2.7	4.0
172.10	Plant-Specific		4.0
K3.10	Recirculation flow control system		3.3
K3.11	MSIV leakage control system: Plant-Specific		2.8
K3.12	Reactor water level control system		3.8
K3.13	Feedwater system		3.5
K3.14	High pressure coolant injection: Plant-Specific		4.2*
K3.15	Isolation condenser: Plant-Specific		4.2*
K3.16	Main turbine	3.0	3.1
K3.17	Emergency generators	3.5	3.7
K3.18	Analog trip system: Plant-Specific	2.9*	3.0
K3.19	Anticipated transient without scram system: Plant-		
	Specific	3.7	4.0*
K3.20	Process computer: Plant-Specific	2.5	2.6
K3.21	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.6*	2.8*
K3.22	Reactor vessel		3.3
K3.23	Vessel temperature monitoring		3.3
K3.24	Vessel level monitoring		4.1
K3.25	Vessel pressure monitoring		4.1
K3.26	Core flow monitoring		3.7
K3.27	Core differential pressure monitoring		3.1
K3.28	Loose parts detection in the primary system: Plant-	,	0.1
113.20	Specific	2.0*	2.1*
K3.29	Jet pump flow monitoring: Plant-Specific		3.2
K3.30	Recirculation system		3.3
113.30	Recirculation system	3.2	3.3
K4.	Knowledge of NUCLEAR BOILER INSTRUMENTATION design		
	feature(s) and/or interlocks which provide for the		
	following:		
	(CFR: 41.7)		
TZ 4 O 1			
K4.01	Reading of nuclear boiler parameters outside the	2.6	2.6
TT 1 00	control room		3.6
K4.02	Physical separation of sensors		3.2
K4.03	Redundancy of sensors		3.6
K4.04	Inputs to the reactor protection system		3.8
K4.05	Initiation of the emergency core cooling systems		4.1
K4.06	Initiation of the PCIS/NSSSS		4.0
K4.07	Recirculation pump protection: Plant-Specific	2.9	3.0

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
K4.08	Protection for the main turbine from high moisture	
	carryover	3.0
K4.09	Protection against filling the main steam lines from	2.2
TT 1 10	the feed system	3.3
K4.10	Automatic recirculation pump speed control: Plant-	2.1
	Specific	3.1
K4.11	Inputs to the redundant reactivity control	4.0
TT 1 10	system/alternate rod insertion: Plant-Specific	4.0
K4.12	Reactor vessel overpressure protection	3.9
K4.13	Overpressure protection for various low-pressure	2.4
TT 1 1 1	systems	3.4
K4.14	Temperature compensation for reactor water level	2.4
	indication: Plant-Specific	3.4
K5.	Knowledge of the operational implications of the	
	following concepts as they apply to NUCLEAR BOILER	
	INSTRUMENTATION:	
	(CFR: 41.5 / 45.3)	
K5.01	Vessel level measurement	3.2
K5.02	Vessel pressure measurement	3.2
K5.03	Vessel temperature measurement	3.2
K5.04	Vessel differential pressure measurement	2.9
K5.05	Vessel vibration measurement (loose parts monitor)	2.3
K5.06	Rapid vessel depressurization effects on vessel level	
	indications	3.6
K5.07	Elevated containment temperature effects on level	
	indication	3.8
K5.08	Steam flow effect on reactor water level	3.2
K5.09	Recirculation flow effects on level indications:	
	Design-Specific	2.9
K5.10	Indicated level versus actual vessel level during	
	vessel heatups or cooldowns	3.3
K5.11	Indicated vessel temperature response during rapid	
110111	heatups or cooldowns	3.3
K5.12	Effects on level indication due to rapid changes in	0.0
110.12	void fraction	3.3
K5.13	Reference leg flashing: Design-Specific	3.6
K5.14	Density	2.6
K5.15	Static pressure	2.2*
K5.16	Dynamic pressure 2.1*	2.1*

Tasks as noted previously

A2.14

IMPORTANCE K/A NO. KNOWLEDGE RO SRO K6. Knowledge of the effect that a loss or malfunction of the following will have on the NUCLEAR BOILER **INSTRUMENTATION:** (CFR: 41.7 / 45.7) K6.01 3.3 K6.02 3.0 K6.03 2.8 **ABILITY** Al. Ability to predict and/or monitor changes in parameters associated with operating the NUCLEAR **BOILER INSTRUMENTATION controls including:** (CFR: 41.5 / 45.5) A1.01 3.3 A1.02 Removing or returning a sensor (transmitter) to service 2.9* 3.1* A1.03 3.2* A1.04 2.8* A2. Ability to (a) predict the impacts of the following on the NUCLEAR BOILER INSTRUMENTATION; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 3.2 A2.02 3.0 A2.033.1 A2.04 3.0 A2.05 3.1 A2.06 A2.07 3.5 A2.08 A2.09 3.2 A2.10 3.5 A2.11 3.3 A2.12 2.9 A2.13 3.0

2.9

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A3.	Ability to monitor automatic operations of the NUCLEAR BOILER Instrumentation including: (CFR: 41.7 / 45.7)	
A3.01	Relationship between meter/recorder readings and actual parameter values: Plant-Specific	3.4
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Recorders	
A4.02	Channel select controls	3.1
A4.03	Process computer: Design-Specific	3.1

TASK: Perform lineups of the area radiation monitoring system

Operate area radiation monitors

Monitor area radiation

Perform lineups of process radiation monitoring system

Operate process radiation monitors

Monitor process radiation monitor operation

K/A NO.	KNOWLEDGE	RO	SRO
		110	5110
K1.	Knowledge of the physical connections and/or cause-		
	effect relationships between RADIATION MONITORING SYSTEM and the following:		
	(CFR: 41.2 to 41.9 / 45.7 to 45.8)		
	(CFR. 41.2 to 41.77 43.7 to 43.0)		
K1.01	Main steam system	. 3.6	3.8
K1.02	Offgas system (augmented offgas): Plant-Specific	. 3.2	3.5
K1.03	Stack gas: Plant-Specific	. 3.3	3.6
K1.04	Applicable component cooling water system	. 2.9	2.9
K1.05	Radwaste system	. 2.8	3.1
K1.06	Reactor building ventilation system: Plant-Specific	. 3.2	3.3
K1.07	Isolation condenser: Plant-Specific	. 3.0	3.2
K1.08	Reactor protection system	. 3.6	3.9
K1.09	Primary containment isolation system	. 3.6	3.8
K1.10	Reactor building refuel floor: Plant-Specific		3.6
K1.11	Reactor building overhead crane; Plant-Specific	. 2.1*	2.4*
K1.12	Reactor building	. 3.1	3.2
K1.13	Turbine building		3.0
K1.14	Radwaste building: Plant-Specific	. 2.7	2.8
K1.15	Filter building: Plant-Specific	. 2.8	3.0
K1.16	Process computer	. 2.2*	2.3*
K1.17	SPDS/ERIS/CRIDS/GDS: Plant-Specific	. 2.4	2.7
K1.18	Primary containment/containment building: Plant-		
	Specific	. 3.1	3.1
K1.19	Drywell		3.2
K1.20	†Auxiliary building: Plant-Specific	. 2.8	3.0
K1.21	Circulating water: Plant-Specific	. 2.3	2.4
K1.22	Fuel building: mark-III	. 3.0	3.4
K1.23	Continuous air monitoring: Plant-Specific	. 3.0	3.3
K2.	Knowledge of electrical power supplies to the		
	following:		
	(CFR: 41.7)		
K2.01	Main steamline radiation monitors	. 2.5	2.8
K2.02	Offgas radiation monitoring system	. 2.5	2.8
K2.03	Stack gas radiation monitoring system	. 2.5	2.8
K2.04	Process liquid radiation monitoring system	. 2.3	2.5

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
K2.05	Reactor building ventilation monitors: Plant-Specific	2.9
K2.06	Area radiation monitors 2.1*	2.2*
K2.07	Control room ventilation monitors: Plant-Specific	2.4*
К3	Knowledge of the effect that a loss or malfunction of the RADIATION MONITORING System will have on following: (CFR: 41.5 / 45.3)	
K3.01	†Station liquid effluent release monitoring	3.8
K3.02	†Station gaseous effluent release monitoring	3.8
K3.03	Station area radiation monitoring	3.4
K3.04	Main steam system	3.8
K3.05	Offgas system	3.7
K3.06	Reactor building ventilation: Plant-Specific	3.6
K3.07	Reactor building overhead crane operation: Plant-	0.0
113.07	Specific	3.0
K3.08	†Auxiliary building ventilation: Plant-Specific	3.3
K3.09	Radwaste building ventilation: Plant-Specific	3.1
K3.10	Control room ventilation: Plant-Specific	3.3
K4.	Knowledge of RADIATION MONITORING System design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02	Redundancy	2.8
K4.03	exceeded	4.1
	logic during conditions of instrument failure	3.9
K5.	Knowledge of the operational implications of the following concepts as they apply to RADIATION MONITORING SYSTEM: (CFR: 41.7 / 45.4)	
K5.01	Hydrogen injection operation's effect on process	
	radiation indications: Plant-Specific	3.5

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
К6	Knowledge of the effect that a loss or malfunction of the following will have on the RADIATION MONITORING SYSTEM: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06	Reactor protection system D.C. power A.C. power Process computer SPDS/ERIS/CRID/GDS: Plant-Specific Continuous air monitoring: Plant-Specific ABILITY	2.5 2.8 2.0* 2.1*	3.2 2.7 3.0 2.2* 2.4* 2.6
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RADIATION MONITORING SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Lights, alarms, and indications associated with normal operations	3.2	3.2
A1.02	Lights, alarms, and indications associated with surveillance testing		2.9
A2.	Ability to (d) predict the impacts of the following on the RADIATION MONITORING SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Fuel element failure		4.1
A2.02 A2.03	Reactor protection system power failure		3.6 3.1
			2.8
A2.04 A2.05	D.C. electrical failure Loss of dilution steam		2.6
A2.06	Downscale trips		2.9
A2.00 A2.07	Hydrogen injection operation: Plant-Specific		2.9
A2.07 A2.08			3.1
A2.09	Offgas system failure		3.3
A2.09 A2.10	Low fuel pool level		3.3 4.1
	Leakage and/or breaks from contaminated systems to	3.9	4.1
A2.11	·	2.4	27
A 2 12	atmosphere or to other process systems		3.7
A2.12	†Refuel floor handling accidents/operations		4.0
A2.13 A2.14	Low reactor water level during refueling operations		3.8
A2.14 A2.15	Loss of, or inadequate, shielding		3.5
A4.13	Maintenance operations	۷.3	2.7

Tasks as noted previously

	K/A NO.	ABILITY RO	SRO
	A2.16	Instrument malfunctions	2.9
	A3.	Ability to monitor automatic operations of the RADIATION MONITORING SYSTEM including: (CFR: 41.7 / 45.7)	
	A3.01	Main steam isolation indications	3.9
	A3.02	Offgas system isolation indications	3.7
	A3.03	Liquid radwaste isolation indications	3.5
	A3.04	Radwaste handing interlocks	2.8
	A3.05	Refuel floor overhead crane operation interrupt:	
		Plant-Specific	3.1
	A3.06	Ventilation system isolation indications	3.4
l	A3.07	Recorder indications	2.9
•	A3.08	Meter indications	2.9
	A3.09	Containment isolation indications	3.5
	A3.10	Lights and alarms	3.2
	A3.11	Circulating water system blowdown isolations: Plant-	
		Specific	2.7
	A4.	Ability to manually operate and/or monitor in the	
		control room: (CFR: 41.7 / 45.5 to 45.8)	
	A4.01	Recorder indications	2.9
	A4.02	Meter indications	3.0
l	A4.03	Power supply status indicators	2.6
l	A4.04	SPDS/ERIS/CRID/GDS	2.7*
•	A4.05	†Convert process radiation monitor readings to offsite	
		release rates: Plant-Specific	3.7*
	A4.06	†Manually trip process radiation monitor logic	3.2

TASK: Energize the reactor protection system

Place a reactor protection channel in the tripped condition

Bypass a trip condition on a reactor protection channel (bypass an average power range monitor trip)

Deenergize the reactor protection system

Monitor the reactor protection system

Operate the reactor protection system MG sets

Operate the reactor mode switch

Operate the reactor trip breakers

Shift the reactor protection system bus to the alternate power supply

Conduct manual SCRAM functional test

Conduct mode switch in shutdown functional test

Conduct RPS channel test switch functional test

K/A NO.	KNOWLEDGE	RO	SRC
K1.	Knowledge of the physical connections and/or cause-effect relationships between REACTOR PROTECTION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
	(CFR: 41.2 to 41.9 / 45. / to 45.8)		
K1.01	Nuclear instrumentation	3.7	3.9
K1.02	Nuclear boiler instrumentation	3.7	3.9
K1.03	Recirculation system	3.4	3.6
K1.04	A.C. electrical distribution		3.6
K1.05	Process radiation monitoring system	3.3	3.6
K1.06	Control rod drive hydraulic system		3.6
K1.07	Relief/safety valves (low-low-set logic): Plant-		
	Specific	3.3	3.5
K1.08	Control rod and drive mechanism		3.1
K1.09	Process computer	2.3	2.4
K1.10	Main turbine		3.4
K1.11	Condenser vacuum		3.5
K1.12	Reactor/turbine pressure control system: Plant-		
	Specific	3.4	3.6
K1.13	Containment pressure		3.6
K1.14	Main steam system		3.7
K1.15	SCRAM air header pressure		3.9
K2.	Knowledge of electrical power supplies to the following:		
	(CFR: 41.7)		
K2.01	RPS motor-generator sets	3.2	3.3
K2.02	Analog trip system logic cabinets		2.9

Tasks as noted previously

K/A NO	D. KNOWLEDGE		RO	SRO
К3.	Knowledge of the effect that a loss or malfunction of the REACTOR PROTECTION SYSTEM will have on following: (CFR: 41.7 / 45.4)			
K3.01 K3.02	Process radiation monitoring Primary containment isolation system/nuclear steam	3.0	3.2	
	supply shut-off: Plant-Specific	3.7	3.9	
K3.03 K3.04	Local power range monitoring system: Plant-Specific Average power range monitoring system: Plant-Specific	3.3	3.4	
		3.5	3.6	
K3.05	RPS logic channels	3.7	3.8	
K3.06	Scram air header solenoid operated valves	4.0	4.1	
K3.07	Reactor power (thermal heat flux)	3.8	3.9	
K3.08	Reactor coolant primary system integrity	3.6	3.8	
K3.09	The magnitude of heat energy that must be absorbed by			
3.6	the containment during accident/transient conditions		3.2	
K3.10	The ability of the core cooling systems to provide			
	adequate core cooling during loss of coolant accidents	3.5	3.9	
K3.11	Recirculation system	3.0	3.3	
K3.12	Secondary containment integrity	3.2	3.3	
K4.	Knowledge of REACTOR PROTECTION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)			
IZ 4 O1	Contain a dead on the second of the Pater		2.4	2.6
K4.01	System redundancy and reliability		3.4	3.6
K4.02	The prevention of a reactor SCRAM following a single component failure		3.5	3.7
K4.03	The prevention of supplying power to a given RPS bus		• • •	
K4.04	from multiple sources simultaneously		3.0*	3.1*
	simultaneously from the alternate power source:			
K4.05	Plant-Specific			3.1
	power operation			3.6
K4.06	Select rod insertion: Plant-Specific			3.0
K4.07	Manual system activation (trip)		4.1*	4.1
K4.08	Complete control rod insertion following SCRAM signal generation		4.2*	4.2*
K4.09	Control rod insertion following RPS system electrical			
	failure			3.9
K4.10	Individual rod SCRAM testing		3.3	3.6
K4.11	Operation with shorting links removed: Plant-Specific		3.3	3.5
K4.12	Bypassing of selected SCRAM signals (manually and			-
	automatically): Plant-Specific		3.9	4.1

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR PROTECTION SYSTEM: (CFR: 41.5 / 45.3)		
K5.01 K5.02	Fuel thermal time constant		2.9 3.4
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR PROTECTION SYSTEM: (CFR: 41.7/45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05	A.C. electrical distribution Nuclear instrumentation Nuclear boiler instrumentation D.C. electrical distribution RPS sensor inputs	3.7 3.5 2.8	3.8 3.9 3.7 3.1 3.8
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR PROTECTION SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08 A1.09 A1.10 A1.11	RPS motor-generator output voltage RPS motor-generator output amps RPS motor-generator output frequency: Plant-Specific RPS bus voltage: Plant-Specific RPS bus frequency: Plant-Specific Reactor power Rod position information Valve position Individual relay status: Plant-Specific Process computer System status lights and alarms	2.8* 2.4* 2.8* 2.6* 4.2* 3.4 3.4 2.7 2.2*	2.9 2.9 2.5 3.0 2.7 4.2* 3.4 3.4 3.0 2.4* 3.3
A2.	Ability to (a) predict the impacts of the following on the REACTOR PROTECTION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02	RPS motor-generator set failure		3.9 3.9

Tasks as noted previously

	IVIFORTANCE		~- ~
K/A NO.	ABILITY	RO	SRO
A2.03	Surveillance testing		3.5
A2.04	Nuclear instrument system failure		3.7
A2.05	Nuclear boiler instrument system failure		3.7
A2.06	High reactor power4	4.1*	4.2*
A2.07	High reactor pressure4	4.1*	4.2*
A2.08	Low reactor level	4.1*	4.2*
A2.09	High containment/drywell pressure 4	4.1*	4.3*
A2.10	Reactor/turbine pressure control system low pressure:		
	Plant-Specific	3.6	3.8
A2.11	Main steamline isolation valve closure		4.1
A2.12	Main turbine stop control valve closure4	4.0	4.1
A2.13	Low condenser vacuum: Plant-Specific		3.9
A2.14	High SCRAM instrument volume water level		4.0
A2.15	Load rejection		3.8
A2.16	Changing mode switch position		4.1
A2.17	Main steamline high radiation		4.2*
A2.18	†SCRAM air header low pressure		3.9
A2.19	Partial system activation (half-SCRAM)		3.9
A2.20	Full system activation (full-SCRAM) 4		4.2*
A2.20 A2.21	†Failure of individual relays to reposition: Plant-	t. 1	4.2
A2.21	Specific	3 6	3.9
	specific	5.0	3.9
A3.	A hility to manitar automatic anarotions of the DEACTOR		
A3.	Ability to monitor automatic operations of the REACTOR		
	PROTECTION SYSTEM including:		
	(CFR: 41.7 / 45.7)		
42.01	D 4 D	4 4 \$	4 4 \$
A3.01	Reactor Power		4.4*
A3.02	Individual system relay status: Plant-Specific		3.5
A3.03	Rod position		4.2*
A3.04	System status lights and alarms		3.8
A3.05	SCRAM instrument volume level		3.9
A3.06	Main turbine trip: Plant-Specific		4.2*
A3.07	SCRAM air header pressure	3.6	3.6
A3.08	Recirculation pump trip	3.7	3.7
A4.	Ability to manually operate and/or monitor in the		
	control room:		
	(CFR: 41.7 / 45.5 to 45.8)		
A4.01	Provide manual SCRAM signal(s)	4.6*	4.6*
A4.02	Perform system functional test(s)	3.6	3.7
A4.03	Provide manual select rod insertion: Plant-Specific	3.9	3.9
A4.04	Bypass SCRAM instrument volume high level SCRAM signal		3.9
A4.05	Reactor power		4.3*
A4.06	Control rod position		4.1*
A4.07	System status lights and alarms		3.9*
A4.08	Individual system relay status: Plant-Specific		3.4
	J J		

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
A4.09	SCRAM instrument volume level	3.8
A4.10	Main turbine trip: Plant-Specific	4.0
A4.11	Scram air header pressure	3.7
A4.12	Close/open SCRAM instrument volume vent and/or drain	
	valves	3.9
A4.13	†Perform individual control rod SCRAM testing	3.6
A4.14	Reset system following system activation	3.8
A4.15	Recirculation pump trip/EOC RPT	3.8
A4.16	Manually activate anticipated transient without SCRAM	
	circuitry/RRCS: Plant-Specific	4.4*
A4.17	Perform alternate reactivity/ shutdown operations	4.1

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between ROD BLOCK MONITOR SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07	APRM: BWR-3,4,5 LPRM: BWR-3,4,5 Reactor manual control: BWR-3,4,5 Recirculation system: BWR-3,4,5 Four rod display: BWR-3,4,5 Control rod selection: BWR-3,4,5 IRM: BWR-3,4,5	3.2 3.2 3.1 3.0 3.0	3.0 3.1 3.2 3.1 3.0 3.1 2.0*
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03	RBM channels: BWR-3,4,5 Recorders: BWR-3,4,5 APRM channels: BWR-3,4,5	2.1*	2.8* 2.1* 2.9
К3.	Knowledge of the effect that a loss or malfunction of the ROD BLOCK MONITOR SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 †Limit	Reactor manual control system: BWR-3,4,5		3.5 3.6
K4.	Knowledge of ROD BLOCK MONITOR SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03	Prevent control rod withdrawal: BWR-3,4,5	2.9	3.5 3.0 3.0
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD BLOCK MONITOR SYSTEM: (CFR: 41.5 / 45.3)		
K5.01 K5.02	Trip reference selection: Plant-Specific		2.8 2.5

SYSTEM: 215002 Rod Block Monitor System

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the ROD BLOCK MONITOR SYSTEM: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05	RPS: BWR-3,4,5 Instrument power: Plant-Specific Essential power: Plant-Specific APRM reference channel: BWR-3,4,5 LPRM detectors: BWR-3,4,5 ABILITY	2.4 2.5 2.8	3.2 2.5 2.5 3.0 3.1
A1.	Ability to predict and/or monitor changes in parameters associated with operating the ROD BLOCK MONITOR SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Trip reference: BWR-3,4,5	2.7	2.8
A2.	Ability to (a) predict the impacts of the following on the ROD BLOCK MONITOR SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Withdrawal of control rod in high power region of	2.2	2.7
A2.02	core: BWR-3,4,5		3.5
12.02	comparator): BWR-3,4,5		3.3
A2.03 A2.04	Loss of associated reference APRM channel: BWR-3,4,5		3.3 2.8
A2.04 A2.05	RBM high or inoperable: BWR-3,4,5		3.3
A3.	Ability to monitor automatic operations of the ROD BLOCK MONITOR SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	Four rod display: BWR-3,4,5	3 1	3.1
A3.02	Meters and recorders: BWR-3,4,5		3.0
A3.03	Alarm and indicating lights: BWR-3,4,5		3.1
A3.04	Verification or proper functioning/ operability:		
	BWR-3,4,5		3.5
A3.05 A3.06	Back panel meters and indicating lights: BWR-3,4,5	3.2	3.2
	bypassed: BWR-3,4,5	2.6	2.6

SYSTEM: 215002 Rod Block Monitor System

Tasks as noted previously

K/A NO.	ABILITY RO	SRC
A4.	Ability to manually operate and/or monitor in the control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	IRM/RBM recorder/switch: BWR-3,4,5	2.7
A4.02	RBM back panel switches, meters and indicating lights:	
	BWR-3,4,5	2.9
A4.03	Trip bypasses: BWR-3,4,5	2.8
A4.04	"Push to Check" pushbutton: Plant-Specific	2.5
A4.05	"Setup" pushbutton: Plant-Specific	2.5
A4.06	Surveillance testing: BWR-3,4,5	2.7

SYSTEM: 201005 Rod Control and Information System (RCIS)

K/A NO.	IMPOR KNOWLEDGE	RTANCE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between ROD CONTROL AND INFORMATION SYSTEM (RCIS) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	ĸ	SKO
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07	Neutron monitoring system: BWR-6 Reactor/turbine pressure control system: BWR-6 Control rod drive system: BWR-6 Rod position information system: BWR-6 Rod action control system: BWR-6 Rod gang drive system: BWR-6 Rod interface system: BWR-6	3.3 3.7 3.7 3.5 3.3	3.3 3.5 3.7 3.7 3.5 3.3
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	A.C. electrical power: BWR-6	2.4	2.6
K3.	Knowledge of the effect that a loss or malfunction of the ROD CONTROL AND INFORMATION SYSTEM (RCIS) will have on following: (CFR: 41.7/45.4)		
K3.01 K3.02 K3.03 K3.04	Control rod drive system: BWR-6 Reactor startup: BWR-6 Reactor shutdown: BWR-6 †FIUX shaping: BWR-6	3.5 3.0	3.7 3.5 3.2 3.3

SYSTEM: 201005 Rod Control and Information System (RCIS)

K/A NO.	KNOWLEDGE IMPORTANCE RO	SRO
K4.	Knowledge of ROD CONTROL AND INFORMATION SYSTEM (RCIS) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Limiting the effects of a control Rod accident: BWR-6	
K4.02 K4.03 K4.04 K4.05 K4.06	Bank position withdrawal sequence (BPWS): BWR-6 3.3 Rod withdrawal block signals: BWR-6 3.5 Rod insertion block signals: BWR-6 3.5 Rod withdrawal limiter: BWR-6 3.5 Rod pattern controller rod blocks: BWR-6 3.5	3.2 3.3 3.5 3.5 3.5 3.5
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD CONTROL AND INFORMATION SYSTEM (RCIS): (CFR: 41.5 / 45.3)	
K5.01	†Rod pattern and program development: BWR-6	3.2
K5.02	Rod pattern controller (RPC): BWR-6	3.3
K5.03	Rod groups: BWR-6	2.7
K5.04	†Rod sequences: BWR-6	3.0
K5.05	Rod density: BWR-6	3.0
K5.06	Target rod pattern: BWR-6	2.8
K5.07	Low power alarm point: BWR-6	3.5
K5.08	Transition zone: BWR-6	3.5
K5.09	High power setpoints BWR-6	3,5
K5.10	Rod withdrawal limiter: BWR-6	3.3
K5.11	Control rod motion: BWR-6	3.3
K5.12	Command word generation and sequencing (operator	
	follow, scan and test): BWR-6	2.2*
K5.13	Position indication probes: BWR-6	2.7
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the ROD CONTROL AND INFORMATION SYSTEM (RCIS): (CFR: 41.7/45.7)	
K6.01	First stage shell pressure or opening of a bypass	3.2
K6.02	valve(s): BWR-6 3.2 Rod position signal: BWR-6 3.2	3.2
K6.03	A.C. electrical power: BWR-6 2.5	2.8
K6.04	IRM channel: BWR-6 3.0	3.2
K6.05	SRM channel: BWR-6	3.2
K6.06	APRM channel: BWR-6 3.0	3.2
170.00	AI KWI CHAIIICH. DWK-0 3.0	5.0

SYSTEM: 201005 Rod Control and Information System (RCIS)

K/A NO.	KNOWLEDGE IMPORTANCE RO	SRO
A1.	Ability to predict and/or monitor changes in parameters associated with operating the ROD CONTROL AND INFORMATION SYSTEM (RCIS) controls including: (CFR: 41.5 / 45.5)	
A1.01	First stage shell pressure/turbine load: BWR-6	3.3
A2.	Ability to (a) predict the impacts of the following on the ROD CONTROL AND INFORMATION SYSTEM (RCIS); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	High flux (SRM, IRM, APRM): BWR-6	3.5
A2.01 A2.02	Position indication probe failure: BWR-6	3.3
A2.02 A2.03	Insert block: BWR-6	3.2
A2.04	Withdraw block: BWR-6 3.2	3.2
A2.05	Insert required: BWR-6 3.2	3.2
A2.06	Insert inhibit: BWR-6	3.2
A2.07	Withdraw inhibit: BWR-6 3.2	3.2
A2.07 A2.08	LPRM upscale/down scale: BWR-6	3.2
A2.09	Test display blinking: BWR-6	3.2
A2.10	Data fault: BWR-6	3.0
A2.10 A2.11	Accumulator fault: BWR-6	3.5
A2.11 A2.12	Rod uncoupled: BWR-6	3.8
A2.12 A2.13	Rod drift: BWR-6	3.8
A2.13	Rod will. BWR-0	3.0
A3.	Ability to monitor automatic operations of the ROD CONTROL AND INFORMATION System (RCIS) including: (CFR: 41.7 / 45.7)	
A3.01	Operator control module lights: BWR-6	3.5
A3.02	Rod display module lights: BWR-6	3.5
A3.03	†Verification of proper functioning/ operability:	0.0
113.03	BWR-6	3.3
A3.04	Annunciator and alarm signals: BWR-6	3.3
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Operator control module (lights and push buttons):	
	BWR-6 3.7	3.7
A4.02	Rod display module (lights and push buttons): BWR-6	3.7
A4.03	Back panel indicating lights: BWR-6	3.3

SYSTEM: 214000 Rod Position Information System

Startup the rod position indication system TASK:

Perform a position indication alignment during a reactor startup

Monitor the rod position indication system Shutdown the rod position indication system (RPIS)

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between ROD POSITION INFORMATION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08	RWM: Plant-Specific RSCS: Plant-Specific CRDM RMCS: Plant-Specific Full core display: Plant-Specific RCIS: Plant-Specific Process computer CRIDS/ERIS/SPDS/GDS: Plant-Specific	2.9 3.0 3.2 3.3 3.4 2.7	3.2 3.1 3.1 3.2 3.3 3.4 3.0 2.6
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
	None		
K3.	Knowledge of the effect that a loss or malfunction of the ROD POSITION INFORMATION SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01	RWM: Plant-Specific	3.0	3.2
K3.02	RSCS: Plant-Specific		3.1
K3.03	RMCS: Plant-Specific	3.1	3.2
K3.04	RCIS: Plant-Specific	3.3	3.3
K3.05	Process computer	2.3	2.6
K3.06	CRIDS/ERIS/SPDS/GDS: Plant-Specific	2.3*	2.5
K4.	Knowledge of ROD POSITION INFORMATION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Reed switch locations	3.0	3.1
K4.02	Thermocouple		2.5

SYSTEM: 214000 Rod Position Information System

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD POSITION INFORMATION SYSTEM:	KO	SKO
K5.01	(CFR: 41.5 / 45.3) Reed switches	. 2.7	2.8
Xu.	the following will have on the ROD POSITION INFORMATION SYSTEM: (CFR: 41.7 / 45.7)		
K6.01 K6.02	A.C. electrical power		2.6 2.7
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the ROD POSITION INFORMATION SYSTEM controls including: (CFR: 41.5 / 45.5)		
	None		[
A2.	Ability to (a) predict the impacts of the following on the ROD POSITION INFORMATION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03	Failed reed switches Reactor SCRAM Overtravel/in-out	3.6	3.3 3.7 3.9
A3.	Ability to monitor automatic operations of the ROD POSITION INFORMATION SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	Full core display		3.3
A3.02	Alarm and indicating lights		3.1
A3.03 A3.04	Verification of proper functioning/ operability		3.7 3.8

SYSTEM: 214000 Rod Position Information System

Tasks as noted previously

KNOWLEDGE RO	SRO
Ability to manually operate and/or monitor in the	
(CFR: 41.7 / 45.5 to 45.8)	
RCIS rod action control bypass switches	3.3
Control rod position	3.8*
Control rod drive temperature	2.7
	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) RCIS rod action control bypass switches 3.2 Control rod position 3.8*

SYSTEM: 201004 Rod Sequence Control System (Plant Specific)

TASK: Conduct rod sequence control functional test

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC) and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04	Reactor manual control system: BWR-4,5 Turbine generator system: BWR-4,5 Rod position information system: BWR-4,5 Rod worth minimizer: BWR-4,5	3.1	3.3 3.1 3.1 3.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
	None		
К3.	Knowledge of the effect that a loss or malfunction of the ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC) will have on following: (CFR: 41.7/45.4)		
K3.01	Reactor manual control: BWR-4,5	. 3.3	3.4
K4.	Knowledge of ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Select blocks: BWR-4,5	3.0	3.1
K4.02	Insert rod blocks: BWR-4,5		3.2
K4.03	Withdraw rod blocks: BWR-4,5		3.4
K4.04	RSCS bypass as reactor power increases: BWR-4,5		3.3
K4.05	Rod movement, direction, and selection information:		
	BWR-4,5		3.2
K4.06	Group notch control: BWR-4,5		3.4
K4.07	Minimizing rod worth: BWR-4,5	. 3.6	3.7
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD SEQUENCE (CFR: $41.5 / 45.3$)		
	CONTROL SYSTEM (PLANT SPECIFIC):		
K5.01	Prevention of clad damage if a control rod drop		
	accident (CRDA) occurs: BWR-4,5		4.0
K5.02 K5.03	Sequences and groups: BWR-4,5		3.3 3.5

SYSTEM: 201004 Rod Sequence Control System (Plant Specific)

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC): (CFR: 41.7/45.7)		
K6.01 K6.02 K6.03 K6.04	Rod position information: BWR-4,5 Rod direction information: BWR-4,5 Rod movement information: BWR-4,5 Turbine generator (1st stage shell pressure): BWR-4,5	. 3.1	3.3 3.2 3.2 3.4
A1.	ABILITY Ability to predict and/or monitor changes in parameters, associated with operating the ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC) controls including: (CFR: 41.5 / 45.5)		
A1.01	Reactor manual control system: BWR-4,5	. 3.3	3.3
A2.	Ability to (a) predict the impacts of the following on the ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03	Loss of rod position information: BWR-4,5 Attempting to move a stuck control rod: BWR-4,5 Turbine trip: BWR-4,5	. 3.4	3.6 3.6 3.2
A3.	Ability to monitor automatic operations of the ROD SEQUENCE CONTROL SYSTEM (PLANT SPECIFIC) including: (CFR: 41.7 / 45.7)		
A3.01 A3.02 A3.03 A3.04 A3.05	Rod select switch light: BWR-4,5 Rod select bottom lamp dimmer logic: BWR-4,5 Back panel indicators: BWR-4,5 Annunciator and alarm signals: BWR-4,5 †Verification of proper function/ operability: BWR-4,5	. 3.1* . 2.8 . 3.2	3.1 3.1* 3.0 3.2 3.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01 A4.02 A4.03	†System bypass switches: BWR-4,5 RSCS console switches and indicators: BWR-4,5 †Rscs back panel switches and indicators: BWR-4,5	. 3.5	3.5 3.2 3.1

SYSTEM: 201006 Rod Worth Minimizer System (RWM) (Plant Specific)

TASK: Conduct rod worth minimizer functional test

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause- effect relationships between ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC) and the following:		
	(CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01	Reactor manual control: P-Spec(Not-BWR6)	. 3.4	3.4
K1.02	Rod position indication system: P-Spec(Not-BWR6)		3.4
K1.03	Reactor water level control (feed flow): P-Spec(Not-BWR6)		3.2
K1.04	Steam flow/reactor power: P-Spec(Not-BWR6)		3.2
K1.04 K1.05	Control rod drop accident: P-Spec(Not-BWR6)		3.8
K1.06	Rod sequence control system: P-Spec(Not-BWR6)		3.4
K1.00	Process computer: P-Spec(Not-BWR6)		2.9
K1.07 K1.08	Reactor power (turbine first stage pressure): P-	. 2.0	2.9
K1.06	Spec(Not-BWR6)	3.2	3.3
	Spec(NOI-BWKO)	. 3.2	3.3
K2.	Knowledge of electrical power supplies to the following:		
	(CFR: 41.7)		
	(CI R. 41.7)		
K2.01	Rod worth minimizer: P-Spec(Not-BWR6)	. 2.2*	2.5*
К3.	Knowledge of the effect that a loss or malfunction of the ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC) will have on following: (CFR: 41.7 / 45.4)		
K3.01	Reactor manual control system: P-Spec(Not-BWR6)	. 3.2	3.5
K4.	Knowledge of ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC) design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Insert blocks/errors: P-Spec(Not-BWR6)	3.4	3.5
K4.02	Withdraw blocks/errors: P-Spec(Not-BWR6)		3.5
K4.03	Select blocks/errors: P-Spec(Not-BWR6)		3.4
K4.04	System bypass: P-Spec(Not-BWR6)		3.5
K4.04 K4.05	Substitute rod position data: P-Spec(Not-BWR6)		3.0
		. 2.0	3.0
K4.06	Correction of out of sequence rod positions: P-	2.2	2.4
V4.07	Spec(Not-BWR6)	. 3.2	3.4
K4.07	Display of out of position control rods without rod	2 1	2.2
IZ 4 00	blocks (transition zone): P-Spec(Not-BWR6)		3.2
K4.08	System testing: P-Spec(Not-BWR6)		2.8
K4.09	System initialization: P-Spec(Not-BWR6)	. 5.2	3.2

SYSTEM: 201006 Rod Worth Minimizer System (RWM) (Plant Specific)

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC): (CFR: 41.5 / 45.3)	
K5.01	Minimize clad damage if a control rod drop accident	
	(CRDA) occurs: P-Spec(Not-BWR6)	3.7
K5.02	Low power set point: P-Spec(Not-BWR6)	3.0
K5.03	Low power alarm point (LPAP): P-Spec(Not-BWR6)	2.9
K5.04	Transition zone: P-Spec(Not-BWR6)	2.8
K5.05	High power set point: P-Spec(Not-BWR6)	3.0
K5.06	Rod groups and steps: P-Spec(Not-BWR6)	3.0
K5.07	Latch groups: P-Spec(Not-BWR6)	2.9
K5.08	Operating sequence: P-Spec(Not-BWR6)	2.9
K5.09	Select error: P-Spec(Not-BWR6)	3.2
K5.10	Withdraw error: P-Spec(Not-BWR6)	3.3
K5.11	Insert error: P-Spec(Not-BWR6)	3.3
K5.12	Withdraw block: P-Spec(Not-BWR6)	3.5
K5.13	Insert block: P-Spec(Not-BWR6)	3.5
K5.14	Alternate withdraw and insert limits: P-Spec(Not-	
	BWR6)	3.0
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC): (CFR: 41.7 / 45.7)	
V (01	DWM rower complex D Coop(Not DWD)	2.2
K6.01	RWM power supply: P-Spec(Not-BWR6)	3.2
K6.02	Reactor water level control input: P-Spec(Not-BWR6)	2.9
K6.03	Rod position indication: P-Spec(Not-BWR6)	2.9
K6.04	Process computer: P-Spec(Not-BWR6)	2.8
K6.05	Steam flow input: P-Spec(Not-BWR6)	2.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC) controls including: (CFR: 41.5 / 45.5)	
A1.01	Rod position: P-Spec(Not-BWR6)	3.3
A1.01 A1.02	Status of control rod movement blocks; P-Spec(Not-	5.5
	BWR6) 3.4	3.5
A1.03	Latched group indication: P-Spec(Not-BWR6)	3.0

SYSTEM; 201006 Rod Worth Minimizer System (RWM) (Plant Specific)

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
A2.	Ability to (a) predict the impacts of the following on the ROD WORTH MINIMIZER SYSTEM (RWH) (PLANT SPECIFIC); and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Power supply loss: P-Spec(Not-BWR6)	2.8
A2.02	Loss of steam flow input: P-Spec(Not-BWR6)	2.9
A2.03	Rod drift: P-Spec(Not-BWR6)	3.2
A2.04	Stuck rod: P-Spec(Not-BWR6)	3.3
A2.05	Out of sequence rod movement; P-Spec(Not-BWR6)	3.5
A2.06	Loss of reactor water level control input: P-	
	Spec(Not-BWR6)	3.3
A2.07	RWM hardware/software failure: P-Spec(Not-BWR6)	2.8
A3.	Ability to monitor automatic operations of the ROD WORTH MINIMIZER SYSTEM (RWM) (PLANT SPECIFIC) including: (CFR: 41.7 / 45.7)	
A3.01	System window and light indication: P-Spec(Not-BWR6)	3.1
A3.02	Verification of proper functioning/ operability: Plant-	
	Spec(Not-BWR6)	3.4
A3.03	Annunciator and alarm signals: P-Spec(Not-BWR6)	3.0
A3.04	Control rod movement blocks: P-Spec(Not-BWR6)	3.4
A3.05	Latched group indication: P-Spec(Not-BWR6)	3.1
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	System bypass switch: P-Spec(Not-BWR6)	3.4
A4.02	Pushbutton indicating switches: P-Spec(Not-BWR6) 2.9	2.9
A4.03	Latched group indication: P-Spec(Not-BWR6)	3.0
A4.04	Rod withdrawal error indication: P-Spec(Not-BWR6)	3.2
A4.05	Rod insert error indication: P-Spec(Not-BWR6)	3.2
A4.06	Selected rod position indication: P-Spec(Not-BWR6)	3.2

SYSTEM: 215004 Source Range Monitor (SRM) System

TASK: Perform lineups of the nuclear instrumentation system

Monitor the nuclear instrumentation system

Startup the nuclear instrumentation system

Place a source range module in/out of service

Operate the nuclear instrumentation system

Secure the nuclear instrumentation system

Conduct source range meter, intermediate range meter detector not in Startup rod block functional test

Conduct SRM functional test

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between SOURCE RANGE MONITOR (SRM) SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04	Reactor protection system Reactor manual control Rod control and information system: Plant-Specific Process computer/ performance monitoring system	. 3.4	3.7 3.4 3.0
K1.05 K1.06	(SPDS/ERIS/CRIDS/GDS): Plant-Specific Display control system: Plant-Specific Reactor vessel	. 2.8	2.6* 3.0 2.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 K2.02 K2.03	SRM channels/detectors	. 2.1*	2.8 2.3* 2.1*
К3.	Knowledge of the effect that a loss or malfunction of the SOURCE RANGE MONITOR (SRM) SYSTEM will have on following: (CFR: 41.7 / 45.4)		
K3.01 K3.02 K3.03 K3.04	RPS Reactor manual control: Plant-Specific Rod control and information system: Plant-Specific Reactor power and indication	. 3.4	3.4 3.4 3.3 3.7
K4.	Knowledge of SOURCE RANGE MONITOR (SRM) SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02 K4.03	Reactor SCRAM signals Gamma compensation	. 3.4	3.7 3.5 2.4

SYSTEM: 215004 Source Range Monitor (SRM) System

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K4.04 K4.05 K4.06	Changing detector position Alarm seal-in IRM/SRM interlock	2.5	2.9 2.5 3.2
K5.	Knowledge of the operational implications of the following concepts as they apply to SOURCE RANGE MONITOR (SRM) SYSTEM: (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03	Detector operation	2.2*	2.6 2.2* 2.8
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the SOURCE RANGE MONITOR (SRH) SYSTEM: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06	RPS 24/48 volt D.C. power Detector drive motor Detectors Trip units Recorder	3.1 2.4 2.9 2.6	3.3 3.3 2.4 2.9 2.8 2.2*
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the SOURCE RANGE MONITOR (SRM) SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06	Detector position Reactor power indication RPS status Control rod block status SCRAM, rod block, and period alarm trip setpoints Lights and alarms	3.6 3.4 3.5 3.6	3.1 3.7 3.5 3.5 3.8 3.1
A2.	Ability to (a) predict the impacts of the following on the SOURCE RANGE MONITOR (SRM) SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6)		
A2.01	Power supply degraded	2.7	2.9

SYSTEM: 215004 Source Range Monitor (SRM) System

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
A2.02	SRM inop condition	3.7
A2.03	Stuck detector	3.3
A2.04	Up scale and downscale trips	3.7
A2.05	Faulty or erratic operation of detectors/system	3.5
A2.06	Failed recorder	2.5
A3.	Ability to monitor automatic operations of the SOURCE	
	RANGE MONITOR (SRM) SYSTEM including:	
	(CFR: 41.7 / 45.7)	
A3.01	Meters and recorders	3.2
A3.02	Annunciator and alarm signals	3.3
A3.03	RPS status	3.5
A3.04	Control rod block status	3.6
A4.	Ability to manually operate and/or monitor in the	
	control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	SRM count rate and period	3.8
A4.02	SRM recorder	3.1
A4.03	CRT displays: Plant-Specific	2.7
A4.04	SRM drive control switches	3.2
A4.05	SRM back panel switches, meters, and indicating lights	3.2
A4.06	Alarms and lights 3.2	3.1
A4.07	Verification of proper functioning/ operability	3.6

System: 215001 Traversing In-Core Probe

TASK: Perform lineups of the nuclear instrumentation system Monitor the nuclear instrumentation system

Startup the nuclear instrumentation system Operate the nuclear instrumentation system Secure the nuclear instrumentation system

Place transversing in-core probe in/out of service

IMPORTANCE

K/A NO.	KNOWLEDGE RO	SRO
К1.	Knowledge of the physical connections and/or cause-effect relationships between TRAVERSING IN-CORE PROBE and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09	Local power range monitors: (Not-BWR1)2.5Process computer: (Not-BWR1)2.5Nitrogen purge system: P-Spec(Not-BWR1)2.1*Plant air systems: P-Spec(Not-BWR1)1.8*Primary containment isolation system: (Not-BWR1)3.3D.C. electrical: (Not-BWR1)1.8*A.C. electrical: (Not-BWR1)1.8*Reactor pressure vessel: (Not-BWR1)2.5Primary containment: (Not-BWR1)2.6	2.8 3.1 2.3 2.0* 3.4 1.9* 1.9* 2.6 2.7
K1.10 K2.	Area radiation monitoring system: (Not-BWR1)	2.8
K2.01	Shear valves: Mark-I&II(Not-BWR1)	2.1*
К3.	Knowledge of the effect that a loss or malfunction of the TRAVERSING IN-CORE PROBE will have on following: (CFR: 41.7 / 45.4)	
K3.01	Local power range monitor's calibration: (Not-BWR1)	2.8
K4.	Knowledge of TRAVERSING IN-CORE PROBE design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02 K4.03	Primary containment isolation: Mark-I&II(Not-BWR1) 3.4 Corrosion prevention: (Not-BWR1) 1.9* Radiation shielding: (Not-BWR1) 2.4	3.5 2.1* 2.7

3.7-41

SYSTEM: 215001 Traversing In-Core Probe

Tasks as noted previously

K5. Knowledge of the operational implications of the following concepts as they apply to TRAVERSING IN-CORE PROBE: (CFR: 41.5 / 45.3) K5.01 Neutron flux detection: (Not-BWR1) 2.2* 2.5 K6. Knowledge of the effect that a loss or malfunction of the following will have on the TRAVERSING IN-CORE PROBE: (CFR: 41.7 / 45.7) K6.01 D.C. electrical power: (Not-BWR1) 1.9* 2.1* K6.02 A.C. electrical power: (Not-BWR1) 1.9* 2.1* K6.03 Process computer: BWR-2,3.4.5.6 2.3 2.7 K6.04 Primary containment isolation system: Mark-L&II(Not-BWR1) 3.1 3.4 K6.05 Plant air systems: P-Spec(Not-BWR1) 3.1 3.4 K6.06 Nitrogen purge: P-Spec(Not-BWR1) 2.0* 2.2* ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the TRAVERSING IN-CORE PROBE controls including: (CFR: 41.5 / 45.5) 2.4 A1.01 Radiation levels: (Not-BWR1) 2.5 2.4 A1.02 Detector position: (Not-BWR1) 2.5* 2.4 A1.03 Valve status: Mark-L&II(Not-BWR1) 2.0* 2.2* A1.04 Drive specic (Not-BWR1) 2.0* 2.2* A1.05 Detector output: (Not-BWR1) 2.0* 2.3* A1.06 Radiation alarms: (Not-BWR1) 2.0* 2.3* A1.07 Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) 2.9 3.0 A2.01 Low reactor water level: Mark-L&II(Not-BWR1) 2.7 2.9 High primary containment pressure: Mark-L&II(Not-BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.9 3.0 A2.04 A.C. failure: (Not-BWR1) 2.9 3.0 A2.05 D.C. failure: (Not-BWR1) 1.8* 2.0*	K/A NO.	KNOWLEDGE	RO	SRO
K6. Knowledge of the effect that a loss or malfunction of the following will have on the TRAVERSING IN-CORE PROBE: (CFR: 41.7/45.7) K6.01 D.C. electrical power: (Not-BWR1) 1.9* 2.1* K6.02 A.C. electrical power: (Not-BWR1) 1.9* 2.1* K6.03 Process computer: BWR-2,3,4,5,6 2.3 2.7 K6.04 Primary containment isolation system: Mark-I&II(Not-BWR1) 3.1 3.4 K6.05 Plant air systems: P-Spec(Not-BWR1) 1.8* 2.1* K6.06 Nitrogen purge: P-Spec(Not-BWR1) 2.0* 2.2 ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the TRAVERSING IN-CORE PROBE controls including: (CFR: 41.5/45.5) A1.01 Radiation levels: (Not-BWR1) 2.8 2.9 A1.02 Detector position: (Not-BWR1) 2.5 2.4 A1.03 Valve status: Mark-I&II(Not-BWR1) 2.6* 2.8 A1.04 Drive speed: (Not-BWR1) 2.0* 2.2* A1.05 Detector output: (Not-BWR1) 2.0* 2.2* A2.0 Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5/45.6) A2.01 Low reactor wat	K5.	following concepts as they apply to TRAVERSING IN-CORE PROBE:		
the following will have on the TRAVERSING IN-CORE PROBE: (CFR: 41.7/45.7) K6.01 D.C. electrical power: (Not-BWR1)	K5.01	Neutron flux detection: (Not-BWR1)	2.2*	2.5
K6.02	К6.	the following will have on the TRAVERSING IN-CORE PROBE:		
R6.03				
R6.04 Primary containment isolation system: Mark-I&II(Not-BWR1) 3.1 3.4				
R6.05 Plant air systems: P-Spec(Not-BWR1) 1.8* 2.1*			2.3	2.7
ABILITY Al. Ability to predict and/or monitor changes in parameters associated with operating the TRAVERSING IN-CORE PROBE controls including: (CFR: 41.5 / 45.5) 2.8 2.9 Al.02				
ABILITY A1. Ability to predict and/or monitor changes in parameters associated with operating the TRAVERSING IN-CORE PROBE controls including: (CFR: 41.5 / 45.5) A1.01 Radiation levels: (Not-BWR1)				
A1. Ability to predict and/or monitor changes in parameters associated with operating the TRAVERSING IN-CORE PROBE controls including:	K 0.00	Nitrogen purge: P-Spec(Not-BWR1)	2.0"	2.2
Parameters associated with operating the TRAVERSING IN-CORE PROBE controls including: (CFR: 41.5 / 45.5)		ABILITY		
A1.02 Detector position: (Not-BWR1) 2.5 2.4 A1.03 Valve status: Mark-I&II(Not-BWR1) 2.6* 2.8 A1.04 Drive speed: (Not-BWR1) 2.0* 2.2* A1.05 Detector output: (Not-BWR1) 2.0* 2.3* A1.06 Radiation alarms: (Not-BWR1) 2.9 2.8 A2. Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Low reactor water level: Mark-I&II(Not-BWR1) 2.7 2.9 High primary containment pressure: Mark-I&II(Not-BWR1) 2.7 2.9 A2.02 High primary containment pressure: Mark-I&II(Not-BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*	A1.	parameters associated with operating the TRAVERSING IN-CORE PROBE controls including:		
A1.03 Valve status: Mark-I&II(Not-BWR1) 2.6* 2.8 A1.04 Drive speed: (Not-BWR1) 2.0* 2.2* A1.05 Detector output: (Not-BWR1) 2.0* 2.3* A1.06 Radiation alarms: (Not-BWR1) 2.9 2.8 A2. Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Low reactor water level: Mark-I&II(Not-BWR1) 2.7 2.9 High primary containment pressure: Mark-I&II(Not-BWR1) 2.7 2.9 A2.02 High primary containment pressure: Mark-I&II(Not-BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*	A1.01	Radiation levels: (Not-BWR1)	2.8	2.9
A1.04 Drive speed: (Not-BWR1) 2.0* 2.2* A1.05 Detector output: (Not-BWR1) 2.0* 2.3* A1.06 Radiation alarms: (Not-BWR1) 2.9 2.8 A2. Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Low reactor water level: Mark-I&II(Not-BWR1) 2.7 2.9 A2.02 High primary containment pressure: Mark-I&II(Not-BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*	A1.02			2.4
A1.05 Detector output: (Not-BWR1)				
A1.06 Radiation alarms: (Not-BWR1)		1 '		
A2. Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 Low reactor water level: Mark-I&II(Not-BWR1) 2.7 2.9 High primary containment pressure: Mark-I&II(Not-BWR1) 2.9 3.0 A2.02 BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*		* '		
A2.02 High primary containment pressure: Mark-l&II(Not-BWR1) 2.9 3.0 A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*		Ability to (a) predict the impacts of the following on the TRAVERSING IN-CORE PROBE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations:		
A2.03 Drive mechanism failure: (Not-BWR1) 2.1* 2.4 A2.04 A.C. failure: (Not-BWR1) 1.8* 2.0*		High primary containment pressure: Mark-l&II(Not-		
A2.04 A.C. failure: (Not-BWR1)	A 2 03			
		,		

SYSTEM: 215001 Traversing In-Core Probe

Tasks as noted previously

K/A NO.	ABILITY RO	SRO
A2.06	Valve closures: Mark-I&II(Not-BWR1)	2.6
A2.07	†Failure to retract during accident conditions: Mark-	
	I&II(Not-BWR1)	3.7
A2.08	Failure to retract to shield: (Not-BWR1)	2.9
A3.	Ability to monitor automatic operations of the TRAVERSING IN-CORE PROBE including: (CFR: 41.7 / 45.7)	
A3.01	Detector position: P-Spec(Not-BWR1)	2.5*
A3.02	Detector drive speed: P-Spec(Not-BWR1)	2.2*
A3.03	Valve operation: Not-BWR1	2.6*
A3.04	Indicating lights: P-Spec(Not-BWR1)	2.4*
A3.05	Detector output: P-Spec(Not-BWR1)	2.2*
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Detector drive speed: P-Spec(Not-BWR1)	2.2*
A4.02	Detector position: P-Spec(Not-BWR1)	2.6*
A4.03	Isolation valves: Mark-I&II(Not-BWR1)	3.1
A4.04	Detector output: P-Spec(Not-BWR1)	2.3*
A4.05	Indicating lights: P-Spec(Not-BWR1)	2.5

3.8	Plant Service Systems	page
286000	Fire Protection System	3.8-3
234000	Fuel Handling	3.8-7
300000	Instrument Air System	3.8-10
400000	Component Cooling Water System	3.8-13

This page left blank

TASK: Perform lineups of the fire protection system (CO2, deluge, freon/halon 1301, foam)

Place the fire protection system in standby

Operate fire protection equipment to combat a fire

Monitor the fire protection system

Operate the fire detection/alarm equipments

Shut down the fire protection system

	IMPURIANCE	~
K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between FIRE PROTECTION SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Component cooling water systems	2.8
K1.02	Isolation condenser: Plant-Specific	3.8
K1.03	Reactor water level: Plant-Specific	3.0
K1.04	D.C. electrical distribution: Plant-Specific	2.6
K1.05	Main generator hydrogen system: Plant-Specific	3.1
K1.06	Auxiliary (boiler) steam system: Plant-Specific	2.3*
K1.07	A.C. power supplies	2.9
K1.08	Intake canals: Plant-Specific	3.0
K1.09	Emergency generator rooms: Plant-Specific	3.3
K1.10	Main generator exciter: Plant-Specific	2.8
K1.11	Screen wash system: Plant-Specific	2.5
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01	Fire protection supervisory circuits: Plant-Specific	2.5*
K2.02	Pumps	3.1
K2.03	Fire detection system: Plant-Specific	2.7*
К3.	Knowledge of the effect that a loss or malfunction of the FIRE PROTECTION SYSTEM will have on following: (CFR: 41.7 / 45.4)	
K3.01	The ability to detect fires	3.4
K3.02	Personnel protection	3.4
K3.03	Plant protection	3.8

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K4.	Knowledge of FIRE PROTECTION SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7) (CFR: 41.5 / 45.3) (CFR: 41.7 / 45.7) (CFR: 41.5 / 45.5) (CFR: 41.5 / 45.6) (CFR: 41.7 / 45.7) (CFR: 41.7 / 45.7)		
IZ 4 O 1	Adams to sense for the first and the first a		
K4.01	Adequate supply of water for the fire protection system	3.4	3.6
K4.02	Automatic system initiation		3.5
K4.02 K4.03	Maintenance of fire header pressure		3.4
K4.04	Personnel safety during halon and/or carbon dioxide	3.3	J. 4
K4.04	system actuationsystem actuation	3.6	3.7
K4.05	Fire protection capability during loss of off-site	5.0	3.7
K4. 03	power	3.7	3.8
K4.06	Fire suppression capability that does not rely on the	3.7	5.0
K4.00	displacement of oxygen (Halon): Plant-Specific	3.4	3.4
K4.07	Diesel engine protection		3.3
114.07	Dieser engine protection	3.3	3.3
K5.	Knowledge of the operational implications of the following concepts as they apply to FIRE PROTECTION SYSTEM: (CFR: 41.5 / 45.3)		
IZ 5 0.1	Effect of a draw live it and five	2.6	2.7
K5.01	Effect of carbon dioxide on fires		2.7
K5.02	Effect of Halon on fires: Plant-Specific		2.6
K5.03	Effect of water spray on electrical components		3.4
K5.04	Valve operation		2.9
K5.05	Diesel operations		3.1*
K5.06	Heat detection		2.7
K5.07	Smoke detection		2.7
K5.08	Gas refrigeration: Plant-Specific	2.4*	2.5*
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the FIRE PROTECTION SYSTEM (CFR: $41.7/45.7$)		
K6.01	A.C. electrical distribution: Plant-Specific	3.1	3.1
K6.02	D. C. electrical distribution		2.9*
K6.03	Applicable component cooling water system: Plant-	2.0	2.,
110.03	Specific	2.4*	2.5
K6.04	Diesel fuel transfer system: Plant-Specific		3.0
K6.05	Screen wash system: Plant-Specific		2.6
110.05	betoen mash system. I min specific	2.0	2.0

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
Al.	Ability to predict and/or monitor changes in parameters associated with operating the FIRE PROTECTION SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06	System pressure System flow Fire doors Fire dampers System lineups Tank pressure: Plant-Specific	. 2.4* . 2.8 . 2.8 . 3.2	2.9 2.5* 3.1 3.1 3.2 3.0
A2.	Ability to (a) predict the impacts of the following on the FIRE PROTECTION SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03	†System logic failure: Plant-Specific D.C. distribution failure: Plant-Specific A.C. distribution failure: Plant-Specific	. 2.6*	2.9 2.7* 3.0
A2.04 A2.05 A2.06 A2.07	Applicable component cooling water system failure: Plant-Specific	. 3.1	2.4* 3.3 3.2 2.9
A2.08 A2.09 A2.10 A2.11	Failure to actuate when required Valve closures: Plant-Specific Valve openings: Plant-Specific Pump trips: Plant-Specific	. 3.2 . 2.7 . 2.6* . 3.1	3.3 2.8 2.7 3.2
A2.12 A3.	Low diesel fuel supply: Plant-Specific	. 3.1	3.3
A3.01 A3.02 A3.03 A3.04 A3.05 A3.06	Fire water pump start Fire main pressure Actuation of fire detectors System initiation Fire doors Fire dampers	. 3.1 . 3.3 . 3.2 . 3.0	3.4 3.2 3.3 3.3 3.1 3.1

Tasks as noted previously

	IVII OKITAVEE	
K/A NO.	ABILITY RO	SRO
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01 A4.02	System alarms and indicating lights	3.2
	Specific	2.5*
A4.03	Applicable component cooling water pressure	2.5*
A4.04	Fire main pressure: Plant-Specific	2.8
A4.05	Fire pump	3.3
A4.06	Fire diesel	3.4

SYSTEM: 234000 Fuel Handling Equipment

K4.01

K4.02

K4.03

K4.04

K4.05

TASK: Operate the spent fuel handling machine/bridge

Operate the refueling machine/main fuel handling bridge (fuel element change) Operate the control rod change machine/main fuel handling bridge (control rod change) Operate the fuel transfer system/fuel transfer carriages and upenders **IMPORTANCE** K/A NO. **KNOWLEDGE** RO **SRO** K1. Knowledge of the physical connections and/or causeeffect relationships between FUEL HANDLING EQUIPMENT and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8) K1.01 3.7 K1.02 3.3 K1.03 2.9 K1.04 3.6 K1.05 3.3 K1.06 3.2 K1.07 3.4 K1.08 3.0 K1.09 2.9 K2. Knowledge of electrical power supplies to the following: (CFR: 41.7) None K3. Knowledge of the effect that a loss or malfunction of the FUEL HANDLING EQUIPMENT will have on following: (CFR: 41.7 / 45.4) K3.01 3.3 K3.02 3.0 K3.03 3.8 K3.04 3.8 K4. **Knowledge of FUEL HANDLING EQUIPMENT design feature(s)** and/or interlocks which provide for the following: (CFR: 41.7)

NUREG-1123,	Dosz	2
NOKEG-TIZ3,	Rev.	

4.1

4.1

4.2

3.3

3.8

†Prevention of core alterations during control rod

†Prevention of control rod movement during core

†Protection against inadvertently lifting radioactive

†Movement of the spent fuel cask only over designated

SYSTEM: 234000 Fuel Handling Equipment

Tasks as noted previously

K/A NO	D. KNOWLEDGE	RO	SRO
K5.	Knowledge of the operational implications of the following concepts as they apply to FUEL HANDLING EQUIPMENT: (CFR: 41.5 / 45.3)		
K5.01 K5.02 K5.03 K5.04 K5.05	†Crane/hoist operation †Fuel handling equipment interlocks †Water as a shield against radiation Spent fuel pool design †Fuel orientation Knowledge of the effect that a loss or malfunction of the following will have on the FUEL HANDLING EQUIPMENT (CFR: 41.7/45.7)	. 3.1 . 2.9 . 2.6	3.4 3.7 3.4 3.1 3.7
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06 K6.07	†Electrical power Reactor manual control system: Plant-Specific RC & IS: Plant-Specific †Refueling platform air system: Plant-Specific Upper fuel pool water inventory: Mark-III Fuel transfer tube interlocks: Mark-III †Fuel pool ventilation: Plant-Specific	. 2.8 . 3.0 . 2.9 . 3.2 . 3.0	3.2 3.5 3.6 3.7 3.3 3.6 3.4
	ABILITY		
Al.	Ability to predict and/or monitor changes in parameters associated with operating the FUEL HANDLING EQUIPMENT controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03	Spent fuel pool level †Refuel floor radiation levels/ airborne levels †core reactivity level	. 3.3	3.4 3.8 3.9
A2.	Ability to (a) predict the impacts of the following on the FUEL HANDLING EQUIPMENT; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03	†Interlock failure	. 3.1	3.7 3.6 3.1

SYSTEM: 234000 Fuel Handling Equipment

Tasks as noted previously

K/A NO.	ABILITY RO	O	SRO
A3.	Ability to monitor automatic operations of the FUEL HANDLING EQUIPMENT including: (CFR: 41.7/45.7)		
A3.01	†Crane/refuel bridge movement: Plant-Specific	2.6	3.6
A3.02	†Interlock operation		3.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	†Neutron monitoring system	.7	3.9
A4.02	Control rod drive system	.4	3.7

SYSTEM: 300000 Instrument Air System (IAS)

Task: Perform lineups of the IAS

Start up the IAS Monitor the IAS

Shift instrument air compressors Operate instrument air compressors

Operate system air dryers

Perform testing of automatic operation of the IAS

K/A NO.	KNOWLEDGE RO	SRO
K1	Knowledge of the connections and / or cause effect relationships between INSTRUMENT AIR SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03 K1.04 K1.05	Sensor air2.4Service air2.7Containment air2.8Cooling water to compressor2.8Main Steam Isolation Valve air3.1	2.7 2.8 2.9 2.9 3.2
K2	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02	Instrument air compressor2.8Emergency air compressor3.0	2.8 3.0
K3. (INSTRUME	Knowledge of the effect that a loss or malfunction of the	
K3.01 K3.02 K3.03	Containment air system2.7Systems having pneumatic valves and controls3.3Cross-tied units2.9	2.9 3.4 3.0
K4.	Knowledge of (INSTRUMENT AIR SYSTEM) design feature(s) and or interlocks which provide for the following: (CFR: 41.7)	
K4.01 K4.02 K4.03	Manual/automatic transfers of control2.8Cross-over to other air systems3.0Securing of IAS upon loss of cooling water2.8	2.9 3.0 2.8
K5.	Knowledge of the operational implications of the following concepts as they apply to the INSTRUMENT AIR SYSTEM: $(CFR:\ 41.5/45.3)$	
K5.01 K5.02	Air compressors2.5Pressure gauges2.3	2.5 2.2

SYSTEM: 300000 Instrument Air System (IAS)

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K5.03	Temperature indicators	2.1
K5.04	Service air refusal valve	2.3
K5.06	Air dryers	2.5
K5.07	Valves	2.3
K5.08	Sensors and detectors	2.5
K5.09	Controllers and positioners	2.1
K5.10	Motors	2.2
K5.11	Heat exchangers and condensers	2.2
K5.12	Breakers, relays and disconnects	2.2
K5.13	Filters	2.9
K6	Knowledge of the effect that a loss or malfunction of the following will have on the INSTRUMENT AIR SYSTEM: (CFR: $41.7/45.7$)	
K6.01	Air compressors	2.2
K6.02	Pressure gauges	2.4
K6.03	Temperature indicators	2.7
K6.04	Service air refusal valve	2.5
K6.06	Air dryers	2.3
K6.07	Valves	2.6
K6.08	Sensors and detectors	2.3
K6.09	Controllers and positioners	2.3
K6.10	Motors	2.4
K6.11	Heat exchangers and condensers	2.3
K6.12	Breakers, relays and disconnects	2.9
K6.13	Filters	2.3
No.	ABILITY	
A1.	Ability to predict and / or monitor changes in parameters	ciated
	None	
A2.	Ability to (a) predict the impacts of the following on the	
A2.01	Air dryer and filter malfunctions	2.8

SYSTEM: 300000 Instrument Air System (IAS)

IMPORTANCE K/A NO. KNOWLEDGE RO SRO Ability to monitor automatic operations of the INSTRUMENT AIR SYSTEM including: **A3.** (CFR: 41.7 / 45.7) A3.01 Air pressure 2.3 2.1 A3.02 Air temperature 2.9 2.7 A4. Ability to manually operate and / or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) A4.01 Pressure gauges 2.6 2.7

K/A NO.	KNOWLEDGE RO	SRC
Task:	Perform CCWS component operability test Perform CCWS flow path verification Perform CCWS pump test Perform CCW flow balance Determine CCWS leak rate from RCS	
K1.	Knowledge of the physical connections and / or cause-effect relationships between CCWS and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 K1.02 K1.03 K1.04	Service water system 3.2 Loads cooled by CCWS 3.2 Radiation monitoring systems 2.7 Reactor coolant system, in order to determine source (s) of RCS leakage into CCWS 2.9	3.3 3.4 3.0 3.1
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 K2.02	CCW pumps 2.9 CCW valves 2.9	3.0 2.9
K3.	Knowledge of the effect that a loss or malfunction of the CCWS will have on the following: $(CFR:\ 41.7/45.6)$	
K3.01	Loads cooled by CCWS	3.3
K4.	Knowledge of CCWS design feature(s) and or interlocks which provide for the following: (CFR: 41.7)	
K4.01	Automatic start of standby pump	3.9
K5.	Knowledge of the operational implications of the following concepts as they apply to the CCWS: $(CFR:\ 41.5/45.3)$	
K5.01	Chemistry control	2.0

K/A NO.	KNOWLEDGE	RO	SRO
К6	Knowledge of the effect that a loss or malfunction of the following will have on the CCWS: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.05 K6.05 K6.06 K6.07	Valves Sensors and detectors Controllers and positioners Pumps Motors Heat exchangers and condensers Breakers, relays, and disconnects	. 2.3 . 2.4 . 3.0 . 2.8 . 2.9	2.8 2.4 2.6 3.1 2.9 2.9 2.8
No.	ABILITY		
A1.	Ability to predict and / or monitor changes in parameters	••••	
A1.01 A1.02 A1.03 A1.04	CCW flow rate CCW temperature CCW Pressure Surge Tank Level	. 2.8 . 2.7	2.8 2.8 2.7 2.8
A2.	Ability to (a) predict the impacts of the following on the CCWS and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal operation: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04	Loss of CCW pump High/low surge tank level High/low CCW temperature Radiation monitoring system alarm	. 2.8 . 2.9	3.4 3.0 3.0 3.0
A3.	Ability to monitor automatic operations of the CCWS including: (CFR: $41.7 / 45.7$)		
A3.01	Setpoints on instrument signal levels for normal operations, warnings, and trips that are applicable to the CCWS	. 3.0 3	5.0
A4.	Ability to manually operate and / or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	CCW indications and control	. 3.1	3.0

3.9	Radioactivity Release	page
239003	Main Steam Isolation Valve Leakage Control System	3.9-3
271000	Offgas System	3.9-7
288000	Plant Ventilation Systems	3.9-11
272000	Radiation Monitoring System	3.9-14
268000	Radwaste	3.9-18
290002	Reactor Vessel Internals	3.9-21
233000	Fuel Pool Cooling and Clean-up	3.9-24
261000	Standby Gas Treatment System	3.9-29
290003	Control Room Heating, Ventilation and Air Conditioning	3.9-33

This page left blank

TASK: Perform one train MSLCS inoperable surveillance

Perform main steam leakage control system operational test (write in

Perform one train main steam leakage control system operability surveillance (write in)

Perform monthly main steam leakage control system DIV 1 and DIV 2 fan and heater tests (write in)

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between MSIV LEAKAGE CONTROL SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03	Main steam system: BWR-4,5,6(P-Spec)		3.4 3.0
K1.04 K1.05 K1.06 K1.07 K1.08	4,5,6(P-Spec) A.C. electrical distribution: BWR-4,5,6(P-Spec) Steam tunnel: BWR-4,5,6(P-Spec) Radwaste system: BWR-4,5,6(P-Spec) Floor drainage system: BWR-4,5,6(P-Spec) Nuclear boiler instrumentation: BWR-4,5,6(P-Spec)	2.7 2.9 2.4 1.9*	3.1 2.8 2.9 2.4 1.9* 2.8
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	2.0	2.0
K2.01 K2.02 K2.03	Motor operated valves: BWR-4,5,6(P-Spec) Leakage control system blowers: BWR-4,5,6(P-Spec) Leakage control system heaters: BWR-4.5,6(P-Spec)	1.9*	2.3* 2.0* 2.0*
К3.	Knowledge of the effect that a loss or malfunction of the MSIV LEAKAGE CONTROL SYSTEM will have on following: (CFR: 41.5 / 45.3)		
K3.01 †Rac	diation release to the environment: BWR-4,5,6(P-Spec)	3.3	4.0
K4.	Knowledge of MSIV LEAKAGE CONTROL SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Performance of its safety function following a loss of offsite power: BWR-4,5,6(P-Spec)	3.2	3.5
K4.02	Performance of intended safety function following any single active component failure: BWR-4,5,6(P-Spec)		3.4
K4.03	The prevention of inadvertent system operation: BWR-4,5,6(P-Spec)		3.2

Tasks as noted previously

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K4.04 K4.05	Surveillance for system operability: BWR-4,5,6	. 2.4	2.8
K4.06	to the atmosphere: BWR-4,5,6(P-Spec)	. 2.4*	2.8*
K4.07	routing leakage through system: BWR-4,5,6	. 3.1	3.3
K4.08	4,5,6(P-Spec)	. 2.4	2.4
K4.09	lines: BWR-4,5,6(P-Spec) The dilution of MSIV leakage: BWR-4,5,6(P-Spec)		2.4 2.4
K 4.09	The dilution of MSIV leakage. BWK-4,3,0(P-Spec)	. 2.4	2.4
K5.	Knowledge of the operational implications of the following concepts as they apply to MSIV LEAKAGE CONTROL SYSTEM: (CFR: 41.7 / 45.4)		
K6.	Knowledge of the effect that a loss or malfunction of		
	the following will have on the MSIV LEAKAGE CONTROL SYSTEM: (CFR: 41.7 / 45.7)		
K6.01	A.C. electrical distribution: BWR-4,5,6(P-Spec)		3.0
K6.02 K6.03	Standby gas treatment system: BWR-4,5,6(P-Spec)		3.0 2.9
	ABILITY		
A1.	Ability to predict and/or monitor changes in parameters associated with operating the MSIV LEAKAGE CONTROL SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07	Main steam line pressure: BWR-4,5,6 Heater operation: BWR-4,5,6(P-Spec) Dilution air flow: BWR-4,5,6(P-Spec) Status indicating lights and alarms: BWR-4,5,6 System lineup: BWR-4,5,6 MSIV leakage flow: BWR-4,5,6 Reactor building temperature: BWR-4,5,6(P-Spec)	. 2.6 . 2.4 . 2.9 . 3.0 . 2.6	3.1 2.6 2.6 2.8 2.9 2.6 2.7

Tasks as noted previously

	IMPORTANCE	
K/A NO.	ABILITY RO	SRO
A2.	Ability to (a) predict the impacts of the following on the MSIV LEAKAGE CONTROL SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	Inboard MSIV valve leakage: BWR-4,5,6 2.8	3.2
A2.02	Outboard MSIV valves leakage: BWR-4,5,6	3.3
A2.03	Low dilution air flow (inboard and/or outboard):	
	BWR-4,5,6(P-Spec)	2.7
A2.04	Outboard system logic failure: BWR-4,5,6	3.0
A2.05	Inboard system logic failure: BWR-4,5,6	3.0
A2.06	Blower failure: BWR-4,5,6(P-Spec)	2.6
A2.07	Heater failure: BWR-4,5,6(P-Spec)	2.4
A2.08	Motor operator valve failure(s): BWR-4,5,6	3.0
A2.09	Outboard main steamline high pressure: BWR-4,5,6(P-	3.0
A2.10	Spec) 2.8 A.C. distribution power failures: BWR-4,5,6 2.8	3.0
	•	
A2.11	High reactor pressure: BWR-4,5,6	3.3
A2.12	MSIV valve failure to close: BWR-4,5,6	3.8
A3.	Ability to monitor automatic operations of the MSIV LEAKAGE CONTROL SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	System logic initiation: BWR-4,5,6(P-Spec)	2.8
A3.02	Main steamline pressures: BWR-4,5,6	2.8
A3.02 A3.03	Dilution air flaws: BWR-4,5,6(P-Spec)	2.3
A3.04	MSIV leakage flows: BWR-4,5,6(P-Spec)	2.6
A3.05	Heater operation: BWR-4,5,6(P-Spec)	2.2
A3.06	System status lights and alarms: BWR-4,5,6	2.8
A3.07	System lineups: BWR-4,5,6	2.9
A3.08	Blower operation: BWR-4,5,6(P-Spec)	2.3
A3.09	Reactor building temperature: BWR-4,5,6(P-Spec)	2.5
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Manually initiate system operation: BWR-4,5,6(P-Spec)	2.2
A 4 02	#Surveillance testing: DWD 4.5.6(D.Spee)	3.2
A4.02	†Surveillance testing: BWR-4,5,6(P-Spec)	2.8
A4.03	Main steamline pressures: BWR-4,5,6	3.2
A4.04	Dilution air flows: BWR-4,5,6(P-Spec)	2.4
A4.05	MSIV leakage flows: BWR-4,5,6(P-Spec)	2.7
A4.06	Heater operation: BWR-4,5,6(P-Spec)	2.3

Tasks as noted previously

		IMPORTANCE		
K/A NO.	ABILITY		RO	SRO
A4.07	System status lights and alarms: BWR-4,5,6(P-Spec)		2.8	2.7
A4.08	System lineups: BWR-4,5,6(P-Spec)		3.1	2.9
A4.09	System reset: BWR-4,5,6(P-Spec)		3.0	2.8

TASK: Conduct lineups on the offgas system

Startup the offgas system

Monitor the offgas system

Operate the recombiner Operate

XE-KR removal equipment

Secure the offgas system

Conduct offgas line isolation logic system functional test

Conduct offgas system automatic isolation and closure test

Conduct offgas process radiation monitor instrument functional test

Conduct steam jet air ejector offgas line isolation logic system functional test

IMPORTANCE		
K/A NO. KNOWLEDGE	RO	SRO
K1. Knowledge of the physical connections and/or cause-effect relationships between OFFGAS SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 Condenser air removal system	3.1	3.1
K1.02 Process radiation monitoring system		3.3
K1.03 Elevated release point		3.0
K1.04 Condensate system		2.7
K1.05 Radwaste system		2.5
K1.06 Main steam system		2.9
K1.07 Plant air systems		2.7
K1.08 Oxygen injection system: Plant-Specific	2.3	2.3
K1.09 Component cooling water systems		2.6
K1.10 Condenser vacuum		3.3
K1.11 †Station radioactive release rate	3.1	3.6
K1.12 A.C. electrical distribution	2.3	2.4
K1.13 Process sampling system	2.6	2.8
K1.14 Radwaste sparging air: Design-Specific	2.0*	2.5
K2. Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01 Glycol pumps	1.5*	1.5*
K3. Knowledge of the effect that a loss or malfunction of the OFFGAS SYSTEM will have on following: (CFR: 41.5 / 45.3)		
K3.01 Condenser vacuum	3.5	3.5
K3.02 †Off-site radioactive release rate		3.9

Tasks as noted previously

K/A NO	D. KNOWLEDGE	RO	SRO
K4.	Knowledge of OFFGAS SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02	Dilution of hydrogen gas concentration 2.9 Prevention of the poisoning of the recombiner catalyst	3.3	
114.02	by the presence of water 2.6	2.7	
K4.03	Maintenance of sufficient oxygen gas inventory to allow for complete hydrogen recombination: Plant-	2.,	
	Specific 2.4		
K4.04	The prevention of hydrogen explosions and/or fires 3.3		
K4.05	Redundancy 2.6	2.6	
K4.06	Decay of fission product gases to particulate		
	daughters 2.7		
K4.07	Maximizing charcoal bed efficiency 2.6		
K4.08	Automatic system isolation 3.1		
K4.09	Filtration of radioactive particulate 2.8	3.1	
K5.	Knowledge of the operational implications of the following concepts as they apply to OFFGAS SYSTEM : $(CFR:\ 41.7/45.4)$		
K5.01	Air operated valve operation		2.3
K5.02	Heat removal mechanisms	. 2.2	2.2
K5.03	Heat addition mechanisms	. 2.2*	2.2
K5.04	Hydrogen concentration measurement		3.1
K5.05	Oxygen concentration measurement		2.9
K5.06	Catalytic recombination		2.7
K5.07	Radioactive decay		2.9
K5.08	Charcoal absorption of fission product gases		2.6
K5.09	Hydrogen and oxygen recombination		2.8
K5.10	Decontamination factors	. 2.0*	2.3*
K5.11	Explain the necessity of reducing relative humidity	2.6	2.0
	for carbon bed filters.	. 2.6	2.8
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the OFFGAS SYSTEM : $(CFR:\ 41.7/45.7)$		
K6.01	Plant air systems	. 2.7	2.8
K6.02	Process radiation monitoring system		3.2
K6.03	Component cooling water systems		2.4
K6.04	Dilution steam		2.8
K6.05	Heating steam: Design-Specific		2.4
K6.06	Oxygen injection system: Plant-Specific		2.5
K6.07	A.C. electrical distribution		2.5
K6.08	Condenser air removal system	. 2.9	3.0

Tasks as noted previously

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
K6.09 K6.10 K6.11 K6.12 K6.13	Fuel cladding integrity Condensate system flow Condenser vacuum Glycol system Plant exhaust: BWR-1 ABILITY	. 2.7 . 3.2 . 2.1*	3.6 2.8 3.3 2.2* 3.4
A1.	Ability to predict and/or monitor changes in parameters associated with operating the OFFGAS SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05 A1.06 A1.07 A1.08 A1.09 A1.10 A1.11 A1.12 A1.13 A1.14 A1.15	Condenser vacuum Station radioactive release rate Preheater discharge temperature Recombiner catalyst temperature Cooler condenser discharge temperature Filter differential pressure Charcoal bed humidity System flow Charcoal bed temperature Charcoal bed temperature Offgas condenser temperature Offgas condenser temperatures Process radiation monitoring indications Hydrogen gas concentration Oxygen gas concentration Steam supply pressures	. 3.0 . 2.2* . 2.2* . 2.4* . 2.4* . 3.1 . 2.1* . 2.3 . 2.3 . 3.1 . 3.2 . 2.7	3.2 3.6 2.3 2.4 2.5 2.5 3.1 2.4 2.5 2.4 3.5 3.7 3.0 2.8
A2.	Ability to (a) predict the impacts of the following on the OFFGAS SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04 A2.05 A2.06 A2.07 A2.08 A2.09 A2.10 A2.11	Low condenser vacuum Low dilution steam flow Main steamline high radiation Offgas system high radiation High charcoal bed humidity Offgas system holdup volume explosion/ fire Low oxygen injection flow: Plant-Specific A.C. distribution failures Valve closures Offgas system high flow Offgas system low flow	. 2.9 . 3.5 . 3.7 . 2.5 . 3.5 . 2.7 . 2.5 . 2.6 . 3.1	3.3 3.1 3.8 4.1 2.9 3.9 3.3 2.7 2.8 3.3 2.9

Tasks as noted previously

K/A NO.	ABILITY RO	SRC
A2.12	Recombiner high temperature	2.9
A2.13	Recombiner low temperature	2.8
A2.14	Offgas filter high differential pressure	2.8
A2.15	Air intrusion	2.9
A2.16	Loss of offgas system loop seals	3.2
A2.17	Reactor power changes	3.1
A3.	Ability to monitor automatic operations of the OFFGAS SYSTEM including: (CFR: 41.7 / 45.7)	
A3.01	Automatic system isolations	3.3
A3.02	System flows	2.8
A3.03	System temperatures	2.8
A3.04	†Station radioactive release rate: Plant-Specific	3.8
A3.05	System indicating lights and alarms	2.9
A3.06	System differential pressures	2.5
A3.07	†Process radiation monitoring system indications	3.6
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Reset system isolations	2.8
A4.02	System flows	2.9
A4.03	System temperatures	2.8
A4.04	Condenser vacuum	3.5
A4.05	Station radioactive release rate	3.9
A4.06	System indicating lights and alarms	3.2
A4.07	System differential pressures	2.5
A4.08	Process radiation monitoring system	3.6
A4.09	Offgas system controls/components 3.3	3.2

SYSTEM: 288000 Plant Ventilation Systems

TASK: Shift ventilation lineups for various modes

Place charcoal filters in service

Remove charcoal filters from service

Operate ventilation fans

Operate air conditioning chiller units

Operate ventilation heating units

Monitor operation of heating, ventilation and air conditioning units

Perform main control room emergency fan and damper operability test (write in)

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between PLANT VENTILATION SYSTEMS and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04	A.C. electrical Secondary containment Standby gas treatment Applicable component cooling water system: Plant- Specific Process radiation monitoring system	. 3.4 . 3.7	2.6 3.4 3.7 2.6 3.6
K1.06	Plant air systems		2.7
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)		
K2.01	Reactor building supply and exhaust fans: Plant-Specific	. 2.4	2.4
K2.02	Auxiliary building supply and exhaust fans (turbine building/ radwaste building): Plant-Specific	. 1.8*	1.9*
K3.	Knowledge of the effect that a loss or malfunction of the PLANT VENTILATION SYSTEMS will have on following: (CFR: 41.5 / 45.3)		
K3.01 K3.02 K3.03 K3.04 K3.05 K3.06	Secondary containment temperature: Plant-Specific Reactor building temperature: Plant-Specific Auxiliary building temperature: Plant-Specific Secondary containment pressure: Plant-Specific Reactor building pressure: Plant-Specific Auxiliary building pressure: Plant-Specific	. 2.9 . 2.5 . 3.2 . 3.1	3.0 3.1 2.5 3.3 3.3 2.4
K4.	Knowledge of PLANT VENTILATION SYSTEMS design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Automatic initiation of standby gas treatment system	. 3.7	3.9

SYSTEM: 288000 Plant Ventilation Systems

Tasks as noted previously

IMPO)RTA	NCE
------	-------------	-----

K/A NO.	KNOWLEDGE RO	SRC
K4.02 K4.03	Secondary containment isolation	3.8 2.9
K5.	Knowledge of the operational implications of the following concepts as they apply to PLANT VENTILATION SYSTEMS: (CFR: 41.7 / 45.4)	
K5.01 K5.02 K5.03	Airborne contamination control3.1Differential pressure control3.2Temperature control2.5	3.2 3.4 2.6
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the PLANT VENTILATION SYSTEMS: (CFR: 41.7 / 45.7)	
K6.01 K6.02	A.C. electrical	2.7
K6.03	Specific 2.5 Plant air systems 2.7	2.5 2.7
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the PLANT VENTILATION SYSTEMS controls including: (CFR: 41.5 / 45.5)	
A1.01	Filter differential pressure	2.2*
A1.02	Fan differential pressure	2.2*
A1.03	Area temperatures	2.4
A2.	Ability to (a) predict the impacts of the following on the PLANT VENTILATION SYSTEMS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	High drywell pressure: Plant-Specific	3.4
A2.02	Low reactor water level: Plant-Specific	3.6
A2.03	Loss of coolant accident: Plant-Specific	3.7
A2.04 A2.05	High radiation: Plant-Specific 3.7 Extreme outside weather conditions: Plant-Specific 2.6	3.8 2.7
114.00	Extreme outside weather conditions. Frame-specific	۷.1

SYSTEM: 288000 Plant Ventilation Systems

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRC
A3.	Ability to monitor automatic operations of the PLANT VENTILATION SYSTEMS including: (CFR: 41.7 / 45.7)		
A3.01	Isolation/initiation signals	. 3.8	3.8
A4.	Ability to manually operate and/or monitor in the control room:		
A4.01 A4.02	Start and stop fans		2.9 2.8

TASK: Perform lineups of the area radiation monitoring system

Operate area radiation monitors

Monitor area radiation

Perform lineups of process radiation monitoring system

Operate process radiation monitors

Monitor process radiation monitor operation

	K/A NO.	KNOWLEDGE RO	SRO
	K1.	Knowledge of the physical connections and/or cause-effect relationships between RADIATION MONITORING SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
	K1.01	Main steam system	3.8
	K1.02	Offgas system (augmented offgas): Plant-Specific	3.5
	K1.03	Stack gas: Plant-Specific	3.6
	K1.04	Applicable component cooling water system	2.9
	K1.05	Radwaste system	3.1
'	K1.06	Reactor building ventilation system: Plant-Specific	3.3
	K1.07	Isolation condenser: Plant-Specific	3.2
	K1.08	Reactor protection system	3.9
	K1.09	Primary containment isolation system	3.8
	K1.10	Reactor building refuel floor: Plant-Specific	3.6
	K1.11	Reactor building overhead crane; Plant-Specific	2.4*
	K1.12	Reactor building	3.2
	K1.13	Turbine building	3.0
	K1.14	Radwaste building: Plant-Specific	2.8
	K1.15	Filter building: Plant-Specific	3.0
	K1.16	Process computer	2.3*
	K1.17	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.7
	K1.18	Primary containment/containment building: Plant-	
		Specific	3.1
	K1.19	Drywell	3.2
	K1.20	†Auxiliary building: Plant-Specific	3.0
	K1.21	Circulating water: Plant-Specific	2.4
	K1.22	Fuel building: mark-III	3.4
	K1.23	Continuous air monitoring: Plant-Specific	3.3
	K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	
	K2.01	Main steamline radiation monitors	2.8
	K2.02	Offgas radiation monitoring system	2.8
	K2.03	Stack gas radiation monitoring system	2.8
	K2.04	Process liquid radiation monitoring system	2.5

Tasks as noted previously

IMPORTANCE K/A NO. KNOWLEDGE RO SRO K2.05 Reactor building ventilation monitors: Plant-Specific 2.6 2.9 K2.06 2.2* K2.07 2.4* **K3** Knowledge of the effect that a loss or malfunction of the RADIATION MONITORING System will have on following: (CFR: 41.5 / 45.3) K3.01 3.8 K3.02 3.8 K3.03 3.4 K3.04 Main steam system 3.7 3.8 K3.05 3.7 K3.06 3.6 K3.07 Reactor building overhead crane operation: Plant-3.0 K3.08 3.3 K3.09 3.1 K3.10 3.3 K4. Knowledge of RADIATION MONITORING System design feature(s) and/or interlocks which provide for the following: (CFR: 41.7) K4.01 2.8 Automatic actions to contain the radioactive release K4.02 in the event that the predetermined release rates are 4.1 K4.03 Fail safe tripping of process radiation monitoring 3.9 K5. Knowledge of the operational implications of the following concepts as they apply to RADIATION **MONITORING SYSTEM:** (CFR: 41.7 / 45.4) K5.01 Hydrogen injection operation's effect on process

3.5

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K6	Knowledge of the effect that a loss or malfunction of the following will have on the RADIATION MONITORING SYSTEM: (CFR: 41.7 / 45.7)		
K6.01 K6.02 K6.03 K6.04 K6.05 K6.06	Reactor protection system D.C. power A.C. power Process computer SPDS/ERIS/CRID/GDS: Plant-Specific Continuous air monitoring: Plant-Specific	. 2.5 . 2.8 . 2.0* . 2.1*	3.2 2.7 3.0 2.2* 2.4* 2.6
A1.	Ability to predict and/or monitor changes in parameters associated with operating the RADIATION MONITORING SYSTEM controls including: (CFR: 41.5 / 45.5)		
A1.01	Lights, alarms, and indications associated with normal		
A1.02	operations Lights, alarms, and indications associated with	. 3.2	3.2
	surveillance testing	. 2.9	2.9
A2.	Ability to (d) predict the impacts of the following on the RADIATION MONITORING SYSTEM; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01	Fuel element failure	. 3.7	4.1
A2.02	Reactor protection system power failure		3.6
A2.03	A.C. electrical failure	. 2.9	3.1
A2.04	D.C. electrical failure	. 2.7	2.8
A2.05	Loss of dilution steam		2.6
A2.06	Downscale trips		2.9
A2.07	Hydrogen injection operation: Plant-Specific		2.8
A2.08	Offgas system failure		3.1
A2.09	Low fuel pool level		3.3
A2.10	Loss of coolant accident	. 3.9	4.1
A2.11	Leakage and/or breaks from contaminated systems to	2.4	27
A 2 12	atmosphere or to other process systems		3.7
A2.12	†Refuel floor handling accidents/operations		4.0
A2.13 A2.14	Loss of or inadequate shielding		3.8 3.5
A2.14 A2.15	Loss of, or inadequate, shielding		3.3 2.7
A2.13	manificiance operations	. 4.3	4.1

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
A2.16	Instrument malfunctions	. 2.7	2.9
A3.	Ability to monitor automatic operations of the RADIATION MONITORING SYSTEM including: (CFR: 41.7 / 45.7)		
A3.01	Main steam isolation indications	. 3.8	3.9
A3.02	Offgas system isolation indications		3.7
A3.03	Liquid radwaste isolation indications		3.5
A3.04	Radwaste handing interlocks		2.8
A3.05	Refuel floor overhead crane operation interrupt:		
	Plant-Specific	. 3.0	3.1
A3.06	Ventilation system isolation indications	. 3.4	3.4
A3.07	Recorder indications	. 2.8	2.9
A3.08	Meter indications	. 2.9	2.9
A3.09	Containment isolation indications	. 3.6	3.5
A3.10	Lights and alarms	. 3.3	3.2
A3.11	Circulating water system blowdown isolations: Plant-		
	Specific	. 2.6	2.7
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	Recorder indications	. 2.9	2.9
A4.02	Meter indications	. 3.0	3.0
A4.03	Power supply status indicators	. 2.6	2.6
A4.04	SPDS/ERIS/CRID/GDS	. 2.5*	2.7*
A4.05	†Convert process radiation monitor readings to offsite		
	release rates: Plant-Specific		3.7*
A4.06	†Manually trip process radiation monitor logic	. 2.9	3.2

SYSTEM: 268000 Radwaste

TASK: Monitor the liquid radwaste system (write in)

Operate the discharge water floor drain system (write in)

Operate the drywell equipment drain pump (write in)

Monitor the liquid radwaste system (waste collection) (write in)

Startup a concentrator/evaporator

Secure a concentrator/evaporator

Perform lineups on the solid radwaste system

K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between RADWASTE and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06 K1.07 K1.08 K1.09 K1.10 K1.11 K1.12 K1.13 K1.14 K1.15	Condensate systems Plant air systems Reactor building equipment drains: Plant-Specific Reactor building floor drains: Plant-Specific Drywell equipment drains Drywell floor drains Reactor water cleanup Fuel pool ECCS systems Auxiliary steam: Plant-Specific Applicable component cooling water system Suppression pool Auxiliary building floor drains: Plant-Specific Auxiliary building equipment drains: Plant-Specific Offgas system Circulating water system: Plant-Specific	. 2.1* . 2.6 . 2.7 . 2.9 . 2.9 . 2.8 . 2.7 . 2.6 . 2.2 . 2.2 . 2.2 . 2.3 . 2.2 . 2.0* . 2.3	2.6 2.4 2.9 2.9 3.2 3.2 2.9 2.8 2.8 2.4 2.5 2.4 2.5 2.5 2.5
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7) None		
К3.	Knowledge of the effect that a loss or malfunction of the RADWASTE will have on following: (CFR: 41.5 / 45.3)		
K3.01 K3.02 K3.03 K3.04 K3.05	RWCU system Condensate system ECCS systems Drain sumps Fuel pools: Plant-Specific	. 2.2 . 2.2* . 2.7	2.5 2.4 2.4 2.8 2.4

SYSTEM: 268000 Radwaste

Tasks as noted previously

IMPORTANCE K/A NO. KNOWLEDGE RO SRO K4. Knowledge of RADWASTE design feature(s) and/or interlocks which provide for the following: (CFR: 41.7) None K5. Knowledge of the operational implications of the following concepts as they apply to RADWASTE: (CFR: 41.5 / 45.3) K5.01 3.0 K5.02 3.6* K6. Knowledge of the effect that a loss or malfunction of the following will have on the RADWASTE: (CFR: 41.7) K6.01 2.5 K6.02 2.6 K6.03 2.7 K6.04 2.3 **ABILITY** A1. Ability to predict and/or monitor changes in parameters associated with operating the RADWASTE controls including: (CFR: 41.5 / 45.5) Radiation level 2.7* A1.01 3.1* A1.02 3.6* A2. Ability to (a) predict the impacts of the following on the RADWASTE; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6) A2.01 3.5

SYSTEM: 268000 Radwaste

A2.02

A2.03

2.7

2.3

K/A NO.	ABILITY RO	SRO
A3.	Ability to monitor automatic operations of the RADWASTE including: (CFR: 41.7 / 45.7)	
	None	
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
A4.01	Sump integrators	3.6

SYSTEM: 290002 Reactor Vessel Internals

K3.07

TASK: Perform heatup/cooldown of reactor vessel

IMPORTANCE K/A NO. **KNOWLEDGE** RO SRO K1. Knowledge of the physical connections and/or causeeffect relationships between REACTOR VESSEL INTERNALS and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8) K1.01 3.2 K1.02 3.2 K1.033.2 K1.04 3.5 K1.053.2 K1.06 3.1 K1.07 3.4 K1.08 3.1 K1.09 3.3 K1.103.1 K1.11 2.9 K1.12 3.5 K1.13 3.5 K1.14 3.1 K1.15 3.5 K1.16 3.4 K1.17 3.4 K1.18 2.2* K1.19 2.6 K1.203.3 K2. Knowledge of electrical power supplies to the following: (CFR: 41.7) None K3. Knowledge of the effect that a loss or malfunction of the REACTOR VESSEL INTERNALS will have on following: (CFR: 41.7 / 45.4) K3.01 3.3 K3.02 3.0 K3.03 3.4 K3.04 Plant radiation levels 2.9 3.2 K3.053.2 K3.06 3.1

3.1

SYSTEM: 290002 Reactor Vessel Internals

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRO
K4.	Knowledge of REACTOR VESSEL INTERNALS design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)	
K4.01	2/3 core coverage following a DBA LOCA	3.9
K4.02	Separation of fluid flow paths within the vessel	3.2
K4.03	Core orificing	3.3
K4.04	Moisture removal from generated steam	2.8
K4.05	Natural circulation	3.5
K5.	Knowledge of the operational implications of the following concepts as they apply to REACTOR VESSEL INTERNALS: (CFR: 41.5 / 45.3)	
K5.01	†Thermal limits	3.9
K5.02	Fission product poisons	3.1
K5.03	Burnable poisons	3.0
K5.04	†PCIOMR Plant-Specific	3.7
K5.05	Brittle fracture	3.3
K5.06	Heat transfer mechanisms	3.2
K5.07	†Safety limits	4.4*
K6.	Knowledge of the effect that a loss or malfunction of the following will have on the REACTOR VESSEL INTERNALS: (CFR: 41.7/45.7)	
K6.01	CRD hydraulic system 2.8	2.9
K6.02	CRD mechanism	2.9
K6.03	Recirculation system	3.2
K6.04	Reactor feedwater system	3.1
K6.05	SBLC 3.3	3.4
K6.06	Relief/safety valves	3.2
K6.07	RWCU	2.7
K6.08	Nuclear boiler instrumentation	3.2
K6.09	LPCS 3.2	3.3
K6.10	HPCI: Plant-Specific	3.3
K6.11	RHR: Plant-Specific	3.2
K6.12	Isolation condenser: Plant-Specific	3.2
K6.13	RCIC: Plant-Specific	2.8
K6.14	LPCI: Plant-Specific	3.3
K6.15	ADS	3.4
K6.16	Loss parts monitoring	2.0*
K6.17	TIP	2.5

SYSTEM: 290002 Reactor Vessel Internals

Tasks as noted previously

	IMPORTANCE	
K/A NO.	KNOWLEDGE RO	SRO
K6.18	Nuclear instrumentation	3.1
K6.19	HPCS: Plant-Specific(BWR-5&6)	3.1
K6.20	Main steam system	3.1
	ABILITY	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the REACTOR VESSEL INTERNALS controls including: (CFR: 41.5 / 45.5)	
	None	
A2.	Ability to (a) predict the impacts of the following on the REACTOR VESSEL INTERNALS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)	
A2.01	LOCA	4.0
A2.02	†Overpressurization transient	3.9
A2.03	†Control rod drop accident	3.9
A2.04	Excessive heatup/cooldown rate	4.1
A2.05	†Exceeding thermal limits	4.2
A2.06	†Exceeding safety limits	4.5*
A3.	Ability to monitor automatic operations of the REACTOR VESSEL INTERNALS including: (CFR: 41.7 / 45.7)	
	None	
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)	
	None	

TASK: Lineup residual heat removal supplemental fuel pool cooling

Monitor residual heat removal supplemental fuel pool cooling

Startup the torus/suppression pool cleanup system (write in)

Stop residual heat removal supplemental fuel pool cooling

Shutdown the torus/suppression pool cleanup system (write in)

Monitor RHR supplemental fuel pool cooling (write in)

Perform lineups on spent fuel pool cooling system

Fill the spent fuel pools

Startup the spent fuel pool cooling system in different pump/heat exchanger combinations

Perform spent fuel pool purification using filter

Perform spent fuel pool purification using demineralizer

Backwash spent fuel pool filter

Change spent fuel pool filter

Replace resin in spent fuel pool demineralizer

Operate system between refueling pool and spent fuel pool in different lineups

Operate the spent fuel pool skimmer loop

Monitor spent fuel pool cooling system operation

Perform borated water storage tank purification using filter

Perform borated water storage tank purification using demineralizer

Recirculate the spent fuel pool

Lower refueling pool level

Fill and vent the spent fuel pool purification system

Perform spent fuel pool leakage test

Fill the fuel transfer canal

Drain the fuel transfer canal

Perform fuel transfer canal purification

Recirculate fuel transfer canal

Perform decay heat removal using the spent fuel cooling system

Shutdown the spent fuel pool cooling system

Fill the dryer-separator pit

Drain the dryer-separator pit

Conduct nitrogen mixing of spent fuel pool cooling demineralizer resin

K/A NO.	KNOWLEDGE RO	SRO
K1.	Knowledge of the physical connections and/or cause- effect relationships between FUEL POOL COOLING AND CLEAN-UP and the following:	
	(CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01	Shutdown cooling system: Plant-Specific	2.9
K1.02	Residual heat removal system: Plant-Specific	3.0
K1.03	Condensate storage tank	2.3
K1.04	Process sampling system	2.0*

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K1.05	Plant air systems	. 2.2	2.2
K1.06	A.C. electrical power	2.3	2.3
K1.07	Condensate system: Plant-Specific	2.1	2.2
K1.08	Condensate transfer	2.5	2.5
K1.09	Component cooling water systems	2.6	2.6
K1.10	Containment drainage system: Plant-Specific	2.2	2.3
K1.11	Reactor building drainage system: Plant-Specific		2.4
K1.12	Radwaste system		2.6
K1.13	Suppression pool cleanup system: Plant-Specific		2.6
K1.14	Reactor building ventilation		2.5
K1.15	Storage pools		2.9
K1.16	Emergency cooling water systems: Plant-Specific		2.8
K2.	Knowledge of electrical power supplies to the		
	following:		
	(CFR: 41.7)		
K2.01	Fuel pool cooling pumps	2.1*	2.2*
K2.02	RHR pumps		2.9*
К3.	Knowledge of the effect that a loss or malfunction of the FUEL POOL COOLING AND CLEAN-UP will have on following: (CFR: 41.7/45.6)		
K3.01	Fuel pool temperature	3.2	3.4
K3.02	Fuel pool water level		3.2
K3.03	Fuel pool water clarity		2.8
K3.04	Fuel pool water chemistry		2.6
K3.05	Fuel pool water fission product concentration		2.8
K3.06	Area radiation levels		3.2
K3.07	Suppression pool chemistry: Plant-Specific		2.9
K3.07 K3.08	†Refueling operations		3.5
		,	0.0
K4.	Knowledge of FUEL POOL COOLING AND CLEAN-UP design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Redundancy	. 2.4	2.6
K4.02	Pool clarity		2.6
K4.03	Maintenance of adequate pool temperature		3.1
K4.04	Overpressure protection for fuel pool cooling system		
77.4.05	filter	. 2.0*	2.1
K4.05	Net positive suction head requirements for fuel pool	2.1*	2.2*
K4.06	cooling pumps		2.2* 3.2
			- · -

Tasks as noted previously

IMPORTANCE K/A NO. KNOWLEDGE RO SRO K4.07 2.9 K4.08 K4.09 Maintenance of filter/demineralizer precoat during low 2.4* K5. Knowledge of the operational implications of the following concepts as they apply to FUEL POOL COOLING **AND CLEAN-UP:** (CFR: 41.5 / 45.3) K5.01 2.7 K5.02 2.2* K5.03 2.8 K5.04 2.2* K5.05 2.2* K5.06 2.7 K5.07 2.8 K6. Knowledge of the effect that a loss or malfunction of the following will have on the FUEL POOL COOLING AND **CLEAN-UP:** (CFR: 41.7 / 45.7) K6.01 2.7 K6.02 2.5* K6.03 2.7 K6.04 2.6 K6.05 2.3 K6.06 2.4 K6.07 2.8 K6.08 2.4 K6.09 2.4 K6.10 3.3 K6.11 2.6* **ABILITY** Al. Ability to predict and/or monitor changes in parameters associated with operating the FUEL POOL **COOLING AND CLEAN-UP controls including:** (CFR: 41.5 / 45.5) A1.01 2.9

A1.02

A1.03

A1.04

Al.05

3.1

3.3

2.5

2.3*

Tasks as noted previously

	IMPORTANCE		
K/A NO.	ABILITY	RO	SRO
Al.06	System flow	2.5	2.4
Al.07	System temperature		2.8
Al.08	Pool chemistry	2.1*	2.4*
Al.09	Pool clarity	. 2.4	2.6
A1.10	Pool activity levels		2.6*
A1.11	Suppression pool chemistry: BWR-6	. 2.4	2.9
A2.	Ability to (a) predict the impacts of the following on		
	the FUEL POOL COOLING AND CLEAN-UP; and (b) based on		
	those predictions, use procedures to correct, control,		
	or mitigate the consequences of those abnormal		
	conditions or operations:		
	(CFR: 41.5 / 45.6)		
A2.01	High pool level	. 2.7	2.9
A2.02	Low pool level	3.1	3.3
A2.03	Low surge tank level/high level	. 2.8	3.0
A2.04	Pump trip		2.7
A2.05	Valve closures		2.5
A2.06	Valve openings		2.5
A2.07	High fuel pool temperature		3.2
A2.08	Closed cooling water failure		3.1
A2.09	A.C. electrical power failures		2.9
A2.10	Refueling bellows seal high flow		3.3
A2.11 A2.12	Fuel pool gate seal high flow		3.2 2.4
A2.12 A2.13	High filter/ demineralizer differential pressure		2.4*
A2.13 A2.14	Low system flow		2.3
A2.14 A2.15	High system temperature		2.9
A2.16	Loss of coolant accident signal		2.8
A2.17	Fuel transfer tube drain tank high level/low level:	. 2.5	2.0
	BWR-6	. 2.8	2.8
A2.18	Low pool clarity	2.5	2.7
A2.19	Inadequate system/pool chemistry	. 2.5	2.8
A3.	Ability to monitor automatic operations of the FUEL POOL COOLING AND CLEAN-UP including: (CFR: 41.7 / 45.7)		
A3.01	Valve operation	2.4	2.5
A3.02	Pump trip(s)		2.6
A3.03	System indicating lights and alarms		2.6

Tasks as noted previously

K/A NO.	ABILITY	RO	SRO
A4.	Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
A4.01	System lights and alarms	2.6	2.6
A4.02	System lineups		2.5
A4.03	System flow		2.4
A4.04	Pool level		3.1
A4.05	Pool temperature	2.7*	3.1*
A4.06	System temperature		2.6*
A4.07	System pressures		2.3*
A4.08	System differential pressures		2.2*
A4.09	Pump operation		2.2*
A4.10	Tank levels		2.6
A4.11	Closed cooling water temperature		2.5

TASK: Perform lineups on the standby gas treatment system

Place the standby gas treatment system in standby readiness

Place the standby gas treatment system in service manually

Monitor the standby gas treatment system following automatic initiation

Remove one standby gas treatment (SGTS) train from service after automatic initiation

Secure the standby gas treatment system (SGTS)

Perform standby gas treatment manual bypass valve operation, and simulated auto act test

Perform standby gas treatment system logic system functional test

Perform one circuit of standby gas treatment system inoperable test

K/A NO. KNOWLEDGE RO	SRO
K1. Knowledge of the physical connections and/or cause-effect relationships between STANDBY GAS TREATMENT SYSTEM and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)	
K1.01 Reactor building ventilation system	3.6
K1.02 Drywell	3.4
K1.03 Suppression pool	3.1
K1.04 High radiation sampling system	2.8
K1.05 Radwaste system: Plant-Specific	2.4
K1.06 High pressure coolant injection system: Plant-	
Specific	3.1
K1.07 Elevated release stack	3.2
K1.08 Process radiation monitoring system	3.1
K1.09 Primary containment isolation system	3.4
K1.10 Plant air systems	2.3
K1.11 Primary containment pressure	3.3
K1.12 Primary containment purge system: Plant-Specific	3.2
11 mary containment purge system. Train Specific	3.2
K2. Knowledge of electrical power supplies to the following: (CFR: 41.7)	
K2.01 Fan power	2.3*
K2.02 Valve power	2.0*
K2.03 Initiation logic	2.5*
K2.03 Initiation logic 2.3 K2.04 Heater power	1.9*
K2.04 Healer power	1.9
K3. Knowledge of the effect that a loss or malfunction of the STANDBY GAS TREATMENT SYSTEM will have on following: (CFR: 41.7 /45.6)	
K3.01 Secondary containment and environment differential pressure	3.6
K3.02 Off-site release rate	3.9

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K3.03 K3.04	Primary containment pressure: Mark-I&II		3.4
	Specific		3.1
K3.05	Secondary containment radiation/ contamination levels		3.5
K3.06	Primary containment oxygen content: Mark-I&II	. 3.0	3.3
K4.	Knowledge of STANDBY GAS TREATMENT SYSTEM design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01	Automatic system initiation	. 3.7	3.8
K4.02	Charcoal bed decay heat removal		2.8
K4.03	Moisture removal		2.7
K4.04	Radioactive particulate filtration		2.9
K4.05	Fission product gas removal		2.8
K4.06	Charcoal bed retention		2.6
K5.	Knowledge of the operational implications of the following concepts as they apply to STANDBY GAS TREATMENT SYSTEM: (CFR: 41.5 / 45.3)		
K5.01	Heat removal mechanisms	. 2.3*	2.6*
K5.02	Air operated valves: Plant-Specific		2.5*
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the STANDBY GAS TREATMENT SYSTEM: (CFR: 41.7 / 45.7)		
K6.01	A.C. electrical distribution	. 2.9	3.0
K6.02	D.C. electrical distribution		2.6*
K6.03	Emergency diesel generator system		3.1
K6.04	Process radiation monitoring		3.1
K6.05	Reactor protection system: Plant-Specific		3.2
K6.06	Plant air systems		2.6
K6.07	Primary containment atmosphere sampling system: Plant-Specific		2.4
K6.08	Reactor vessel level: Plant-Specific		3.1
K6.09	Primary containment high pressure: Plant-Specific		3.3
110.07	1 mary contaminent ingit pressure. Trant-specific	. 5.1	5.5

Tasks as noted previously

K/A NO.	IMPORTANCE KNOWLEDGE RO	SRO
MA NO.	MIO II LEDGE RU	SKU
	ABILITY	
	ADILITI	
A1.	Ability to predict and/or monitor changes in parameters associated with operating the STANDBY GAS TREATMENT SYSTEM controls including: (CFR: 41.5 / 45.5)	
A1.01	System flow	3.1
A1.02	Primary containment pressure	
A1.03	†Off-site release levels	
A1.04	Secondary containment differential pressure	
A1.05	Primary containment oxygen level: Mark-I&II	
A1.06	Drywell and suppression chamber differential pressure:	2.,
711.00	Mark-I	7 3.0
A1.07	SBGTS train temperature	
711.07	bbotb tain emperature	2.7
A2.	Ability to (a) predict the impacts of the following on	
112.	the STANDBY GAS TREATMENT SYSTEM; and (b) based on	
	those predictions, use procedures to correct, control,	
	or mitigate the consequences of those abnormal	
	conditions or operations:	
	(CFR: 41.5 / 45.6)	
	(CIR. 11.57 15.0)	
A2.01	Low system flow	3.1
A2.02	High system flow	
A2.03	High train temperature	
A2.04	High train moisture content	
A2.05	Fan trips	
A2.06	Valve closures	
A2.07	A.C. electrical failure 2.7	
A2.08	D.C. electrical failure 2.4	
A2.09	Plant air system failure	
A2.10	Low reactor water level: Plant-Specific	3.2
A2.10 A2.11	•	
A2.11 A2.12	High containment pressure 3.2 High fuel pool ventilation radiation: Plant-Specific 3.2	
A2.12 A2.13	High secondary containment ventilation exhaust	3.4
A2.13		2.7
A 2 14	radiation	
A2.14	High system pressure: Plant-Specific	
A2.15	High area radiation by refuel bridge: Plant-Specific	3.4
A3.	Ability to monitor automatic operations of the STANDBY	
110.	GAS TREATMENT SYSTEM including:	
	(CFR: 41.7/45.7)	
	(CI IX. 71.// TJ./)	
A3.01	System flow	2 3.3
A3.02	Fan start	
113.02	1 un start	. 3.1

Tasks as noted previously

K/A NO.	KNOWLEDGE RO	SRC
A3.03	Valve operation	2.9
A3.04	System temperature	3.1
A4.	Ability to manually operate and/or monitor in the control room:	
	(CFR: 41.7 / 45.5 to 45.8)	
A4.01	†Off-site release levels: Plant-Specific	4.0*
A4.02	Suction valves	3.1
A4.03	Fan	3.0
A4.04	Primary containment pressure	3.4
A4.05	Drywell to suppression chamber/torus differential	
	pressure: Mark-I,II	3.2
A4.06	Reactor building differential pressure	3.6
A4.07	System flow	3.2
A4.08	System temperature	2.7
A4.09	Ventilation valves/dampers	2.7

SYSTEM: 290003 Control Room HVAC

TASK: Perform system lineups
Place system in standby operating mode

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.	Knowledge of the physical connections and/or cause-effect relationships between CONTROL ROOM HVAC and the following: (CFR: 41.2 to 41.9 / 45.7 to 45.8)		
K1.01 K1.02 K1.03 K1.04 K1.05 K1.06	Radiation monitors Chlorine amonia detectors: Plant-Specific Remote air intakes: Plant-Specific Nuclear steam supply shut off system (NSSSS/PCIS): Plant-Specific Component cooling water systems Plant air systems	2.9 2.8 3.2 2.8	3.5 3.1 2.9 3.3 3.0 2.7
K1.07	Fire protection		3.0
K2.	Knowledge of electrical power supplies to the following: (CFR: 41.7)	,	3.0
K2.01 K2.02 K2.03	Fans Chiller units Motor operated valves: Plant-Specific	2.4*	2.4* 2.4* 2.0*
К3.	Knowledge of the effect that a loss or malfunction of the CONTROL ROOM HVAC will have on following: (CFR: 41.7 /45.6)		
K3.01 K3.02 K3.03 K3.04	Control room habitability Computer/instrumentation: Plant-Specific Control room temperature Control room pressure	3.3 2.9	3.8 3.6 3.1 2.9
K4.	Knowledge of CONTROL ROOM HVAC design feature(s) and/or interlocks which provide for the following: (CFR: 41.7)		
K4.01 K4.02	System initiations/reconfiguration: Plant-Specific		3.2 2.6
K5.	Knowledge of the operational implications of the following concepts as they apply to CONTROL ROOM HVAC (CFR: $41.5/45.3$)		
K5.01	Airborne contamination (e.g., radiological, toxic gas, smoke) control	3.2	3.5
K5.02	Differential pressure control		2.8

SYSTEM: 290003 Control Room HVAC

Tasks as noted previously

K/A NO.	KNOWLEDGE	RO	SRO
K5.03	Temperature control	. 2.6	2.7
К6.	Knowledge of the effect that a loss or malfunction of the following will have on the CONTROL ROOM HVAC: (CFR: 41.7/45.7)		
K6.01 K6.02 K6.03 K6.04	Electrical power Component cooling water systems Plant air systems Fire protection: Plant-Specific ABILITY	. 2.7 . 2.4	2.9 2.9 2.6 2.8
A1.	Ability to predict and/or monitor changes in parameters associated with operating the CONTROL ROOM HVAC controls including: (CFR: 41.5 / 45.5)		
A1.01 A1.02 A1.03 A1.04 A1.05	Filter differential pressure Fan differential pressure Area temperatures Control room pressure Radiation monitoring (control room)	. 2.1* . 2.6 . 2.5	2.1* 2.1* 2.6 2.8 3.3
A2.	Ability to (a) predict the impacts of the following on the CONTROL ROOM HVAC; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those abnormal conditions or operations: (CFR: 41.5 / 45.6)		
A2.01 A2.02 A2.03 A2.04	Initiation/reconfiguration Extreme environmental conditions Initiation/reconfiguration failure Initiation/failure of fire protection system	. 3.1	3.2 3.4 3.6 3.3
A3.	Ability to monitor automatic operations of the CONTROL ROOM HVAC including: (CFR: 41.7 / 45.7)		
A3.01 A3.02	Initiation/reconfiguration		3.5 3.4

SYSTEM: 290003 Control Room HVAC

Tasks as noted previously

KNOWLEDGE	RO	SRO
Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8)		
Initiate/reset system	. 3.2	3.2
		2.8
Reposition dampers	. 2.8	2.8
Environmental conditions	. 2.8	3.0
	KNOWLEDGE Ability to manually operate and/or monitor in the control room: (CFR: 41.7 / 45.5 to 45.8) Initiate/reset system Fans Reposition dampers	KNOWLEDGE RO Ability to manually operate and/or monitor in the control room:

4.1	Emergency Plant Evolutions	page
295024	High Drywell Pressure	4.1-3
295025	High Reactor Pressure	4.1-5
295026	Suppression Pool High Water Temperature	4.1-7
295027	High Containment Temperature (Mark III Containment Only)	4.1-8
295028	High Drywell Temperature	4.1-9
295029	High Suppression Pool Water Level	4.1-11
295030	Low Suppression Pool Water Level	4.1-12
295031	Reactor Low Water Level	4.1-14
295032	High Secondary Containment Area Temperature	4.1-16
295033	High Secondary Containment Area Radiation Levels	4.1-18
295034	Secondary Containment Ventilation High Radiation	4.1-20
295035	Secondary Containment High Differential Pressure	4.1-22
295036	Secondary Containment High Sump / Area Water Level	4.1-23
295037	SCRAM Condition Present and Reactor Power Above APRM	4.1-24
	Downscale or unknown	
295038	High Off-Site Release Rate	4.1-26
500000	High Containment Hydrogen Concentration	4.1-28

This page left blank

EPE: 295024 High Drywell Pressure

		IMPORTANCE		
K/A NO.	KNOWLEDGE		RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH DRY PRESSURE: (CFR: 41.8 to 41.10)			
EK1.01 EK1.02	Drywell integrity: Plant-Specific Containment building integrity: Mark-III		4.1 3.9	4.2* 4.1
EK2.	Knowledge of the interrelations between HIGH PRESSURE and the following: (CFR: 41.7 / 45.8)	DRYWELL		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05 EK2.06 EK2.07 EK2.08 EK2.09 EK2.10 EK2.11 EK2.12 EK2.13 EK2.14 EK2.15 EK2.14 EK2.15 EK2.16 EK2.17 EK2.18 EK2.19 EK2.20	HPCI (FWCI): Plant-Specific		3.9 3.7 3.8 3.9 3.9 3.9 4.0 2.9 3.5 4.2 3.5 3.8 3.9 3.8 3.2 3.0 3.3 2.9 2.8	4.0 3.7 3.8 3.9 4.0 4.0 3.9 4.1 3.5 4.2* 3.5 3.8 3.9 3.9 3.2 3.3 3.4 2.9 2.9
EK3.	D.C. distribution: Plant-Specific Knowledge of the reasons for the following res as they apply to HIGH DRYWELL PRESSURE (CFR: 41.5 / 45.6)	_	2.0	2.9
EK3.01 EK3.02 EK3.03 EK3.04 EK3.05 EK3.06 EK3.07 EK3.08 EK3.09	Drywell spray operation: Mark-I&II		3.6 3.5 3.6 3.7 3.5 4.0* 3.5 3.7 3.1	4.0 3.8 4.1 4.1 3.8 4.1 4.0 4.1 3.6

EPE: 295024 High Drywell Pressure

IMPORTAN	CE		
K/A NO.	ABILITY	RO	SRO
EA1.	Ability to operate and/or monitor the following as		
	they apply to HIGH DRYWELL PRESSURE:		
	(CFR: 41.7 / 45.6)		
EA1.01	HPCI (FWCI): Plant-Specific	4.1*	4.0
EA1.02	HPCS: Plant-Specific	3.8	3.7
EA1.03	LPCS: Plant-Specific	4.0	3.9
EA1.04	RHR/LPCI	4.1	3.9
EA1.05	RPS	3.9	4.0
EA1.06	Emergency generators	3.7	3.7
EA1.07	PCIS/NSSSS	3.8	3.9
EA1.08	ADS: Plant-Specific	3.9	3.9
EA1.09	Suppression pool makeup: Plant-Specific	2.9	3.0
EA1.10	A.C. distribution	3.4	3.6
EA1.11	Drywell spray: Mark-I&II	4.2*	4.2*
EA1.12	Suppression pool spray: Mark-I&II	3.8	3.8
EA1.13	Suppression pool cooling	3.6	3.6
EA1.14	Drywell ventilation system	3.4	3.5
EA1.15	Containment/drywell atmospheric monitoring	3.6	3.7
EA1.16	Containment/drywell vacuum breakers	3.4	3.4
EA1.17	Containment spray: Plant-Specific	3.9	3.9
EA1.18	Containment ventilation system: Mark-III	3.6	3.6
EA1.19	Containment atmosphere control: Plant-Specific	3.3	3.4
EA1.20	Standby gas treatment/FRVS: Plant-Specific	3.5	3.6
EA1.21	Recirculation system (LPCI loop select logic):		
	Plant-Specific	3.4	3.8
EA1.22	D.C. distribution: Plant-Specific	2.7	2.9
EA2.	Ability to determine and/or interpret the following as		
	they apply to HIGH DRYWELL PRESSURE:		
	(CFR: 41.10 / 43.5 / 45.13)		
EA2.01	Drywell pressure	4.2*	4.4*
EA2.02	Drywell temperature	3.9	4.0
EA2.03	Suppression pool level	3.8	3.8
EA2.04	Suppression chamber pressure: Plant-Specific	3.9	3.9
EA2.05	Suppression chamber air-space temperature: Plant-	3.7	3.7
2112.00	Specific	3.6	3.7
EA2.06	Suppression pool temperature	4.1	4.1
EA2.07	Containment radiation levels: Mark-III	3.4	3.9
EA2.08	Drywell radiation levels	3.6	4.0
EA2.09	Containment pressure: Mark-III	4.0*	4.1*
EA2.10	Containment temperature: Mark-III	3.7	3.9
		5.7	2.,

EPE: 295025 High Reactor Pressure

IMPORTANC	E		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the		
	following concepts as they apply to HIGH REACTOR PRESSURE:		
	(CFR: 41.8 to 41.10)		
	(CITAL THOU THIS)		
EK1.01	Pressure effects on reactor power	3.9	4.0
EK1.02	Reactor vessel integrity	4.1	4.2
EK1.03	Safety/relief valve tailpipe temperature/pressure		
	relationships	3.6	3.8
EK1.04	Decay heat generation	3.6	3.9
EK1.05	†Exceeding safety limits	4.4*	4.7*
EK1.06	Pressure effects on reactor water level	3.5	3.6
EK2.	Knowledge of the interrelations between HIGH REACTOR		
	PRESSURE and the following:		
	(CFR: 41.7 / 45.8)		
EU2 01	DDG	4 1 4	4 1
EK2.01	RPS	4.1*	4.1
EK2.02	Isolation condenser: Plant-Specific	4.2*	4.5*
EK2.03	RRCS: Plant-Specific	4.0 3.9	4.3
EK2.04 EK2.05	ARI/RPT/ATWS: Plant-Specific	3.9 4.1*	4.1* 4.2
EK2.05 EK2.06	Safety/relief valves: Plant-Specific	3.8	3.8
EK2.00 EK2.07	HPCI: Plant-SpecificRCIC: Plant-Specific	3.6 3.7	3.8 3.7
EK2.07 EK2.08	Reactor/turbine pressure regulating system: Plant-	3.7	3.7
EK2.06	Specific	3.7	3.7
EK2.09	Reactor power	3.9	3.7
EK2.10	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.9	3.2
EK2.10 EK2.11	Reactor water level	3.5	3.6
LK2.11	Reactor water level	3.3	5.0
EK3.	Knowledge of the reasons for the following responses		
	as they apply to HIGH REACTOR PRESSURE :		
	(CFR: 41.5 / 45.6)		
EK3.01	Safety/relief valve opening	4.2	4.3*
EK3.02	Recirculation pump trip: Plant-Specific	3.9	4.1
EK3.03	HPCI operation: Plant-Specific	3.8	3.8
EK3.04	Isolation condenser initiation: Plant-Specific	4.5*	4.7*
EK3.05	RCIC operation: Plant-Specific	3.6	3.7
EK3.06	Alternate rod insertion: Plant-Specific	4.2*	4.4*
EK3.07	†RRCs initiation: Plant-Specific	3.3	3.7
EK3.08	Reactor/turbine pressure regulating system operation	3.5	3.5
EK3.09	Low-low set initiation: Plant-Specific	3.7	3.7

295025 High Reactor Pressure EPE:

	IMPORTANCE		
K/A NO.	ABILITY	RO	SRO
EA1.	Ability to operate and/or monitor the following as they apply to HIGH REACTOR PRESSURE: (CFR: 41.7 / 45.6)		
EA1.01 EA1.02 EA1.03 EA1.04 EA1.05 EA1.06 EA1.07 EA1.08	Main steam line drains	2.9 3.8 4.4* 3.8 3.7 4.5* 4.1	3.0 3.8 4.4* 3.9 3.7 4.5* 4.1 3.7*
EA2.	Ability to determine and/or interpret the following as they apply to HIGH REACTOR PRESSURE: (CFR: 41.10 / 43.5 / 45.13)		
EA2.01 EA2.02 EA2.03 EA2.04 EA2.05 EA2.06	Reactor pressure	4.3* 4.2* 3.9 3.9 3.4 3.7	4.3* 4.2 4.1 3.9 3.6 3.8

EPE: 295026 Suppression Pool High Water Temperature

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to SUPPRESSION POOL HIGH WATER TEMPERATURE: (CFR: 41.8 to 41.10)		
EK1.01	Pump NPSH	3.0	3.4
EK1.02	Steam condensation	3.5	3.8
EK2.	Knowledge of the interrelations between SUPPRESSION POOL HIGH WATER TEMPERATURE and the following: (CFR: 41.7 / 45.8)		
EK2.01	Suppression pool cooling	3.9	4.0
EK2.02	Suppression pool spray: Plant-Specific	3.6	3.8
EK2.03	Suppression chamber pressure: Mark-I&II	3.2	3.6
EK2.04	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.5	2.8
EK2.05	Containment pressure: Mark-III	3.0	3.3
EK2.06	Suppression pool level	3.5	3.7
EK3.	Knowledge of the reasons for the following responses as they apply to SUPPRESSION POOL HIGH WATER TEMPERATURE: (CFR: 41.5 / 45.6)		
EK3.01	Emergency/normal depressurization	3.8	4.1
EK3.02	Suppression pool cooling	3.9	4.0
EK3.03	Suppression pool spray: Plant-Specific	3.5	3.8
EK3.04	†SBLC injection	3.7	4.1*
EK3.05	Reactor SCRAM	3.9	4.1
LIX3.03		3.7	7.1
	ABILITY		
EA1.	Ability to operate and/or monitor the following as they apply to SUPPRESSION POOL HIGH WATER TEMPERATURE: (CFR: 41.7 / 45.6)		
EA1.01	Suppression pool cooling	4.1	4.1
EA1.02	Suppression pool spray: Plant-Specific	3.6	3.8
EA1.03	Temperature monitoring	3.9*	3.9
EA2.	Ability to determine and/or interpret the following as they apply to SUPPRESSION POOL HIGH WATER TEMPERATURE: (CFR: $41.10/43.5/45.13$)		
EA2.01	Suppression pool water temperature	4.1*	4.2*
EA2.02	Suppression pool level	3.8	3.9
EA2.03	Reactor pressure	3.9	4.0
2.12.03	2.00001 p.2000utoniiniiniiniiniiniiniiniiniiniiniiniinii	5.7	

EPE: 295027 High Containment Temperature (Mark III Containment Only)

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** EK1. Knowledge of the operational implications of the following concepts as they apply to HIGH CONTAINMENT TEMPERATURE (MARK III CONTAINMENT ONLY): (CFR: 41.8 to 41.10) EK1.01 Equipment environmental qualifications: Mark-III..... 2.5 2.7 EK1.02 Reactor water level measurement: Mark-III..... 3.0 3.2 EK1.03 Containment integrity: Mark-III..... 3.8 3.8 EK2. Knowledge of the interrelations between HIGH CONTAINMENT TEMPERATURE (MARK III CONTAINMENT ONLY) and the following: (CFR: 41.7 / 45.8) EK2.01 Containment spray: Plant-Specific..... 3.2 3.4 EK2.02 Components internal to the containment: Mark-III..... 3.2 3.3 Containment ventilation/cooling: Mark-III..... EK2.03 3.5 3.7 EK2.04 SPDS/ERIS/CRIDS/GDS: Mark-III..... 2.6 3.2 **EK3. Knowledge of the reasons for the following responses** as they apply to HIGH CONTAINMENT TEMPERATURE (MARK **III CONTAINMENT ONLY):** (CFR: 41.5 / 45.6) EK3.01 Emergency depressurization: Mark-III..... 3.7 3.8 EK3.02 Containment spray: Plant-Specific..... 3.2 3.2 EK3.03 Reactor SCRAM: Mark-III..... 3.7 3.7 **ABILITY** EA1. Ability to operate and/or monitor the following as they apply to HIGH CONTAINMENT TEMPERATURE (MARK III **CONTAINMENT ONLY):** (CFR: 41.7 / 45.6) EA1.01 Containment spray: Plant-Specific..... 3.2 3.4 EA1.02 Containment ventilation/cooling: Mark-III..... 3.5 3.5 EA1.03 Emergency depressurization: Mark-III..... 3.5 3.8 EA2. Ability to determine and/or interpret the following as they apply to HIGH CONTAINMENT TEMPERATURE (MARK III **CONTAINMENT ONLY):** (CFR: 41.10 / 43.5 / 45.13) EA2.01 Containment temperature: Mark-III..... 3.7 3.7 EA2.02 Containment pressure: Mark-III..... 3.7 3.7 EA2.03 Reactor pressure: Mark-III..... 3.3 3.3 EA2.04 Containment radiation levels: Mark-III..... 3.3 3.7

EPE: 295028 High Drywell Temperature

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH DRYWELL TEMPERATURE: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02	Reactor water level measurement Equipment environmental qualification	3.5 2.9	3.7 3.1
EK2.	Knowledge of the interrelations between HIGH DRYWELL TEMPERATURE and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05	†Drywell spray: Mark-I&II Components internal to the drywell Reactor water level indication Drywell ventilation SPDS/ERIS/CRIDS/GDS: Plant-Specific	3.7 3.2 3.6 3.6 2.3*	4.1 3.3 3.8 3.6 2.5
EK3.	Knowledge of the reasons for the following responses as they apply to HIGH DRYWELL TEMPERATURE : $(CFR:\ 41.5/45.6)$		
EK3.01 EK3.02 EK3.03 EK3.04 EK3.05 EK3.06	Emergency depressurization	3.6 3.5 3.6 3.6 3.6 3.4	3.9 3.8 3.9 3.8 3.7 3.7
EA1.	ABILITY Ability to operate and/or monitor the following as they apply to HIGH DRYWELL TEMPERATURE: (CFR: 41.7 / 45.6)		
EA1.01 EA1.02 EA1.03 EA1.04 EA1.05	Drywell spray: Mark-I&II Drywell ventilation system Drywell cooling system Drywell pressure ADS	3.8 3.9 3.9 3.9 3.7	3.9 3.8 3.9 4.0 3.7
EA2.	Ability to determine and/or interpret the following as they apply to HIGH DRYWELL TEMPERATURE : (CFR: $41.10/43.5/45.13$)		
EA2.01 EA2.02 EA2.03	Drywell temperatureReactor pressureReactor water level	4.0* 3.8 3.7	4.1* 3.9 3.9

EPE: 295028 High Drywell Temperature

K/A NO.	ABILITY	RO	SRO
EA2.04	Drywell pressure	4.1	4.2
EA2.05	Torus/suppression chamber pressure: Plant-Specific	3.6	3.8
EA2.06	Torus/suppression chamber air space temperature:		
	Plant-Specific	3.4	3.7

EPE: 295029 High Suppression Pool Water Level

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH SUPPRESSION POOL WATER LEVEL: (CFR: 41.8 to 41.10)		
EK1.01	Containment integrity	3.4	3.7
EK2.	Knowledge of the interrelations between HIGH SUPPRESSION POOL WATER LEVEL and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05 EK2.06 EK2.07 EK2.08 EK2.09	RHR/LPCI HPCI: Plant-Specific HPCS: Plant-Specific Suppression pool cleanup system: Plant-Specific Containment/drywell vacuum breakers SRV's and discharge piping Drywell/containment water level Drywell/suppression chamber ventilation RCIC: Plant-Specific	3.0 3.4 3.3 2.4* 3.1 3.4 3.1 2.6 3.1	3.3 3.6 3.5 2.4* 3.3 3.5 3.2 2.9 3.2
EK3.	Knowledge of the reasons for the following responses as they apply to HIGH SUPPRESSION POOL WATER LEVEL: (CFR: 41.5/45.6)	5.1	5.2
EK3.01 EK3.02 EK3.03	Emergency depressurization Lowering suppression pool water level Reactor SCRAM ABILITY	3.5 3.6 3.4	3.9* 4.0 3.5
EA1.	Ability to operate and/or monitor the following as they apply to HIGH SUPPRESSION POOL WATER LEVEL: (CFR: 41.7/45.6)		
EA1.01 EA1.02 EA1.03 EA1.04	HPCI: Plant-Specific HPCS: Plant-Specific RHR/LPCI RCIC: Plant-Specific	3.4* 3.1 2.9 3.4	3.5 3.1 3.0 3.5
EA2.	Ability to determine and/or interpret the following as they apply to HIGH SUPPRESSION POOL WATER LEVEL : (CFR: $41.10 / 43.5 / 45.13$)		
EA2.01 EA2.02 EA2.03	Suppression pool water level	3.9* 3.5 3.4	3.9* 3.6 3.5

EPE: 295030 Low Suppression Pool Water Level

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to LOW SUPPRESSION POOL WATER LEVEL: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02 EK1.03	Steam condensationPump NPSHHeat capacity	3.8* 3.5 3.8	4.1* 3.8 4.1*
EK2.	Knowledge of the interrelations between LOW SUPPRESSION POOL WATER LEVEL and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05 EK2.06 EK2.07 EK2.08 EK2.09	HPCI: Plant-Specific	3.8 3.7 3.8 3.7 3.8 3.9* 3.5 3.5 2.5	3.9 3.8 3.9 3.8 3.9 3.9* 3.8 3.8 2.8
EK3.	Knowledge of the reasons for the following responses as they apply to LOW SUPPRESSION POOL WATER LEVEL: (CFR: $41.5/45.6$)		
EK3.01 EK3.02 EK3.03 EK3.04 EK3.05 EK3.06 EK3.07	Emergency depressurization	3.8 3.5 3.6 3.5 3.6 3.6 3.5	4.1 3.7 3.7 3.5 3.6 3.8 3.8
EA1.	ABILITY Ability to operate and/or monitor the following as they apply to LOW SUPPRESSION POOL WATER LEVEL: (CFR: 41.7 / 45.6)		
EA1.01 EA1.02 EA1.03 EA1.04 EA1.05	ECCS systems (NPSH considerations): Plant-Specific RCIC: Plant-Specific HPCS: Plant-Specific Suppression pool make-up system: Mark-III HPCI	3.6 3.4 3.4 4.0 3.5	3.8 3.5 3.4 4.0 3.5

EPE: 295030 Low Suppression Pool Water Level

IMPORTANCE K/A NO. **ABILITY** RO **SRO** EA1.06 Condensate storage and transfer (make-up to the suppression pool): Plant-Specific..... 3.4 3.4 EA2. Ability to determine and/or interpret the following as they apply to LOW SUPPRESSION POOL WATER LEVEL: (CFR: 41.10 / 43.5 / 45.13) Suppression pool level..... 4.1* EA2.01 4.2* EA2.02 Suppression pool temperature..... 3.9 3.9 EA2.03 Reactor pressure..... 3.7 3.9 EA2.04 Drywell/ suppression chamber differential pressure: Mark-I&II..... 3.5 3.7

EPE: 295031 Reactor Low Water Level

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** EK1. Knowledge of the operational implications of the following concepts as they apply to REACTOR LOW WATER LEVEL: (CFR: 41.8 to 41.10) EK1.01 Adequate core cooling..... 4.6* 4.7* EK1.02 Natural circulation: Plant-Specific..... 3.8 4.1 3.7 EK1.03 Water level effects on reactor power..... 4.1 EK2. **Knowledge of the interrelations between REACTOR LOW WATER LEVEL and the following:** (CFR: 41.7 / 45.8) 4.4* 4.4* EK2.01 Reactor water level indication..... EK2.02 Reactor pressure..... 3.8 3.9 EK2.03 Low pressure core spray..... 4.2 4.3* EK2.04 Reactor core isolation cooling: Plant-Specific...... 4.0 4.1 EK2.05 Low pressure coolant injection (RHR)..... 4.2 4.3 EK2.06 High pressure (feedwater) coolant injection (FWCI/HPCI): Plant-Specific..... 4.1 4.2 EK2.07 High pressure core spray: Plant-Specific..... 4.0 4.1 4.2* EK2.08 Automatic depressurization system..... 4.3* EK2.09 Recirculation system: Plant-Specific..... 3.3 3.4 Redundant reactivity control: Plant-Specific....... 4.0 EK2.10 4.0 EK2.11 Reactor protection system..... 4.4* 4.4* EK2.12 Primary containment isolation system/ Nuclear steam 4.5* supply shutoff..... 4.5* EK2.13 ARI/RPT/ATWS: Plant-Specific..... 4.1 4.2 EK2.14 Emergency generators..... 3.9 4.0 EK2.15 A.C. distribution: Plant-Specific..... 3.2 3.2 Reactor water level control..... 4.1* EK2.16 4.1 EK3. **Knowledge of the reasons for the following responses** as they apply to REACTOR LOW WATER LEVEL: (CFR: 41.5 / 45.6) EK3.01 Automatic depressurization system actuation...... 3.9 4.2* 4.4* EK3.02 Core coverage..... 4.7* Spray cooling..... 4.1 4.4* EK3.03 EK3.04 Steam cooling..... 4.0 4.3*

EK3.05

Emergency depressurization.....

4.2*

4.3*

EPE: 295031 Reactor Low Water Level

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EA1.	Ability to operate and/or monitor the following as they apply to REACTOR LOW WATER LEVEL: (CFR: 41.7 / 45.6)		
EA1.01	Low pressure coolant injection (RHR): Plant-Specific.	4.4*	4.4*
EA1.02	High pressure (feedwater) coolant injection: Plant-		
	Specific	4.5*	4.5*
EA1.03	Low pressure core spray	4.4*	4.4*
EA1.04	High pressure core spray: Plant-Specific	4.3*	4.2
EA1.05	Reactor core isolation system: Plant-Specific	4.3*	4.3*
EA1.06	Automatic depressurization system	4.4*	4.4*
EA1.07	Safety/relief valves	3.7*	3.7*
EA1.08	Alternate injection systems: Plant-specific	3.8	3.9
EA1.09	Isolation condenser: Plant-Specific	3.3*	3.5*
EA1.10	Control rod drive	3.6	3.7
EA1.11	Condensate	4.1	4.1
EA1.12	Feedwater	3.9	4.1*
EA1.13	Reactor water level control	4.3*	4.3*
EA2.	Ability to determine and/or interpret the following as they apply to REACTOR LOW WATER LEVEL: (CFR: 41.10 / 43.5 / 45.13)		
EA2.01	Reactor water level	4.6*	4.6*
EA2.02	Reactor power	4.0	4.2*
EA2.03	Reactor pressure	4.2*	4.2*
EA2.04	Adequate core cooling	4.6*	4.8*

EPE: 295032 High Secondary Containment Area Temperature

K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH SECONDARY CONTAINMENT AREA TEMPERATURE:		
	(CFR: 41.8 to 41.10)		
EK1.01	Personnel protection	3.6	3.8
EK1.02	†Radiation releases	3.6	4.0
EK1.03	Secondary containment leakage detection: Plant-		
	Specific	3.5?	3.9?
EK1.04	Impact of operating environment on components	3.1	3.6
EK2.	Knowledge of the interrelations between HIGH SECONDARY CONTAINMENT AREA TEMPERATURE and the following:		
	(CFR: 41.7 / 45.8)		
EK2.01	Area/room coolers	3.5	3.6
EK2.02	Secondary containment ventilation	3.6	3.7
EK2.03	Fire protection system	3.3	3.4
EK2.04	PCIS/NSSSS	3.6	3.8
EK2.05	Temperature sensitive instrumentation	3.2	3.4
EK2.06	Area temperature monitoring system	3.3	3.4
EK2.07	Leak detection system concept: Plant-Specific	3.6	3.8
EK2.08	Systems required for safe shut-down	3.8	3.9
EK3.	Knowledge of the reasons for the following responses		
	as they apply to HIGH SECONDARY CONTAINMENT AREA TEMPERATURE:		
	(CFR: 41.5 / 45.6)		
EK3.01	Emergency/normal depressurization	3.5	3.8
EK3.02	Reactor SCRAM	3.6	3.8
EK3.03	Isolating affected systems	3.8	3.9*
	ABILITY		
EA1.	Ability to operate and/or monitor the following as		
	they apply to HIGH SECONDARY CONTAINMENT AREA		
	TEMPERATURE:		
	(CFR: 41.7 / 45.6)		
EA1.01	Area temperature monitoring system	3.6	3.7
EA1.02	Leak detection system concept: Plant-Specific	3.4	3.5
EA1.03	Secondary containment ventilation	3.7	3.7
EA1.04	Fire protection system	3.3	3.4
EA1.05	Affected systems so as to isolate damaged portions	3.7	3.9

EPE: 295032 High Secondary Containment Area Temperature

K/A NO.	ABILITY	RO	SRO
EA2.	Ability to determine and/or interpret the following as they apply to HIGH SECONDARY CONTAINMENT AREA TEMPERATURE: (CFR: 41.10 / 43.5 / 45.13)		
EA2.01 EA2.02 EA2.03	Area temperature Equipment operability Cause of high area temperature	3.8* 3.3 3.8	3.8 3.5 4.0

EPE: 295033 High Secondary Containment Area Radiation Levels

K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH SECONDARY CONTAINMENT AREA RADIATION LEVELS: (CFR: 41.8 to 41.10)		
EK1.01	Component environmental qualifications	2.4	2.8*
EK1.02	Personnel protection	3.9	4.2*
EK1.03	†Radiation releases	3.9	4.2*
EK2.	Knowledge of the interrelations between HIGH SECONDARY CONTAINMENT AREA RADIATION LEVELS and the following: (CFR: $41.7/45.8$)		
EK2.01	Area radiation monitoring system	3.8	4.0
EK2.02	Process radiation monitoring system	3.8	4.1
EK2.03	Secondary containment ventilation: Plant-Specific	3.7	3.9
EK2.04	Standby gas treatment system/FRVS	3.9	4.2
EK3.	Knowledge of the reasons for the following responses as they apply to HIGH SECONDARY CONTAINMENT AREA RADIATION LEVELS: (CFR: 41.5 / 45.6)		
EK3.01	Emergency depressurization	3.3	3.5
EK3.02	Reactor SCRAM	3.5	3.6
EK3.03	Isolating affected systems	3.8	3.9
EK3.04	Personnel evacuation	4.0	4.4*
EK3.05	Emergency plan	3.6	4.5*
ABILIT	Y		
EA1.	Ability to operate and/or monitor the following as they apply to HIGH SECONDARY CONTAINMENT AREA RADIATION LEVELS: (CFR: 41.7 / 45.6)		
EA1.01	Area radiation monitoring system	3.9	4.0
EA1.02	Process radiation monitoring system	3.7	3.8
EA1.03	Secondary containment ventilation	3.8	3.8
EA1.04	SBGT/FRVS	4.2*	4.2
EA1.05	Affected systems so as to isolate damaged portions	3.9	4.0
EA1.06	Portable radiation monitoring instruments	2.9*	3.1*
EA1.07	Personnel dosimetry	3.5	3.6
EA1.08	Control room ventilation: Plant-Specific	3.6	3.8

EPE: 295033 High Secondary Containment Area Radiation Levels

IMPORTANCE K/A NO. **ABILITY** RO **SRO** EA2. Ability to determine and/or interpret the following as they apply to HIGH SECONDARY CONTAINMENT AREA **RADIATION LEVELS:** (CFR: 41.10 / 43.5 / 45.13) EA2.01 Area radiation levels..... 3.8 3.9 EA2.02 Equipment operability..... 3.1 3.2 EA2.03 †Cause of high area radiation..... 3.7 4.2

EPE: 295034 Secondary Containment Ventilation High Radiation

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to SECONDARY CONTAINMENT VENTILATION HIGH RADIATION: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02	Personnel protection†Radiation releases	3.8 4.1	4.1 4.4*
EK2.	Knowledge of the interrelations between SECONDARY CONTAINMENT VENTILATION HIGH RADIATION and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05 EK2.06	Process radiation monitoring system	3.9 3.8 4.3* 3.9 3.5 3.9	4.2 3.9 4.5* 3.9 3.7 4.2
EK3.	Knowledge of the reasons for the following responses as they apply to SECONDARY CONTAINMENT VENTILATION HIGH RADIATION: (CFR: 41.5 / 45.6)		
EK3.01 EK3.02 EK3.03 EK3.04 EK3.05	Isolating secondary containment ventilation Starting SBGT/FRVS: Plant-Specific Personnel evacuation Fuel building ventilation: Plant-Specific Manual SCRAM and depressurization: Plant-Specific	3.8 4.1 4.0* 3.7 3.6	4.1 4.1 4.4* 3.8 3.9
ABILIT	Y		
EA1.	Ability to operate and/or monitor the following as they apply to SECONDARY CONTAINMENT VENTILATION HIGH RADIATION: (CFR: 41.7 / 45.6)		
EA1.01 EA1.02 EA1.03 EA1.04	Area radiation monitoring system Process radiation monitoring system Secondary containment ventilation SBGT/FRVS: Plant-Specific	3.8 3.9 4.0 4.1*	3.8 4.0 3.9 4.2*

EA1.05

3.8

3.8

Fuel building ventilation: Plant-Specific.....

EPE: 295034 Secondary Containment Ventilation High Radiation

IMPORTANCE K/A NO. **ABILITY** RO **SRO** EA2. Ability to determine and/or interpret the following as they apply to SECONDARY CONTAINMENT VENTILATION HIGH **RADIATION:** (CFR: 41.10 / 43.5 / 45.13) EA2.01 Ventilation radiation levels..... 3.8 4.2 Cause of high radiation levels..... 3.7 4.2* EA2.02

EPE: 295035 Secondary Containment High Differential Pressure

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02	Secondary containment integrity †Radiation release	3.9 3.7	4.2* 4.2
EK2.	Knowledge of the interrelations between SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04	Secondary containment ventilation	3.6 3.6 3.3 3.3	3.6 3.8 4.1 3.7
EK3.	Knowledge of the reasons for the following responses as they apply to SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE: (CFR: 41.5 / 45.6)		
EK3.01 EK3.02	Blow-out panel operation: Plant-Specific Secondary containment ventilation response	2.8 3.3	3.1 3.5
ABILIT	Y		
EA1.	Ability to operate and/or monitor the following as they apply to SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE: (CFR: 41.7/45.6)		
EA1.01 EA1.02	Secondary containment ventilation system SBGT/FRVS	3.6 3.8	3.6 3.8
EA2.	Ability to determine and/or interpret the following as they apply to SECONDARY CONTAINMENT HIGH DIFFERENTIAL PRESSURE: (CFR: 41.8 to 41.10)		
EA2.01 EA2.02	Secondary containment pressure: Plant-Specific †Off-site release rate: Plant-Specific	3.8 2.8*	3.9 4.1

EPE: 295036 Secondary Containment High Sump/Area Water Level

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to SECONDARY CONTAINMENT HIGH SUMP/AREA WATER LEVEL: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02	Radiation releases Electrical ground/ circuit malfunction	2.9 2.6*	3.1 2.8*
EK2.	Knowledge of the interrelations between SECONDARY CONTAINMENT HIGH SUMP/AREA WATER LEVEL and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03	Secondary containment equipment and floor drain system Post-accident sampling system: Plant-Specific Radwaste	3.1 2.6 2.8	3.2 2.9 3.1
EK3.	Knowledge of the reasons for the following responses as they apply to SECONDARY CONTAINMENT HIGH SUMP/AREA WATER LEVEL: (CFR: 41.5 / 45.6)		
EK3.01 EK3.02 EK3.03 EK3.04	Emergency depressurization	2.6 2.8 3.5 3.1	2.8 2.8 3.6 3.4
ABILITY	?		
EA1.	Ability to operate and/or monitor the following as they apply to SECONDARY CONTAINMENT HIGH SUMP/AREA WATER LEVEL: (CFR: 41.7 / 45.6)		
EA1.01	Secondary containment equipment and floor drain	2.0	2.2
EA1.02	systems Affected systems so as to isolate damaged portions	3.2 3.5	3.3 3.6
EA1.03	Radwaste	2.8	3.0
EA1.04	Radiation monitoring: Plant-Specific	3.1	3.4
EA2.	Ability to determine and/or interpret the following as they apply to SECONDARY CONTAINMENT HIGH SUMP/AREA WATER LEVEL: (CFR: 41.10 / 43.5 / 45.13)		
EA2.01	Operability of components within the affected area	3.0	3.2
EA2.02	Water level in the affected area	3.1	3.1
EA2.03	Cause of the high water level	3.4	3.8

EPE: 295037 SCRAM Condition Present and Reactor Power Above APRM Downscale or Unknown

	K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
	EK1.	Knowledge of the operational implications of the following concepts as they apply to SCRAM CONDITION PRESENT AND REACTOR POWER ABOVE APRM DOWNSCALE OR UNKNOWN: (CFR: 41.8 to 41.10)		
	EK1.01	Reactor pressure effects on reactor power	4.1*	4.3*
	EK1.02	Reactor water level effects on reactor power	4.1*	4.3*
	EK1.03	Boron effects on reactor power (SBLC)	4.2	4.4*
	EK1.04	Hot shutdown boron weight: Plant-Specific	3.4	3.6
	EK1.05	Cold shutdown boron weight: Plant-Specific	3.4	3.6
	EK1.06	Cooldown effects on reactor power	4.0*	4.2*
	EK1.07	Shutdown margin	3.4	3.8
	EK1.07	Shutdown margin	3.4	3.0
	EK2.	Knowledge of the interrelations between SCRAM CONDITION PRESENT AND REACTOR POWER ABOVE APRM DOWNSCALE OR UNKNOWN and the following: (CFR: 41.7 / 45.8)		
I	EK2.01	RPS	4.2*	4.3*
•	EK2.02	RRCS: Plant-Specific	4.0	4.2
	EK2.03	ARI/RPT/ATWS: Plant-Specific	4.1	4.2*
	EK2.04	SBLC system	4.4*	4.5*
'	EK2.05	CRD hydraulic system	4.0	4.1
	EK2.06	CRD mechanisms	3.5	3.6
Ι	EK2.07	Neutron monitoring system	4.0*	4.0
1	EK2.08	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.7	3.1
	EK2.09	Reactor water level	4.0	4.2
	EK2.10	Reactor pressure	3.8	4.1
	EK2.11	RMCS: Plant-Specific	3.8	3.9
	EK2.12	Rod control and information system: Plant-Specific	3.6	3.8
	EK2.13	Alternate boron injection methods: Plant-Specific	3.4	4.1
	EK2.14	RPIS: Plant-Specific	3.6	3.9
	LK2.14	RI 13. 1 tant-specific	3.0	3.9
	EK3.	Knowledge of the reasons for the following responses as they apply to SCRAM CONDITION PRESENT AND REACTOR POWER ABOVE APRM DOWNSCALE OR UNKNOWN: (CFR: 41.5 / 45.6)		
	EK3.01	Recirculation pump trip/runback: Plant-Specific	4.1	4.2
	EK3.02	SBLC injection	4.3*	4.5*
	EK3.03	Lowering reactor water level	4.1*	4.5*
	EK3.04	Hot shutdown boron weight: Plant-Specific	3.2	3.7
	LIX3.04	Hot shudown boron weight. Ham-specific	٥.۷	5.1

EPE: 295037 SCRAM Condition Present and Reactor Power Above APRM Downscale or Unknown

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
EK3.05 EK3.06 EK3.07	Cold shutdown boron weight: Plant-Specific Maintaining heat sinks external to the containment Various alternate methods of control rod insertion:	3.2 3.8	3.7 4.1
EK3.08	Plant-SpecificATWS circuitry: Plant-Specific	4.2 3.6*	4.3* 3.9*
ABILITY	Y .		
EA1.	Ability to operate and/or monitor the following as they apply to SCRAM CONDITION PRESENT AND REACTOR POWER ABOVE APRM DOWNSCALE OR UNKNOWN: (CFR: 41.7 / 45.6)		
EA1.01	Reactor Protection System	4.6*	4.6*
EA1.02	RRCS: Plant-Specific	3.8	4.0
EA1.03	ARI/RPT/ATWS: Plant-Specific	4.1*	4.1*
EA1.04	SBLC	4.5*	4.5*
EA1.05	CRD hydraulics systems	3.9	4.0
EA1.06	Neutron monitoring system	4.1*	4.1
EA1.07	RMCS: Plant-Specific	3.9	4.0
EA1.08	Rod control and information system: Plant-Specific	3.6	3.6
EA1.09	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8*	3.0
EA1.10	Alternate boron injection methods: Plant-Specific	3.7	3.9
EA1.11	PCIS/NSSSS	3.5	3.6
EA2.	Ability to determine and/or interpret the following as they apply to SCRAM CONDITION PRESENT AND REACTOR POWER ABOVE APRM DOWNSCALE OR UNKNOWN: (CFR: 41.10 / 43.5 / 45.13)		
EA2.01	Reactor power	4.2*	4.3*
EA2.02	Reactor water level	4.1*	4.2*
EA2.03	SBLC tank level	4.3*	4.4*
EA2.04	Suppression pool temperature	4.0*	4.1*
EA2.05	Control rod position	4.2*	4.3*
EA2.06	Reactor pressure	4.0	4.1
EA2.07	Containment conditions/isolations	4.0	4.2*

EPE: 295038 High Off-Site Release Rate

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
EK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: 41.8 to 41.10)		
EK1.01 EK1.02 EK1.03	Biological effects of radioisotope ingestion †Protection of the general public †Meteorological effects on off-site release	2.5 4.2* 2.8	3.1 4.4* 3.8
EK2.	Knowledge of the interrelations between HIGH OFF-SITE RELEASE RATE and the following: (CFR: 41.7 / 45.8)		
EK2.01 EK2.02 EK2.03 EK2.04 EK2.05 EK2.06 EK2.07 EK2.08 EK2.09 EK2.10 EK2.11	Radwaste	3.1 3.6 3.6 3.9 3.7 3.4 3.5 2.6 2.9* 3.2 3.1 3.5	3.4 3.8 3.8 4.2 4.7* 3.7 3.7 3.1 3.5* 3.4 3.8
EK3.	Knowledge of the reasons for the following responses as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: $41.5 / 45.6$)		
EK3.01 EK3.02 EK3.03 EK3.04	†Implementation of site emergency plan System isolations	3.6 3.9 3.7 3.6	4.5* 4.2 3.9 3.9
ABILITY	Z .		
EA1.	Ability to operate and/or monitor the following as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: 41.7 / 45.6)		
EA1.01 EA1.02 EA1.03 EA1.04 EA1.05 EA1.06 EA1.07	Stack-gas monitoring system: Plant-Specific †Meteorological instrumentation	3.9 3.0* 3.7 2.8 3.0* 3.5 3.6	4.2 3.8 3.9 3.2 3.5* 3.6 3.8

EPE: 295038 High Off-Site Release Rate

IMPORTANCE ABILITY K/A NO. RO **SRO** EA2. Ability to determine and/or interpret the following as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: 41.10 / 43.5 / 45.13) EA2.01 †Off-site.... 3.3* 4.3* EA2.02 †Total number of curies released..... 2.5* 3.3* 3.5* EA2.03 †Radiation levels..... 4.3* Source of off-site release......4.1* EA2.04 4.5*

EPE: 500000 High Containment Hydrogen Concentration

IMPORTANCE K/A NO. Knowledge RO **SRO** EK1. Knowledge of the operational implications of the following concepts as they apply to HIGH CONTAINMENT **HYDROGEN CONCENTRATIONS:** (CFR: 41.8 to 41.10) EK1.01 3.9 EK2. **Knowledge of the interrelations between HIGH** CONTAINMENT HYDROGEN CONCENTRATIONS the following: (CFR: 41.7 / 45.8) EK2.01 3.5 EK2.02 3.5 EK2.03 3.4 EK2.04 2.9 EK2.05 3.3 3.4 EK2.06 EK2.07 3.7 EK2.08 3.6 EK2.09 3.3 EK3. Knowledge of the reasons for the following responses as they apply to HIGH PRIMARY CONTAINMENT HYDROGEN **CONCENTRATIONS:** (CFR: 41.5 / 45.6) EK3.01 3.3 EK3.02 3.0 EK3.03 3.5 EK3.04 3.9 EK3.05 3.4 EK3.06 3.7 3.7 EK3.07 EK3.08 3.6 EA1. Ability to operate and monitor the following as they apply to HIGH CONTAINMENT HYDROGEN CONTROL: (CFR: 41.7 / 45.6) EA1.01 3.3 EA1.02 3.2 EA1.03 3.2 EA1.04 2.9 EA1.05 3.3 EA1.06 3.4 EA1.07 3.3

EPE: 500000 High Containment Hydrogen Concentration

K/A NO.	Knowledge	RO	SRO
EA2	Ability to determine and / or interpret the following as they apply to HIGH PRIMARY CONTAINMENT HYDROGEN CONCENT (CFR: 41.10 / 43.5 / 45.13)	RATION	NS:
EA2.01	Hydrogen monitoring system availability		3.5
EA2.02	Oxygen monitoring system availability	3.0	3.5
EA2.03	Combustible limits for drywell	. 3.3	3.8
EA2.04	Combustible limits for wetwell	. 3.3	3.3

This page left blank

4.2	Abnormal Plant Evolutions	page
295001	Partial or Complete Loss of Forced Core Flow Circulation	4.2-3
295002	Loss of Main Condenser Vacuum	4.2-5
295003	Partial or Complete Loss of A.C. Power	4.2-7
295004	Partial or Complete Loss of D.C. Power	4.2-9
295005	Main Turbine Trip	4.2-10
295006	SCRAM	4.2-12
295007	High Reactor Pressure	4.2-14
295008	High Reactor Water Level	4.2-16
295009	Low Reactor Water Level	4.2-18
295010	High Drywell Pressure	4.2-19
295011	High Containment Temperature (Mark III Containment Only)	4.2-21
295012	High Drywell Temperature	4.2-22
295013	High Suppression Pool Water Temperature	4.2-23
295014	Inadvertent Reactivity Addition	4.2-24
295015	Incomplete SCRAM	4.2-26
295016	Control Room Abandonment	4.2-28
295017	High Off-Site Release Rate	4.2-29
295018	Partial or Complete Loss of Component Cooling Water	4.2-31
295019	Partial or Complete Loss of Instrument Air	4.2-33
295020	Inadvertent Containment Isolation	4.2-35
295021	Loss of Shutdown Cooling	4.2 - 37
295022	Loss of Control Rod Drive Pumps	4.2-39
295023	Refueling Accidents	4.2-40
600000	Plant Fire On Site	4.2-42
700000	Generator Voltage and Electric Grid Disturbances	4.2 - 44

APE: 295001 Partial or Complete Loss of Forced Core Flow Circulation

	IMPORTANCE				
K/A NO.	KNOWLEDGE	RO	SRO		
AK1.	Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF FORCED CORE FLOW CIRCULATION: (CFR: 41.8 to 41.10)				
AK1.01	Natural circulation	3.5	3.6		
AK1.02	Power/flow distribution	3.3	3.5		
AK1.03	†Thermal limits	3.6	4.1		
AK1.04	†Limiting cycle oscillation: Plant-Specific	2.5	3.3		
AK2.	Knowledge of the interrelations between PARTIAL OR COMPLETE LOSS OF FORCED CORE FLOW CIRCULATION and the following: (CFR: 41.7 / 45.8)				
AK2.01	Recirculation system	3.6	3.7		
AK2.02	Nuclear boiler instrumentation	3.2	3.3		
AK2.03	Reactor water level	3.6	3.7		
AK2.04	Reactor/turbine pressure regulating system: Plant-				
	Specific	3.3	3.3		
AK2.05	LPCI loop select logic: Plant-Specific	3.2	3.6		
AK2.06	Reactor power	3.8	3.8		
AK2.07	Core flow indication	3.4	3.4		
AK2.08	Standby liquid control: BWR-1	2.5*	2.8		
AK3.	Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF FORCED CORE FLOW CIRCULATION: (CFR: 41.5 / 45.6)				
AK3.01	Reactor water level response	3.4	3.6		
AK3.02	Reactor power response	3.7	3.8		
AK3.03	Idle loop flow	2.8	2.9		
AK3.04	Reactor SCRAM	3.4	3.6		
AK3.05	Reduced loop operating requirements: Plant-Specific	3.2	3.6		
AK3.06	Core flow indication	2.9	3.0		
1112.00	Core now indicates in management and a second secon	2.7	2.0		
ABILI	ΓY				
AA1.	Ability to operate and/or monitor the following as they apply to PARTIAL CLOSS OF FORCED CORE FLOW CIRCULATION : $(CFR:\ 41.7/45.6)$	OR COM	PLETE		
AA1.01	Recirculation system	3.5	3.6		
AA1.02	RPS	3.3	3.3		

APE: 295001 Partial or Complete Loss of Forced Core Flow Circulation

K/A NO.	ABILITY	RO	SRO
AA1.03	RMCS: Plant-Specific	2.6	2.7
AA1.04	Rod control and information system: BWR-5&6	2.6	2.8
AA1.05	Recirculation flow control system	3.3	3.3
AA1.06	Neutron monitoring system	3.3	3.4
AA1.07	Nuclear boiler instrumentation system	3.1	3.2
AA1.08	Standby liquid control: BWR-1	2.5*	2.8
AA2.	Ability to determine and/or interpret the following as they apply to PARTIAL OR COMPLETE LOSS OF FORCED CORE FLOW CIRCULATION: (CFR: 41.10 / 43.5 / 45.13)		
AA2.01	Power/flow map	3.5	3.8
AA2.02	Neutron monitoring	3.1	3.2
AA2.03	Actual core flow	3.3	3.3
AA2.04	Individual jet pump flows: Not-BWR-1&2	3.0	3.1
AA2.05	Jet pump operability: Not-BWR-1&2	3.1	3.4
AA2.06	Nuclear boiler instrumentation	3.2	3.3

APE: 295002 Loss of Main Condenser Vacuum

IMPORTANCE			
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to LOSS OF MAIN CONDENSER VACUUM: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03 AK1.04	Plant efficiency Turbine efficiency Loss of heat sink Increased offgas flow	2.1* 2.2* 3.6 3.0	2.5 2.5 3.8 3.3
AK2.	Knowledge of the interrelations between LOSS OF MAIN CONDENSER VACUUM and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07 AK2.08 AK2.09 AK2.10 AK2.11	RPS	3.5 3.1 3.5 3.2 2.7 2.6 3.1 3.1 2.4 2.4* 2.6	3.5 3.2 3.6 3.3 2.7 2.7 3.1 3.2 2.4 2.5 2.7
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05 AK3.06 AK3.07 AK3.08 AK3.09	Reactor SCRAM: Plant-Specific Turbine trip	3.7 3.4 3.3 3.4 2.9 2.4 2.8 3.2	3.8 3.4 3.3 3.6 3.4 2.9 2.5 2.9 3.2

APE: 295002 Loss of Main Condenser Vacuum

IMPORTANCE

K/A NO. KNOWLEDGE RO **SRO ABILITY** AA1. Ability to operate and/or monitor the following as they apply to LOSS OF MAIN CONDENSER VACUUM: (CFR: 41.7 / 45.6) AA1.01 Condensate system 2.6 2.6 AA1.02 Offgas system 2.9 2.9 AA1.03 RPS. 3.4 3.5 AA1.04 PCIS/NSSSS 3.3 3.4 AA1.05 Main turbine 3.2 3.2 Reactor/turbine pressure regulating system 3.1 AA1.06 3.0 Condenser circulating water system 2.9 AA1.07 3.1 AA1.08 Recirculating flow control system 2.6 2.7 AA1.09 Reactor manual control/rod control and information 2.4 2.4 system..... AA1.10 Feedwater system: Plant-Specific 2.7 2.7 AA2. Ability to determine and/or interpret the following as they apply to LOSS OF MAIN CONDENSER VACUUM: (CFR: 41.10 / 43.5 / 45.13) AA2.01 2.9 3.1 Condenser vacuum/absolute pressure..... AA2.02 Reactor power: Plant-Specific..... 3.2 3.3 AA2.03 Generator output..... 2.3 2.4 AA2.04 2.8 2.9 Offgas system flow.....

APE: 295003 Partial or Complete Loss of A.C. Power

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF A.C. POWER: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03	Effect of battery discharge rate on capacity Load shedding Under voltage/degraded voltage effects on electrical loads	2.7 3.1 2.9	2.9 3.4 3.2
AK1.04 AK1.05 AK1.06	Electrical bus divisional separation Failsafe component design Station blackout: Plant-Specific	3.1 2.6 3.8	3.2 2.7 4.0*
AK2.	Knowledge of the interrelations between PARTIAL OR COMPLETE LOSS OF A.C. POWER and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06	Station batteries	3.2 4.1* 3.7 3.4 3.8* 3.4	3.3 4.2* 3.9 3.5 4.0 3.5
AK3.	Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF A.C. POWER: (CFR: 41.5 / 45.6)		
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05 AK3.06 AK3.07	Manual and auto bus transfer	3.3 2.9 3.5 3.0 3.7 3.7 3.8*	3.5 3.1 3.6 3.2 3.7 3.7 4.0*
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to PARTIAL OR COMPLETE LOSS OF A.C. POWER : (CFR: $41.7/45.6$)		
AA1.01 AA1.02 AA1.03	A.C. electrical distribution system Emergency generators Systems necessary to assure safe plant shutdown	3.7 4.2* 4.4*	3.8 4.3* 4.4*

APE: 295003 Partial or Complete Loss of A.C. Power

IMPORTANCE K/A NO. **ABILITY** RO **SRO** AA1.04 D.C. electrical distribution system..... 3.6 3.7 AA2. Ability to determine and/or interpret the following as they apply to PARTIAL OR COMPLETE LOSS OF A.C. POWER: (CFR: 41.10 / 43.5 / 45.13) 3.4 AA2.01 Cause of partial or complete loss of A.C. power...... 3.7 Reactor power / pressure / and level..... 4.2* 4.3* AA2.02 3.2 AA2.03 Battery status: Plant-Specific..... 3.5 AA2.04 System lineups..... 3.5 3.7 Whether a partial or complete loss of A.C. power has AA2.05 3.9* occurred..... 4.2*

APE: 295004 Partial or Complete Loss of D.C. Power

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF D.C. POWER: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03 AK1.04 AK1.05 AK1.06	†Automatic load shedding: Plant-Specific	2.9 3.2 2.9 2.8 3.3	3.2 3.4 2.9 2.9 3.4 3.6
AK2.	Knowledge of the interrelations between PARTIAL OR COMPLETE LOSS OF D.C. POWER and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03	Battery charger Batteries D.C. bus loads	3.1 3.0 3.3	3.1 3.1 3.3
AK3.	Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF D.C. POWER: (CFR: 41.5 / 45.6)		
AK3.01 AK3.02 AK3.03	†Load shedding: Plant-Specific	2.6 2.9 3.1	3.1 3.3 3.5
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to PARTIAL OR COMPLETE LOSS OF D.C. POWER: (CFR: 41.7 / 45.6)		
AA1.01 AA1.02 AA1.03	D.C. electrical distribution systems Systems necessary to assure safe plant shutdown A.C. electrical distribution	3.3 3.8 3.4	3.4 4.1 3.6
AA2.	Ability to determine and/or interpret the following as they apply to PARTIAL OR COMPLETE LOSS OF D.C. POWER : (CFR: $41.10/43.5/45.13$)		
AA2.01 AA2.02 AA2.03 AA2.04	Cause of partial or complete loss of D.C. power Extent of partial or complete loss of D.C. power Battery voltage System lineups	3.2 3.5 2.8 3.2	3.6 3.9 2.9 3.3

APE: 295005 Main Turbine Generator Trip

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to MAIN TURBINE GENERATOR TRIP: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03	Pressure effects on reactor power †Core thermal limit considerations Pressure effects on reactor level	4.0 3.2 3.5	4.1 3.6 3.7
AK2.	Knowledge of the interrelations between MAIN TURBINE GENERATOR TRIP and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07 AK2.08 AK2.09	RPS Feedwater temperature Recirculation system Main generator protection Extraction steam system Seal steam evaporator: Plant-Specific Reactor pressure control A.C. electrical distribution Feedwater - HPCI: BWR-2	3.8 2.9 3.2 3.3 2.6 1.9* 3.6 3.2 4.0	3.9 3.0 3.3 3.3 2.7 1.9* 3.7 3.3 4.3
AK3.	Knowledge of the reasons for the following responses as they apply to MAIN TURBINE GENERATOR TRIP: (CFR: 41.5 / 45.6)		0
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05 AK3.06 AK3.07 AK3.08	Reactor SCRAM	3.8 3.4 2.8 3.2 2.5 3.3 3.8 4.0	3.8 3.5 3.0 3.2 2.6 3.3 3.8 4.3
ABILIT	Y		
AA1.	Ability to operate and/or monitor the following as they apply to MAIN TURBINE GENERATOR TRIP : (CFR: 41.7 / 45.6)		
AA1.01 AA1.02 AA1.03	Recirculation system: Plant-Specific RPS Reactor manual control/Rod control and information	3.1 3.6	3.3 3.6
AA1.04	System Main generator controls	2.7 2.7	2.8 2.8

APE: 295005 Main Turbine Generator Trip

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** AA1.05 Reactor/turbine pressure regulating system..... 3.6 3.6 AA1.06 Condenser vacuum breaker..... 2.4 2.6 AA1.07 A.C. electrical distribution..... 3.3 3.3 AA2. Ability to determine and/or interpret the following as they apply to MAIN TURBINE GENERATOR TRIP: (CFR: 41.10 / 43.5 / 45.13) AA2.01 Turbine speed..... 2.6 2.7 AA2.02 Turbine vibration..... 2.4 2.7 AA2.03 Turbine valve position..... 3.1 3.1 3.7 AA2.04 Reactor pressure..... 3.8 AA2.05 Reactor power..... 3.8 3.9 AA2.06 Feedwater temperature..... 2.6 2.7 Reactor water level..... AA2.07 3.5 3.6 Electrical distribution status..... AA2.08 3.2 3.3

APE: 295006 SCRAM

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to SCRAM: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03	Decay heat generation and removal Shutdown margin Reactivity control	3.7 3.4 3.7	3.9 3.7 4.0
AK2.	Knowledge of the interrelations between SCRAM and the following: $(CFR:\ 41.7\ /\ 45.8)$		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07	RPS	4.3* 3.8 3.7 3.6 3.1 4.2* 4.0	4.4* 3.8 3.8 3.7 3.3 4.3* 4.1
AK3.	Knowledge of the reasons for the following responses as they apply to SCRAM : $(CFR:\ 41.5/\ 45.6)$		
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05 AK3.06	Reactor water level response	3.8 4.1* 3.8 3.1 3.8 3.2	3.9 4.2* 3.9* 3.3 4.0 3.3
ABILIT	Y		
AA1.	Ability to operate and/or monitor the following as they apply to SCRAM: (CFR: 41.7 / 45.6)		
AA1.01 AA1.02 AA1.03 AA1.04 AA1.05 AA1.06 AA1.07	RPS Reactor water level control system Reactor/turbine pressure regulating system Recirculation system Neutron monitoring system CRD hydraulic system Control rod position	4.2* 3.9 3.7 3.1 4.2* 3.5 4.1	4.2* 3.8 3.7 3.2 4.2* 3.6 4.1

APE: 295006 SCRAM

IMPORTANCE

K/A NO.	ABILITY	RO	SRO
AA2. Ability to determine and/or interpret the following as they apply to SCRAM: (CFR: 41.10 / 43.5 / 45.13)			
AA2.01	Reactor power	4.5*	4.6*
AA2.02	Control rod position	4.3*	4.4*
AA2.03	Reactor water level	4.0	4.2*
AA2.04	Reactor pressure	4.1	4.1*
AA2.05	Whether a reactor SCRAM has occurred	4.6*	4.6*
AA2.06	Cause of reactor SCRAM	3.5	3.8

APE: 295007 High Reactor Pressure

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH REACTOR PRESSURE: (CFR: 41.8 to 41.10)		
AK1.01	Pump shutoff head	2.9	3.2
AK1.02	Decay heat generation	3.1	3.4
AK1.03	Pressure effects on reactor power	3.8	3.9
AK1.04	Turbine load	2.7	2.8
AK2.	Knowledge of the interrelations between HIGH REACTOR PRESSURE and the following: (CFR: 41.7 / 45.8)		
AK2.01	Reactor/turbine pressure regulating system	3.5	3.7
AK2.02	Reactor power	3.8	3.8
AK2.03	RHR/LPCI: Plant-Specific	3.1	3.2
AK2.04	LPCS	3.2	3.3
AK2.05	Shutdown cooling: Plant-Specific	2.9	3.1
AK2.06	PCIS/NSSSS: Plant-Specific	3.5	3.7
AK3.	Knowledge of the reasons for the following responses as they apply to HIGH REACTOR PRESSURE : (CFR: $41.5/45.6$)		
AK3.01	Isolation condenser operation: Plant-Specific	4.0	4.2
AK3.02	HPCI operation: Plant-Specific	3.7	3.8*
AK3.03	RCIC operation: Plant-Specific	3.4	3.5
AK3.04	Safety/relief valve operation: Plant-Specific	4.0	4.1*
AK3.05	Low pressure system isolation	3.0	3.2
AK3.06	Reactor/turbine pressure regulating system operation	3.7	3.8
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to HIGH REACTOR PRESSURE: (CFR: 41.7 / 45.6)		
AA1.01	Isolation condenser: Plant-Specific	4.0	4.2
AA1.02	HPCI: Plant-Specific	3.5	3.7*
AA1.03	RCIC: Plant-Specific	3.4	3.5
AA1.04	Safety/relief valve operation: Plant-Specific	3.9	4.1*
AA1.05	Reactor/turbine pressure regulating system	3.7	3.8

APE: 295007 High Reactor Pressure

IMPORTANCE K/A NO. RO **KNOWLEDGE SRO** AA2. Ability to determine and/or interpret the following as they apply to HIGH REACTOR PRESSURE: (CFR: 41.10 / 43.5 / 45.13) AA2.01 Reactor pressure..... 4.1* 4.1* AA2.02 Reactor power..... 4.1* 4.1* AA2.03 Reactor water level..... 3.7 3.7

APE: 295008 High Reactor Water Level

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH REACTOR WATER LEVEL: (CFR: 41.8 to 41.10)		
AK1.01	Moisture carryover	3.0	3.2
AK1.02 AK1.03	Component erosion/damage Feed flow/steam flow mismatch	2.8 3.2	2.8 3.2
AK1.03 AK1.04	Containment integrity: Alis-Chalmers	4.0	4.3*
AK1.04	Containment integrity. Ans-chaimers	4.0	4.5
AK2.	Knowledge of the interrelations between HIGH REACTOR WATER LEVEL and the following: (CFR: 41.7 / 45.8)		
AK2.01	RPS: Plant-Specific	3.7	3.8
AK2.02	Reactor feedwater system	3.6	3.8
AK2.03	Reactor water level control	3.6	3.7
AK2.04	PCIS/NSSS: Plant-Specific	3.1	3.3
AK2.05	HPCI: Plant-Specific	3.8	3.9
AK2.06	RCIC: Plant-Specific	3.4	3.6
AK2.07	HPCS: Plant-Specific	2.9	3.0
AK2.08	Main turbine: Plant-Specific	3.4	3.5
AK2.09	Reactor water cleanup system (ability to drain):		
	Plant-Specific	3.1	3.1
AK2.10	RHR (ability to drain): Plant-Specific	2.7	2.8
AK2.11	Main steam	3.1	3.3
AK3.	Knowledge of the reasons for the following responses as they apply to HIGH REACTOR WATER LEVEL: (CFR: 41.5 / 45.6)		
AK3.01	Main turbine trip	3.4	3.5
AK3.02	Reactor SCRAM: Plant-Specific	3.6*	3.9*
AK3.03	PCIS/NSSSS initiation: Plant-Specific	2.9	3.1
AK3.04	Reactor feed pump trip: Plant-Specific	3.3	3.5
AK3.05	HPCI turbine trip: Plant-Specific	3.5	3.6
AK3.06	RCIC turbine trip: Plant-Specific	3.4	3.5
AK3.07	HPCS isolation: Plant-Specific	3.2	3.3
AK3.08	RCIC steam supply valve closure: Plant-Specific	3.4	3.5
AK3.09	HPCS injection valve closure: Plant-Specific	3.3	3.4
	-		

IMPORTANCE

K/A NO.	ABILITY	RO	SRO
AA1.	Ability to operate and/or monitor the following as they apply to HIGH REACTOR WATER LEVEL: (CFR: 41.7 / 45.6)		
AA1.01	Reactor water level control: Plant-Specific	3.7	3.7
AA1.02	Reactor water cleanup (ability to drain): Plant-		
	Specific	3.3	3.3
AA1.03	Main steam system: Plant-Specific	3.1	3.1
AA1.04	HPCI: Plant-Specific	3.5	3.5
AA1.05	RCIC: Plant-Specific	3.3	3.3
AA1.06	HPCS: Plant-Specific	2.8	2.8
AA1.07	Main turbine: Plant-Specific	3.4	3.4
AA1.08	Feedwater system	3.5	3.5
AA1.09	Ability to drain: Plant-Specific	3.3	3.3
AA2.	Ability to determine and/or interpret the following as they apply to HIGH REACTOR WATER LEVEL: (CFR: 41.10 / 43.5 / 45.13)		
AA2.01	Reactor water level	3.9	3.9
AA2.02	Steam flow/feedflow mismatch	3.4	3.4
AA2.03	Reactor water cleanup blowdown flow	2.9	3.0
AA2.04	Heatup rate: Plant-Specific	3.1	3.3
AA2.05	Swell	2.9	3.1

APE: 295009 Low Reactor Water Level

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to LOW REACTOR WATER LEVEL: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02	Steam carryunder Recirculation pump net positive suction head: Plant-	2.7	2.9
	Specific	3.0	3.1
AK1.03	Jet pump net positive suction head: Not-BWR-1&2	2.7	2.7
AK1.04	Jet pump efficiency: Not-BWR-1&2	2.4	2.4
AK1.05	Natural circulation	3.3	3.4
AK2.	Knowledge of the interrelations between LOW REACTOR WATER LEVEL and the following: (CFR: 41.7 / 45.8)		
AK2.01	Reactor water level indication	3.9	4.0
AK2.02	Reactor water level control	3.9	3.9
AK2.03	Recirculation system	3.1	3.2
AK2.04	Reactor water cleanup	2.6	2.6
AK3.	Knowledge of the reasons for the following responses as they apply to LOW REACTOR WATER LEVEL : (CFR: $41.5 / 45.6$)		
AK3.01	Recirculation pump run back: Plant-Specific	3.2	3.3
AK3.02	Reactor feedpump runout flow control: Plant-Specific.	2.7	2.8
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to LOW REACTOR WATER LEVEL: (CFR: 41.7 / 45.6)		
AA1.01	Reactor feedwater	3.9	3.9
AA1.02	Reactor water level control	4.0	4.0
AA1.03	Recirculation system: Plant-Specific	3.0	3.1
AA1.04	Reactor water cleanup	2.7	2.7
AA2.	Ability to determine and/or interpret the following as they apply to LOW REACTOR WATER LEVEL: (CFR: 41.10 / 43.5 / 45.13)		
AA2.01	Reactor water level	4.2	4.2
AA2.02	Steam flow/feed flow mismatch	3.6	3.7
AA2.03	Reactor water cleanup blowdown rate	2.9	2.9
	1		

APE: 295010 High Drywell Pressure

IMPORTANCE				
K/A NO.	KNOWLEDGE	RO	SRO	
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH DRYWELL PRESSURE: (CFR: 41.8 to 41.10)			
AK1.01 AK1.02 AK1.03	Downcomer submergence: Mark-I&II Submergence vent control: Mark-III Temperature increases	3.0 2.8 3.2	3.4 3.1* 3.4	
AK2.	Knowledge of the interrelations between HIGH DRYWELL PRESSURE and the following: (CFR: 41.7 / 45.8)			
AK2.01 AK2.02	Suppression pool level Drywell/suppression chamber differential pressure:	3.2	3.3	
AK2.03 AK2.04 AK2.05	Mark-I&II Drywell/containment differential pressure: Mark-III Nitrogen makeup system: Plant-Specific Drywell cooling and ventilation	3.3 3.0 2.6 3.7	3.5 3.1 2.8 3.8	
AK3.	Knowledge of the reasons for the following responses as they apply to HIGH DRYWELL PRESSURE : $(CFR:\ 41.5\ /\ 45.6)$			
AK3.01	Drywell venting	3.8	4.0*	
AK3.02	Increased drywell cooling	3.4	3.4	
AK3.03	Radiation level monitoring	3.2	3.5	
AK3.04	Leak investigation	3.5	3.8	
AK3.05	Temperature monitoring	3.5	3.4	
AK3.06	Termination of drywell inerting: Plant-Specific	2.4*	2.8	
ABILIT	\mathbf{Y}			
AA1.	Ability to operate and/or monitor the following as they apply to HIGH DRYWELL PRESSURE: (CFR: 41.7 / 45.6)			
AA1.01	Drywell ventilation/cooling	3.4	3.5	
AA1.02	Drywell floor and equipment drain sumps	3.6	3.6	
AA1.03	Nitrogen makeup: Plant-Specific	2.6	2.6	
AA1.04	Drywell sampling system	3.1	3.0	
AA1.05	Drywell/suppression vent and purge	3.1	3.4	
AA1.06	Leakage detection systems	3.3	3.5	
AA1.07	Containment (drywell) atmosphere control	3.2	3.4	
	(a.ja.) wandapara controllinininin	3.2	٠	

APE: 295010 High Drywell Pressure

IM	D(NDT	$\Gamma \Lambda$	N	TF.

K/A NO.	ABILITY	RO	SRO
AA2.	Ability to determine and/or interpret the following as they apply to HIGH DRYWELL PRESSURE : (CFR: $41.10/43.5/45.13$)		
AA2.01	†Leak rates	3.4	3.8
AA2.02	Drywell pressure	3.8	3.9
AA2.03	Drywell radiation levels	3.3	3.6
AA2.04	Drywell humidity: Plant-Specific	2.8	3.0
AA2.05	Drywell air cooler drain flow: BWR-6	3.3	3.3
AA2.06	Drywell temperature	3.6	3.6

IMPORTANCE K/A NO. RO **SRO KNOWLEDGE** AK1. Knowledge of the operational implications of the following concepts as they apply to HIGH CONTAINMENT TEMPERATURE (MARK III CONTAINMENT ONLY): (CFR: 41.8 to 41.10) AK1.01 Containment pressure: Mark-III..... 4.0* 4.1* AK2. **Knowledge of the interrelations between HIGH** CONTAINMENT TEMPERATURE (MARK III CONTAINMENT ONLY) and the following: (CFR: 41.7 / 45.8) AK2.01 Containment ventilation/cooling: Mark-III..... 3.7 4.0 AK3. Knowledge of the reasons for the following responses as they apply to HIGH CONTAINMENT TEMPERATURE (MARK **III CONTAINMENT ONLY):** (CFR: 41.5 / 45.6) AK3.01 Increased containment cooling: Mark-III..... 3.6 3.9 **ABILITY** Ability to operate and/or monitor the following as AA1. they apply to HIGH CONTAINMENT TEMPERATURE (MARK III **CONTAINMENT ONLY):** (CFR: 41.7 / 45.6) AA1.01 Containment ventilation/cooling system: Mark-III..... 3.6 3.9 AA2. Ability to determine and/or interpret the following as they apply to HIGH CONTAINMENT TEMPERATURE (MARK III **CONTAINMENT ONLY):** (CFR: 41.10 / 43.5 / 45.13) AA2.01 3.6 3.9 Containment temperature: Mark-III..... AA2.02 Containment pressure: Mark-III..... 4.0* 4.1* Containment humidity: Mark-III..... AA2.03 2.8 3.2

APE: 295012 High Drywell Temperature

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH DRYWELL TEMPERATURE: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02	Pressure/temperature relationship Reactor power level control	3.3 3.1	3.5 3.2
AK2.	Knowledge of the interrelations between HIGH DRYWELL TEMPERATURE and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02	Drywell ventilation Drywell cooling	3.4 3.6	3.5 3.7
AK3.	Knowledge of the reasons for the following responses as they apply to HIGH DRYWELL TEMPERATURE : $(CFR:\ 41.5\ /\ 45.6)$		
AK3.01	Increased drywell cooling	3.5	3.6
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to HIGH DRYWELL TEMPERATURE: (CFR: 41.7 / 45.6)		
AA1.01 AA1.02	Drywell ventilation system Drywell cooling system	3.5 3.8	3.6 3.8
AA2.	Ability to determine and/or interpret the following as they apply to HIGH DRYWELL TEMPERATURE : (CFR: $41.10 / 43.5 / 45.13$)		
AA2.01 AA2.02 AA2.03	Drywell temperature Drywell pressure Drywell humidity: Plant-Specific	3.8 3.9 2.8	3.9 4.1 3.1

APE: 295013 High Suppression Pool Temperature

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH SUPPRESSION POOL TEMPERATURE: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03 AK1.04	Pool stratification	2.5 2.4 3.0 2.9	2.6 2.5 3.3 3.2
AK2.	Knowledge of the interrelations between HIGH SUPPRESSION POOL TEMPERATURE and the following: (CFR: 41.7 / 45.8)		
AK2.01	Suppression pool cooling	3.6	3.7
AK3.	Knowledge of the reasons for the following responses as they apply to HIGH SUPPRESSION POOL TEMPERATURE : (CFR: $41.5/45.6$)		
AK3.01 AK3.02	Suppression pool cooling operation Limiting heat additions	3.6 3.6	3.8 3.8
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to HIGH SUPPRESSION POOL TEMPERATURE : (CFR: $41.7/45.6$)		
AA1.01	Suppression pool cooling	3.9	3.9
AA1.02	Systems that add heat to the suppression pool	3.9	3.9
AA2.	Ability to determine and/or interpret the following as they apply to HIGH SUPPRESSION POOL TEMPERATURE : (CFR: $41.10/43.5/45.13$)		
AA2.01	Suppression pool temperature	3.8	4.0
AA2.02	Localized heating/stratification	3.2	3.5

APE: 295014 Inadvertent Reactivity Addition

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to INADVERTENT REACTIVITY ADDITION: (CFR: 41.8 to 41.10)		
AK1.01	Prompt critical	3.7	3.8
AK1.02	Reactivity anomaly	3.3	3.7
AK1.03	Shutdown margin	3.7	4.0
AK1.04	PCIOMR: Plant-Specific	3.0	3.4
AK1.05 AK1.06	†Fuel thermal limitsAbnormal reactivity additions	3.7 3.8	4.2* 3.9
AK2.	Knowledge of the interrelations between INADVERTENT REACTIVITY ADDITION and the following: (CFR: 41.7 / 45.8)		
AK2.01	RPS	3.9	4.1
AK2.02	†Fuel thermal limits	3.7	4.2*
AK2.03	Fuel temperature	3.3	3.4
AK2.04	Void concentration	3.2	3.3
AK2.05	Neutron monitoring system	4.0	4.1*
AK2.06	Moderator temperature	3.4	3.5
AK2.07	Reactor power	3.9	3.9
AK2.08	RMCS: Plant-Specific	3.4	3.5
AK2.09	Rod control and information system: Plant-Specific	3.4	3.6
AK2.10	Safety limits	4.1	4.5*
AK2.11	Recirculation flow control	3.6	3.7
AK3.	Knowledge of the reasons for the following responses as they apply to INADVERTENT REACTIVITY ADDITION: (CFR: $41.5 / 45.6$)		
AK3.01	Reactor SCRAM	4.1*	4.1
AK3.02	Control rod blocks	3.7	3.7
ABILIT	Y		
AA1.	Ability to operate and/or monitor the following as they apply to INADVERTENT REACTIVITY ADDITION: (CFR: 41.7 / 45.6)		
AA1.01	RPS	4.0	4.1*
AA1.02	Recirculation flow control system	3.6	3.8
AA1.03	RMCS: Plant-Specific	3.5	3.5
AA1.04	Rod control and information system: Plant-Specific	3.2	3.3
AA1.05	Neutron monitoring system	3.9	3.9
AA1.06	Reactor/turbine pressure regulating system	3.3	3.4

APE: 295014 Inadvertent Reactivity Addition

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AA1.07	Cold water injection	4.0	4.1
AA2.	Ability to determine and/or interpret the following as they apply to INADVERTENT REACTIVITY ADDITION : (CFR: $41.10/43.5/45.13$)		
AA2.01	Reactor power	4.1*	4.2*
AA2.02	Reactor period	3.9	3.9
AA2.03	Cause of reactivity addition	4.0	4.3*
AA2.04	†Violation of fuel thermal limits	4.1	4.4*
AA2.05	†Violation of safety limits	4.2*	4.6*

APE: 295015 Incomplete SCRAM

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to INCOMPLETE SCRAM: (CFR: 41.8 to 41.10)		
AK1.01	Shutdown margin	3.6*	3.9*
AK1.02	Cooldown effects on reactor power	3.9	4.1
AK1.03	Reactivity effects	3.8	3.9
AK1.04	Reactor pressure: Plant-Specific	3.8	3.8
AK2.	Knowledge of the interrelations between INCOMPLETE SCRAM and the following: (CFR: 41.7 / 45.8)		
AK2.01	CRD hydraulics	3.8	3.9
AK2.02	RMCS: Plant-Specific	3.6	3.7
AK2.03	Rod control and information system: Plant-Specific	3.2	3.6
AK2.04	RPS	4.0	4.1
AK2.05	Rod worth minimizer: Plant-Specific	2.6	2.8
AK2.06	RSCS: Plant-Specific	2.6	2.8
AK2.07	CRD mechanism	3.3	3.4
AK2.08	Neutron monitoring system	3.6	3.7
AK2.09	RPIS	3.5	3.6
AK2.10	SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.8	3.0
AK2.11	Instrument air	3.5	3.7
AK3.	Knowledge of the reasons for the following responses as they apply to INCOMPLETE SCRAM : $(CFR:\ 41.5/45.6)$		
AK3.01	Bypassing rod insertion blocks	3.4	3.7
ABILI	TY		
AA1.	Ability to operate and/or monitor the following as they apply to INCOMPLETE SCRAM: (CFR: 41.7 / 45.6)		
AA1.01	CRD hydraulics	3.8	3.9
AA1.02	RPS	4.0	4.2*
AA1.03	RMCS: Plant-Specific	3.6	3.8
AA1.04	Rod control and information system: Plant-Specific	3.4	3.7
4 4 1 07	D. I. d DI G	0.5*	2.0*

AA1.05

AA1.06

2.5*

2.7

2.8*

2.9

Rod worth minimizer: Plant-Specific.....

RSCS: Plant-Specific....

APE: 295015 Incomplete SCRAM

IMPORTANCE K/A NO. **ABILITY** RO **SRO** AA1.07 Neutron monitoring system..... 3.6 3.7 Process computer/SPDS/ERIS/CRIDS/GDS: Plant-Specific. AA1.08 2.7 2.9 AA2. Ability to determine and/or interpret the following as they apply to INCOMPLETE SCRAM: (CFR: 41.10 / 43.5 / 45.13) AA2.01 4.1* Reactor power..... 4.3* AA2.02 Control rod position..... 4.1* 4.2*

APE: 295016 Control Room Abandonment

		IMPORTANCE		
K/A NO.	KNOWLEDGE	IVII OKIMICE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to CONTROL ROOM ABANDONMENT: (CFR: 41.8 to 41.10)			
	None			
AK2.	Knowledge of the interrelations between CONTROL RC ABANDONMENT and the following: (CFR: 41.7 / 45.8)	OOM		
AK2.01	Remote shutdown panel: Plant-Specific		4.4*	4.5*
AK2.02	Local control stations: Plant-Specific		4.0*	4.1*
AK2.03	Control room HVAC		2.9*	3.1*
1112.00			,	0.1
AK3.	Knowledge of the reasons for the following responses as they apply to CONTROL ROOM ABANDONMENT : $(CFR:\ 41.5/\ 45.6)$			
AK3.01	Reactor SCRAM		4.1*	4.2*
AK3.02	Turbine trip		3.7*	3.8*
AK3.03	Disabling control room controls		3.5	3.7*
ABILIT				
AA1.	Ability to operate and/or monitor the following as			
	they apply to CONTROL ROOM ABANDONMENT:			
	(CFR: 41.7 / 45.6)			
AA1.01	RPS		3.8	3.9
AA1.02	Reactor/turbine pressure regulating system		2.9*	3.1*
AA1.03	RPIS		3.0*	3.1
AA1.04	A.C. electrical distribution		3.1	3.2
AA1.05	D.C. electrical distribution		2.8	2.9
AA1.06	Reactor water level		4.0	4.1
AA1.07	Control room/local control transfer mechanisms		4.2*	4.3*
AA1.08	Reactor pressure		4.0	4.0
AA1.09	Isolation/emergency condenser(s): Plant-Specific		4.0	4.0
AA2.	Ability to determine and/or interpret the following as they apply to CONTROL ROOM ABANDONMENT: (CFR: 41.10 / 43.5 / 45.13)			
	(22.23 11.10 / 10.10 / 10.10 /			
AA2.01	Reactor power		4.1*	4.1*
AA2.02	Reactor water level		4.2*	4.3*
AA2.03	Reactor pressure		4.3*	4.4*
AA2.04	Suppression pool temperature		3.9	4.1
AA2.05	Drywell pressure		3.8	3.9
AA2.06	Cooldown rate		3.3	3.5
AA2.07	Suppression chamber pressure		3.2	3.4

APE: 295017 High Off-Site Release Rate

	IMPO	ORTANCE	
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02 AK1.03	Biological effects of radioisotope ingestion †Protection of the general public †Meteorological effects on off-site release	2.2* 3.8* 2.7	2.5 4.3* 3.4
AK2.	Knowledge of the interrelations between HIGH OFF-SITE RELEASE RATE and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07 AK2.08 AK2.10 AK2.11 AK2.12 AK2.13 AK2.14	Fission product production versus reactor power Radwaste	2.8 2.8 3.3 3.1 3.4 3.4 3.2 2.8 2.8 3.3 3.1 3.4 4.0	3.3 3.1 3.5 3.3 3.5 4.6* 3.4 3.3 2.9 3.6 3.2 3.7 4.1
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05	(CFR: 41.5 / 45.6) System isolations	3.6 3.3 3.3 3.6 3.3	3.9 3.5 4.5* 3.8 3.6
ABILIT	Y		
AA1.	Ability to operate and/or monitor the following as they apply to HIGH OFF-SITE RELEASE RATE: (CFR: 41.7 / 45.6)		
AA1.01 AA1.02 AA1.03 AA1.04 AA1.05	Radwaste Off-gas system Plant ventilation systems Stack-gas monitoring system: Plant-Specific SPDS/ERIS/CRIDS/GDS: Plant-Specific	2.7* 3.5 3.4 3.6 2.7	3.1 3.7 3.4 3.8 3.2

APE: 295017 High Off-Site Release Rate

IMPORTANCE

K/A NO.	ABILITY	RO	SRO
AA1.06	Condenser air removal system: Plant-Specific	3.2	3.2
AA1.07	Process radiation monitoring system	3.4	3.6
AA1.08	MSIV leakage control: Plant-Specific	3.1	3.4
AA1.09	Standby gas treatment/FRVS	3.6	3.8
AA1.10	RPS	3.6	3.7
AA1.11	PCIS/NSSSS	3.9	4.1
AA1.12	†Meteorological data	2.5*	3.9
AA2.	Ability to determine and/or interpret the following as they apply to HIGH OFF-SITE RELEASE RATE : $(CFR:\ 41.10/43.5/45.13)$		
AA2.01	†Off-site release rate: Plant-Specific	2.9*	4.2*
AA2.02	†Total number of curies released: Plant-Specific	2.4*	3.5*
AA2.03	†Radiation levels: Plant-Specific	3.1	3.9
AA2.04	†Source of off-site release	3.6	4.3*
AA2.05	†Meteorological data	2.5	3.8

APE: 295018 Partial or Complete Loss of Component Cooling Water

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
WATO.	KIOWEEDGE	RO	SKO
AK1.	Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF COMPONENT COOLING WATER: (CFR: 41.8 to 41.10)		
AK1.01	Effects on component/system operations	3.5	3.6
AK2.	Knowledge of the interrelations between PARTIAL OR COMPLETE LOSS OF COMPONENT COOLING WATER and the following: (CFR: 41.7 / 45.8)		
AK2.01	System loads	3.3	3.4
AK2.02	Plant operations	3.4	3.6
71112.02	Than operations	3.1	5.0
AK3.	Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF COMPONENT COOLING WATER: (CFR: 41.5 / 45.6)		
AK3.01	Isolation of non-essential heat loads: Plant-Specific	2.9	3.2
AK3.02	Reactor power reduction	3.3	3.4
AK3.03	Securing individual components (prevent equipment	0.0	
	damage)	3.1	3.3
AK3.04	Starting standby pump	3.3	3.3
AK3.05	Placing standby heat exchanger in service	3.2	3.3
AK3.06	Increasing cooling water flow to heat exchangers	3.3	3.3
AK3.07	Cross-connecting with backup systems	3.1	3.2
ABILIT	Y		
AA1.	Ability to operate and/or monitor the following as they apply to PARTIAL OR COMPLETE LOSS OF COMPONENT COOLING WATER: (CFR: 41.7 / 45.6)		
AA1.01	Backup systems	3.3	3.4
AA1.02	System loads	3.3	3.4
AA1.03	Affected systems so as to isolate damaged portions	3.3	3.4
11/11.03	Affected systems so as to isolate damaged portions	5.5	٠.┭

APE: 295018 Partial or Complete Loss of Component Cooling Water

IMPORTANCE K/A NO. **ABILITY** RO **SRO** AA2. Ability to determine and/or interpret the following as they apply to PARTIAL OR COMPLETE LOSS OF COMPONENT **COOLING WATER:** (CFR: 41.10 / 43.5 / 45.13) AA2.01 3.3 3.4 Component temperatures..... AA2.02 Cooling water temperature..... 3.1 3.2 Cause for partial or complete loss..... AA2.03 3.2 3.5 AA2.04 System flow..... 2.9 2.9 AA2.05 System pressure..... 2.9 2.9

APE: 295019 Partial or Complete Loss of Instrument Air

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR: (CFR: 41.8 to 41.10)		
	None		
AK2.	Knowledge of the interrelations between PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR and the following: (CFR: 41.7 / 45.8)		
AK2.01	CRD hydraulics	3.8	3.9
AK2.02	Component cooling water	2.9	3.0
AK2.03	Reactor feedwater	3.2	3.3
AK2.04	Reactor water cleanup	2.8	2.8
AK2.05	Main steam system	3.4	3.4
AK2.06	Offgas system	2.8	2.9
AK2.07	Condensate system	3.2	3.2
AK2.08	Plant ventilation	2.8	2.9
AK2.09	Containment	3.3	3.3
AK2.10	Fuel pool cooling	2.8	2.8
AK2.11	Radwaste	2.5	2.6
AK2.12	Standby gas treatment/FRVS	3.3	3.4
AK2.13	Isolation condenser: Plant-Specific	3.2*	3.2*
AK2.14	Plant air systems	3.2	3.2
AK2.15	Standby liquid control system	2.3*	2.6
AK2.16	Reactor core isolation cooling	2.8	2.8
AK2.17	High pressure coolant injection: Plant-Specific	2.7	2.7
AK2.18	ADS: Plant-Specific	3.5	3.5
AK2.19	RHR/LPCI: Plant-Specific	2.7	2.8
AK3.	Knowledge of the reasons for the following responses as they apply to PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR: (CFR: 41.5 / 45.6)		
AK3.01	Backup air system supply: Plant-Specific	3.3	3.4
AK3.02	Standby air compressor operation	3.5	3.4
AK3.03	Service air isolations: Plant-Specific	3.2	3.2
		5.2	5.2
ABILITY			
AA1.	Ability to operate and/or monitor the following as they apply to PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR: (CFR: 41.7/45.6)		
AA1.01	Backup air supply	3.5	3.3

APE: 295019 Partial or Complete Loss of Instrument Air

IMPORTANCE

K/A NO.	ABILITY	RO	SRO
AA1.02	Instrument air system valves: Plant-Specific	3.3	3.1
AA1.03	Instrument air compressor power supplies	3.0	3.0
AA1.04	Service air isolations valves: Plant-Specific	3.3	3.2
AA2.	Ability to determine and/or interpret the following as		
	they apply to PARTIAL OR COMPLETE LOSS OF INSTRUMENT AIR:		
	(CFR: 41.10 / 43.5 / 45.13)		
AA2.01	Instrument air system pressure	3.5	3.6
AA2.02	Status of safety-related instrument air system loads		
	(see AK2.1 - AK2.19)	3.6	3.7

APE: 295020 Inadvertent Containment Isolation

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to INADVERTENT CONTAINMENT ISOLATION: (CFR: 41.8 to 41.10)		
AK1.01	Loss of normal heat sink	3.7	3.9
AK1.02	Power/reactivity control	3.5 2.3	3.8 2.5
AK1.03 AK1.04	Water chemistry Bottom head thermal stratification	2.5	2.3
AK1.04 AK1.05	Loss of drywell/containment cooling	3.3	3.6
AK1.03	Loss of dry wen/contamment cooling	5.5	5.0
AK2.	Knowledge of the interrelations between INADVERTENT CONTAINMENT ISOLATION and the following: (CFR: 41.7 / 45.8)		
AK2.01	Main steam system	3.6	3.7
AK2.02	Sampling system	2.6	2.8
AK2.03	Drywell/containment ventilation/cooling: Plant-		
	Specific	3.1	3.3
AK2.04	RWCU system	3.1	3.1
AK2.05	Isolation condenser: Plant-Specific	4.2*	4.2
AK2.06	HPCI: Plant-Specific	3.8	3.8
AK2.07	RCIC: Plant-Specific	3.4	3.4
AK2.08	Traversing in-core probes: Plant-Specific	2.5*	2.6
AK2.09	RHR/shutdown cooling: Plant-Specific	3.1	3.3
AK2.10	Drywell equipment/floor drain sumps	2.9	3.1
AK2.11	Standby gas treatment system/FRVS: Plant-Specific	3.2	3.4
AK2.12	Instrument air/nitrogen: Plant-Specific	3.1	3.2
AK3.	Knowledge of the reasons for the following responses as they apply to INADVERTENT CONTAINMENT ISOLATION: (CFR: $41.5/45.6$)		
AK3.01	Reactor SCRAM	3.8	3.8
AK3.02	Drywell/containment pressure response	3.3	3.5
AK3.03	Drywell/containment temperature response	3.2	3.2
AK3.04	Reactor pressure response	4.1	4.1
AK3.05	Reactor water level response	3.8	3.9
AK3.06	Suppression pool water level response	3.3	3.4
AK3.07	Suppression pool temperature response	3.4	3.6
AK3.08	Suppression chamber pressure response	3.3	3.5

APE: 295020 Inadvertent Containment Isolation

	IMPORTANCE		
K/A NO.	ABILITY	RO	SRO
AA1.	Ability to operate and/or monitor the following as they apply to INADVERTENT CONTAINMENT ISOLATION: (CFR: 41.7 / 45.6)		
AA1.01	PCIS/NSSSS	3.6	3.6
AA1.02	Drywell ventilation/cooling system	3.2	3.2
AA1.03	Containment ventilation system: Plant-Specific	2.9	3.1
AA2.	Ability to determine and/or interpret the following as they apply to INADVERTENT CONTAINMENT ISOLATION : (CFR: $41.10/43.5/45.13$)		
AA2.01	Drywell/containment pressure	3.6	3.7
AA2.02	Drywell/containment temperature	3.3	3.4
AA2.03	Reactor power	3.7	3.7
AA2.04	Reactor pressure	3.9	3.9
AA2.05	Reactor water level	3.6	3.6
AA2.06	Cause of isolation	3.4	3.8

APE: 295021 Loss of Shutdown Cooling

	IMPORTANCE			
K/A NO.	KNOWLEDGE	RO	SRO	
AK1.	Knowledge of the operational implications of the following concepts as they apply to LOSS OF SHUTDOWN COOLING: (CFR: 41.8 to 41.10)			
AK1.01 AK1.02 AK1.03 AK1.04	Decay heat Thermal stratification Adequate core cooling Natural circulation	3.6 3.3 3.9 3.6	3.8 3.4 3.9 3.7	
AK2.	Knowledge of the interrelations between LOSS OF SHUTDOWN COOLING and the following: (CFR: 41.7 / 45.8)			
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07	Reactor water temperature Reactor water cleanup RHR/shutdown cooling Component cooling water systems: Plant-Specific Fuel pool cooling and cleanup system Reactor vessel headspray: Plant-Specific Reactor recirculation	3.6 3.2 3.6 3.0 2.7 2.5 3.1	3.7 3.3 3.6 3.1 2.8 2.6 3.2	
AK3.	Knowledge of the reasons for the following responses as they apply to LOSS OF SHUTDOWN COOLING : (CFR: $41.5/45.6$)			
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05	Raising reactor water level Feeding and bleeding reactor vessel Increasing drywell cooling Maximizing reactor water cleanup flow Establishing alternate heat removal flow paths	3.3 3.3 2.9 3.3 3.6	3.4 3.4 2.9 3.4 3.8	
ABILI	TY			
AA1.	Ability to operate and/or monitor the following as they apply to LOSS OF SHUTDOWN COOLING: (CFR: 41.7 / 45.6)			
AA1.01 AA1.02 AA1.03 AA1.04 AA1.05 AA1.06	Reactor water cleanup system RHR/shutdown cooling Component cooling water systems: Plant-Specific Alternate heat removal methods Reactor recirculation Containment/ drywell temperature	3.4 3.5 3.1 3.7 3.0 2.8	3.4 3.5 3.1 3.7 3.0 3.0	

APE: 295021 Loss of Shutdown Cooling

IMPORTANCE

K/A NO.	ABILITY		R	O	SRO
AA2.	Ability to determine and/or interpret the following as they apply to LOSS OF SHUTDOWN COOLING : (CFR: $41.10/43.5/45.13$)				
AA2.01	Reactor water heatup/cooldown rate		3.5	3.6	
AA2.02	RHR/shutdown cooling system flow		3.4	3.4	
AA2.03	Reactor water level		3.5	3.5	
AA2.04	Reactor water temperature		3.6	3.6	
AA2.05	Reactor vessel metal temperature		3.4	3.5	
AA2.06	Reactor pressure		3.2	3.3	
AA2.07	Reactor recirculation flow		2.9	3.1	

APE: 295022 Loss of CRD Pumps

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
AK1.	Knowledge of the operational implications of the following concepts as they apply to LOSS OF CRD PUMPS: (CFR: 41.8 to 41.10)		
AK1.01 AK1.02	Reactor pressure vs. rod insertion capability Reactivity control	3.3 3.6	3.4 3.7
AK2.	Knowledge of the interrelations between LOSS OF CRD PUMPS and the following: (CFR: 41.7 / 45.8)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07	Recirculation system: Plant-Specific	2.8 3.1 3.4 2.5 2.4 2.6 3.4	3.0 3.1 3.4 2.7 2.5 2.8 3.6
AK3.	Knowledge of the reasons for the following responses as they apply to LOSS OF CRD PUMPS: (CFR: 41.5 / 45.6)		
AK3.01 AK3.02	Reactor SCRAMCRDM high temperature	3.7* 2.9	3.9* 3.1
ABILITY	Y		
AA1.	Ability to operate and/or monitor the following as they apply to LOSS OF CRD PUMPS: (CFR: 41.7 / 45.6)		
AA1.01 AA1.02 AA1.03 AA1.04	CRD hydraulic system RPS Recirculation system: Plant-Specific Reactor water cleanup system: Plant-Specific	3.1 3.6 2.7 2.5	3.2 3.6 2.8 2.6
AA2.	Ability to determine and/or interpret the following as they apply to LOSS OF CRD PUMPS : $(CFR:\ 41.10/43.5/45.13)$		
AA2.01 AA2.02 AA2.03	Accumulator pressure CRD system status CRD mechanism temperatures	3.5 3.3 3.1	3.6 3.4 3.2

APE: 295023 Refueling Accidents

	IMPORTANCE			
K/A NO.	KNOWLEDGE	RO	SRO	
AK1.	Knowledge of the operational implications of the following concepts as they apply to REFUELING ACCIDENTS: (CFR: 41.8 to 41.10)			
AK1.01 AK1.02 AK1.03	Radiation exposure hazardsShutdown marginInadvertent criticality	3.6 3.2 3.7	4.1 3.6 4.0	
AK2.	Knowledge of the interrelations between REFUELING ACCIDENTS and the following: (CFR: 41.7 / 45.8)			
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07	Fuel handling equipment Fuel pool cooling and cleanup system Radiation monitoring equipment RMCS/Rod control and information system Secondary containment ventilation Containment ventilation: Mark-III Standby gas treatment/FRVS	3.3 2.9 3.4 3.2 3.5 3.4 3.6	3.7 3.2 3.6 3.4 3.7 3.8 3.9	
AK3.	Knowledge of the reasons for the following responses as they apply to REFUELING ACCIDENTS : (CFR: $41.5 / 45.6$)			
AK3.01 AK3.02 AK3.03 AK3.04 AK3.05	Refueling floor evacuation Interlocks associated with fuel handling equipment Ventilation isolation Non-coincident SCRAM function Initiation of SLC/shut-down cooling: Plant- Specific(BWR-1)	3.6 3.4 3.3 3.0	4.3* 3.8 3.6 3.5 4.0	
ABILITY				
AA1.	Ability to operate and/or monitor the following as they apply to REFUELING ACCIDENTS: (CFR: 41.7 / 45.6)			
AA1.01 AA1.02 AA1.03 AA1.04 AA1.05 AA1.06 AA1.07 AA1.08	Secondary containment ventilation	3.3 2.9 3.3 3.4 2.8 3.3 3.6 3.3	3.5 3.1 3.6 3.7 3.5 3.4 3.6 3.4	

APE: 295023 Refueling Accidents

K/A NO.	ABILITY	RO	SRO
AA2.	Ability to determine and/or interpret the following as they apply to REFUELING ACCIDENTS: $(CFR:\ 41.10/43.5/45.13)$		
AA2.01	Area radiation levels	3.6	4.0
AA2.02	Fuel pool level	3.4	3.7
AA2.03	Airborne contamination levels	3.3*	3.8*
AA2.04	†Occurrence of fuel handling accident	3.4	4.1
AA2.05	†Entry conditions of emergency plan	3.2	4.6*

APE: 600000 Plant Fire On Site

	IMPORTANCE				
K/A NO.	KNOWLEDGE	RO	SRC		
AK1	Knowledge of the operation applications of the following concepts as they apply to Plant Fire On Site:				
AK1.01	Fire Classifications by type	2.5	2.8		
AK1.02	Fire Fighting	2.9	3.1		
AK2.	Knowledge of the interrelations between PLANT FIRE ON SITE and the following:				
AK2.01	Sensors / detectors and valves	2.6	2.7		
AK2.02	Controllers and positioners	2.4	2.5		
AK2.03	Motors	2.5	2.6		
AK2.04	Breakers / relays / and disconnects	2.5	2.6		
AK3	Knowledge of the reasons for the following responses as they apply to PLANT FIRE ON SITE:				
AK3.01	Installation of fire detectors	2.0	2.1		
AK3.02	Steps called our in the site fire protection plant /				
	fire protection system manual / and fire zone manual	2.2	2.8		
AK3.03	Fire detector surveillance test		2.2		
AK3.04	Actions contained in the abnormal procedure for plant				
	fire on site	20	2.4		

APE: 600000 Plant Fire On Site

IMPORTANCE K/A NO. **ABILITY** RO **SRO** AA1 Ability to operate and / or monitor the following as they apply to PLANT FIRE ON SITE: AA1.01 2.9 AA1.02 1.9 AA1.03 2.2 AA1.04 2.2 AA1.05 3.1 AA1.06 3.0 AA1.07 2.4 2.9 AA1.08 AA1.09 2.7 AA2 Ability to determine and interpret the following as they apply to PLANT FIRE ON SITE: AA2.01 2.3 2.9 AA2.02 AA2.03 3.2 AA2.04 The fire's extent of potential operational damage 3.1 Ventilation alignment necessary to secure AA2.05 3.0 AA2.06 Need for pressurizing control room 2.8 AA2.07 Whether malfunction is due to common-mode electrical 3.0 AA2.08 Limits of affected area AA2.09 2.8 AA2.10 Time limit of long-term-breathing air system for 3.1 AA2.11 3.0 AA2.12 3.5 AA2.13 3.8 Equipment that will be affected by fire suppression AA2.14 3.6 AA2.15 3.5 AA2.16 Vital equipment and control systems to be maintained 3.5 AA2.17 3.6

APE: 700000 Generator Voltage and Electric Grid Disturbances			
K/A NO.	IMPORTANCE RO	SRO	
AK1.	Knowledge of the operational implications of the following concepts as they apply to GENERATOR VOLTAGE AND ELECTRIC GRID DISTURBANCES: (CFR: 41.4, 41.5, 41.7, 41.10 / 45.8)		
AK1.01 AK1.02 AK1.03	Definition of terms: volts, watts, amps, VARs, power factor3.3Over-excitation3.3Under-excitation3.3	3.5 3.4 3.4	
AK2.	Knowledge of the interrelations between GENERATOR VOLTAGE AND ELECTRIC GRID DISTURBANCES and the following: (CFR: 41.4 , 41.5 , 41.7 , $41.10 / 45.8$)		
AK2.01 AK2.02 AK2.03 AK2.04 AK2.05 AK2.06 AK2.07	Motors3.1Breakers, relays3.1Sensors, detectors, indicators3.0Controllers, positioners3.0Pumps3.1Reactor power3.9Turbine/generator control3.6	3.2 3.3 3.1 3.0 3.2 4.0 3.7	
AK3.	Knowledge of the reasons for the following responses as they apply to GENERATOR VOLTAGE AND ELECTRIC GRID DISTURBANCES: (CFR: 41.4, 41.5, 41.7, 41.10 / 45.8)		
AK3.01 AK3.02	Reactor and turbine trip criteria	4.2 3.9	
ABI	LITY		
AA1.	Ability to operate and/or monitor the following as they apply to GENERATOR VOLTAGE AND ELECTRIC GRID DISTURBANCES: (CFR: 41.5 and 41.10 / 45.5, 45.7, and 45.8)		
AA1.01 AA1.02 AA1.03 AA1.04 AA1.05	Grid frequency and voltage3.6Turbine/generator controls3.8Voltage regulator controls3.8Reactor controls4.1Engineered safety features3.9	3.7 3.7 3.7 4.1 4.0	

APE: 700000 Generator Voltage and Electric Grid Disturbances

IMPORTANCE K/A NO. **ABILITY** RO **SRO** AA2. Ability to determine and/or interpret the following as they apply to GENERATOR VOLTAGE AND ELECTRIC GRID **DISTURBANCES:** (CFR: 41.5 and 43.5 / 45.5, 45.7, and 45.8) AA2.01 3.6 AA2.02 3.6 AA2.03 3.6 AA2.04 3.6 AA2.05 3.8 3.5 AA2.06 AA2.07 4.0 AA2.08 4.4 AA2.09 4.3 3.8 AA2.10

5	Components	page
291001	Valves	5-3
291002	Sensors and Detectors	5-4
291003	Controllers and Positioners	5-6
291004	Pumps	5-7
291005	Motors and Generators	5-9
291006	Heat Exchangers and Condensers	5-10
291007	Demineralizers and Ion Exchangers	5-11
291008	Breakers, Relays and Disconnects	5-12

5-1

This page left blank.

COMPONENT: 291001 Valves

(CFR: 41.3)

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	The operation of safety valves	3.4	3.5
K1.02	The operation of relief valves	3.4	3.6
K1.03	The relationship of valve position to flow rate and back pressure	2.7	2.8
K1.04	Valve design for a given failed-valve position (open, closed, and as-is positions; spring loaded valves; hydraulic, pneumatically controlled valves; electric motor-driven valves)	2.7	2.8
K1.05	The significance of stem position (valve status) for gate valves	2.9	2.8
K1.06	Safety concerns in the use of gate valves (protect valves seals, open slowly)	2.7	2.7
K1.07	Cautions for placing a valve controller in manual mode	3.4	3.4
K1.08	Emergency operation of MOV with motor inoperable	3.4	3.5
K1.09	The stroke test for a valve, including the use of a		
	stopwatch	2.7	2.7
K1.10	Principles of operation and purpose of check valves	3.1	3.1
K1.11	Operation of manual valves and verification of		
	position with indicator lights	3.2	3.2
K1.12	Reason for using globe valves versus gates valves for throttling	2.6	2.8

COMPONENT: 291002 Sensors/Detectors

(CFR: 41.7)

K/A NO.	KNOWLEDGE	RO	SRO
Flow			
K1.01	Operation of venturis and orifices	2.4	2.5
K1.02	Temperature compensation requirements	2.4	2.5
K1.03	Effects of gas or steam on liquid flow rate		
	indications (erroneous reading)	2.5	2.6
K1.04	Modes of failure	2.9	3.1
K1.05	Operation of a flow D/P cell type flow detector	3.1	3.1
Level			
K1.06	Temperature/pressure compensation requirements	2.8	2.9
K1.07	Operation of a differential pressure level detector	3.2	3.2
K1.08	Effects of operating environment (pressure, temperature, and radiation)	2.8	2.9
K1.09	Modes of failure	3.3	3.3
Pressur	<u>e</u>		
K1.10	Theory of operation of bourdon tubes, diaphragms, bellows, and pressure detectors	2.4	2.5
K1.11	Effects of operating environment (pressure, temperature, radiation)	2.3	2.5
K1.12	Operation of a pressure D/P cell	2.8	2.9
K1.13	Modes of failure	2.9	3.1
Temper	<u>ature</u>		
K1.14	Theory of operation of T/C, RTD, thermostats, thermometers (expanding fluid)	2.3*	2.4
K1.15	Indications of failure modes of T/C, RTD, thermometers	2.6	2.8
Positio	n Detector_		
K1.16	Failure modes of reed switches, LVDT, limit switches, and potentiometers	2.5	2.7

COMPONENT: 291002 Sensors/Detectors

(CFR: 41.7)

K/A NO.	KNOWLEDGE	RO	SRO
K1.17	Applications of reed switches, magnets, LVDT, potentiometers, and limit switches	2.3*	2.4
	Electrical		
K1.18	Applications of voltmeters, ammeters, frequency, and ground detectors	2.2*	2.4
	Nuclear Instrumentation		
K1.19	Operation of fission chambers, ion chambers	3.0	3.1
K1.20	Neutron monitoring indication units	3.2	3.2
K1.21	Effects of voltage changes on neutron detector performance	2.8	2.9
K1.22	Failure modes of fission chambers, ion chambers, and proportional counters	3.0	3.1
	Radiation Detection		
K1.23	Operation of ion chambers, G-M tubes and scintillation detectors	2.8	2.9
K1.24	Use of portable radiation monitoring instruments	3.1	3.2

COMPONENT: 291003 Controllers and Positioners (CFR: 41.7)

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Function and operation of flow controller in manual and automatic modes	3.5	3.7
K1.02	Function and operation of a speed controller	3.5	3.6
K1.03	Operation of a valve controller, including seal-in features	3.3	3.4
K1.04	Function and operation of pressure and temperature controllers, including pressure and temperature control valves	3.3	3.3
K1.05	Function and characteristics of valve positioners	2.8	2.8
K1.06	Function and characteristics of governors and other mechanical controllers	2.5	2.6
K1.07	Safety precautions with respect to the operation of controllers and positioners	2.8	2.8
K1.08	Theory of operation of the following types of controllers: electronic, electrical, and pneumatic	2.2*	2.2*
K1.09	Effects on operation of controllers due to proportional, proportional and reset, and proportional and integral features	2.0*	2.2*

COMPONENT: 291004 Pumps

(CFR: 41.3)

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** Centrifugal K1.01 Identification, symptoms, and consequences of cavitation 3.2 3.2 K1.02 Reasons for venting a centrifugal pump 2.8 2.8 K1.03 2.8 2.9 Consequences of air binding Consequences of operating a pump dead headed or for K1.04 extended recirculation times 3.0 3.1 K1.05 Discuss relationships among head, flow, speed, and 2.8 2.9 power K1.06 Need for net positive suction head (NPSH); effects of loss of suction 3.3 3.3 K1.07 Starting current and operating current interpretation 2.8 2.8 K1.08 Purpose of starting a pump with discharge valve closed 2.8 2.8 K1.09 Pressure and flow relationship of pumps in parallel 2.3* 2.4* K1.10 Pressure and flow relationship of pumps in series 2.3* 2.4* K1.11 2.4 2.5 Definition of pump shutoff head K1.12 "Runout" of a centrifugal pump (definition, indications, causes, effects, and corrective measures) 2.8 2.8 K1.13 Principles of operation of a centrifugal pump 2.6 2.7 K1.14 Relationship between flow from a pump and suction 2.5 2.5 heads K1.15 Purpose of pump minimum flow requirements 2.9 Positive Displacement 2.9 K1.16 Discuss relationship among head, flow, speed, and 2.5 2.7 power K1.17 Net positive suction head (NSPH) requirements for a positive displacement pump 2.5 2.6 K1.18 Consequences of operating a positive displacement pump against a closed flow path 3.3 3.3

COMPONENT: 291004 Pumps (CFR: 41.3)

K/A NO.	KNOWLEDGE	RO	SRO
K1.19	Functions and characteristics of positive displacement		
	pumps	2.6	2.6
K1.20	Reason for starting a positive displacement pump with		
	the discharge valve open; need to clear the flow path	3.1	3.1
K1.21	Safety procedures and precautions associated with		
	positive displacement pumps	3.1	3.0

COMPONENT: 291005 Motors and Generators

(CFR: 41.7)

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Locked motor rotor, recognition from motor parameters	2.6	2.6
K1.02	Potential consequences of overheating motor insulation or motor bearings	2.6	2.7
K1.03	Causes of excessive current in motors, such as low voltage, overloading, and mechanical binding	2.6	2.7
K1.04	Relationship between pump motor current (ammeter reading) and the following: pump fluid flow, head, speed, and stator temperature	2.7	2.7
K1.05	Explain the difference between starting current and operating (running) current in a motor	2.6	2.7
K1.06	Reason for limiting the number of motor starts in a given time period	2.9	3.1
K1.07	Electrical units: volts, amps, A.C., D.C., and hertz	2.6	2.6
K1.08	Consequences of overexcited/underexcited	2.5	2.6
K1.09	†Interrelations of the following: VARs, Watts, Amps,	2 3*	26

COMPONENT: 291006 Heat Exchangers and Condensers (CFR: 41.4)

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Startup/shutdown of a heat exchanger	2.7	2.7
K1.02	Proper filling of a shell-and-tube heat exchanger	2.6	2.6
K1.03	Basic heat transfer in a heat exchanger	2.4	2.6
K1.04	Effects of heat exchanger flow rates that are too high or too low	2.8	2.8
K1.05	Flow paths for the heat exchanger (counterflow and U-types)	2.2*	2.3*
K1.06	Components of a heat exchanger (shells, tubes, plates, etc.)	2.3*	2.3*
K1.07	Control of heat exchanger temperatures	2.7	2.8
K1.08	Relationship between flow rates and temperatures	2.9	3.0
K1.09	Definition of thermal shock	2.7	2.8
K1.10	Principle of operation of condensers	2.8	2.8
K1.11	Relationship between condenser vacuum and backpressure	2.8	2.8
K1.12	Causes of natural circulation	2.9	3.0
K1.13	Use of steam tables to determine saturation pressure for a given temperature and vice versa	2.7	2.9
K1.14	Fluid hammer and methods of prevention	3.1	3.2
K1.15	Effects of heat exchanger tube fouling	2.6	2.8
K1.16	Effects of scaling on heat exchanger operation	2.5	2.6
K1.17	Consequences of heat exchanger tube failure	2.7	2.8
K1.18	Reasons for non-condensible gas removal	2.8	2.9

COMPONENT: 291007 Demineralizers and Ion Exchangers (CFR: 41.3)

IMPORTANCE

K/A NO.	KNOWLEDGE	RO	SRO	
K1.01	Effect of excessive differential pressure on demineralizer performance	2.6	2.7	
K1.02	Reason for sampling inlet and outlet of demineralizer	2.5	2.6	
K1.03	Effects of channeling in a demineralizer	2.8	2.9	
K1.04	Purpose of a demineralizer	2.8	2.9	
K1.05	Purpose of demineralizer D/P gauge	2.4	2.5	
K1.06	Reason for demineralizer temperature and flow limits	2.7	2.7	
K1.07	Principles of demineralizer operation	2.3*	2.5	
K1.08	Demineralizer D/P to determine condition of demineralizer resin bed	2.6	2.6	
K1.09	Effects of demineralizer operation on water conductivity	2.7	2.7	

5-11

COMPONENT: 291008 Breakers, Relays and Disconnects (CFR: 41.7)

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Purpose for racking out breakers (de-energize components and associated control and indication circuits)	3.6	3.6
K1.02	Local indication that breaker is open, closed or tripped	3.4	3.5
K1.03	Meaning of power supply circuit breaker indicator lights and capability to remotely open and close	3.3	3.4
K1.04	Operation of various push buttons, switches and handles and the resulting action on breakers	3.3	3.3
K1.05	Function of thermal overload protection device	3.0	3.1
K1.06	Interpreting one-line diagram of control circuitry	3.2	3.6
K1.07	Safety procedures and precautions associated with breakers, including MCC bus breakers, high, medium and low voltage breakers, relays and disconnects	3.5*	3.7
K1.08	Effects of closing breakers with current out of phase, different frequencies, high voltage differential, low current, or too much load	3.4	3.5
K1.09	Effect of racking out breakers on control and indicating circuits and removal of control power on breaker operation	3.4	3.5
K1.10	Function, control, and precautions associated with disconnects	3.3*	3.4

6	Theory	page
6.1	Reactor Theory	
292001	Neutrons	6.1-3
292002	Neutron Life Cycle	6.1-4
292003	Reactor Kinetics and Neutron Sources	6.1-5
292004	Reactivity Coefficients	6.1-6
292005	Control Rods	6.1-7
292006	Fission Product Poisons	6.1-8
292007	Fuel Depletion and Burnable Poisons	6.1-10
292008	Reactor Operational Physics	6.1-11
6.2	Thermodynamics Theory	
293001	Thermodynamic Units and Properties	6.2-1
293002	Basic Energy Concepts	6.2-2
293003	Steam	6.2-3
293004	Thermodynamic Process	6.2-4
293005	Thermodynamic Cycles	6.2-5
293006	Fluid Statics	6.2-6
293007	Heat Transfer and Heat Exchangers	6.2-8
293008	Thermal Hydraulics	6.2-9
293009	Core Thermal Limits	6.2-12
293010	Brittle Fracture and Vessel Thermal Stress	6.2-15

This page left blank

6.1 Reactor Theory (CFR: 41.1)

REACTOR THEORY: 292001 Neutrons

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Define fast, intermediate, and slow neutrons.	2.0*	2.1*
K1.02	Define prompt and delayed neutrons.	3.0	3.1
K1.03	Define thermal neutrons.	2.7	2.7
K1.04	Describe neutron moderation.	3.2	3.2
K1.05	Identify characteristics of good moderators.	2.4*	2.6*
K1.06	Define neutron lifetime.	1.9*	1.9*
K1.07	Define neutron generation time.	1.9*	1.9*
K1.08	Describe fast flux, thermal flux, and flux distribution.	2.2*	2.4

REACTOR THEORY: 292002 Neutron Life Cycle

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** Describe the neutron life cycle using the following terms: K1.01 --fast fission factor. 1.9* 1.9* K1.02 1.9* 1.9* -- fast non-leakage probability factor. 2.0* K1.03 --resonance escape probability factor. 2.1* K1.04 --thermal non-leakage probability factor. 1.9* 2.0* K1.05 1.9* 2.0* --thermal utilization factor. 1.9* K1.06 --reproduction factor. 1.9* K1.07 Define critical, subcritical, and supercritical with 3.5* 3.5 respect to a reactor. K1.08 Define effective multiplication factor and discuss its relationship to the state of d reactor. 2.7 2.8 K1.09 Define K-excess. 2.4* 2.6 K1.10 Define shutdown margin. 3.2 3.5 K1.11 Define reactivity. 3.2 3.3 K1.12 State the relationship between reactivity and effective multiplication factor. 2.4 2.5 K1.13 †Calculate shutdown margin using procedures and given plant parameters 1.8* 2.4* K1.14 †Evaluate change in shutdown margin due to changes in plant parameters 2.6 2.9

REACTOR THEORY: 292003 Reactor Kinetics and Neutron Sources

cycle of core operation.

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K1.01 2.9 Explain the concept of subcritical multiplication. 3.0 K1.02 Given the simplified formula for subcritical multiplication, perform calculations involving steady state count rate and source count rate. 2.1* 2.3* K1.03 2.4 Describe the production of delayed neutrons. 2.4 K1.04 Define delayed neutron fraction and effective delayed neutron fraction; state the reasons for variation. 2.5 2.5 K1.05 3.7 Define reactor period. 3.7 Explain the effect of delayed neutrons on reactor K1.06 period. 3.7 3.7 Explain prompt critical, prompt jump, and prompt drop. K1.07 3.3 3.3 K1.08 Given the power equation, solve problems for power changes and period. 2.7 2.8 K1.09 Define doubling time and calculate it using the power 2.5* 2.6* equation. K1.10 Explain the necessity for installed neutron sources in a reactor core. 2.4* 2.4 K1.11 Explain why installed sources are not needed after one

2.4

2.4

REACTOR THEORY: 292004 Reactivity Coefficients

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K1.01 3.2 Define the temperature coefficient of reactivity. 3.2 K1.02 Describe the effect on the magnitude of the temperature coefficient of reactivity from changes in moderator temperature and core age. 2.5* 2.6* K1.03 Explain resonance absorption. 2.6 2.7 K1.04 Explain doppler broadening and self-shielding. 2.6 2.7 K1.05 Define the doppler coefficient of reactivity. 2.9 2.9 Describe the effect on the magnitude of the doppler coefficient of reactivity for changes in the following: K1.06 --Moderator temperature 2.1* 2.2* 2.1* K1.07 --Core void fraction 2.2* K1.08 2.2* 2.4* --Fuel temperature K1.09 1.9* 2.1* --Core age K1.10 Define the void coefficient of reactivity. 3.2 3.2 Describe the effect on the magnitude of void coefficient from changes in the following: K1.11 --Core void fraction 2.5 2.6 Kl. 12 2.2* 2.3* --Fuel temperature 2.1* 2.2* K1.13 --Core age K1.14 Compare the relative magnitudes of the temperature, doppler, and void coefficients of reaCtivitY. 3.3 3.3

REACTOR THEORY: 292005 Control Rods

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K1.01 3.2* 3.3* Relate notch and rod position. K1.02 Name the material used for thermal neutron absorption in control rods. 2.5 2.6 K1.03 Describe nuclear properties of active material in the 1.9* 1.9* K1.04 Predict direction of change in reactor power for a change in control rod position. 3.5 3.5 K1.05 2.5* 2.6 Define rod density. K1.06 Define reactor scram. 3.7* 3.8* Define control rod worth, differential control rod K1.07 worth, and integral control rod worth. 2.4 2.6 K1.08 Explain the shape of curves for differential and integral CRW versus rod position. 2.1* 2.3 K1.09 Explain direction of change in the magnitude of CRW for a change in moderator temperature, void fraction, and control rod density, and Xenon. 2.5* 2.6 K1.10 †State the purpose of flux shaping and rod sequencing. 2.8 3.3 K1.11 2.4* 2.5* Define deep rods, and shallow rods. K1.12 †Describe effects of deep, and shallow control rods on axial and radial flux distribution. 2.6 2.9

REACTOR THEORY: 292006 Fission Product Poisons

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** K1.01 Define fission product poison. 2.7 2.8 K1.02State the characteristics of Xenon-135 as a fission 3.1 3.1 product poison. K1.03 Describe the production of Xenon-135. 2.9 2.9 K1.04 Describe the removal of Xenon-135. 2.9 2.9 Describe the following processes and state their effect on reactor operations: K1.05 --Equilibrium Xenon 2.9 2.9 K1.06 -- Maneuvering Xenon 2.7 2.7 K1.07 --Xenon following a scram 3.2 3.2 K1.08 †Describe the effects that Xenon concentration has on flux shape and control rod patterns. 2.8 3.2 Plot the curve and explain the reasoning for the reactivity insertion by Xenon-135 versus time for the following: K1.09 --Initial reactor startup and ascension to rated 2.5 power. 2.5 K1.10 --Reactor startup with Xenon-135 already present in the core 2.9 2.9

2.6

2.8

2.6*

3.1

2.1*

1.8*

1.9*

2.7

2.3

2.6

3.2

2.1*

1.9*

1.9*

--Power changes from steady-state power to another.

Explain the process and reasons for the Reactor

of Xenon-135 concentration in the reactor.

Describe the production of Samarium-149.

Describe the removal of Samarium-149.

Operator to compensate for the time dependent behavior

State the characteristics of Samarium-149 as a fission

-- Reactor scram.

product poison.

--Reactor shutdown.

K1.11

K1.12

K1.13

K1.14

K1.15

K1.16

K1.17

REACTOR THEORY: 292006 Fission Product Poisons

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** K1.18 Define equilibrium samarium. 1.8* 1.8* Plot the curve and explain the reasoning for reactivity insertion by Samarium-149 versus time for the following: K1.19 --Initial reactor startup and ascension to rated 1.7* 1.8* power. K1.20 --Reactor shutdown. 1.6* 1.7* K1.21 Describe effects of power changes on samarium concentration. 1.7* 1.8* K1.22 Compare effects of Samarium-149 on reactor operation with those of Xenon-135. 2.4* 2.4

REACTOR THEORY: 292007 Fuel Depletion And Burnable Poisons

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Define burnable poison and state its use in the reactor.	2.9	3.1
K1.02	Describe and explain distribution of burnable poisons in the core.	1.8*	2.0*
K1.03	†Given a curve of K-effective versus core age, state the reasons for maximum, minimum, and inflection		
	points.	2.4*	2.7

REACTOR THEORY: 292008 Reactor Operational Physics

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
Startup a	and Approach to Criticality		
K1.01	List parameters which should be monitored and controlled during the approach to criticality.	3.8	3.9*
K1.02	List reactivity control mechanisms which exist for plant conditions during the approach to criticality.	3.8	3.8
K1.03	Describe count rate and period response which should be observed for rod withdrawal during the approach to criticality.	4.1	4.0
K1.04	Relate the concept of subcritical multiplication to predicted count rate and period response for control rod withdrawal during the approach to critical.	3.3	3.4
K1.05	Explain characteristics to be observed when the reactor is very close to criticality.	4.3*	4.3*
Criticali	<u>ty</u>		
K1.06	List parameters which should be monitored and controlled upon reaching initial criticality.	4.2*	4.2
K1.07	Define criticality as related to a reactor startup.	3.9	3.9
K1.08	Describe reactor power and period response once criticality is reached.	4.1	4.1
Intermed	liate Range Operation		
K1.09	List parameters which should be monitored and controlled during the intermediate phase of startup.	3.9*	3.9*
K1.10	Explain procedures for adjusting reactor period during the intermediate phase of startup.	3.6	3.6
K1.11	Discuss the concept of the point of adding heat (POAH) and its impact on reactor power.	3.7	3.8
K1.12	Describe reactor power and period response prior to reaching the POAH.	3.6	3.7
K1.13	Explain characteristics to look for when the POAH is reached.	3.8	3.9

REACTOR THEORY: 292008 Reactor Operational Physics

K/A NC	IMPORTANCE D. KNOWLEDGE	RO	SRO
	Heatup Operation	210	2110
K1.14	Describe three parameters to be monitored and controlled during heatup.	3.5	3.5
K1.15	Describe reactor power and period response after reaching the point of adding heat.	3.7	3.7
K1.16	Explain procedures for establishing and controlling heatup rate.	3.6	3.7
<u>I</u>	Power Operation		
K1.17	Describe three parameters to be monitored and controlled during power operation.	3.6	3.6
K1.18	Describe means by which reactor power will be increased to rated power.	3.8	3.8
K1.19	Explain transient and steady-state effects of a control rod withdrawal on reactor power and void fraction content.	3.1	3.2
K1.20	Explain transient and steady-state effects of an increase in core flow on reactor power and void fraction.	3.3	3.4
K1.21	Explain the relationship between steam production rate and reactor power given specific conditions.	2.9	3.0
K1.22	Explain the effect that opening steam bypass valves, during power operation, will have on reactor power.	3.5	3.6
K1.23	†Explain the necessity for rod pattern exchanges.	2.6	3.1
K1.24	†Describe the parameters to be monitored and controlled during rod pattern exchanges.	2.8	3.2
<u> </u>	Reactor Response on a Scram		
K1.25	Explain the shape of a curve of reactor power versus time after a scram.	2.8	2.9
1	Normal Reactor Shutdown		
K1.26	Explain reactor power response to a decrease in core flow.	3.4	3.7

REACTOR THEORY: 292008 Reactor Operational Physics

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.27	Explain reactor power response to a control rod insertion.	3.4	3.5
K1.28	Explain the necessity for inserting control rods in a predetermined sequence during normal shutdown.	3.4	3.7
K1.29	Define decay heat.	3.4	3.6
K1.30	Explain the relationship between decay heat generation and: a) power level history, b) power production, and c) time since reaction shut down.	3.2	3.5

This page left blank

6.2 THERMODYNAMICS

(CFR: 41.14)

THERMODYNAMICS: 293001 Thermodynamic Units and Properties

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Convert between absolute and relative pressure and vacuum scales.	2.2*	2.3*
K1.02	Recognize the difference between absolute and relative temperature scales.	2.1*	2.1*
K1.03	Describe how common pressure and level sensing instruments work.	2.5*	2.7
K1.04	Explain relationships between work, power, and energy.	1.8*	1.9*

THERMODYNAMICS: 293002 Basic Energy Concepts

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Identify energy and work forms.	1.6*	1.7*
K1.02	Explain the law of conservation of energy.	1.9*	1.9*
K1.03	Explain the difference between state and phase of a working substance.	1.6*	1.7*
K1.04	Explain the application of enthalpy in the monitoring of plant processes.	2.1*	2.4*
K1.05	Identify the relationship between heat flow during a process and a T-s diagram representation of the process.	2.0*	2.2*
K1.06	Define specific heat.	1.8*	2.1*
K1.07	Apply specific heat in solving heat transfer problems.	1.5*	1.6*

THERMODYNAMICS: 293003 Steam

K/A NO.	KNOWLEDGE	IMPORTANCE	RO	SRO
K1.01	Describe effects of pressure on density or specific volume of a liquid.		2.3*	2.4
K1.02	Distinguish between liquids, vapors, gases, and fluids.		2.2*	2.3*
K1.03	Define latent heat of vaporization		2.3	2.4
K1.04	Define vaporization line		2.0*	2.1*
K1.05	Define critical point		1.8*	1.8*
K1.06	Define vapor dome		1.8*	2.0*
K1.07	Define saturated liquid		2.7	2.8
K1.08	Define wet vapor		1.8*	1.9*
K1.09	Define saturated vapor		2.5*	2.6*
K1.10	Define vapor pressure		1.8*	1.9*
K1.11	Define moisture content		2.3*	2.3*
K1.12	Define quality		2.5	2.6
K1.13	Define superheated vapor		2.3*	2.4*
K1.14	Define supersaturated vapor		1.8*	1.8*
K1.15	Define subcooled and compressed liquids		2.4*	2.4*
K1.16	Define subcooling		2.8	2.8
K1.17	Define specific heat		1.9*	2.1*
	<u>Identify the following terms on a T-s diagram:</u>			
K1.18	Critical point		1.7*	1.7*
K1.19	Saturated liquid line		2.1*	2.2*
K1.20	Saturated vapor line		2.2*	2.3*
K1.21	Solid, liquid, gas, vapor, and fluid regions		2.1*	2.2*
K1.22	Explain the usefulness of steam tables to the Control Room Operator.		2.9	3.2
K1.23	Use saturated and superheated steam tables.		2.8*	3.1*

THERMODYNAMICS: 293004 Thermodynamic Processes

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Explain the relationship between real and ideal processes.	1.6*	1.7*
K1.02	Explain the shape of the T-s diagram process line for a typical boiler.	1.8*	1.9*
	Nozzles		
K1.03	Describe the functions of nozzles in flow restrictors.	2.2*	2.2*
K1.04	Describe the functions of nozzles in air ejectors.	2.5	2.6
K1.05	Describe the principles of operation of a jet pump	2.7	2.7
Turbines			
K1.06	Explain the function of nozzles, fixed blading, and moving blading in the turbine.	1.9*	2.1*
K1.07	Explain the reason turbines are multistages.	2.1*	2.2*
K1.08	Define turbine efficiency.	2.0*	2.1*
K1.09	Explain the difference between actual turbine performance and ideal thermal efficiency.	1.7*	1.8*
	<u>Pumps</u>		
K1.10	Define pump efficiency.	1.8*	1.9*
K1.11	Explain the difference between ideal and real pumping processes.	1.7*	1.8*
	Condensers		
K1.12	Discuss subcooling.	2.9	3.1
K1.13	Explain vacuum formation in condenser processes.	2.5	2.6
K1.14	Explain the condensing process.	2.6	2.7
Throttlin	g and the Throttling Process		
K1.15	Define throttling.	2.2*	2.3*
K1.16	Explain the reduction of process pressure from throttling.	2.1*	2.3*

THERMODYNAMICS: 293005 Thermodynamic Cycles

IMPORTANCE

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	Define thermodynamic cycle.	1.7*	1.8*
K1.02	Define thermodynamic cycle efficiency in terms of net work produced and energy applied.	1.7*	1.7*
K1.03	Describe the moisture effects on turbine integrity and efficiency.	2.6	2.7
K1.04	Explain steam quality effects on nuclear turbine design.	2.3*	2.4*
K1.05	State the advantages of moisture separators/reheaters and feedwater heaters for a typical steam cycle.	2.7	2.8

THERMODYNAMICS: 293006 Fluid Statics

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** K1.01 1.7* 1.8* Distinguish between fluids and other substances. K1.02 Distinguish between static pressure, dynamic pressure, and total pressure. 2.0* 2.2* K1.03 2.4 Define head loss. 2.5 K1.04 Discuss operational considerations of viscosity as related to head loss. 1.7* 1.9* K1.05 Explain operational implications of fluid hammer 3.2 3.3 Pumps and Pump Characteristics K1.06 --State the purpose of a pump. 2.5* 2.6* K1.07 -- Discuss pump head. 2.5 2.6 K1.08 --Discuss relationship between pump speed, head, flow, and power without using formulas or calculations. 2.5 2.6 K1.09 -- Define cavitation. 2.8 2.9 K1.10-- Define net positive suction head (NPSH). 2.7 2.8 K1.11 --Define pump shut-off head, pump runout, and axial 2.4 thrust. 2.5 K1.12 --Explain the importance of proper system venting for pump operations. 2.9 2.9 K1.13 --Explain the results of putting centrifugal pumps in parallel or series combinations. 2.6 2.7 K1.14 --Given the characteristic curve for a typical centrifugal pump, explain the reason for its shape. 2.2* 2.3* K1.15 --Using a centrifugal pump characteristic curve and a system characteristic curve, illustrate how the system operating point changes due to system changes. 2.3* 2.4* K1.16 --Describe how a centrifugal pump characteristic curve will change with pump speed. 2.1* 2.3* K1.17 --Explain how operating a centrifugal pump at shutoff head may cause overheating of the pump and describe methods used to avoid overheating. 2.7 2.6

THERMODYNAMICS: 293006 Fluid Statics

K1.29

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K1.18 --Discuss the characteristic curve for a typical positive displacement pump and explain the reason for 1.9* its shape. 2.1* K1.19 -- Describe the problems that will occur in emergency core cooling systems if the pumps are operated at lower than design flow for extended periods of time. 2.7 2.9 K1.20 Define or explain mass flow rate 2.4 2.4 K1.21 2.4* Define or explain two-phase flow 2.6 K1.22 Define or explain pressure spike 2.2* 2.3* K1.23 Define or explain gas binding 2.2* 2.3* K1.24 2.1* 2.3* Define or explain recirculation ratio 2.1* K1.25 Define or explain pipe whip 2.2* K1.26 Explain why flow measurements must be corrected for density changes. 2.3 2.4 K1.27 Explain the relationship between pressure head and velocity head in a fluid system. 1.8* 2.0* K1.28 Discuss the velocity profiles for laminar flow and tubulent flow. 1.7* 1.8*

Describe the methods of controlling system flow rates.

2.6

2.7

THERMODYNAMICS: 293007 Heat Transfer and Heat Exchanges

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** Heat Transfer K1.01 Describe three mechanisms of heat transfer. 3.2 3.2 K1.02 Describe thermal conductivity. 2.4 2.6 K1.03 Explain the manner in which fluid films affects heat transfer. 2.7 2.8 Heat Exchangers K1.04 1.9* Discuss parallel-flow heat exchangers. 2.2* K1.05 Discuss counter-flow heat exchangers. 2.0* 2.2* K1.06 Discuss the factors which affect heat transfer rate in 2.7 2.8 a heat exchanger. K1.07 Describe how the presence of gases or steam can affect heat transfer and fluid flow in heat exchangers. 2.7 2.9 Condenser Applications of Heat Transfer K1.08 List functions of the main condenser in a power plant. 3.0 3.1 K1.09 Discuss operational implications of condensate 2.5 depression. 2.7 Core Thermal Power Define core thermal power. K1.10 2.7* 2.9* K1.11 †Explain methods of calculating core thermal power. 2.6 3.1 K1.12 Define percent reactor power. 2.6* 2.7* K1.13 †Calculate core thermal power using a simplified heat 2.3* 2.9* balance.

THERMODYNAMICS: 293008 Thermal Hydraulics

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** Boiling Heat Transfer K1.01 Distinguish between boiling processes and other heat transfer mechanisms. 2.6 2.8 K1.02 Describe surface or cavity nucleation. 2.2* 2.3* K1.03 List factors affecting bubble formation in a cavity. 1.9* 2.1* K1.04 Describe means by which boiling improves convection heat transfer. 2.6 2.7 K1.05 1.4* Describe microconvection. 1.5* Pool Boiling Curve (T vs. Q/A) K1.06 Define a natural convection heat transfer. 2.5 2.6 K1.07 Define nucleate boiling, subcooled nucleate boiling, and bulk boiling. 2.8 3.0 K1.08 2.9 3.1 Describe DNB (departure from nucleate boiling). K1.09 Describe OTB (onset of transition boiling). 3.0 3.2 K1.10 Describe CHF (critical heat flux). 2.9 3.0 K1.11 Describe transition (partial film) boiling. 2.7 2.8 K1.12 Describe stable film boiling. 2.7 2.8 K1.13 Describe burnout and burnout heat flux. 2.3* 2.3* Two Phase Flow K1.14 Classify slug flow region along a fuel channel, experiencing two phase flow. 2.0* 2.1* K1.15 Describe annular flow region along a hypothetical fuel channel, experiencing two phase flow. 2.2* 2.3 K1.16 Describe dryout region or mist flow region along a hypothetical fuel channel, experiencing two phase flow. 2.2* 2.3 K1.17 Describe OTB point along a hypothetical fuel channel, experiencing two phase flow. 2.5 2.8

THERMODYNAMICS: 293008 Thermal Hydraulics

	IMPORTANCE			
K/A NO.	KNOWLEDGE	RO	SRO	
K1.18	Describe effects of flowrate and phase change on the heat transfer coefficient.	2.2*	2.4	
Core Inle	et Subcooling			
K1.19	Define core inlet subcooling.	2.6	2.8	
K1.20	Define carryunder.	2.4	2.6	
Voids an	d Void Fraction			
K1.21	Define void fraction.	3.0	3.0	
K1.22	Explain the term void as applied to core operations	2.9	3.0	
K1.23	Define qualilty	2.5	2.7	
K1.24	Draw the temperature profile from the centerline of a fuel pellet to the centerline of the channel.	2.4	2.5	
Recircul	ation System			
K1.25	Explain the reason for forced core recirculation.	3.2	3.2	
K1.26	Explain the jet pump operating principle.	2.9	3.1	
K1.27	Explain the necessity of determining core coolant flow.		3.0	
K1.28	Describe the factors affecting single- and two-phase flow resistance.	2.3*	2.5*	
Core Ori	ficing			
K1.29	Describe the effects of increasing bundle power on bundle flow resistance.	2.8	3.0	
K1.30	Compare the flow resistance through high powered bundles to that of low powered bundles.	2.7	2.7	
K1.31	Explain the necessity of core orificing.	2.9	3.0	
K1.32	Describe core bypass flow.	2.5	2.6	
K1.33	Explain the need for adequate core bypass flow.			
	Natural Circulation	2.4	2.6	

THERMODYNAMICS: 293008 Thermal Hydraulics

IMPORTANCE K/A NO. **KNOWLEDGE** RO **SRO** K1.34 2.9 Explain the causes of natural circulation in BWR's. 3.1 K1.35 Describe problems that thermal stratification can 3.1 3.3 cause. K1.36 Describe means by which the operator can determine if natural circulation flow exists. 3.1 3.3 K1.37 Describe means by which the operator can enhance natural circulation. 3.2 3.4 Sketch the axial temperature and enthalpy profiles for a typical reactor coolant channel and describe how they are affected by the following: K1.38 --Onset of nucleate boiling 1.8* 2.1* K1.39 --Axial core flux 1.8* 1.9* K1.40 --Inlet temperature 1.8* 1.9* 1.8* K1.41 --Heat generation rate 2.0* K1.42 --Flow rate in the channel 1.8* 1.9* K1.43 Sketch the temperature profile in the axial and radial directions for a typical fuel rod and explain the reason for its shape. 2.0* 2.2*

THERMODYNAMICS: 293009 Core Thermal Limits

K/A NO.	IMPORTANCE KNOWLEDGE	RO	SRO
K1.01	†Explain radial peaking factor (RPF)	2.1*	2.5*
K1.02	†Explain axial peaking factor(APF)	2.2*	2.6
K1.03	†Explain local peaking factor(LPF)	2.1*	2.5*
K1.04	†Explain total peaking factor(TPF)	2.2*	2.6
K1.05	State the reason thermal limits are necessary.	3.3	3.5
	State the reason thermal mints are necessary.	3.3	3.3
<u>LHGR</u>	ID (* LUCD	2.4	2.0
K1.06	†Define LHGR.	3.4	3.8
K1.07	†Explain the basis of the limiting condition of LHGR.	2.8	3.6
K1.08	†Describe the mode of fuel failure for LHGR.	3.0	3.4
K1.09	†Define FLPD and MFLPD.	3.1	3.7
MAPLHO	<u>GR</u>		
K1.10	†Define APLHGR	3.3	3.7
K1.11	†Explain the basis of the limiting condition for APLGHR.	2.8	3.6
K1.12	†Describe the mode of fuel failure for APLHGR.	2.9	3.5
K1.13	†Define MAPLHGR	3.1	3.6
†Explain the mechanisms most limiting for each region of the MAPLHGR limit curves.		2.2*	2.7
K1.15	†Describe conditions under which radiative heat transfer becomes the significant method of heat transfer within a fuel bundle.		3.1
K1.16	†Discuss how changes in the heat generation rate and thermal conductivity of the fuel rod affect fuel centerline temperature	2.4	2.8
	<u>MCPR</u>		
K1.17	†Define critical power.	3.3	3.7
K1.18	†Define critical power ratio.	3.2	3.7

THERMODYNAMICS: 293009 Core Thermal Limits

IMPORTANCE K/A NO. KNOWLEDGE RO **SRO** K1.19 †Explain the basis of the limiting condition for CPR. 2.8 3.6 K1.20 †Describe the mode of fuel failure for CPR. 3.1 3.6 K1.21 †Define MCPR. 3.1 3.6 K1.22 †Describe the effects of subcooling on critical power. 2.9 3.3 K1.23 †Describe the effects of mass flow on critical power. 2.8 3.2 K1.24 †Describe the effects of pressure on critical power. 2.7 3.2 K1.25 †Describe the effects of local power distribution on critical power. 2.7 3.2 K1.26 †Describe the effects of axial power distribution on 2.6 3.1 critical power. K1.27 †Explain the purpose of the flow biasing correlation factor, (K), as it relates to MCPR limits. 2.7 3.3 K1.28 †Define FLCPR. 3.0 3.5 Thermal Time Constant K1.29 Define fuel thermal time constant. 2.4* 2.7 K1.30 †Relate thermal time constant to transient operating condition. 2.3 2.7 Pellet Clad Interaction K1.31 Describe pellet-clad interaction (PCI). 3.0 3.4 K1.32 List the causes of PCI. 2.9 3.3 K1.33 Describe the purpose of the pellet to clad gap. 2.4 2.8 K1.34 2.3* Identify the possible effects of fuel densification. 2.6 K1.35 Describe the effects of iodine and cadmium on PCI. 2.2* 2.6* **PCIOMR** K1.36 †Explain the purpose for PCIOMR (Plant Specific). 2.8 3.4

THERMODYNAMICS: 293009 Core Thermal Limits

	IMPORTANCE		
K/A NO.	KNOWLEDGE	RO	SRO
K1.37	†Identify how the PCIOMR rules minimize the adverse effects of PCI (Plant Specific).	2.6	3.3
K1.38	†State the items measured for each of the three core thermal limits.	2.7	3.1
	For the following plant operating or accident conditions, identify which of the three core thermal limits are most limiting:		
K1.39	Full power operation	2.8	3.2
K1.40	Loss of reactor coolant	2.8	3.3
K1.41	Increase in core flow	2.8	3.3
K1.42	Increase in reactor pressure	2.8	3.3
K1.43	Cold water addition	2.9	3.4

THERMODYNAMICS: 293010 Brittle Fracture and Vessel Thermal Stress

IMPORTANCE

K/A NO.	KNOWLEDGE	RO	SRO
K1.01	State the brittle fracture mode of failure.	2.4*	2.8
K1.02	†State the definition of Nil-Ductility Transition Temperature.	2.2*	2.7
K1.03	Define reference temperature.	2.0*	2.5
K1.04	†State how the possibility of brittle fracture is minimized by operating limitations.	2.9	3.2
K1.05	†State the effect of fast neutron irradiation on reactor vessel metals.	2.5	2.8

This page left blank

NRC FORM 335 (9-2004) NRCMD 3.7	U.S. NUCLEAR REGULATORY COMMISSION	REPORT NUMBER (Assigned by NRC, Ac and Addendum Numb		
BIBLIOGRAPHIC DA (See instructions on the		NUREG-1123, Revision 2, Supplement 1		
2. TITLE AND SUBTITLE		3. DATE REPOR	RT PUBLISHED	
Knowledge and Abilities Catalog for Nuclear Power Plant Operators: Boiling Water Reactors		MONTH	YEAR	
		October 4. FIN OR GRANT NUI	2007 MBER	
5. AUTHOR(S)		6. TYPE OF REPORT		
D. Muller	D. Muller		Technical	
			7. PERIOD COVERED (Inclusive Dates)	
8. PERFORMING ORGANIZATION - NAME AND ADDRESS (If NRC, provide name and mailing address.) Division of Inspection and Regional Support Office of Nuclear Reactor Regulation U.S. Nuclear Regulatory Commission Washington, DC 20555-0001 9. SPONSORING ORGANIZATION - NAME AND ADDRESS (If NRC, ty and mailing address.) Same as above				
10. SUPPLEMENTARY NOTES				
This document provides the basis for development of reactor operators. The examinations developed usi Licenses." The BWR catalog contains approximate senior reactor operators. Each K/A statement has be Supplement 1 to Revision 2 of NUREG-1123 reword added a new K/A topic to Section 4, "Emergency/Abelectric grid disturbances, and corrected other mino	ing this document will cover those topics lister by 7,000 knowledge and ability (K/A) statemed been rated for its importance to safety. It ded and reorganized Section 2, "Generic Known and Plant Evolutions," to address generated the safety and t	d under 10 CFR 55 nts for reactor oper owners.	5, "Operators' rators and	
12. KEY WORDS/DESCRIPTORS (List words or phrases that will assist rese	earchers in locating the report.)		ITY STATEMENT	
operator licensing examinations reactor operator senior reactor operator training task analysis boiling water reactors		14. SECURITY (This Page) un (This Report) un	classified classified classified	
		16. PRICE		

NRC FORM 335 (9-2004)

PRINTED ON RECYCLED PAPER