

## **Residential Construction Post Test**

**On the answer sheet, please fill in the correct answer to the following questions.**

- 1.** A fully enclosed chute shall be used when materials are dropped more than 20 feet to a point outside the building.
  - a. True
  - b. False
  
- 2.** Ground Fault Circuit Interrupters (GFCI) must be used on all 120 volt, single phase, 15 and 20 ampere receptacle outlets.
  - a. True
  - b. False
  
- 3.** The standards regulating fall protection systems used on roofs change at what pitch?
  - a. 4/12
  - b. 5/12
  - c. 8/12
  - d. None of the above
  
- 4.** OSHA's standards require extension ladders be placed at a 4 ½ to 1 ratio.
  - a. True
  - b. False
  
- 5.** A Personal Fall Arrest System (safety harness & lanyard) must have a proper tie off point. That point must be rated at least 5000 pounds.
  - a. True
  - b. False

6. The maximum free fall allowed by OSHA is.
  - a. 4 feet
  - b. 6 feet
  - c. 10 feet
  - d. 12 feet
  
7. Guardrail systems must have an upright member (or standard) every 6 feet.
  - a. True
  - b. False
  
8. Type IA ladders are rated for \_\_\_\_\_ pounds.
  - a. 150
  - b. 200
  - c. 250
  - d. 300
  
9. Steps or stairs of more than 30" in height must have a stair rail or guardrail.
  - a. True
  - b. False
  
10. While placing decking or installing outside walls on the second floor of a residence, workers are exempt from fall protection standards.
  - a. True
  - b. False