

EVALUATED PRODUCTS LIST – DEGAUSSER

INTRODUCTION

1. The EPL (Evaluated Products List)-*Degausser* specifies the current models of commercial equipment that have been evaluated and satisfy NSA/CSS requirements for erasure of magnetic storage devices that retain any classified or sensitive data. Listing of a product on the EPL-Degausser does not constitute endorsement of the product by the USG or NSA/CSS; it only states that the evaluated degausser has met the applicable NSA/CSS performance requirements. Neither does the listing guarantee continued performance: customers that acquire these products should have them re-tested periodically according to the manufacturer's recommendations.

2. Magnetic storage devices are defined in this document by a magnetic property called *coercivity* in units of Oe (*Oersteds*). Degaussers listed in this document are rated by the coercivity of the magnetic storage devices they can securely erase (tape and disk storage devices). Tape storage devices are defined as any product that contains magnetic tape as the recording medium. Disk storage devices are defined as any product that contains a flexible or rigid disk as the recording medium. The correct use of these degausser products will ensure that any classified or sensitive data is irretrievable.

3. Disk storage devices consist of two categories: Longitudinal (L) and Perpendicular (P). These names state how data is stored on a disk storage device, and each requires different magnetic field configurations to erase them. See chart on page 12 for the years of manufacture and coercivities for the different technologies. Degaussers capable of erasing the latest technology tape and disk storage devices are colored in green.

4. Degaussers are ineffective in erasing optical and solid state storage devices. Hybrid magnetic/solid state disk drives contain a magnetic component inside the disk drive housing which can be erased by degaussers and a solid state component on the external circuit board which cannot be erased by degaussers.

NOTE: IN ADDITION TO DEGAUSSING, CERTAIN ADMINISTRATIVE PROCEDURES MAY BE REQUIRED BEFORE DEGAUSSED MAGNETIC STORAGE DEVICES MAY BE DECLASSIFIED. CONSULT YOUR SECURITY OR INFORMATION TECHNOLOGY OFFICER FOR GUIDANCE IN THIS REGARD.

5. Proper use of this equipment is necessary to ensure inadvertent disclosure of classified or sensitive information does not occur. Accordingly, users having operational questions about the equipment should direct their questions to the manufacturer. Questions regarding security requirements should be addressed to your Security or Information Technology Officer.

6. Additional equipment included is a NSA/CSS evaluated magnetic field verification device used to detect and measure a degausser's magnetic field.

7. Companies wishing to submit a product for evaluation or customers that have queries regarding magnetic storage device erasure and/or degaussers should contact:

National Security Agency ATTN: LL43 Media Technology Center, Suite 6877 9800 Savage Road Fort George G. Meade, MD 20755-6877 Voice 301.688.1053, E-mail mtc@nsa.gov

ELECTROMAGNETIC DEGAUSSER EQUIPMENT

8. Tabletop Degaussers: These are electromagnetic tabletop degaussers that provide automatic one pass operation for tape and disk storage device erasure (except where noted). On hard disk drives, all extraneous steel shielding materials (e.g., cabinets, casings, and mounting brackets), but not the hard disk assembly, must be removed before degaussing. The degaussers must be operated at their full magnetic field strength. The erasure of hard disk drives causes damage that prohibits their continued use.

NOTE: ADAPTORS MAY BE NECESSARY TO ACCOMMODATE THE VARIOUS SIZES OF STORAGE DEVICE PRODUCTS.

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Data Devices International 2600 Mission Street San Marino, CA 91108-1676 626.799.6545 ATTN: David Partridge	Cambrian	350	Not Tested
Data Security, Inc. 729 Q Street Lincoln, NE 68508 402.434.5959 800.225.7554 <u>www.datasecurityinc.com</u> ATTN: Renee Schafer <u>rschafer@telesis-inc.com</u>	Туре I, 911-0000	350	Not Tested
Data Security, Inc.	Type HD-2000, 940-0001	750	L-1500
NOTE: FOR DISK ERASURE IN HORIZONTALLY, DEGAUSSED SECOND TIME.	,		

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Data Security, Inc.	Type HD-3000, 905-0001	750	L-1800
NOTE: FOR DISK ERASURE IN HORIZONTALLY, DEGAUSSED SECOND TIME.	THIS MODEL, THE D		
Data Security, Inc.	Type II-A, 930-0000	1000	Not Tested
Data Security, Inc.	Type III, 943-0001	1700	Not Tested
Data Security, Inc.	HD-5T	2800	L-5000 P-5000
Garner Products, Inc. 10620 Industrial Avenue, Suite 100 Roseville, CA 95678 800.624.1903 916.784.0200	2700	350	Not Tested
Garner Products, Inc.	CF750	750	Not Tested
Garner Products, Inc.	TS-1	2800	L-5000 P-5000
Martin Yale Industries 251 Wedcor Avenue Wabash, IN 46992 <u>www.intimus.com</u> ATTN: Greg German 260.569.7226 greg.german@martinyale.com	INTIMUS 20 000	2800	L-5000 P-5000
Proton Engineering, Inc. P.O. Box 1852 Palm City, FL 34991 772.223.1685 ATTN: William Olliges proton@bellsouth.net	T-4	2800	L-5000 P-5000

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
VS and Associates 3160 Texas Hill Road Placerville, CA 95667 530.626.6924 ATTN: Linda Schiro linda.schiro@vssecurityproducts.co	SDD Master	2800	L-5000 P-5000
Whitaker Brothers Business Machines, Inc. 3 Taft Court Rockville, MD 20850 800.243.9226 301.354.3000 www.whitakerbrothers.com ATTN: Lauren Rossi <u>lr@whitakerbrothers.com</u>	Datastroyer 105 Hard Drive Degausser	1 2800	L-5000 P-5000

9. Standalone Degaussers: These are standalone electromagnetic degaussers that provide automatic one pass operation for tape and disk storage device erasure. On hard disk drives, all extraneous steel shielding materials (e.g., cabinets, casings, and mounting brackets), but not the hard disk assembly, must be removed before degaussing. The degaussers must be operated at their full magnetic field strength. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER / DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Data Security, Inc. 729 Q Street Lincoln, NE 68508 402.434.5959 800.225.7554 www.datasecurityinc.com ATTN: Renee Schafer rschafer@telesis-inc.com	HD-6600	2800	L-4200
Data Security, Inc.	HD-1T	2800	L-5000 P-5000

PERMANENT MAGNET DEGAUSSER EQUIPMENT

10. Hand Degaussers: These are hand held permanent magnet degaussers. To degauss disk storage devices, insert the degaussing wand into the disk pack so that the active

magnetic portion completely covers the recording surface of the disk from hub to perimeter. Wipe each active disk surface (top and bottom) at least three times with the magnet. If disks are part of a sealed hard disk drive assembly, they must be removed from the assembly for degaussing. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Applied Magnetics Laboratory, Inc. 1404 Bare Hills Rd. Baltimore, MD 21209 410.583.2100	AML-6KG	Not Tested	L-5000 P-5000
Proton Engineering, Inc. P.O. 1852 Palm City, FL 34991 772.223.1685 ATTN: William Olliges proton@bellsouth.net	1100	Not Tested	L-5000
Whitaker Brothers Business Machines, Inc. 3 Taft Court Rockville, MD 20850 800.243.9226 301.354.3000 www.whitakerbrothers.com ATTN: Lauren Rossi <u>lr@whitakerbrothers.com</u>	Datastroyer 102-DG	Not Tested	L-5000 P-5000

11. Single Pass Slot Hand Degaussers: These are enclosed permanent magnet degaussers that provide automatic one pass operation for tape and disk storage device erasure. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER / DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Applied Magnetics Laboratory, Inc. 1404 Bare Hills Rd. Baltimore, MD 21209 410.583.2100	Magnastroyer AML-MS1	2150	L-750
Applied Magnetics Laboratory, Inc.	Magnastroyer AML-MS2	Not Tested	L-5000 P-5000

12. Dual Pass Slot Hand Degaussers: These are enclosed permanent magnet degaussers. To properly degauss disk storage devices, pass the disk through the entry slot, turn the disk 90 degrees and slide the disk through the slot again. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Proton Engineering, Inc. P.O. Box 1852 Palm City, FL 34991 772.223.1685 ATTN: William Olliges proton@bellsouth.net	1090	Not Tested	L-750

13. Tabletop Degaussers: These are enclosed tabletop permanent magnet degaussers that provide automatic one pass operation for tape and disk storage device erasure (except where noted). On hard disk drives, all extraneous steel shielding materials (e.g., cabinets, casings, and mounting brackets), but not the hard disk assembly, must be removed before degaussing. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Data Security, Inc. 729 Q Street Lincoln, NE 68508 402.434.5959 800.225.7554 <u>www.datasecurityinc.com</u> ATTN: Renee Schafer <u>rschafer@telesis-inc.com</u>	APM-10	2800	L-5000 P-5000
Data Security, Inc.	HPM-1	2800	L-5000 P-5000
Data Security, Inc.	HPM-1A	2800	L-5000 P-5000
Data Security, Inc.	HPM-4	2800	L-5000 P-5000
Data Security, Inc.	HPM-4E	2800	L-5000 P-5000

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK(Oe)		
Garner Products, Inc. 10620 Industrial Avenue, Suite 100 Roseville, CA 95678 800.624.1903 916.784.0200	REM-1400NSA	2800	L-5000 P-5000		
Red River Computer 85 Mechanic Street Lebanon, NH 03766 603.448.8880 <u>www.redriver.com</u> ATTN: Kurt Gantrish	ME-RRC3	2800	L-5000 P-5000		
Red River Computer	ME-RRC3M	2800	L-5000 P-5000		
NOTE: IN THIS DEGAUSSER ERASURE OF LTO-4 AND LTO-5 TAPE STORAGE DEVICES REQUIRES AN ADDITIONAL STEP FOR SECURE ERASURE; AFTER THE FIRST ERASURE PASS, REMOVE THE TAPE CARTRIDGE, ROTATE THE CARTRIDGE 90 DEGREES, REPLACE IN THE TRAY, AND ERASE A SECOND TIME.					
Security Engineered Machinery/ Toshiba 4720 Boston Way, Suite Q Lanham, MD 20706 800.645.1157 301.735.7100 ATTN: Terry Creek	ME-P3	2800	L-5000 P-5000		
Security Engineered Machinery/ Toshiba NOTE: IN THIS DEGAUSSER ER DEVICES REQUIRES AN ADDIT THE FIRST ERASURE PASS, REM CARTRIDGE 90 DEGREES, REPL TIME.	IONAL STEP FOR SE MOVE THE TAPE CA	ECURE ERASU RTRIDGE, RO	JRE; AFTER DTATE THE		
Security Engineered Machinery/ Toshiba	ME-P3E	2800	L-5000 P-5000		

MANUFACTURER/	MODEL	TAPE (Oe)	DISK(Oe)
DISTRIBUTOR			

Security Engineered Machinery/ ME-P3M 2800 L-5000 Toshiba P-5000 NOTE: IN THIS DEGAUSSER ERASURE OF LTO-4 AND LTO-5 TAPE STORAGE DEVICES REQUIRES AN ADDITIONAL STEP FOR SECURE ERASURE; AFTER THE FIRST ERASURE PASS, REMOVE THE TAPE CARTRIDGE, ROTATE THE CARTRIDGE 90 DEGREES, REPLACE IN THE TRAY, AND ERASE A SECOND TIME.

14. Conveyor Degaussers: These are enclosed permanent magnet degaussers that are continuous duty conveyor belt types and provide one pass erasure for tape and disk storage devices. On hard disk drives, all extraneous steel shielding materials (e.g., cabinets, casings, and mounting brackets), but not the hard disk assembly, must be removed before degaussing. The erasure of hard disk drives causes damage that prohibits their continued use.

MANUFACTURER/ DISTRIBUTOR	MODEL	TAPE (Oe)	DISK (Oe)
Data Security, Inc. 729 Q Street Lincoln, NE 68508 402.434.5959 800.225.7554 <u>www.datasecurityinc.com</u> ATTN: Renee Schafer <u>rschafer@telesis-inc.com</u>	LM-4	2800	L-5000 P-5000
Data Security, Inc.	LM-4E	2800	L-5000 P-5000
Dexter Magnetic Technologies 400 Karin Lane Hicksville, NY 11801 908.668.4821 ATTN: Thomas Devaney	U5000	2800	L-5000 P-5000

DEGAUSSER MAGNETIC FIELD VERIFICATION DEVICE

MANUFACTURER

MODEL

Data Security, Inc. 729 Q Street Lincoln, NE 68508 402.434.5959 800.225.7554 www.datasecurityinc.com ATTN: Renee Schafer rschafer@telesis-inc.com Field CheckR

DEGAUSSERS NO LONGER MANUFACTURED

MANUFACTURER	MODEL	TAPE (Oe)	DISK (Oe)
Ampex Corporation	SE20	350	Not Tested
Ampex Corporation	SE750	750	Not Tested
Applied Magnetics Laboratory, Inc.	Data Muncher	Not Tested	L-350
Bell & Howell Company	TD-2903-4B	350	Not Tested
CMC Technology Corporation	TD-800	350	Not Tested
Computer Link Corporation	CF750	750	Not Tested
Computer Link Corporation	515	350	Not Tested
Computer Link Corporation	520	350	Not Tested
Computer Link Corporation	530	350	Not Tested
Computer Link Corporation	538	350	Not Tested
Computer Link Corporation	540	350	Not Tested
Consolidated Electrodynamics	TD-2903-4A	350	Not Tested
Data Security, Inc.	HD-6000	2500	L-3800
Data Security, Inc.	Type II, 900-0001	750	Not Tested
Data Security, Inc.	Type II, 902-0001	750	L-1800
Datatape, Incorporated	HDD-2000	750	L-1500
Datatape, Incorporated	TD-1700	1700	Not Tested
Datatape, Incorporated	TD-2903-4B	350	Not Tested
Datatape, Incorporated	TD-350	350	Not Tested
Datatape, Incorporated	TD-500	350	Not Tested
Datatape, Incorporated	TD-750	750	L-1800
Datatape, Incorporated	TD-900	900	L-1800
Electro-Matic Products Company	2PTFB15-17	350	Not Tested
Electro-Matic Products Company	2PTFB15-18	350	Not Tested
Electro-Matic Products Company	2PTFB15-113	350	Not Tested
Electro-Matic Products Company	HE15FB-4	750	Not Tested
General Kinetics Incorporated	K80	350	Not Tested
General Kinetics Incorporated	K90	350	Not Tested
Hewlett Packard Company	3603A	350	Not Tested
Integra Technologies Corporation	D530	350	Not Tested

MANUFACTURER	MODEL	TAPE (Oe)	DISK (Oe)
Integra Technologies Corporation	D538	350	Not Tested
Integra Technologies Corporation	D538-II	750	Not Tested
Integra Technologies Corporation	D540	350	Not Tested
Integra Technologies Corporation	I600-F4	Not Tested	L-350
IXI, Incorporated	5661C	350	L-2200
J.C. Nickels, Incorporated	1084 Bit Scrubber	Not Tested	L-350
KYBE Corporation	1100	350	Not Tested
Metrum-Datatape	HDD-2000	750	L-1500
Metrum-Datatape	TD-1700	1700	Not Tested
Metrum-Datatape	TD-350	350	Not Tested
Metrum-Datatape	TD-750	750	L-1800
Metrum-Datatape	TD-900	900	L-1800
Precision Methods, Incorporated	2000	Not Tested	L-350
Proton Engineering, Inc.	1084	Not Tested	L-350
Rimage Corporation	5661C	350	L-2200

DEFINITIONS

15. Coercive Force – A negative or reverse magnetic force applied for the purpose of reducing magnetic flux density.

16. Coercivity – A property of magnetic material, measured in Oersteds, used as a measure of the amount of *coercive force* required to reduce the magnetic induction to zero from its remanent state. Generally used as a measure of difficulty with which magnetic storage devices can be degaussed.

17. Degausser – An electrical device or permanent magnet assembly which generates a coercive magnetic force for the purpose of degaussing magnetic storage devices or other magnetic material.

18. Degaussing (or Demagnetizing) – Process for reducing the magnetization of a magnetic storage device to zero by applying a reverse (coercive) magnetizing force, rendering any previously stored data unreadable and unintelligible, and ensuring that it cannot be recovered by any technology known to exist.

19. Oersted (Oe) – The unit of measure of a magnetic field.

COERCIVITIES

Magnetic Storage Device	Oe
9-Track Reel-to-Reel Computer tape	300
TK50, TK70	350
3480, 3490E	520
SLR1, SLR2, TR-1, DC2120, DC6150, DC6525	550
SLR3, SLR4, SLR5, TR-3, DC9100, DC9120, ID-1, SLR24, SLR32, TR-4,	900

Magnetic Storage Device	Oe
ADR30, ADR50, ADR2-120	
Mammoth 8mm, AIT-1 8mm, VXA-1 8mm	1320
M2 Mammoth2 8mm, VXA-2 8mm 230m	
AIT-2 8mm	1380
AIT-3 8mm, AIT-4 8mm, S-AIT-1 1/2"	1400
Redwood SD-3	1515
DLTtape III, DLTtape IIIXT	1540
DD-2 19mm	1550
DTF-1	1579
DDS1: 4mm60m, 4mm90m	1590
D8: 8mm 112m, 8mm 160m	1600
MagstarMP: 3570-B, 3570-C, 3570-C/XL, Magstar: 3590, 3590-E, STK-9840,	1625
STK-T9940	
TR-5, SLR40, SLR50, SLR60, SLR100, TR-7 (Travan 40 GB), SLR75, SLR140	1650
DDS2 4mm 120m	1750
DLTtape IV, DLTtape VS1, NCTP, DD-2QD (Quad Density) 19mm, LTO-	1850
Ultrium1	
SuperDLTtape1	1900
LTO-Ultrium2	2150
DDS3 4mm 125m	2250
DTF-2	2300
DDS4 4mm 150m, DAT-72 4mm 170m	2350
Enterprise 3592, STK-T10000 (T10K)	2500
Super DLTtape II	2600
DLTtape S4, LTO-Ultrium3	2650
LTO-4	2800
LTO-5	2800
5 ¼" 360KB DD Minidisk	300
3.5" 720KB DD Microdisk, 5 ¼" 1.2MB HD Minidisk	650
3.5" 1.44MB HD Microdisk	720
SuperDisk 120MB	1500
Zip 100 MB Disk	1550
Zip 250 MB Disk, Zip 750 MB Disk	2250

