

Table A3. Approximate Heat Content of Petroleum Consumption and Biofuels Production, Selected Years, 1949-2011
 (Million Btu per Barrel)

Year	Total Petroleum ¹ Consumption by Sector						Liquefied Petroleum Gases Consumption ⁶	Motor Gasoline Consumption ⁷	Fuel Ethanol ⁸	Fuel Ethanol Feedstock Factor ⁹	Biodiesel	Biodiesel Feedstock Factor ¹⁰
	Residential	Commercial ²	Industrial ²	Trans- portation ^{2,3}	Electric Power ^{4,5}	Total ²						
1949	5.484	5.813	5.957	5.465	6.254	5.649	4.011	5.253	NA	NA	NA	NA
1950	5.473	5.817	5.953	5.461	6.254	5.649	4.011	5.253	NA	NA	NA	NA
1955	5.469	5.781	5.881	5.407	6.254	5.591	4.011	5.253	NA	NA	NA	NA
1960	5.417	5.781	5.818	5.387	6.267	5.555	4.011	5.253	NA	NA	NA	NA
1965	5.364	5.760	5.748	5.386	6.267	5.532	4.011	5.253	NA	NA	NA	NA
1970	5.260	5.708	5.595	5.393	6.252	5.503	63.779	5.253	NA	NA	NA	NA
1975	5.253	5.649	5.513	5.392	6.250	5.494	3.715	5.253	NA	NA	NA	NA
1976	5.277	5.672	5.523	5.396	6.251	5.504	3.711	5.253	NA	NA	NA	NA
1977	5.285	5.682	5.539	5.401	6.249	5.518	3.677	5.253	NA	NA	NA	NA
1978	5.287	5.665	5.536	5.405	6.251	5.519	3.669	5.253	NA	NA	NA	NA
1979	5.365	5.717	5.409	5.429	6.258	5.494	3.680	5.253	NA	NA	NA	NA
1980	5.321	5.751	5.366	5.441	6.254	5.479	3.674	5.253	3.563	6.586	NA	NA
1981	5.283	5.693	5.299	5.433	6.258	5.448	3.643	5.253	3.563	6.562	NA	NA
1982	5.266	5.698	5.247	5.423	6.258	5.415	3.615	5.253	3.563	6.539	NA	NA
1983	5.140	5.591	5.254	5.416	6.255	5.406	3.614	5.253	3.563	6.515	NA	NA
1984	5.307	5.657	5.207	5.418	6.251	5.395	3.599	5.253	3.563	6.492	NA	NA
1985	5.263	5.598	5.199	5.423	6.247	5.387	3.603	5.253	3.563	6.469	NA	NA
1986	5.268	5.632	5.269	5.426	6.257	5.418	3.640	5.253	3.563	6.446	NA	NA
1987	5.239	5.594	5.233	5.429	6.249	5.403	3.659	5.253	3.563	6.423	NA	NA
1988	5.257	5.597	5.228	5.433	6.250	5.410	3.652	5.253	3.563	6.400	NA	NA
1989	5.194	5.549	5.219	5.438	6.240	5.410	3.683	5.253	3.563	6.377	NA	NA
1990	5.145	5.553	5.253	5.442	6.244	5.411	3.625	5.253	3.563	6.355	NA	NA
1991	5.094	5.528	5.167	5.441	6.246	5.384	3.614	5.253	3.563	6.332	NA	NA
1992	5.124	5.513	5.168	5.443	6.238	5.378	3.624	5.253	3.563	6.309	NA	NA
1993	5.102	25.505	25.178	25.436	6.230	25.379	3.606	5.253	3.563	6.287	NA	NA
1994	5.098	5.515	5.150	5.424	6.213	5.361	3.635	75.230	3.563	6.264	NA	NA
1995	5.063	5.478	5.121	5.417	6.188	5.341	3.623	5.215	3.563	6.242	NA	NA
1996	4.998	5.433	5.114	5.420	6.195	5.336	3.613	5.216	3.563	6.220	NA	NA
1997	4.989	5.391	5.120	5.416	6.199	5.336	3.616	5.213	3.563	6.198	NA	NA
1998	4.975	5.365	5.137	5.413	6.210	5.349	3.614	5.212	3.563	6.176	NA	NA
1999	4.902	5.291	5.092	5.413	6.205	5.328	3.616	5.211	3.563	6.167	NA	NA
2000	4.908	5.316	5.057	5.422	6.189	5.326	3.607	5.210	3.563	6.159	NA	NA
2001	4.937	5.325	5.142	5.412	6.199	5.345	3.614	5.210	3.563	6.151	5.359	5.433
2002	4.886	5.293	5.093	5.411	6.173	5.324	3.613	5.208	3.563	6.143	5.359	5.433
2003	4.907	5.307	5.142	5.409	6.182	5.340	3.629	5.207	3.563	6.116	5.359	5.433
2004	4.953	5.328	5.144	5.421	6.192	5.350	3.618	5.215	3.563	6.089	5.359	5.433
2005	4.916	5.364	5.178	5.427	6.188	5.365	3.620	5.218	3.563	6.063	5.359	5.433
2006	4.894	5.310	5.160	5.431	6.143	5.353	3.605	5.218	3.563	6.036	5.359	5.433
2007	4.850	5.298	5.127	5.434	6.151	5.346	3.591	5.219	3.563	6.009	5.359	5.433
2008	4.732	5.175	5.149	5.426	6.123	5.339	3.600	5.218	3.563	5.983	5.359	5.433
2009	4.691	5.266	5.018	35.414	6.105	35.301	3.558	5.218	3.563	5.957	5.359	5.433
2010	R4.692	R5.263	R4.988	R5.421	R6.084	R5.297	R3.557	5.218	3.561	R5.931	5.359	5.433
2011	E4.692	E5.261	E4.964	E5.425	E6.062	E5.291	E3.529	E5.218	E3.560	E5.905	5.359	5.433

¹ Petroleum products supplied, including natural gas plant liquids and crude oil burned directly as fuel. Quantity-weighted averages of the petroleum products included in each category are calculated by using heat content values shown in Table A1.

² Beginning in 1993, includes fuel ethanol blended into motor gasoline.

³ Beginning in 2009, includes renewable diesel fuel (including biodiesel) blended into distillate fuel oil.

⁴ Electricity-only and combined-heat-and-power (CHP) plants within the NAICS 22 category whose primary business is to sell electricity, or electricity and heat, to the public. Through 1988, data are for electric utilities only; beginning in 1989, data are for electric utilities and independent power producers.

⁵ Electric power sector factors are weighted average heat contents for distillate fuel oil, petroleum coke, and residual fuel oil; they exclude other liquids.

⁶ There is a discontinuity in this time series between 1966 and 1967; beginning in 1967, the single constant factor is replaced by a quantity-weighted factor—quantity-weighted averages of the major components of liquefied petroleum gases are calculated by using heat content values shown in Table A1.

⁷ There is a discontinuity in this time series between 1993 and 1994; beginning in 1994, the single constant factor is replaced by a quantity-weighted factor—quantity-weighted averages of the major components of motor gasoline, including fuel ethanol, are calculated by using heat content values shown in Table A1.

⁸ Includes denaturant (petroleum added to ethanol to make it undrinkable). Fuel ethanol factors are weighted average heat contents for undenatured ethanol (3.539 million Btu per barrel), pentanes plus used as denaturant (4.620 million Btu per barrel), and conventional motor gasoline and motor gasoline blending components used as denaturant (5.253 million Btu per barrel). The factor for 2009 is used as the estimated

factor for 1980–2008.

⁹ Corn input to the production of undenatured ethanol (million Btu corn per barrel undenatured ethanol), used as the factor to estimate total biomass inputs to the production of undenatured ethanol. Observed ethanol yields (gallons undenatured ethanol per bushel of corn) are 2.5 in 1980, 2.666 in 1998, 2.68 in 2002, and 2.764 in 2009; yields in other years are estimated. Corn is assumed to have a gross heat content of 0.392 million Btu per bushel. Undenatured ethanol is assumed to have a gross heat content of 3.539 million Btu per barrel.

¹⁰ Soybean oil input to the production of biodiesel (million Btu soybean oil per barrel biodiesel), used as the factor to estimate total biomass inputs to the production of biodiesel. It is assumed that 7.65 pounds of soybean oil are needed to produce one gallon of biodiesel, and 5.433 million Btu of soybean oil are needed to produce one barrel of biodiesel. Soybean oil is assumed to have a gross heat content of 16,909 Btu per pound, or 5,483 million Btu per barrel. Biodiesel is assumed to have a gross heat content of 17,253 Btu per pound, or 5,359 million Btu per barrel.

R=Revised. P=Preliminary. E=Estimate. NA=Not available.

Notes: • Residential, commercial, industrial, and transportation petroleum heat contents are revised beginning in 1949 due to a change in the estimation methodology. • The heat content values in this table are for gross heat contents. See "Heat Content" in Glossary.

Web Pages: • See <http://www.eia.gov/totalenergy/data/monthly/#appendices> for updated annual conversion factors. • See <http://www.eia.gov/totalenergy/data/annual/#appendices> for all annual data beginning in 1949.

Sources: See "Thermal Conversion Factor Source Documentation," which follows Table A6.