


**WEST BANK OF THE MISSISSIPPI RIVER  
IN THE VICINITY OF NEW ORLEANS, LA  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT**

**DESIGN MEMORANDUM NO. 2  
EAST AND WEST OF  
ALGIERS CANAL**

**IN TWO VOLUMES  
VOLUME 2**



**DEPARTMENT OF THE ARMY  
NEW ORLEANS DISTRICT, CORPS OF ENGINEERS  
NEW ORLEANS, LOUISISANA  
JANUARY 1999**

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY  
OF NEW ORLEANS, LOUISIANA  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
DESIGN MEMORANDUM NO. 2  
EAST AND WEST OF ALGIERS CANAL

TABLE OF CONTENTS

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
PROJECT AUTHORIZATION		
1	Authority	1
2	Purpose and Scope	1
3	Other Pertinent Projects	1
	a. Mississippi River Levees	1
	b. Algiers Lock and Canal	2
	c. Westwego to Harvey	2
4	Local Cooperation	2
5	Status of Local Cooperation	2
6	Project Document Investigation	2
	a. General	2
	b. Future investigations required	3
LOCATION OF PROJECT AND TRIBUTARY AREA		
7	Project Location	3
PROJECT PLAN		
8	General	3
HYDROLOGY AND HYDRAULICS		
9	General	4
10	Design Hurricane	4
11	Design Heights of Protected Structures	4
SOILS AND FOUNDATIONS INVESTIGATION AND DESIGN		
12	General	4

## TABLE OF CONTENTS (CONT'D)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
13	Field Exploration	5
14	Laboratory Tests	5
15	Description of Subsoil Conditions	5
	a. Geology	5
	b. Topography	5
	c. Stratigraphy	6
	d. Design Soil Parameters	6
16	Levee Analyses	6
	a. Levee Stability	6
	b. Settlement of Levees	7
17	Earth Ramp Analyses	8
	a. Levee Stability	8
	b. Settlement of Ramp Areas	8
18	I-Wall Analyses	9
	a. Cantilever Analyses	9
	b. Seepage	9
	c. Minimum Penetration	9
19	Floodgates/T-Walls	9
	a. Stability	9
	b. Seepage	10
	c. Allowable Pile Load Capacity	10
20	Pump Station	10
	a. General	10
	b. Additional Borings	10
	c. Stability	10
	d. Slope Stability and New T-Wall Analysis	11
	e. Seepage Analyses	11
21	Pile Foundation	11
	a. Allowable Pile Load capacity	11
	b. Horizontal Support	11
	c. Pile Group Effects	12
	d. Pile Driving	12
	e. Predrilling	12
	f. Driving Stresses	12
	g. Test Piles	12
	h. Load Tests	12
	i. Dynamic Pile Tests	12

## TABLE OF CONTENTS (CONT'D)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
DESCRIPTION OF PROPOSED STRUCTURES AND IMPROVEMENTS		
22	Levees	13
METHOD OF CONSTRUCTION		
23	Recommended Levee Construction	13
OTHER LEVEE PLANS CONSIDERED		
24	Alternative Levee Plans Considered	13
ACCESS ROADS		
25	Access Roads	13
RELOCATIONS		
26	Relocations	14
RAMPS		
27	Ramps	15
DESCRIPTION OF PROPOSED FLOODWALLS AND GATES		
28	Floodwalls and Gates	16
	a. Floodwalls	16
	b. Gates	17
PUMP STATION FRONTAL PROTECTION		
29	General	17
30	Belle Chasse Pump Station No. 2	17
31	Planters Pump Station	18
32	Sewerage & Water Board Pump Station No. 11	18
33	Sewerage & Water Board Pump Station No. 13	18
34	Plaquemines Pump Station (Belle Chasse No. 1)	19

## TABLE OF CONTENTS (CONT'D)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
<b>PUMP STATION BACK FLOW PROTECTION</b>		
35	Belle Chasse Pump Station No. 2	19
36	Planters Pump Station	20
37	Sewerage & Water Board Pump Station No. 11	22
38	Sewerage & Water Board Pump Station No. 13	24
39	Plaquemines Pump Station (Belle Chasse No. 1)	26
<b>STRUCTURAL DESIGN</b>		
40	Criteria for Structural Design	29
41	Basic Data	29
	a. Water Elevation	29
	b. Levee and Floodwall Net Grades	29
42	Design Methods	30
	a. Reinforced Concrete	30
43	I-Type Floodwalls	30
	a. General	30
	b. Loading Cases	30
	c. Joints	31
44	T-Type Floodwalls	31
	a. General	31
	b. Loading Cases	31
	c. Joints	31
45	Swing Gates and Gate Monoliths	31
	a. General	31
	b. Loading Cases	32
46	Cathodic Protection and Corrosion Control	32
	a. Cathodic Protection for Steel Sheet Piling	32
	b. Corrosion Control	32
<b>ENVIRONMENTAL EFFECTS</b>		
47	Environmental Assessment	33
	a. General	33
	b. Recreation	33
48	Mitigation	33
49	Hazardous, Toxic and Radioactive Wastes	33

## TABLE OF CONTENTS (CONT'D)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
50	Status of Environmental Compliance	34
	a. National Environmental Policy Act	34
	b. Clean Water Act	34
	c. Coastal Zone Management Act	34
	d. National Historic Preservation Act	34
REAL ESTATE REQUIREMENTS		
51	General	34
OPERATION AND MAINTENANCE		
52	Operation And Maintenance	35
	a. General	35
	b. Mitigation Feature	35
ESTIMATE OF INCREMENTAL COSTS		
53	General	36
54	Schedule for Design and Construction	37
55	Funds Required by Fiscal Year	37
56	Recommendations	38

### TABLES

<u>No.</u>	<u>Title</u>	<u>Page</u>
1	Consolidation Settlement	7
2	Utility Relocation Schedule	14
3	Ramp Schedule	15
4	Planters Pumping Station Minimum Seal Water Elevation for Air Suppression	20
5	Sewerage & Water Board Pumping Station No.11 Minimum Seal Water Elevations for Air Suppression	22

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>	<u>Page</u>
6	Sewerage and Water Board Pumping Station No. 13 Minimum Seal Water Elevation for Air Suppression	24
7	Plaquemines Pumping Station Existing Pump Information	26
8	Relevant Structural Design Data	29
9	Pertinent Stresses for Reinforced Concrete Design	30
10	Schedule for Design and Construction	37
11	Funds Required by Fiscal Year	38

## PLATES

<u>No.</u>	<u>Title</u>
1	Project Location and Vicinity Map
2	East Levee Plan and Profile Sta. 318+07.16 to Sta. 367+50.00
3	East Levee Plan and Profile Sta. 367+50.00 to Sta. 423+50.00
4	East Levee Plan and Profile Sta. 423+50.00 to Sta. 479+00.00
5	East Levee Plan and Profile Sta. 479+00.00 to Sta. 544+00.00
6	East Levee Plan and Profile Sta. 544+00.00 to Sta. 599+00.00
7	East Levee Plan and Profile Sta. 599+00.00 to Sta. 655+50.00
8	East Levee Plan and Profile Sta. 655+50.00 to Sta. 712+50.00
9	East Levee Plan and Profile Sta. 712+50.00 to Sta. 769+16.36
10	East Levee Plan and Profile Sta. 769+16.36 to Sta. 828+50.00

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
11	West Levee Plan and Profile Sta. 828+50.00 to Sta. 893+50.00
12	West Levee Plan and Profile Sta. 893+50.00 to Sta. 955+00.00
13	West Levee Plan and Profile Sta. 955+00.00 to Sta. 1018+50.00
14	West Levee Plan and Profile Sta. 1018+50.00 to Sta. 1071+00.00
15	West Levee Plan and Profile Sta. 1071+00.00 to Sta. 1125+50.00
16	West Levee Plan and Profile Sta. 1125+50.00 to Sta. 1181+50.00
17	West Levee Plan and Profile Sta. 1181+50.00 to Sta. 1230+43.21
18	Belle Chasse Pump Station No. 2 Plan
19	Belle Chasse Pump Station No. 2 Frontal Protection Profile
20	Belle Chasse Pump Station No. 2 Section Thru Station
21	Belle Chasse Pump Station No. 2 Frontal Protection T-Wall Details
22	Plaquemines Pump Station Plan
23	Plaquemines Pump Station Plan
24	Plaquemines Pump Station Frontal Protection Profile
25	Plaquemines Pump Station Section Thru Original Station
26	Plaquemines Pump Station Section Thru Pump Station Addition
27	Plaquemines Pump Station T-Wall Details
28	Planters Pump Station Plan
29	Planters Pump Station Foundation Plan
30	Planters Pump Station Frontal Protection Profile



## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
31	Planters Pump Station Section Thru Original Pump Station
32	Planters Pump Station Section Thru Pump Station Addition
33	Planters Pump Station T-Wall Details
34	NOS&WB No. 11 Pump Station Plan
35	NOS&WB No. 11 Pump Station Foundation Plan
36	NOS&WB No. 11 Pump Station Frontal Protection Profile
37	NOS&WB No. 11 Pump Station Section Thru Original Station
38	NOS&WB No. 11 Pump Station Section Thru Station Addition
39	NOS&WB No. 11 Pump Station T-Wall Details
40	NOS&WB No. 11 Pump Station Discharge Tube Details
41	NOS&WB No. 13 Pump Station Plan
42	NOS&WB No. 13 Pump Station Section Thru Original Station
43	NOS&WB No. 13 Pump Station Section Thru Station Addition
44	Typical Levee Sections (Sheet 1 of 3)
45	Typical Levee Sections (Sheet 2 of 3)
46	Typical Levee Sections (Sheet 3 of 3)
47	Gates 1 thru 4 (Profile)
48	Gates 5, 6, 7 & 10 (Profile)
49	Gates 8, 9, 11 & 12 (Profile)
50	Gates 13, 14, 15 & 16 (Profile)

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
51	Typical Floodwall/Floodgate Sections
52	Typical Wall Joint (Sheet 1 of 2)
53	Typical Wall Joint (Sheet 2 of 2)
54	Typical Swing Gate
55	Swing Gate Upper Hinge Details
56	Swing Gate Lower Hinge Details
57	Hinge Details
58	Swing Gate Seal
59	Latching Details
60	Details of Utility Penetrations
61	Utility Crossing - South Central Bell
62	Typical Ramp Plan & Profiles
F-1	Soil Boring Location Plan
F-2	Subsoil Profile "A-A"
F-3	Subsoil Profile "A-A"
F-4	Subsoil Profile "B-B"
F-5	Subsoil Profile "B-B"
F-6	Design Soil Parameters Reaches 1 & 2
F-7	Design Soil Parameters Reaches 3 & 4

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
F-8	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 1 Westbank
F-9	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 1 Westbank
F-10	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 1 Eastbank
F-11	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 1 Eastbank
F-12	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 2 Westbank
F-13	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 2 Westbank
F-14	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 2 Eastbank
F-15	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 2 Eastbank
F-16	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 3 Westbank
F-17	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 3 Westbank
F-18	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 3 Eastbank
F-19	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 3 Eastbank
F-20	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 4 Westbank

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
F-21	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 4 Westbank
F-22	Slope Stability Analysis of Raised Levee Due to Storm Water Level Reach 4 Eastbank
F-23	Slope Stability Analysis of Raised Levee Toward Canal at Low Water Reach 4 Eastbank
F-24	Slope Stability Analysis of Ramp on One Side of Levee Reach 1
F-25	Slope Stability Analysis of Ramp on One Side of Levee Reach 2
F-26	Slope Stability Analysis of Ramp on One Side of Levee Reach 3
F-27	Slope Stability Analysis of Ramp on One Side of Levee Reach 4
F-28	Slope Stability Analysis of Ramp Toward Canal at Low Water Reach 1
F-29	Slope Stability Analysis of Ramp Toward Canal at Low Water Reach 2
F-30	Slope Stability Analysis of Ramp Toward Canal at Low Water Reach 3
F-31	Slope Stability Analysis of Ramp Toward Canal at Low Water Reach 4
F-32	Slope Stability Analysis and I-Wall Design - Reach 2 - Westbank
F-32a	Replacement I-wall Design at Discharge of Modified Belle Chasse Pump Station No. 2
F-33	I-Wall Design Near Floodgates - Reaches 1 &2

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
F-34	I-Wall Design Near Floodgates - Reaches 3 & 4
F-35	Floodgate/T-Wall Analysis - Reach 1
F-36	Floodgate/T-Wall Analysis - Reach 2
F-37	Floodgate/T-Wall Analysis - Reach 3
F-38	Floodgate/T-Wall Analysis - Reach 4
F-39	Slope Stability Analyses Belle Chasse Pump Station No.2
F-40	Slope Stability Analyses of Units 1 Through 5 Planters Pump Station
F-41	Slope Stability Analyses of Units 6 Through 9 Planters Pump Station
F-42	Slope Stability Analyses Plaquemines Pump Station
F-43	Slope Stability Analyses Addition to Plaquemines Pump Station
F-44	Slope Stability Analyses N.O. S&WB Pump No. 11 West
F-45	Slope Stability Analyses of N.O. S&WB Station No. 11 East
F-46	Slope Stability Analyses of East Units 1 Through 3 N.O. S&WB Pump Station No. 13
F-47	Slope Stability Analyses of East Units 4 Through 7 N.O. S&WB Pump Station No. 13
F-48	Slope Stability/T-Wall Analyses Modified Belle Chasse Pump Station No. 2
F-49	Slope Stability/T-Wall Analyses Modified Units 1 Through 5 Planters Pump Station
F-50	Slope Stability/T-Wall Analyses Modified Units 6 Through 9 Planters Pump Station

## TABLE OF CONTENTS (CONT'D)

<u>No.</u>	<u>Title</u>
F-51	Slope Stability/T-Wall Analyses Modified Plaquemines Pump Station
F-52	Slope Stability/T-Wall Analyses Modified Addition to Plaquemines Pump Station
F-53	Slope Stability/T-Wall Analyses Modified N.O. S&WB Pump Station 11 West
F-54	Slope Stability/T-Wall Analyses Modified N.O. S&WB Pump Station 11 East
F-55	Floodgate/T-Wall Structures - Reaches 1&2
F-56	Floodgate/T-Wall Structures - Reaches 3 & 4
F-57	T-Wall Foundation Allowable Pile Load Capacities
F-58	T-Wall Foundation Allowable Pile Load Capacities
F-59	T-Wall Foundation Allowable Pile Load Capacities
F-60	Axial and Horizontal Resistance of Batter Piles
F-61	Modulus of Horizontal Subgrade Reaction
F-62	Modulus of Horizontal Subgrade Reaction
F-63	Capacity of Pile Groups And Pile Spacing

## APPENDIX

### VOLUME 1

A	Detailed Cost Estimate
---	------------------------

TABLE OF CONTENTS (CONT'D)

VOLUME 2

F-I	Geotechnical Boring Logs and Laboratory Data
F-II	Geotechnical Computer Data
B	Design Calculations

**WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF  
NEW ORLEANS, LA  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
DESIGN MEMORANDUM NO. 2  
EAST AND WEST OF ALGIERS CANAL**

**APPENDIX F-I**

**GEOTECHNICAL BORING LOGS AND  
LABORATORY DATA**



APPENDIX F-I





BORING LOGS AND LABORATORY TEST DATA



## LEGEND AND NOTES FOR LOG OF BORING AND TEST RESULTS

PP Pocket penetrometer resistance in tons per square foot  
TV Torvane shear strength in tons per square foot  
SPT Standard Penetration Test. Number of blows of a 140-lb. hammer dropped 30 inches required to drive 2-in O.D., 1.4-in. I.D. sampler a distance of one foot into the soil, after first seating it 6 inches

SPLR Type of Sampling  Shelby  SPT  Auger  No Sample

SYMBOL Clay Silt Sand Humus Predominant type shown heavy;  
Modifying type shown light  
   

DENSITY Unit weight in pounds per cubic foot

USC Unified Soil Classification

TYPE UC Unconfined compression shear  
OB Unconsolidated undrained triaxial compression shear on one specimen confined at the approximate overburden pressure  
UU Unconsolidated undrained triaxial compression shear  
CU Consolidated undrained triaxial compression shear  
DS Direct shear  
CON Consolidation  
PD Particle size distribution  
k Coefficient of permeability in centimeters per second  
SP Swelling pressure in pounds per square foot

$\phi$  Angle of internal friction in degrees

c Cohesion in pounds per square foot

Other laboratory test results reported on separate figure

Ground Water Measurements  Initial  Final

### GENERAL NOTES

- (1) At the time the borings were made, ground water levels were measured below existing ground surface. These observations are shown on the boring logs. However, ground water levels may vary due to seasonal and other factors. If important to construction, the depth to ground water should be determined by those persons responsible for construction, immediately prior to beginning work.
- (2) While the individual logs of borings are considered to be representative of subsurface conditions at their respective locations on the dates shown, it is not warranted that they are representative of subsurface conditions at other locations and times.

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.69 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/15/96 Boring: ALGE1 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff brown silty clay w/roots, shells, & organic matter	CL	1	0	30									
1.25					Stiff gray & tan clay w/organic matter & clayey silt lenses	CH	2	1.5	44									
1.00					w/silty sand lenses & layers	SC	3	4	50									
0.60					Medium dense tan & gray clayey sand		4	6.5	28									
10					Soft gray clay w/sandy silt lenses & layers, organic matter, & small roots	CH	5	9	49									
0.50					Soft gray silty clay w/roots	CL	6	11.5	36									
0.50					w/small roots & silty sand lenses		7	14	34									
0.50					Soft gray clay w/sandy silt lenses & few roots	CH	8	16.5	36									
20							9	19	120									
0.50					Medium stiff gray clay w/clayey silt lenses & layers, & trace of wood	CH	10	21.5	96									
0.50					Soft gray clay w/trace of small roots, clayey silt lenses, & few shell fragments	CH	11	24	74									
0.50					w/shells, clayey silt lenses & layers, & organic matter		12	26.5	79									
30					w/organic matter & clayey silt pockets & lenses		13	29	57									
0.50					w/clayey silt lenses, layers, & pockets		14	31.5	46									
0.50					Loose gray sandy silt w/silty sand layers	ML	15	34	25									
4					Loose gray fine sand w/sandy silt & clayey silt layers	SP	16	37	27									
40					Loose gray silty sand w/few small clay lenses	SM	17	39	26									
0.50					w/clay lenses & pockets		18	41.5	33									
0.50					Medium dense gray silty sand w/clay layers	SM	19	44	29									
0.50					Soft gray silty clay w/silt lenses & trace of wood	CL	20	46.5	31									
50					w/few silt lenses & wood		21	49	40									

Comments: Coordinates: North 484688.370, East 3685189.805

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.69 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/15/96 Boring: ALGE1 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50	0.50				Soft gray clay w/silty sand lenses & layers	CH	22	51.5-52.5	57										
	0.50						23	54-55	44										
	0.50						24	56.5-57.5	45										
60	0.50					w/silt lenses		25	59-60	55									
	0.50							26	61.5-62.5	61									
	0.50							27	64-65	55									
	0.50							28	66.5-67.5	56									
70	0.50							29	69-70	63									
	0.50							30	71.5-72.5	57									
	0.60					Medium stiff gray clay w/clayey silt lenses	CH	31	74-75	55									
	0.50				Soft gray clay w/shell fragments, & clayey sand pockets & lenses	CH	32	76.5-77.5	37										
80	0.50						33	79-80	36										
90																			
100																			

Comments: Coordinates: North 484688.370, East 3685189.805

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -0.73 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/14/96 Boring: ALGE2 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
0				Stiff brown & tan clay w/organic matter & roots	CH	1	0-1	31										
1.50				Stiff gray & tan clay w/silt lenses, pockets, & organic matter	CH	2	1.5-2.5	58										
1.00				Medium stiff gray clay w/clayey silt pockets & roots	CH	3	4-5	114										
0.40				Soft gray clay w/clayey silt & silty sand layers	CH	4	6.5-7.5	29										
10				w/shells & alternating silty sand layers		5	9-10	38										
0.40				w/shells		6	11.5-12.5	96										
0.50						7	14-15	97										
0.50						8	16.5-17.5	102										
20					w/silty sand layers & lenses		9	19-20	44									
0.40						10	21.5-22.5	68										
0.50					w/silty sand layers		11	24-25	63									
0.50						12	26.5-27.5	49										
30						13	29-30	41										
0.50					w/few silt lenses		14	31.5-32.5	60									
0.50						15	34-35	64										
0.50						16	36.5-37.5	65										
40					Loose gray sandy silt w/silty clay layers	ML	17	39-40	33									
0.50					Soft gray clay	CH	18	41.5-42.5	65									
0.50							19	44-45	61									
0.50							20	46.5-47.5	60									
50					w/clayey silt lenses		21	49-50	57									

Comments: Coordinates: North 488130.438, East 3689961.091

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -0.73 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/14/96 Boring: ALGE2 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50	0.50				Soft gray clay	CH	22	51.5-52.5	53									
	0.50						23	54-55	56									
	0.50						24	56.5-57.5	63									
60	0.50				w/few silt lenses		25	59-60	58									
	0.50						26	61.5-62.5	59									
	0.50						27	64-65	58									
	0.50						28	66.5-67.5	54									
70	0.50				w/sandy clay layers, sand pockets, & shell fragments		29	69-70	33									
	0.60				Medium stiff gray clay w/sandy clay pockets & layers, shell fragments, & sand layers & pockets	CH	30	71.5-72.5	49									
	2.00				Very stiff greenish-gray & gray sandy clay w/clayey sand lenses & pockets	CH	31	74-75	20									
	2.25				Very stiff greenish-gray & tan clay w/clayey sand lenses & layers	CH	32	76.5-77.5	20									
80					Dense greenish-gray & tan silty sand w/clay pockets	SM	33	79-80	27									
90																		
100																		

Comments: Coordinates: North 488130.438, East 3689961.091

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.07 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/08/96 Boring: ALGE3 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & tan silty clay w/roots & sand pockets	CL	1	0	24									
1.25					Loose gray silty sand w/clay layers w/clay layers & lenses	SM	2	1.5	25									
1.00							3	4	26									
1.00							4	6.5	26									
10					Medium stiff gray clay w/sandy silt lenses & layers, & organic matter	CH	5	9	66									
0.75					Loose gray silty sand w/clay layers & pockets, & few roots	SM	6	11.5	27									
0.50					Soft gray & tan clay w/clayey silt pockets, organic matter, & much wood	CH	7	14	48									
0.50					w/wood		8	16.5	41									
20					Loose brown & black humus w/clay layers & much wood	PT	9	19	245									
0.50					Loose gray silty sand w/clay lenses & pockets, & roots	SM	10	21.5	33									
0.50					Loose gray silty sand w/wood, sandy silt layers, clay pockets, & roots	SM	11	24	28									
30					Medium stiff gray clay w/many shell fragments, organic matter, & small silty clay layers	CH	12	26.5	69									
0.50					w/shells, clayey silt lenses, & silty sand pockets		13	29	98									
0.50					w/clayey silt lenses, few silty sand lenses, & pockets		14	31.5	54									
0.50					w/clayey silt lenses, & pockets		15	34	56									
0.50					w/clayey silt lenses & silt lenses		16	36.5	54									
40					w/many sandy silt lenses		17	39	50									
0.50					Soft gray clay w/silt lenses	CH	18	41.5	67									
0.50							19	44	61									
0.50							20	46.5	67									
50							21	49	60									

Comments: Coordinates: North 491737.652, East 3694801.079

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.07 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/08/96 Boring: ALGE3 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests		
									Dry	Wet	Type	φ	C	LL	PL	PI			
50	0.50			Soft gray clay w/clayey silt lenses & silt lenses	CH	22	51.5	65											
	0.50					23	54	61											
	0.50					24	56.5	54											
60	0.50					25	59	56											
	0.50					26	61.5	58											
	0.50					27	64	63											
	0.50					28	66.5	59											
70	0.50					29	69	58											
	0.50					30	71.5	58											
	0.50					31	74	58											
	0.50					32	76.5	56											
80	0.50						Soft gray sandy clay w/clay layers & shells	CL	33	79	24								
90																			
100																			

Comments: Coordinates: North 491737.652, East 3694801.079



# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 0.17 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/12/96 Boring: ALGE4 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Very stiff tan & gray silty clay w/roots	CL	1	0-1	45									
	2.25				w/roots & sand pockets		2	1.5-2.5	25									
	0.50				Soft to medium stiff black & gray organic clay w/organic matter & wood	OH	3	4-5	57									
	0.05				Very soft gray silty clay w/silt lenses & roots	CL	4	6.5-7.5	37									
	0.05				Loose gray clayey silt w/sandy silt layers	ML	5	9-10	32									
10	0.05				Loose gray sandy silt w/small clay lenses & silty clay layers	ML	6	11.5-12.5	32									
	0.05				Very soft gray clay w/silt lenses, organic matter & few roots	CH	7	14-15	85									
	0.05				w/few sand pockets, organic matter & shell fragments		8	16.5-17.5	93									
	0.05				w/shells & organic matter		9	19-20	58									
20	0.05				w/organic matter		10	21.5-22.5	73									
	0.05				w/organic matter & few shell fragments		11	24-25	62									
	0.05				w/silty sand lenses & layers		12	26.5-27.5	40									
	0.05						13	29-30	61									
30	0.05				w/silty sand lenses		14	31.5-32.5	76									
	0.05				w/few silty sand lenses		15	34-35	67									
	0.05						16	36.5-37.5	72									
	0.05						17	39-40	64									
40	0.05						18	41.5-42.5	69									
	0.05						19	44-45	69									
	0.05						20	46.5-47.5	58									
	0.05				Soft gray clay	CH	21	49-50	58									
50	0.05						21	49-50	58									

Comments: Coordinates: North 493957.230, East 3697224.019

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 0.17 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/12/96 Boring: ALGE4 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	φ	C	LL	PL	PI		
50	0.10				Soft gray clay	CH	22	51.5-52.5	55										
	0.10						23	54-55	58										
	0.10						24	56.5-57.5	62										
60	0.10						25	59-60	63										
	0.20						26	61.5-62.5	60										
	0.20					w/sand layers & lenses		27	64-65	70									
	0.20							28	66.5-67.5	64									
	0.10					Loose gray clayey sand w/shell fragments	SC	29	69-70	29									
70	0.10						30	71.5-72.5	30										
	0.30				Medium stiff gray clay w/sand lenses	CH	31	74-75	41										
	1.25					Stiff greenish-gray & light gray sandy clay w/clayey sand layers	CL	32	76.5-77.5	24									
80	1.75						33	79-80	22										
90																			
100																			

Comments: Coordinates: North 493957.230, East 3697224.019

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.71 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/07/96 Boring: ALGE5 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
0				Stiff gray & tan silty clay w/roots & organic matter	CL	1	0-1	33									
1.25				Stiff gray clay w/clayey silt lenses, organic matter, & roots	CH	2	1.5-2.5	54									
1.50				Medium stiff dark gray clay w/organic matter & clayey silt layers	CH	3	4-5	31									
0.60				Soft dark gray clay w/organic matter & small roots	CH	4	6.5-7.5	76									
10				Soft gray clay w/organic matter & wood	CH	5	9-10	97									
0.50				Medium stiff gray clay w/wood, organic matter, & clayey silt lenses	CH	6	11.5-12.5	67									
0.60				w/clayey silt lenses & sandy silt lenses		7	14-15	50									
20				Soft brown humus w/wood & organic clay layers	PT	8	16.5-17.5	64									
0.50				Soft gray clay w/wood & organic matter	CH	9	19-20	224									
0.40						10	21.5-22.5	142									
0.30				w/sandy silt lenses & layers		11	24-25	66									
30				Loose gray sandy silt	ML	12	26.5-27.5	33									
0.50				Loose gray silty sand w/sand layers	SM	13	29-30	49									
						14	31.5-32.5										
		31		Dense gray fine sand	SP	15	34-35										
		30				16	37-38										
40		10		Soft gray clay w/sand lenses & layers	CH	17	39-40	42									
0.50				Soft gray silty clay w/silty sand layers	CL	18	41.5-42.5										
0.50				Soft gray silty clay w/clay layers	CL	19	44-45	65									
0.50				Soft gray clay	CH	20	46.5-47.5	38									
50		0.50		w/few silt lenses		21	49-50	51									

Comments: Coordinates: North 497996.807, East 3699266.828

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.71 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/07/96 Boring: ALGE5 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	φ	C	LL	PL	PI		
50	0.50			[Hatched Pattern]	Soft gray clay w/clayey silt lenses & pockets	CH	22	51.5-52.5	53										
	0.50							23	54-55	49									
	0.50							24	56.5-57.5	58									
60	0.50							25	59-60	61									
	0.50							26	61.5-62.5	64									
	0.50							27	64-65	63									
	0.50							28	66.5-67.5	65									
	0.60					Medium stiff gray clay	CH	29	69-70	60									
70	0.50					Soft gray clay w/few sandy silt lenses	CH	30	71.5-72.5	59									
	0.50							31	74-75	57									
	0.50							32	76.5-77.5	61									
80	0.50							33	79-80	56									
90																			
100																			

Comments: Coordinates: North 497996.807, East 3699266.828

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.12 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12/96 Boring: ALGE6 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPT R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium compact gray & tan clayey silt w/roots & shell fragments	ML	1	0-0.3	39									
1.50					Stiff brown clay w/sand pockets, roots, & shell fragments	CH	2	1.5-2.5	63									
0.40					Stiff dark gray organic clay w/clayey silt lenses & pockets	OH	3	4-5	81									
					Medium stiff dark gray & brown organic clay w/clayey silt pockets & clay layers	CL	4	6.5-7.5	37									
10					Soft gray silty clay w/clay layers & lenses	CH	5	9-10	74									
0.25					Soft gray clay w/sandy silt pockets w/organic clay layers & pockets, & wood w/trace of organic matter & sandy silt pockets	CH	6	11.5-12.5	100									
0.25					Soft gray clay w/sandy silt pockets, lenses, trace of organic matter, & trace of wood	CH	7	14-15	74									
0.25					Medium compact gray clayey silt w/clay pockets	ML	8	16.5-17.5	76									
20					Medium dense gray silty sand	SM	9	19-20	31									
			11		Loose gray fine sand w/clay pockets	SM	10	21.5-22.5	30									
			7		Loose gray silty sand	SP	11	24-25	33									
					Loose gray clayey silt w/clay lenses	SP	12	26.5-27.5	40									
30					Very soft gray silty clay w/clay layers	SM	13	29-30	31									
0.30					Soft gray clay w/clayey silt layers	ML	14	31.5-32.5	34									
					Soft gray clay w/clayey silt pockets	CL	15	34-35	31									
40					Loose gray silty sand w/clay layers	CH	16	36.5-37.5	39									
0.30					Soft gray clay w/clayey silt pockets	CH	17	39-40	29									
0.30					Soft gray clay	CH	18	41.5-42.5	38									
0.30						CH	19	44-45	48									
0.30						CH	20	46.5-47.5	55									
50						CH	21	49-50	62									

Comments: Coordinates: North 501517.478, East 3701098.846

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.12 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12/96 Boring: ALGE6 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
50	0.40			Soft gray clay	CH	22	51.5-52.5	59										
	0.40						23	54-55	62									
	0.40						24	56.5-57.5	63									
60	0.40						25	59-60	64									
	0.40				w/fine sand lenses		26	61.5-62.5	64									
	0.40				w/silty sand layers		27	64-65	53									
	0.40				w/sand pockets & shell fragments		28	66.5-67.5	33									
70	0.40				w/clay pockets & shell fragments		29	69-70	33									
	0.40				Loose gray fine sand w/clay pockets	SP	30	71.5-72.5	28									
		50=5"			Very dense gray fine sand	SP	31	74-75	28									
		22		Very stiff gray clay w/sand pockets & shell fragments	CH	32	76.5-77.5	28										
80	1.00			Medium stiff gray sandy clay w/shell fragments & trace of wood	CL	33	79-80											
90																		
100																		

Comments: Coordinates: North 501517.478, East 3701098.846

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.79 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGE7 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & brown silty clay w/limestone & roots	CL	1	0										
1.25						CH	2	1.5	56									
1.00					Stiff gray & tan clay w/clayey silt lenses & organic matter w/clayey silt lenses	CH	3	4	69									
0.80					Medium stiff gray & tan clay w/clayey silt pockets, organic matter, & wood	CH	4	6.5	44									
0.75					Medium stiff gray clay w/wood, clayey silt lenses, & roots	CH	5	9	33									
10					Soft gray clay w/sandy silt lenses, wood, & organic matter	CH	6	11.5	54									
0.50					w/sandy silt lenses, roots, & clayey silt lenses	CH	7	14	64									
0.50					Very soft gray clay w/wood, humus layers, & pockets	CH	8	16.5	104									
20					Soft brown humus w/wood	PT	9	19	293									
0.40					Medium stiff gray clay w/wood	CH	10	21.5	67									
0.60					Soft gray clay w/roots & organic matter	CH	11	24	33									
0.50					w/roots	CH	12	26.5	75									
30					w/clayey silt lenses & trace of roots	CH	13	29	46									
0.50					w/clayey silt lenses & layers	CH	14	31.5	53									
0.50					w/clayey silt lenses	CH	15	34	53									
0.50					Loose gray sandy silt w/clay lenses	ML	16	36.5										
40					w/clayey silt layers	CH	17	39										
0.30					Soft gray clay w/clayey silt lenses	CH	18	41.5	39									
0.50						CH	19	44	48									
0.50					w/clayey silt lenses & layers	CH	20	46.5	51									
50						CH	21	49	41									

Comments: Coordinates: North 506135.743, East 3703397.032

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.79 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGE7 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50	0.40			Soft gray clay	CH	22	51.5	39										
	0.50						23	54	45									
	0.50				w/clayey silt lenses		24	56.5	60									
60	0.50						25	59	63									
	0.50						26	61.5	62									
	0.50						27	64	58									
	0.50						28	66.5	59									
70	0.50						29	69	66									
	0.50				w/silty sand lenses & layers		30	71.5	63									
	0.50				w/silty sand layers		31	74	51									
	0.50				w/clayey sand pockets & shell fragments		32	76.5	45									
80	0.50				w/sand pockets & shell fragments		33	79	32									
90																		
100																		

Comments: Coordinates: North 506135.743, East 3703397.032



# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 5.50 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGE8 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0		10	X		Loose gray clayey silt w/roots & glass	ML	1	0										
			X		Loose brown clayey silt w/roots, gravel, & glass	ML	2	1										
		5	X		Medium stiff gray clay w/clayey silt, gravel, glass, & shells	CH	3	4	43									
1.00					Medium stiff dark gray & tan clay w/organic matter & clayey silt pockets	CH	4	7	40									
10	0.30				Soft gray clay w/clayey silt pockets & lenses & organic matter	CH	5	9	50									
	0.05				Soft gray organic clay w/humus layers & decayed wood	OH	6	12	141									
	0.30				Soft gray organic clay w/humus layers & decayed wood w/clay & humus layers	OH	7	14	186									
	0.70				Medium stiff gray clay w/organic matter & clayey silt lenses w/organic matter & wood	CH	8	17	86									
20	1.00				Medium stiff gray organic clay w/humus layers & wood	OH	9	19	54									
	0.60				Medium stiff gray organic clay w/humus layers & wood w/humus & clay layers	OH	10	22	180									
	0.60				Soft gray clay w/clayey silt lenses & organic matter	CH	11	24	163									
	0.25				Soft gray clay w/clayey silt lenses & organic matter	CH	12	27	60									
30	0.50				Medium stiff gray clay w/trace of wood & silt layers	CH	13	29	83									
					Loose gray silty sand w/clay lenses	SM	14	32										
	0.50				Medium stiff gray & tan clay w/sandy silt layers & lenses	CH	15	34	57									
	0.60				Medium stiff gray clay w/clayey silt layers & lenses	CH	16	37	66									
40	0.60				Medium stiff gray clay w/clayey silt layers & lenses w/clayey silt pockets	CH	17	39	68									
	0.75				Medium stiff gray clay w/clayey silt layers & lenses w/clayey silt pockets	CH	18	42	67									
	0.50				Medium stiff gray clay w/clayey silt layers & lenses w/clayey silt pockets	CH	19	44	67									
	0.60				Medium stiff gray clay w/clayey silt layers & lenses w/sandy silt lenses	CH	20	47	67									
50	0.60				Medium stiff gray clay w/clayey silt layers & lenses w/sandy silt lenses	CH	21	49	55									

Comments: Coordinates: North 511863.1, East 3706454.431

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 5.50 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGE8 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50					Medium stiff gray clay w/silt lenses	CH													
0.75					w/silt layers		22	52	70										
0.75							23	54	66										
0.75							24	57	58										
60							25	59	57										
0.60						w/silt pockets		26	62	60									
0.75							27	64	60										
0.75						w/sand lenses		28	67	65									
70						w/clayey sand layers		29	69	59									
0.80							30	72	58										
1.00					Stiff gray clay w/shell fragments	CH													
1.00							31	74	56										
1.20							32	77	53										
80					Medium dense gray clayey sand w/shell fragments & clay layers	SC													
							33	79											
90																			
100																			

Comments: Coordinates: North 511863.1, East 3706454.431

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.25 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGE9 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
0				Stiff dark gray clay w/roots & grass	CH	1	0	32									
1.40				Stiff gray & tan clay w/clayey silt lenses & layers, & organic matter	CH	2	2	57									
1.40				Loose gray clayey silt w/silty sand pockets & lenses	ML	3	4	24									
1.20				Medium stiff gray & tan clay w/many silty sand pockets & lenses	CH	4	7	59									
10 0.80				Medium stiff gray & dark gray clay w/organic matter	CH	5	9	71									
0.80				Soft brown & gray organic clay w/clay layers	OH	6	12	73									
0.60				Stiff gray & dark gray clay w/organic clay & wood	CH	7	14	174									
1.00				Loose black humus w/clay layers & wood	PT	8	17	118									
20 0.60				Medium stiff gray organic clay w/humus, wood, & decayed roots	OH	9	19	270									
0.60				Medium stiff dark brown & gray organic clay w/clayey silt lenses, wood, roots, & organic matter	OH	10	22	155									
0.50				Soft gray & tan clay w/sandy silt layers	CH	11	24	229									
30 0.50				w/sandy silt layers & lenses		12	27	50									
0.80				Medium stiff gray clay w/silty sand layers & lenses	CH	13	29	56									
0.80				Medium compact gray clayey silt w/silty sand layers	ML	14	32	56									
0.25				Soft gray & tan clay w/silty sand layers & lenses	CH	15	34										
40 0.25				Soft gray clay w/silty sand layers & pockets	SM	16	37	48									
0.50				Medium stiff gray clay	CH	17	39	51									
0.75				w/silty sand pockets		18	42	66									
0.75				w/clayey silt layers		19	44	64									
50 0.75						20	47	68									
						21	49	54									

Comments: Coordinates: North 514667.790, East 3709519.893

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.25 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGE9 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	φ	C	LL	PL	PI		
50					Medium stiff gray clay	CH													
0.75							22	52	72										
0.75							23	54	62										
0.80							24	57	68										
60							25	59	62										
1.00							26	62	75										
1.00							27	64	62										
1.20						w/few silty sand layers		28	67	67									
70						Medium dense gray clayey sand w/clay layers & shell fragments	SC	29	69	27									
1.20						Stiff gray clay w/clayey sand layers & pockets, & shells	CH	30	72	44									
1.25					w/sand pockets & shell fragments		31	74	61										
80					Medium stiff gray clay w/clayey sand pockets & shells	CH	32	77	47										
0.30					w/clayey sand layers & pockets, & shells		33	79	39										
90																			
100																			

Comments: Coordinates: North 514667.790, East 3709519.893

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.69 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 2/29/96 Boring: ALGW1 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
0		8	X		Loose gray limestone & shells	GP	1	0										
			X		Medium stiff gray clay w/shells	CH	2	2	31									
0.50			X		Medium stiff gray & tan clay w/silty sand pockets & shell fragments	CH	3	4	55									
0.40			X		Soft gray clay w/clayey silt lenses & organic matter	CH	4	7	68									
10 0.40			X		w/clayey silt pockets, organic matter, wood, & roots		5	9	59									
0.30			X		w/wood		6	12	92									
0.30			X		w/sandy silt lenses, pockets, & wood		7	14	46									
			X		Very loose gray sandy silt w/clay lenses	ML	8	17										
20			X		Medium stiff black organic clay w/humus layers	OH	9	19	197									
			X		Medium stiff gray clay w/organic clay & humus layers	CH	10	22	83									
0.25			X		Loose gray sandy silt w/clay pockets	ML	11	24	39									
			X		Medium dense gray silty sand	SM	12	27										
30		6	X		Medium stiff gray clay w/silty sand layers	CH	13	29	61									
			X		Loose gray fine sand w/clay layers	SP	14	32										
		28	X		Medium dense gray silty sand w/clay layers	SM	15	34										
		27	X				16	36										
40		5	X		Medium stiff gray clay w/sandy silt	CH	17	39	37									
0.20			X		Loose gray silty sand	SM	18	42										
0.20			X				19	44										
0.25			X		Soft gray clay w/silty sand layers & silt lenses	CH	20	47	66									
50 0.25			X				21	49	46									

Comments: Coordinates: North 485906.337, East 3682390.777

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.69 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 2/29/96 Boring: ALGW1 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
50				Soft gray clay	CH													
0.30				w/clayey silt layers & silt lenses		22	52	51										
0.40				w/few silt lenses		23	54	69										
0.30						24	57	58										
0.30				w/silt layers		25	59	59										
60					Medium stiff gray clay	CH												
0.50					26		62	54										
0.50					27		64	54										
0.50					28		67	67										
0.60					29		69	65										
0.60					30		72	60										
70				w/sand layers & pockets, clayey sand layers, & shell fragments	SC													
0.60				31		74	45											
0.60				32		77												
80				Medium dense gray clayey sand w/clay layers & shell fragments		33	79											
90																		
100																		

Comments: Coordinates: North 485906.337, East 3682390.777

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.58 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 2/29 & 3/01/96 Boring: ALGW2

Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0	2.40				Loose tan & gray clayey silt w/trace of fine sand	ML	1	0.0										
					Very stiff dark gray & tan clay w/thin clayey silt & sandy silt layers & pockets, & trace of wood	CH	2	1.5	25									
					Stiff dark gray clay w/clayey silt layers & decayed wood	CH	3	4	37									
1.20					Loose gray clayey silt w/thin clay layers & few roots	ML	4	6.5	53									
10	0.70				Soft gray clay w/clayey silt pockets & trace of organic matter	CH	5	9										
	0.25				w/clayey silt lenses, roots, trace of organic matter, & shell fragments	ML	6	11.5	46									
	0.25				Loose gray clayey silt w/organic matter & organic clay layers	ML	7	14	80									
0.50					Medium stiff dark gray clay w/organic matter & organic clay layers	CH	8	16.5										
20	0.40				w/trace of organic matter	CH	9	19										
	0.90				Medium stiff gray clay w/fine sand & silt lenses	CH	10	21.5	119									
	0.75				Loose gray fine sand w/trace of organic matter & few clay lenses	SP	11	24	118									
	0.50				Very dense gray fine sand	SP	12	26.5	40									
30	50 = 11"				Very loose gray clayey silt w/clay layers	ML	13	29										
	4				Medium stiff gray clay w/clayey silt lenses & thin layers, & pockets	CH	14	31										
	0.50				w/clayey silt layers	CH	15	33										
40	0.50				w/few fine sand lenses		16	36.5	38									
	0.60				w/few clayey silt lenses		17	39	37									
	0.75				w/trace of organic matter		18	41.5	42									
	0.70						19	44	55									
	0.70						20	46.5	43									
50	0.70						21	49	48									

Comments: Coordinates: North 485135.505, East 3684681.569

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.58 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 2/29 & 3/01/96 Boring: ALGW2 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPT L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
50	0.75				Medium stiff gray clay	CH	22	51.5	45									
	0.90				w/clayey silt layers		23	54	42									
	0.90						24	56.5	61									
60	0.90						25	59	50									
	0.90						26	61.5	60									
	0.90						27	64	60									
	0.90					w/few clayey silt lenses		28	66.5	58								
70	0.90						29	69	58									
	0.75					w/sand layers, pockets, & shell fragments		30	71.5	38								
						Loose gray clayey sand w/clay pockets	SC	31	74									
		33			Dense gray fine sand w/shell fragments & few clay lenses	SP	32	76.5										
80					Very stiff green & tan sandy clay	CL	33	79	19									
90																		
100																		

Comments: Coordinates: North 485135.505, East 3684681.569



# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.495 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/01/96 Boring: ALGW3 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff gray clay w/roots, shells & grass	CH	1	0	27									
					Loose tan silt w/roots	ML	2	2										
1.75					Stiff gray, tan, & brown clay w/silt layers & pockets	CH	3	4	29									
0.75					Medium stiff gray & dark gray clay w/silty sand layers & pockets	CH	4	7	76									
10 0.30					Soft gray clay w/silty sand pockets & shell fragments	CH	5	9	69									
0.30					w/clayey silt layers, silty sand lenses, & shells		6	12	52									
					Medium stiff gray clay w/organic clay & clayey silt lenses	CH	7	14	55									
					Loose black humus w/clay layers	Pt	8	17	133									
20 0.30					Loose gray clayey silt w/silty sand layers & lenses	ML	9	19										
0.25					Loose gray silty sand	SM	10	22										
0.25					Soft gray clay w/shell fragments	CH	11	24	80									
0.30					w/organic matter & shell fragments		12	27	71									
30 0.40					w/silty sand layers & lenses		13	29	52									
0.40					w/silty sand layers & pockets		14	32	45									
					Medium compact gray sandy silt w/clay layers	ML	15	34										
0.30					Soft gray clay w/silty sand layers	CH	16	37	43									
40 16					Medium dense gray silty sand w/clay layers	SM	17	39										
18							18	42										
14							19	44										
0.50					Medium stiff gray clay w/silty sand layers	CH	20	47	45									
50 0.50							21	49	57									

Comments: Coordinates: North 489031.072, East 3690060.058

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.495 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/01/96 Boring: ALGW3 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50					Medium stiff gray clay	CH	22	52	63										
0.50							23	54	63										
0.60							24	57	63										
60							25	59	58										
0.75							26	62	55										
0.60							27	64	58										
0.60							28	67	59										
70							29	69	57										
0.75						Stiff gray clay	CH	30	72	59									
0.75						w/silty sand pockets		31	74	57									
1.00								32	77	32									
1.00						Medium stiff gray sandy clay w/clay layers & shells	CL												
80						Medium stiff gray clay w/clay layers, shells, sand pockets, & lenses	CH	33	79	43									
0.80																			
90																			
100																			

Comments: Coordinates: North 489031.072, East 3690060.058

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 0.438 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/01/96 Boring: ALGW4 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Loose brown medium to fine sand w/trace of medium sand & grass roots	SP	1	0										
2.20					Compact gray & tan clayey silt w/silty clay pockets & layers, & clay layers	ML	2	1.5										
1.20					Loose gray clayey silt w/clay layers	ML	3	4										
1.20					Stiff dark gray & brown clay w/organic matter & organic clay layers	CH	4	6.5	168									
0.50					Loose gray clayey silt	ML	5	9										
10					Soft dark gray clay w/organic matter, shells, & shell fragments	CH	6	11.5	86									
0.25							7	14	55									
0.25					Soft gray clay w/organic matter & shell fragments	CH	8	16.5	76									
0.40					Loose gray clayey silt w/sandy silt layers	ML	9	19										
20					w/silty sand layers & trace of wood	SM	10	21.5										
0.30					Very loose to loose gray silty sand w/sandy silt layers	ML	11	24										
0.70					Loose gray clayey silt w/clay layers	CH	12	26.5										
30					Soft gray clay w/clayey silt layers	CH	13	29	63									
0.40					w/clayey silt lenses		14	31.5	67									
0.40					w/few clayey silt lenses		15	34	59									
0.40							16	36.5	58									
0.40							17	39	60									
40					Medium stiff gray clay	CH	18	41.5	47									
0.40							19	44	53									
0.40							20	46.5	69									
0.50							21	49	60									
50																		

Comments: Coordinates: North 491181.668, East 3692925.745

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 0.438 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/01/96 Boring: ALGW4 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	SPT Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
50				Medium stiff gray clay	CH	22	51.5	58									
0.60	0.80			w/few clayey silt lenses		23	54	59									
0.70					24	56.5	67										
60	0.70			25	59	59											
0.70				26	61.5	61											
0.70				27	64	59											
0.50					Loose gray clayey sand w/clay pockets & shell fragments	SC	28	66.5									
70	0.60				Medium stiff gray clay w/sand lenses & layers, & shells	CH	29	69	37								
0.60					Loose gray clayey sand w/small clay layers & shell fragments	SC	30	71.5									
2.25					Very stiff greenish-gray & tan sandy clay w/sandy silt lenses	CL	31	74	21								
2.25						32	76.5	21									
80	1.75			Stiff greenish-gray & tan sandy clay	CL	33	79	28									

Comments: Coordinates: North 491181.668, East 3692925.745

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.816 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW5 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPT R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0	2.40				Medium compact dark gray & tan clayey silt w/shells & roots	ML	1	0-0.5										
					Very compact tan & gray clayey silt w/fine sand pockets	ML	2	1.5-2.5										
	1.90				Dense brown & dark gray silty sand w/clay lenses & pockets	CH	3	4-5										
	0.60				Medium stiff gray & tan clay w/clayey silt lenses & pockets	CH	4	6.5-7.5	45									
10	0.30				Soft gray & tan clay w/clayey silt pockets	CH	5	9-10	77									
	0.25				Soft gray clay w/clayey silt lenses, pockets, shell fragments, & organic matter	CH	6	11.5-12.5	77									
	0.60				Soft gray clay w/clayey silt lenses & organic matter	CH	7	14-15	59									
	0.30				Medium stiff gray clay w/clayey silt, humus layers, wood, & organic clay layers	SC	8	16.5-17.5	47									
20					Loose gray clayey sand	ML	9	19-20	31									
					Loose gray clayey silt w/clay lenses		10	21.5-22.5										
					Loose gray clayey silt		11	24-25										
	0.40				Soft gray clay w/organic matter & shell fragments	CH	12	26.5-27.5	74									
30	0.30				Soft gray & tan clay w/silty clay layers, shell fragments, & organic matter	CH	13	29-30	107									
	0.30				w/organic matter		14	31.5-32.5	90									
	0.30						15	34-35	74									
	0.30				Soft gray clay w/clayey silt layers & lenses & silt lenses	CH	16	36.5-37.5	50									
40	0.30				w/sandy silt layers & lenses		17	39-40	57									
	0.40				w/clayey sand lenses & sandy silt lenses		18	41.5-42.5	63									
	0.40						19	44-45	64									
	0.40				w/clayey silt lenses		20	46.5-47.5	67									
50	0.40				w/few clayey silt lenses		21	49-50	67									

Comments: Coordinates: North 493544.923, East 3696054.745

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.816 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW5 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50	0.40			Soft gray clay	CH	22	51.5-52.5	69										
	0.40			23	54-55													
	0.40			24	56.5-57.5													
60	0.40			25	59-60													
	0.40			26	61.5-62.5													
	0.40			27	64-65													
	0.40			28	66.5-67.5													
70	0.40			29	69-70													
	0.40			30	71.5-72.5													
	0.40			31	74-75													
	0.40			32	76.5-77.5													
80				33	79-80													
					w/clayey sand layers & pockets, & shell fragments													
90																		
100																		

Comments: Coordinates: North 493544.923, East 3696054.745

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 1.58      Datum: NGVD    Gr. Water Depth: See Text    Job No.: 14638    Date Drilled: 4/11/96    Boring: ALGW6    Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
0					Medium compact gray & tan clayey silt w/roots & gravel	ML	1	0-0.3	27									
	0.70				Loose tan fine sand w/gravel	SP	2	0.3-1	5									
					Loose tan fine sand w/gravel	CH	3	1.5-2.5	46									
	0.30				Medium stiff gray, tan & black clay w/clayey silt lenses, pockets, organic matter, organic layers, & brick fragments	CH	4	4-5	46									
					Soft gray & tan clay w/clayey silt layers, lenses, pockets, & organic matter	ML	5	6.5-7.5	66									
10					w/sandy silt layers & trace of organic matter	OH	6	9-10	32									
	0.25				Loose gray clayey silt w/clay layers	CH	7	12-12.5	89									
					Medium stiff dark gray & black organic clay w/clay layers w/decayed wood	CH	8	14-15	210									
					Soft gray clay w/trace of organic matter	CH	9	16.5-17.5	92									
20					Soft gray clay w/trace of organic matter & decayed wood	CH	10	19-20	109									
	0.25				w/trace of organic matter w/clayey silt layers & clayey silt pockets	ML	11	21.5-22.5	75									
					Loose gray clayey silt w/clay lenses	ML	12	24-25	49									
					Loose gray silty sand w/clay layers & lenses	SM	13	26.5-27.5	33									
30					Loose gray clayey silt w/clay lenses	ML	14	29-30	32									
					Medium compact gray sandy silt	ML	15	31.5-32.5	34									
					Soft gray clay w/silty sand lenses	CH	16	34-35	35									
	0.30				Soft gray clay w/clayey silt lenses	CH	17	36.5-37.5	47									
40					Medium stiff gray clay w/clayey silt layers	CH	18	39-40	40									
	0.30					CH	19	41.5-42.5	55									
						CH	20	44-45	55									
	0.30					CH	21	46.5-47.5	64									
						CH	22	49-50	57									
50						CH												

Comments: Coordinates: North 500281.942, East 3699699.114

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 1.58 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/11/96 Boring: ALGW6 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPL R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50	0.30				Medium stiff gray clay	CH	23	51.5-52.5	58										
	0.30						24	54-55	49										
	0.30						25	56.5-57.5	56										
60	0.30						26	59-60	54										
	0.30						27	61.5-62.5	66										
	0.30						28	64-65	62										
	0.40					Medium stiff gray clay w/silty sand lenses	CH	29	66.5-67.5	62									
70	0.40					w/silty sand lenses & pockets		30	69-70	60									
					Loose gray clayey sand w/shells & clay layers	SC	31	71.5-72.5	26										
					Medium dense gray fine sand w/clay layers	SP	32	74-75	25										
	0.40				Medium stiff gray clay w/fine sand pockets & shell fragments	CH	33	76.5-77.5											
80	0.40						34	79-80											
90																			
100																			

Comments: Coordinates: North 500281.942, East 3699699.114



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.78 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW7 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPL R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Loose tan & gray clayey silt w/trace of fine sand	ML	1	0-1	32									
3.25					Very stiff dark gray & tan clay w/thin clayey silt & sandy silty clay & pockets, & trace of wood w/organic matter & silt lenses	CH	2	1.5-2.5	23									
2.25					Very stiff dark gray & tan clay w/silt pockets, thin sandy silt layer & lenses, few pockets, & trace of organic matter	CH	3	4-5	29									
2.10					Stiff dark gray clay w/clayey silt layers & decayed wood	CH	4	6.5-7.5	32									
10					Loose gray clayey silt w/thin clay layers & few roots	CH	5	9-10	43									
0.60					Soft gray clay w/clayey silt pockets & trace of organic matter	ML	6	11.5-12.5	56									
0.80					Medium stiff gray clay w/clayey silt lenses, roots, trace of organic matter, & shell fragments	CH	7	14-15	53									
0.70					Loose gray clayey silt w/clay layers	CH	8	16.5-17.5	40									
0.50					Very soft dark gray clay w/trace of organic matter w/fine sand & silt lenses	CH	9	19-20	45									
20					Loose gray fine sand w/few clay lenses & trace of organic matter	SP	10	21.5-22.5	39									
0.95					Very loose gray clayey silt w/clay layers	ML	11	24-25	43									
0.55					Medium stiff gray clay w/clayey silt lenses, pockets, & thin clay layers	CH	12	26.5-27.5	44									
0.05					Loose gray sandy silt w/clayey silt lenses & organic matter w/clayey silt lenses, organic matter, & fine sand lenses	ML	13	29-30	70									
0.05					Medium stiff dark gray clay w/organic clay layers & organic matter	CH	14	31.5-32.5	43									
0.05					Soft gray clay w/silty sand layers & trace of organic matter	CH	15	34-35	34									
30					Loose gray clayey silt w/clay layers	ML	16	36.5-37.5										
0.05					Medium stiff gray clay w/clayey silt lenses, pockets, & thin clay layers	CH	17	39-40										
0.05					Loose gray sandy silt w/clayey silt lenses & organic matter w/clayey silt lenses, organic matter, & fine sand lenses	ML	18	41.5-42.5	33									
40					Medium stiff gray clay w/silt lenses	CH	19	44-45	43									
0.05					Soft gray clay w/silty sand layers & trace of organic matter	CH	20	46.5-47.5	34									
50							21	49-50	39									

Comments: Coordinates: North 485135.505, East 3684681.569

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 8.78 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW7 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	φ	C	LL	PL	PI		
50	0.05				Soft gray clay	CH	22	51.2-52.2	41										
			Very soft gray clay w/silty sand layers		CH														
	0.05				Soft gray clay w/clayey silt layers	CH	23	54-55	28										
	0.30						24	56.5-57.5	52										
60	0.30						25	59-60	46										
	0.40						26	61.5-62.5	52										
	0.40						27	64-65	53										
	0.35					w/few clayey silt lenses & layers		28	66.5-67.5	55									
70	0.35						29	69-70	55										
	0.30					w/fine sand lenses, layers & pockets, & shell fragments		30	71.5-72.5	51									
	0.55				Loose gray clayey sand w/clay pockets	SC	31	74-75	52										
	0.60				Medium dense gray fine sand w/few clay lenses & shell fragments	SP	32	76.5-77.5	34										
80	0.60				Stiff green & tan sandy clay w/sand pockets & shell fragments	CL	33	79-80	32										
90																			
100																			

Comments: Coordinates: North 485135.505, East 3684681.569

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.951 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW8 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
0	0.75				Medium stiff gray & tan clay w/roots & organic matter w/roots & organic matter	CH	1	0-1	58									
							2	1.5-2.5	88									
	0.50				Soft dark gray clay w/humus layers, organic matter, organic clay layers	CH	3	4-5	140									
	0.20				Extremely soft gray clay w/wood & organic matter	CH	4	7.5-8.5	196									
10	0.20				w/wood, organic matter & humus layers		5	9-10	224									
	0.20				Very soft gray clay w/clayey silt pockets	CH	6	11.5-12.5	78									
	0.20				w/wood		7	14-15	71									
	0.25				w/trace of wood & organic matter		8	16.5-17.5	82									
20	0.20				w/clayey silt layers		9	19-20	85									
	0.20				w/sandy silt lenses & layers		10	21.5-22.5	40									
	0.30				Soft gray clay w/clayey silt & sandy silt lenses	CH	11	24-25	41									
	0.40				w/clayey silt lenses		12	26.5-27.5	70									
30	0.30						13	29-30	78									
	0.30						14	31.5-32.5	76									
	0.30						15	34-35	67									
	0.30						16	36.5-37.5	61									
40	0.40						17	39-40	78									
	0.40						18	41.5-42.5	69									
	0.40						19	44-45	69									
	0.40						20	46.5-47.5	68									
50	0.50						21	49-50	61									

Comments: Coordinates: North 509148.427, East 3704175.151

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.951 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/04/96 Boring: ALGW8 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50	0.50				Soft gray clay w/clayey silt lenses	CH	22	51.5-52.5	60									
	0.50						23	54-55	63									
	0.50				w/sandy silt lenses		24	56.5-57.5	65									
60	0.50				w/sandy silt lenses & layers		25	59-60	69									
	0.20				Loose gray clayey sand w/shell fragments	SC	26	61.5-62.5										
	0.40				Soft gray clay w/clayey sand layers & shell fragments	CH	27	64-65	51									
	0.50				Soft gray clay w/sand lenses & shells	CH	28	66.5-67.5	61									
70	0.50				w/sand lenses & pockets, & shell fragments		29	69-70	35									
	0.50						30	71.5-72.5	48									
	0.50						31	74-75	32									
	0.50						32	76.5-77.5	60									
80	0.70						33	79-80	67									
90																		
100																		

Comments: Coordinates: North 509148.427, East 3704175.151

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.009 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGW9 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0	1.90				Stiff gray & brown silty clay w/roots & organic matter	CL	1	0	25									
					Very stiff gray & brown silty clay w/roots, organic matter, & trace of wood	CH	2	1.5	41									
	1.50						3	4	42									
	0.50				Stiff gray & tan clay w/clayey silt lenses & organic matter	CH	4	6.5	74									
10	0.60				Soft gray clay w/sandy silt lenses	CH	5	9	153									
	0.50				Medium stiff gray & brown clay w/organic matter & organic clay layers	CH	6	11.5	129									
	0.50				Soft gray & brown clay w/humus layers, wood & roots	PT	7	14	388									
	0.50				Soft brown humus w/roots	OH	8	16.5	194									
20	0.50				Soft gray & brown organic clay w/roots & humus layers		9	19	126									
	0.50				Soft black & dark gray clay w/humus layers & many roots	CH	10	21.5	193									
	0.50				Soft gray & brown organic clay w/clayey silt layers & organic matter	OH	11	24	190									
	0.30				Soft gray clay w/clayey silt lenses	CH	12	26.5	75									
30	0.30						13	29	80									
	0.30				Loose gray clayey silt w/small clay layers & sandy silt lenses & layers	ML	14	31.5										
	0.30				Soft gray clay w/clayey silt lenses	CH	15	34	64									
	0.30						16	36.5	75									
40	0.30						17	39	64									
	0.30						18	41.5	70									
	0.40						19	44	67									
	0.30						20	46.5	66									
50	0.40						21	49	71									

Comments: Coordinates: North 513359.703, East 3707077.608

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.009 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGW9 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
50	0.50				Soft gray clay w/clayey silt lenses	CH	22	51.5	66									
	0.50						23	54	63									
	0.50						24	56.5	61									
60	0.50						25	59	58									
	0.50						26	61.5	62									
	0.50						27	64	61									
	0.50						28	66.5	55									
70	0.50				w/sand layers		29	69	68									
	0.30				Loose gray clayey sand	SC	30	71.5										
	0.50				Soft gray clay w/shells & clayey sand lenses & layers	CH	31	74	58									
	0.50				w/sandy silt lenses & layers		32	76.5	58									
80	0.50				w/sandy silt lenses		33	79	39									
90																		
100																		

Comments: Coordinates: North 513359.703, East 3707077.608

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 2.70 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGW10 Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	$\phi$	C	LL	PL	PI	
0					Medium compact tan clayey silt w/roots	ML	1	0	31									
0.60					Medium compact tan & gray clayey silt w/silty clay layers & shell fragments	ML	2	1.5	20									
1.80					Stiff dark gray & tan clay w/clayey silt layers	CH	3	4	27									
2.50					Very stiff gray & tan clay w/clayey silt layers & pockets	CH	4	6.5	32									
10					Medium stiff gray & tan clay w/gravel	CH	5	9	52									
0.30					Soft gray & tan clay w/organic clay layers & organic matter	CH	6	11.5	89									
0.30					Loose dark brown humus w/organic layers	PT	7	14	267									
0.30					Soft gray clay	CH	8	16.5	69									
20					Soft dark brown & gray organic clay w/humus pockets	OH	9	19	178									
					Soft gray & tan clay w/silty sand layers	CH	10	21.5	54									
					Soft gray clay	CH	11	24	81									
30					Loose gray silty sand	SM	12	29.5	51									
0.30					Soft gray clay w/clayey silt lenses	CH	13	31.5	40									
0.30							14	34	69									
0.30					w/few silt lenses		15	36.5	69									
40							16	39	65									
0.30							17	41.5	66									
0.30							18	44	68									
0.30					w/few clayey silt lenses		19	46.5	59									
50							20	49	56									

Comments: Coordinates: North 517774.112, East 3712102.544

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 2.70 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/05/96 Boring: ALGW10 Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
50	0.30		[Diagonal Hatching]	Soft gray clay	CH	21	51.5	62										
	0.30						22	54	62									
	0.50				w/few clayey silt lenses		23	56.5	61									
60	0.50	19	[Cross-hatching]	Medium dense gray fine sand	SP	24	59	64										
		8	[Cross-hatching]	w/clay layers		25	60											
	0.30		[Diagonal Hatching]	Soft gray clay w/sand pockets	CH	26	63	40										
	0.30		[Diagonal Hatching]	w/shell fragments & sand pockets		27	64											
70	0.30		[Cross-hatching]	Loose gray clayey sand w/shell fragments	SC	28	66.5	37										
			[Cross-hatching]	Loose gray silty sand	SM	29	69	25										
			[Cross-hatching]	Loose gray silty sand	SM	30	71.5	28										
		11	[Cross-hatching]	Medium dense gray fine sand w/clay layers	SP	31	74	26										
		22	[Cross-hatching]	Medium dense gray fine sand w/clay layers	SP	32	76											
80						33	79											
90																		
100																		

Comments: Coordinates: North 517774.112, East 3712102.544



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.75 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/19/96 Boring: ALGE-1U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff tan silty clay w/roots	CL												
					Medium stiff gray & tan clay w/wood, organic matter, & shells	CH												
					Soft gray clay w/silt lenses & organic matter	CH	3C	6.0	32	88	117	UU	4	377	33	19	14	
10					w/humus pockets													
					w/wood & sandy silt lenses													
					Medium stiff gray clay w/silt layers & lenses, & organic matter	CH	5C	14.1	47	72	107	UU	0	446	70	19	51	
					Wood	WD												
20		8			Loose gray fine silty sand w/clay layers & wood layers	SM												
		10			w/thin clay layers													
		3			Soft gray silty clay w/clayey silt & silty clay layers, & organic matter	CL												
					Soft gray clay	CH	9C	27.2	35	85	114	UU	0	373	39	19	20	
30					Medium stiff gray clay w/sand layers, & silt layers & lenses	CH	10C	31.4	70	60	101	UC	0	297	92	30	62	
					Soft gray clay w/clayey silt layers	CH	10D	31.7	66	61	101	UU		359				
40		5			Loose gray clayey silt w/silty clay layers	ML												
		3			Soft gray clay w/clayey silt lenses	CH												
					Medium stiff gray clay w/clayey silt lenses	CH	13D	43.8	38	83	115	UU	0	524	51	19	32	
50					Soft gray clay w/silt lenses & pockets	CH	14C	47.5	54	69	106	UC		414				

Comments: Coordinates: North 483259.046, East 3683305.925  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.75 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/19/96 Boring: ALGE-1U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests		
										Dry	Wet	Type	φ	C	LL	PL	PI			
50					Soft gray clay w/silt lenses & pockets	CH	15C	51.4	36	84	115	UC		545	CONS					
					Medium stiff gray clay w/silt lenses & pockets	CH	15D	51.7	43	77	110	UU	0	552				86	23	43
							16C	55.5	58	86	105	UC		538						
60					w/silt layers & layers		17C	59.5	50	70	108	UC	0	603				81	25	56
							17D	59.8	51	70	105	UU		670						
							18C	63.5	58	65	103	UC		608				88	27	61
							18D	63.8	56	67	105	UC		608						
					w/silt lenses & pockets		19C	67.5	51	71	107	UC		606						
70							20B	70.5	57	64	101	UU	0	488				94	27	67
							20C	71.5	55	69	107	UC		570						
					w/sandy silt lenses, layers, & pockets		21C	75.5	58	65	103	UC		835						
					w/fine sand layers & lenses, & shell fragments		22B	78.5	37	84	115	UU	0	825	50	19	31			
80																				
90																				
100																				

Comments: Coordinates: North 483259.046, East 3683305.925  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.65 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/20/96 Boring: ALGE-2U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & tan silty clay w/roots & organic matter	CL												
					Medium stiff gray & brown clay w/organic matter & roots	CH												
					Soft gray clay w/clayey silt lenses & layers	CH												
10					w/shells, & sandy silt lenses & layers		4C		98	46	91	UU	0	341	131	35	96	
					Very soft gray clay w/silt lenses	CH												
					Soft gray clay w/clayey silt lenses & layers	CH	5D		59	65	104	UU	0	213	66	21	45	
20					Loose gray sandy silt w/silty sand layers	ML												
		8			Loose gray silty sand	SM												
		3			Soft gray clay w/sandy silt lenses w/clayey silt lenses & layers	CH												
30							10C		59	63	101	UU	0	450	74	23	51	
					w/silt lenses & pockets		12D		52	70	106	UU	0	278	79	23	56	
40							13D		58	66	104				77	19	58	
					Medium stiff gray clay w/silt pockets	CH	14B		55	67	104	UU	0	656	88	21	67	
50					w/silt lenses & pockets													CONS

Comments: Coordinates: North 486362.907, East 3687549.870  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.65 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/20/96 Boring: ALGE-2U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Medium stiff gray clay w/silt lenses & pockets w/fine sand lenses & pockets	CH	18D	53.8	61	64	102	UU	0	636	89	27	62	
60					w/shells & clayey sand lenses & layers		18B	60.5	59	63	101	UU	0	739	91	26	65	
70					Stiff reddish-gray sandy clay w/shells & clayey sand layers	CL	19D	65.8	28	93	118	UU	0	983	23	16	7	
		29			Medium dense gray clayey sand w/shells & sandy clay layers	SC												
		26			Medium dense greenish-gray clayey sand w/sandy clay layers	SC												
		24			Medium dense greenish-gray clayey sand w/sandy clay layers													
80		36			Dense greenish-gray & tan fine sand	SP												
		31																
90																		
100																		

Comments: Coordinates: North 486362.907, East 3687549.870  
 5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.469 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/18/96 Boring: ALGE-3U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & tan clay w/roots & clayey silt lenses	CH												
					Medium stiff gray silty clay w/silt lenses & clay pockets	CL	3D	6.1	31	89	117	UU	0	739	45	15	30	
10					Medium compact gray sandy silt w/clay layers	ML												
					Soft gray clay w/silty clay layers & lenses, large organic matter pockets, & shell fragments	CH	5B	13.4	67	58	98	UU	0	384	101	31	70	
					Medium stiff dark gray & black organic clay w/peat layers & lenses, & clay pockets	OH	6B	17.1	131	35	79				177	52	125	CONS
20					Soft gray silty clay w/clay layers & pockets	CL	7B	20.9	39						41	19	22	
					Soft gray clay w/organic matter pockets & shell fragments	CH	7C	22.5	79	54	97	UC		475				
					Medium stiff gray clay w/silt layers & lenses, organic matter pockets, & shell fragments	CH	8D	26.6	57	66	104	UU	0	578	78	27	51	
30					Soft gray silty clay w/clay layers & lenses	CL	9B	29.6	34						34	18	16	
					Soft gray clay w/sandy silt layers	CH												
		5			Loose gray sandy silt w/clay layers	ML												
		7			Soft gray clay w/sandy silt lenses	CH												
40		7			Loose gray silty sand	SM												
		7																
		6																
		4																
50					Soft gray clay w/clayey silt lenses & lenses	CH	17B	48.7	49	72	108	UU	0	638	72	26	46	

Comments: Coordinates: North 489889.329, East 3692280.732  
5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.469 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/18/96 Boring: ALGE-3U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
50				Medium stiff gray clay w/clayey silt layers & lenses	CH	17C		56	68	106	UC		529					
				w/clayey silt layers & lenses			18C		51	72	109	UC		503				
							19C 19D		57 54	66 68	104 105	UC UU	0	549 544	83	24	59	
60					Soft gray clay w/silt pockets	CH	20C		54	70	107	UC	0	315	83	23	60	
					Very soft gray clay w/silt pockets	CH	200		51	70	106	UU		179				
					Medium stiff gray clay w/silt lenses & pockets w/silt pockets	CH	21C		61	65	105	UC		656				
70					w/silt lenses & silty sand lenses & pockets		22C 22D		56 54	66 67	104 103	UC UU	0	613 584	88	27	61	
					w/fine sand layers		23C 24B		54 56	69 66	107 103	UC UU		650 737	88	26	62	
80		4 4			Loose gray fine clayey sand w/sandy clay layers & shells	SC												
90																		
100																		

Comments: Coordinates: North 489889.329, East 3692280.732  
 5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.90 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/17/96 Boring: ALGE-4U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff gray & tan silty clay w/small roots	CL												
					Medium stiff gray clay w/shells	CH												
10					Soft black peat w/roots	PT	3C		271	20	72	UU	0	330	307	109	198	
					Medium stiff gray clay w/shells	CH												
20					Very soft gray clay w/silt layers & lenses, & shell fragments	CH	4D		74	56	97	UC		144	/			
					w/silt layers & lenses, organic matter pockets, & shell fragments	CH	6C 6D		77 87	55 50	97 94	UC UU	0	156 340	110	34	76	
30					Soft gray clay w/silt layers & lenses, & shell fragments		8B 8C		68 72	60 56	100 96	UU UC	0	292 268	82	24	58	
					w/silt layers & lenses													
40							9C		60	66	105	UC		259				
							10C 10D		63 68	64 59	103 100	UC UU	0	242 332	90	26	64	
50							11C		63	64	103	UC		276				
							12C 12D		67 69	61 59	102 100	UC UU	0	304 383	95	26	69	
							13C		70	59	101	UC		357				

Comments: Coordinates: North 492367.653, East 3695724.177  
5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.90 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/17/96 Boring: ALGE-4U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent		Shear Tests			Atterberg Limits			Other Tests	
									Dry	Wet	Type	φ	C	LL	PL	PI		
50					Soft gray clay w/silt layers & lenses	CH	14C 14D	50.5 50.8	67 57	61 66	102 104	UC UU	0	294 440	79	25	54	CONS
					Very soft gray clay w/silt layers & lenses	CH	15C	54.5	63	64	104	UC		223				
60					Soft gray clay w/silt layers & lenses	CH	16C 16D	58.5 58.8	64 63	61 62	101 100	UC UU	0	346 416	94	27	67	
					Medium stiff gray clay w/silt layers & lenses	CH	17B	61.5	66	61	102	UC		224	89	33	56	
					Very soft gray clay w/silt layers & lenses	CH	17C	62.5	53	71	108	UC						
70		29			Medium stiff light gray & tan clay w/shell fragments	CH	19B	69.2	22	96	119	UU	0	864	23	14	9	
	34		Medium dense gray & tan clayey sand		SC													
	40				Dense gray & tan clayey sand w/sandy clay pockets	SC												
	41																	
80		24			Medium dense gray clayey silt w/silty clay layers	ML												
90																		
100																		

Comments: Coordinates: North 492367.653, East 3695724.177  
5-in. diameter samples



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.61 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/18/96 Boring: ALGE-5U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests		
									Dry	Wet	Type	φ	C	LL	PL	PI			
0				Medium stiff gray & tan clay w/roots & clayey silt lenses	CH	2C	3.0	32						56	22	34			
		Stiff gray & tan clay w/clayey silt layers & lenses, large organic matter pockets, & roots		CH															
10				Soft dark gray & brown organic clay w/clay layers & pockets, & decayed wood pockets	OH	4C	10.1	86	48	90	UU	0	402	130	43	87			
				w/clay pockets, decayed wood, & roots		5B	13.6	55	66	102	UC		476						
20				Soft gray clay w/silt layers & lenses, & organic pockets	CH	6C	18.5	61	64	103	UC		250						
				Medium stiff dark gray organic clay w/clay layers & pockets, roots, decayed wood, & peat layers	OH	7C 7D	22.5 22.9	60 91	59 43	94 82	UC UU	0	758 833	137	51	86			
30		3		Loose gray sandy silt w/clay layers	ML	10C	31.9	36	83	113	UU	0	430	35	22	13			
				Soft gray clay w/clayey silt layers & lenses	CH														
				Soft gray sandy clay w/clay layers	CL														
				Soft gray clay w/clay layers & lenses	CH	11C	36.5	35						32	18	14			
40							12B 12C	39.6 39.9	45 47	75 73	109 108	UC		348	50	19		31	CONS
							13C 13D	43.9 44.4	40 61	80 64	112 103	UU UC	0	483 327	50	23		27	
50							14C	48.5	57	66	103	UC		281					

Comments: Coordinates: North 496725.774, East 3698623.889  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.61 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/18/96 Boring: ALGE-5U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Soft gray clay w/clayey silt layers & lenses	CH	15B	51.5	67	61	101	UU	0	617	99	27	72	
					Medium stiff gray clay w/clayey silt layers & lenses	CH	15C	52.5	57	65	103	UC	0	404				
					Soft gray clay w/silt layers & lenses	CH	16C	56.5	53	68	104	UC		278				
60					Medium stiff gray clay w/silt layers & lenses	CH	17C 17D	60.5 60.8	58 59	64 65	102 104	UC UU	0	365 652	93	27	66	
					Soft gray clay w/silt layers & lenses	CH	18C	64.5	53	68	104	UC		369				
70					Medium stiff gray clay w/silt layers & lenses	CH	19C 19D	68.5 68.8	58 60	65 64	102 103	UC UU	0	372 535	100	28	72	
					Soft gray clay	CH	20C	72.5	54	69	106	UC		608				
					Soft gray clay	CH	21B	74.7	65	62	102	UU	0	422				
80					Soft gray sandy clay w/shell fragments	CL	22C	80.2	29					40	16	24		
90																		
100																		

Comments: Coordinates: North 496725.774, East 3698623.889  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.08 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/15/96 Boring: ALGE-6U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff brown silty clay w/grass roots	CL												
10					Soft dark gray & brown organic clay w/shell fragments, roots, & decayed wood	OH	3C	9.1	119	39	85	UU	0	274	155	41	114	
					Very soft gray clay w/silt layers & lenses	CH	4C	13.4	70	56	96	UU	0	194	85	25	60	
20					Soft gray silty clay w/silt layers & lenses, & clay	CL	5B	16.7	35	85	115				36	23	13	CONS
		12	X		Medium dense gray fine sand	SP												
		11	X		w/clayey sand layers													
		8	X		Loose gray sandy silt w/clayey silt layers	ML												
		5	X		Loose gray clayey silt w/clay layers & sandy silt layers	ML												
30		4	X		Soft gray clay w/silty sand layers	CH												
					Medium stiff green silty clay w/silt layers & lenses	CL	13C 13D	37.0 37.3	39 37	83 83	115 114	UC UU	0	427 540	48	17	31	
40					Soft gray sandy clay w/silt layers & lenses	CL	14C	41.2	45	75	109	UC		317				
							15B 15C	44.5 45.5	49 55	70 65	105 101	UU UC	0	412 467	76	23	53	
50																		

Comments: Coordinates: North 500124.973, East 3700396.794  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.08 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/15/96 Boring: ALGE-6U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
50				Soft gray sandy clay w/silt layers & lenses	CL												
				Medium stiff gray sandy clay w/silt layers & lenses	CL	17C	53.5	58	67	105	UC	0	551	86	26	60	
				Medium stiff gray clay w/silt layers & lenses	CH	17D	53.8	54	67	104	UU		557				
				Medium stiff gray clay w/silt layers & lenses		18C	57.5	66	61	102	UC		579				
60				Medium stiff gray clay w/silt layers & lenses		19C	61.4	54	67	104	UU	0	756	90	29	61	
		14		Loose gray clayey sand w/shell fragments	SC												
70		40		Medium dense gray clayey sand w/sandy clay, sand layers, & shell fragments	SC												
		48		Medium dense gray clayey sand w/sandy clay, sand layers, & shell fragments	SP												
		47		Dense gray fine sand													
		6		Medium stiff gray clay w/sand pockets	CH												
80				Stiff gray clay w/sandy clay layers, silt pockets, & decayed wood	CH	26B	78.2	53	70	105	UU	0	1156	70	20	50	
90																	
100																	

Comments: Coordinates: North 500124.973, East 3700396.794  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.230 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12/96 Boring: ALGE-7U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Very stiff brown silty clay w/roots	CL												
					Medium stiff tan & gray silty clay w/silt lenses Soft gray clay w/silt layers & lenses	CL CH	2B	4.9	60	64	102	UU	0	374	82	29	53	
					Medium stiff gray & tan silty clay w/silt layers & lenses, large organic matter layers & pockets	CL	4C 4D	14.1 14.7	29 30	91 92	118 120	UU UC	0	590 519	42	17	25	
					Soft gray silty clay w/silt layers & lenses	CL	6D	22.8	40	79	111	UU	0	414	45	21	24	
		4			Loose gray sandy silt	ML												
		8																
		4			Soft gray clay w/sandy silt layers	CH												
		6			Medium stiff gray clay w/wood	CH												
		20			Medium dense gray fine sand w/clay layers	SP												
		29																
		34			Dense gray fine sand	SP												
		29			Medium dense gray fine sand	SP												
		25																
		40			Dense gray fine sand	SP												
		47																
		53			Very dense gray fine sand	SP												

Comments: Coordinates: North 504278.169, East 3702451.616

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.230 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12/96 Boring: ALGE-7U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
50		50 = 11"			Very dense gray fine sand	SP											
51					Medium dense gray sandy silt w/clayey silt layers	ML											
59		12			Loose gray clayey silt w/clay layers	ML											
60		9			Medium stiff gray clay w/clayey silt layers & pockets	CH											
		8			Medium stiff gray clay w/clayey silt layers & pockets	CH	25B 25C	61.5 62.5	45 53	74 71	109 108	UU UC	0	654 705	72	24	48
					Stiff gray clay w/silt lenses & pockets	CH	26C 26D	68.5 66.8	57 58	67 66	105 104	UC		615	94	28	66
70					Stiff gray clay w/silt lenses & pockets	CH	27D 27C	70.5 71.1	58 58	67 66	105 103	UC UU	0	1029 1169	94	30	64
					Loose gray clayey sand w/shell fragments & clay layers	SC											
80					Medium stiff gray sandy clay w/fine sand layers & shell fragments	CL	29C	78.1	33					41	17	24	

Comments: Coordinates: North 504278.169, East 3702451.616

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.75 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/22/96 Boring: ALGE-8U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests													
									Dry	Wet	Type	φ	C	LL	PL	PI														
0				Stiff gray & brown clay w/roots & wood	CH	3C	5.8	150	31	77	UU	0	391	206	54	152														
		Medium stiff gray & brown clay w/organic matter & wood		CH																										
		Soft gray organic clay w/decayed wood & roots		OH																										
10				Loose gray clayey silt w/roots	ML																									
				Very soft gray clay w/silt layers & lenses, & few concretions	CH													5C	14.2	61	63	101	UU	0	175	90	23	67		
				Loose gray clayey silt	ML																									
20					Soft gray clay w/silt layers, lenses & pockets													CH	8C	26.1	52	68	104	UU	0	312	60	21	39	
																			9C	30.5	70	59	100	UC		277				
																			10C	34.1	66	60	100	UU	0	388	85	27	58	
40					Very soft gray clay w/silt layers & lenses													CH	11C	38.5	60	69	109	UC		209	88	32	56	CONS
				Medium stiff gray clay w/silt layers & lenses	CH	11D	38.8	70	59	100																				
				Soft gray clay w/silt pockets	CH	13D	46.2	61	63	101	UU	0	415	81	25	56														
50																														

Comments: Coordinates: North 508246.628, East 3704510.434  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -2.75 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/22/96 Boring: ALGE-8U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Soft gray clay w/silt pockets	CH												
					Medium stiff gray clay w/silt pockets	CH	15C	54.1	65	60	100	UU	0	585	93	29	64	
60					Medium stiff gray sandy clay w/fine sand layers	CL	17C	61.8	62	62	101	UU	0	553	88	28	60	
		10			Medium dense gray fine sand w/clayey sand pockets	SP												
		11			Medium stiff gray clay w/shells	CH												
70		4			Medium stiff gray clay w/shells	CH												
					Medium compact gray sandy silt w/shells & sandy silt pockets	ML												
					Stiff gray clay w/shell fragments & clay pockets	CH	22D	76.8	30	91	118	UU	0	577	28	15	13	
80		6			Loose gray silty sand w/shells & sandy silt pockets	SM												
90																		
100																		

Comments: Coordinates: North 508246.628, East 3704510.434  
 5-in. diameter samples



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.06 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/20/96 Boring: ALGE-9U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff dark gray clay w/roots & grass	CH												
					w/roots, humus, & grass roots		2B	4.6	38	74	103	UU	0	1690	82	33	49	
					Stiff dark gray & tan clay w/humus	CH												
					Loose black humus w/wood	Pt												
10																		
					Soft gray clay w/wood	CH	5C	17.7	64	55	91	UU	0	300	118	28	90	
20					Loose black humus w/wood	Pt												
					w/clay layers & wood													
					Very soft gray clay w/silt layers & lenses	CH	7D	26.2	62	62	100	UU	0	212	72	23	49	
30					Soft gray clay w/clayey silt layers & pockets	CH												
							9D	34.8	58	64	102	UU	0	310	92	30	62	
40																		
					Very soft gray clay w/clayey silt layers, lenses, & pockets	CH	11C	42.1	59	62	98				81	26	55	CONS
50																		

Comments: Coordinates: North 512862.124, East 3707443.123  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.06 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/20/96 Boring: ALGE-9U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Very soft gray clay w/clayey silt layers, lenses, & pockets Soft gray clay w/clayey silt layers & lenses	CH CH	13D	50.8	61	63	102	UU	0	381	84	25	59	
60					Medium stiff gray clay w/clayey silt layers & lenses	CH	15D	58.5	66	58	98	UU	0	489	93	27	66	
70		17			Soft gray clay w/clayey silt layers & lenses	CH	17D	66.8	64	60	98	UU	0	478	91	23	68	
		14			Medium dense gray silty sand w/shell fragments	SM												
		17			Medium dense gray clayey sand w/clay layers & shell fragments	SC												
		7			Medium stiff gray clay w/shell fragments	CH												
80		11			w/silty sand layers Medium dense gray silty sand w/clay layers & shells	SM	22B	77.1	44	75	109	UU	0	736	64	18	46	
90																		
100																		

Comments: Coordinates: North 512862.124, East 3707443.123  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 1.95 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/19/96 Boring: ALGE-10U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff dark gray clay w/roots, shells & grass	CH												
					Stiff gray & tan clay w/roots	CH												
10					Medium stiff gray clay w/humus & wood  w/organic matter layers & lenses, & decayed wood	CH	3C 3D	10.5 10.8	54 61	67 62	103 98	UC UU	0	271 506	103	32	71	
					Soft gray clay w/humus & wood	CH												
20					Very soft gray clay w/sandy silt layers & lenses, & organic matter pockets	CH	6B 6C	21.5 22.5	66 51	62 72	101 109	UU UC	0	542 221	76	25	51	
					Soft gray clay w/clayey silt lenses	CH	8C 8D	30.5 30.8	70 70	58 58	98 98	UC UU	0	332 422	96	27	69	
					Very soft gray clay w/silt layers & lenses	CH	9C	34.4	66	61	101	UC		207				
40					Soft gray clay w/silt layers & lenses	CH	10C 10D	38.5 38.8	72 68	57 58	99 97	UC UU	0	259 542	86	27	59	
						CH	11C	42.4	63	63	102	UC		380	81	26	55	
50					Medium stiff gray clay w/silt layers & lenses	CH	12C 12D	46.5 46.8	55 53	67 67	103 103	UC UU	0	263 646	72	25	47	

Comments: Coordinates: North 515847.833, East 3710935.137  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 1.95 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/19/96

Boring: ALGE-10U

Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests	
										Dry	Wet	Type	φ	C	LL	PL	PI		
50					Medium stiff gray clay w/silt layers & lenses	CH	13C	50.5	54	67	103	UC			265				
					Soft gray clay w/silt pockets	CH													
					Medium stiff gray clay w/silt pockets	CH	14C 14D	54.4 54.7	57 56	67 65	105 101	UC UU	0		399 660	80	28	52	
60		19			Medium dense gray silty sand	SM	15C	57.6	63	63	102					87	28	59	CONS
		12			Medium dense gray clayey sand w/shell fragments	SC													
		8			Loose gray clayey sand w/shell fragments & clay layers	SC													
		9																	
		5			Loose gray sandy clay w/shell fragments & clayey sand layers	CL													
70		12			Medium dense gray silty sand w/clay layers	SM													
		9				SM													
		5			Loose gray silty sand w/clay layers & shell fragments														
		6																	
		8																	
80		18			Medium stiff gray silty clay w/many shell fragments & clayey silt layers	CL													
					Very stiff greenish-gray clay	CH													
90																			
100																			

Comments: Coordinates: North 515847.833, East 3710935.137  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.03 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGW-1U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
0				Stiff tan & gray silty clay w/roots & sandy silt pockets	CL												
				Soft gray clay w/oxidation, silt lenses, & pockets	CH	3C	6.1	71	56	96	UU	0	381	98	32	66	
10				Soft gray silty clay w/sandy silt layers & roots	CL												
				Wood	WD												
20				Soft gray silty clay w/silt lenses, roots, & wood	CL	6B	18.9	42	79	113	UU	0	335	47	18	29	
				Soft gray clay w/silt lenses	CH	8B	24.1	63	62	102	UU	0	309	93	27	66	
30		6		Loose gray sandy silt w/silty clay layers	ML												
		14		Medium dense gray fine sand w/clay layers	SP												
		5		Soft gray silty clay w/silty sand layers	CL												
		15		Medium dense gray fine sand w/clayey sand layers	SP												
40		13															
		13															
		9		Loose gray fine sand	SP												
		8		Loose gray clayey silt w/sandy silt layers & clay layers	ML												
		5		Soft to medium stiff gray clay w/silty sand lenses	CH												
50																	

Comments: Coordinates: North 484210.581, East 3683302.379  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.03 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/06/96 Boring: ALGW-1U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50		11			Medium compact gray sandy silt	ML												
		5			Soft to medium stiff gray clay w/silt lenses	CH												
					Medium stiff gray clay w/silty sand pockets	CH	22C	55.1	49	70	105	UU	0	754	73	25	48	
60							24B	62.4	42	77	110	UU	0	804	65	25	40	
							24C	63.5	50	71	106	UC		919				
							25C	67.5	51	71	107	UC		689				
70							26C	71.5	55	68	105	UC	0	964	88	26	62	
							26D	71.8	52	69	107	UU		990				
					Stiff gray clay	CH	27C	75.5	59	65	103	UC		1169	83	25	58	CONS
					Medium stiff gray clay w/silt lenses & pockets, & silty sand pockets	CH	27D	75.8	59	65	104							
80					Soft gray clay w/shell fragments	CH	28C	79.3	27						32	18	14	
90																		
100																		

Comments: Coordinates: North 484210.581, East 3683302.379  
 5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.47 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/12/96 Boring: ALGW-2U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & dark gray clay w/shells, concrete fragments, & roots	CH												
					Medium stiff gray, dark gray, & tan clay w/clayey silt pockets & shells	CH												
					Stiff gray & brown silty clay w/silt layers & lenses, fine sand layers, organic matter, & oxidized pockets	CL	2B	5.3	28	90	116	UU	0	492	47	22	25	
					Soft gray clay w/oxidized pockets, silt lenses & pockets, large organic matter pockets, & decayed wood	CH												
					Soft gray silty clay w/silty sand lenses & wood	CL												
10					Medium dense gray silty sand w/clay layers & wood	SM												
					Soft gray clay w/silt layers & lenses, & trace of organic matter	CH	5C	18.4	58	66	104	UU	0	475	97	21	76	
20					Medium stiff gray clay w/silt lenses & layers, & fine sand laeyrs	CH	6C	22.0	48	73	108				71	22	49	
					Soft gray clay w/silt lenses	CH												
					Stiff gray clay w/silty sand & clayey silt pockets	CH												
30					Medium stiff gray clay w/silt layers & lenses	CH	9C	34.4	45	77	112	UU	0	538	67	25	42	
					Medium stiff gray clay w/clayey silt pockets	CH												
40							11B	41.5	55	67	105	UU	0	646	84	27	57	
							11C	42.5	52	69	106	UC		512				
							12C	46.5	52	69	105	UC		470				
50																		

Comments: Coordinates: North 484210.581, East 3683302.379  
5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 3.47 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/12/96 Boring: ALGW-2U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
50				Medium stiff gray clay	CH	13C	49.9	49	72	108	UU	0	679	75	24	51	
						13C	50.5	57	66	103	UC		499				
				w/silty sand pockets		14C	54.5	52	69	104	UC		491				
						15C	58.5	54	66	102	UC	0	551				
						15D	58.8	53	69	107	UU		725	86	29	57	
				w/silty lenses & pockets, & trace of organic matter		16C	62.5	52	69	105	UC		756				
						17C	66.1	55	67	105	UU	0	753	89	30	69	
						18C	70.5	27						25	17	8	
						19B	73.5	31						36	17	19	
						20B	78.0	21						26	12	14	
				Soft gray silty clay w/silt layers & lenses, & shell fragments	CL												
				Stiff tan & gray silty clay w/shell fragments	CL												

**Comments:** Coordinates: North 484210.581, East 3683302.379  
5-in. diameter samples



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.58 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/08 & 3/11/96 Boring: ALGW-3U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPT R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0		8			Loose gray & tan clayey silt w/roots w/silty sand pockets	ML												
		8			Medium stiff gray clay w/clayey silt lenses & pockets, & shell fragments	CH												
10					Soft gray clay w/silt lenses & shell fragments	CH	4B	9.1	66	59	98	UU	0	314	100	32	68	
					Stiff gray clay w/clayey silt pockets & wood	CH												
20					Medium stiff gray clay w/clayey silt lenses & shell fragments	CH	7B	21.5	67	61	102	UU	0	553	95	26	69	
							7C	21.8	73	57	98	UC		511				
							8C	26.4	57	65	100	UU	0	613	92	28	64	
30					Soft gray sandy clay w/clayey sand layers & pockets	CL												
40					Medium stiff gray clay w/silt lenses	CH	12C	42.0	53	68	106	UU	0	603	81	25	56	
50							13C	46.1	68	60	101				93	26	67	CONS

Comments: Coordinates: North 490347.872, East 3691858.068  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 9.58 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/08 & 3/11/96 Boring: ALGW-3U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
									Dry	Wet	Type	φ	C	LL	PL	PI	
50				Medium stiff gray clay	CH	14C	50.5	56	67	105	UC		500				
				w/silt layers & lenses		15C	54.5	61	64	103	UC	0	548				
				w/silt pockets		15D	54.8	52	69	106	UU		554	73	28	45	
						16B	57.6	57	67	105	UC		712				
				w/silt layers & lenses		17B	61.6	56	67	104	UC	0	677				
60						17C	62.1	60	64	104	UU		746	96	27	69	
70						19C	70.1	58	64	102	UU	0	758	97	30	67	
				Medium stiff gray sandy clay w/clayey sand & clay layers, & shells	CL												
				Medium stiff gray clay w/clayey sand layers & pockets, & shells	CH												
80																	
90																	
100																	

Comments: Coordinates: North 490347.872, East 3691858.068  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.91 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/18/96 Boring: ALGW-4U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff gray silty clay w/shells & roots	CL												
					Very soft gray clay w/silt layers & pockets, & roots	CH	2B	4.4	55	67	106	UU	0	81	58	20	38	
10					Very loose gray clayey silt w/silty sand layers & pockets	ML												
		4			Loose gray clayey silt w/silty sand & clay layers	ML												
		5			Soft gray silty clay w/silty sand pockets & shell fragments	CL												
		7			Soft gray organic clay w/trace of organic matter	OH	8C	22.1	85	50	93	UU	0	430	128	35	93	
20		3			Very soft gray clay w/shell fragments & silt lenses, & pockets	CH	9D	26.7	76	57	100	UC		213				
					Soft gray clay w/silt layers & lenses	CH	10B	29.5	57	65	104	UU	0	319	72	24	48	
					Very soft gray clay w/silt layers & lenses	CH	10C	30.5	70	60	101	UC		211				
					Soft gray clay w/silt layers & lenses	CH	11C	34.5	58	68	107	UC		323				
30					Very soft gray clay w/silt lenses & pockets	CH	12C	38.5	69	59	100	UC	0	210	101	31	70	
					Soft gray clay w/silt lenses & pockets	CH	12D	38.8	63	63	103	UU		411				
							3C	42.5	70	59	99	UC		396				
40					Medium stiff gray clay w/silt layers & lenses	CH	14C	46.1	71	63	107	UC	0	396	83	26	57	
							14D	46.4	68	60	101	UU		497				
50																		

Comments: Coordinates: North 492391.906, East 3694557.800  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.91 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/18/96 Boring: ALGW-4U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Soft gray clay w/silt pockets	CH	15C	50.3	56	72	113	UC		314				CONS
					Medium stiff gray clay w/silt layers & lenses	CH	16C 16D	54.1 54.4	64 61	63 63	103 103	UC UU	0	452 562	89	30	59	
							17C 17C	57.5 58.0	64 60	62 65	102 105	UC		543	86	33	53	
60					Soft gray clay w/silt layers & lenses	CH	18C 18C	61.6 62.2	65 61	62 64	102 102	UU UC	0	548 420	92	28	64	
		11			Medium dense gray clayey sand w/shell fragments	SC												
		7			Loose gray clayey sand w/clay layers & shell fragments	SC												
70		7																
		27			Medium dense greenish-gray & tan clayey sand	SC												
		37			Dense greenish-gray & tan fine sand	SP												
		50 = 11"			Very dense gray fine sand	SP												
		26			Medium compact gray clayey silt w/silty sand pockets, shell fragments, & clay layers	ML												
80		32			Compact gray clayey silt w/silty sand pockets, shell fragments, & clay layers	ML												
90																		
100																		

Comments: Coordinates: North 492391.906, East 3694557.800  
 5-in. diameter samples

# LOG OF BORING AND TEST RESULTS

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.06 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/16/96 Boring: ALGW-5U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff dark gray & tan clay w/shells & roots	CH	1C	2.4	44									
					Medium stiff brown & gray clay w/clay layers & lenses	CH											66	22
					Loose black humus w/clay layers	Pt	3B 3C	9.4 9.7	63 75	62 56	103 99	UU UC	0	383 343	98	27	71	
10					Soft gray clay w/organic matter, peat pockets, & silt	CH												
					Very soft gray clay w/silt, organic matter & shell fragments	CH	4D	14.4	79	55	95	UU	0	224	89	29	60	
					Loose black humus w/wood & clay layers	Pt	6C	21.3	70	58	98				88	26	62	
20					Soft gray clay w/silt lenses & pockets, & trace of decayed wood	CH												
					Soft gray organic clay w/organic matter, lenses, & pockets	OH	7D	27.2	121	38	84	UU	0	392	188	63	125	
					Soft gray clay w/silt pockets & decayed wood	CH	8C	30.5	118	39	85	UC		411				
							9C	33.6	43	76	109	UU	0	325	90	19	71	
							11C 11D	42.5 42.8	66 65	60 62	100 102	UC UU	0	341 415	92	31	61	
					Very soft gray clay w/silt layers & lenses	CH	12C	46.1	68	59	99	UC		217				
50																		

Comments: Coordinates: North 495298.753, East 3697204.168  
5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 7.06 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/16/96 Boring: ALGW-5U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent		Density			Shear Tests			Atterberg Limits			Other Tests
								Dry	Wet	Dry	Wet	Type	$\phi$	C	LL	PL	PI		
50				Soft gray clay w/silt lenses & layers	CH	13C	49.9	63	63	102	UC	0	368	98	31	67			
						13D	50.2	66	61	101	UU		447						
60				Medium stiff gray clay w/silt layers & lenses	CH	14C	54.4	61	63	102	UC		342	90	27	63			
						15C	57.8	67	60	100	UC	0	310						
70						15D	58.1	59	64	102	UU		488						
						16C	62.2	55	66	103	UC		437						
80	9	7		Loose gray clayey silt w/silty sand pockets & clay layers	ML	18C	69.9	65	59	99	UU	0	678	94	33	61			
						18C	70.5	67	60	100	UC		590						
90						19C	74.5	51	69	104	UC	0	352	86	31	55			
						19D	74.8	55	66	103	UU		576						
100																			

Comments: Coordinates: North 495298.753, East 3697204.168  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.18 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/11/96 Boring: ALGW-6U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Medium stiff gray clay w/clayey silt lenses, roots, grass, & organic matter	CH	2D	6.2	39	77	108	UU	0	503	69	23	46	
10					Soft gray clay w/clay layers & lenses	CH	4C 4D	13.9 14.2	36 37	86 83	117 115	UC UU	0	327 264	40	18	22	
20					Loose gray clayey silt w/silty sand pockets	ML												
14					w/clay layers													
16					Medium dense gray silty sand	SM												
13																		
30					Loose gray silty sand w/clay layers	SM												
8																		
10																		
9																		
9																		
40					Medium stiff gray silty clay w/silty sand layers & pockets	CL												
8					Medium stiff gray clay	CH												
50							17B 17C 17D	45.9 46.5 46.8	58 51 54	66 70 68	104 105 106	UC UU	0	509 695	92 82	27 26	65 56	CONS

Comments: Coordinates: North 502723.351, East 3700920.051  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -1.18 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/11/96 Boring: ALGW-6U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Medium stiff gray clay	CH	18C	50.5	54	67	103	UC		581				
					Medium stiff dark gray clay	CH												
					Medium stiff gray clay w/silt pockets	CH	19C 19D	54.5 54.8	53 60	68 64	105 103	UC UU	0	717 747	102	32	70	
60							20C	58.2	53	69	106	UC		794				
							21D	62.6	52	66	101	UU	0	683	85	27	58	
		9			Loose gray silty sand w/clay layers & shell fragments	SM												
		10			Loose gray clayey sand w/shell fragments	SC												
		12			Medium dense gray clayey sand w/shell fragments	SC												
70		9			Loose gray clayey sand w/shell fragments	SC												
		8			Loose gray clayey sand w/shell fragments & clay layers													
		11			Medium dense gray clayey sand w/shell fragments	SC												
		14																
		11																
80		13																
90																		
100																		

Comments: Coordinates: North 502723.351, East 3700920.051  
 5-in. diameter samples



**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.37 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12-15/96 Boring: ALGW-7U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff gray & tan silty clay w/silty sand pockets & roots	CL												
					Medium stiff gray & tan clay w/clayey silt pockets, organic matter, & wood	CH												
10					Soft gray clay w/silt lenses & pockets, organic matter, & few concretions	CH	3C	9.7	56	67	105	UU	0	292	70	26	44	
20					Medium stiff gray & brown clay w/trace of organic matter lenses, & silt pockets	CH	5C	18.1	67	57	95	UU	0	706	104	36	68	
					Soft gray clay w/clayey silt pockets	CH												
30					Medium stiff gray clay w/silt layers & lenses	CH	8B	29.7	71	58	100	UU	0	493	97	32	65	
					Soft gray clay w/silt layers & lenses	CH	8C	30.3	85	52	96	UC		411				
40		17			Medium compact gray clayey silt w/clay layers	ML												
		13			Loose gray clayey silt w/clay layers	ML												
		8			Soft gray clay	CH												
		4																
50							14C	46.2	48	73	108	UC	0	289	67	23	44	
							14D	46.5	49	73	109	UU		378				

Comments: Coordinates: North 507430.878, East 3703361.531  
 5-in diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.37 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/12-15/96 Boring: ALGW-7U Refer to "Legends & Notes"

Scale in Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth in Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Soft gray clay	CH	15C	50.5	58	65	103	UC		321				CONS
							16C	54.5	58	67	106	UC	0	421	92	27	65	
							16D	54.8	62	64	102	UU		460				
							17C	57.2	64	62	102	UC		285	91	31	60	
							17C	57.8	51	71	107	UC						
60					Medium stiff gray clay w/silt lenses & pockets	CH	18C	62.4	60	65	104	UC	0	526	91	27	64	
							18D	62.7	61	63	102	UU		515				
							19C	65.8	56	67	104	UC		555				
70		4			Very loose gray clayey silt w/clay layers & silty sand pockets	ML												
		6			Loose gray clayey silt w/clay layers & silty sand pockets	ML												
		7																
		3			Soft gray sandy clay w/many shell fragments	CL												
		7				CL												
		8			Medium stiff gray silty clay w/many shells & shell fragments													
80																		
90																		
100																		

Comments: Coordinates: North 507430.878, East 3703361.531  
 5-in diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -3.21 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/10/96 Boring: ALGW-8U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Stiff dark gray clay w/roots & organic matter	CH												
					Medium stiff gray & tan clay w/organic matter, roots, & humus	CH												
10					Soft gray clay w/silt layers & lenses	CH	4C	14.4	49	73	108	UU	0	296	56	20	36	
					Medium stiff gray clay w/silt pockets, trace of concretions, & trace of decayed wood	CH	5B	17.5	89	49	93				118	26	92	CONS
20					Loose gray silty sand	SM												
					Medium stiff gray clay w/clayey silt pockets	CH												
30					Soft gray clay w/silt layers & lenses	CH	7C 7D	26.5 26.8	55 75	68 56	106 98	UC UU	0	233 271	97	28	69	
							8C	30.5	68	59	100	UC		270				
40							9C 9D	34.5 34.8	70 58	58 65	99 103	UC UU	0	323 327	76	23	53	
							10D	38.7	65	62	102	UC		258				
50					Very soft gray clay w/silt pockets	CH	11C 11D	42.0 42.7	66 58	60 66	100 104	UU UC	0	492 335	96	32	64	
							12C	46.5	64	61	100	UC		158				

Comments: Coordinates: North 511549.059, East 3705397.981  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: -3.21 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 4/10/96 Boring: ALGW-8U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Very soft gray clay w/silt pockets	CH	13C	50.5	58	65	103	UC	0	252	85	27	58	
					Soft dark gray clay	CH	13D	50.8	57	66	104	UU	0	550				
							14C	54.5	56	66	103	UC		441				
					Medium stiff gray clay w/silty sand layers & lenses	CH	15B	57.4	58	65	103	UU	0	655	84	27	57	
60		13			Medium dense gray clayey sand	SC												
		8																
					Loose gray clayey sand w/clay layers & shell fragments	SC												
					Medium stiff gray clay w/silt layers & pockets, & shell fragments	CH	18C	66.1	59	64	103	UU	0	798	94	29	65	
70																		
					Loose gray sandy silt w/shell fragments	ML												
					Medium stiff gray sandy clay w/clay layers & lenses, & shell fragments	CL	20C	73.8	37	82	112	UU	0	604	38	17	21	
		9																
		7			Loose gray sandy silt w/shell fragments & clay layers	ML												
		3			Soft gray clay w/clayey sand layers & shell fragments	CH												
80																		
90																		
100																		

Comments: Coordinates: North 511549.059, East 3705397.981  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



Ground Elev.: 6.36 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/25/96 Boring: ALGW-9U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	SPLR	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
0					Very stiff gray clay w/roots & grass	CH												
					Stiff gray & tan clay w/roots & organic matter	CH												
					Medium stiff gray & tan clay w/roots & organic matter	CH												
					Soft brown organic clay w/silt layers & lenses, & roots	OH	2C	5.8	91	45	87	UU	0	465	104	34	70	
10					Compact gray clayey silt w/clay layers & silty sand pockets	ML												
					Medium stiff gray & dark gray clay w/silty sand pockets	CH												
20					Medium stiff gray clay w/organic matter & humus	CH	5B	17.2	55	65	101	UU	0	590	110	36	74	
					Soft gray clay w/silt layers & lenses, & trace of organic matter	CH	7B 7C	25.5 26.5	63 65	62 61	103 101	UU UC	0 0	318 337	86	24	62	
30							9C	34.1	62	62	101	UU	0	419	88	25	63	
							10C 10C	37.9 38.5	65 72	61 58	101 99	UC		273	83	25	58	CONS
40							11C 11D	42.5 42.8	59 66	65 60	103 101	UC UU	0 0	298 416	94	27	67	
							12C	46.5	76	55	97	UC		295				
50																		

Comments: Coordinates: North 515626.413, East 3709614.241  
 5-in. diameter samples

**LOG OF BORING AND TEST RESULTS**  
 U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA





Ground Elev.: 6.36 Datum: NGVD Gr. Water Depth: See Text Job No.: 14638 Date Drilled: 3/25/96 Boring: ALGW-9U Refer to "Legends & Notes"

Scale In Feet	PP	SPT	S P L R	Symbol	Visual Classification	USC	Sample Number	Depth In Feet	Water Content Percent	Density		Shear Tests			Atterberg Limits			Other Tests
										Dry	Wet	Type	φ	C	LL	PL	PI	
50					Soft gray clay w/silt layers & lenses, & trace of organic matter	CH	13C 13D	50.5 50.8	63 62	83 62	102 102	UC UU	0	341 379	89	23	66	
					Medium stiff gray clay	CH	14C	54.5	65	61	101	UC		435				
60					Medium stiff gray clay	CH	15C 15D	58.5 58.8	66 62	61 62	100 103	UC UU	0	576 562	82	23	59	
		18			Medium dense gray silty sand w/clay layers & shell fragments	SM												
		7			Loose gray silty sand w/clay layers	SM												
70		8			Medium stiff gray sandy clay w/clay layers & shell fragments	CL												
					Soft gray clay w/shell fragments	CH	21C	74.5	31						29	23	6	
80					Medium stiff gray clay w/shell fragments	CH	22C 22C	77.9 78.5	29 30	94	121	UU	0	856	32 56	20 22	12 34	
					Soft gray clay w/shell fragments	CH												
					Stiff gray clay w/clayey sand & clayey sand pockets, & shell fragments	CH												
90																		
100																		

Comments: Coordinates: North 515626.413, East 3709614.241  
 5-in. diameter samples

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
99.8 %	58.8	65.4	83	58	2.740	1.92	0.78	1.6144

### TEST RESULTS

Compression Index = 0.78

### MATERIAL DESCRIPTION

M Gr CH4 w/ Ins, ars ML & ars SM

Class: CH

Remarks:

Water table = N/A  
Contract No.  
DACW29-95-D-0012



Project No.: 13622  
Project: Algiers Levees  
Location: Boring ALGW-1U, Sample 27-D  
Depth 75.8'  
Date: 7-18-96

CONSOLIDATION TEST REPORT

Tested by RNE  
Fig. No. \_\_\_\_\_

## EUSTIS ENGINEERING COMPANY, INC.

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	C <sub>c</sub>	e <sub>0</sub>
98.1 %	48.0	72.9	71	49	2.720	1.11	0.43	1.3308


TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.43  Project No.: 13622 Project: Algiers Levees Location: Boring ALGW-2U, Sample 6-C Depth 22.0' Date: 7-18-96	M Gr CH3 w/ Ins, lyr ML & Ins, lyr SP Class: CH Remarks: Water table = N/A Contract No. DACW29-95-D-0012 Tested by RNE Fig. No. _____

CONSOLIDATION TEST REPORT

EUSTIS ENGINEERING COMPANY, INC.




# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.8 %	67.5	60.5	93	67	2.750	1.45	1.01	1.8398

TEST RESULTS	MATERIAL DESCRIPTION
<p>Compression Index = 1.01</p>	<p>M Gr CH4 w/ Ins ML Class: CH</p>
<p>Project No.: 13622 Project: Algiers Levees Location: Boring ALGW-3U, Sample 13-C Depth 46.1' Date: 7-30-96</p>	<p>Remarks: Water table = N/A Contract No. DACW29-95-D-0012</p>
<p>CONSOLIDATION TEST REPORT</p> <p><b>EUSTIS ENGINEERING COMPANY, INC.</b></p>	<p>Tested by RNE Fig. No. _____</p>



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.6 %	64.0	62.4	86	53	2.750	1.40	0.80	1.7509

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.80	M Gr CH4 w/ Ins. 1yr ML Class: CH
Project No.: 13622 Project: Algiers Levees Location: Boring ALGW-4U, Sample 17-C Depth 57.5' Date: 7-30-96	Remarks: Water table = N/A Contract No. DACW29-95-D-0012
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	Tested by RNE Fig. No. _____

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	C <sub>c</sub>	e <sub>0</sub>
97.1 %	69.8	57.7	88	62	2.750	0.55	0.76	1.9749

### TEST RESULTS

Compression Index = 0.76

Project No.: 13622  
 Project: Algiers Levees  
 Location: Boring ALGW-5U, Sample 6-C  
 Depth 21.3'  
 Date: 7-30-96

### MATERIAL DESCRIPTION

So Gr CH4 w/ Ins, ars  
 ML & tr dec wd  
 Class: CH



Remarks:  
 Water table = N/A  
 Contract No.  
 DACW29-95-D-0012

CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**

Tested by RNE  
 Fig. No. \_\_\_\_\_



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
99.4 %	58.3	65.7	92	65	2.750	1.19	0.69	1.6130

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.69  Project No.: 13622 Project: Algiers Levees Location: Boring ALGW-6U, Sample 17-C Depth 45.9' Date: 7-30-96	M Gr CH4 w/ Ins, ars ML Class: CH Remarks: Water table = N/A Contract No. DACW29-95-D-0012  Tested by RNE Fig. No. _____
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.6 %	64.2	62.3	91	60	2.750	1.29	0.88	1.7538

### TEST RESULTS

Compression Index = 0.88

Project No.: 13622  
 Project: Algiers Levees  
 Location: Boring ALGW-7U, Sample 17-C  
 Depth 57.2'  
 Date: 7-30-96

### CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**

### MATERIAL DESCRIPTION



So Gr CH4  
 w/ Ins, ars ML  
 Class: CH

#### Remarks:

Water table = N/A  
 Contract No.  
 DACW29-95-D-0012

Tested by RNE  
 Fig. No. \_\_\_\_\_

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.4 %	89.1	49.3	118	92	2.650	0.54	1.25	2.3530

### TEST RESULTS

Compression Index = 1.25

### MATERIAL DESCRIPTION

M Gr CH4 w/ ars ML & tr conc & tr dec wd  
Class: CH

#### Remarks:

Water table = N/A  
Contract No. DACW29-95-D-0012



Project No.: 13622  
Project: Algiers Levees  
Location: Boring ALGW-8U, Sample 5-B  
Depth 17.5'  
Date: 7-30-96

CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**

Tested by RNE  
Fig. No. \_\_\_\_\_



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	Pl	Sp.Gr.	Precons. press.	Cc	e <sub>o</sub>
99.8 %	64.9	61.5	83	58	2.740	1.00	0.86	1.7834

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.86  Project No.: 13622 Project: Algiers Levees Location: Boring ALGW-9U, Sample 10-C Depth 37.9' Date: 7-30-96	So Gr CH3 w/ lyr, Ins ML Class: CH Remarks: Water table = N/A Contract No. DACW29-95-D-0012 Tested by RNE Fig. No. _____
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	

# CONSOLIDATION TEST REPORT





Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
99.4 %	56.2	67.1	88	61	2.740	1.73	0.70	1.5496

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.70  Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-1U, Sample 18-D Depth 63.8' Date: 8-23-96	M Gr CH4 w/ ars & lyr ML Class: CH  Remarks: Water table = N/A Contract No. DACW29-95-D-0012  Tested by RNE & RET Fig. No. _____
CONSOLIDATION TEST REPORT  <b>EUSTIS ENGINEERING COMPANY, INC.</b>	



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	C <sub>c</sub>	e <sub>0</sub>
99.2 %	58.1	65.7	77	58	2.740	1.05	0.72	1.6044

### TEST RESULTS

### MATERIAL DESCRIPTION

Compression Index = 0.72

So Gr CH4  
w/ Ins & ars ML  
Class: CH

Project No.: 13622  
Project: Algiers Levees  
Location: Boring ALGE-2U, Sample 13-D  
Depth 41.8'  
Date: 8-23-96


Remarks:  
Water table = N A  
Contract No.  
DACW29-95-D-0012

CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**

Tested by RNE & RET  
Fig. No. \_\_\_\_\_


# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
89.4 %	123.4	35.2	177	125	2.550	2.28	1.98	3.5209

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 1.98	M DGr & Bk CHOC w/ lyr & Ins PT, ars CH Class: OH
Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-3U, Sample 6-B Depth 17.1' Date: 8-23-96	Remarks: Water table = N A Contract No. DACW29-95-D-0012
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	Tested by RNE & RET Fig. No. _____



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.6 %	65.5	61.4	89	56	2.740	1.52	0.95	1.7855

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.95	M Gr CH4 w/ Ins & lyr ML Class: CH
Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-4U, Sample 17-B Depth 61.5' Date: 8-23-96	Remarks: Water table = N A Contract No. DACW29-95-D-0012
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	Tested by RNE & RET Fig. No. _____



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
98.2 %	47.4	73.2	50	31	2.700	0.94	0.43	1.3036

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.43	So Gr CH2 w/ Ins & 1yr ML Class: CL
Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-5U, Sample 12-C Depth 39.9' Date: 8-23-96	Remarks: Water table = N A Contract No. DACW29-95-D-0012
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	Tested by RNE & RET Fig. No. _____


# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
95.6 %	34.7	85.1	36	13	2.700	2.85	0.20	0.9799

TEST RESULTS	MATERIAL DESCRIPTION
<p>Compression Index = 0.20</p>	<p>So Gr CL4 w/ Ins, 1yr ML &amp; CH3 Class: CL</p>
<p>Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-6U, Sample 5-B Depth 16.7' Date: 8-23-96</p>	<p>Remarks: Water table = N A Contract No. DACW29-95-D-0012</p>
<p>CONSOLIDATION TEST REPORT</p>	<p>Tested by RNE &amp; RET Fig. No. _____</p>
<p><b>EUSTIS ENGINEERING COMPANY, INC.</b></p>	



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
99.2 %	57.7	66.0	94	66	2.750	1.97	0.77	1.6006

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.77	M Gr CH4 w/ ars & Ins ML Class: CH
Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-7U, Sample 26-D Depth 66.8' Date: 8-23-96	Remarks: Water table = N A Contract No. DACW29-95-D-0012
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	Tested by RNE & RET Fig. No. _____

# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
100.0 %	69.5	59.0	88	56	2.750	0.94	0.94	1.9117

### TEST RESULTS

Compression Index = 0.94

Project No.: 13622  
 Project: Algiers Levees  
 Location: Boring ALGE-8U, Sample 11-D  
 Depth 38.8'  
 Date: 8-23-96

### MATERIAL DESCRIPTION

M Gr CH4  
 w/ Ins & lyr ML  
 Class: CH



Remarks:  
 Water table = N A  
 Contract No.  
 DACW29-95-D-0012

CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**

Tested by RNE & RET  
 Fig. No. \_\_\_\_\_

# CONSOLIDATION TEST REPORT





Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	e <sub>0</sub>
91.8 %	59.4	61.8	81	55	2.750	0.93	0.85	1.7778

TEST RESULTS	MATERIAL DESCRIPTION
Compression Index = 0.85  Project No.: 13622 Project: Algiers Levees Location: Boring ALGE-9U, Sample 11-C Depth 42.1' Date: 8-23-96	VSo Gr CH3 w/ Ins & ars ML Class: CH Remarks: Water table = N/A Contract No. DACW29-95-D-0012  Tested by RNE Fig. No. _____
CONSOLIDATION TEST REPORT <b>EUSTIS ENGINEERING COMPANY, INC.</b>	



# CONSOLIDATION TEST REPORT



Natural Saturation	Natural Moisture	Dry Density	LL	PI	Sp.Gr.	Precons. press.	Cc	eo
99.8 %	62.9	62.8	87	59	2.750	1.31	0.82	1.7325

### TEST RESULTS

### MATERIAL DESCRIPTION

Compression Index = 0.82

So Gr CH4  
w/ ars ML  
Class: CH

Remarks:



Water table = N/A  
Contract No.  
DACW29-95-D-0012

Tested by RNE  
Fig. No. \_\_\_\_\_

Project No.: 13622  
Project: Algiers Levees  
Location: Boring ALGE-10U, Sample 15-C  
Depth 57.6'  
Date: 8-23-96

CONSOLIDATION TEST REPORT

**EUSTIS ENGINEERING COMPANY, INC.**



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	33.9	29.6	33.5
	DRY DENSITY, pcf	83.5	90.7	85.5
	SATURATION, %	90.8	94.1	94.2
	VOID RATIO	0.997	0.838	0.950
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	3.00	2.99	2.99
AT TEST	WATER CONTENT, %	37.7	31.4	35.5
	DRY DENSITY, pcf	83.0	90.7	85.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.007	0.838	0.948
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.99	2.99	2.99
Strain rate, in/min		0.0954	0.0996	0.0988
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		936	1063	1385
ULTIMATE STRESS, psf		749	914	1385
$\sigma_1$ FAILURE, psf		1944	3079	4409
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CL4  
w/ Ins & ars ML

LL= 33      PL= 19      PI= 14

SPECIFIC GRAVITY= 2.67

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-1U,  
Sample 3-C, Depth 6.0'

PROJ. NO.: 13622      DATE: 6-25-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-1U, Sample 3-C, Depth 6.0'

File: UU-6797

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	45.2	47.8	50.6
	DRY DENSITY, pcf	74.5	72.5	71.5
	SATURATION, %	95.6	96.5	99.5
	VOID RATIO	1.296	1.359	1.393
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	47.3	49.4	50.6
	DRY DENSITY, pcf	74.5	72.7	71.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.295	1.353	1.387
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10140	0.10060	0.0990	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	888	947	904	
ULTIMATE STRESS, psf	858	702	695	
$\sigma_1$ FAILURE, psf	1896	2963	3928	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ lyr & Ins ML, ars org  
 LL= 70      PL= 19      PI= 51  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 5-C, Depth 14.1'

PROJ. NO.: 13622      DATE: 6-25-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 5-C, Depth 14.1'  
 File: UU-6798 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	34.3	33.7	38.9
	DRY DENSITY, pcf	85.2	87.8	81.1
	SATURATION, %	94.9	99.0	97.3
	VOID RATIO	0.978	0.920	1.079
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.78	2.81
AT TEST	WATER CONTENT, %	36.1	33.7	41.0
	DRY DENSITY, pcf	85.3	88.3	80.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.975	0.910	1.108
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.79	2.80
Strain rate, in/min	0.10280	0.10130	0.1025	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	605	1186	764	
ULTIMATE STRESS, psf	717	1186	742	
$\sigma_1$ FAILURE, psf	1613	3202	3788	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL4  
 w/ lyr & ars CH  
 LL= 39      PL= 19      PI= 20  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 9-C, Depth 27.2'  
 PROJ. NO.: 13622      DATE: 6-25-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 9-C, Depth 27.2'  
 File: UU-6799 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.4	67.4	65.2
	DRY DENSITY, pcf	60.4	60.4	61.3
	SATURATION, %	100.7	100.7	99.7
	VOID RATIO	1.833	1.834	1.791
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.82	2.80	2.80
AT TEST	WATER CONTENT, %	68.9	66.9	65.2
	DRY DENSITY, pcf	59.2	60.4	61.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.888	1.832	1.785
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.10040	0.10040	0.1011
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		437	784	730
ULTIMATE STRESS, psf		292	711	529
$\sigma_1$ FAILURE, psf		1445	2800	3754
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins ML, ars org  
 LL= 92      PL= 30      PI= 62  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 10-D, Depth 31.7'  
 PROJ. NO.: 13622      DATE: 6-25-96

FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-1U, Sample 10-D, Depth 31.7'

File: UU-6800

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	37.1	37.1	38.0
	DRY DENSITY, pcf	83.6	84.0	83.6
	SATURATION, %	97.2	98.1	99.3
	VOID RATIO	1.045	1.036	1.047
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.79
AT TEST	WATER CONTENT, %	38.2	37.7	37.6
	DRY DENSITY, pcf	83.6	84.1	84.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.047	1.033	1.030
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.09700	0.10020	0.1020	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	991	1294	1067	
ULTIMATE STRESS, psf	913	1267	1013	
$\sigma_1$ FAILURE, psf	1999	3310	4091	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH3  
w/ Ins ML

LL= 51      PL= 19      PI= 32  
SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGE-1U,  
Sample 13-D, Depth 43.8'






PROJ. NO.: 13622

DATE: 6-25-96

TRIAxIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 13-D, Depth 43.8'  
 File: UU-6801 Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	45.1	42.6	42.5
	DRY DENSITY, pcf	75.1	77.5	78.5
	SATURATION, %	97.1	97.2	99.3
	VOID RATIO	1.262	1.192	1.163
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	46.3	43.8	42.5
	DRY DENSITY, pcf	75.1	77.5	78.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.260	1.191	1.157
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.10070	0.10110	0.1019
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1048	1089	1209
ULTIMATE STRESS, psf		966	1001	1090
$\sigma_1$ FAILURE, psf		2056	3105	4233
$\sigma_3$ FAILURE, psf		1008	2016	3024



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ Ins & ars ML  
 LL= 66      PL= 23      PI= 43  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 15-D, Depth 51.7'  
 PROJ. NO.: 13622      DATE: 6-25-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 15-D, Depth 51.7'  
 File: UU-6802 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	52.8	50.4	50.9
	DRY DENSITY, pcf	68.3	70.9	70.5
	SATURATION, %	96.5	98.2	98.1
	VOID RATIO	1.486	1.396	1.410
	DIAMETER, in	1.42	1.41	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	54.7	51.2	51.3
	DRY DENSITY, pcf	68.3	71.0	70.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.487	1.393	1.396
Strain rate, in/min	DIAMETER, in	1.42	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1294	1342	1366	
ULTIMATE STRESS, psf	854	910	1043	
$\sigma_1$ FAILURE, psf	2302	3358	4390	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ ars ML  
 LL= 81      PL= 25      PI= 56  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 17-D, Depth 59.8'  
 PROJ. NO.: 13622      DATE: 6-25-96



FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 17-D, Depth 59.8'  
 File: UU-6803                      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	56.6	56.5	57.4
	DRY DENSITY, pcf	64.3	64.5	64.8
	SATURATION, %	93.7	94.1	96.4
	VOID RATIO	1.642	1.634	1.620
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.79	2.79	2.79
AT TEST	WATER CONTENT, %	59.2	59.1	58.0
	DRY DENSITY, pcf	65.1	65.1	65.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.610	1.608	1.577
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.10050	0.10140	0.1005
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		794	970	987
ULTIMATE STRESS, psf		506	728	685
$\sigma_1$ FAILURE, psf		1802	2986	4011
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins & ars ML  
 LL= 94      PL= 27      PI= 67  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-1U,  
 Sample 20-B, Depth 70.5'  
 PROJ. NO.: 13622      DATE: 6-25-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-1U, Sample 20-B, Depth 70.5'

File: UU-6804

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	37.7	37.7	35.2
	DRY DENSITY, pcf	84.0	83.7	85.8
	SATURATION, %	99.6	98.8	97.1
	VOID RATIO	1.036	1.045	0.993
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.79	2.79	2.80
AT TEST	WATER CONTENT, %	37.3	37.5	35.9
	DRY DENSITY, pcf	84.6	84.4	86.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.022	1.027	0.983
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.0985	0.0997	0.1011	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1611	1816	1647	
ULTIMATE STRESS, psf	1398	1450	1141	
$\sigma_1$ FAILURE, psf	2619	3832	4671	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH2  
 w/ lyr & Ins SM, slf  
 LL= 50      PL= 19      PI= 31  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGE-1U,

Sample 22-B, Depth 78.5'






PROJ. NO.: 13622

DATE: 6-25-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-1U, Sample 22-B, Depth 78.5'  
 File: UU-6805      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	96.0	96.8	101.0
	DRY DENSITY, pcf	46.8	46.3	45.0
	SATURATION, %	99.0	98.3	98.8
	VOID RATIO	2.657	2.697	2.801
	DIAMETER, in	1.40	1.40	1.40
AT TEST	HEIGHT, in	2.80	2.80	2.81
	WATER CONTENT, %	97.1	98.6	103.8
	DRY DENSITY, pcf	46.7	46.2	44.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.661	2.702	2.843
Strain rate, in/min	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	727	646	671	
ULTIMATE STRESS, psf	579	487	535	
$\sigma_1$ FAILURE, psf	1735	2662	3695	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ slf  
 LL= 131      PL= 35      PI= 96  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 4-C, Depth 9.9'  
 PROJ. NO.: 13622      DATE: 6-25-96



TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-2U, Sample 4-C, Depth 9.9'  
 File: UU-6806 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.0	58.8	58.8
	DRY DENSITY, pcf	63.5	65.6	65.9
	SATURATION, %	100.3	100.2	100.9
	VOID RATIO	1.694	1.606	1.597
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	61.9	58.8	58.0
	DRY DENSITY, pcf	63.5	65.5	66.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.695	1.612	1.590
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.09530	0.09760	0.1009	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	419	467	391	
ULTIMATE STRESS, psf	392	422	403	
$\sigma_1$ FAILURE, psf	1427	2483	3415	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: VSo Gr CH3  
w/ Ins ML  
LL= 66      PL= 21      PI= 45  
SPECIFIC GRAVITY= 2.74  
REMARKS:

CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGE-2U,  
Sample 5-D, Depth 14.8'  
PROJ. NO.: 13622      DATE: 6-26-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-2U, Sample 5-D, Depth 14.8'  
 File: UU-6807 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.7	60.5	59.8
	DRY DENSITY, pcf	63.6	63.0	64.3
	SATURATION, %	96.8	96.7	98.6
	VOID RATIO	1.689	1.715	1.661
	DIAMETER, in	1.41	1.41	1.40
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	61.8	62.6	60.1
	DRY DENSITY, pcf	63.5	63.0	64.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.692	1.717	1.648
DIAMETER, in	1.41	1.41	1.40	
HEIGHT, in	2.80	2.80	2.80	
Strain rate, in/min	0.099	50.098	10.1010	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	943	852	907	
ULTIMATE STRESS, psf	664	548	711	
$\sigma_1$ FAILURE, psf	1951	2868	3931	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 74      PL= 23      PI= 51  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 10-C, Depth 29.4'  
 PROJ. NO.: 13622      DATE: 6-26-96

FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-2U, Sample 10-C, Depth 29.4'

File: UU-6808

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	50.5	52.5	51.9
	DRY DENSITY, pcf	71.2	69.5	69.6
	SATURATION, %	99.2	98.9	98.1
	VOID RATIO	1.384	1.444	1.439
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.12
AT TEST	WATER CONTENT, %	50.8	53.0	52.3
	DRY DENSITY, pcf	71.3	69.5	70.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.383	1.442	1.424
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.12
Strain rate, in/min	0.09470	0.10150	0.0998	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	556	556	722	
ULTIMATE STRESS, psf	669	563	687	
$\sigma_1$ FAILURE, psf	1564	2572	3746	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins & ars ML  
 LL= 79      PL= 23      PI= 56  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 12-D, Depth 37.8'  
 PROJ. NO.: 13622      DATE: 6-26-96

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-2U, Sample 12-D, Depth 37.8'  
 File: UU-6809      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	56.9	54.8	55.9
	DRY DENSITY, pcf	66.6	67.9	66.0
	SATURATION, %	99.9	99.2	96.8
	VOID RATIO	1.548	1.502	1.572
	DIAMETER, in	1.40	1.40	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	56.9	55.0	57.7
	DRY DENSITY, pcf	66.7	68.0	66.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.548	1.497	1.570
Strain rate, in/min	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1404	1325	1205	
ULTIMATE STRESS, psf	1016	959	955	
$\sigma_1$ FAILURE, psf	2412	3341	4229	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH4  
w/ ars ML  
LL= 88      PL= 21      PI= 67  
SPECIFIC GRAVITY= 2.72  
REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGE-2U,  
Sample 14-B, Depth 44.5'

PROJ. NO.: 13622      DATE: 6-26-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-2U, Sample 14-B, Depth 44.5'

File: UU-6810

Project No.: 13622






FIG. NO.: \_\_\_\_\_





SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	61.4	61.0	59.5
	DRY DENSITY, pcf	63.2	64.1	64.3
	SATURATION, %	99.0	100.7	98.6
	VOID RATIO	1.688	1.648	1.642
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	62.2	60.5	60.3
	DRY DENSITY, pcf	63.1	64.2	64.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.693	1.644	1.641
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09950	0.10070	0.0995
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1043	1294	1313
ULTIMATE STRESS, psf		627	921	991
$\sigma_1$ FAILURE, psf		2051	3310	4337
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins & ars ML  
 LL= 89      PL= 27      PI= 62  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 16-D, Depth 53.8'  
 PROJ. NO.: 13622      DATE: 6-26-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-2U, Sample 16-D, Depth 53.8'  
 File: UU-6811      Project No.: 13622      FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	60.5	59.6	59.2
	DRY DENSITY, pcf	63.1	63.8	64.4
	SATURATION, %	97.4	97.6	98.5
	VOID RATIO	1.689	1.661	1.635
	DIAMETER, in	1.41	1.41	1.40
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	62.1	60.8	59.9
	DRY DENSITY, pcf	63.2	64.0	64.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.688	1.655	1.630
Strain rate, in/min	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1462	1472	1651	
ULTIMATE STRESS, psf	855	977	1126	
$\sigma_1$ FAILURE, psf	2470	3488	4675	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ Ins & ars SP  
 LL= 91      PL= 26      PI= 65  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:






CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 18-B, Depth 60.5'  
 PROJ. NO.: 13622      DATE: 6-26-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-2U, Sample 18-B, Depth 60.5'  
 File: UU-6812 Project No.: 13622 FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	28.4	27.9	27.5
	DRY DENSITY, pcf	93.4	92.3	92.4
	SATURATION, %	95.2	91.1	90.1
	VOID RATIO	0.805	0.827	0.825
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.99	2.99	2.99
AT TEST	WATER CONTENT, %	29.9	30.7	30.7
	DRY DENSITY, pcf	93.2	92.2	92.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.808	0.828	0.829
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.99	2.99	2.99
Strain rate, in/min	0.1017	0.1022	0.1013	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1050	2234	2024	
ULTIMATE STRESS, psf	1112	2234	2024	
$\sigma_1$ FAILURE, psf	2058	4250	5048	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL3  
 w/ sif  
 LL= 23      PL= 16      PI= 7  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-2U,  
 Sample 19-D, Depth 65.8'

PROJ. NO.: 13622      DATE: 6-26-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-2U, Sample 19-D, Depth 65.8'

File: UU-6813

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	32.4	26.5	31.2
	DRY DENSITY, pcf	87.3	92.9	89.2
	SATURATION, %	93.8	87.8	94.5
	VOID RATIO	0.932	0.815	0.890
	DIAMETER, in	1.41	1.42	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.79
	WATER CONTENT, %	34.4	29.9	32.5
	DRY DENSITY, pcf	87.4	93.2	89.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.929	0.808	0.878
AT TEST	DIAMETER, in	1.41	1.42	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.0976	0.1025	0.0969
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1485	2191	1009
ULTIMATE STRESS, psf		1015	2424	1205
$\sigma_1$ FAILURE, psf		2493	4207	4033
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CL6  
 w/ Ins ML, ars CH  
 LL= 45      PL= 15      PI= 30  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 3-D, Depth 6.1'  
 PROJ. NO.: 13622      DATE: 6-26-96



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 3-D, Depth 6.1'  
 File: UU-6814 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.6	77.8	56.4
	DRY DENSITY, pcf	58.3	53.7	66.5
	SATURATION, %	95.8	97.5	98.3
	VOID RATIO	1.935	2.187	1.572
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	70.5	79.6	57.6
	DRY DENSITY, pcf	58.3	53.8	66.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.932	2.180	1.578
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10050	0.10120	0.1027	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	761	915	806	
ULTIMATE STRESS, psf	679	873	775	
$\sigma_1$ FAILURE, psf	1769	2931	3830	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH2 w/ 1yr &  
 Ins CL, lg ars org, & sif  
 LL= 101 PL= 31 PI= 70  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 5-B, Depth 13.4'  
 PROJ. NO.: 13622 DATE: 6-26-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-3U, Sample 5-B, Depth 13.4'

File: UU-6815

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	57.8	56.4	56.4
	DRY DENSITY, pcf	66.1	66.6	66.7
	SATURATION, %	99.6	98.6	98.9
	VOID RATIO	1.588	1.568	1.564
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	58.2	57.3	56.9
	DRY DENSITY, pcf	65.9	66.5	66.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.595	1.571	1.559
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09250	0.10050	0.0991
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1198	1156	1114
ULTIMATE STRESS, psf		874	855	827
$\sigma_1$ FAILURE, psf		2206	3172	4138
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3 w/ lyr &  
 Ins ML, ars org & slf  
 LL= 78      PL= 27      PI= 51  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 8-D, Depth 26.6'  
 PROJ. NO.: 13622      DATE: 6-27-96

FIG. NO.:



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 8-D, Depth 26.6'  
 File: UU-6816 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	49.1	50.0	48.3
	DRY DENSITY, pcf	72.6	72.2	73.6
	SATURATION, %	99.1	100.2	99.9
	VOID RATIO	1.357	1.368	1.325
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.81	2.80	2.80
AT TEST	WATER CONTENT, %	49.9	49.9	48.1
	DRY DENSITY, pcf	72.3	72.2	73.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.367	1.368	1.318
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.1026	0.0952	0.0994	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1297	1240	1371	
ULTIMATE STRESS, psf	1023	940	1021	
$\sigma_1$ FAILURE, psf	2305	3256	4395	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH3  
w/ 1yr & Ins ML

LL= 72      PL= 26      PI= 46

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-3U,  
Sample 17-B, Depth 48.7'

PROJ. NO.: 13622      DATE: 6-27-96

FIG. NO.: \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 17-B, Depth 48.7'  
 File: UU-6817 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.2	53.1	54.7
	DRY DENSITY, pcf	68.2	68.6	67.5
	SATURATION, %	98.5	97.5	97.8
	VOID RATIO	1.507	1.493	1.533
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	55.0	54.1	55.8
	DRY DENSITY, pcf	68.2	68.9	67.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.507	1.484	1.528
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10200	0.09710	0.0934	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1109	1089	805	
ULTIMATE STRESS, psf	1045	908	833	
$\sigma_1$ FAILURE, psf	2117	3105	3829	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 . w/ lyr & Ins ML  
 LL= 83      PL= 24      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 19-D, Depth 57.1'  
 PROJ. NO.: 13622      DATE: 6-27-96

FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-3U, Sample 19-D, Depth 57.1'

File: UU-6818

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	51.3	51.4	50.5
	DRY DENSITY, pcf	70.0	69.9	70.7
	SATURATION, %	97.8	97.7	98.1
	VOID RATIO	1.426	1.430	1.401
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	52.4	52.3	51.5
	DRY DENSITY, pcf	70.0	70.1	70.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.426	1.422	1.401
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.09610	0.09940	0.0988	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	844	298	370	
ULTIMATE STRESS, psf	739	306	378	
$\sigma_1$ FAILURE, psf	1852	2314	3394	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH4  
 w/ ars ML  
 LL= 83      PL= 23      PI= 60  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 20-D, Depth 61.7'  
 PROJ. NO.: 13622      DATE: 6-27-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 20-D, Depth 61.7'  
 File: UU-6819 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.6	54.1	54.0
	DRY DENSITY, pcf	66.8	67.1	67.0
	SATURATION, %	95.9	95.7	95.2
	VOID RATIO	1.560	1.550	1.552
	DIAMETER, in	1.40	1.40	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.81
	WATER CONTENT, %	57.0	56.8	57.5
	DRY DENSITY, pcf	66.7	66.9	66.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.563	1.556	1.574
Strain rate, in/min	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
	BACK PRESSURE, psf	0	0	0
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1127	1177	1322	
ULTIMATE STRESS, psf	789	904	1024	
$\sigma_1$ FAILURE, psf	2135	3193	4346	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins ML  
 LL= 88      PL= 27      PI= 61  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 22-D, Depth 69.8'  
 PROJ. NO.: 13622      DATE: 6-27-96



FIG. NO. : \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 22-D, Depth 69.8'  
 File: UU-6820      Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.7	57.1	55.9
	DRY DENSITY, pcf	66.3	65.3	66.0
	SATURATION, %	96.5	96.6	96.2
	VOID RATIO	1.581	1.619	1.591
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.79	2.79
AT TEST	WATER CONTENT, %	57.3	58.3	57.4
	DRY DENSITY, pcf	66.6	65.9	66.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.570	1.596	1.574
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.097	0.100	0.0937	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1498	1309	1663	
ULTIMATE STRESS, psf	1124	871	1342	
$\sigma_1$ FAILURE, psf	2506	3325	4687	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr SP  
 LL= 88      PL= 26      PI= 62  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-3U,  
 Sample 24-B, Depth 75.8'  
 PROJ. NO.: 13622      DATE: 6-27-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-3U, Sample 24-B, Depth 75.8'  
 File: UU-6821 Project No.: 13622

FIG. NO.: \_\_\_\_\_






SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	271.4	271.6	248.5
	DRY DENSITY, pcf	19.2	19.3	21.1
	SATURATION, %	94.4	95.4	96.5
	VOID RATIO	7.473	7.405	6.691
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	288.3	283.9	256.7
	DRY DENSITY, pcf	19.1	19.4	21.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	7.497	7.381	6.673
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.106	0.1056	0.1093
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		661	675	644
ULTIMATE STRESS, psf		600	620	615
$\sigma_1$ FAILURE, psf		1669	2691	3668
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So BK PEAT  
 w/ rts  
 LL= 307      PL= 109      PI= 198  
 SPECIFIC GRAVITY= 2.6  
 REMARKS:



FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 3-C, Depth 5.8'  
 PROJ. NO.: 13622      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 3-C, Depth 5.8'  
 File: UU-6822                      Project No.: 13622                      FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	88.5	87.0	86.8
	DRY DENSITY, pcf	49.5	50.6	50.5
	SATURATION, %	98.7	100.2	99.6
	VOID RATIO	2.456	2.380	2.389
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.81
AT TEST	WATER CONTENT, %	89.6	86.7	88.3
	DRY DENSITY, pcf	49.5	50.7	50.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.455	2.374	2.418
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.1058	0.0953	0.1028
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		675	779	584
ULTIMATE STRESS, psf		460	529	453
$\sigma_1$ FAILURE, psf		1683	2795	3608
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ 1yr & Ins ML, sif  
 LL= 110    PL= 34    PI= 76  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 6-D, Depth 18.8'  
 PROJ. NO.: 13622                      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 6-D, Depth 18.8'  
 File: UU-6823 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	68.4	68.3	67.0
	DRY DENSITY, pcf	59.8	60.0	60.4
	SATURATION, %	100.8	101.1	100.1
	VOID RATIO	1.859	1.852	1.834
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.83	2.81
AT TEST	WATER CONTENT, %	67.9	70.4	67.4
	DRY DENSITY, pcf	59.8	58.4	60.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.861	1.929	1.846
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10280	0.09850	0.0914	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	670	584	292	
ULTIMATE STRESS, psf	535	400	221	
$\sigma_1$ FAILURE, psf	1678	2600	3316	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ 1yr & Ins ML  
 LL= 82      PL= 24      PI= 58  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 8-B, Depth 25.5'  
 PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**







Stress Paths: + indicates end    o indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 8-B, Depth 25.5'  
 File: UU-6824      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.9	68.3	68.0
	DRY DENSITY, pcf	59.7	59.6	59.6
	SATURATION, %	99.7	100.0	99.7
	VOID RATIO	1.867	1.871	1.870
	DIAMETER, in	1.40	1.40	1.40
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	68.4	67.9	68.1
	DRY DENSITY, pcf	59.5	59.8	59.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.873	1.859	1.867
Strain rate, in/min	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	362	693	680	
ULTIMATE STRESS, psf	276	610	592	
$\sigma_1$ FAILURE, psf	1370	2709	3704	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST: Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & ins ML  
 LL= 90      PL= 26      PI= 64  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 10-D, Depth 34.8'  
 PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_



TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 10-D, Depth 34.8'  
 File: UU-6825 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	69.9	69.6	68.9
	DRY DENSITY, pcf	59.1	58.6	59.2
	SATURATION, %	101.5	99.9	100.4
	VOID RATIO	1.873	1.896	1.867
	DIAMETER, in	1.40	1.41	1.40
AT TEST	HEIGHT, in	2.80	2.81	2.81
	WATER CONTENT, %	68.9	70.4	69.5
	DRY DENSITY, pcf	59.1	58.3	58.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.875	1.915	1.890
Strain rate, in/min	DIAMETER, in	1.40	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	739	801	799	
ULTIMATE STRESS, psf	602	682	599	
$\sigma_1$ FAILURE, psf	1747	2817	3823	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins & ars ML  
 LL= 95      PL= 26      PI= 69  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 12-D, Depth 42.8'  
 PROJ. NO.: 13622      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-4U, Sample 12-D, Depth 42.8'

File: UU-6826

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	57.4	56.7	57.5
	DRY DENSITY, pcf	65.5	66.4	66.0
	SATURATION, %	97.6	98.7	99.1
	VOID RATIO	1.611	1.575	1.591
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.81	2.80	2.81
AT TEST	WATER CONTENT, %	59.9	57.1	59.2
	DRY DENSITY, pcf	64.8	66.7	65.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.641	1.566	1.622
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.10650	0.10580	0.1070
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		735	967	922
ULTIMATE STRESS, psf		556	791	677
$\sigma_1$ FAILURE, psf		1743	2983	3946
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ lyr & Ins ML  
 LL= 79      PL= 25      PI= 54  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 14-D, Depth 50.8'  
 PROJ. NO.: 13622      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 14-D, Depth 50.8'  
 File: UU-6827      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.8	63.4	63.6
	DRY DENSITY, pcf	61.8	62.4	61.1
	SATURATION, %	97.3	99.7	96.9
	VOID RATIO	1.768	1.743	1.798
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.82	2.81	2.81
AT TEST	WATER CONTENT, %	66.7	64.9	66.4
	DRY DENSITY, pcf	60.5	61.6	60.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.827	1.778	1.819
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10020	0.09970	0.1011	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	949	751	798	
ULTIMATE STRESS, psf	778	646	657	
$\sigma_1$ FAILURE, psf	1957	2767	3822	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ lyr & Ins ML  
 LL= 94      PL= 27      PI= 67  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 16-D, Depth 58.8'  
 PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 16-D, Depth 58.8'  
 File: UU-6828 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2
INITIAL	WATER CONTENT, %	23.9	21.4
	DRY DENSITY, pcf	94.3	99.9
	SATURATION, %	81.9	84.2
	VOID RATIO	0.787	0.687
	DIAMETER, in	1.40	1.40
	HEIGHT, in	2.99	2.99
AT TEST	WATER CONTENT, %	29.1	25.3
	DRY DENSITY, pcf	94.4	100.2
	SATURATION, %	100.0	100.0
	VOID RATIO	0.785	0.682
	DIAMETER, in	1.40	1.40
	HEIGHT, in	2.99	2.99
Strain rate, in/min	0.1023	0.1031	
BACK PRESSURE, psf	0	0	
CELL PRESSURE, psf	2016	3024	
FAILURE STRESS, psf	1007	2860	
ULTIMATE STRESS, psf	911	2860	
$\sigma_1$ FAILURE, psf	3023	5884	
$\sigma_3$ FAILURE, psf	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M LGr & T CL3  
 w/ slf  
 LL= 23      PL= 14      PI= 9  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-4U,  
 Sample 19-B, Depth 69.2'  
 PROJ. NO.: 13622      DATE: 6-28-96



FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-4U, Sample 19-B, Depth 69.2'  
 File: UU-6829 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	84.7	87.6	96.2
	DRY DENSITY, pcf	49.4	48.6	44.6
	SATURATION, %	94.9	95.9	93.5
	VOID RATIO	2.410	2.468	2.778
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.81	2.79	2.80
AT TEST	WATER CONTENT, %	90.4	90.1	102.3
	DRY DENSITY, pcf	49.0	49.1	44.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.440	2.433	2.762
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.1074	0.1094	0.1089	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	621	848	817	
ULTIMATE STRESS, psf	512	804	720	
$\sigma_1$ FAILURE, psf	1629	2864	3841	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So DGr & Br CHOC  
 w/ lyr & ars CH, ars dec wd  
 LL= 130 PL= 43 PI= 87  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-5U,  
 Sample 4-C, Depth 10.1'  
 PROJ. NO.: 13622 DATE: 6-28-96

FIG. NO.: \_\_\_\_\_



TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 4-C, Depth 10.1'  
 File: UU-6830 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	86.8	90.2	97.6
	DRY DENSITY, pcf	46.3	43.6	41.1
	SATURATION, %	90.2	86.1	86.1
	VOID RATIO	2.504	2.722	2.946
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.79	2.79
AT TEST	WATER CONTENT, %	96.1	103.2	111.4
	DRY DENSITY, pcf	46.4	44.1	41.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.498	2.682	2.896
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09970	0.10230	0.1020
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1576	1682	2234
ULTIMATE STRESS, psf		1374	1643	2137
$\sigma_1$ FAILURE, psf		2584	3698	5258
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M DGr & BK CHOC w/  
ars, lyr CH, rts, dec wd & PT

LL= 137      PL= 51      PI= 86

SPECIFIC GRAVITY= 2.6

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-5U,  
Sample 7-D, Depth 22.9'

PROJ. NO.: 13622      DATE: 6-28-96

TRIAxIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 7-D, Depth 22.9'  
 File: UU-6831      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	36.7	35.5	36.3
	DRY DENSITY, pcf	82.5	84.0	83.5
	SATURATION, %	94.9	95.1	96.0
	VOID RATIO	1.044	1.007	1.019
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	38.4	37.0	37.9
	DRY DENSITY, pcf	82.7	84.4	83.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.037	0.998	1.024
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.1086	0.1076	0.1075	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	851	1017	709	
ULTIMATE STRESS, psf	857	921	523	
$\sigma_1$ FAILURE, psf	1859	3033	3733	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL5  
 w/ Ins CH  
 LL= 35      PL= 22      PI= 13  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-5U,  
 Sample 10-C, Depth 31.9'






PROJ. NO.: 13622      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 10-C, Depth 31.9'  
 File: UU-6832 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	38.1	40.3	40.8
	DRY DENSITY, pcf	81.4	79.4	79.5
	SATURATION, %	94.7	95.7	97.1
	VOID RATIO	1.101	1.154	1.152
	DIAMETER, in	1.40	1.40	1.40
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	40.2	42.4	42.0
	DRY DENSITY, pcf	81.4	79.2	79.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.101	1.161	1.151
Strain rate, in/min	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	964	869	1048	
ULTIMATE STRESS, psf	898	729	958	
$\sigma_1$ FAILURE, psf	1972	2885	4072	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH2  
w/ lyr & Ins ML

LL= 50      PL= 23      PI= 27

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-5U,  
Sample 13-C, Depth 43.9'

PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 13-C, Depth 43.9'  
 File: UU-6833 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.4	67.1	66.4
	DRY DENSITY, pcf	59.5	61.0	61.2
	SATURATION, %	98.6	101.8	101.4
	VOID RATIO	1.874	1.805	1.793
	DIAMETER, in	1.41	1.40	1.40
AT TEST	HEIGHT, in	2.81	2.80	2.80
	WATER CONTENT, %	70.0	65.7	65.4
	DRY DENSITY, pcf	58.6	61.1	61.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.917	1.800	1.793
DIAMETER, in	1.41	1.40	1.40	
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10760	0.09960	0.1052	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1305	1245	1154	
ULTIMATE STRESS, psf	838	903	940	
$\sigma_1$ FAILURE, psf	2313	3261	4178	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ 1yr & Ins ML  
 LL= 99      PL= 27      PI= 72  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-5U,  
 Sample 15-B, Depth 51.5'  
 PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-5U, Sample 15-B, Depth 51.5'

File: UU-6834

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.2	59.5	58.6
	DRY DENSITY, pcf	65.4	65.5	66.2
	SATURATION, %	100.4	101.2	101.3
	VOID RATIO	1.617	1.610	1.584
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	59.2	58.2	57.5
	DRY DENSITY, pcf	65.2	65.9	66.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.622	1.596	1.576
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.08970	0.09920	0.0984
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1301	919	1463
ULTIMATE STRESS, psf		951	582	1106
$\sigma_1$ FAILURE, psf		2309	2935	4487
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ lyr & Ins ML

LL= 93      PL= 27      PI= 66

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-5U,  
Sample 17-D, Depth 60.8'

PROJ. NO.: 13622      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 17-D, Depth 60.8'  
 File: UU-6835      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.8	60.1	60.2
	DRY DENSITY, pcf	64.1	64.4	64.2
	SATURATION, %	98.1	99.5	99.1
	VOID RATIO	1.669	1.656	1.666
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.79
AT TEST	WATER CONTENT, %	61.2	60.7	59.8
	DRY DENSITY, pcf	63.9	64.3	64.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.678	1.662	1.638
	DIAMETER, in	1.41	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09750	0.10180	0.1021
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1009	739	1106
ULTIMATE STRESS, psf		716	701	932
$\sigma_1$ FAILURE, psf		2017	2755	4130
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr & Ins ML  
 LL= 100    PL= 28    PI= 72  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-5U,  
 Sample 19-D, Depth 68.8'  
 PROJ. NO.: 13622                      DATE: 6-28-96

FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**







Stress Paths: + indicates end    O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-5U, Sample 19-D, Depth 68.8'  
 File: UU-6836                      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	63.7	63.7	66.5
	DRY DENSITY, pcf	62.3	62.7	61.0
	SATURATION, %	100.0	100.9	100.9
	VOID RATIO	1.746	1.730	1.806
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.81	2.80	2.79
AT TEST	WATER CONTENT, %	65.1	62.8	65.2
	DRY DENSITY, pcf	61.4	62.9	61.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.785	1.721	1.785
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.099	30.101	20.0995	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	805	960	808	
ULTIMATE STRESS, psf	603	707	550	
$\sigma_1$ FAILURE, psf	1813	2976	3832	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 LL= 89      PL= 30      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-5U,  
 Sample 21-B, Depth 74.7'  
 PROJ. NO.: 13622      DATE: 6-28-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-5U, Sample 21-B, Depth 74.7'

File: UU-6837

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	115.2	113.0	126.2
	DRY DENSITY, pcf	40.3	40.7	36.8
	SATURATION, %	98.3	97.8	95.7
	VOID RATIO	3.108	3.063	3.494
	DIAMETER, in	1.41	1.40	1.41
AT TEST	HEIGHT, in	2.81	2.80	2.80
	WATER CONTENT, %	118.8	115.9	131.4
	DRY DENSITY, pcf	39.9	40.6	36.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	3.149	3.071	3.482
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
	Strain rate, in/min	0.08930	0.08950	0.0927
	BACK PRESSURE, psf	0	0	0
	CELL PRESSURE, psf	1008	2016	3024
	FAILURE STRESS, psf	557	609	478
	ULTIMATE STRESS, psf	519	553	414
	$\sigma_1$ FAILURE, psf	1565	2625	3502
	$\sigma_3$ FAILURE, psf	1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So DGr & Br CHOB  
 w/ slf, rts, dec wd  
 LL= 155      PL= 41      PI= 114  
 SPECIFIC GRAVITY= 2.65  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 3-C, Depth 9.1'  
 PROJ. NO.: 13622      DATE: 7-1-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-6U, Sample 3-C, Depth 9.1'  
 File: UU-6851 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	74.9	70.7	67.9
	DRY DENSITY, pcf	54.1	56.2	58.9
	SATURATION, %	94.9	94.8	97.7
	VOID RATIO	2.161	2.043	1.903
	DIAMETER, in	1.41	1.41	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	78.4	74.8	69.3
	DRY DENSITY, pcf	54.4	56.1	59.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.147	2.049	1.899
DIAMETER, in	1.41	1.41	1.41	
HEIGHT, in	2.80	2.80	2.80	
Strain rate, in/min	0.08970	0.10550	0.0996	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	389	318	542	
ULTIMATE STRESS, psf	324	276	488	
$\sigma_1$ FAILURE, psf	1397	2334	3566	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH4  
 w/ 1/2 yr & Ins ML  
 LL= 85      PL= 25      PI= 60  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 4-C, Depth 13.4'  
 PROJ. NO.: 13622      DATE: 7-1-96

FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-6U, Sample 4-C, Depth 13.4'

File: UU-6852

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	37.0	37.1	36.8
	DRY DENSITY, pcf	83.6	83.7	83.4
	SATURATION, %	97.6	98.3	96.6
	VOID RATIO	1.030	1.028	1.035
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	38.0	37.6	38.0
	DRY DENSITY, pcf	83.5	83.9	83.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.034	1.023	1.033
	DIAMETER, in	1.41	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10690	0.10820	0.1058	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1135	1053	1050	
ULTIMATE STRESS, psf	1054	983	994	
$\sigma_1$ FAILURE, psf	2143	3069	4074	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CL6  
 w/ Ins & ars ML  
 LL= 48      PL= 17      PI= 31  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 13-D, Depth 37.3'






PROJ. NO.: 13622      DATE: 7-1-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-6U, Sample 13-D, Depth 37.3'

File: UU-6853

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	49.9	49.7	49.1
	DRY DENSITY, pcf	70.5	70.4	70.1
	SATURATION, %	96.0	95.1	93.5
	VOID RATIO	1.425	1.431	1.440
	DIAMETER, in	1.40	1.41	1.41
	HEIGHT, in	2.80	2.80	2.79
AT TEST	WATER CONTENT, %	51.5	51.7	52.0
	DRY DENSITY, pcf	70.9	70.8	70.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.411	1.417	1.425
	DIAMETER, in	1.40	1.41	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.09370	0.09970	0.1014	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	740	867	861	
ULTIMATE STRESS, psf	738	790	850	
$\sigma_1$ FAILURE, psf	1748	2883	3885	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ lyr & ins ML  
 LL= 76      PL= 23      PI= 53  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 15-B, Depth 44.5'  
 PROJ. NO.: 13622      DATE: 7-1-96

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-6U, Sample 15-B, Depth 44.5'

File: UU-6854

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.0	54.6	53.8
	DRY DENSITY, pcf	67.4	67.3	67.3
	SATURATION, %	97.8	97.1	95.5
	VOID RATIO	1.540	1.540	1.542
	DIAMETER, in	1.41	1.41	1.42
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	56.2	55.9	56.0
	DRY DENSITY, pcf	67.4	67.6	67.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.540	1.531	1.533
	DIAMETER, in	1.41	1.41	1.42
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.0985	0.0974	0.0985
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1172	1133	1035
ULTIMATE STRESS, psf		872	846	945
$\sigma_1$ FAILURE, psf		2180	3149	4059
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr & Ins ML  
 LL= 86      PL= 26      PI= 60  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 17-D, Depth 53.8'  
 PROJ. NO.: 13622      DATE: 7-1-96



TRIAxIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-6U, Sample 17-D, Depth 53.8'  
 File: UU-6855 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	52.5	54.7	54.1
	DRY DENSITY, pcf	68.3	66.6	68.2
	SATURATION, %	95.6	95.6	98.4
	VOID RATIO	1.503	1.568	1.506
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	55.1	57.1	54.6
	DRY DENSITY, pcf	68.2	66.7	68.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.509	1.564	1.495
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10030	0.09950	0.0972	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1347	1745	1543	
ULTIMATE STRESS, psf	869	1081	1149	
$\sigma_1$ FAILURE, psf	2355	3761	4567	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH4  
w/ lyr & Ins ML  
LL= 90      PL= 29      PI= 61  
SPECIFIC GRAVITY= 2.74  
REMARKS:

CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGE-6U,  
Sample 19-C, Depth 61.4'  
PROJ. NO.: 13622      DATE: 7-1-96



FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-6U, Sample 19-C, Depth 61.4'  
 File: UU-6856 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	46.6	56.6	55.8
	DRY DENSITY, pcf	73.1	65.1	66.2
	SATURATION, %	95.3	95.2	96.6
	VOID RATIO	1.340	1.629	1.582
	DIAMETER, in	1.40	1.41	1.41
AT TEST	HEIGHT, in	2.80	2.80	2.80
	WATER CONTENT, %	48.9	58.9	57.4
	DRY DENSITY, pcf	73.1	65.4	66.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.339	1.614	1.573
DIAMETER, in	1.40	1.41	1.41	
HEIGHT, in	2.80	2.80	2.80	
Strain rate, in/min	0.09240	0.09960	0.1020	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	2338	2245	2577	
ULTIMATE STRESS, psf	1818	1916	1779	
$\sigma_1$ FAILURE, psf	3346	4261	5601	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: St Gr CH3 w/  
 lyr CL5, ars ML & dec wd  
 LL= 70 PL= 20 PI= 50  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:






CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-6U,  
 Sample 26-B, Depth 78.2'  
 PROJ. NO.: 13622 DATE: 7-1-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.:





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-6U, Sample 26-B, Depth 78.2'  
 File: UU-6857 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	58.0	61.4	58.6
	DRY DENSITY, pcf	64.9	63.2	64.7
	SATURATION, %	97.1	98.7	97.6
	VOID RATIO	1.636	1.705	1.646
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	59.9	62.1	60.2
	DRY DENSITY, pcf	64.7	63.3	64.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.642	1.702	1.649
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09690	0.09850	0.0973
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		857	789	720
ULTIMATE STRESS, psf		614	704	642
$\sigma_1$ FAILURE, psf		1865	2805	3744
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ 1yr & Ins ML  
 LL= 82      PL= 29      PI= 53  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-7U,  
 Sample 2-B, Depth 2.0'  
 PROJ. NO.: 13622      DATE: 7-11-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-7U, Sample 2-B, Depth 2.0'  
 File: UU-6942 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	28.8	29.6	31.0
	DRY DENSITY, pcf	92.0	91.3	88.8
	SATURATION, %	91.9	92.9	91.6
	VOID RATIO	0.860	0.873	0.926
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.79
AT TEST	WATER CONTENT, %	31.5	31.6	33.2
	DRY DENSITY, pcf	91.8	91.6	89.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.864	0.867	0.908
	DIAMETER, in	1.40	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.0984	0.1018	0.1023
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1495	1205	1187
ULTIMATE STRESS, psf		1354	1074	1161
$\sigma_1$ FAILURE, psf		2503	3221	4211
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr & T CL6 w/lyr  
& Ins ML, lyr & lg ars org

LL= 42      PL= 17      PI= 25

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-7U,  
Sample 4-C, Depth 14.1'

PROJ. NO.: 13622      DATE: 7-11-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-7U, Sample 4-C, Depth 14.1'

File: UU-6943

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	40.6	40.0	40.9
	DRY DENSITY, pcf	78.8	80.8	79.4
	SATURATION, %	95.1	98.2	96.9
	VOID RATIO	1.170	1.118	1.155
	DIAMETER, in	1.42	1.40	1.40
	HEIGHT, in	2.81	2.81	2.81
AT TEST	WATER CONTENT, %	43.3	41.3	42.5
	DRY DENSITY, pcf	78.2	80.2	79.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.187	1.132	1.164
	DIAMETER, in	1.42	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.110	0.114	0.106	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	881	829	774	
ULTIMATE STRESS, psf	812	788	718	
$\sigma_1$ FAILURE, psf	1889	2845	3798	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL6  
 w/ 1yr & 1ns ML  
 LL= 45      PL= 21      PI= 24  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-7U,  
 Sample 6-D, Depth 22.8'  
 PROJ. NO.: 13622      DATE: 7-11-96

FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-7U, Sample 6-D, Depth 22.8'

File: UU-6944

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	45.6	46.5	45.7
	DRY DENSITY, pcf	74.6	74.7	75.0
	SATURATION, %	97.3	99.3	98.4
	VOID RATIO	1.275	1.273	1.264
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	46.9	46.6	46.2
	DRY DENSITY, pcf	74.6	74.9	75.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.275	1.267	1.257
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.0959	0.0976	0.0954	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	2208	2619	2653	
ULTIMATE STRESS, psf	1643	1693	1822	
$\sigma_1$ FAILURE, psf	3216	4635	5677	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: St Gr CH4  
w/ Ins & ars ML

LL= 72      PL= 24      PI= 48

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGE-7U,  
Sample 25-B, Depth 61.5'






PROJ. NO.: 13622      DATE: 7-11-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO. : \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-7U, Sample 25-B, Depth 61.5'  
 File: UU-6945                      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.3	56.3	58.2
	DRY DENSITY, pcf	64.9	67.0	64.9
	SATURATION, %	100.0	99.8	97.8
	VOID RATIO	1.614	1.533	1.617
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.79
AT TEST	WATER CONTENT, %	59.3	56.2	58.6
	DRY DENSITY, pcf	65.0	67.1	65.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.614	1.529	1.595
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.0829	0.0901	0.0965	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	2339	2652	1718	
ULTIMATE STRESS, psf	1139	1843	264	
$\sigma_1$ FAILURE, psf	3347	4668	4742	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: St Gr CH4  
 w/ Ins & ars ML  
 LL= 94      PL= 30      PI= 64  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-7U,  
 Sample 27-C, Depth 71.1'

PROJ. NO.: 13622      DATE: 7-11-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-7U, Sample 27-C, Depth 71.1'  
 File: UU-6946 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	149.5	143.5	152.0
	DRY DENSITY, pcf	30.5	32.1	29.7
	SATURATION, %	89.7	91.5	87.9
	VOID RATIO	4.416	4.156	4.579
	DIAMETER, in	1.41	1.40	1.42
	HEIGHT, in	2.81	2.79	2.78
AT TEST	WATER CONTENT, %	167.5	154.6	168.7
	DRY DENSITY, pcf	30.4	32.5	30.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	4.439	4.098	4.470
	DIAMETER, in	1.41	1.40	1.42
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.11170	0.10560	0.1034	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	716	1246	788	
ULTIMATE STRESS, psf	714	847	660	
$\sigma_1$ FAILURE, psf	1724	3262	3812	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CHOB  
 w/ dec wd & rts  
 LL= 206      PL= 54      PI= 152  
 SPECIFIC GRAVITY= 2.65  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-8U,  
 Sample 3-C, Depth 5.6'  
 PROJ. NO.: 13622      DATE: 7-11-96



FIG. NO.:



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 3-C, Depth 5.6'  
 File: UU-6947 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2
INITIAL	WATER CONTENT, %	62.5	59.1
	DRY DENSITY, pcf	62.2	64.4
	SATURATION, %	97.9	97.7
	VOID RATIO	1.750	1.657
	DIAMETER, in	1.40	1.40
AT TEST	HEIGHT, in	2.81	2.80
	WATER CONTENT, %	64.7	60.5
	DRY DENSITY, pcf	61.7	64.4
	SATURATION, %	100.0	100.0
	VOID RATIO	1.772	1.657
DIAMETER, in	1.40	1.40	
HEIGHT, in	2.80	2.80	
Strain rate, in/min	0.10700	0.1106	
BACK PRESSURE, psf	0	0	
CELL PRESSURE, psf	1008	3024	
FAILURE STRESS, psf	311	363	
ULTIMATE STRESS, psf	279	363	
$\sigma_1$ FAILURE, psf	1319	3387	
$\sigma_3$ FAILURE, psf	1008	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: VSo Gr CH4 w/ lyr  
& Ins ML & few conc

LL= 90      PL= 23      PI= 67

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-8U,  
Sample 5-C, Depth 14.2'

PROJ. NO.: 13622      DATE: 7-11-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 5-C, Depth 14.2'  
 File: UU-6948 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	52.5	50.8	53.4
	DRY DENSITY, pcf	68.4	69.6	68.1
	SATURATION, %	96.2	96.0	97.2
	VOID RATIO	1.483	1.439	1.494
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.81	2.80	2.80
AT TEST	WATER CONTENT, %	54.9	53.2	54.7
	DRY DENSITY, pcf	68.1	69.4	68.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.493	1.448	1.489
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.10770	0.10630	0.1057	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	543	621	694	
ULTIMATE STRESS, psf	413	620	652	
$\sigma_1$ FAILURE, psf	1551	2637	3718	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ Ins, lyr & ars ML  
 LL= 60      PL= 21      PI= 39  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-8U,  
 Sample 8-C, Depth 26.1'  
 PROJ. NO.: 13622      DATE: 7-12-96

FIG. NO.: \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 8-C, Depth 26.1'  
 File: UU-6950      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.4	66.8	66.0
	DRY DENSITY, pcf	60.2	59.2	60.3
	SATURATION, %	99.2	97.1	98.9
	VOID RATIO	1.819	1.870	1.816
	DIAMETER, in	1.41	1.42	1.41
	HEIGHT, in	2.81	2.80	2.80
AT TEST	WATER CONTENT, %	67.4	68.8	66.7
	DRY DENSITY, pcf	59.9	59.2	60.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.833	1.870	1.815
	DIAMETER, in	1.41	1.42	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.10140	0.09830	0.0961
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		567	793	803
ULTIMATE STRESS, psf		459	584	585
$\sigma_1$ FAILURE, psf		1575	2809	3827
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4  
w/ Ins & ars ML

LL= 85      PL= 27      PI= 58

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-8U,  
Sample 10-C, Depth 34.1'

PROJ. NO.: 13622      DATE: 7-12-96

TRIAxIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-8U, Sample 10-C, Depth 34.1'

File: UU-6951

Project No.: 13622



FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	60.4	60.9	61.2
	DRY DENSITY, pcf	63.3	62.8	63.0
	SATURATION, %	97.6	97.3	98.3
	VOID RATIO	1.683	1.704	1.694
	DIAMETER, in	1.42	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	62.2	62.4	62.5
	DRY DENSITY, pcf	63.1	63.0	62.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.691	1.697	1.701
	DIAMETER, in	1.42	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.0998	0.1071	0.1109
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		821	843	921
ULTIMATE STRESS, psf		628	670	702
$\sigma_1$ FAILURE, psf		1829	2859	3945
$\sigma_3$ FAILURE, psf		1008	2016	3024



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ ars ML  
 LL= 81      PL= 25      PI= 56  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-8U,  
 Sample 13-D, Depth 46.2'  
 PROJ. NO.: 13622      DATE: 7-12-96  
**TRIAxIAL SHEAR TEST REPORT**  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 13-D, Depth 46.2'  
 File: UU-6952      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	65.5	65.6	65.2
	DRY DENSITY, pcf	60.4	60.5	60.8
	SATURATION, %	98.4	98.7	99.0
	VOID RATIO	1.809	1.808	1.791
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	66.3	66.6	65.8
	DRY DENSITY, pcf	60.6	60.4	60.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.804	1.811	1.789
	DIAMETER, in	1.41	1.40	1.41
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.0954	0.0986	0.0980
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1171	1059	1231
ULTIMATE STRESS, psf		879	624	843
$\sigma_1$ FAILURE, psf		2179	3075	4255
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ ars ML  
 LL= 93      PL= 29      PI= 64  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-8U,  
 Sample 15-C, Depth 54.1'  
 PROJ. NO.: 13622      DATE: 7-12-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 15-C, Depth 54.1'  
 File: UU-6953 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.6	62.9	62.9
	DRY DENSITY, pcf	62.1	62.5	62.2
	SATURATION, %	97.8	99.2	98.5
	VOID RATIO	1.754	1.738	1.749
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
AT TEST	WATER CONTENT, %	64.0	63.3	63.6
	DRY DENSITY, pcf	62.1	62.6	62.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.754	1.734	1.741
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09890	0.09940	0.0959
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1137	1097	1085
ULTIMATE STRESS, psf		846	799	798
$\sigma_1$ FAILURE, psf		2145	3113	4109
$\sigma_3$ FAILURE, psf		1008	2016	3024



TYPE OF TEST: Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ lyr SP  
 LL= 88      PL= 28      PI= 60  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-8U,  
 Sample 17-C, Depth 61.8'  
 PROJ. NO.: 13622      DATE: 7-12-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-9U, Sample 15-D, Depth 58.8'  
 File: UU-7111 Project No.: 13622 FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	65.8	64.4	63.2
	DRY DENSITY, pcf	60.0	60.2	60.4
	SATURATION, %	97.4	95.7	94.6
	VOID RATIO	1.852	1.843	1.831
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	67.5	67.1	66.2
	DRY DENSITY, pcf	60.0	60.3	60.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.849	1.838	1.814
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.112	0.112	0.109	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	919	942	983	
ULTIMATE STRESS, psf	819	830	829	
$\sigma_1$ FAILURE, psf	1927	2958	4007	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 91      PL= 23      PI= 68  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 17-D, Depth 66.8'  
 PROJ. NO.: 13622      DATE: 7-24-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-9U, Sample 13-D, Depth 50.8'  
 File: UU-7110      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.2	64.2	67.4
	DRY DENSITY, pcf	58.9	59.8	58.4
	SATURATION, %	95.3	94.4	95.7
	VOID RATIO	1.904	1.862	1.930
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	69.8	67.8	70.2
	DRY DENSITY, pcf	58.7	59.8	58.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.913	1.859	1.924
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11470	0.11440	0.1065	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1040	937	960	
ULTIMATE STRESS, psf	833	724	798	
$\sigma_1$ FAILURE, psf	2048	2953	3984	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ 1yr & Ins ML  
 LL= 93      PL= 27      PI= 66  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 15-D, Depth 58.8'  
 PROJ. NO.: 13622      DATE: 7-24-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-9U, Sample 9-D, Depth 34.8'

File: UU-7109

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.5	61.0	59.2
	DRY DENSITY, pcf	61.9	65.9	63.5
	SATURATION, %	97.0	104.6	95.8
	VOID RATIO	1.764	1.597	1.694
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	64.7	58.2	61.8
	DRY DENSITY, pcf	61.7	65.9	63.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.773	1.594	1.692
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.1128	0.1161	0.1117
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		749	717	805
ULTIMATE STRESS, psf		548	589	595
$\sigma_1$ FAILURE, psf		1757	2733	3829
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST: Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 84      PL= 25      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 13-D, Depth 50.8'  
 PROJ. NO.: 13622      DATE: 7-24-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-9U, Sample 7-D, Depth 26.2'  
 File: UU-7108 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.4	56.2	60.7
	DRY DENSITY, pcf	64.2	64.6	63.6
	SATURATION, %	97.8	93.6	98.5
	VOID RATIO	1.666	1.647	1.688
	DIAMETER, in	1.40	1.39	1.39
	HEIGHT, in	2.99	2.99	2.98
AT TEST	WATER CONTENT, %	61.5	60.3	61.8
	DRY DENSITY, pcf	63.7	64.5	63.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.686	1.653	1.693
	DIAMETER, in	1.40	1.39	1.39
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.115	0.114	0.1126
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		579	632	658
ULTIMATE STRESS, psf		465	518	521
$\sigma_1$ FAILURE, psf		1587	2648	3682
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 92      PL= 30      PI= 62  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:






CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 9-D, Depth 34.8'  
 PROJ. NO.: 13622      DATE: 7-24-96

FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-9U, Sample 5-C, Depth 17.7'

File: UU-7107

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.5	60.7	63.0
	DRY DENSITY, pcf	62.5	62.4	61.4
	SATURATION, %	98.5	95.6	96.7
	VOID RATIO	1.738	1.740	1.785
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.99	2.98
AT TEST	WATER CONTENT, %	64.0	64.0	65.6
	DRY DENSITY, pcf	62.1	62.1	61.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.753	1.755	1.799
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11570	0.11640	0.1161	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	388	430	473	
ULTIMATE STRESS, psf	363	392	410	
$\sigma_1$ FAILURE, psf	1396	2446	3497	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH3  
 w/ 1yr & 1ns ML  
 LL= 72      PL= 23      PI= 49  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 7-D, Depth 26.2'  
 PROJ. NO.: 13622      DATE: 7-24-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-9U, Sample 2-B, Depth 4.6'  
 File: UU-7106 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	64.9	64.8	63.8
	DRY DENSITY, pcf	56.1	52.1	57.1
	SATURATION, %	86.9	77.8	87.7
	VOID RATIO	2.047	2.283	1.993
	DIAMETER, in	1.40	1.39	1.40
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	75.0	83.4	72.5
	DRY DENSITY, pcf	56.0	52.1	57.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.055	2.284	1.986
	DIAMETER, in	1.40	1.39	1.40
	HEIGHT, in	2.97	2.98	2.97
Strain rate, in/min		0.09690	0.09980	0.0985
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		391	627	1045
ULTIMATE STRESS, psf		424	633	801
$\sigma_1$ FAILURE, psf		1399	2643	4069
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ wd  
 LL= 118      PL= 28      PI= 90  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 5-C, Depth 17.7'  
 PROJ. NO.: 13622      DATE: 7-24-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-8U, Sample 22-D, Depth 76.8'

File: UU-6955

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	40.0	39.6	33.2
	DRY DENSITY, pcf	73.6	74.6	76.0
	SATURATION, %	83.2	84.4	73.3
	VOID RATIO	1.307	1.276	1.234
	DIAMETER, in	1.42	1.41	1.40
	HEIGHT, in	2.80	2.80	2.98
AT TEST	WATER CONTENT, %	47.8	46.7	44.1
	DRY DENSITY, pcf	73.8	74.8	77.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.301	1.269	1.199
	DIAMETER, in	1.42	1.41	1.40
	HEIGHT, in	2.80	2.80	2.99
Strain rate, in/min		0.09730	0.09680	0.1022
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		3422	3376	1576
ULTIMATE STRESS, psf		1934	2509	1730
$\sigma_1$ FAILURE, psf		4430	5392	4600
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: St LGr & T CH2 w/  
 Ins & ars ML, ox, rts  
 LL= 82      PL= 33      PI= 49  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-9U,  
 Sample 2-B, Depth 4.6'  
 PROJ. NO.: 13622      DATE: 7-24-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-8U, Sample 17-C, Depth 61.8'  
 File: UU-6954 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	29.7	31.1	28.9
	DRY DENSITY, pcf	91.0	90.4	92.2
	SATURATION, %	94.0	97.1	94.3
	VOID RATIO	0.853	0.865	0.828
	DIAMETER, in	1.40	1.40	1.42
	HEIGHT, in	2.80	2.81	2.80
AT TEST	WATER CONTENT, %	31.8	32.4	30.8
	DRY DENSITY, pcf	90.7	89.9	92.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.859	0.874	0.831
	DIAMETER, in	1.40	1.40	1.42
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.1083	0.1121	0.1116
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		2263	1218	1103
ULTIMATE STRESS, psf		2263	1218	567
$\sigma_1$ FAILURE, psf		3271	3234	4127
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: ST Gr CL3  
w/ sif & ars CH

LL= 28      PL= 15      PI= 13

SPECIFIC GRAVITY= 2.7

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGE-8U,  
Sample 22-D, Depth 76.8'






PROJ. NO.: 13622      DATE: 7-12-96

TRIAXIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGE-9U, Sample 17-D, Depth 66.8'

File: UU-7112

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	43.6	45.3	42.7
	DRY DENSITY, pcf	76.7	74.8	76.7
	SATURATION, %	98.4	97.7	96.2
	VOID RATIO	1.197	1.252	1.199
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.97	2.97	2.97
AT TEST	WATER CONTENT, %	44.1	46.1	43.6
	DRY DENSITY, pcf	76.9	75.1	77.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.192	1.244	1.177
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11260	0.11630	0.1101	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1517	962	1455	
ULTIMATE STRESS, psf	1318	965	1278	
$\sigma_1$ FAILURE, psf	2525	2978	4479	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH3  
w/ slf






LL= 64      PL= 18      PI= 46  
SPECIFIC GRAVITY= 2.7

REMARKS:

CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGE-9U,  
Sample 22-B. Depth 77.1'  
PROJ. NO.: 13622      DATE: 7-24-96

FIG. NO.:



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-9U, Sample 22-B, Depth 77.1'  
 File: UU-7113 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	61.4	56.5	62.9
	DRY DENSITY, pcf	59.9	64.4	59.9
	SATURATION, %	90.7	93.6	92.8
	VOID RATIO	1.853	1.654	1.857
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.81	2.80	2.80
AT TEST	WATER CONTENT, %	68.4	60.5	67.5
	DRY DENSITY, pcf	59.5	64.4	60.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.875	1.657	1.851
	DIAMETER, in	1.41	1.41	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min		0.09970	0.09520	0.0978
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		498	413	820
ULTIMATE STRESS, psf		348	391	649
$\sigma_1$ FAILURE, psf		1506	2429	3844
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ lyr & ins org & dec wd  
 LL= 103      PL= 32      PI= 71  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-10U,  
 Sample 3-D, Depth 10.8'  
 PROJ. NO.: 13622      DATE: 7-25-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 3-D, Depth 10.8'  
 File: UU-7114 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	61.0	67.9	69.6
	DRY DENSITY, pcf	63.7	60.3	59.0
	SATURATION, %	99.2	101.2	100.4
	VOID RATIO	1.685	1.838	1.899
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.81	2.81	2.82
AT TEST	WATER CONTENT, %	61.9	68.2	71.6
	DRY DENSITY, pcf	63.4	59.6	57.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.696	1.868	1.962
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.80	2.80	2.80
Strain rate, in/min	0.11550	0.11520	0.1158	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	267	601	542	
ULTIMATE STRESS, psf	172	331	431	
$\sigma_1$ FAILURE, psf	1275	2617	3566	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH3  
 .w/ lyr & Ins ML & ars org  
 LL= 76      PL= 25      PI= 51  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-10U,  
 Sample 6-B, Depth 21.5'  
 PROJ. NO.: 13622      DATE: 7-25-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 6-B, Depth 21.5'  
 File: UU-7115      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	70.1	70.3	69.1
	DRY DENSITY, pcf	58.1	57.5	58.3
	SATURATION, %	98.7	97.6	97.9
	VOID RATIO	1.946	1.975	1.933
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	3.00	2.99	2.98
AT TEST	WATER CONTENT, %	73.2	73.4	70.9
	DRY DENSITY, pcf	56.9	56.8	58.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.006	2.011	1.942
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11370	0.11770	0.1161	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	224	501	438	
ULTIMATE STRESS, psf	119	335	281	
$\sigma_1$ FAILURE, psf	1232	2517	3462	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: XSo Gr CH4  
 w/ Ins ML  
 LL= 96      PL= 27      PI= 69  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-10U,  
 Sample 8-D, Depth 30.8'  
 PROJ. NO.: 13622      DATE: 7-25-96

FIG. NO.: \_\_\_\_\_



TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 8-D, Depth 30.8'  
 File: UU-7116      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.8	68.1	68.3
	DRY DENSITY, pcf	58.8	58.2	58.0
	SATURATION, %	97.4	96.3	96.0
	VOID RATIO	1.907	1.939	1.949
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.97	2.98	3.00
AT TEST	WATER CONTENT, %	69.3	70.7	73.2
	DRY DENSITY, pcf	59.0	58.3	56.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.898	1.936	2.006
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11490	0.11430	0.1135	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	561	403	560	
ULTIMATE STRESS, psf	420	260	436	
$\sigma_1$ FAILURE, psf	1569	2419	3584	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 86      PL= 27      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-10U,  
 Sample 10-D, Depth 38.8'  
 PROJ. NO.: 13622      DATE: 7-25-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 10-D, Depth 38.8'  
 File: UU-7117 Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	53.7	52.5	53.3
	DRY DENSITY, pcf	67.2	68.2	67.6
	SATURATION, %	95.2	95.5	95.4
	VOID RATIO	1.544	1.507	1.530
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	3.01	2.99	3.00
AT TEST	WATER CONTENT, %	59.4	55.9	57.9
	DRY DENSITY, pcf	65.1	67.6	66.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.627	1.532	1.586
	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11550	0.11550	0.1134	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	347	657	757	
ULTIMATE STRESS, psf	250	522	593	
$\sigma_1$ FAILURE, psf	1355	2673	3781	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH3  
 w/ lyr & Ins ML  
 LL= 72      PL= 25      PI= 47  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGE-10U,  
 Sample 12-D, Depth 46.8'  
 PROJ. NO.: 13622      DATE: 7-25-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 12-D, Depth 46.8'  
 File: UU-7118 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.6	57.0	56.0
	DRY DENSITY, pcf	66.1	64.6	65.2
	SATURATION, %	96.5	95.2	95.0
	VOID RATIO	1.568	1.630	1.604
	DIAMETER, in	1.40	1.40	1.40
AT TEST	HEIGHT, in	2.98	3.00	3.00
	WATER CONTENT, %	58.0	62.0	61.4
	DRY DENSITY, pcf	65.9	63.2	63.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.578	1.686	1.670
AT TEST	DIAMETER, in	1.40	1.40	1.40
	HEIGHT, in	2.97	2.98	2.98
Strain rate, in/min		0.11370	0.11290	0.1165
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		662	694	846
ULTIMATE STRESS, psf		591	601	738
$\sigma_1$ FAILURE, psf		1670	2710	3870
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH3  
w/ ars ML

LL= 80      PL= 28      PI= 52

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGE-10U,  
Sample 14-D, Depth 54.7'

PROJ. NO.: 13622      DATE: 7-25-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGE-10U, Sample 14-D, Depth 54.7'  
 File: UU-7119 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	69.8	71.6	72.8
	DRY DENSITY, pcf	57.8	56.1	54.7
	SATURATION, %	97.9	96.1	94.0
	VOID RATIO	1.940	2.027	2.106
	DIAMETER, in	1.37	1.37	1.38
AT TEST	HEIGHT, in	2.97	2.96	2.96
	WATER CONTENT, %	71.6	73.7	76.1
	DRY DENSITY, pcf	57.6	56.5	55.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.948	2.004	2.069
Strain rate, in/min	DIAMETER, in	1.37	1.37	1.38
	HEIGHT, in	2.97	2.97	2.97
BACK PRESSURE, psf	0	0	0	
OELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	701	750	987	
ULTIMATE STRESS, psf	715	793	971	
$\sigma_1$ FAILURE, psf	1709	2766	4011	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4 w/ ox.  
Ins & ars ML, lg ars org, dw  
LL= 98 PL= 32 PI= 66  
SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-1U,  
Sample 3-C, Depth 6.1'

PROJ. NO.: 13622 DATE: 7-30-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-1U, Sample 3-C, Depth 6.1'

File: UU-7182

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	43.3	42.2	42.7
	DRY DENSITY, pcf	78.8	79.7	79.7
	SATURATION, %	101.3	100.9	102.2
	VOID RATIO	1.170	1.145	1.145
	DIAMETER, in	1.38	1.37	1.37
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	43.0	42.2	41.7
	DRY DENSITY, pcf	78.5	79.4	79.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.179	1.155	1.142
	DIAMETER, in	1.38	1.37	1.37
	HEIGHT, in	2.97	2.98	2.97
Strain rate, in/min		0.10890	0.11140	0.1124
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		676	654	692
ULTIMATE STRESS, psf		678	682	703
$\sigma_1$ FAILURE, psf		1684	2670	3716
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL6  
 w/ Ins ML  
 LL= 47      PL= 18      PI= 29  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-1U,  
 Sample 6-B, Depth 18.9'  
 PROJ. NO.: 13622      DATE: 7-30-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-1U, Sample 6-B, Depth 18.9'  
 File: UU-7183      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.8	62.9	61.9
	DRY DENSITY, pcf	60.3	63.5	63.6
	SATURATION, %	99.7	101.7	100.4
	VOID RATIO	1.836	1.694	1.690
	DIAMETER, in	1.38	1.38	1.37
AT TEST	HEIGHT, in	2.98	2.98	2.97
	WATER CONTENT, %	67.3	62.0	61.5
	DRY DENSITY, pcf	60.1	63.4	63.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.844	1.699	1.685
DIAMETER, in	1.38	1.38	1.37	
HEIGHT, in	2.97	2.97	2.98	
Strain rate, in/min	0.112	0.106	0.116	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	531	694	630	
ULTIMATE STRESS, psf	445	521	591	
$\sigma_1$ FAILURE, psf	1539	2710	3654	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins ML  
 LL= 93      PL= 27      PI= 66  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-1U,  
 Sample 8-B, Depth 24.1'  
 PROJ. NO.: 13622      DATE: 7-30-96



TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-1U, Sample 8-B, Depth 24.1'  
 File: UU-7184 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.4	47.0	45.2
	DRY DENSITY, pcf	70.0	73.0	68.3
	SATURATION, %	103.8	96.3	82.8
	VOID RATIO	1.426	1.326	1.486
	DIAMETER, in	1.38	1.38	1.40
	HEIGHT, in	2.97	2.97	2.98
AT TEST	WATER CONTENT, %	52.6	47.8	53.9
	DRY DENSITY, pcf	69.9	73.8	68.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.431	1.301	1.465
	DIAMETER, in	1.38	1.38	1.40
	HEIGHT, in	2.97	2.98	2.99
Strain rate, in/min		0.09850	0.09950	0.1015
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1534	1519	739
ULTIMATE STRESS, psf		1026	1185	768
$\sigma_1$ FAILURE, psf		2542	3535	3763
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ ars SM  
 LL= 73      PL= 25      PI= 48  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-1U,  
 Sample 22-C, Depth 55.1'  
 PROJ. NO.: 13622      DATE: 7-30-96

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-1U, Sample 22-C, Depth 55.1'

File: UU-7185

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	43.6	41.6	41.4
	DRY DENSITY, pcf	78.3	79.3	75.7
	SATURATION, %	101.3	99.2	90.6
	VOID RATIO	1.170	1.140	1.243
	DIAMETER, in	1.38	1.38	1.39
	HEIGHT, in	2.97	2.97	2.96
AT TEST	WATER CONTENT, %	42.7	41.2	44.7
	DRY DENSITY, pcf	78.6	80.0	76.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.161	1.121	1.215
	DIAMETER, in	1.38	1.38	1.39
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.10	0.10	0.15	0.10
BACK PRESSURE, psf	0	0	0	0
CELL PRESSURE, psf	1008	2016	3024	3024
FAILURE STRESS, psf	1570	1665	1591	1591
ULTIMATE STRESS, psf	1304	1507	1365	1365
$\sigma_1$ FAILURE, psf	2578	3681	4615	4615
$\sigma_3$ FAILURE, psf	1008	2016	3024	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ Ins & ars ML, few ars org  
 LL= 65      PL= 25      PI= 40  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-1U,  
 Sample 24-B, Depth 62.4'  
 PROJ. NO.: 13622      DATE: 7-30-96

FIG. NO.: \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-1U, Sample 24-B, Depth 62.4'  
 File: UU-7186      Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.5	51.6	52.0
	DRY DENSITY, pcf	68.9	70.9	70.3
	SATURATION, %	100.7	100.1	99.4
	VOID RATIO	1.483	1.413	1.432
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	54.3	51.7	52.0
	DRY DENSITY, pcf	68.8	70.8	70.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.487	1.418	1.425
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.0952	0.0806	0.0796	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1960	2146	1833	
ULTIMATE STRESS, psf	1327	1362	1624	
$\sigma_1$ FAILURE, psf	2968	4162	4857	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
  
 LL= 88      PL= 26      PI= 62  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-1U,  
 Sample 26-D, Depth 71.8'  
  
 PROJ. NO.: 13622      DATE: 7-30-96  
  
 TRIAXIAL SHEAR TEST REPORT  
  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-1U, Sample 26-D, Depth 71.8'  
 File: UU-7187 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	28.9	27.1	28.0
	DRY DENSITY, pcf	89.4	91.3	90.9
	SATURATION, %	88.0	86.3	88.5
	VOID RATIO	0.886	0.847	0.854
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.97	2.98	2.96
	WATER CONTENT, %	32.7	30.9	30.8
	DRY DENSITY, pcf	89.6	91.9	92.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.882	0.834	0.830
DIAMETER, in	1.38	1.38	1.38	
HEIGHT, in	2.98	2.99	2.98	
Strain rate, in/min	0.102	0.1017	0.1013	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1463	2177	2093	
ULTIMATE STRESS, psf	1548	1987	1941	
$\sigma_1$ FAILURE, psf	2471	4193	5117	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: ST Gr & Br CL6 w/  
 1yr. Ins ML, 1yr SP, ars org, ox  
 LL= 47 PL= 22 PI= 25  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-2U,  
 Sample 2-B, Depth 5.3'  
 PROJ. NO.: 13622 DATE: 7-30-96



FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 2-B, Depth 5.3'  
 File: UU-7188 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	63.7	42.4	69.0
	DRY DENSITY, pcf	62.8	77.8	59.4
	SATURATION, %	101.1	96.8	100.7
	VOID RATIO	1.726	1.200	1.879
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.97	2.98	2.98
	WATER CONTENT, %	62.3	44.0	68.2
	DRY DENSITY, pcf	63.2	77.6	59.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.706	1.205	1.870
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.114	0.112	0.1082
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		961	1230	920
ULTIMATE STRESS, psf		816	1141	810
$\sigma_1$ FAILURE, psf		1969	3246	3944
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4  
w/ 1yr & Ins ML, ars org

LL= 97      PL= 21      PI= 76

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-2U,

Sample 5-C, Depth 18.4'






PROJ. NO.: 13622

DATE: 7-30-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 5-C, Depth 18.4'  
 File: UU-7189 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	45.6	44.5	46.4
	DRY DENSITY, pcf	77.8	77.3	76.5
	SATURATION, %	104.4	100.6	102.9
	VOID RATIO	1.197	1.212	1.236
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	43.8	44.2	44.3
	DRY DENSITY, pcf	77.8	77.4	77.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.199	1.210	1.214
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10650	0.10680	0.1093
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1173	1110	944
ULTIMATE STRESS, psf		991	819	884
$\sigma_1$ FAILURE, psf		2181	3126	3968
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH3  
w/ 1yr & 1ns ML

LL= 67      PL= 25      PI= 42  
SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-2U,  
Sample 9-C, Depth 34.4'

PROJ. NO.: 13622






DATE: 7-30-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.:





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 9-C, Depth 34.4'  
 File: UU-7190 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.9	56.1	54.1
	DRY DENSITY, pcf	69.1	65.8	69.2
	SATURATION, %	102.5	96.5	101.2
	VOID RATIO	1.456	1.582	1.454
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	53.4	58.1	53.2
	DRY DENSITY, pcf	69.2	65.8	69.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.452	1.581	1.447
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.1086	0.1074	0.1072
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1071	2693	1287
ULTIMATE STRESS, psf		922	928	1035
$\sigma_1$ FAILURE, psf		2079	4709	4311
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ Ins & ars ML

LL= 84      PL= 27      PI= 57

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-2U,  
Sample 11-B, Depth 41.5'

PROJ. NO.: 13622      DATE: 7-31-96

FIG. NO.:



TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 11-B, Depth 41.5'  
 File: UU-7191 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	49.3	49.5	50.2
	DRY DENSITY, pcf	73.5	72.9	71.9
	SATURATION, %	102.2	101.2	100.4
	VOID RATIO	1.311	1.330	1.361
	DIAMETER, in	1.38	1.38	1.38
HEIGHT, in	2.98	2.98	2.98	
AT TEST	WATER CONTENT, %	48.1	48.6	49.7
	DRY DENSITY, pcf	73.5	73.1	72.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.309	1.322	1.352
	DIAMETER, in	1.38	1.38	1.38
HEIGHT, in	2.98	2.98	2.98	
Strain rate, in/min	0.11180	0.11070	0.1095	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1405	1354	1314	
ULTIMATE STRESS, psf	1133	976	1014	
$\sigma_1$ FAILURE, psf	2413	3370	4338	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins, lyr & ars ML  
 LL= 75      PL= 24      PI= 51  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-2U,  
 Sample 13-C, Depth 49.9'  
 PROJ. NO.: 13622      DATE: 7-31-96

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO. : \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 13-C, Depth 49.9'  
 File: UU-7192 Project No.: 13622 FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	52.9	53.4	53.7
	DRY DENSITY, pcf	70.6	69.2	69.7
	SATURATION, %	102.4	99.9	101.8
	VOID RATIO	1.404	1.454	1.435
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	51.4	53.7	52.6
	DRY DENSITY, pcf	70.8	69.0	69.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.399	1.461	1.430
AT TEST	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.08030	0.09920	0.1008
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1442	1415	1480
ULTIMATE STRESS, psf		1328	1123	1148
$\sigma_1$ FAILURE, psf		2450	3431	4504
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ sm ars ML  
 LL= 86      PL= 29      PI= 57  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-2U,  
 Sample 15-D, Depth 58.8'  
 PROJ. NO.: 13622      DATE: 7-31-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-2U, Sample 15-D, Depth 58.8'  
 File: UU-7193 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	58.6	55.7	54.2
	DRY DENSITY, pcf	65.4	67.9	69.4
	SATURATION, %	99.3	100.5	101.5
	VOID RATIO	1.617	1.519	1.463
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	58.9	55.6	52.8
	DRY DENSITY, pcf	65.4	67.8	69.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.615	1.524	1.446
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.095	0.0955	0.0941	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1485	1495	1715	
ULTIMATE STRESS, psf	1028	1153	1228	
$\sigma_1$ FAILURE, psf	2493	3511	4739	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ 1yr & Ins ML  
 LL= 89      PL= 30      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:






CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-2U,  
 Sample 17-C, Depth 66.1'

PROJ. NO.: 13622      DATE: 7-31-96

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-2U, Sample 17-C, Depth 66.1'

File: UU-7194

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.2	68.4	64.9
	DRY DENSITY, pcf	58.1	60.5	59.2
	SATURATION, %	94.7	102.5	94.1
	VOID RATIO	1.944	1.829	1.889
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	71.2	66.4	67.6
	DRY DENSITY, pcf	58.0	60.7	60.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.951	1.820	1.851
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.10770	0.10920	0.0986	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	636	536	654	
ULTIMATE STRESS, psf	569	490	556	
$\sigma_1$ FAILURE, psf	1644	2552	3678	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins ML, slf  
 LL= 100 PL= 32 PI= 68  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 4-B, Depth 9.1'

PROJ. NO.: 13622 DATE: 7-31-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 4-B, Depth 9.1'  
 File: UU-7195 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO. :		1	2	3
INITIAL	WATER CONTENT, %	65.9	66.9	68.7
	DRY DENSITY, pcf	61.1	60.3	62.1
	SATURATION, %	100.3	99.7	107.3
	VOID RATIO	1.800	1.838	1.754
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	66.1	67.0	62.6
	DRY DENSITY, pcf	60.9	60.3	63.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.811	1.837	1.715
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10690	0.10970	0.1039
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1242	1094	984
ULTIMATE STRESS, psf		828	889	841
$\sigma_1$ FAILURE, psf		2250	3110	4008
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins ML, sif  
 LL= 95      PL= 26      PI= 69  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 7-B, Depth 21.5'






PROJ. NO.: 13622

DATE: 7-31-96

TRIAXIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**

FIG. NO. : \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 7-B, Depth 21.5'  
 File: UU-7196 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.7	57.0	59.1
	DRY DENSITY, pcf	67.1	65.6	59.4
	SATURATION, %	98.4	97.1	86.1
	VOID RATIO	1.550	1.609	1.880
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.95
AT TEST	WATER CONTENT, %	56.5	58.5	66.9
	DRY DENSITY, pcf	67.1	65.7	60.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.549	1.602	1.834
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
Strain rate, in/min		0.09870	0.09950	0.0982
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1270	1249	1115
ULTIMATE STRESS, psf		962	967	919
$\sigma_1$ FAILURE, psf		2278	3265	4139
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4 w/ 1yr &  
 Ins ML, slf & ars org  
 LL= 92      PL= 28      PI= 64  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 8-C, Depth 26.4'

PROJ. NO.: 13622      DATE: 7-31-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 8-C, Depth 26.4'  
 File: UU-7197 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.1	53.1	55.2
	DRY DENSITY, pcf	69.6	69.9	67.9
	SATURATION, %	101.7	100.5	99.6
	VOID RATIO	1.456	1.447	1.519
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	53.1	52.7	55.1
	DRY DENSITY, pcf	69.7	70.0	68.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.455	1.444	1.510
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09060	0.10110	0.0938	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1264	1278	1035	
ULTIMATE STRESS, psf	976	996	899	
$\sigma_1$ FAILURE, psf	2272	3294	4059	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH4  
w/ Ins ML  
LL= 81      PL= 25      PI= 56  
SPECIFIC GRAVITY= 2.74  
REMARKS:






CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGW-3U,  
Sample 12-C, Depth 42.0'  
PROJ. NO.: 13622      DATE: 8-1-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 12-C, Depth 42.0'  
 File: UU-7198 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	53.2	52.3	52.5
	DRY DENSITY, pcf	69.6	69.9	70.0
	SATURATION, %	100.1	99.0	99.8
	VOID RATIO	1.456	1.448	1.442
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.98
AT TEST	WATER CONTENT, %	53.3	52.3	52.4
	DRY DENSITY, pcf	69.6	70.3	70.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.459	1.434	1.437
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09780	0.10020	0.1000	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1092	1120	1148	
ULTIMATE STRESS, psf	773	804	839	
$\sigma_1$ FAILURE, psf	2100	3136	4172	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ 1yr & 1ns ML  
 LL= 73      PL= 28      PI= 45  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 15-D, Depth 54.8'  
 PROJ. NO.: 13622      DATE: 8-1-96



FIG. NO.:

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 15-D, Depth 54.8'  
 File: UU-7199      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	58.5	64.7	58.6
	DRY DENSITY, pcf	66.6	62.4	66.3
	SATURATION, %	102.2	101.9	101.5
	VOID RATIO	1.568	1.740	1.581
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	57.1	63.6	57.8
	DRY DENSITY, pcf	66.7	62.4	66.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.565	1.743	1.583
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.099	0.096	0.086	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1617	1139	1506	
ULTIMATE STRESS, psf	986	550	1095	
$\sigma_1$ FAILURE, psf	2625	3155	4530	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr & Ins ML  
 LL= 96      PL= 27      PI= 69  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 17-C, Depth 62.1'  
 PROJ. NO.: 13622      DATE: 8-1-96



TRIAXIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 17-C, Depth 62.1'  
 File: UU-7200 Project No.: 13622 FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	58.5	58.4	59.4
	DRY DENSITY, pcf	64.8	64.9	64.6
	SATURATION, %	97.8	97.7	98.7
	VOID RATIO	1.638	1.637	1.649
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.97	2.96	2.95
AT TEST	WATER CONTENT, %	58.8	57.9	57.1
	DRY DENSITY, pcf	65.5	66.1	66.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.612	1.587	1.564
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.0973	0.0941	0.0956	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1460	1542	1560	
ULTIMATE STRESS, psf	983	889	1195	
$\sigma_1$ FAILURE, psf	2468	3558	4584	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST: Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ 1yr & Ins ML  
 LL= 97      PL= 30      PI= 67  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-3U,  
 Sample 19-C, Depth 70.1'  
 PROJ. NO.: 13622      DATE: 8-1-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-3U, Sample 19-C, Depth 70.1'  
 File: UU-7201 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	60.8	52.8	54.8
	DRY DENSITY, pcf	65.4	69.6	69.1
	SATURATION, %	103.5	99.7	102.1
	VOID RATIO	1.598	1.440	1.459
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.99	2.98	2.98
AT TEST	WATER CONTENT, %	59.2	53.1	53.6
	DRY DENSITY, pcf	65.0	69.5	69.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.611	1.445	1.457
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.110	0.115	0.1123	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	145	189	153	
ULTIMATE STRESS, psf	151	193	158	
$\sigma_1$ FAILURE, psf	1153	2205	3177	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: VSo Gr CH2  
w/ lyr & ars ML, rts

LL= 58      PL= 20      PI= 38

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-4U,  
Sample 2-B, Depth 4.4'






PROJ. NO.: 13622      DATE: 8-2-96

FIG. NO.: \_\_\_\_\_



TRIAXIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-4U, Sample 2-B, Depth 4.4'  
 File: UU-7231                      Project No.: 13622                      FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	86.9	84.7	85.0
	DRY DENSITY, pcf	49.3	50.9	50.4
	SATURATION, %	96.5	98.4	97.5
	VOID RATIO	2.468	2.358	2.391
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.97
AT TEST	WATER CONTENT, %	90.2	85.6	86.6
	DRY DENSITY, pcf	49.3	51.1	50.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.471	2.344	2.373
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.0944	0.0834	0.0953	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	876	834	872	
ULTIMATE STRESS, psf	540	696	627	
$\sigma_1$ FAILURE, psf	1884	2850	3896	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained

SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CHOA  
 w/ Tr org

LL= 128    PL= 35    PI= 93  
 SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-4U,  
 Sample 8-C, Depth 22.1'






PROJ. NO.: 13622

DATE: 8-2-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-4U, Sample 8-C, Depth 22.1'  
 File: UU-7232                      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	56.6	59.5	60.9
	DRY DENSITY, pcf	66.8	65.8	64.2
	SATURATION, %	99.5	101.8	100.4
	VOID RATIO	1.560	1.602	1.663
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	57.0	58.4	60.5
	DRY DENSITY, pcf	66.7	65.8	64.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.563	1.599	1.656
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.10370	0.11080	0.1098	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	547	670	665	
ULTIMATE STRESS, psf	410	519	541	
$\sigma_1$ FAILURE, psf	1555	2686	3689	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ 1yr & 1ns ML  
 LL= 72      PL= 24      PI= 48  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-4U,  
 Sample 10-B, Depth 29.5'  
 PROJ. NO.: 13622      DATE: 8-5-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-4U, Sample 10-B, Depth 29.5'  
 File: UU-7246 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	63.1	63.0	63.8
	DRY DENSITY, pcf	64.1	63.2	62.4
	SATURATION, %	104.0	101.6	100.8
	VOID RATIO	1.649	1.686	1.723
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	60.9	62.0	63.1
	DRY DENSITY, pcf	63.9	63.2	62.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.656	1.687	1.716
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09490	0.09430	0.1004	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	843	843	780	
ULTIMATE STRESS, psf	675	706	669	
$\sigma_1$ FAILURE, psf	1851	2859	3804	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4  
w/ Ins & ars ML

LL= 101    PL= 31    PI= 70

SPECIFIC GRAVITY= 2.72

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-4U,  
Sample 12-D, Depth 38.8'

PROJ. NO.: 13622                      DATE: 8-5-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-4U, Sample 12-D, Depth 38.8'  
 File: UU-7247 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.8	68.6	68.1
	DRY DENSITY, pcf	60.8	60.2	59.9
	SATURATION, %	102.5	102.0	100.4
	VOID RATIO	1.813	1.843	1.858
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	66.4	67.2	67.4
	DRY DENSITY, pcf	60.7	60.2	60.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.820	1.842	1.846
DIAMETER, in	1.38	1.38	1.38	
HEIGHT, in	2.98	2.98	2.98	
Strain rate, in/min	0.09700	0.09290	0.0994	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1102	1038	841	
ULTIMATE STRESS, psf	821	821	652	
$\sigma_1$ FAILURE, psf	2110	3054	3865	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr & Ins ML  
 LL= 83      PL= 26      PI= 57  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-4U,  
 Sample 14-D, Depth 46.4'






PROJ. NO.: 13622      DATE: 8-6-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.:





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-4U, Sample 14-D, Depth 46.4'

File: UU-7262

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.9	60.5	59.4
	DRY DENSITY, pcf	62.9	64.7	65.2
	SATURATION, %	100.3	100.8	100.3
	VOID RATIO	1.719	1.644	1.622
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	62.8	59.7	58.8
	DRY DENSITY, pcf	62.8	64.9	65.5
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.722	1.637	1.610
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09120	0.09770	0.0944	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1106	1143	1258	
ULTIMATE STRESS, psf	813	776	943	
$\sigma_1$ FAILURE, psf	2114	3159	4282	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ 1yr & 1ns ML

LL= 89      PL= 30      PI= 59

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-4U,  
Sample 16-D, Depth 54.4'

PROJ. NO.: 13622      DATE: 8-6-96

FIG. NO. : \_\_\_\_\_



TRIAxIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-4U, Sample 16-D, Depth 54.4'  
 File: UU-7263      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.4	64.7	65.0
	DRY DENSITY, pcf	61.7	62.7	62.2
	SATURATION, %	102.7	102.7	101.9
	VOID RATIO	1.770	1.728	1.749
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.98
AT TEST	WATER CONTENT, %	64.4	62.5	63.5
	DRY DENSITY, pcf	61.9	63.1	62.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.763	1.712	1.741
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.09810	0.09920	0.0840
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1130	1123	1076
ULTIMATE STRESS, psf		773	759	912
$\sigma_1$ FAILURE, psf		2138	3139	4100
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr & Ins SM  
 LL= 92      PL= 28      PI= 64  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-4U,  
 Sample 18-C, Depth 61.6'

PROJ. NO.: 13622      DATE: 8-6-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-4U, Sample 18-C, Depth 61.6'

File: UU-7264

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	64.1	62.6	62.8
	DRY DENSITY, pcf	62.4	63.8	63.6
	SATURATION, %	101.2	102.6	102.3
	VOID RATIO	1.723	1.661	1.669
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	63.8	61.3	61.3
	DRY DENSITY, pcf	62.1	63.6	63.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.734	1.668	1.667
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.10870	0.09950	0.1075	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	748	955	792	
ULTIMATE STRESS, psf	597	619	638	
$\sigma_1$ FAILURE, psf	1756	2971	3816	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr org, ars PT & ML  
 LL= 98      PL= 27      PI= 71  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 3-B, Depth 9.4'  
 PROJ. NO.: 13622      DATE: 8-6-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-5U, Sample 3-B, Depth 9.4'  
 File: UU-7265                      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	85.3	65.2	89.3
	DRY DENSITY, pcf	50.5	60.0	49.4
	SATURATION, %	98.3	96.9	99.6
	VOID RATIO	2.361	1.831	2.440
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	87.0	67.4	88.8
	DRY DENSITY, pcf	50.4	59.9	49.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.366	1.833	2.414
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.11260	0.10570	0.1095	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	445	476	420	
ULTIMATE STRESS, psf	438	474	417	
$\sigma_1$ FAILURE, psf	1453	2492	3444	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: VSo Gr CH4  
 w/ ars org & ML, slt  
 LL= 89      PL= 29      PI= 60  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 4-D, Depth 14.4'  
 PROJ. NO.: 13622      DATE: 8-6-96  
**TRIAXIAL SHEAR TEST REPORT**  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-5U, Sample 4-D, Depth 14.4'

File: UU-7266

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	120.0	122.7	119.4
	DRY DENSITY, pcf	38.8	37.8	38.7
	SATURATION, %	96.3	95.5	95.5
	VOID RATIO	3.412	3.520	3.424
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.99	2.98	2.97
AT TEST	WATER CONTENT, %	125.3	128.6	123.4
	DRY DENSITY, pcf	38.6	37.8	39.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	3.434	3.524	3.382
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10850	0.10940	0.1118
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		726	829	872
ULTIMATE STRESS, psf		557	580	725
$\sigma_1$ FAILURE, psf		1734	2845	3896
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CHOC  
 w/ Ins & ars org  
 LL= 188    PL= 63    PI= 125  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 7-D, Depth 27.2'  
 PROJ. NO.: 13622                      DATE: 8-6-96

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-5U, Sample 7-D, Depth 27.2'  
 File: UU-7267 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	42.3	49.0	40.9
	DRY DENSITY, pcf	78.6	71.6	79.0
	SATURATION, %	99.1	97.2	96.8
	VOID RATIO	1.160	1.370	1.151
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	42.9	50.5	42.2
	DRY DENSITY, pcf	78.4	71.5	79.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.167	1.374	1.147
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.11240	0.11200	0.1127
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		630	467	665
ULTIMATE STRESS, psf		566	508	610
$\sigma_1$ FAILURE, psf		1638	2483	3689
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr. Ins & ars ML  
 LL= 90      PL= 26      PI= 64  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 9-C, Depth 33.6'

PROJ. NO.: 13622      DATE: 8-6-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-5U, Sample 9-C, Depth 33.6'

File: UU-7268

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	65.3	65.3	65.4
	DRY DENSITY, pcf	62.2	61.7	61.6
	SATURATION, %	102.3	101.1	100.7
	VOID RATIO	1.749	1.771	1.777
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	64.0	64.5	64.4
	DRY DENSITY, pcf	62.1	61.8	61.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.754	1.768	1.764
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10870	0.10080	0.1091
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		869	851	770
ULTIMATE STRESS, psf		641	689	647
$\sigma_1$ FAILURE, psf		1877	2867	3794
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr & Ins ML  
 LL= 92      PL= 31      PI= 61  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 11-D, Depth 42.8'

PROJ. NO.: 13622      DATE: 8-6-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-5U, Sample 11-D, Depth 42.8'

File: UU-7269

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.0	66.2	66.4
	DRY DENSITY, pcf	61.4	61.5	60.7
	SATURATION, %	101.3	101.8	100.1
	VOID RATIO	1.786	1.782	1.818
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	65.1	64.9	65.8
	DRY DENSITY, pcf	61.4	61.5	61.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.784	1.779	1.802
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.1079	0.1083	0.1093
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		890	932	858
ULTIMATE STRESS, psf		703	651	661
$\sigma_1$ FAILURE, psf		1898	2948	3882
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 -w/ lyr & Ins ML  
 LL= 98      PL= 31      PI= 67  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 13-D, Depth 50.2'



PROJ. NO.: 13622      DATE: 8-7-96

TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.:





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-5U, Sample 13-D, Depth 50.2'  
 File: UU-7270 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	60.6	58.9	59.1
	DRY DENSITY, pcf	64.1	64.6	64.1
	SATURATION, %	99.4	97.9	97.0
	VOID RATIO	1.670	1.647	1.670
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	60.8	59.8	60.6
	DRY DENSITY, pcf	64.1	64.8	64.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.667	1.639	1.660
DIAMETER, in	1.38	1.38	1.38	
HEIGHT, in	2.98	2.98	2.98	
Strain rate, in/min		0.1019	0.1042	0.1079
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		986	1022	919
ULTIMATE STRESS, psf		712	763	807
$\sigma_1$ FAILURE, psf		1994	3038	3943
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ 1yr & Ins ML  
 LL= 90      PL= 27      PI= 63  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-5U,

Sample 15-D, Depth 58.1'






PROJ. NO.: 13622

DATE: 8-7-96

TRIAxIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-5U, Sample 15-D, Depth 58.1'  
 File: UU-7271      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	66.8	66.9	65.0
	DRY DENSITY, pcf	60.5	58.6	61.7
	SATURATION, %	100.1	95.4	100.4
	VOID RATIO	1.827	1.920	1.773
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	66.8	69.9	64.3
	DRY DENSITY, pcf	60.4	58.7	61.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.832	1.914	1.762
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09580	0.10690	0.1083	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1381	1188	1382	
ULTIMATE STRESS, psf	958	907	955	
$\sigma_1$ FAILURE, psf	2389	3204	4406	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: M Gr CH4  
w/ lyr & Ins ML  
LL= 94 PL= 33 PI= 61  
SPECIFIC GRAVITY= 2.74  
REMARKS:

CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGW-5U,  
Sample 18-C, Depth 69.9'  
PROJ. NO.: 13622 DATE: 8-7-96



TRIAXIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_








Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-5U, Sample 18-C, Depth 69.9'  
 File: UU-7272 Project No.: 13622 FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.2	54.9	57.0
	DRY DENSITY, pcf	67.7	66.0	65.4
	SATURATION, %	97.4	94.4	96.7
	VOID RATIO	1.525	1.593	1.615
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.97
AT TEST	WATER CONTENT, %	55.4	57.4	58.1
	DRY DENSITY, pcf	67.9	66.5	66.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.519	1.572	1.593
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.109	50.098	20.1076	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1154	1170	1130	
ULTIMATE STRESS, psf	965	858	902	
$\sigma_1$ FAILURE, psf	2162	3186	4154	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ 1yr & 1ns SM, 1ns ML  
 LL= 86      PL= 31      PI= 55  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-5U,  
 Sample 19-D, Depth 74.8'  
 PROJ. NO.: 13622      DATE: 8-7-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-5U, Sample 19-D, Depth 74.8'

File: UU-7273

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	37.4	40.0	42.6
	DRY DENSITY, pcf	81.7	78.4	72.9
	SATURATION, %	93.8	92.7	86.9
	VOID RATIO	1.094	1.181	1.345
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	39.9	42.9	49.3
	DRY DENSITY, pcf	81.7	78.6	72.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.094	1.177	1.352
AT TEST	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.11180	0.11090	0.1043
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1210	1050	756
ULTIMATE STRESS, psf		1208	1021	665
$\sigma_1$ FAILURE, psf		2218	3066	3780
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ Ins ML & ars org  
 LL= 69      PL= 23      PI= 46  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-6U,  
 Sample 2-D, Depth 6.2'  
 PROJ. NO.: 13622      DATE: 8-7-96

FIG. NO.: \_\_\_\_\_



TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-6U, Sample 2-D, Depth 6.2'  
 File: UU-7274      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	37.0	37.8	38.2
	DRY DENSITY, pcf	84.7	83.5	82.7
	SATURATION, %	99.5	98.6	97.9
	VOID RATIO	1.020	1.049	1.068
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	37.4	38.2	39.0
	DRY DENSITY, pcf	84.4	83.6	82.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.026	1.047	1.069
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.10780.10080.1011			
BACK PRESSURE, psf	0 0 0			
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	512	458	632	
ULTIMATE STRESS, psf	567	461	664	
$\sigma_1$ FAILURE, psf	1520	2474	3656	
$\sigma_3$ FAILURE, psf	1008	2016	3024	






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CL6  
 w/ 1yr & 1ns CH  
 LL= 40      PL= 18      PI= 22  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-6U,  
 Sample 4-D, Depth 14.2'  
 PROJ. NO.: 13622      DATE: 8-7-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-6U, Sample 4-D, Depth 14.2'  
 File: UU-7275 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	54.1	53.7	54.5
	DRY DENSITY, pcf	69.5	69.1	68.8
	SATURATION, %	102.1	100.3	101.0
	VOID RATIO	1.442	1.456	1.468
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	53.1	53.4	53.6
	DRY DENSITY, pcf	69.5	69.3	69.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.443	1.452	1.459
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.0982	0.0919	0.0908	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf.	1008	2016	3024	
FAILURE STRESS, psf	1397	1442	1331	
ULTIMATE STRESS, psf	1103	1070	1047	
$\sigma_1$ FAILURE, psf	2405	3458	4355	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins & ars ML  
 LL= 82      PL= 26      PI= 56  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-6U,  
 Sample 17-D, Depth 46.8'



PROJ. NO.: 13622

DATE: 8-7-96

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-6U, Sample 17-D, Depth 46.8'  
 File: UU-7276      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	61.5	59.6	59.8
	DRY DENSITY, pcf	64.0	65.0	64.7
	SATURATION, %	101.2	100.6	100.1
	VOID RATIO	1.654	1.612	1.625
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	61.0	59.2	59.7
	DRY DENSITY, pcf	63.9	65.1	64.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.658	1.609	1.623
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.09160	0.08540	0.0721
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1436	1533	1524
ULTIMATE STRESS, psf		1048	1212	1213
$\sigma_1$ FAILURE, psf		2444	3549	4548
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ Ins & ars ML

LL= 102    PL= 32    PI= 70

SPECIFIC GRAVITY= 2.72

REMARKS:

FIG. NO.:

CLIENT: U.S. Army Corps of Engineers






PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-6U,  
Sample 19-D, Depth 54.8'

PROJ. NO.: 13622                      DATE: 8-7-96

TRIAXIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-6U, Sample 19-D, Depth 54.8'

File: UU-7277

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	49.6	55.4	52.8
	DRY DENSITY, pcf	70.3	63.0	67.7
	SATURATION, %	94.7	88.6	94.8
	VOID RATIO	1.434	1.714	1.527
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	52.5	62.2	55.0
	DRY DENSITY, pcf	70.2	63.2	68.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.437	1.705	1.507
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.0919	0.0932	0.1001
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1683	952	1379
ULTIMATE STRESS, psf		1414	861	1208
$\sigma_1$ FAILURE, psf		2691	2968	4403
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ 1yr & -Ins ML

LL= 85      PL= 27      PI= 58

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-6U,  
Sample 21-D, Depth 62.6'






PROJ. NO.: 13622      DATE: 8-7-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.:





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-6U, Sample 21-D, Depth 62.6'  
 File: UU-7278      Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.9	54.9	59.9
	DRY DENSITY, pcf	68.5	68.8	65.3
	SATURATION, %	102.7	101.9	101.8
	VOID RATIO	1.479	1.467	1.601
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	54.6	54.0	58.8
	DRY DENSITY, pcf	68.3	68.7	65.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.485	1.470	1.600
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.1075	0.1122	0.1110
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		598	614	538
ULTIMATE STRESS, psf		477	590	496
$\sigma_1$ FAILURE, psf		1606	2630	3562
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3 w/ Ins &  
 ars ML, ars org, few conc  
 LL= 70      PL= 26      PI= 44  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 3-C, Depth 9.7'  
 PROJ. NO.: 13622      DATE: 8-7-96



FIG. NO.: \_\_\_\_\_

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-7U, Sample 3-C, Depth 9.7'  
 File: UU-7279 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	65.1	71.9	67.3
	DRY DENSITY, pcf	60.3	54.3	57.0
	SATURATION, %	97.3	91.8	92.4
	VOID RATIO	1.818	2.129	1.980
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.97
AT TEST	WATER CONTENT, %	66.8	77.5	71.6
	DRY DENSITY, pcf	60.3	54.7	57.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.816	2.107	1.947
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.09650	0.09660	0.0949
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1462	1422	1352
ULTIMATE STRESS, psf		1250	1217	1119
$\sigma_1$ FAILURE, psf		2470	3438	4376
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr & Br CH4 w/  
 lyr & Ins org, ars ML  
 LL= 104 PL= 36 PI= 68  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 5-C, Depth 18.1'  
 PROJ. NO.: 13622 DATE: 8-7-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.



Stress Paths: + indicates end O indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-7U, Sample 5-C, Depth 18.1'  
 File: UU-7280 Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	69.8	72.9	73.6
	DRY DENSITY, pcf	59.5	57.7	57.4
	SATURATION, %	102.0	101.7	101.8
	VOID RATIO	1.876	1.964	1.980
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	68.4	71.7	72.2
	DRY DENSITY, pcf	59.5	57.7	57.4
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.875	1.965	1.979
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09280	0.09830	0.0975	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	958	983	1032	
ULTIMATE STRESS, psf	671	777	817	
$\sigma_1$ FAILURE, psf	1966	2999	4056	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ lyr. & ins ML  
 LL= 97      PL= 32      PI= 65  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 8-C, Depth 29.7'  
 PROJ. NO.: 13622      DATE: 8-7-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-7U, Sample 8-C, Depth 29.7'  
 File: UU-7281 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	49.7	49.5	48.0
	DRY DENSITY, pcf	73.0	72.7	73.8
	SATURATION, %	101.4	100.3	99.9
	VOID RATIO	1.343	1.354	1.318
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	48.8	49.3	47.8
	DRY DENSITY, pcf	73.2	72.8	74.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.338	1.351	1.309
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.09670	0.10140	0.1016
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		753	647	821
ULTIMATE STRESS, psf		650	587	732
$\sigma_1$ FAILURE, psf		1761	2663	3845
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ lyr & Ins ML  
 LL= 67      PL= 23      PI= 44  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 14-D, Depth 46.5'  
 PROJ. NO.: 13622      DATE: 8-7-96

FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-7U, Sample 14-D, Depth 46.5'

File: UU-7282

Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.0	62.1	61.4
	DRY DENSITY, pcf	64.0	63.2	63.6
	SATURATION, %	102.1	100.0	100.0
	VOID RATIO	1.651	1.688	1.671
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.97	2.97
	WATER CONTENT, %	60.6	61.4	60.7
	DRY DENSITY, pcf	64.1	63.6	64.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.649	1.670	1.650
DIAMETER, in	1.38	1.38	1.38	
HEIGHT, in	2.98	2.98	2.98	
Strain rate, in/min	0.10770	0.09710	0.1078	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	934	955	872	
ULTIMATE STRESS, psf	755	708	697	
$\sigma_1$ FAILURE, psf	1942	2971	3896	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins & ars ML  
 LL= 92      PL= 27      PI= 65  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 16-D, Depth 54.8'  
 PROJ. NO.: 13622      DATE: 8-8-96



FIG. NO.: \_\_\_\_\_

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-7U, Sample 16-D, Depth 54.8'  
 File: UU-7283 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.7	61.5	60.1
	DRY DENSITY, pcf	62.7	63.5	64.2
	SATURATION, %	99.9	99.9	99.4
	VOID RATIO	1.708	1.675	1.645
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.97	2.98	2.98
	WATER CONTENT, %	62.2	61.1	60.4
	DRY DENSITY, pcf	63.1	63.8	64.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.693	1.661	1.642
DIAMETER, in	1.38	1.38	1.38	
HEIGHT, in	2.98	2.98	2.98	
Strain rate, in/min	0.0958	0.0966	0.0929	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1062	945	1094	
ULTIMATE STRESS, psf	887	840	877	
$\sigma_1$ FAILURE, psf	2070	2961	4118	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins & ars ML  
 LL= 91      PL= 27      PI= 64  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-7U,  
 Sample 18-D, Depth 62.7'  
 PROJ. NO.: 13622      DATE: 8-8-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-7U, Sample 18-D, Depth 62.7'  
 File: UU-7284      Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	50.6	49.5	48.4
	DRY DENSITY, pcf	72.8	72.7	74.0
	SATURATION, %	102.7	100.4	101.2
	VOID RATIO	1.350	1.351	1.311
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	49.5	49.4	47.8
	DRY DENSITY, pcf	72.6	72.7	74.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.357	1.353	1.309
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.11080	0.11060	0.1115
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		609	577	589
ULTIMATE STRESS, psf		494	494	508
$\sigma_1$ FAILURE, psf		1617	2593	3613
$\sigma_3$ FAILURE, psf		1008	2016	3024



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH3  
 w/ 1yr & Ins ML  
 LL= 56      PL= 20      PI= 36  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 4-C, Depth 14.4'  
 PROJ. NO.: 13622      DATE: 8-8-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-8U, Sample 4-C, Depth 14.4'  
 File: UU-7285 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	76.1	74.7	75.3
	DRY DENSITY, pcf	56.3	56.5	56.1
	SATURATION, %	102.3	100.8	100.6
	VOID RATIO	2.037	2.029	2.050
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	74.8	74.1	74.7
	DRY DENSITY, pcf	56.1	56.4	56.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	2.051	2.032	2.047
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.1004	0.1083	0.1026	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	627	540	537	
ULTIMATE STRESS, psf	489	427	435	
$\sigma_1$ FAILURE, psf	1635	2556	3561	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained  
SAMPLE TYPE: Undisturbed  
DESCRIPTION: So Gr CH4  
w/ 1yr & 1ns ML  
LL= 97      PL= 28      PI= 69  
SPECIFIC GRAVITY= 2.74  
REMARKS:






CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGW-8U,  
Sample 7-D, Depth 26.8'  
PROJ. NO.: 13622      DATE: 8-8-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.

FIG. NO.:





Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-8U, Sample 7-D, Depth 26.8'

File: UU-7286

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	57.6	59.2	57.2
	DRY DENSITY, pcf	65.9	65.1	65.5
	SATURATION, %	99.3	100.1	97.5
	VOID RATIO	1.577	1.609	1.594
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	58.1	59.3	58.4
	DRY DENSITY, pcf	65.8	65.0	65.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.581	1.612	1.589
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.11	0.10	0.10
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		677	652	632
ULTIMATE STRESS, psf		519	550	504
$\sigma_1$ FAILURE, psf		1685	2668	3656
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins & ars ML  
 LL= 76      PL= 23      PI= 53  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 9-D, Depth 34.8'  
 PROJ. NO.: 13622      DATE: 8-8-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-8U, Sample 9-D, Depth 34.8'

File: UU-7287

Project No.: 13622

FIG. NO.: \_\_\_\_\_




SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.1	66.6	65.5
	DRY DENSITY, pcf	60.3	61.0	60.7
	SATURATION, %	100.0	101.0	98.6
	VOID RATIO	1.839	1.806	1.820
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	67.2	65.7	66.0
	DRY DENSITY, pcf	60.2	61.1	60.9
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.841	1.801	1.808
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10040	0.10720	0.0999
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		950	1037	990
ULTIMATE STRESS, psf		664	780	723
$\sigma_1$ FAILURE, psf		1958	3053	4014
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ Ins ML  
 LL= 96      PL= 32      PI= 64  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:



CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 11-C, Depth 42.0'  
 PROJ. NO.: 13622      DATE: 8-8-96

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-8U, Sample 11-C, Depth 42.0'  
 File: UU-7288      Project No.: 13622      FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	58.0	57.7	57.5
	DRY DENSITY, pcf	66.0	66.2	66.1
	SATURATION, %	100.2	100.4	99.7
	VOID RATIO	1.574	1.564	1.569
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	58.3	57.6	57.3
	DRY DENSITY, pcf	65.7	66.1	66.3
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.584	1.567	1.560
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.09770	0.10400	0.1000	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1086	1130	1102	
ULTIMATE STRESS, psf	771	858	851	
$\sigma_1$ FAILURE, psf	2094	3146	4126	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ ars ML  
 LL= 85      PL= 27      PI= 58  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 13-D, Depth 50.8'  
 PROJ. NO.: 13622      DATE: 8-8-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-8U, Sample 13-D, Depth 50.8'

File: UU-7289

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	59.6	58.0	58.7
	DRY DENSITY, pcf	65.6	66.2	64.8
	SATURATION, %	101.6	100.3	97.9
	VOID RATIO	1.607	1.584	1.642
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	58.4	57.8	59.6
	DRY DENSITY, pcf	65.8	66.2	65.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.601	1.583	1.634
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.07800	0.08990	0.0924
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		1360	1299	1268
ULTIMATE STRESS, psf		955	1047	1089
$\sigma_1$ FAILURE, psf		2368	3315	4292
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: M Gr CH4  
w/ lyr. & Ins SM

LL= 84      PL= 27      PI= 57

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-8U,  
Sample 15-B, Depth 57.4'






PROJ. NO.: 13622      DATE: 8-8-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-8U, Sample 15-B, Depth 57.4'  
 File: UU-7290      Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	60.2	58.8	60.2
	DRY DENSITY, pcf	65.4	65.1	63.7
	SATURATION, %	102.6	99.3	98.3
	VOID RATIO	1.596	1.610	1.665
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	58.5	58.7	60.6
	DRY DENSITY, pcf	65.5	65.4	64.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.592	1.597	1.648
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.09500	0.08340	0.0917
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		2039	1554	1624
ULTIMATE STRESS, psf		1243	1063	1056
$\sigma_1$ FAILURE, psf		3047	3570	4648
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 -w/ lyr & ars SM, sif  
 LL= 94      PL= 29      PI= 65  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee

Contract No. DACW29-95-D-0012

SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 18-C, Depth 66.1'






PROJ. NO.: 13622

DATE: 8-8-96

TRIAXIAL SHEAR TEST REPORT



Eustis Engineering Company, Inc.

FIG. NO.:



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-8U, Sample 18-C, Depth 66.1'  
 File: UU-7291 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	34.8	33.6	42.0
	DRY DENSITY, pcf	86.0	84.7	76.7
	SATURATION, %	98.0	91.6	94.8
	VOID RATIO	0.959	0.990	1.198
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.99	2.98	2.97
AT TEST	WATER CONTENT, %	35.9	36.4	43.9
	DRY DENSITY, pcf	85.5	85.1	77.1
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.970	0.982	1.185
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.111	0.118	0.1106	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1192	1366	635	
ULTIMATE STRESS, psf	1014	1345	567	
$\sigma_1$ FAILURE, psf	2200	3382	3659	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CL5  
 w/ 1yr & 1ns CH, slf  
 LL= 38      PL= 17      PI= 21  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-8U,  
 Sample 20-C, Depth 73.8'  
 PROJ. NO.: 13622      DATE: 8-8-96

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-8U, Sample 20-C, Depth 73.8'

File: UU-7292

Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	105.9	85.8	83.7
	DRY DENSITY, pcf	41.3	46.7	48.9
	SATURATION, %	92.7	88.8	92.3
	VOID RATIO	3.085	2.610	2.447
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.97	2.97
AT TEST	WATER CONTENT, %	114.9	95.5	88.8
	DRY DENSITY, pcf	41.1	47.1	49.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	3.101	2.578	2.398
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.1096	0.1118	0.1094	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	935	1025	831	
ULTIMATE STRESS, psf	882	942	786	
$\sigma_1$ FAILURE, psf	1943	3041	3855	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Br CHOA  
 w/ lyr & ins ML, rts  
 LL= 104    PL= 34    PI= 70  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-9U,  
 Sample 2-C, Depth 5.8'  
 PROJ. NO.: 13622                      DATE: 8-8-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U, Sample 2-C, Depth 5.8'  
 File: UU-7293 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	55.9	54.9	55.8
	DRY DENSITY, pcf	64.3	67.2	63.6
	SATURATION, %	92.7	97.8	91.0
	VOID RATIO	1.640	1.527	1.668
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.97
AT TEST	WATER CONTENT, %	60.1	56.1	60.5
	DRY DENSITY, pcf	64.4	67.3	64.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.635	1.525	1.647
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.0798	0.0996	0.1019
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		928	1225	1214
ULTIMATE STRESS, psf		761	1100	1029
$\sigma_1$ FAILURE, psf		1936	3241	4238
$\sigma_3$ FAILURE, psf		1008	2016	3024






TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH3  
 w/ ars ML & org  
 LL= 110    PL= 36    PI= 74  
 SPECIFIC GRAVITY= 2.72  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. CACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-9U  
 Sample 5-B, Depth 17.2'  
 PROJ. NO.: 13622    DATE: 8-8-96

TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



FIG. NO.: \_\_\_\_\_





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. CACW29-95-D-0012  
 Location: Boring ALGW-9U Sample 5-B, Depth 17.2'  
 File: UU-7294 Project No.: 13622

FIG. NO.: \_\_\_\_\_








SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	63.9	64.2	62.6
	DRY DENSITY, pcf	63.8	62.7	62.9
	SATURATION, %	104.1	101.8	99.7
	VOID RATIO	1.682	1.729	1.721
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	61.6	63.3	62.6
	DRY DENSITY, pcf	63.6	62.6	63.0
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.688	1.734	1.716
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.10700	0.10530	0.1092
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		632	652	635
ULTIMATE STRESS, psf		498	541	448
$\sigma_1$ FAILURE, psf		1640	2668	3659
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: So Gr CH4  
 w/ lyr. & Ins ML, ars org  
 LL= 86      PL= 24      PI= 62  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-9U  
 Sample 7-B, Depth 25.5'  
 PROJ. NO.: 13622      DATE: 8-8-96

TRIAxIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



FIG. NO.: \_\_\_\_\_



Stress Paths: + indicates end o indicates peak

Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U Sample 7-B, Depth 25.5'  
 File: UU-7295 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	62.6	62.6	63.0
	DRY DENSITY, pcf	63.7	63.1	61.0
	SATURATION, %	101.8	100.2	95.6
	VOID RATIO	1.684	1.713	1.805
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	61.5	62.3	65.6
	DRY DENSITY, pcf	63.7	63.2	61.2
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.686	1.707	1.797
Strain rate, in/min	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	867	875	770	
ULTIMATE STRESS, psf	665	701	648	
$\sigma_1$ FAILURE, psf	1875	2891	3794	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4  
w/ 1yr & Ins ML

LL= 88      PL= 25      PI= 63

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-9U,  
Sample 9-C, Depth 34.1'

PROJ. NO.: 13622      DATE: 8-8-96

TRIAXIAL SHEAR TEST REPORT



**Eustis Engineering Company, Inc.**

FIG. NO.: \_\_\_\_\_



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U, Sample 9-C, Depth 34.1'  
 File: UU-7296 Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	67.4	68.3	65.1
	DRY DENSITY, pcf	60.9	59.4	61.6
	SATURATION, %	102.2	99.6	100.5
	VOID RATIO	1.809	1.879	1.775
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	66.0	68.6	64.4
	DRY DENSITY, pcf	60.9	59.4	61.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.809	1.880	1.766
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min		0.0996	0.1065	0.0985
BACK PRESSURE, psf		0	0	0
CELL PRESSURE, psf		1008	2016	3024
FAILURE STRESS, psf		871	780	876
ULTIMATE STRESS, psf		646	655	713
$\sigma_1$ FAILURE, psf		1879	2796	3900
$\sigma_3$ FAILURE, psf		1008	2016	3024

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed

DESCRIPTION: So Gr CH4  
w/ Ins ML

LL= 94      PL= 27      PI= 67

SPECIFIC GRAVITY= 2.74

REMARKS:

CLIENT: U.S. Army Corps of Engineers

PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012






SAMPLE LOCATION: Boring ALGW-9U,  
Sample 11-D, Depth 42.8'

PROJ. NO.: 13622      DATE: 8-8-96

FIG. NO.:

TRIAxIAL SHEAR TEST REPORT

**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers



Project: Algiers Levee Contract No. DACW29-95-D-0012

Location: Boring ALGW-9U, Sample 11-D, Depth 42.8'

File: UU-7297

Project No.: 13622

FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	61.3	60.4	64.4
	DRY DENSITY, pcf	64.2	63.9	61.6
	SATURATION, %	101.0	99.2	99.8
	VOID RATIO	1.653	1.657	1.755
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	60.6	60.7	64.2
	DRY DENSITY, pcf	64.1	64.1	61.8
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.654	1.650	1.746
Strain rate, in/min	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	773	813	689	
ULTIMATE STRESS, psf	587	664	528	
$\sigma_1$ FAILURE, psf	1781	2829	3713	
$\sigma_3$ FAILURE, psf	1008	2016	3024	

TYPE OF TEST:  
Unconsolidated Undrained

SAMPLE TYPE: Undisturbed  
DESCRIPTION: So Gr CH4  
w/ ars ML

LL= 89      PL= 23      PI= 66  
SPECIFIC GRAVITY= 2.727

REMARKS:






CLIENT: U.S. Army Corps of Engineers  
PROJECT: Algiers Levee  
Contract No. DACW29-95-D-0012  
SAMPLE LOCATION: Boring ALGW-9U,  
Sample 13-D, Depth 50.8'  
PROJ. NO.: 13622      DATE: 8-8-96

TRIAxIAL SHEAR TEST REPORT

Eustis Engineering Company, Inc.



FIG. NO.:





Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U, Sample 13-D, Depth 50.8'  
 File: UU-7298 Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	63.4	62.6	64.2
	DRY DENSITY, pcf	63.2	63.5	62.5
	SATURATION, %	101.8	101.2	101.2
	VOID RATIO	1.706	1.696	1.739
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
AT TEST	WATER CONTENT, %	62.4	61.7	63.3
	DRY DENSITY, pcf	63.1	63.6	62.6
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	1.710	1.689	1.735
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
Strain rate, in/min	0.106	0.101	0.1015	
BACK PRESSURE, psf	0	0	0	
CELL PRESSURE, psf	1008	2016	3024	
FAILURE STRESS, psf	1146	1143	1083	
ULTIMATE STRESS, psf	866	824	749	
$\sigma_1$ FAILURE, psf	2154	3159	4107	
$\sigma_3$ FAILURE, psf	1008	2016	3024	



TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CH4  
 w/ Ins ML  
 LL= 82      PL= 23      PI= 59  
 SPECIFIC GRAVITY= 2.74  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-9U,  
 Sample 15-D, Depth 48.8'  
 PROJ. NO.: 13622      DATE: 8-8-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U, Sample 15-D, Depth 48.8'  
 File: UU-7299 Project No.: 13622






FIG. NO.: \_\_\_\_\_



SPECIMEN NO.:		1	2	3
INITIAL	WATER CONTENT, %	29.9	28.3	29.3
	DRY DENSITY, pcf	94.3	95.0	93.3
	SATURATION, %	102.3	98.7	97.9
	VOID RATIO	0.788	0.774	0.807
	DIAMETER, in	1.38	1.38	1.38
AT TEST	HEIGHT, in	2.98	2.98	2.98
	WATER CONTENT, %	29.3	28.7	29.6
	DRY DENSITY, pcf	94.1	95.0	93.7
	SATURATION, %	100.0	100.0	100.0
	VOID RATIO	0.790	0.775	0.800
	DIAMETER, in	1.38	1.38	1.38
	HEIGHT, in	2.98	2.98	2.98
	Strain rate, in/min	0.10310	0.11150	0.1121
	BACK PRESSURE, psf	0	0	0
	CELL PRESSURE, psf	1008	2016	3024
	FAILURE STRESS, psf	1388	1750	1719
	ULTIMATE STRESS, psf	1276	1619	1600
	$\sigma_1$ FAILURE, psf	2396	3766	4743
	$\sigma_3$ FAILURE, psf	1008	2016	3024

TYPE OF TEST:  
 Unconsolidated Undrained  
 SAMPLE TYPE: Undisturbed  
 DESCRIPTION: M Gr CL4  
 w/ slf  
 LL= 32      PL= 20      PI= 12  
 SPECIFIC GRAVITY= 2.7  
 REMARKS:  
 FIG. NO.: \_\_\_\_\_

CLIENT: U.S. Army Corps of Engineers  
 PROJECT: Algiers Levee  
 Contract No. DACW29-95-D-0012  
 SAMPLE LOCATION: Boring ALGW-9U,  
 Sample 22-C, Depth 77.9'  
 PROJ. NO.: 13622      DATE: 8-8-96  
 TRIAXIAL SHEAR TEST REPORT  
**Eustis Engineering Company, Inc.**



Client: U.S. Army Corps of Engineers  
 Project: Algiers Levee Contract No. DACW29-95-D-0012  
 Location: Boring ALGW-9U, Sample 22-C, Depth 77.9'  
 File: UU-7300                      Project No.: 13622                      FIG. NO.: \_\_\_\_\_

APPENDIX F-II  
COMPUTER OUTPUT

**WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF  
NEW ORLEANS, LA  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
DESIGN MEMORANDUM NO. 2  
EAST AND WEST OF ALGIERS CANAL**

**APPENDIX F-II**

**GEOTECHNICAL COMPUTER OUTPUT**







LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

ELEV. (FT)	<-LEFTSIDE PRESSURES->		<---NET PRESSURES----> (SOIL PLUS WATER)		<RIGHTSIDE PRESSURES->	
	PASSIVE (PSF)	ACTIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)
11.50	.00	.00	.000	.000	.00	.00
10.50	.00	.00	62.400	62.400	.00	.00
9.50	.00	.00	124.800	124.800	.00	.00
8.50	.00	.00	187.200	187.200	.00	.00
7.50	.00	.00	249.600	249.600	.00	.00
6.50	.00	.00	312.000	312.000	.00	.00
5.50	.00	.00	374.400	374.400	.00	.00
4.50	.00	.00	436.800	436.800	.00	.00
3.50	.00	.00	499.200	499.200	.00	.00
3.00+	.00	.00	530.400	530.400	.00	.00
3.00-	760.00	.00	-229.600	1290.400	.00	760.00
2.75	748.64	.00	-202.636	1280.000	.00	734.00
2.50	737.27	.00	-175.673	1269.600	.00	708.00
2.00	783.64	.00	-190.836	1317.891	.00	725.09
1.50	830.51	.00	-206.510	1366.690	.00	742.69
.50	913.20	.00	-226.796	1453.239	.00	766.84
.00	937.78	.00	-220.178	1480.005	.00	762.40
-.50	959.92	.00	-211.123	1504.820	.00	756.02
-1.50	1032.69	.00	-221.491	1583.190	.00	771.99
-2.50	1115.91	.00	-242.309	1672.509	.00	798.91
-3.50	1182.55	.00	-246.549	1761.091	.00	825.09
-4.50	1218.96	.00	-282.964	1787.273	.00	851.27
-5.50	1239.53	.00	-303.535	1813.455	.00	877.45
-6.50	1259.62	.00	-323.618	1839.636	.00	903.64
-7.50	1279.95	.00	-343.945	1865.818	.00	929.82
-8.50	1300.27	.00	-364.273	1892.000	.00	956.00
-9.50	1320.60	.00	-384.600	1918.182	.00	982.18
-10.50	1340.93	.00	-404.927	1944.364	.00	1008.36
-11.50	1361.25	.00	-425.255	1970.545	.00	1034.55
-12.50	1381.58	.00	-445.582	1996.727	.00	1060.73
-13.50	1401.91	.00	-465.909	2022.909	.00	1086.91
-14.50	1422.24	.00	-486.236	2049.091	.00	1113.09
-15.50	1442.56	.00	-506.564	2075.273	.00	1139.27
-16.50	1462.89	.00	-526.891	2101.455	.00	1165.45
-17.50	1483.22	.00	-547.218	2127.636	.00	1191.64
-18.50	1503.55	.00	-567.545	2153.818	.00	1217.82
-19.50	1523.87	44.43	-587.873	2135.572	.00	1244.00
-20.50	1544.20	162.67	-608.200	2043.513	.00	1270.18
-21.50	1564.53	244.28	-628.527	1988.079	.00	1296.36
-22.50	1584.85	261.34	-648.855	1997.202	.00	1322.55
-23.50	1605.18	280.30	-669.182	2004.427	.00	1348.73
-24.50	1625.51	299.70	-689.509	2011.209	.00	1374.91
-25.50	1645.84	319.10	-709.836	2017.991	.00	1401.09
-26.50	1666.16	338.50	-730.164	2024.773	.00	1427.27
-27.50	1686.49	357.90	-750.491	2031.555	.00	1453.45



## I.--HEADING

'ALGIERS CANAL, EE14638

'REACH 4, I WALL, NEAR FLOOD GATE, WATER EL 11.5

## II.--RESULTS

ELEVATION (FT)	BENDING MOMENT (LB-FT)	SHEAR (LB)	SCALED DEFLECTION (LB-IN <sup>3</sup> )	NET PRESSURE (PSF)
11.50	0.	0.	7.6853E+09	.00
10.50	10.	31.	7.2329E+09	62.40
9.50	83.	125.	6.7805E+09	124.80
8.50	281.	281.	6.3282E+09	187.20
7.50	666.	499.	5.8765E+09	249.60
6.50	1300.	780.	5.4260E+09	312.00
5.50	2246.	1123.	4.9777E+09	374.40
4.50	3567.	1529.	4.5334E+09	436.80
3.50	5325.	1997.	4.0953E+09	499.20
3.00	6387.	2254.	3.8795E+09	530.40
3.00	6387.	2254.	3.8795E+09	-229.60
2.75	6944.	2200.	3.7726E+09	-202.64
2.50	7488.	2153.	3.6665E+09	-175.67
2.00	8541.	2061.	3.4567E+09	-190.84
1.50	9548.	1962.	3.2506E+09	-206.51
.50	11403.	1745.	2.8511E+09	-226.80
.00	12247.	1634.	2.6586E+09	-220.18
-.50	13037.	1526.	2.4714E+09	-211.12
-1.50	14455.	1309.	2.1141E+09	-221.49
-2.50	15651.	1077.	1.7818E+09	-242.31
-3.50	16606.	833.	1.4765E+09	-246.55
-4.50	17310.	568.	1.1998E+09	-282.96
-5.50	17733.	275.	9.5303E+08	-303.53
-6.50	17853.	-39.	7.3684E+08	-323.62
-7.50	17650.	-372.	5.5146E+08	-343.95
-8.50	17102.	-726.	3.9653E+08	-364.27
-9.50	16190.	-1101.	2.7110E+08	-384.60
-10.50	14893.	-1496.	1.7359E+08	-404.93
-11.50	13192.	-1911.	1.0176E+08	-425.25
-12.50	11065.	-2346.	5.2659E+07	-445.58
-13.50	8493.	-2802.	2.2617E+07	-465.91
-13.73	7823.	-2912.	1.7869E+07	-470.67
-14.50	5511.	-3057.	7.1860E+06	91.88
-15.50	2623.	-2597.	1.2916E+06	826.67
-16.50	561.	-1403.	4.8574E+04	1561.45
-17.26	0.	0.	0.0000E+00	2121.41

(NOTE: DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN IN\*\*4 TO OBTAIN DEFLECTION IN INCHES.)

## III.--SOIL PRESSURES

ELEVATION (FT)	< LEFTSIDE PRESSURE (PSF) >		< RIGHTSIDE PRESSURE (PSF) >	
	PASSIVE	ACTIVE	ACTIVE	PASSIVE
11.50	0.	0.	0.	0.
10.50	0.	0.	0.	0.
9.50	0.	0.	0.	0.

8.50	0.	0.	0.	0.
7.50	0.	0.	0.	0.
6.50	0.	0.	0.	0.
5.50	0.	0.	0.	0.
4.50	0.	0.	0.	0.
3.50	0.	0.	0.	0.
3.00+	0.	0.	0.	0.
3.00-	760.	0.	0.	760.
2.75	749.	0.	0.	734.
2.50	737.	0.	0.	708.
2.00	784.	0.	0.	725.
1.50	831.	0.	0.	743.
.50	913.	0.	0.	767.
.00	938.	0.	0.	762.
-.50	960.	0.	0.	756.
-1.50	1033.	0.	0.	772.
-2.50	1116.	0.	0.	799.
-3.50	1183.	0.	0.	825.
-4.50	1219.	0.	0.	851.
-5.50	1240.	0.	0.	877.
-6.50	1260.	0.	0.	904.
-7.50	1280.	0.	0.	930.
-8.50	1300.	0.	0.	956.
-9.50	1321.	0.	0.	982.
-10.50	1341.	0.	0.	1008.
-11.50	1361.	0.	0.	1035.
-12.50	1382.	0.	0.	1061.
-13.50	1402.	0.	0.	1087.
-13.73	1407.	0.	0.	1093.
-14.50	1422.	0.	0.	1113.
-15.50	1443.	0.	0.	1139.
-16.50	1463.	0.	0.	1165.
-17.26	1483.	0.	0.	1192.
-18.50	1504.	0.	0.	1218.

Refer to Photo F-34

PROGRAM CWALSHT-DESIGN/ANALYSIS OF ANCHORED OR CANTILEVER SHEET PILE WALLS BY CLASSICAL METHODS

DATE: 20-MAR-1998

TIME: 8.28.39

èèèèèèèèèèèèèèèèèèèè
INPUT DATA
àèèèèèèèèèèèèèèèèèèèè

I.--HEADING:

'ALGIERS CANAL, EE14638
'REACH 3,I WALL, NEAR FLOOD GATE, WATER EL 11.5

II.--CONTROL

CANTILEVER WALL DESIGN

LEVEL 1 FACTOR OF SAFETY FOR ACTIVE PRESSURES = 1.00
LEVEL 1 FACTOR OF SAFETY FOR PASSIVE PRESSURES = 1.00

III.--WALL DATA

ELEVATION AT TOP OF WALL = 11.50 (FT)

IV.--SURFACE POINT DATA

IV.A--RIGHTSIDE

DIST. FROM ELEVATION
WALL (FT) (FT)
.00 3.00
30.00 .00
100.00 .00

IV.B-- LEFTSIDE

DIST. FROM ELEVATION
WALL (FT) (FT)
.00 3.00
30.00 .00
100.00 .00

V.--SOIL LAYER DATA

V.A.--RIGHTSIDE LAYER DATA

LEVEL 2 FACTOR OF SAFETY FOR ACTIVE PRESSURES = DEFAULT
LEVEL 2 FACTOR OF SAFETY FOR PASSIVE PRESSURES = DEFAULT

Table with 10 columns: SAT. WGHT. (PCF), MOIST WGHT. (PCF), ANGLE OF INTERNAL FRICTION (DEG), COH-ESION (PSF), ANGLE OF WALL FRICTION (DEG), ADH-ESION (PSF), ELEV. (FT), SLOPE (FT/FT), <-SAFETY-> <-FACTOR->, ACT. PASS. DEF DEF



LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

ELEV. (FT)	<-LEFTSIDE PRESSURES->		<---NET PRESSURES---> (SOIL PLUS WATER)		<RIGHTSIDE PRESSURES->	
	PASSIVE (PSF)	ACTIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)
11.50	.00	.00	.000	.000	.00	.00
10.50	.00	.00	62.400	62.400	.00	.00
9.50	.00	.00	124.800	124.800	.00	.00
8.50	.00	.00	187.200	187.200	.00	.00
7.50	.00	.00	249.600	249.600	.00	.00
6.50	.00	.00	312.000	312.000	.00	.00
5.50	.00	.00	374.400	374.400	.00	.00
4.50	.00	.00	436.800	436.800	.00	.00
3.50	.00	.00	499.200	499.200	.00	.00
3.00+	.00	.00	530.400	530.400	.00	.00
3.00-	760.00	.00	-229.600	1290.400	.00	760.00
2.75	748.64	.00	-202.636	1280.455	.00	734.45
2.50	737.27	.00	-175.673	1270.509	.00	708.91
2.00	783.64	.00	-190.836	1319.709	.00	726.91
1.50	830.00	.00	-206.000	1369.409	.00	745.41
.50	922.73	.00	-236.327	1457.809	.00	771.41
.00	969.09	.00	-251.491	1486.509	.00	768.91
-.50	1015.45	.00	-266.655	1515.209	.00	766.41
-1.50	1108.43	.00	-297.226	1603.359	.00	792.16
-2.50	1200.91	.00	-327.309	1702.509	.00	828.91
-3.50	1277.55	.00	-341.549	1800.909	.00	864.91
-4.50	1323.96	.00	-387.964	1836.909	.00	900.91
-5.50	1354.53	.00	-418.535	1872.909	.00	936.91
-6.50	1384.62	.00	-448.618	1908.909	.00	972.91
-7.50	1414.95	.00	-478.945	1944.909	.00	1008.91
-8.50	1445.27	.00	-509.273	1980.909	.00	1044.91
-9.50	1475.60	.00	-539.600	2016.909	.00	1080.91
-10.50	1505.93	.00	-569.927	2052.909	.00	1116.91
-11.50	1536.25	.00	-600.255	2088.909	.00	1152.91
-12.50	1566.58	.00	-630.582	2124.909	.00	1188.91
-13.50	1596.91	.00	-660.909	2160.909	.00	1224.91
-14.50	1627.24	.00	-691.236	2196.909	.00	1260.91
-15.50	1657.56	.00	-721.564	2232.909	.00	1296.91
-16.50	1687.89	25.32	-751.891	2243.593	.00	1332.91
-17.50	1718.22	140.79	-782.218	2164.118	.00	1368.91
-18.50	1748.55	281.32	-812.545	2059.587	.00	1404.91
-19.50	1778.87	342.05	-842.873	2034.862	.00	1440.91
-20.50	1809.20	367.10	-873.200	2045.809	.00	1476.91
-21.50	1839.53	396.50	-903.527	2052.409	.00	1512.91
-22.50	1869.85	425.90	-933.855	2059.009	.00	1548.91
-23.50	1900.18	455.30	-964.182	2065.609	.00	1584.91
-24.50	1930.51	484.70	-994.509	2072.209	.00	1620.91
-25.50	1960.84	514.10	-1024.836	2078.809	.00	1656.91
-26.50	1991.16	543.50	-1055.164	2085.409	.00	1692.91
-27.50	2021.49	572.90	-1085.491	2092.009	.00	1728.91



PROGRAM CWALSHT-DESIGN/ANALYSIS OF ANCHORED OR CANTILEVER SHEET PILE WALLS BY CLASSICAL METHODS

DATE: 20-MAR-1998

TIME: 8.28.57

Summary of Results for Cantilever Wall Design

I.--HEADING

'ALGIERS CANAL, EE14638
'REACH 3,I WALL, NEAR FLOOD GATE, WATER EL 11.5

II.--SUMMARY

RIGHTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

Table with 2 columns: Parameter and Value. Rows include WALL BOTTOM ELEV. (FT), PENETRATION (FT), MAX. BEND. MOMENT (LB-FT), AT ELEVATION (FT), MAX. SCALED DEFL. (LB-IN3), AT ELEVATION (FT).

(NOTE: DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN IN\*\*4 TO OBTAIN DEFLECTION IN INCHES.)

PROGRAM CWALSHT-DESIGN/ANALYSIS OF ANCHORED OR CANTILEVER SHEET PILE WALLS BY CLASSICAL METHODS

DATE: 20-MAR-1998

TIME: 8.28.57

COMPLETE RESULTS FOR Cantilever Wall Design

I.--HEADING

'ALGIERS CANAL, EE14638

'REACH 3,I WALL, NEAR FLOOD GATE, WATER EL 11.5

II.--RESULTS

ELEVATION (FT)	BENDING MOMENT (LB-FT)	SHEAR (LB)	SCALED DEFLECTION (LB-IN3)	NET PRESSURE (PSF)
11.50	0.	0.	5.7319E+09	.00
10.50	10.	31.	5.3650E+09	62.40
9.50	83.	125.	4.9983E+09	124.80
8.50	281.	281.	4.6316E+09	187.20
7.50	666.	499.	4.2655E+09	249.60
6.50	1300.	780.	3.9006E+09	312.00
5.50	2246.	1123.	3.5379E+09	374.40
4.50	3567.	1529.	3.1792E+09	436.80
3.50	5325.	1997.	2.8267E+09	499.20
3.00	6387.	2254.	2.6537E+09	530.40
3.00	6387.	2254.	2.6537E+09	-229.60
2.75	6944.	2200.	2.5683E+09	-202.64
2.50	7488.	2153.	2.4835E+09	-175.67
2.00	8541.	2061.	2.3165E+09	-190.84
1.50	9548.	1962.	2.1532E+09	-206.00
.50	11402.	1741.	1.8394E+09	-236.33
.00	12242.	1619.	1.6897E+09	-251.49
-.50	13019.	1489.	1.5452E+09	-266.65
-1.50	14370.	1207.	1.2735E+09	-297.23
-2.50	15424.	895.	1.0266E+09	-327.31
-3.50	16153.	561.	8.0630E+08	-341.55
-4.50	16535.	196.	6.1386E+08	-387.96
-5.50	16532.	-207.	4.4993E+08	-418.53
-6.50	16111.	-641.	3.1451E+08	-448.62
-7.50	15241.	-1105.	2.0686E+08	-478.95
-8.50	13891.	-1599.	1.2549E+08	-509.27
-9.50	12033.	-2123.	6.8040E+07	-539.60
-10.50	9635.	-2678.	3.1308E+07	-569.93
-10.95	8386.	-2935.	2.0571E+07	-583.42
-11.50	6690.	-3140.	1.1144E+07	-158.08
-12.50	3598.	-2915.	2.5178E+06	608.33
-13.50	1115.	-1924.	1.9662E+05	1374.74
-14.50	6.	-166.	5.3487E+00	2141.14
-14.58	0.	0.	0.0000E+00	2199.66

(NOTE: DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN IN\*\*4 TO OBTAIN DEFLECTION IN INCHES.)

III.--SOIL PRESSURES

ELEVATION (FT)	< LEFTSIDE PRESSURE (PSF) >		<RIGHTSIDE PRESSURE (PSF) >	
	PASSIVE	ACTIVE	ACTIVE	PASSIVE
11.50	0.	0.	0.	0.
10.50	0.	0.	0.	0.
9.50	0.	0.	0.	0.
8.50	0.	0.	0.	0.
7.50	0.	0.	0.	0.

6.50	0.	0.	0.	0.
5.50	0.	0.	0.	0.
4.50	0.	0.	0.	0.
3.50	0.	0.	0.	0.
3.00+	0.	0.	0.	0.
3.00-	760.	0.	0.	760.
2.75	749.	0.	0.	734.
2.50	737.	0.	0.	709.
2.00	784.	0.	0.	727.
1.50	830.	0.	0.	745.
.50	923.	0.	0.	771.
.00	969.	0.	0.	769.
-.50	1015.	0.	0.	766.
-1.50	1108.	0.	0.	792.
-2.50	1201.	0.	0.	829.
-3.50	1278.	0.	0.	865.
-4.50	1324.	0.	0.	901.
-5.50	1355.	0.	0.	937.
-6.50	1385.	0.	0.	973.
-7.50	1415.	0.	0.	1009.
-8.50	1445.	0.	0.	1045.
-9.50	1476.	0.	0.	1081.
-10.50	1506.	0.	0.	1117.
-10.95	1519.	0.	0.	1133.
-11.50	1536.	0.	0.	1153.
-12.50	1567.	0.	0.	1189.
-13.50	1597.	0.	0.	1225.
-14.50	1627.	0.	0.	1261.
-14.58	1658.	0.	0.	1297.
-16.50	1688.	25.	0.	1333.





RIGHTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

ELEV. (FT)	<-LEFTSIDE PRESSURES->		<---NET PRESSURES----> (SOIL PLUS WATER)		<RIGHTSIDE PRESSURES->	
	PASSIVE (PSF)	ACTIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)
11.50	.00	.00	.000	.000	.00	.00
10.50	.00	.00	62.400	62.400	.00	.00
9.50	.00	.00	124.800	124.800	.00	.00
8.50	.00	.00	187.200	187.200	.00	.00
7.50	.00	.00	249.600	249.600	.00	.00
6.50	.00	.00	312.000	312.000	.00	.00
5.50	.00	.00	374.400	374.400	.00	.00
4.50	.00	.00	436.800	436.800	.00	.00
3.50	.00	.00	499.200	499.200	.00	.00
3.00+	.00	.00	530.400	530.400	.00	.00
3.00-	760.00	.00	-229.600	1290.400	.00	760.00
2.75	749.32	.00	-203.318	1281.136	.00	735.14
2.50	738.64	.00	-177.036	1271.873	.00	710.27
2.00	786.36	.00	-193.564	1322.436	.00	729.64
1.50	835.27	.00	-211.265	1374.174	.00	750.17
.50	907.36	.00	-220.955	1451.937	.00	765.54
.00	906.29	.00	-188.688	1453.707	.00	736.11
-.50	903.39	.00	-154.593	1453.648	.00	704.85
.50	967.71	.00	-156.510	1523.394	.00	712.19
-2.50	1057.16	.00	-183.559	1618.759	.00	745.16
-3.50	1129.03	.00	-193.026	1712.386	.00	776.39
-4.50	1170.67	.00	-234.668	1743.614	.00	807.61
-5.50	1196.47	.00	-260.466	1774.841	.00	838.84
-6.50	1221.78	.00	-285.777	1806.068	.00	870.07
-7.50	1247.33	.00	-311.332	1837.295	.00	901.30
-8.50	1272.89	.00	-336.886	1868.523	.00	932.52
-9.50	1298.44	32.16	-362.441	1867.591	.00	963.75
-10.50	1324.01	123.97	-388.006	1807.015	.00	994.99
-11.50	1349.53	197.02	-413.530	1765.169	.00	1026.18
-12.00	1361.47	208.40	-425.474	1768.568	.00	1040.97
-12.50	1371.83	217.04	-435.834	1773.119	.00	1054.16
-13.50	1390.92	238.87	-454.919	1776.047	.00	1078.92
-14.50	1409.96	297.28	-473.964	1742.361	.00	1103.64
-15.50	1429.02	377.44	-493.018	1686.926	.00	1128.36
-16.50	1448.07	419.11	-511.768	1669.985	.30	1153.09
-17.50	1467.13	434.15	-506.372	1679.668	24.76	1177.82
-18.50	1486.18	452.25	-474.455	1686.295	75.73	1202.55
-19.50	1505.24	470.35	-456.100	1692.923	113.14	1227.27
-20.50	1524.29	488.45	-452.401	1699.550	135.89	1252.00
-21.50	1543.35	506.55	-447.115	1706.177	160.23	1276.73
-22.50	1562.40	524.65	-441.830	1712.805	184.57	1301.45
-23.50	1581.45	542.75	-436.545	1719.432	208.91	1326.18
-24.50	1600.51	560.85	-431.259	1726.059	233.25	1350.91
-25.50	1619.56	578.95	-425.974	1732.686	257.59	1375.64
-26.50	1638.62	597.05	-420.688	1739.314	281.93	1400.36
-27.50	1657.67	615.15	-415.403	1745.941	306.27	1425.09







## III.--SOIL PRESSURES

ELEVATION (FT)	< LEFTSIDE PRESSURE (PSF) >		< RIGHTSIDE PRESSURE (PSF) >	
	PASSIVE	ACTIVE	ACTIVE	PASSIVE
11.50	0.	0.	0.	0.
10.50	0.	0.	0.	0.
9.50	0.	0.	0.	0.
8.50	0.	0.	0.	0.
7.50	0.	0.	0.	0.
6.50	0.	0.	0.	0.
5.50	0.	0.	0.	0.
4.50	0.	0.	0.	0.
3.50	0.	0.	0.	0.
3.00+	0.	0.	0.	0.
3.00-	760.	0.	0.	0.
2.75	749.	0.	0.	760.
2.50	739.	0.	0.	735.
2.00	786.	0.	0.	710.
1.50	835.	0.	0.	730.
.50	907.	0.	0.	750.
.00	906.	0.	0.	766.
-.50	903.	0.	0.	736.
-1.50	968.	0.	0.	705.
-2.50	1057.	0.	0.	712.
-3.50	1129.	0.	0.	745.
-4.50	1171.	0.	0.	776.
-5.50	1196.	0.	0.	808.
-6.50	1222.	0.	0.	839.
-7.50	1247.	0.	0.	870.
-8.50	1273.	0.	0.	901.
-9.50	1298.	32.	0.	933.
-10.50	1324.	124.	0.	964.
-11.50	1350.	197.	0.	995.
-12.00	1361.	208.	0.	1026.
-12.50	1372.	217.	0.	1041.
-13.50	1391.	239.	0.	1054.
-14.50	1410.	297.	0.	1079.
-14.51	1410.	298.	0.	1104.
-15.50	1429.	377.	0.	1104.
-16.50	1448.	419.	0.	1128.
-17.50	1467.	434.	25.	1153.
-18.50	1486.	452.	76.	1178.
-19.09	1505.	470.	113.	1203.
-20.50	1524.	488.	136.	1227.
				1252.





## LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

ELEV. (FT)	<-LEFTSIDE PRESSURES->		<---NET PRESSURES---> (SOIL PLUS WATER)		<RIGHTSIDE PRESSURES->	
	PASSIVE (PSF)	ACTIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)
11.50	.00	.00	.000	.000	.00	.00
10.50	.00	.00	62.400	62.400	.00	.00
9.50	.00	.00	124.800	124.800	.00	.00
8.50	.00	.00	187.200	187.200	.00	.00
7.50	.00	.00	249.600	249.600	.00	.00
6.50	.00	.00	312.000	312.000	.00	.00
5.50	.00	.00	374.400	374.400	.00	.00
4.50	.00	.00	436.800	436.800	.00	.00
3.50	.00	.00	499.200	499.200	.00	.00
3.00+	.00	.00	530.400	530.400	.00	.00
3.00-	760.00	.00	-229.600	1290.400	.00	760.00
2.75	749.32	.00	-203.318	1281.136	.00	735.14
2.50	738.64	.00	-177.036	1271.873	.00	710.27
2.00	786.36	.00	-193.564	1322.436	.00	729.64
1.50	834.09	.00	-210.094	1373.003	.00	749.00
.50	929.54	.00	-243.138	1474.119	.00	787.72
.00	976.94	.00	-259.345	1524.363	.00	806.76
-.50	1023.74	.00	-274.942	1573.997	.00	825.20
-1.50	1116.95	.00	-305.752	1672.636	.00	861.44
-2.50	1209.66	.00	-336.059	1771.259	.00	897.66
-.00	1286.53	.00	-350.526	1869.886	.00	933.89
-4.50	1333.17	.00	-397.168	1906.114	.00	970.11
-5.50	1363.97	.00	-427.966	1942.341	.00	1006.34
-6.50	1394.28	.00	-458.277	1978.568	.00	1042.57
-7.50	1424.83	.00	-488.832	2014.795	.00	1078.80
-8.50	1455.39	.00	-519.386	2051.023	.00	1115.02
-9.50	1485.94	.00	-549.941	2087.250	.00	1151.25
-10.50	1516.50	.00	-580.495	2123.477	.00	1187.48
-11.50	1547.05	.00	-611.050	2159.705	.00	1223.70
-12.50	1577.60	.00	-641.605	2195.932	.00	1259.93
-13.50	1608.16	.00	-672.159	2232.159	.00	1296.16
-14.50	1638.71	.00	-702.714	2268.386	.00	1332.39
-15.50	1669.27	1.59	-733.268	2303.020	.00	1368.61
-16.50	1699.82	85.56	-763.823	2255.285	.00	1404.84
-17.50	1730.38	243.91	-794.377	2133.162	.00	1441.07
-18.50	1760.93	327.84	-824.932	2085.452	.00	1477.30
-19.50	1791.49	350.60	-855.486	2098.923	.00	1513.52
-20.50	1822.04	380.20	-886.041	2105.550	.00	1549.75
-21.50	1852.60	409.80	-916.595	2112.177	.00	1585.98
-22.50	1883.15	439.40	-947.150	2118.805	.00	1622.20
-23.50	1913.70	469.00	-977.705	2125.432	.00	1658.43
-24.50	1944.26	498.60	-1008.259	2132.059	.00	1694.66
-25.50	1974.81	528.20	-1038.814	2138.686	.00	1730.89
-26.50	2005.37	557.80	-1069.368	2145.314	.00	1767.11
-27.50	2035.92	587.40	-1099.923	2151.941	.00	1803.34

PROGRAM CWALSHT-DESIGN/ANALYSIS OF ANCHORED OR CANTILEVER SHEET PILE WALLS BY CLASSICAL METHODS

DATE: 19-MAR-1998

TIME: 13.45.53

Summary of Results for Cantilever Wall Design

I.--HEADING

'ALGIERS CANAL, EE14638
'REACH 1,I WALL, NEAR FLOOD GATE, WATER EL 11.5

II.--SUMMARY

RIGHTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

Table with 2 columns: Parameter and Value. Rows include WALL BOTTOM ELEV. (FT), PENETRATION (FT), MAX. BEND. MOMENT (LB-FT), AT ELEVATION (FT), MAX. SCALED DEFL. (LB-IN3), AT ELEVATION (FT).

(NOTE: DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN IN\*\*4 TO OBTAIN DEFLECTION IN INCHES.)

PROGRAM CWALSHT-DESIGN/ANALYSIS OF ANCHORED OR CANTILEVER SHEET PILE WALLS BY CLASSICAL METHODS

DATE: 19-MAR-1998

TIME: 13.45.53

COMPLETE RESULTS FOR Cantilever Wall Design

## I.--HEADING

'ALGIERS CANAL, EE14638

'REACH 1,I WALL, NEAR FLOOD GATE, WATER EL 11.5

## II.--RESULTS

ELEVATION (FT)	BENDING MOMENT (LB-FT)	SHEAR (LB)	SCALED DEFLECTION (LB-IN3)	NET PRESSURE (PSF)
11.50	0.	0.	5.5605E+09	.00
10.50	10.	31.	5.2018E+09	62.40
9.50	83.	125.	4.8431E+09	124.80
8.50	281.	281.	4.4845E+09	187.20
7.50	666.	499.	4.1265E+09	249.60
6.50	1300.	780.	3.7697E+09	312.00
5.50	2246.	1123.	3.4151E+09	374.40
4.50	3567.	1529.	3.0645E+09	436.80
3.50	5325.	1997.	2.7201E+09	499.20
3.00	6387.	2254.	2.5512E+09	530.40
3.00	6387.	2254.	2.5512E+09	-229.60
2.75	6944.	2200.	2.4677E+09	-203.32
2.50	7487.	2153.	2.3850E+09	-177.04
2.00	8541.	2060.	2.2221E+09	-193.56
1.50	9546.	1959.	2.0628E+09	-210.09
.50	11394.	1732.	1.7571E+09	-243.14
.00	12230.	1607.	1.6114E+09	-259.34
-.50	13000.	1473.	1.4710E+09	-274.94
-1.50	14330.	1183.	1.2074E+09	-305.75
-2.50	15355.	862.	9.6842E+08	-336.06
-3.50	16047.	519.	7.5597E+08	-350.53
-4.50	16382.	145.	5.7120E+08	-397.17
-5.50	16323.	-268.	4.1468E+08	-427.97
-6.50	15837.	-711.	2.8631E+08	-458.28
-7.50	14891.	-1184.	1.8523E+08	-488.83
-8.50	13457.	-1689.	1.0982E+08	-519.39
-9.50	11504.	-2223.	5.7589E+07	-549.94
-10.50	9001.	-2788.	2.5156E+07	-580.50
-10.78	8185.	-2955.	1.8975E+07	-589.18
-11.50	5968.	-3170.	8.1947E+06	-11.56
-12.50	2927.	-2778.	1.5451E+06	795.38
-13.50	682.	-1579.	6.8294E+04	1602.32
-14.32	0.	0.	0.0000E+00	2261.76

(NOTE: DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN IN\*\*4 TO OBTAIN DEFLECTION IN INCHES.)

## III.--SOIL PRESSURES

ELEVATION (FT)	< LEFTSIDE PRESSURE (PSF) >		< RIGHTSIDE PRESSURE (PSF) >	
	PASSIVE	ACTIVE	ACTIVE	PASSIVE
11.50	0.	0.	0.	0.
10.50	0.	0.	0.	0.
9.50	0.	0.	0.	0.
8.50	0.	0.	0.	0.
7.50	0.	0.	0.	0.
6.50	0.	0.	0.	0.

5.50	0.	0.	0.	0.
4.50	0.	0.	0.	0.
3.50	0.	0.	0.	0.
3.00+	0.	0.	0.	0.
3.00-	760.	0.	0.	0.
2.75	749.	0.	0.	760.
2.50	739.	0.	0.	735.
2.00	786.	0.	0.	710.
1.50	834.	0.	0.	730.
.50	930.	0.	0.	749.
.00	977.	0.	0.	788.
-.50	1024.	0.	0.	807.
-1.50	1117.	0.	0.	825.
-2.50	1210.	0.	0.	861.
-3.50	1287.	0.	0.	898.
-4.50	1333.	0.	0.	934.
-5.50	1364.	0.	0.	970.
-6.50	1394.	0.	0.	1006.
-7.50	1425.	0.	0.	1043.
-8.50	1455.	0.	0.	1079.
-9.50	1486.	0.	0.	1115.
-10.50	1516.	0.	0.	1151.
-10.78	1525.	0.	0.	1187.
-11.50	1547.	0.	0.	1198.
-12.50	1578.	0.	0.	1224.
-13.50	1608.	0.	0.	1260.
-14.32	1639.	0.	0.	1296.
-15.50	1669.	2.	0.	1332.
				1369.







## II.--SOIL PRESSURES

RIGHTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

LEFTSIDE SOIL PRESSURES DETERMINED BY FIXED SURFACE WEDGE METHOD.

ELEV. (FT)	<-LEFTSIDE PRESSURES->		<---NET PRESSURES----> (SOIL PLUS WATER)		<RIGHTSIDE PRESSURES->	
	PASSIVE (PSF)	ACTIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)	ACTIVE (PSF)	PASSIVE (PSF)
11.50	.00	.00	.000	.000	.00	.00
10.50	.00	.00	62.400	62.400	.00	.00
9.50	.00	.00	124.800	124.800	.00	.00
8.50	.00	.00	187.200	187.200	.00	.00
7.50	.00	.00	249.600	249.600	.00	.00
6.50	.00	.00	312.000	312.000	.00	.00
5.50+	.00	.00	374.400	374.400	.00	.00
5.50-	760.00	.00	-385.600	1134.400	.00	760.00
5.00	812.50	.00	-406.900	1188.405	.00	782.81
4.50	865.00	.00	-428.200	1242.410	.00	805.61
3.50	970.00	.00	-470.800	1326.588	.00	827.39
2.50	1075.00	.00	-513.400	1351.654	.00	790.05
1.50	1181.76	.00	-557.762	1373.324	.00	749.32
.50	1262.81	.00	-576.410	1423.958	.00	737.56
.00	1270.03	.00	-552.426	1424.291	.00	706.69
- .50	1260.32	15.07	-511.521	1405.771	.00	672.04
- 1.00	1241.56	99.22	-430.360	1382.315	.00	670.33
-2.50	1242.47	201.71	-368.871	1382.208	.00	710.32
-3.50	1294.14	298.55	-358.144	1463.459	.00	826.01
-4.00	1323.68	339.31	-356.485	1535.657	.00	907.77
-4.50	1336.10	364.86	-368.905	1554.858	.00	952.51
-5.50	1345.25	400.79	-378.047	1549.856	.00	983.45
-6.50	1354.00	432.52	-386.800	1553.234	.00	1018.55
-7.50	1362.85	450.12	-395.650	1570.734	.00	1053.65
-8.50	1371.70	453.50	-404.500	1602.453	.00	1088.75
-9.50	1380.55	453.05	-413.350	1638.000	.00	1123.85
-10.50	1389.41	453.16	-422.210	1673.000	.00	1158.96
-11.50	1398.23	453.23	-426.296	1708.000	4.73	1194.03
-12.00	1401.82	452.45	-414.095	1725.500	20.53	1210.75
-12.50	1403.83	450.08	-392.361	1743.000	44.27	1225.88
-13.50	1406.21	443.71	-359.989	1778.000	79.02	1254.51
-14.50	1408.55	437.30	-335.459	1813.000	105.89	1283.10
-15.50	1410.90	430.90	-316.309	1848.000	127.39	1311.70
-16.50	1413.25	424.50	-302.928	1883.000	143.12	1340.30
-17.50	1415.60	418.10	-291.155	1918.000	157.24	1368.90
-18.50	1434.20	411.70	-295.300	1953.000	171.70	1397.50
-19.50	1462.80	405.30	-305.839	1988.000	189.76	1426.10
-20.50	1491.40	398.90	-309.500	2023.000	214.70	1454.70
-21.50	1520.00	389.16	-309.555	2061.337	243.24	1483.30
-22.50	1548.60	399.68	-309.500	2079.425	271.90	1511.90
-23.50	1577.20	531.65	-309.500	1976.050	300.50	1540.50
-24.50	1605.80	728.13	-309.500	1808.175	329.10	1569.10
-25.50	1634.40	796.69	-309.500	1768.212	357.70	1597.70





-1.78	1242.	202.	0.	710.
-3.50	1294.	299.	0.	826.

**WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF  
NEW ORLEANS, LA  
EAST OF HARVEY CANAL HURRICANE PROTECTION PROJECT  
DESIGN MEMORANDUM NO. 2  
EAST AND WEST OF ALGIERS CANAL**

**APPENDIX B**

**DESIGN CALCULATIONS**

**PUMPING STATION FLOODWALL  
CALCULATIONS**

BELLE CHASSE NO. 2.

FOR FAILURE SURFACE (B)③,

REQ'D PRESSURE = 2635 psf under intake basin area.

- THIS IS IMPOSSIBLE TO ACHIEVE WITH DL OF STRUCTURE + PILES IN TENSION -

- USE NEW T-WALL IN FRONT OF EXISTING DISCHARGE BASIN

13-782 500 SHEETS FILLER 5 SQUARE  
42-381 50 SHEETS FILLER 5 SQUARE  
42-382 100 SHEETS FILLER 5 SQUARE  
42-383 200 SHEETS FILLER 5 SQUARE  
42-384 100 SHEETS FILLER 5 SQUARE  
42-385 100 RECYCLED WHITE 5 SQUARE  
42-386 200 RECYCLED WHITE 5 SQUARE  
Make P.O. 3-4





BELLE CHASSE NO. 2 PUMPING STATION.


- ADD T-WALL TO FRONT OF STATION
- PASS DISCHARGE PIPES THROUGH T-WALL
- EXISTING DISCHARGE BASIN IS LINED W/ RIPPAP
- TOP OF BASE SLAB @ EL -5.5
- DEPTH OF BASE SLAB = 2'-6"
- HEIGHT OF STEM = 15'
- TOE OF BASE SLAB IS 50' FROM EXISTING STATION
- LENGTH OF WALL = 86'

400 SHEETS FILER 5 SQUARE  
 50 SHEETS EYE EASE 5 SQUARE  
 100 SHEETS EYE EASE 5 SQUARE  
 42-392 100 SHEETS EYE EASE 5 SQUARE  
 42-393 100 SHEETS EYE EASE 5 SQUARE  
 42-394 100 SHEETS EYE EASE 5 SQUARE  
 42-395 200 RECYCLED WHITE 5 SQUARE  
 42-396 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



P/S

F/S





# EUSTIS ENGINEERING COMPANY, INC.

Geotechnical Engineers  
Metairie, Louisiana

Page \_\_\_\_\_

Date 11/26/97

Job 14638

By TUS

Project \_\_\_\_\_

Subject \_\_\_\_\_

Checked By \_\_\_\_\_

U.S. Army Corps of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, La.

Allowable Pile Load Capacities  
T-Wall Foundation  
Belle Chasse Pump Station No. 2

Pile Type	Pile Tip Elevation	Estimated Allowable Single Pile Load Capacity in Tons	
		Factor of Safety = 2.0 Compression	Tension
14-in. square prestressed concrete	-70	18	12
	-82	30	22
6-in square, prestressed concrete	-70	21	14
	-82	34 (76)	25 (56 k)

## PRELIMINARY

Note: 1) Top of pile at el -7.5.

2) Capacity contribution to el -50 has been ignored.

11/26/97  
TUS

PCA INPJT:

10	BC#2	FRONTAL PROTECTION T-WALL							
20	PROP	4030	3201	3201	196	2	0	ALL	
30	ES		L	83	ALL				
40	PIN	ALL							
50	DLS	S	60	24	600.2	223.1	132.6	1510.0	1125.2 H 14 AL
60	ASC	S	196	457	0.8160	0.8560	2.0	0.0	ALL
70	BAT	2	ALL						
80	ANGLE	0	SET						
90	ANGLE	180	SET						
100	PILE	1							0
110		2							0
120		3							0
130		4							0
140		5							0
150		6							0
160		7							0
170		8							0
180		9							0
190		10							0
200		11							0
210		12							0
220		13							0
230		14							0
240		15							0
250		16							0
260		17							0
270		18							0
280		19							0
290		20							0
300	LOAD	1	843	0	1040	6	-6325	0	
310	LOAD	2	843	0	875	0	-5944	0	
320	LOAD	3	786	0	811	0	-6172	0	
330	LOAD	4	786	0	670	0	-5853	0	
340	LOAD	5	172	0	864	0	-1869	0	
350	LOAD	6	92	0	642	0	-892	0	
360	FOOT	1 2 3 4 5 6 7	BC2OUT						
370	PFO	ALL							
380	FPL	N							

13 SHEETS  
14 SHEETS  
15 SHEETS  
16 SHEETS  
17 SHEETS  
18 SHEETS  
19 SHEETS  
20 SHEETS  
21 SHEETS  
22 SHEETS  
23 SHEETS  
24 SHEETS  
25 SHEETS  
26 SHEETS  
27 SHEETS  
28 SHEETS  
29 SHEETS  
30 SHEETS  
31 SHEETS  
32 SHEETS  
33 SHEETS  
34 SHEETS  
35 SHEETS  
36 SHEETS  
37 SHEETS  
38 SHEETS  
39 SHEETS  
40 SHEETS  
41 SHEETS  
42 SHEETS  
43 SHEETS  
44 SHEETS  
45 SHEETS  
46 SHEETS  
47 SHEETS  
48 SHEETS  
49 SHEETS  
50 SHEETS  
51 SHEETS  
52 SHEETS  
53 SHEETS  
54 SHEETS  
55 SHEETS  
56 SHEETS  
57 SHEETS  
58 SHEETS  
59 SHEETS  
60 SHEETS  
61 SHEETS  
62 SHEETS  
63 SHEETS  
64 SHEETS  
65 SHEETS  
66 SHEETS  
67 SHEETS  
68 SHEETS  
69 SHEETS  
70 SHEETS  
71 SHEETS  
72 SHEETS  
73 SHEETS  
74 SHEETS  
75 SHEETS  
76 SHEETS  
77 SHEETS  
78 SHEETS  
79 SHEETS  
80 SHEETS  
81 SHEETS  
82 SHEETS  
83 SHEETS  
84 SHEETS  
85 SHEETS  
86 SHEETS  
87 SHEETS  
88 SHEETS  
89 SHEETS  
90 SHEETS  
91 SHEETS  
92 SHEETS  
93 SHEETS  
94 SHEETS  
95 SHEETS  
96 SHEETS  
97 SHEETS  
98 SHEETS  
99 SHEETS  
100 SHEETS




13,787 50 SHEETS PER LHM, 5 SQUARE  
 42,381 50 SHEETS FY LASH, 5 SQUARE  
 42,382 100 SHEETS FY LASH, 5 SQUARE  
 42,383 100 SHEETS UY LASH, 5 SQUARE  
 42,384 200 SHEETS UY LASH, 5 SQUARE  
 42,385 200 SHEETS UY LASH, 5 SQUARE  
 42,386 200 SHEETS UY LASH, 5 SQUARE  
 42,387 200 SHEETS UY LASH, 5 SQUARE  
 42,388 200 SHEETS UY LASH, 5 SQUARE  
 42,389 200 SHEETS UY LASH, 5 SQUARE  
 42,390 200 SHEETS UY LASH, 5 SQUARE  
 42,391 200 SHEETS UY LASH, 5 SQUARE  
 42,392 200 SHEETS UY LASH, 5 SQUARE  
 42,393 200 SHEETS UY LASH, 5 SQUARE  
 42,394 200 SHEETS UY LASH, 5 SQUARE  
 42,395 200 SHEETS UY LASH, 5 SQUARE  
 42,396 200 SHEETS UY LASH, 5 SQUARE  
 42,397 200 SHEETS UY LASH, 5 SQUARE  
 42,398 200 SHEETS UY LASH, 5 SQUARE  
 42,399 200 SHEETS UY LASH, 5 SQUARE  
 42,400 200 SHEETS UY LASH, 5 SQUARE  
 Made in U.S.A.



F/S

F/S

Pressure diagram



U.S ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL  
 HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA

MODULUS OF HORIZONTAL SUBGRADE REACTION  
 REACH 3

ELEVATION IN FEET NGVD	$\frac{K_h \times B}{DC}$
10 to 0	169
0 to -19	155
-19 to -40	167
-40 to -45	178
-45 to -50	222
-56 to -67	311

- Where:
- $K_h$  = Modulus of horizontal subgrade reaction (lbs/in.<sup>3</sup>)
  - B = Diameter of pile (inches)
  - C = Reduction factor for cyclic loading
    - C = 0.5 for cyclic loading
    - C = 1.0 for initial loading
  - D = Reduction factor for effect of group action

D	PILE SPACING IN DIRECTION OF LOADING
1.0	8B
0.85	7B
0.7	6B
0.55	5B
0.40	4B
0.25	3B

## T-WALL LOADING CASES:

CASE I: STATIC WATER PRESSURE TO SWL, NO WIND, IMPERVIOUS SHEET PILE CUTOFF (100% FORCES)

CASE II: STATIC WATER PRESSURE TO SWL, NO WIND, PERVIOUS SHEET PILE CUTOFF (100% FORCES)

CASE III: STATIC WATER PRESSURE TO SWL+2', NO WIND, IMPERVIOUS SHEET PILE CUTOFF (75% FORCES)

CASE IV: STATIC WATER PRESSURE TO SWL+2', NO WIND, PERVIOUS SHEET PILE CUTOFF (75% FORCES)

CASE V: WATER @ LOW WATER LEVEL, NO WIND (100% FORCES)

CASE VI: WATER @ LOW WATER LEVEL, WIND FROM P/S (75% FORCES)

REGISTERED PROFESSIONAL ENGINEER  
STATE OF TEXAS  
NO. 10423  
EXPIRES 12/31/00  
BRUCE L. HILL, M.D.  
11/17/77



DEAD LOADS:

STEM:  $(15' \times 12') \times (.150 \text{ k/cf}) =$

$\frac{5.1}{4.5} \text{ k/ft}$

BASE:  $(10' \times 2.5') \times (.150) =$

$\frac{4.31}{5.65} \text{ k/ft}$

WATER:

@ SWL:  $(13' \times 6') \times (.064) =$

$\frac{7.2}{4.87} \text{ k/ft}$


@ SWL + 2':  $(17' \times 6') \times (.064) =$

$\frac{8.16}{5.62} \text{ k/ft}$

@ Low Water:  $(5.5' \times 6') \times (.064) =$

$\frac{2.64}{2.06} \text{ k/ft}$

WATER LOADS:



@ SWL:  $p = (13.5') \times (.064) = 1.12$   
 $0.97 \text{ k/ft}^2$

@ SWL + 2':  $p = (17.5') \times (.064) = 1.25$   
 $1.09 \text{ k/ft}^2$

@ Low Water:  $p = (2') \times (.064) = 0.51$   
 $0.50 \text{ k/ft}^2$

WIND LOADS:

FROM PROTECTED SIDE:

WIND ABOVE EL. 0:  $(50 \text{ psf}) \times (9.5') = 0.575$   
 $0.475 \text{ k/ft}$

13 SHEETS  
 14 SHEETS  
 15 SHEETS  
 16 SHEETS  
 17 SHEETS  
 18 SHEETS  
 19 SHEETS  
 20 SHEETS  
 21 SHEETS  
 22 SHEETS  
 23 SHEETS  
 24 SHEETS  
 25 SHEETS  
 26 SHEETS  
 27 SHEETS  
 28 SHEETS  
 29 SHEETS  
 30 SHEETS  
 31 SHEETS  
 32 SHEETS  
 33 SHEETS  
 34 SHEETS  
 35 SHEETS  
 36 SHEETS  
 37 SHEETS  
 38 SHEETS  
 39 SHEETS  
 40 SHEETS  
 41 SHEETS  
 42 SHEETS  
 43 SHEETS  
 44 SHEETS  
 45 SHEETS  
 46 SHEETS  
 47 SHEETS  
 48 SHEETS  
 49 SHEETS  
 50 SHEETS  
 51 SHEETS  
 52 SHEETS  
 53 SHEETS  
 54 SHEETS  
 55 SHEETS  
 56 SHEETS  
 57 SHEETS  
 58 SHEETS  
 59 SHEETS  
 60 SHEETS  
 61 SHEETS  
 62 SHEETS  
 63 SHEETS  
 64 SHEETS  
 65 SHEETS  
 66 SHEETS  
 67 SHEETS  
 68 SHEETS  
 69 SHEETS  
 70 SHEETS  
 71 SHEETS  
 72 SHEETS  
 73 SHEETS  
 74 SHEETS  
 75 SHEETS  
 76 SHEETS  
 77 SHEETS  
 78 SHEETS  
 79 SHEETS  
 80 SHEETS  
 81 SHEETS  
 82 SHEETS  
 83 SHEETS  
 84 SHEETS  
 85 SHEETS  
 86 SHEETS  
 87 SHEETS  
 88 SHEETS  
 89 SHEETS  
 90 SHEETS  
 91 SHEETS  
 92 SHEETS  
 93 SHEETS  
 94 SHEETS  
 95 SHEETS  
 96 SHEETS  
 97 SHEETS  
 98 SHEETS  
 99 SHEETS  
 100 SHEETS



T-WALL FORCE TABULATION

↑

No.	DESCRIPTION	FORCES (KIPS)			LEVER ARM (FT)			MOMENTS (FT.K)		
		F <sub>x</sub>	F <sub>y</sub>	F <sub>z</sub>	x	y	z	M <sub>xx</sub>	M <sub>yy</sub>	M <sub>zz</sub>
I	DEAD LOADS									
	(a) STEM			5.1	+2.75				-14.02	
	(b) BASE			4.31	0'				-0	
	(c) SWL			7.2	-2'				+14.4	
	(d) SWL 2'			8.16	-2'				+16.32	
	(e) LOW WATER			2.64	-2'				+5.28	
II	WATER LOADS									
	(a) SWL									
	(2)(1.12)(17.5)	9.6					-5.83		-57.13	
	buoyancy:									
	imp: (1.12)(4)			-4.48	-3.75				-16.8	
	per: (2)(1.12)(11.5)			-6.44	-1.92				-12.36	
	(b) SWL 12'									
	(2)(1.25)(19.5)	12.19					-6.5		-79.24	
	buoyancy:									
	imp: (1.25)(4)			-5.0	-3.75				-18.75	
	per: (2)(1.25)(11.5)			-7.19	-1.92				-13.80	
	(c) Low Water									
	(2)(0.51)(8)	2.0					-2.67		-5.34	
	buoyancy:									
	imp: (0.51)(4)			-2.04	-3.75				-7.65	
	per: 2(0.51)(11.5)			-2.93	-1.92				-5.62	
III	WIND									
	(a) from P/S	-0.575					-12.75		+7.91	
IV	LATERAL SOIL PRESSURE									
	ECCS 2' Fix (ANCHOR FORCE, FROM EUSTIS)	-4.6					0.0			
	Shield Pipe Pressure (from EUSTIS)	9.32					+26.5		+246.98	
		-3.84					+39.5		-151.68	
		-0.33							-14.07	
		5.15					+42.5		+81.23	

50 SHEETS FILLER 3 SQUARE  
 50 SHEETS FILLER 3 SQUARE  
 50 SHEETS FILLER 3 SQUARE  
 100 SHEETS FILLER 3 SQUARE  
 100 SHEETS FILLER 3 SQUARE  
 200 SHEETS FILLER 3 SQUARE  
 42,389 100 RECYCLED WHITE 3 SQUARE  
 42,389 200 RECYCLED WHITE 3 SQUARE  
 Made in U.S.A.





## SOIL CONSTANT:

- use soil constant below el. -50 H.G. 1.D. :

$$\frac{K_h \times B}{DC} = 311$$

$$K_h \times B = ES$$

$$C = 1.0$$

D = Reduction for group action.

Pile Spacing = 9'

$$\frac{9 \times 12}{14} = 7.7$$

$$D = .85 + 0.7(0.15) \\ = 0.96$$

$$ES = 311(1.0)(.96) \\ = 298.56 \text{ psi} \\ = 0.298 \text{ ksi}$$

12 IN. 50 SHEETS PER EA. 5 SQUARE  
12 IN. 50 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
42 IN. 100 SHEETS PER EA. 5 SQUARE  
MADE IN U.S.A.

National Brand

LOAD COMBINATIONS

LOADING CASE	DESCRIPTION	FORCES		MOMENTS	
		F <sub>x</sub>	F <sub>z</sub>	M <sub>xy</sub>	
I	DL, SWL, IMP 100%	DL		+16.61	+0.38
		SWL	+9.8		-57.13
		IMP		-4.48	-16.80
		TOTAL	+9.8	+12.13	-73.55
	FOR 86':	+842.8	+1043.18	-6325.3	
II	DL, SWL, PER 100%	DL		+16.61	+0.38
		SWL	+9.8		-57.13
		PER.		-6.44	-12.30
		TOTAL	+9.8	+10.17	-69.11
	FOR 86':	+842.8	+874.62	-5943.46	
III	DL, SWL+2', IMP 75%	DL		+17.57	+2.30
		SWL+2'	+12.19		-79.24
		IMP		-5.0	-18.75
		TOTAL	+12.19	+12.57	-95.69
	75% TOTAL	+9.14	+9.43	-71.77	
	FOR 86':	+786.04	+810.98	-6172.22	
IV	DL, SWL+2', PER. 75%	DL		+17.57	+2.30
		SWL+2'	+12.19		-79.24
		PER.		-7.19	-13.80
		TOTAL	+12.19	+10.38	-90.74
	75% TOTAL	+9.14	+7.79	-68.06	
	FOR 86':	+786.04	+669.94	-5853.16	
V	DL, LOW WATER, IMP. 100%	DL		+12.05	-8.74
		LW	+2.0		-5.34
		IMP		-2.0	-7.65
	TOTAL	+2.0	+10.05	-21.73	
	FOR 86':	+172	+864.3	-1868.78	
VI	DL, LW, IMP, WIND 75%	DL		+12.05	-8.74
		LW	+2.0		-5.34
		IMP		-2.0	-7.65
		WIND	-0.57		+7.91
	TOTAL	+1.42	+10.05	-13.82	
	75% TOTAL	+1.07	+7.54	-10.37	
	FOR 86':	+92.02	+648.44	-891.82	


13-782 500 SHEETS, 11 1/2" x 17" SQUARE  
 42-981 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-982 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-983 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-984 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-985 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-986 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-987 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-988 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-989 50 SHEETS, 11 1/2" x 17" SQUARE  
 42-990 50 SHEETS, 11 1/2" x 17" SQUARE  
 MADE IN U.S.A.



PILE LAYOUT

F/S

F/S



42 287 500 WHITE PILLS 5 SQUARE  
 42 281 500 WHITE P/L 5 SQUARE  
 42 282 1000 WHITE P/L 5 SQUARE  
 42 283 1000 WHITE P/L 5 SQUARE  
 42 284 1000 WHITE P/L 5 SQUARE  
 42 285 1000 WHITE P/L 5 SQUARE  
 42 286 1000 WHITE P/L 5 SQUARE  
 42 288 1000 WHITE P/L 5 SQUARE  
 42 289 1000 WHITE P/L 5 SQUARE  
 42 290 1000 WHITE P/L 5 SQUARE  
 42 291 1000 WHITE P/L 5 SQUARE  
 42 292 1000 WHITE P/L 5 SQUARE  
 42 293 1000 WHITE P/L 5 SQUARE  
 42 294 1000 WHITE P/L 5 SQUARE  
 42 295 1000 WHITE P/L 5 SQUARE  
 42 296 1000 WHITE P/L 5 SQUARE  
 42 297 1000 WHITE P/L 5 SQUARE  
 42 298 1000 WHITE P/L 5 SQUARE  
 42 299 1000 WHITE P/L 5 SQUARE  
 42 300 1000 WHITE P/L 5 SQUARE  
 Made in U.S.A.




PILE LAYOUT

P/S

P/S

19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100  
 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200  
 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300  
 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400  
 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500  
 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600  
 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700  
 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800  
 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900  
 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000



41.25  
 38.5  
 35.75  
 23  
 30.25  
 27.5  
 24.75  
 22  
 19.25  
 16.5  
 13.75  
 11.0  
 8.25  
 5.5  
 2.75  
 0  
 39  
 38  
 37  
 36  
 35  
 34  
 33  
 32

1.75  
 5.5  
 7.5  
 4.25  
 10.75  
 4.25

1010	BELLE CHASSE NO. 2 FRONTAL PROTECTION T-WALL
1020	PROP 4030 3201 3201 196 2 0 ALL
1030	SOIL ES 0.298 LEN 83 0 ALL
1040	PIN ALL
1050	DLS S 67 49 600.2 223.1 1326 1510 1166.8 H 14 ALL
1060	ASC S 196 457 0.816 0.856 2 0 ALL
1070	BATTER 2 ALL
1080	ANGLE 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 12 13 14 15 16
1085	ANGLE 0 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
1090	ANGLE 180 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47
1100	PILE 1 4.25 -41.25 0
1105	PILE 2 4.25 -35.75 0
1110	PILE 3 4.25 -30.25 0
1115	PILE 4 4.25 -24.75 0
1120	PILE 5 4.25 -19.25 0
1125	PILE 6 4.25 -13.75 0
1130	PILE 7 4.25 -8.25 0
1135	PILE 8 4.25 8.25 0
1140	PILE 9 4.25 13.75 0
1145	PILE 10 4.25 19.25 0
1150	PILE 11 4.25 24.75 0
1155	PILE 12 4.25 30.25 0
1160	PILE 13 4.25 35.75 0
1161	PILE 14 4.25 41.25 0
1162	PILE 15 4.25 -2.75 0
1163	PILE 16 4.25 2.75 0
1164	PILE 17 0.25 -38.5 0
1165	PILE 18 0.25 -33.0 0
1166	PILE 19 0.25 -27.5 0
1167	PILE 20 0.25 -22.0 0
1168	PILE 21 0.25 -16.5 0
1169	PILE 22 0.25 -11.0 0
1170	PILE 23 0.25 -5.5 0
1171	PILE 24 0.25 0 0
1172	PILE 25 0.25 5.5 0
1173	PILE 26 0.25 11.0 0
1174	PILE 27 0.25 16.5 0
1175	PILE 28 0.25 22.0 0
1176	PILE 29 0.25 27.5 0
1177	PILE 30 0.25 33.0 0
1178	PILE 31 0.25 38.5 0
1179	PILE 32 -4.25 -41.25 0
1180	PILE 33 -4.25 -35.75 0
1181	PILE 34 -4.25 -30.25 0
1182	PILE 35 -4.25 -24.75 0
1183	PILE 36 -4.25 -19.25 0
1184	PILE 37 -4.25 -13.75 0
1185	PILE 38 -4.25 -8.25 0
1186	PILE 39 -4.25 -2.75 0
1187	PILE 40 -4.25 2.75 0
1188	PILE 41 -4.25 8.75 0
1188	PILE 42 -4.25 13.75 0
1188	PILE 43 -4.25 19.25 0
1188	PILE 44 -4.25 24.75 0
1188	PILE 45 -4.25 30.25 0
1188	PILE 46 -4.25 35.75 0
1188	PILE 47 -4.25 41.25 0
1300	LOAD 1 1239 0 1040 0 -6325 0
1310	LOAD 2 1239 0 875 0 -5944 0
1320	LOAD 3 1083 0 811 0 -6172 0

*-have Tom Strandam do capacities for 87 NSVD. Pile tip*

1330	LOAD	4	1083	0	670	0	-5853	0
1340	LOAD	5	588	0	864	0	-1869	0
1350	LOAD	6	389	0	648	0	-892	0
1360	FOUT	1	2	3	4	5	6	7 BC2OUT
1370	PFO ALL							
1380	FPL N							

\*\*\*\*\*  
 \* CORPS PROGRAM # X0080 \* CPGA - CASE FILE GROUP ANALYSIS PROGRAM  
 \* VERSION NUMBER # 86/09/02-A \* RUN DATE 12-11-97 RUN TIME 14:12:21  
 \*\*\*\*\*

BELLE CHASSE NO. 2 FRONTAL PROTECTION T-WALL

THERE ARE 47 PILES AND  
 6 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = {  $\begin{matrix} \text{---} \\ \text{X} \\ \text{---} \\ -4.25 \\ 4.25 \end{matrix}$  ;  $\begin{matrix} \text{---} \\ \text{Y} \\ \text{---} \\ -41.25 \\ 41.25 \end{matrix}$  ;  $\begin{matrix} \text{---} \\ \text{Z} \\ \text{---} \\ .00 \\ .00 \end{matrix}$  }

\*\*\*\*\*

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40300E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.29800E+00	L	.83000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	4.25	-41.25	.00	2.00	.00	83.00	P
2	4.25	-35.75	.00	2.00	.00	83.00	P
3	4.25	-30.25	.00	2.00	.00	83.00	P
4	4.25	-24.75	.00	2.00	.00	83.00	P
5	4.25	-19.25	.00	2.00	.00	83.00	P
6	4.25	-13.75	.00	2.00	.00	83.00	P

7	4.225	-8.225	.00	2.00	.00	83.00	
8	4.225	8.225	.00	2.00	.00	83.00	
9	4.225	13.75	.00	2.00	.00	83.00	
10	4.225	19.25	.00	2.00	.00	83.00	
11	4.225	24.75	.00	2.00	.00	83.00	
12	4.225	30.25	.00	2.00	.00	83.00	
13	4.225	35.75	.00	2.00	.00	83.00	
14	4.225	41.25	.00	2.00	.00	83.00	
15	4.225	-2.75	.00	2.00	.00	83.00	
16	4.225	2.75	.00	2.00	.00	83.00	
17	.225	-38.50	.00	2.00	.00	83.00	
18	.225	-33.00	.00	2.00	.00	83.00	
19	.225	-27.50	.00	2.00	.00	83.00	
20	.225	-22.00	.00	2.00	.00	83.00	
21	.225	-16.50	.00	2.00	.00	83.00	
22	.225	-11.00	.00	2.00	.00	83.00	
23	.225	-5.50	.00	2.00	.00	83.00	
24	.225	.00	.00	2.00	.00	83.00	
25	.225	5.50	.00	2.00	.00	83.00	
26	.225	11.00	.00	2.00	.00	83.00	
27	.225	16.50	.00	2.00	.00	83.00	
28	.225	22.00	.00	2.00	.00	83.00	
29	.225	27.50	.00	2.00	.00	83.00	
30	.225	33.00	.00	2.00	.00	83.00	
31	.225	38.50	.00	2.00	.00	83.00	
32	-4.225	-41.25	.00	2.00	180.00	83.00	
33	-4.225	-35.75	.00	2.00	180.00	83.00	
34	-4.225	-30.25	.00	2.00	180.00	83.00	
35	-4.225	-24.75	.00	2.00	180.00	83.00	
36	-4.225	-19.25	.00	2.00	180.00	83.00	
37	-4.225	-13.75	.00	2.00	180.00	83.00	
38	-4.225	-8.25	.00	2.00	180.00	83.00	
39	-4.225	-2.75	.00	2.00	180.00	83.00	
40	-4.225	2.75	.00	2.00	180.00	83.00	
41	-4.225	8.25	.00	2.00	180.00	83.00	
42	-4.225	13.75	.00	2.00	180.00	83.00	
43	-4.225	19.25	.00	2.00	180.00	83.00	
44	-4.225	24.75	.00	2.00	180.00	83.00	
45	-4.225	30.25	.00	2.00	180.00	83.00	
46	-4.225	35.75	.00	2.00	180.00	83.00	
47	-4.225	41.25	.00	2.00	180.00	83.00	

3901.00

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	1239.0	.0	1040.0	.0	-6325.0	.0
2	1239.0	.0	875.0	.0	-5944.0	.0
3	1083.0	.0	811.0	.0	-6172.0	.0
4	1083.0	.0	670.0	.0	-5853.0	.0
5	588.0	.0	864.0	.0	-1869.0	.0
6	389.0	.0	648.0	.0	-892.0	.0



\*\*\*\*\*

ORIGINAL PILE GROUP STIFFNESS MATRIX

.15552E+05	.43894E-03	.94141E+04	-.37659E+04	-.10525E+07	-.19854E+04
.43894E-03	.80333E+03	-.87787E-03	-.32919E-03	-.44771E-01	.76915E+03
.94141E+04	-.87787E-03	.59798E+05	.76337E+04	-.57253E+05	.37659E+04
-.37659E+04	-.32920E-03	.76337E+04	.53220E+10	.38932E+06	-.76471E+09
-.10525E+07	-.44771E-01	-.57253E+05	.38931E+06	.10607E+09	.19205E+06
-.19855E+04	.76915E+03	.37659E+04	-.76471E+09	.19205E+06	.13856E+10

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	16.

\*\*\*\*\*

PILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.8897E-01	-.1596E-06	.3548E-02	.6414E-07	.1691E-03	.1298E-06
2	.1072E+00	-.1764E-06	-.1877E-02	.7063E-07	.3906E-03	.1436E-06
3	.6158E-01	-.1531E-06	.3786E-02	.6221E-07	-.8515E-04	.1241E-06
4	.7699E-01	-.1674E-06	-.8199E-03	.6777E-07	.1014E-03	.1359E-06
5	.6301E-01	-.2982E-07	.4928E-02	.1065E-07	.4164E-03	.2505E-07
6	.4942E-01	-.9800E-08	.3432E-02	.2676E-08	.3913E-03	.8728E-08

\*\*\*\*\*

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3\*EMIN) FOR CONCRETE PILES  
 B INDICATES BUCKLING CONTROLS

LOAD CASE -	1										
PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99	#
2	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99	#

3	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
4	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
5	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
6	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
7	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
8	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
9	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
10	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
11	1.4	.0	55.9	.0	-51.6	.0	.83	.34	1.25	.99
12	1.4	.0	55.9	.0	-51.6	.0	.83	.34	1.25	.99
13	1.4	.0	55.9	.0	-51.6	.0	.83	.34	1.25	.99
14	1.4	.0	55.9	.0	-51.6	.0	.83	.34	1.25	.99
15	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
16	1.4	.0	55.9	.0	-51.7	.0	.83	.34	1.25	.99
17	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
18	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
19	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
20	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
21	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
22	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
23	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
24	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
25	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
26	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
27	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
28	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
29	1.3	.0	67.4	.0	-49.4	.0	1.01	.36	1.31	1.05
30	1.3	.0	67.4	.0	-49.3	.0	1.01	.36	1.31	1.05
31	1.3	.0	67.4	.0	-49.3	.0	1.01	.36	1.31	1.05
32	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
33	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
34	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
35	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
36	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
37	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
38	1.5	.0	-45.9	.0	53.7	.0	.94	.68	.74	.46
39	1.5	.0	-45.8	.0	53.7	.0	.94	.68	.74	.46
40	1.5	.0	-45.8	.0	53.7	.0	.94	.68	.74	.46
41	1.5	.0	-45.8	.0	53.7	.0	.94	.68	.74	.46
42	1.5	.0	-45.8	.0	53.7	.0	.93	.68	.74	.46
43	1.5	.0	-45.8	.0	53.7	.0	.93	.68	.74	.46
44	1.5	.0	-45.8	.0	53.7	.0	.93	.68	.74	.46
45	1.5	.0	-45.8	.0	53.7	.0	.93	.68	.74	.47
46	1.5	.0	-45.8	.0	53.7	.0	.93	.68	.74	.47
47	1.5	.0	-45.7	.0	53.6	.0	.93	.68	.74	.47

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	1.8	.0	45.1	.0	-66.8	.0	.67	.33	1.23	.90
2	1.8	.0	45.1	.0	-66.8	.0	.67	.33	1.23	.90
3	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
4	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
5	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
6	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
7	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
8	1.8	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90

9	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
10	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
11	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
12	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
13	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
14	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
15	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
16	1.88	.0	45.1	.0	-66.7	.0	.67	.33	1.23	.90
17	1.7	.0	71.7	.0	-61.5	.0	1.07	.37	1.36	1.05
18	1.7	.0	71.7	.0	-61.5	.0	1.07	.37	1.36	1.05
19	1.7	.0	71.7	.0	-61.5	.0	1.07	.37	1.36	1.05
20	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
21	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
22	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
23	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
24	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
25	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
26	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
27	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
28	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
29	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
30	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
31	1.7	.0	71.7	.0	-61.4	.0	1.07	.37	1.36	1.05
32	1.88	.0	50.6	.0	65.7	.0	1.03	.76	.74	.41
33	1.88	.0	50.6	.0	65.7	.0	1.03	.76	.74	.41
34	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
35	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
36	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
37	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
38	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
39	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
40	1.88	.0	50.5	.0	65.7	.0	1.03	.76	.74	.41
41	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.41
42	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42
43	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42
44	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42
45	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42
46	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42
47	1.88	.0	50.4	.0	65.6	.0	1.03	.76	.74	.42

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
2	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
3	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
4	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
5	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
6	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
7	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
8	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
9	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
10	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
11	.9	.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
12	.9	.0	55.2	.0	-32.4	.0	.82	.34	1.21	1.03
13	.9	.0	55.2	.0	-32.4	.0	.82	.34	1.21	1.03
14	.9	.0	55.2	.0	-32.4	.0	.82	.34	1.21	1.03

15		.0	55.2	.0	-32.5	.0	.82	.34	1.21	1.03
16	.99	.00	55.2	.00	-32.5	.00	.82	.34	1.21	1.03
17	.99	.00	49.4	.00	-33.7	.00	.74	.33	1.18	.99
18	.99	.00	49.4	.00	-33.7	.00	.74	.33	1.18	.99
19	.99	.00	49.4	.00	-33.7	.00	.74	.33	1.18	.99
20	.99	.00	49.4	.00	-33.7	.00	.74	.33	1.18	.99
21	.99	.00	49.4	.00	-33.7	.00	.74	.33	1.18	.99
22	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
23	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
24	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
25	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
26	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
27	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
28	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
29	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
30	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
31	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
32	.99	.00	49.4	.00	-33.6	.00	.74	.33	1.18	.99
33	.99	.00	-44.6	.00	34.6	.00	.91	.62	.70	.51
34	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
35	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
36	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
37	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
38	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
39	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
40	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
41	.99	.00	-44.5	.00	34.6	.00	.91	.62	.70	.51
42	.99	.00	-44.4	.00	34.6	.00	.91	.62	.70	.51
43	.99	.00	-44.4	.00	34.6	.00	.91	.62	.71	.51
44	.99	.00	-44.4	.00	34.6	.00	.91	.62	.71	.51
45	.99	.00	-44.4	.00	34.6	.00	.91	.62	.71	.51
46	.99	.00	-44.4	.00	34.6	.00	.91	.62	.71	.51
47	.99	.00	-44.4	.00	34.6	.00	.91	.62	.71	.51

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
2	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
3	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
4	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
5	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
6	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
7	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
8	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
9	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
10	1.2	.0	46.1	.0	-45.1	.0	.69	.32	1.19	.95
11	1.2	.0	46.1	.0	-45.1	.0	.69	.32	1.19	.95
12	1.2	.0	46.1	.0	-45.1	.0	.69	.32	1.19	.95
13	1.2	.0	46.1	.0	-45.1	.0	.69	.32	1.19	.95
14	1.2	.0	46.1	.0	-45.1	.0	.69	.32	1.19	.95
15	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
16	1.2	.0	46.1	.0	-45.2	.0	.69	.32	1.19	.95
17	1.2	.0	53.0	.0	-43.8	.0	.79	.34	1.22	.99
18	1.2	.0	53.0	.0	-43.8	.0	.79	.34	1.22	.99
19	1.2	.0	53.0	.0	-43.8	.0	.79	.34	1.22	.99
20	1.2	.0	53.0	.0	-43.8	.0	.79	.34	1.22	.99

21	1.1.2	.0	53.0	.0	-43.8	.0	.79	.34	1.22	.99
22	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
23	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
24	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
25	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
26	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
27	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
28	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
29	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
30	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
31	1.1.2	.00	53.0	.00	-43.8	.00	.79	.34	1.22	.99
32	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
33	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
34	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
35	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
36	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
37	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
38	-1.1.2	.00	-48.5	.00	44.7	.00	.99	.69	.71	.47
39	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
40	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
41	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
42	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
43	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
44	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
45	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
46	-1.1.2	.00	-48.4	.00	44.7	.00	.99	.69	.71	.47
47	-1.1.2	.00	-48.3	.00	44.7	.00	.99	.69	.71	.47

LOAD CASE - 5

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	1.1	.0	21.6	.0	-40.2	.0	.32	.29	1.05	.84
2	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
3	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
4	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
5	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
6	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
7	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
8	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
9	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
10	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
11	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
12	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
13	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
14	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
15	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
16	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
17	1.1	.00	21.6	.00	-40.2	.00	.32	.29	1.05	.84
18	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
19	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
20	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
21	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
22	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
23	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
24	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
25	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00
26	.99	.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00

27		.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00	#
28		.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00	#
29		.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00	#
30		.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00	#
31		.00	49.9	.00	-34.5	.00	.74	.33	1.19	1.00	#
32	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
33	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
34	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
35	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
36	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
37	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
38	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
39	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
40	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
41	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
42	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
43	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
44	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
45	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
46	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#
47	-1.2	.00	-7.6	.00	43.0	.00	.15	.19	.91	.68	#

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
2	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
3	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
4	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
5	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
6	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
7	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
8	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
9	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
10	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
11	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
12	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
13	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
14	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
15	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
16	.9	.00	11.6	.00	-32.6	.00	.17	.28	.99	.80	
17	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
18	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
19	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
20	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
21	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
22	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
23	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
24	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
25	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
26	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
27	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
28	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
29	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
30	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
31	.7	.00	38.3	.00	-27.3	.00	.57	.31	1.11	.95	#
32	.9	.00	11.6	.00	34.5	.00	.04	.10	.92	.73	#

33	1	.0	1	.0	34.5	.0	.04	.10	.92	.73
34	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
35	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
36	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
37	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
38	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
39	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
40	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
41	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
42	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
43	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
44	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
45	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
46	1	.00	1	.00	34.5	.0	.04	.10	.92	.73
47	1	.00	1	.00	34.5	.0	.04	.10	.92	.73

\*\*\*\*\*

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	26.3	.0	49.4	.0	.0	.0
2	26.3	.00	49.4	.00	.00	.00
3	26.3	.00	49.4	.00	.00	.00
4	26.3	.00	49.4	.00	.00	.00
5	26.3	.00	49.4	.00	.00	.00
6	26.3	.00	49.4	.00	.00	.00
7	26.3	.00	49.4	.00	.00	.00
8	26.3	.00	49.4	.00	.00	.00
9	26.3	.00	49.4	.00	.00	.00
10	26.3	.00	49.4	.00	.00	.00
11	26.3	.00	49.4	.00	.00	.00
12	26.3	.00	49.4	.00	.00	.00
13	26.3	.00	49.4	.00	.00	.00
14	26.3	.00	49.4	.00	.00	.00
15	26.3	.00	49.4	.00	.00	.00
16	26.3	.00	49.4	.00	.00	.00
17	31.3	.00	59.7	.00	.00	.00
18	31.3	.00	59.7	.00	.00	.00
19	31.3	.00	59.7	.00	.00	.00
20	31.3	.00	59.7	.00	.00	.00
21	31.3	.00	59.7	.00	.00	.00
22	31.3	.00	59.7	.00	.00	.00
23	31.3	.00	59.7	.00	.00	.00
24	31.3	.00	59.7	.00	.00	.00
25	31.3	.00	59.7	.00	.00	.00
26	31.3	.00	59.7	.00	.00	.00
27	31.3	.00	59.7	.00	.00	.00
28	31.3	.00	59.7	.00	.00	.00
29	31.3	.00	59.7	.00	.00	.00
30	31.3	.00	59.7	.00	.00	.00
31	31.3	.00	59.7	.00	.00	.00
32	21.8	.0	-40.4	.0	.0	.0

33	21.8	.0	-40.4	.0	.0	.0
34	21.8	.00	-40.4	.00	.00	.00
35	21.8	.00	-40.4	.00	.00	.00
36	21.8	.00	-40.4	.00	.00	.00
37	21.8	.00	-40.4	.00	.00	.00
38	21.8	.00	-40.4	.00	.00	.00
39	21.8	.00	-40.4	.00	.00	.00
40	21.8	.00	-40.3	.00	.00	.00
41	21.8	.00	-40.3	.00	.00	.00
42	21.8	.00	-40.3	.00	.00	.00
43	21.8	.00	-40.3	.00	.00	.00
44	21.8	.00	-40.3	.00	.00	.00
45	21.8	.00	-40.3	.00	.00	.00
46	21.8	.00	-40.3	.00	.00	.00
47	21.8	.0	-40.3	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	21.8	.0	39.6	.0	.0	.0
2	21.8	.00	39.6	.00	.00	.00
3	21.8	.00	39.6	.00	.00	.00
4	21.8	.00	39.6	.00	.00	.00
5	21.8	.00	39.6	.00	.00	.00
6	21.8	.00	39.6	.00	.00	.00
7	21.8	.00	39.6	.00	.00	.00
8	21.8	.00	39.6	.00	.00	.00
9	21.8	.00	39.6	.00	.00	.00
10	21.8	.00	39.6	.00	.00	.00
11	21.8	.00	39.6	.00	.00	.00
12	21.8	.00	39.6	.00	.00	.00
13	21.8	.00	39.6	.00	.00	.00
14	21.8	.00	39.6	.00	.00	.00
15	21.8	.00	39.6	.00	.00	.00
16	21.8	.00	39.6	.00	.00	.00
17	33.6	.00	63.4	.00	.00	.00
18	33.6	.00	63.4	.00	.00	.00
19	33.6	.00	63.4	.00	.00	.00
20	33.6	.00	63.4	.00	.00	.00
21	33.6	.00	63.4	.00	.00	.00
22	33.6	.00	63.4	.00	.00	.00
23	33.6	.00	63.4	.00	.00	.00
24	33.6	.00	63.4	.00	.00	.00
25	33.6	.00	63.4	.00	.00	.00
26	33.6	.00	63.4	.00	.00	.00
27	33.6	.00	63.4	.00	.00	.00
28	33.6	.00	63.4	.00	.00	.00
29	33.6	.00	63.4	.00	.00	.00
30	33.6	.00	63.4	.00	.00	.00
31	33.6	.00	63.4	.00	.00	.00
32	24.2	.00	-44.4	.00	.00	.00
33	24.2	.00	-44.4	.00	.00	.00
34	24.2	.00	-44.4	.00	.00	.00
35	24.2	.00	-44.4	.00	.00	.00
36	24.2	.00	-44.4	.00	.00	.00
37	24.2	.00	-44.4	.00	.00	.00
38	24.2	.0	-44.4	.0	.0	.0



39	24.2	.0	-44.4	.0	.0	.0
40	24.2	.00	-44.3	.00	.00	.00
41	24.1	.00	-44.3	.00	.00	.00
42	24.1	.00	-44.3	.00	.00	.00
43	24.1	.00	-44.3	.00	.00	.00
44	24.1	.00	-44.3	.00	.00	.00
45	24.1	.00	-44.3	.00	.00	.00
46	24.1	.00	-44.3	.00	.00	.00
47	24.1	.0	-44.3	.0	.0	.0

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	225.5	.00	49.00	.00	.00	.00
2	225.5	.00	49.00	.00	.00	.00
3	225.5	.00	49.00	.00	.00	.00
4	225.5	.00	49.00	.00	.00	.00
5	225.5	.00	49.00	.00	.00	.00
6	225.5	.00	49.00	.00	.00	.00
7	225.5	.00	49.00	.00	.00	.00
8	225.5	.00	49.00	.00	.00	.00
9	225.5	.00	49.00	.00	.00	.00
10	225.5	.00	49.00	.00	.00	.00
11	225.5	.00	49.00	.00	.00	.00
12	225.5	.00	49.00	.00	.00	.00
13	225.5	.00	49.00	.00	.00	.00
14	225.5	.00	49.00	.00	.00	.00
15	225.5	.00	49.00	.00	.00	.00
16	225.5	.00	49.00	.00	.00	.00
17	222.9	.00	43.88	.00	.00	.00
18	222.9	.00	43.88	.00	.00	.00
19	222.9	.00	43.88	.00	.00	.00
20	222.9	.00	43.88	.00	.00	.00
21	222.9	.00	43.88	.00	.00	.00
22	222.9	.00	43.88	.00	.00	.00
23	222.9	.00	43.88	.00	.00	.00
24	222.9	.00	43.88	.00	.00	.00
25	222.9	.00	43.88	.00	.00	.00
26	222.9	.00	43.88	.00	.00	.00
27	222.9	.00	43.88	.00	.00	.00
28	222.9	.00	43.88	.00	.00	.00
29	222.9	.00	43.88	.00	.00	.00
30	222.9	.00	43.88	.00	.00	.00
31	222.9	.00	43.88	.00	.00	.00
32	200.8	.00	-39.4	.00	.00	.00
33	200.8	.00	-39.4	.00	.00	.00
34	200.8	.00	-39.4	.00	.00	.00
35	200.8	.00	-39.4	.00	.00	.00
36	200.7	.00	-39.4	.00	.00	.00
37	200.7	.00	-39.4	.00	.00	.00
38	200.7	.00	-39.4	.00	.00	.00
39	200.7	.00	-39.4	.00	.00	.00
40	200.7	.00	-39.4	.00	.00	.00
41	200.7	.00	-39.3	.00	.00	.00
42	200.7	.00	-39.3	.00	.00	.00
43	200.7	.00	-39.3	.00	.00	.00
44	200.7	.00	-39.3	.00	.00	.00

45	20.7	.0	-39.3	.0	.0	.0
46	20.7	.0	-39.3	.0	.0	.0
47	20.7	.0	-39.3	.0	.0	.0

LOAD CASE - 4

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	21.7	.0	40.7	.0	.0	.0
2	21.7	.0	40.7	.0	.0	.0
3	21.7	.0	40.7	.0	.0	.0
4	21.7	.0	40.7	.0	.0	.0
5	21.7	.0	40.7	.0	.0	.0
6	21.7	.0	40.7	.0	.0	.0
7	21.7	.0	40.7	.0	.0	.0
8	21.7	.0	40.7	.0	.0	.0
9	21.7	.0	40.7	.0	.0	.0
10	21.7	.0	40.7	.0	.0	.0
11	21.7	.0	40.7	.0	.0	.0
12	21.7	.0	40.7	.0	.0	.0
13	21.7	.0	40.7	.0	.0	.0
14	21.7	.0	40.7	.0	.0	.0
15	21.7	.0	40.7	.0	.0	.0
16	21.7	.0	40.7	.0	.0	.0
17	24.8	.0	46.9	.0	.0	.0
18	24.8	.0	46.9	.0	.0	.0
19	24.8	.0	46.9	.0	.0	.0
20	24.8	.0	46.9	.0	.0	.0
21	24.8	.0	46.9	.0	.0	.0
22	24.8	.0	46.9	.0	.0	.0
23	24.8	.0	46.9	.0	.0	.0
24	24.8	.0	46.9	.0	.0	.0
25	24.8	.0	46.9	.0	.0	.0
26	24.8	.0	46.9	.0	.0	.0
27	24.8	.0	46.9	.0	.0	.0
28	24.8	.0	46.9	.0	.0	.0
29	24.8	.0	46.9	.0	.0	.0
30	24.8	.0	46.9	.0	.0	.0
31	24.8	.0	46.9	.0	.0	.0
32	22.8	.0	-42.9	.0	.0	.0
33	22.8	.0	-42.9	.0	.0	.0
34	22.8	.0	-42.8	.0	.0	.0
35	22.8	.0	-42.8	.0	.0	.0
36	22.8	.0	-42.8	.0	.0	.0
37	22.8	.0	-42.8	.0	.0	.0
38	22.8	.0	-42.8	.0	.0	.0
39	22.7	.0	-42.8	.0	.0	.0
40	22.7	.0	-42.8	.0	.0	.0
41	22.7	.0	-42.8	.0	.0	.0
42	22.7	.0	-42.8	.0	.0	.0
43	22.7	.0	-42.7	.0	.0	.0
44	22.7	.0	-42.7	.0	.0	.0
45	22.7	.0	-42.7	.0	.0	.0
46	22.7	.0	-42.7	.0	.0	.0
47	22.7	.0	-42.7	.0	.0	.0

LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	10.6	.0	18.8	.0	.0	.0
2	10.6	.00	18.8	.00	.00	.00
3	10.6	.00	18.8	.00	.00	.00
4	10.6	.00	18.8	.00	.00	.00
5	10.6	.00	18.8	.00	.00	.00
6	10.6	.00	18.8	.00	.00	.00
7	10.6	.00	18.8	.00	.00	.00
8	10.6	.00	18.8	.00	.00	.00
9	10.6	.00	18.8	.00	.00	.00
10	10.6	.00	18.8	.00	.00	.00
11	10.6	.00	18.8	.00	.00	.00
12	10.6	.00	18.8	.00	.00	.00
13	10.6	.00	18.8	.00	.00	.00
14	10.6	.00	18.8	.00	.00	.00
15	10.6	.00	18.8	.00	.00	.00
16	10.6	.00	18.8	.00	.00	.00
17	23.2	.00	44.2	.00	.00	.00
18	23.2	.00	44.2	.00	.00	.00
19	23.2	.00	44.2	.00	.00	.00
20	23.2	.00	44.2	.00	.00	.00
21	23.2	.00	44.2	.00	.00	.00
22	23.2	.00	44.2	.00	.00	.00
23	23.2	.00	44.2	.00	.00	.00
24	23.2	.00	44.2	.00	.00	.00
25	23.2	.00	44.2	.00	.00	.00
26	23.2	.00	44.2	.00	.00	.00
27	23.2	.00	44.2	.00	.00	.00
28	23.2	.00	44.2	.00	.00	.00
29	23.2	.00	44.2	.00	.00	.00
30	23.2	.00	44.2	.00	.00	.00
31	23.2	.00	44.2	.00	.00	.00
32	4.4	.00	-6.3	.00	.00	.00
33	4.4	.00	-6.3	.00	.00	.00
34	4.4	.00	-6.3	.00	.00	.00
35	4.4	.00	-6.3	.00	.00	.00
36	4.4	.00	-6.3	.00	.00	.00
37	4.4	.00	-6.3	.00	.00	.00
38	4.4	.00	-6.3	.00	.00	.00
39	4.4	.00	-6.3	.00	.00	.00
40	4.4	.00	-6.3	.00	.00	.00
41	4.4	.00	-6.3	.00	.00	.00
42	4.4	.00	-6.2	.00	.00	.00
43	4.4	.00	-6.2	.00	.00	.00
44	4.4	.00	-6.2	.00	.00	.00
45	4.4	.00	-6.2	.00	.00	.00
46	4.4	.00	-6.2	.00	.00	.00
47	4.4	.00	-6.2	.00	.00	.00

LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	6.0	.0	10.0	.0	.0	.0
2	6.0	.0	10.0	.0	.0	.0



## PLAQUEMINES PUMP STATION ADDITION:

Stability Analysis w/ SWL = 9.5:

FAILURE SURFACE (A) Required a Vertical Pressure of 1435 psf.

base slab thickness = 1'-6"

$$wt = (1.5')(150-91) = 90 \text{ psf}$$

floor slab thickness = 1'-0"

$$wt = (1.0)(150) = 150 \text{ psf}$$

Walls:

INTAKE BASIN FRONT WALL:

2' x 15.75' over 32.33'

$$wt = (2)(15.75/32.33)(150) = 146 \text{ psf}$$

SIDE WALLS:

2 @ 2' x 23.25' over 60'

$$wt = (2)(2)(23.25/60)(150) = 232.5 \text{ psf}$$

$$\text{total } wt = 90 + 150 + 146 + 232.5 = 618.5 \text{ psf}$$

$$\begin{aligned} \text{Pressure to be taken by tension piles: } & 1435 - 618.5 \\ & = 816.5 \text{ psf} \end{aligned}$$

- CAN NOT VERIFY TENSION CONNECTORS IN PILES,  
 ∴ REQUIRE NEW T-WALL.

NEW T-WALL ~ 54' FROM FRONT EDGE OF BLDG.

500 SHEETS, FULLER 5 SQUARE  
 60 SHEETS, FULLER 5 SQUARE  
 42 SHEETS, FULLER 5 SQUARE  
 200 SHEETS, FULLER 5 SQUARE  
 100 RECYCLED WHITE 5 SQUARE  
 42 SHEETS, FULLER 5 SQUARE  
 100 RECYCLED WHITE 5 SQUARE  
 42 SHEETS, FULLER 5 SQUARE  
 100 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



## PLAQUEMINES PUMP STATION - ORIGINAL

FOR FAILURE SURFACE (A) ①, REQ'D PRESSURE = 1337 psf  
FAILURE SURFACE @ el -23

BASE SLAB THICKNESS = 2'

$$wt = (150 - 91)(2) = 118 \text{ psf}$$

FLOOR SLAB THICKNESS = 8"

$$wt = (8/12)(150) = 100 \text{ psf}$$

WALLS: 2 @ 14" x 23' over 62'-8"

$$wt = \frac{2 \left( \frac{14}{12} \right) (23') (150 \text{ pcf})}{62.67} = 128.4 \text{ psf}$$

Columns: 12 @ 14" x 18" x 23'  
12 @ 14" x 22" x 23'  
4 @ 16" x 30" x 23'  
4 @ 16" x 39" x 23'  
4 @ 14" x 14" x 23'

over 62'-8" x 78'-2"

$$wt = \left[ 12 \left( \frac{14}{12} \right) \left( \frac{18}{12} \right) (23) (150) + 12 \left( \frac{14}{12} \right) \left( \frac{22}{12} \right) (23) (150) + 4 \left( \frac{16}{12} \right) \left( \frac{30}{12} \right) (23) (150) \right. \\ \left. + 4 \left( \frac{16}{12} \right) \left( \frac{39}{12} \right) (23) (150) + 4 \left( \frac{14}{12} \right) \left( \frac{14}{12} \right) (23) (150) \right] / 62.67 = 78.167 \\ = 58.3 \text{ psf}$$

$$\text{Total wt} = 118 + 100 + 128 + 58 = 404 \text{ psf}$$

$$\text{Pressure to be taken by piles in tension} = 1337 - 404 \\ = 933 \text{ psf}$$

$$\text{Passive wedge area} = (62.67')(7') = 438.69 \text{ sf}$$

$$\text{Total load to be taken by piles in tension} = \frac{933(438.69)}{1000} = 409 \text{ K}$$

# PILES = 28

$$\text{Req'd tension per pile} = 409/28 = 14.6 \text{ K/PILE } \textcircled{0.2}$$

## PLAQUEMINES PUMP STATION (CONT.)

FAILURE SURFACE (B4) - Reg'd Pressure = 650 psf  
el - 30

$$\text{total wt} = 404 \text{ psf}$$

$$\text{Pressure to be taken by piles in tension} = 650 - 404 = 246 \text{ psf}$$

$$\text{Passive wedge area} = (62.67)(14') = 877.38 \text{ sf}$$

Total load to be taken by piles in tension =


$$\frac{(246)(877.38)}{1000} = 216 \text{ K}$$

$$\# \text{ piles} = 49$$

$$\text{Reg'd tension per pile} = 216/49 = 4.4 \text{ K/pile}$$

13-782 500 SHEETS, FILER, 5 SQUARE  
42-381 50 SHEETS, EYE EASY, 5 SQUARE  
42-382 100 SHEETS, EYE EASY, 5 SQUARE  
42-383 100 SHEETS, EYE EASY, 5 SQUARE  
42-384 100 SHEETS, EYE EASY, 5 SQUARE  
42-385 100 SHEETS, EYE EASY, 5 SQUARE  
42-386 200 RECYCLED WHITE, 5 SQUARE  
42-389 200 RECYCLED WHITE, 5 SQUARE  
MADE IN U.S.A.






**NOTE:**


Test piles shall be driven to El.-71.0 and test loads indicate a capacity of 12 tons per pile the drawing may be reduced for estimate purposes. El.-75.0 has been assumed. Details furnished will be determined by the engineer after completion. For details of foundation

**THIS PLAN  
CHANGE OF  
CONTRACT  
eng-1856**

A-A



**TYPICAL PILE ANCHOR**  
(For all untreated piles and piles under fuel oil tank supports)



REVISION	DATE	DESCRIPTION
△	9-18-52	Added one pile
△	7-15-52	Revised pile ar
△	5-25-52	Revised in accorda
CORPS OF ENGINEERS OFFICE OF THE CHIEF OF ENGINEERS NEW ORLEANS		
DRAWN BY: J.C.M.	INTRACOASTAL ALGIERS PLAQUEMINES P. PILI	
TRACED BY: J.C.M.		
CHECKED BY: J.A.G.		
SUBMITTED: <i>G. H. Dudley</i> CHIEF, DESIGN BRANCH		
APPROVED: <i>Wm. H. ...</i> CHIEF, ENGINEERING DIVISION		





P/S

F/S

100 SHEETS FILLER 3 SQUARE  
 100 SHEETS FILLER 4 SQUARE  
 100 SHEETS FILLER 5 SQUARE  
 100 SHEETS FILLER 6 SQUARE  
 100 SHEETS FILLER 7 SQUARE  
 100 SHEETS FILLER 8 SQUARE  
 100 SHEETS FILLER 9 SQUARE  
 100 SHEETS FILLER 10 SQUARE  
 100 SHEETS FILLER 11 SQUARE  
 100 SHEETS FILLER 12 SQUARE  
 100 SHEETS FILLER 13 SQUARE  
 100 SHEETS FILLER 14 SQUARE  
 100 SHEETS FILLER 15 SQUARE  
 100 SHEETS FILLER 16 SQUARE  
 100 SHEETS FILLER 17 SQUARE  
 100 SHEETS FILLER 18 SQUARE  
 100 SHEETS FILLER 19 SQUARE  
 100 SHEETS FILLER 20 SQUARE  
 100 SHEETS FILLER 21 SQUARE  
 100 SHEETS FILLER 22 SQUARE  
 100 SHEETS FILLER 23 SQUARE  
 100 SHEETS FILLER 24 SQUARE  
 100 SHEETS FILLER 25 SQUARE  
 100 SHEETS FILLER 26 SQUARE  
 100 SHEETS FILLER 27 SQUARE  
 100 SHEETS FILLER 28 SQUARE  
 100 SHEETS FILLER 29 SQUARE  
 100 SHEETS FILLER 30 SQUARE  
 100 SHEETS FILLER 31 SQUARE  
 100 SHEETS FILLER 32 SQUARE  
 100 SHEETS FILLER 33 SQUARE  
 100 SHEETS FILLER 34 SQUARE  
 100 SHEETS FILLER 35 SQUARE  
 100 SHEETS FILLER 36 SQUARE  
 100 SHEETS FILLER 37 SQUARE  
 100 SHEETS FILLER 38 SQUARE  
 100 SHEETS FILLER 39 SQUARE  
 100 SHEETS FILLER 40 SQUARE  
 100 SHEETS FILLER 41 SQUARE  
 100 SHEETS FILLER 42 SQUARE  
 100 SHEETS FILLER 43 SQUARE  
 100 SHEETS FILLER 44 SQUARE  
 100 SHEETS FILLER 45 SQUARE  
 100 SHEETS FILLER 46 SQUARE  
 100 SHEETS FILLER 47 SQUARE  
 100 SHEETS FILLER 48 SQUARE  
 100 SHEETS FILLER 49 SQUARE  
 100 SHEETS FILLER 50 SQUARE

Made in U.S.A.



LAQUEMINES PUMP STATION: (ORIGINAL STATION)  
 T-WALL IN FRONT OF EXISTING DISCHARGE BASIN SLAB:

- REANALYSIS DUE TO SWL = 9.5 NGVD:

FOR FAILURE SURFACE (A)Ⓛ, REQ'D PRESSURE = 1797 psf

DEAD LOAD PRESSURE = 404 psf

PRESSURE TO BE TAKEN BY TENSION PILES = 1797 - 404  
 = 1393 psf

PASSIVE WEDGE AREA = 438 SF

Total load to be taken by tension piles =  $\frac{(1393)(438)}{1000} = 610^k$

# PILES = 28

TENSION/PILE =  $610/28 = 21.7^k = 10.9^T$  N.G.

- PUT NEW T-WALL IN FRONT OF DISCHARGE BASIN SLAB.

13-782 500 SHEETS, FILLER 5 SQUARE  
 42-381 50 SHEETS, EYE CASE 2 SQUARE  
 42-382 100 SHEETS, EYE CASE 2 SQUARE  
 42-383 200 SHEETS, EYE CASE 2 SQUARE  
 42-392 100 RECYCLED WHITE 5 SQUARE  
 42-399 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



LOADS :

DEADLOADS :

STEM: ① (1')(21.5')(1.150  $\frac{K}{ft}$ ) = 3.23  $\frac{K}{ft}$   
 ② (2')(1')(21.5')(1.150) = 1.61  $\frac{K}{ft}$

BASE: (1.5')(2.5')(1.180) = 5.63  $\frac{K}{ft}$


WATER OVER BASE:

@ SWL: (11')(11.5')(0.064) = 13.73  $\frac{K}{ft}$   
 @ SWL + 2': (11')(21.5')(0.064) = 15.14  $\frac{K}{ft}$   
 @ Low Water: (11')(10')(0.064) = 7.04  $\frac{K}{ft}$


SOIL OVER BASE:

(2')(7')(1.20) = 1.68  $\frac{K}{ft}$

12,782 200 SHEETS, GREEN, 5 SQUARE  
 42,981 50 SHEETS, YELLOW, 5 SQUARE  
 42,982 100 SHEETS, YELLOW, 5 SQUARE  
 42,989 200 SHEETS, YELLOW, 5 SQUARE  
 42,990 200 SHEETS, CYCLED, WHITE, 5 SQUARE  
 MADE IN U.S.A.



WATER LOADS:



@ SWL:  $p = (22)(0.064) = 1.41 \text{ k/ft}^2$


@ SWL + 2'  $p = (24)(0.064) = 1.54$

@ low water  $p = (12.5)(0.064) = 0.80$

WIND LOADS:

P/S: WIND above el 0.0:  $(50 \text{ psf})(11.5) = 0.575 \text{ klf}$

Soil Pressure on P/S: (add wDL)



- Use "at rest" soil pressures:


$p_0 = \gamma z K_0$

$K_0 = 1 - \sin \phi$   
 $= 1 - \sin 30$   
 $= 0.5$

$p_0 = (1.20)(9.5)(0.5)$   
 $= 0.57$

$P = \frac{1}{2}(0.57)(9.5) = 2.71 \text{ k} @ \frac{9.5}{3} = 3.17'$


13,782 500 SHEETS, FILLER 5 SQUARE  
 42,381 50 SHEETS, EYE PAPER 5 SQUARE  
 42,382 100 SHEETS, EYE PAPER 5 SQUARE  
 42,383 100 SHEETS, EYE PAPER 5 SQUARE  
 42,384 100 SHEETS, EYE PAPER 5 SQUARE  
 42,385 100 SHEETS, EYE PAPER 5 SQUARE  
 42,386 100 SHEETS, EYE PAPER 5 SQUARE  
 42,387 100 SHEETS, EYE PAPER 5 SQUARE  
 42,388 100 SHEETS, EYE PAPER 5 SQUARE  
 42,389 100 SHEETS, EYE PAPER 5 SQUARE  
 42,390 100 SHEETS, EYE PAPER 5 SQUARE  
 42,391 100 SHEETS, EYE PAPER 5 SQUARE  
 42,392 100 SHEETS, EYE PAPER 5 SQUARE  
 42,393 100 SHEETS, EYE PAPER 5 SQUARE  
 42,394 100 SHEETS, EYE PAPER 5 SQUARE  
 42,395 100 SHEETS, EYE PAPER 5 SQUARE  
 42,396 100 SHEETS, EYE PAPER 5 SQUARE  
 42,397 100 SHEETS, EYE PAPER 5 SQUARE  
 42,398 100 SHEETS, EYE PAPER 5 SQUARE  
 42,399 100 SHEETS, EYE PAPER 5 SQUARE  
 42,400 100 SHEETS, EYE PAPER 5 SQUARE  
 Made in U.S.A.



## T-WALL LOADING CASES:

- I: STATIC WATER PRESSURE TO SWL, NO WIND, IMPERVIOUS SHEET PILE CUTOFF (100% FORCES)
- II: STATIC WATER PRESSURE TO SWL, NO WIND, PERVIOUS SHEET PILE CUTOFF (100% FORCES)
- III: STATIC WATER PRESSURE TO SWL+2', NO WIND, IMPERVIOUS SHEET PILE CUTOFF (75% FORCES)
- IV: STATIC WATER PRESSURE TO SWL+2', NO WIND, PERVIOUS SHEET PILE CUTOFF (75% FORCES)
- V: WATER @ LOW WATER LEVEL, NO WIND (100% FORCES)
- VI: WATER @ LOW WATER LEVEL, WIND FROM P/S (75% FORCES)

13-782 500 SHEETS FULLER 5 SQUARE  
 42-381 50 SHEETS FV-LEASE 5 SQUARE  
 42-382 100 SHEETS FV-LEASE 5 SQUARE  
 42-383 100 SHEETS FV-LEASE 5 SQUARE  
 42-384 100 SHEETS FV-LEASE 5 SQUARE  
 42-385 100 RECYCLED WHITE 5 SQUARE  
 42-386 100 RECYCLED WHITE 5 SQUARE  
 42-387 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



T-WALL FORCE TABULATION

2+

DESCRIPTION	FORCES (KIPS)		LEVER ARM (FT)		MOMENTS (K') <sup>2</sup>
	F <sub>x</sub>	F <sub>z</sub>	X	Z	M <sub>y-y</sub>
DEADLOADS					
STEM(1)		3.23	+4.0		- 12.92
STEM(2)		1.61	+4.83		- 7.78
BASE		5.63	0		
SWL		13.73	-2.0		+ 27.46
SWL+2'		15.14	-2.0		+ 30.28
LOW WATER		7.04	-2.0		+ 14.08
Soil on P/S		1.68	6.5		- 10.92
WATER LOADS	-2.71			-3.17	+ 8.59
(a) SWL					
(i) (1.41)(22) =	15.51			- 7.33	- 113.69
buoyancy:					
imp: (1.41)(5.5) =		-7.75	-4.75		- 36.81
per: 1/2(1.41)(15) =		-10.575	-2.5		- 26.44
(b) SWL+2'					
1/2(1.54)(24) =	18.48			- 8.0	- 147.84
buoyancy:					
imp: (1.54)(5.5) =		- 8.47	-4.75		- 40.23
per: 1/2(1.54)(15) =		- 11.55	-2.5		- 28.88
(c) Low WATER					
1/2(0.80)(12.5) =	5.0			- 4.17	- 20.85
buoyancy:					
imp: (0.80)(5.5) =		- 4.4	-4.75		- 20.90
per: 1/2(0.80)(15) =		- 6.0	-2.5		- 15.0
WIND					
P/S	-0.575			-19.25	+ 11.07
LATERAL SOIL PRESSURE: (FROM EUSTIS)					
ANCHOR FORCE (INCLUDE w/DL)	+3.7			0	

13-702 500 SHEET IS FULLER 5 SQUARE  
 42-281 50 SHEET IS FULLER 5 SQUARE  
 42-282 100 SHEET IS FULLER 5 SQUARE  
 42-283 100 SHEET IS FULLER 5 SQUARE  
 42-284 100 SHEET IS FULLER 5 SQUARE  
 42-285 100 SHEET IS FULLER 5 SQUARE  
 42-286 100 SHEET IS FULLER 5 SQUARE  
 42-287 100 SHEET IS FULLER 5 SQUARE  
 42-288 100 SHEET IS FULLER 5 SQUARE  
 42-289 100 SHEET IS FULLER 5 SQUARE  
 42-290 100 SHEET IS FULLER 5 SQUARE  
 42-291 100 SHEET IS FULLER 5 SQUARE  
 42-292 100 SHEET IS FULLER 5 SQUARE  
 42-293 100 SHEET IS FULLER 5 SQUARE  
 42-294 100 SHEET IS FULLER 5 SQUARE  
 42-295 100 SHEET IS FULLER 5 SQUARE  
 42-296 100 SHEET IS FULLER 5 SQUARE  
 42-297 100 SHEET IS FULLER 5 SQUARE  
 42-298 100 SHEET IS FULLER 5 SQUARE  
 42-299 100 SHEET IS FULLER 5 SQUARE  
 42-300 100 SHEET IS FULLER 5 SQUARE  
 Made in U.S.A.





U.S ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA

MODULUS OF HORIZONTAL SUBGRADE REACTION  
REACH 2

ELEVATION IN FEET NGVD	$\frac{K_h \times B}{DC}$
10 to 0	169
0 to -30	138
-30 to -40	152
-40 to -50	182
-50 to -60	211
-60 to -68	237

- Where:
- $K_h$  = Modulus of horizontal subgrade reaction (lbs/in.<sup>3</sup>)
  - B = Diameter of pile (inches)
  - C = Reduction factor for cyclic loading
    - C = 0.5 for cyclic loading
    - C = 1.0 for initial loading
  - D = Reduction factor for effect of group action

D	PILE SPACING IN DIRECTION OF LOADING
1.0	8B
0.85	7B
0.7	6B
0.55	5B
0.40	4B
0.25	3B



AXIAL AND HORIZONTAL RESISTANCE OF BATTER PILES

ESTIMATED FROM ALLOWABLE VERTICAL LOAD CAPACITY

L = VERTICAL COMPONENT OF BATTER PILE EMBEDMENT LENGTH.

V = ESTIMATED ALLOWABLE SINGLE PILE LOAD CAPACITY OF A PILE DRIVEN VERTICALLY WITH EMBEDMENT LENGTH, L.

B = BATTER OF PILE EXPRESSED AS A RATIO OF VERTICAL DISTANCE TO ONE FOOT HORIZONTAL DISTANCE.



H = HORIZONTAL RESISTANCE OF BATTER PILE ESTIMATED AS FOLLOWS:

$$H = \frac{V}{B}$$


A = ALLOWABLE AXIAL PILE LOAD CAPACITY OF A SINGLE BATTER PILE ESTIMATED AS FOLLOWS:

$$A = \sqrt{V^2 \left(1 + \frac{1}{B^2}\right)}$$

NOTE: THE AXIAL LOAD RESISTANCE OF A VERTICAL PILE, V, IS DEPENDENT ON THE TYPE OF LOADING--TENSION OR COMPRESSION. CAUTION SHOULD BE EXERCISED TO INSURE THAT THE CORRECT VERTICAL CAPACITY IS USED.



VECTOR DIAGRAM FOR TENSION PILE



VECTOR DIAGRAM FOR COMPRESSION PILE

## SOIL CONSTANT:

- use weighted average of soil constant below el. = 44:

$$\frac{K_h \times B}{DC} = \frac{(6)(182) + 10(211) + 8(237)}{24}$$

$$= 212$$

$$ES = K_h \times B$$

$$ES = (212)(D)(C)$$

$$C = 1.0$$

D = Reduction factor for group action

Assume 14"  $\phi$  Piles Spaced @ 12' in direction of Loading

$$144 = 14(X)$$

$$10.2 = X$$

$$D = 1.0$$

$$ES = 212$$


## Allowable Pile Loads:

$$\text{- use Pile Tip} = -80 \text{ NGVD } c = 22^T$$

$$= 44^k$$

$$T = 18^T$$

$$= 36^k$$



$$\text{Length: } \begin{matrix} -12.5^T \\ -80^T \end{matrix} = 67.5' \text{ Vert.}$$

$$\text{Length} = 75.5'$$

$$A = \sqrt{V^2 \left(1 + \frac{1}{B^2}\right)}$$


$$A_c = \sqrt{(44)^2 (1.25)}$$

$$A_c = 49^k$$

$$A_T = \sqrt{(36)^2 (1.25)}$$


$$A_T = 40^k$$

13,782 200 BULK IS. FILLER 5 SQUARE  
 42,381 100 SHEETS EYE CASE 5 SQUARE  
 42,381 100 SHEETS EYE CASE 5 SQUARE  
 42,381 100 SHEETS EYE CASE 5 SQUARE  
 42,381 100 SHEETS EYE CASE 5 SQUARE  
 42,381 100 RECYCLED WHITE 5 SQUARE  
 42,381 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



use 50' length of wall

14 #2 500 SHEETS FILLER 5 SQUARE  
 42 #81 675 SHEETS 1 1/2" CASE 5 SQUARE  
 42 #82 100 SHEETS 1 1/2" CASE 5 SQUARE  
 42 #83 100 SHEETS 1 1/2" CASE 5 SQUARE  
 42 #84 100 SHEETS 1 1/2" CASE 5 SQUARE  
 42 #85 100 SHEETS 1 1/2" CASE 5 SQUARE  
 42 #86 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



	x	y	z
1	6	-22.5	0
2		-17.5	
3		-12.5	
4		-7.5	
5		-2.5	
6		2.5	
7		7.5	
8		12.5	
9		17.5	
10	6	22.5	
11	2	-20	
12		-10	
13		0	
14		10	
15	2	20	
16	-6	-22.5	
17		-17.5	
18		-12.5	
19		-7.5	
20		-2.5	
21		2.5	
22		7.5	
23		12.5	
24		17.5	
25	-6	22.5	0

50'  
5'

LOAD COMBINATIONS					
LOADING	DESCRIPTION		FORCES		MOMENTS
CASE			Fx	Fz	My
1	DL,SWL,IMP. S/P	DL	0.99	25.88	4.43
	100%	SWL	15.51		-113.69
		IMP		-7.75	-36.81
		TOTAL	16.5	18.13	-146.07
		FOR 50'	825	906.5	-7303.5
2	DL,SWL,PER. S/P	DL	0.99	25.88	4.43
	100%	SWL	15.51		-113.69
		IMP		-10.58	-26.44
		TOTAL	16.5	15.3	-135.7
		FOR 50'	825	765	-6785
3	DL,SWL+2',IMP S/P	DL	0.99	27.29	7.25
	75%	SWL	18.48		-147.84
		IMP		-8.47	-40.23
		TOTAL	19.47	18.82	-180.82
		75% TOTAL	14.6025	14.115	-135.615
	FOR 50'	730.125	705.75	-6780.75	
4	DL,SWL+2',PER S/P	DL	0.99	27.29	7.25
	75%	SWL	18.48		-147.84
		IMP		-11.55	-28.88
		TOTAL	19.47	15.74	-169.47
		75% TOTAL	14.6025	11.805	-127.1025
	FOR 50'	730.125	590.25	-6355.125	
5	DL,LOW WATER	DL	0.99	19.19	-8.95
	100%	SWL	5		-28.85
		IMP		-4.4	-20.9
		TOTAL	5.99	14.79	-58.7
		FOR 50'	299.5	739.5	-2935
6	DL,LOW WATER,WIND	DL	0.99	19.19	-8.95
	75%	SWL	5		-20.85
		IMP		-4.4	-20.9
		WIND	-0.58		11.07
		TOTAL	5.41	14.79	-39.63
	75% TOTAL	4.0575	11.0925	-29.7225	
	FOR 50'	202.875	554.625	-1486.125	

1010	PLAQUEMINES FRONTAL PROTECTION T-WALL																				
1020	PROP	4030	3201	3201	196	2	0	ALL													
1030	SOIL ES	0.212	LEN	75.5	0	ALL															
1040	PIN ALL																				
1050	DLS S	49	40	600.2	223.1	132.6	1510	1166.8	H	14	ALL										
1060	ASC S	196	457	0.816	0.856	2	0	ALL													
1070	BATTER 2 ALL																				
1080	ANGLE	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	12	13	14	15	
1085	ANGLE	0	16	17	18	19	20	21	22	23											
1090	ANGLE	180	24	25	26	27	28	29	30	31	32	33	34	35							
1100	PILE		1				6														
1105	PILE		2				6														
1110	PILE		3				6														
1115	PILE		4				6														
1120	PILE		5				6														
1125	PILE		6				6														
1130	PILE		7				6														
1135	PILE		8				6														
1140	PILE		9				6														
1145	PILE		10				6														
1146	PILE		11				6														
1147	PILE		12				6														
1150	PILE		13				22														
1155	PILE		14				22														
1160	PILE		15				22														
1161	PILE		16				22														
1162	PILE		17				22														
1163	PILE		18				22														
1164	PILE		19				22														
1165	PILE		20				22														
1166	PILE		21				22														
1167	PILE		22				22														
1168	PILE		23				2														
1169	PILE		24				-6														
1170	PILE		25				-6														
1180	PILE		26				-6														
1190	PILE		27				-6														
1200	PILE		28				-6														
1210	PILE		29				-6														
1220	PILE		30				-6														
1230	PILE		31				-6														
1240	PILE		32				-6														
1250	PILE		33				-6														
1260	PILE		34				-6														
1270	PILE		35				-6														
1300	LOAD		1				825														
1310	LOAD		2				825														
1320	LOAD		3				730.1		0												
1330	LOAD		4				730.1		0												
1340	LOAD		5				299.5		0												
1350	LOAD		6				202.9		0												
1360	FOUT		1				2			3											
1370	PFO ALL																				
1380	FPL PLAQPLOT																				

906.5	0	-7303.5	0
765.0	0	-6785	0
705.75	0	-6780.8	0
590.25	0	-6355.1	0
739.5	0	-2935	0
554.6	0	-1486.1	0
4	5	6	7 PLAQOUT

\*\*\*\*\*  
 \* CORPS PROGRAM # X0080 \* CPGA - CASE PILE GROUP ANALYSIS PROGRAM  
 \* VERSION NUMBER # 86/09/02-A \* RUN DATE 02-11-98 RUN TIME 15:21:36  
 \*\*\*\*\*

PLAQUEMINES FRONTAL PROTECTION T-WALL

THERE ARE 44 PILES AND  
 6 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = {  $\begin{matrix} X & Y & Z \\ \hline -6.00 & -24.50 & .00 \\ 6.00 & 24.50 & .00 \end{matrix}$  }

\*\*\*\*\*

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40300E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -  
 ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.21200E+00	L	.75500E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -  
 ALL

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	6.00	-24.50	.00	2.00	.00	75.50	P
2	6.00	-21.00	.00	2.00	.00	75.50	P
3	6.00	-17.50	.00	2.00	.00	75.50	P
4	6.00	-14.00	.00	2.00	.00	75.50	P
5	6.00	-10.50	.00	2.00	.00	75.50	P
6	6.00	-7.00	.00	2.00	.00	75.50	P

7	6.00	-3.50	.00	2.00	.00	75.50	
8	6.00	.00	.00	2.00	.00	75.50	P
9	6.00	3.50	.00	2.00	.00	75.50	P
10	6.00	7.00	.00	2.00	.00	75.50	P
11	6.00	10.50	.00	2.00	.00	75.50	P
12	6.00	14.00	.00	2.00	.00	75.50	P
13	6.00	17.50	.00	2.00	.00	75.50	P
14	6.00	21.00	.00	2.00	.00	75.50	P
15	6.00	24.50	.00	2.00	.00	75.50	P
16	2.00	-22.75	.00	2.00	.00	75.50	P
17	2.00	-19.25	.00	2.00	.00	75.50	P
18	2.00	-15.75	.00	2.00	.00	75.50	P
19	2.00	-12.25	.00	2.00	.00	75.50	P
20	2.00	-8.75	.00	2.00	.00	75.50	P
21	2.00	-5.25	.00	2.00	.00	75.50	P
22	2.00	-1.75	.00	2.00	.00	75.50	P
23	2.00	1.75	.00	2.00	.00	75.50	P
24	2.00	5.25	.00	2.00	.00	75.50	P
25	2.00	8.75	.00	2.00	.00	75.50	P
26	2.00	12.25	.00	2.00	.00	75.50	P
27	2.00	15.75	.00	2.00	.00	75.50	P
28	2.00	19.25	.00	2.00	.00	75.50	P
29	2.00	22.75	.00	2.00	.00	75.50	P
30	-6.00	-24.50	.00	2.00	180.00	75.50	P
31	-6.00	-21.00	.00	2.00	180.00	75.50	P
32	-6.00	-17.50	.00	2.00	180.00	75.50	P
33	-6.00	-14.00	.00	2.00	180.00	75.50	P
34	-6.00	-10.50	.00	2.00	180.00	75.50	P
35	-6.00	-7.00	.00	2.00	180.00	75.50	P
36	-6.00	-3.50	.00	2.00	180.00	75.50	P
37	-6.00	.00	.00	2.00	180.00	75.50	P
38	-6.00	3.50	.00	2.00	180.00	75.50	P
39	-6.00	7.00	.00	2.00	180.00	75.50	P
40	-6.00	10.50	.00	2.00	180.00	75.50	P
41	-6.00	14.00	.00	2.00	180.00	75.50	P
42	-6.00	17.50	.00	2.00	180.00	75.50	P
43	-6.00	21.00	.00	2.00	180.00	75.50	P
44	-6.00	24.50	.00	2.00	180.00	75.50	P

3322.00

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	825.0	.0	906.5	.0	-7303.5	.0
2	825.0	.0	765.0	.0	-6785.0	.0
3	730.1	.0	705.8	.0	-6780.8	.0
4	730.1	.0	590.3	.0	-6355.1	.0
5	299.5	.0	739.5	.0	-2935.0	.0
6	202.9	.0	554.6	.0	-1486.1	.0

\*\*\*\*\*

ORIGINAL PILE GROUP STIFFNESS MATRIX

.15810E+05	.45384E-03	.96904E+04	-.62500E-01	-.17277E+07	-.31250E-01
.45384E-03	.58256E+03	-.90767E-03	.74506E-08	-.65352E-01	.44486E+04
.96904E+04	-.90767E-03	.61493E+05	.28125E+00	-.46959E+06	.62500E-01
.00000E+00	.37253E-08	.12500E+00	.19414E+10	.00000E+00	-.27777E+09
-.17277E+07	-.65352E-01	-.46959E+06	.20000E+01	.22862E+09	.10000E+01
-.15625E-01	.44486E+04	.00000E+00	-.27777E+09	.30000E+01	.50132E+09

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	15.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	15.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	15.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	15.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.

\*\*\*\*\*

PILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.4175E-01	-.2626E-07	.7766E-02	-.2564E-12	-.5190E-04	.1703E-11
2	.6994E-01	-.3019E-07	.2779E-02	.2040E-13	.1781E-03	.1393E-11
3	.2841E-01	-.2723E-07	.6016E-02	-.1257E-12	-.1289E-03	.1829E-11
4	.5152E-01	-.3043E-07	.1936E-02	.1005E-12	.5972E-04	.1574E-11
5	-.1611E-01	.4244E-08	.1266E-01	-.7367E-12	-.2498E-03	.5469E-12
6	.7309E-02	.5731E-08	.7816E-02	-.5128E-12	-.6715E-05	-.6699E-13

\*\*\*\*\*

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO  
 (F3\*EMIN) FOR CONCRETE PILES  
 B INDICATES BUCKLING CONTROLS

LOAD CASE -	1										
PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.4	.0	50.5	.0	-17.1	.0	1.03	.13	1.15	1.04	#
2	.4	.0	50.5	.0	-17.1	.0	1.03	.13	1.15	1.04	#
3	.4	.0	50.5	.0	-17.1	.0	1.03	.13	1.15	1.04	#
4	.4	.0	50.5	.0	-17.1	.0	1.03	.13	1.15	1.04	#
5	.4	.0	50.5	.0	-17.1	.0	1.03	.13	1.15	1.04	#



6	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
7	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
8	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
9	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
10	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
11	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
12	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
13	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
14	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
15	.4	.0	50	.0	-17.1	.0	1.03	.13	1.15	1.04	##
16	.4	.0	46.6	.0	-17.7	.0	1.03	.13	1.15	1.04	##
17	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
18	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
19	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
20	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
21	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
22	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
23	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
24	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
25	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
26	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
27	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
28	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
29	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
30	.4	.0	46.6	.0	-17.7	.0	.95	.13	1.13	1.01	##
31	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
32	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
33	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
34	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
35	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
36	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
37	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
38	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
39	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
40	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
41	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
42	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
43	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##
44	.4	.0	26.3	.0	20.8	.0	.66	.37	.77	.64	##

LOAD CASE -

2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	##
1	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
2	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
3	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
4	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
5	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
6	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
7	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
8	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
9	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
10	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
11	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
12	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
13	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##
14	.9	.0	38.9	.0	-35.7	.0	.79	.14	1.13	.94	##

15		.0	338	.0	-335.7	.0	.79	.14	1.13	.94	#
16		.00	528	.00	-333.7	.00	1.07	.15	1.20	1.01	#
17		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
18		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
19		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
20		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
21		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
22		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
23		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
24		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
25		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
26		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
27		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
28		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
29		.00	522	.00	-333.7	.00	1.07	.15	1.20	1.01	#
30		.00	300	.00	-333.7	.00	1.07	.15	1.20	1.01	#
31		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
32		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
33		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
34		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
35		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
36		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
37		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
38		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
39		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
40		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
41		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
42		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
43		.00	300	.00	37.0	.00	.76	.45	.78	.58	#
44		.00	300	.00	37.0	.00	.76	.45	.78	.58	#

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	#
1	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
2	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
3	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
4	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
5	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
6	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
7	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
8	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
9	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
10	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
11	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
12	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
13	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
14	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
15	.2	.0	46.0	.0	-9.9	.0	.94	.13	1.11	1.03	#
16	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
17	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
18	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
19	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
20	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
21	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
22	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#
23	.3	.0	36.4	.0	-11.4	.0	.74	.15	1.07	.98	#

24		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
25		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
26		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
27		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
28		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
29		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
30		.00	36.4	.00	-11.4	.00	.74	.15	1.07	.98	#
31	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
32	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
33	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
34	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
35	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
36	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
37	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
38	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
39	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
40	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
41	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
42	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
43	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#
44	..	.00	-27.2	.00	12.8	.00	.68	.36	.74	.65	#

LOAD CASE - 4

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
2	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
3	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
4	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
5	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
6	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
7	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
8	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
9	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
10	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
11	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
12	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
13	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
14	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
15	.6	.00	36.5	.00	-25.1	.00	.74	.15	1.10	.95	#
16	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
17	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
18	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
19	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
20	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
21	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
22	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
23	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
24	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
25	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
26	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
27	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
28	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
29	.6	.00	41.0	.00	-24.4	.00	.84	.14	1.12	.97	#
30	..	.00	30.4	.00	26.0	.00	.76	.43	.76	.60	#
31	..	.00	30.4	.00	26.0	.00	.76	.43	.76	.60	#
32	..	.00	30.4	.00	26.0	.00	.76	.43	.76	.60	#

33	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
34	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
35	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
36	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
37	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
38	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
39	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
40	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
41	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
42	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
43	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60
44	-.6	.0	-30.4	.0	26.0	.0	.76	.43	.76	.60

LOAD CASE - 5

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
2	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
3	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
4	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
5	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
6	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
7	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
8	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
9	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
10	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
11	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
12	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
13	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
14	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
15	-.4	.0	35.2	.0	15.0	.0	.72	.15	1.07	.96
16	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
17	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
18	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
19	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
20	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
21	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
22	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
23	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
24	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
25	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
26	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
27	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
28	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
29	-.3	.0	16.5	.0	12.1	.0	.34	.19	.97	.87
30	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
31	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
32	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
33	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
34	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
35	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
36	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
37	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
38	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
39	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
40	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82
41	.2	.0	4.3	.0	1.8	.0	.09	.22	.90	.82

42	.2	.0	4.3	.0	-8.9	.0	.09	.22	.90	.82
43	.2	.0	4.3	.0	-8.9	.0	.09	.22	.90	.82
44	.2	.0	4.3	.0	-8.9	.0	.09	.22	.90	.82

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
2	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
3	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
4	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
5	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
6	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
7	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
8	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
9	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
10	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
11	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
12	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
13	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
14	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
15	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
16	.0	.0	18.6	.0	-1.5	.0	.38	.19	.95	.91	#
17	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
18	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
19	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
20	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
21	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
22	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
23	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
24	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
25	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
26	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
27	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
28	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
29	.0	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
30	.1	.0	18.1	.0	-1.6	.0	.37	.19	.95	.91	#
31	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
32	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
33	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
34	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
35	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
36	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
37	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
38	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
39	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
40	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
41	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
42	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
43	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#
44	.1	.0	18.7	.0	-1.2	.0	.12	.22	.90	.83	#

\*\*\*\*\*

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	23.0	.0	45.0	.0	.0	.0
2	23.0	.0	45.0	.0	.0	.0
3	23.0	.0	45.0	.0	.0	.0
4	23.0	.0	45.0	.0	.0	.0
5	23.0	.0	45.0	.0	.0	.0
6	23.0	.0	45.0	.0	.0	.0
7	23.0	.0	45.0	.0	.0	.0
8	23.0	.0	45.0	.0	.0	.0
9	23.0	.0	45.0	.0	.0	.0
10	23.0	.0	45.0	.0	.0	.0
11	23.0	.0	45.0	.0	.0	.0
12	23.0	.0	45.0	.0	.0	.0
13	23.0	.0	45.0	.0	.0	.0
14	23.0	.0	45.0	.0	.0	.0
15	23.0	.0	45.0	.0	.0	.0
16	21.2	.0	41.5	.0	.0	.0
17	21.2	.0	41.5	.0	.0	.0
18	21.2	.0	41.5	.0	.0	.0
19	21.2	.0	41.5	.0	.0	.0
20	21.2	.0	41.5	.0	.0	.0
21	21.2	.0	41.5	.0	.0	.0
22	21.2	.0	41.5	.0	.0	.0
23	21.2	.0	41.5	.0	.0	.0
24	21.2	.0	41.5	.0	.0	.0
25	21.2	.0	41.5	.0	.0	.0
26	21.2	.0	41.5	.0	.0	.0
27	21.2	.0	41.5	.0	.0	.0
28	21.2	.0	41.5	.0	.0	.0
29	21.2	.0	41.5	.0	.0	.0
30	12.2	.0	-23.3	.0	.0	.0
31	12.2	.0	-23.3	.0	.0	.0
32	12.2	.0	-23.3	.0	.0	.0
33	12.2	.0	-23.3	.0	.0	.0
34	12.2	.0	-23.3	.0	.0	.0
35	12.2	.0	-23.3	.0	.0	.0
36	12.2	.0	-23.3	.0	.0	.0
37	12.2	.0	-23.3	.0	.0	.0
38	12.2	.0	-23.3	.0	.0	.0
39	12.2	.0	-23.3	.0	.0	.0
40	12.2	.0	-23.3	.0	.0	.0
41	12.2	.0	-23.3	.0	.0	.0
42	12.2	.0	-23.3	.0	.0	.0
43	12.2	.0	-23.3	.0	.0	.0
44	12.2	.0	-23.3	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	18.2	.0	34.4	.0	.0	.0
2	18.2	.0	34.4	.0	.0	.0

3	18.2	.0	34.4	.0	.0	.0
4	18.2	.0	34.4	.0	.0	.0
5	18.2	.0	34.4	.0	.0	.0
6	18.2	.0	34.4	.0	.0	.0
7	18.2	.0	34.4	.0	.0	.0
8	18.2	.0	34.4	.0	.0	.0
9	18.2	.0	34.4	.0	.0	.0
10	18.2	.0	34.4	.0	.0	.0
11	18.2	.0	34.4	.0	.0	.0
12	18.2	.0	34.4	.0	.0	.0
13	18.2	.0	34.4	.0	.0	.0
14	18.2	.0	34.4	.0	.0	.0
15	18.2	.0	34.4	.0	.0	.0
16	24.1	.0	46.3	.0	.0	.0
17	24.1	.0	46.3	.0	.0	.0
18	24.1	.0	46.3	.0	.0	.0
19	24.1	.0	46.3	.0	.0	.0
20	24.1	.0	46.3	.0	.0	.0
21	24.1	.0	46.3	.0	.0	.0
22	24.1	.0	46.3	.0	.0	.0
23	24.1	.0	46.3	.0	.0	.0
24	24.1	.0	46.3	.0	.0	.0
25	24.1	.0	46.3	.0	.0	.0
26	24.1	.0	46.3	.0	.0	.0
27	24.1	.0	46.3	.0	.0	.0
28	24.1	.0	46.3	.0	.0	.0
29	24.1	.0	46.3	.0	.0	.0
30	14.3	.0	-26.6	.0	.0	.0
31	14.3	.0	-26.6	.0	.0	.0
32	14.3	.0	-26.6	.0	.0	.0
33	14.3	.0	-26.6	.0	.0	.0
34	14.3	.0	-26.6	.0	.0	.0
35	14.3	.0	-26.6	.0	.0	.0
36	14.3	.0	-26.6	.0	.0	.0
37	14.3	.0	-26.6	.0	.0	.0
38	14.3	.0	-26.6	.0	.0	.0
39	14.3	.0	-26.6	.0	.0	.0
40	14.3	.0	-26.6	.0	.0	.0
41	14.3	.0	-26.6	.0	.0	.0
42	14.3	.0	-26.6	.0	.0	.0
43	14.3	.0	-26.6	.0	.0	.0
44	14.3	.0	-26.6	.0	.0	.0

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	20.8	.0	41.0	.0	.0	.0
2	20.8	.0	41.0	.0	.0	.0
3	20.8	.0	41.0	.0	.0	.0
4	20.8	.0	41.0	.0	.0	.0
5	20.8	.0	41.0	.0	.0	.0
6	20.8	.0	41.0	.0	.0	.0
7	20.8	.0	41.0	.0	.0	.0
8	20.8	.0	41.0	.0	.0	.0
9	20.8	.0	41.0	.0	.0	.0
10	20.8	.0	41.0	.0	.0	.0
11	20.8	.0	41.0	.0	.0	.0

12	20	.0	41.0	.0	.0	.0
13	20	.00	41.0	.00	.00	.00
14	20	.00	41.0	.00	.00	.00
15	20	.00	41.0	.00	.00	.00
16	16	.00	32.4	.00	.00	.00
17	16	.00	32.4	.00	.00	.00
18	16	.00	32.4	.00	.00	.00
19	16	.00	32.4	.00	.00	.00
20	16	.00	32.4	.00	.00	.00
21	16	.00	32.4	.00	.00	.00
22	16	.00	32.4	.00	.00	.00
23	16	.00	32.4	.00	.00	.00
24	16	.00	32.4	.00	.00	.00
25	16	.00	32.4	.00	.00	.00
26	16	.00	32.4	.00	.00	.00
27	16	.00	32.4	.00	.00	.00
28	16	.00	32.4	.00	.00	.00
29	16	.00	32.4	.00	.00	.00
30	12	.00	-24.2	.00	.00	.00
31	12	.00	-24.2	.00	.00	.00
32	12	.00	-24.2	.00	.00	.00
33	12	.00	-24.2	.00	.00	.00
34	12	.00	-24.2	.00	.00	.00
35	12	.00	-24.2	.00	.00	.00
36	12	.00	-24.2	.00	.00	.00
37	12	.00	-24.2	.00	.00	.00
38	12	.00	-24.2	.00	.00	.00
39	12	.00	-24.2	.00	.00	.00
40	12	.00	-24.2	.00	.00	.00
41	12	.00	-24.2	.00	.00	.00
42	12	.00	-24.2	.00	.00	.00
43	12	.00	-24.2	.00	.00	.00
44	12	.00	-24.2	.00	.00	.00

LOAD CASE - 4

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	16.9	.0	32.4	.0	.0	.0
2	16.9	.00	32.4	.00	.00	.00
3	16.9	.00	32.4	.00	.00	.00
4	16.9	.00	32.4	.00	.00	.00
5	16.9	.00	32.4	.00	.00	.00
6	16.9	.00	32.4	.00	.00	.00
7	16.9	.00	32.4	.00	.00	.00
8	16.9	.00	32.4	.00	.00	.00
9	16.9	.00	32.4	.00	.00	.00
10	16.9	.00	32.4	.00	.00	.00
11	16.9	.00	32.4	.00	.00	.00
12	16.9	.00	32.4	.00	.00	.00
13	16.9	.00	32.4	.00	.00	.00
14	16.9	.00	32.4	.00	.00	.00
15	16.9	.00	32.4	.00	.00	.00
16	18.9	.00	36.4	.00	.00	.00
17	18.9	.00	36.4	.00	.00	.00
18	18.9	.00	36.4	.00	.00	.00
19	18.9	.00	36.4	.00	.00	.00
20	18.9	.00	36.4	.00	.00	.00



21	18.9	.00	36.4	.00	.00	.00
22	18.9	.00	36.4	.00	.00	.00
23	18.9	.00	36.4	.00	.00	.00
24	18.9	.00	36.4	.00	.00	.00
25	18.9	.00	36.4	.00	.00	.00
26	18.9	.00	36.4	.00	.00	.00
27	18.9	.00	36.4	.00	.00	.00
28	18.9	.00	36.4	.00	.00	.00
29	18.9	.00	36.4	.00	.00	.00
30	14.2	.00	26.9	.00	.00	.00
31	14.2	.00	26.9	.00	.00	.00
32	14.2	.00	26.9	.00	.00	.00
33	14.2	.00	26.9	.00	.00	.00
34	14.2	.00	26.9	.00	.00	.00
35	14.2	.00	26.9	.00	.00	.00
36	14.2	.00	26.9	.00	.00	.00
37	14.2	.00	26.9	.00	.00	.00
38	14.2	.00	26.9	.00	.00	.00
39	14.2	.00	26.9	.00	.00	.00
40	14.2	.00	26.9	.00	.00	.00
41	14.2	.00	26.9	.00	.00	.00
42	14.2	.00	26.9	.00	.00	.00
43	14.2	.00	26.9	.00	.00	.00
44	14.2	.00	26.9	.00	.00	.00

LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	15.4	.00	31.7	.00	.00	.00
2	15.4	.00	31.7	.00	.00	.00
3	15.4	.00	31.7	.00	.00	.00
4	15.4	.00	31.7	.00	.00	.00
5	15.4	.00	31.7	.00	.00	.00
6	15.4	.00	31.7	.00	.00	.00
7	15.4	.00	31.7	.00	.00	.00
8	15.4	.00	31.7	.00	.00	.00
9	15.4	.00	31.7	.00	.00	.00
10	15.4	.00	31.7	.00	.00	.00
11	15.4	.00	31.7	.00	.00	.00
12	15.4	.00	31.7	.00	.00	.00
13	15.4	.00	31.7	.00	.00	.00
14	15.4	.00	31.7	.00	.00	.00
15	15.4	.00	31.7	.00	.00	.00
16	7.1	.00	14.9	.00	.00	.00
17	7.1	.00	14.9	.00	.00	.00
18	7.1	.00	14.9	.00	.00	.00
19	7.1	.00	14.9	.00	.00	.00
20	7.1	.00	14.9	.00	.00	.00
21	7.1	.00	14.9	.00	.00	.00
22	7.1	.00	14.9	.00	.00	.00
23	7.1	.00	14.9	.00	.00	.00
24	7.1	.00	14.9	.00	.00	.00
25	7.1	.00	14.9	.00	.00	.00
26	7.1	.00	14.9	.00	.00	.00
27	7.1	.00	14.9	.00	.00	.00
28	7.1	.00	14.9	.00	.00	.00
29	7.1	.00	14.9	.00	.00	.00

30	-2.1	.0	3.7	.0	.0	.0
31	-2.1	.00	3.7	.00	.00	.00
32	-2.1	.000	3.7	.000	.000	.000
33	-2.1	.0000	3.7	.0000	.0000	.0000
34	-2.1	.00000	3.7	.00000	.00000	.00000
35	-2.1	.000000	3.7	.000000	.000000	.000000
36	-2.1	.0000000	3.7	.0000000	.0000000	.0000000
37	-2.1	.00000000	3.7	.00000000	.00000000	.00000000
38	-2.1	.000000000	3.7	.000000000	.000000000	.000000000
39	-2.1	.0000000000	3.7	.0000000000	.0000000000	.0000000000
40	-2.1	.00000000000	3.7	.00000000000	.00000000000	.00000000000
41	-2.1	.000000000000	3.7	.000000000000	.000000000000	.000000000000
42	-2.1	.0000000000000	3.7	.0000000000000	.0000000000000	.0000000000000
43	-2.1	.00000000000000	3.7	.00000000000000	.00000000000000	.00000000000000
44	-2.1	.0	3.7	.0	.0	.0

LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	8.4	.0	16.7	.0	.0	.0
2	8.4	.00	16.7	.00	.00	.00
3	8.4	.000	16.7	.000	.000	.000
4	8.4	.0000	16.7	.0000	.0000	.0000
5	8.4	.00000	16.7	.00000	.00000	.00000
6	8.4	.000000	16.7	.000000	.000000	.000000
7	8.4	.0000000	16.7	.0000000	.0000000	.0000000
8	8.4	.00000000	16.7	.00000000	.00000000	.00000000
9	8.4	.000000000	16.7	.000000000	.000000000	.000000000
10	8.4	.0000000000	16.7	.0000000000	.0000000000	.0000000000
11	8.4	.00000000000	16.7	.00000000000	.00000000000	.00000000000
12	8.4	.000000000000	16.7	.000000000000	.000000000000	.000000000000
13	8.4	.0000000000000	16.7	.0000000000000	.0000000000000	.0000000000000
14	8.4	.00000000000000	16.7	.00000000000000	.00000000000000	.00000000000000
15	8.4	.000000000000000	16.7	.000000000000000	.000000000000000	.000000000000000
16	8.1	.0000000000000000	16.2	.0000000000000000	.0000000000000000	.0000000000000000
17	8.1	.00000000000000000	16.22	.00000000000000000	.00000000000000000	.00000000000000000
18	8.1	.000000000000000000	16.22	.000000000000000000	.000000000000000000	.000000000000000000
19	8.1	.0000000000000000000	16.22	.0000000000000000000	.0000000000000000000	.0000000000000000000
20	8.1	.00000000000000000000	16.22	.00000000000000000000	.00000000000000000000	.00000000000000000000
21	8.1	.000000000000000000000	16.22	.000000000000000000000	.000000000000000000000	.000000000000000000000
22	8.1	.0000000000000000000000	16.22	.0000000000000000000000	.0000000000000000000000	.0000000000000000000000
23	8.1	.00000000000000000000000	16.22	.00000000000000000000000	.00000000000000000000000	.00000000000000000000000
24	8.1	.000000000000000000000000	16.22	.000000000000000000000000	.000000000000000000000000	.000000000000000000000000
25	8.1	.0000000000000000000000000	16.22	.0000000000000000000000000	.0000000000000000000000000	.0000000000000000000000000
26	8.1	.00000000000000000000000000	16.22	.00000000000000000000000000	.00000000000000000000000000	.00000000000000000000000000
27	8.1	.000000000000000000000000000	16.22	.000000000000000000000000000	.000000000000000000000000000	.000000000000000000000000000
28	8.1	.0000000000000000000000000000	16.22	.0000000000000000000000000000	.0000000000000000000000000000	.0000000000000000000000000000
29	8.1	.00000000000000000000000000000	16.22	.00000000000000000000000000000	.00000000000000000000000000000	.00000000000000000000000000000
30	-2.4	.000000000000000000000000000000	5.22	.00000000000000000000000000000000	.000000000000000000000000000000000	.0000000000000000000000000000000000
31	-2.4	.00000000000000000000000000000000	5.22	.0000000000000000000000000000000000	.00000000000000000000000000000000000	.000000000000000000000000000000000000
32	-2.4	.0000000000000000000000000000000000	5.22	.000000000000000000000000000000000000	.0000000000000000000000000000000000000	.00000000000000000000000000000000000000
33	-2.4	.000000000000000000000000000000000000	5.22	.00000000000000000000000000000000000000	.000000000000000000000000000000000000000	.00
34	-2.4	.00000000000000000000000000000000000000	5.22	.00	.000	.00
35	-2.4	.00	5.22	.00	.00	.00
36	-2.4	.000	5.22	.000	.000	.000
37	-2.4	.000	5.22	.000	.000	.000
38	-2.4	.0	5.22	.0	.0	.0

39  
40  
41  
42  
43  
44

-12.4  
-12.4  
-12.4  
-12.4  
-12.4

.0  
.00  
.00  
.00  
.00

TTTTTTT  
NNNNNNN

.0  
.0000  
.000000

.0  
.0000  
.000000

.0  
.0000  
.000000



APRIL8

February 4, 1998

Page 1

**RECEIVED**

FEB 4 1998

MEMO  
TO:DEI

DATE:2/4/98

**D. E. I.**

MS APRIL HURRY  
FROM: EUSTIS ENGINEERING  
TOM STREMLAU  
SUBJECT: PREL DATA

PLAQ PUMP STATION UNITS 1 AND 2

I HAVE ENCLOSED REANALYSIS OF P STATION FOR THE HIGHER STORM WATER LEVEL.  
I HAVE INCLUDED A MARKED UP COPY OF PREVIOUS PRESENTATION BUT INCLUDING  
IMPACT OF RAISED WATER LEVEL. ASSUME WILL NEED NEW FRONTAL PROTECTION.  
HAVE INCLUDED SLOPE STABILITY AND T WALL ANALYSIS WITH NEW WALL.  
ALSO PRESENT PREL PILE CAPACITY FOR PILES TO SUPPORT T WALL.

*Original  
Presentation*

FILE	<u>3004</u>	
DISTRIBUTION	<u>WB</u>	<u>Ad /</u>
	<u>JH ✓</u>	<u>          </u>



# EUSTIS ENGINEERING COMPANY, INC.

Geotechnical Engineers  
Metairie, Louisiana

Date 2/4/98

Job 14638

By TLS

Projec \_\_\_\_\_

Subjec \_\_\_\_\_

call  
Tom

ask to  
double check  
capacities

Army Corps of Engineers  
of Harvey Canal  
vicinity Protection Project  
Iberon Parish, La.

Pile Load Capacities  
Full Foundation

mine Pump Station Unit 1+2

## PRELIMINARY


70  
0.05  
350

Pile Type	Pile Tip Elevation NGVD	Estimated Allowable Single Pile Load Capacity, in Tons	
		Factor of Safety = 2.0 Compression	Tension
14-in. square Precast, Prestressed Concrete	-60	10	7
	-70	17	12
	-80	22	18
16-in. square Precast, Prestressed Concrete	-60	12	8
	-70	19	14
	-80	25	20


Note: 1) Top of pile at el -11.0

2) Capacity contribution to el -44.0 has been ignored.

## PRELIMINARY



Elevation in Feet (NGVD)



**PRELIMINARY**

Strata No	Soil Type	Unit Weight PCF	Unfactored		Safety Factor of 1.3			
			Friction Angle Degrees	Cohesion - PSF	Friction Angle Degrees	Cohesion - PSF	Friction Angle Degrees	Cohesion - PSF
1	Sand F.I.I	120	30	0	0	24	0	0
2	Clay Silty Clay Organic Clay and Humus	91	0	310	370	0	238	238
3	Clay	101	0	310	310	0	238	238
4	Clay	101	0	343	376	0	264	289
5	Clay	101	0	409	442	0	313	340
6	Clay	101	0	475	507	0	365	390


Failure Surface	T-Wall Analysis (Using summation of forces Factored Shear Strengths)				
	ER Resisting lbs/ft	ED Driving lbs/ft	ER-ED lbs/ft	Change in Net Force lbs/ft	Equivalent Pressure PSP/ft
(A) 1	5673	8154	-2481		
(B) 2	19278	25475	-6197	-3716	-323
(C) 3	25442	33840	-7898	-1701	-243
(D) 4	38542	45827	-7285	613	61
(E) 5	53102	57858	-4756	2529	253

Stability of Pump Station			
Failure Surface	Summation of Forces		Factor of Safety
	Resisting lbs/ft	Driving lbs/ft	
(A) 1	25525	18486	1.38
(B) 2	42615	26759	1.59

- Notes: 1) To satisfy moment equilibrium, summing moments about base of footing at El-11.5, requires sheetpile penetration to El-44.0.  
 2) Maximum moment occurs at El-23.0 and is 21.3 ft kips/ft of wall.  
 3) Calculated Anchor Force,  $F_A$ , is 3.7 kips/ft of wall at El-11.5.  
 4) The anchor load and indicated T-wall pressure must be supported by driven batter piles.  
 5) Using the Harr method of seepage analysis, the factor of safety against piping failure is 5 or more if the sheetpile tip is at El-44.0.

6) Reads 2 soil parameters were used for these analyses.

Slope Stability and T-Wall Analyses  
 Units 1 and 2, Plaquemines Pumping Station  
 US Army Corps of Engineers  
 East of Harvey Canal  
 Hurricane Protection Project  
 Jefferson Parish, La



NOTE : 1) "P" IS REQUIRED VERTICAL PRESSURE ACROSS TOP OF PASSIVE WEDGES TO ACHIEVE A CALCULATED FACTOR OF SAFETY OF 1.3 OR MORE AGAINST A STABILITY FAILURE.


2) SEEPAGE ANALYSIS BY HARR METHOD INDICATES A FACTOR OF SAFETY OF 2 AGAINST PIPING WHICH IS CONSIDERED ACCEPTABLE.

3) REACH 2 SOIL PARAMETERS WERE USED FOR THESE ANALYSES.

FAILURE SURFACE	SUMMATION OF FORCES LB/FT		FACTOR OF SAFETY	VERTICAL PRESSURE * P, IN PSF TO ACHIEVE FACTOR OF SAFETY - 1.3
	RESISTING	DRIVING		
(A) ①	14286	24470 21024	0.880.58	1837 1747
(A) ②	24826	24470 21024	1.181.01	258 716
(A) ③	33506	24470 21024	1.581.37	-
(B) ④	24527	32551 28280	0.870.75	658 944
(B) ⑤	33517	32551 28280	1.181.03	178 467
(C) ⑥	41620	32551 28280	1.070.94	274 495
(C) ⑦	49892	44145 38718	1.291.13	14 235
(C) ⑧	57036	44145 38718	1.471.29	-
(D) ⑨	62277	55796 49192	1.271.12	37 229

STRATUM NO.	SOIL TYPE	UNIT WEIGHT IN PCF	FRICTION ANGLE DEGREES	COHESION - PSF	
				AVERAGE	BOTTOM
①	CLAY, SILTY CLAY, ORGANIC CLAY & HUMUS	91.0	0	310	310
②	CLAY	101.0	0	310	310
③	CLAY	101.0	0	343	382 376
④	CLAY	101.0	0	409	442
⑤	CLAY	101.0	0	475	507

**PRELIMINARY**




EUSTIS ENGINEERING COMPANY, INC.

Revised SWL E1 9.5  
 SLOPE STABILITY ANALYSES  
 PLAQUEMINE PUMP STATION  
 U. S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL  
 HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA



ADDITION TO PLAQUEMINES PUMP STATION  
(ALGIBRS CANAL)

TRIAL 2.  
PPSTW03.



FLOOD SIDE: WATER PR SWL 9.5 =  $(9.5 + 15.5) 62.5 = 1563$  PSF  
 WATER LEVEL EL 11.5 =  $(11.5 + 15.5) 62.5 = 1688$  PSF  
 LWL EL 0.0 =  $(0 + 15.5) 62.5 = 969$  PSF


PROT. SIDE :

Earth  $P_r @$  Rest =  $0.95 \times 91 \times 16.5 = 1426$  PSF.  
 $K_0 = 0.95$  for in-situ soil

500 SHEETS, FILLER 3 SQUARE  
 100 SHEETS, EYE EAST 3 SQUARE  
 100 SHEETS, EYE WEST 3 SQUARE  
 200 SHEETS, EYE EAST 3 SQUARE  
 42,388  
 42,388  
 42,388  
 100 RECYCLED WHITE 3 SQUARE  
 200 RECYCLED WHITE 3 SQUARE  
 Made in U.S.A.



50 SHEETS FULL SIZE SQUARE  
 42 SHEETS FULL SIZE  
 100 SHEETS 1/4" CASE 5 SQUARE  
 42 SHEETS 1/4" CASE 5 SQUARE  
 200 SHEETS 1/4" CASE 5 SQUARE  
 42 SHEETS 1/4" CASE 5 SQUARE  
 42 SHEETS 1/4" CASE 5 SQUARE  
 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



MS.

ADDITION TO PLAQUEMINES  
PUMPING STA.


- CLOCKWISE  
+ ANTICLOCK


BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y FT	3 FT	MOMENT IK
1	<u>DEAD LOAD</u> <u>WT. OF STEM &amp; BASE</u>					
	STEM. 24.5' x 1' x .15		3.68	3.0		+ 11.04 ↷
	1/2 x 24.5 x 1' x .15		1.84	3.83		+ 7.04 ↷
	BASE 17 x 2.5' x .15 KCF		6.38	-		-
	TOTAL	-	11.90 ↓	-		+ 18.08 ↷
2	<u>SOIL + WATER ON FLOODSIDE.</u> <u>SWL 9.50</u>					
	a) VERTICAL					
	1) Water 11' x 22.5' x .0625		15.47	3.00		- 46.41 ↷
	2) Soil -		-			
	b) LATERAL					
	1) Water 1/2 x 1563 x 25'	19.54 ←		8.33	8.33'	+ 162.77 ↷
	TOTAL	19.54 ←	15.47 ↓			+ 116.36 ↷

NATIONAL BRAND  
 100% PURE  
 100% COTTON  
 100% EGYPTIAN  
 100% GINNING  
 100% PICKING  
 100% SEEDING  
 100% SPINNING  
 100% WEAVING  
 100% FINISHING  
 100% PACKING  
 100% DISTRIBUTION  
 100% RETAILING  
 100% EXPORTING



- CLOCKWISE  
+ ANTICLOCK


BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y. FT	3 FT	MOMENT IK
3	BUOYANCY SWL EL 9.50					
	PVIOUS 1/2 x 1563 x 17'		-13.3	2.83		37.64 ↷
	IMPERVIOUS 1563 x 8.5		-13.3	4.25		+56.5 ↶
4)	SOIL + WATER ON PROTECTED SIDE					
	a) VERTICAL					
	1) WATER					
	2) SOIL					
	 <p>0.091 x 4.0' x 14'</p> <p>1/2 x 0.091 x 57 x 14'</p>	5.10	6.5		+33.1 ↷	
		0.36	4.31			+1.55
	b) LATERAL					
	1) WATER					
	2) SOIL					
	1/2 x 1.426 x 16.5	-11.76			5.5	-64.70 ↷
		-11.76	5.46			-30.05 ↷



- CLOCKWISE  
+ ANTICLOCK


BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y. FT	- Z FT	MOMENT IK
5)	Soil + WATER ON FLOODSIDE SWL + 2'-0" W.S. EL 11.50					
	a) VERTICAL					
	1) WATER 11' x 24.5' x .0625		16.84	3.00		- 50.53 ↷
	2) SOIL	-				
	b) Lateral.					
	1) WATER 1/2 x 1688 x 27'	22.80		9.00		205.2 ↷
	TOTAL	22.80	16.84			154.67 ↷
6)	BUOYANCY W.S. EL 11.50					
	PERVIOUS 1/2 x 1688 x 17		-14.35	2.83		+ 40.60 ↷
	IMPER 1688 x 8.5		-14.35	4.25		+ 61.0 ↷

1. ALL DIMENSIONS IN FEET  
 2. ALL DIMENSIONS IN FEET  
 3. ALL DIMENSIONS IN FEET  
 4. ALL DIMENSIONS IN FEET  
 5. ALL DIMENSIONS IN FEET  
 6. ALL DIMENSIONS IN FEET  
 7. ALL DIMENSIONS IN FEET  
 8. ALL DIMENSIONS IN FEET  
 9. ALL DIMENSIONS IN FEET  
 10. ALL DIMENSIONS IN FEET  
 11. ALL DIMENSIONS IN FEET  
 12. ALL DIMENSIONS IN FEET  
 13. ALL DIMENSIONS IN FEET  
 14. ALL DIMENSIONS IN FEET  
 15. ALL DIMENSIONS IN FEET  
 16. ALL DIMENSIONS IN FEET  
 17. ALL DIMENSIONS IN FEET  
 18. ALL DIMENSIONS IN FEET  
 19. ALL DIMENSIONS IN FEET  
 20. ALL DIMENSIONS IN FEET  
 21. ALL DIMENSIONS IN FEET  
 22. ALL DIMENSIONS IN FEET  
 23. ALL DIMENSIONS IN FEET  
 24. ALL DIMENSIONS IN FEET  
 25. ALL DIMENSIONS IN FEET  
 26. ALL DIMENSIONS IN FEET  
 27. ALL DIMENSIONS IN FEET  
 28. ALL DIMENSIONS IN FEET  
 29. ALL DIMENSIONS IN FEET  
 30. ALL DIMENSIONS IN FEET  
 31. ALL DIMENSIONS IN FEET  
 32. ALL DIMENSIONS IN FEET  
 33. ALL DIMENSIONS IN FEET  
 34. ALL DIMENSIONS IN FEET  
 35. ALL DIMENSIONS IN FEET  
 36. ALL DIMENSIONS IN FEET  
 37. ALL DIMENSIONS IN FEET  
 38. ALL DIMENSIONS IN FEET  
 39. ALL DIMENSIONS IN FEET  
 40. ALL DIMENSIONS IN FEET  
 41. ALL DIMENSIONS IN FEET  
 42. ALL DIMENSIONS IN FEET  
 43. ALL DIMENSIONS IN FEET  
 44. ALL DIMENSIONS IN FEET  
 45. ALL DIMENSIONS IN FEET  
 46. ALL DIMENSIONS IN FEET  
 47. ALL DIMENSIONS IN FEET  
 48. ALL DIMENSIONS IN FEET  
 49. ALL DIMENSIONS IN FEET  
 50. ALL DIMENSIONS IN FEET  
 51. ALL DIMENSIONS IN FEET  
 52. ALL DIMENSIONS IN FEET  
 53. ALL DIMENSIONS IN FEET  
 54. ALL DIMENSIONS IN FEET  
 55. ALL DIMENSIONS IN FEET  
 56. ALL DIMENSIONS IN FEET  
 57. ALL DIMENSIONS IN FEET  
 58. ALL DIMENSIONS IN FEET  
 59. ALL DIMENSIONS IN FEET  
 60. ALL DIMENSIONS IN FEET  
 61. ALL DIMENSIONS IN FEET  
 62. ALL DIMENSIONS IN FEET  
 63. ALL DIMENSIONS IN FEET  
 64. ALL DIMENSIONS IN FEET  
 65. ALL DIMENSIONS IN FEET  
 66. ALL DIMENSIONS IN FEET  
 67. ALL DIMENSIONS IN FEET  
 68. ALL DIMENSIONS IN FEET  
 69. ALL DIMENSIONS IN FEET  
 70. ALL DIMENSIONS IN FEET  
 71. ALL DIMENSIONS IN FEET  
 72. ALL DIMENSIONS IN FEET  
 73. ALL DIMENSIONS IN FEET  
 74. ALL DIMENSIONS IN FEET  
 75. ALL DIMENSIONS IN FEET  
 76. ALL DIMENSIONS IN FEET  
 77. ALL DIMENSIONS IN FEET  
 78. ALL DIMENSIONS IN FEET  
 79. ALL DIMENSIONS IN FEET  
 80. ALL DIMENSIONS IN FEET  
 81. ALL DIMENSIONS IN FEET  
 82. ALL DIMENSIONS IN FEET  
 83. ALL DIMENSIONS IN FEET  
 84. ALL DIMENSIONS IN FEET  
 85. ALL DIMENSIONS IN FEET  
 86. ALL DIMENSIONS IN FEET  
 87. ALL DIMENSIONS IN FEET  
 88. ALL DIMENSIONS IN FEET  
 89. ALL DIMENSIONS IN FEET  
 90. ALL DIMENSIONS IN FEET  
 91. ALL DIMENSIONS IN FEET  
 92. ALL DIMENSIONS IN FEET  
 93. ALL DIMENSIONS IN FEET  
 94. ALL DIMENSIONS IN FEET  
 95. ALL DIMENSIONS IN FEET  
 96. ALL DIMENSIONS IN FEET  
 97. ALL DIMENSIONS IN FEET  
 98. ALL DIMENSIONS IN FEET  
 99. ALL DIMENSIONS IN FEET  
 100. ALL DIMENSIONS IN FEET



- CLOCKWISE  
+ ANTICLOCK

BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y. FT	- Z FT	MOMENT IK
7)	SOIL + WATER ON FLOODSIDE LWL = 0.0					
	a) Vertical					
	1) water 11' x 13' x .0625	-	8.94	3.00	-	26.82 ↘
	2) soil	-	-	-	-	-
b) Lateral	1) Water 1/2 x 0.969 x 15.5	7.50	-	-	5.17	38.82 ↗
		7.50	8.94			12.00 ↗
8)	BUOYANCY LWL 0.0.					
	PERVIOUS 1/2 x 0.969 x 17'		-8.24	2.83		23.32 ↗
	IMPERVIOUS 0.969 x 8.5		-8.24	4.25		35.02 ↗






## LOAD COMBINATIONS.

LD. CASE NO.	DESCRIPTION	$\leftarrow$ F <sub>y</sub>	F <sub>z</sub> ↓	MOMENT M <sub>XX</sub>
1	<u>SWL @ 9.5 PERV. SH.T. PILE</u>  <u>SOIL @ PROT. SIDE UPTO EL 1.00</u>  <u>NO WIND</u>			
	1) D.L.		11.90	+18.08 ↗
	2) SOIL+WATER FLOODSIDE	+19.54	15.47	+116.36 ↗
	3) BUOY PERV		-13.30	+37.64 ↗
	4) SOIL+WATER PROT. SIDE. Unbalanced Force	-11.76 +6.3	5.46	-30.05 ↓
	TOTAL PER LFT	14.08	19.53	142.03 ↗
	TOTAL PER 40'	+563.2	781.2	5,681.2 ↗
2	<u>SWL @ 9.5 IMPER. SH.T. PILE, SOIL</u>  <u>@ PROT. SIDE, UPTO EL 1.00 NO WIND</u>			
	1) DL.		11.90	+18.08 ↗
	2) SOIL+WATER FLOOD SIDE	19.54	15.47	+116.36 ↗
	3) BUOY IMP		-13.3	+56.5 ↗
	4) SOIL+WATER PR. SIDE UNBALANCED FORCE	-11.76 +6.3	5.46	-30.05 ↓
	TOTAL PER LFT	14.08	19.53	160.89 ↗
	TOTAL PER 40' 0"	+563.2	781.2	6435.6 ↗


11.00' 11.00' 11.00' 11.00' 11.00'  
 12.00' 12.00' 12.00' 12.00' 12.00'  
 13.00' 13.00' 13.00' 13.00' 13.00'  
 14.00' 14.00' 14.00' 14.00' 14.00'  
 15.00' 15.00' 15.00' 15.00' 15.00'  
 16.00' 16.00' 16.00' 16.00' 16.00'  
 17.00' 17.00' 17.00' 17.00' 17.00'  
 18.00' 18.00' 18.00' 18.00' 18.00'  
 19.00' 19.00' 19.00' 19.00' 19.00'  
 20.00' 20.00' 20.00' 20.00' 20.00'





LOAD COMBINATIONS.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200




LD. CASE NO.	DESCRIPTION	$F_y$ ←	$F_z$ ↓	MOMENT $M_{XX}$
3	W.S. EL 11.5, PERV. SHT. PILE, SOIL ON P/S UPTO EL 1.00 NO WIND			
	1) D.L.		11.90	18.00 ↻
	5) SOIL+WATER FLOODSIDE	+22.80	16.84	154.67 ↻
	6) BUOY PERV		-14.35	+ 40.63 ↻
	4) SOIL+WATER PROT. SIDE	-11.76		
	UNBALANCED FORCE	+ 6.3		
	TOTAL PER LFT	17.34	14.39	213.35 ↻
	0.75 X TOTAL PER 40'	520.2	431.70	6,400.5
4	W.S. EL 11.5, IMP. SHT. PILE, SOIL ON P/S UPTO EL 1.00, NO WIND			
	1) D.L.		+11.90	18.08 ↻
	5) SOIL+WATER F/S	+22.80	+16.84	154.67 ↻
	6) BUOY IMP.		-14.35	+ 61.0 ↻
	4) SOIL+WATER F/S	-11.76		
	UNBALANCED FORCE	+ 6.3		
	TOTAL PER LFT	17.34	14.39	233.75
	0.75 X TOTAL PER 40' 0"	520.2	431.7	+7012.5 ↻

LOAD COMBINATIONS.

LD. COMB NO.	DESCRIPTION	$F_y$	$F_z \downarrow$	MOMENT $M_{XX}$
5	LWL @ 0.0 NO WIND			
	PERV. SHEET PILING			
	1) DL		11.90	+18.08 ↘
	7) SOIL+WATER FLOODSIDE	7.50	8.94	+12.00 ↘
	8) PERV. SH. PL		-8.24	23.32 ↘
	4) SOIL+WATER P/S	-11.76	5.46	-30.05 ↘
TOTAL PER LFT		-4.26	18.06	23.35 ↘
TOTAL PER 40'		-170.4	722.4	934.0 ↘
6	LWL @ 0.0 NO WIND			
	IMPERVIOUS SHEET PILING			
	1) DL		11.90	+18.08 ↘
	7) SOIL+WATER FLOODSIDE	7.50	8.94	+12.00 ↘
	8) IMP. SH. PL		-8.24	35.02 ↘
	4) SOIL+WATER P/S	-11.76	5.46	-30.05 ↘
TOTAL PER LFT		-4.26	18.06	35.05 ↘
TOTAL PER 40'-0"		-170.4	722.4	1402 ↘


42-001 50 SHEETS (131 LEAFS)  
42-002 50 SHEETS (131 LEAFS)  
42-003 50 SHEETS (131 LEAFS)  
42-004 50 SHEETS (131 LEAFS)  
42-005 50 SHEETS (131 LEAFS)  
42-006 50 SHEETS (131 LEAFS)  
42-007 50 SHEETS (131 LEAFS)  
42-008 50 SHEETS (131 LEAFS)  
42-009 50 SHEETS (131 LEAFS)  
42-010 50 SHEETS (131 LEAFS)



LOAD COMBINATIONS.

LD. COMB NO.	DESCRIPTION	← F <sub>1</sub>	F <sub>2</sub> ↓	MOMENT M <sub>XX</sub>
7	LWL @ 0.0 WIND FROM F/S IMP. SHT. PL  LOAD COMB 6) BASIC LD CASE 9) WIND FROM F/S	   -4.26 0.58	   18.06	   35.05 ↗ 12.21 ↗
	TOTAL PER LFT TOTAL PER 40'	-3.68 -147.2	18.06 722.4	47.26 ↗ 189.0 ↗
8	LWL @ 0.0 WIND FROM P/S PERM. SHT. PL  LOAD COMB 3) BASIC LD CASE 10) WIND FROM P/S	   -4.26 -0.52	   18.06	   23.35 ↗ 11.31 ↘
	TOTAL PER LFT TOTAL PER 40' 0"	-4.78 -191.2	18.06 722.4	12.04 481.6 <sup>WK</sup> ↗

4726  
X 410  
445  
19.00



MANUFACTURED BY...  
42 101  
42 102  
42 103  
42 104  
42 105  
42 106  
42 107  
42 108  
42 109  
42 110  
42 111  
42 112  
42 113  
42 114  
42 115  
42 116  
42 117  
42 118  
42 119  
42 120  
42 121  
42 122  
42 123  
42 124  
42 125  
42 126  
42 127  
42 128  
42 129  
42 130  
42 131  
42 132  
42 133  
42 134  
42 135  
42 136  
42 137  
42 138  
42 139  
42 140  
42 141  
42 142  
42 143  
42 144  
42 145  
42 146  
42 147  
42 148  
42 149  
42 150  
42 151  
42 152  
42 153  
42 154  
42 155  
42 156  
42 157  
42 158  
42 159  
42 160  
42 161  
42 162  
42 163  
42 164  
42 165  
42 166  
42 167  
42 168  
42 169  
42 170  
42 171  
42 172  
42 173  
42 174  
42 175  
42 176  
42 177  
42 178  
42 179  
42 180  
42 181  
42 182  
42 183  
42 184  
42 185  
42 186  
42 187  
42 188  
42 189  
42 190  
42 191  
42 192  
42 193  
42 194  
42 195  
42 196  
42 197  
42 198  
42 199  
42 200

## COMPUTER INPUT

14" x 14" SQ. P.P.C. PILES.

$$\begin{aligned} \text{Area} &= 14 \times 14 = 196 \text{ in}^2 & I &= \frac{1}{12} \times 14 \times 14^3 \\ & & &= 3201 \text{ in}^4 \\ & & S &= 457 \text{ in}^3. \end{aligned}$$

Es: Pile Spacing 5'-0" on Prod Side Rows.

$$\text{Spacing} = \frac{60}{14} = 4.3$$

$$\text{At 4B} \quad D = 0.4.$$

$$\begin{aligned} E_s &= 138 \text{ pci} \times 0.4 = 55 \text{ pci} \\ &= .055 \text{ ksi.} \end{aligned}$$

Piles length Tip El. - 90.0 Cut off - 15.0

$$\text{Length} = 75'$$

$$\begin{aligned} \text{Capacity} &= 72 \text{ Kips Comp.} \\ &52 \text{ Kips Tension} \end{aligned}$$

SUMMARY OF LOADSALL PILES 16x16  
@ 2:1 BATTER

DESCRIPTION	MAX. AXIAL LOAD IN KIPS		MAX CBF	ASL KIP.	-
	COMP.	TENS.			
FLOODSIDE		-60.0 (4)	57 (4)	-	
MIDD ROW NEXT TO F/S	99.0 (6)	-11.7 (1)	-	1.40 (6)	
MIDD ROW NEXT TO P/S	74.1 (1)	-41.4 (6)	-	-	
PROT. SIDE	93.9 (4)	-	-	-	

Vertical loads =

$$\begin{aligned} \text{Comp} &= 99 \times 0.89 = 88.1 \text{ K} \\ &= \underline{44 \text{ Tons}} \end{aligned}$$


$$\begin{aligned} \text{Tension} &= -60 \times 0.89 = 54 \text{ K} \\ &= \underline{27 \text{ Tons}} \end{aligned}$$

Pile Tip - 92.0

$$\text{Allow. Comp} = 44 \text{ Tons}$$


$$\text{Tens} = 32 \text{ Tons}$$

# ADDITION TO PLAQUEMINES PUMP STATION



## LEGEND

BATTER 2:1  
▣  
FILE NUMBER



16" x 16"  
P.P.C. PILES



Date 2/4/98

Job 14638

By TLS

Checked By \_\_\_\_\_

Project \_\_\_\_\_

Subject \_\_\_\_\_

- U.S. Army Corps of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, La.

Allowable Pile Load Capacities  
T-wall Foundation

**PRELIMINARY**

Plaquemine Pump Station Unit 1+2

and Addition to Pump Station

Estimated Allowable Single  
Pile Load Capacity in Tons  
Factor of Safety = 2.0

Compression

Tension

Pile  
Type

Pile  
Tip  
Elevation  
NGVD

14-in. square  
precast, prestressed  
concrete

-60  
-70  
-80  
-90  
-100

1.0  
1.7  
2.4  
3.6  
4.5

7  
12

18  
26

16-in. square  
precast, prestressed  
concrete

-60  
-70  
-80  
-90  
-100

1.2  
1.9  
2.7  
4.2  
5.1

36

8

14

20

30

41

Note: 1) Dredge level between El -100 and -13.0.

2) Capacity contribution to el -44.0 has been ignored.

3) Soil parameters below El -80 have been assumed. Soil borings must be performed to confirm soil conditions below this level for final design.



Date 2/4/98

Job 14638

By TLS

Project \_\_\_\_\_

Subject \_\_\_\_\_ Checked By \_\_\_\_\_

- U.S. Army Corps of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, La.

Allowable Pile Load Capacities  
T-wall Foundation

Plaquemine Pump Station Unit 1 & 2  
and Addition to Pump Station

Estimated Allowable Single  
Pile Load Capacity in Tons  
Factor of Safety = 2.0  
Compression Tension

Pile Type	Pile Tip Elevation NGVD	Estimated Allowable Single Pile Load Capacity in Tons	
		Compression	Tension
14-in. square Precast, Prestressed Concrete	-60	10	7
	-70	17	12
	-80	22	18
16-in. square Precast, Prestressed Concrete	-60	12	8
	-70	19	14
	-80	25	20

**PRELIMINARY**

- Note: 1) Dredge level between El -100 and -15.0.  
 2) Capacity contribution to el -44.0 has been ignored.



U.S. ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL  
 HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA

MODULUS OF HORIZONTAL SUBGRADE REACTION  
 REACH 2


ELEVATION IN FEET	$\frac{K_h \times B}{DC}$
10 to 0	169
0 to -30	138
-30 to -40	152
-40 to -50	182
-50 to -60	211
-60 to -68	237

- Where:
- $K_h$  = Modulus of horizontal subgrade reaction (lbs/in.<sup>3</sup>)
  - B = Diameter of pile (inches)
  - C = Reduction factor for cyclic loading  
 C = 0.5 for cyclic loading  
 C = 1.0 for initial loading
  - D = Reduction factor for effect of group action

PRELIMINARY

D	PILE SPACING IN DIRECTION OF LOADING
1.0	8B
0.85	7B
0.7	6B
0.55	5B
0.40	4B
0.25	3B

TWLP  
STRQ, 3



Strata No.	Soil Type	Unit Weight PCF	Friction Angle Degrees	Unfactored Cohesion - PSF		Friction Angle Degrees	Safety Factor of 1.3 Cohesion - PSF	
				Average	Bottom		Average	Bottom
1	Clay, Silty (Clay) Organic (Clay + Humus)	91.0	0	310	310	0	235	235
2	Clay	101.0	0	310	310	0	238	238
3	Clay	101.0	0	343	376	0	264	289
4	Clay	101.0	0	409	442	0	315	340
5	Clay	101.0	0	475	507	0	365	390

F-wall Analysis  
Summation of Forces (Using Factored Shear Strengths)

Failure Surface	Resisting lbs/ft	Driving lbs/ft	SR-EE lbs/ft	Change in Net Force lbs/ft	Equivalent Pressure PSF
(A) 1	10563	6172	4391	-	-
(B) 2	29786	34707	-4921	-9312	-621
(C) 3	43675	47157	-3482	+1439	+144
(D) 4	59664	59614	-10	+3472	+347

Note: 1) To satisfy moment equilibrium, summing moments about base of footing at El. -15.0, requires sheetpile penetration to El. -44.5.  
2) Maximum moment occurs at El. -25.0 and is 32.1 Ft Kips/Ft of wall.

Stability of Pump Station

Failure Surface	Summation of Forces lbs/ft		Factor of Safety
	Resisting	Driving	
(E) 2	35340	26594	1.33
(F) 3	46838	35551	1.32
(G) 5	66546	42356	1.57

3) Calculated Anchor Force,  $F_A$ , is 6.3 Kips per Ft of wall at El. -15.0.  
4) The anchor load and indicated T wall pressure must be supported by driven batter piles. Axial capacity of these piles above el. -44.5 must be ignored.  
5) Using the Haas Method of seepage analysis, the factor of safety against piping failure is four or more if the sheetpile tip is at El. -44.5.  
6) Reach 2 soil parameters were used for these analyses.

Slope Stability and Proposed T-Wall Analyses  
Addition to Plaquemines Pump Station  
US Army Corp of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, La.

Enclosure

EE14638

u:\FILE\PPSTW05

04/01/98

Last Modified: 04-01-98 at 16:08:48

100 ADDITION TO FLAQUEMINES PUMP STATION-  
150 T WALL ANALYSIS  
200 PROP 4074 5461 5461 256 2 0 ALL  
300 SOIL ES 0.035 LEN 75 0 ALL  
320 PIN ALL  
410 DLS S 84 80 985 294 188 2341 1760 H 16 ALL  
430 ASC S 256 683 .813 .955 1.75 0 ALL  
440 BAT 2 1 2 3 4 5 6 7  
441 BAT 2 8 9 10 11 12 13 14  
442 BAT 2 15 16 17 18 19 20 21  
443 BAT 2 22 23 24 25 26 27 28  
450 ANG 270 1 2 3 4 5 6 7 8 9 10 11 12 13 14  
455 ANG 90 15 16 17 18 19 20 21 22 23 24 25 26 27 28  
460 PILE 1 -18.0 -7.0 0 8 -18.0 -3.0 0  
465 PILE 15 -18.0 3.0 0 22 -18.0 7.0 0  
470 ROW X 7 1 6 AT 6.0  
480 ROW X 7 8 6 AT 6.0  
485 ROW X 7 15 6 AT 6.0  
490 ROW X 7 22 6 AT 6.0  
500 LOA 1 0 563.2 781.2 5681.2 0 0  
510 LOA 2 0 563.2 781.2 6435.6 0 0  
520 LOA 3 0 520.2 431.7 6400.5 0 0  
540 LOA 4 0 520.2 431.7 7012.5 0 0  
550 LOA 5 0 -170.4 722.4 934.0 0 0  
560 LOA 6 0 -170.4 722.4 1402 0 0  
570 LOA 7 0 -147.2 722.4 189 0 0  
580 LOA 8 0 -191.2 722.4 481.6 0 0  
610 FOU 1 2 3 4 5 6 7 PPSTW50  
620 PFO ALL  
630 FPL PPSTW05

D:\FILE\PPSTW50  
Last Modified: 04-01-98 at 16:08:18

04/01 3

\*\*\*\*\*  
\* CORPS PROGRAM # X0080 \* CFGA - CASE FILE GROUP ANALYSIS PROGRAM  
\* VERSION NUMBER # 86/09/02-A \* RUN DATE 04-01-98 RUN TIME 16:08:36  
\*\*\*\*\*

ADDITION TO PLAQUEMINES PUMP STATION  
T WALL ANALYSIS

THERE ARE 28 PILES AND  
8 LOAD CASES IN THIS RUN.

ALL FILE COORDINATES ARE CONTAINED WITHIN A BOX

	X	Y	Z
	-----	-----	-----
WITH DIAGONAL COORDINATES = (	-18.00	-7.00	.00
(	18.00	7.00	.00

\*\*\*\*\*

FILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KS1	IN**4	IN**4	IN**2		
.40740E+04	.54610E+04	.54610E+04	.25600E+03	.20000E+01	.00000E+00

THESE FILE PROPERTIES APPLY TO THE FOLLOWING FILES -

ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.35000E-01	L	.75000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING FILES -

ALL

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	-18.00	-7.00	.00	2.00	270.00	75.00	F
2	-12.00	-7.00	.00	2.00	270.00	75.00	F
3	-6.00	-7.00	.00	2.00	270.00	75.00	F
4	.00	-7.00	.00	2.00	270.00	75.00	F
5	6.00	-7.00	.00	2.00	270.00	75.00	F
6	12.00	-7.00	.00	2.00	270.00	75.00	F
7	18.00	-7.00	.00	2.00	270.00	75.00	F
8	-18.00	-3.00	.00	2.00	270.00	75.00	F
9	-12.00	-3.00	.00	2.00	270.00	75.00	F
10	-6.00	-3.00	.00	2.00	270.00	75.00	F
11	.00	-3.00	.00	2.00	270.00	75.00	F
12	6.00	-3.00	.00	2.00	270.00	75.00	F
13	12.00	-3.00	.00	2.00	270.00	75.00	F
14	18.00	-3.00	.00	2.00	270.00	75.00	F
15	-18.00	3.00	.00	2.00	90.00	75.00	F
16	-12.00	3.00	.00	2.00	90.00	75.00	F
17	-6.00	3.00	.00	2.00	90.00	75.00	F
18	.00	3.00	.00	2.00	90.00	75.00	F
19	6.00	3.00	.00	2.00	90.00	75.00	F
20	12.00	3.00	.00	2.00	90.00	75.00	F
21	18.00	3.00	.00	2.00	90.00	75.00	F
22	-18.00	7.00	.00	2.00	90.00	75.00	F
23	-12.00	7.00	.00	2.00	90.00	75.00	F
24	-6.00	7.00	.00	2.00	90.00	75.00	F
25	.00	7.00	.00	2.00	90.00	75.00	F
26	6.00	7.00	.00	2.00	90.00	75.00	F
27	12.00	7.00	.00	2.00	90.00	75.00	F
28	18.00	7.00	.00	2.00	90.00	75.00	F
						-----	
						2100.00	

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	.0	563.2	781.2	5681.2	.0	.0
2	.0	563.2	781.2	6435.6	.0	.0
3	.0	520.2	431.7	6400.5	.0	.0
4	.0	520.2	431.7	7012.5	.0	.0
5	.0	-170.4	722.4	934.0	.0	.0
6	.0	-170.4	722.4	1402.0	.0	.0

7	.0	-147.2	722.4	189.0	.0	.0
8	.0	-191.2	722.4	481.6	.0	.0

\*\*\*\*\*

ORIGINAL FILE GROUP STIFFNESS MATRIX

.11003E+03	-.36044E-03	-.41185E-03	-.43252E-01	.00000E+00	-.45776E-03
-.36044E-03	.13067E+05	.12207E-03	.15548E+07	.15625E-01	.15625E-01
-.41185E-03	.12207E-03	.51937E+05	-.62500E-01	.31250E-01	.15625E-01
-.43252E-01	.15548E+07	-.62500E-01	.21689E+09	.40000E+01	.00000E+00
-.93132E-09	.15625E-01	.00000E+00	.40000E+01	.10770E+10	-.40000E+01
-.21362E-03	.15625E-01	.15625E-01	.00000E+00	-.40000E+01	.27141E+09

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	14.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	7.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	14.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	7.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	1.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	14.
LOAD CASE	7.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	7.
LOAD CASE	8.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	14.

\*\*\*\*\*

FILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.1976E-06	.3877E-01	.1504E-01	.3637E-04	-.6976E-12	-.3098E-11
2	.1985E-06	.4989E-02	.1504E-01	.3203E-03	-.1262E-11	-.1153E-11
3	.1631E-06	-.1583E-01	.8312E-02	.4676E-03	-.1507E-11	.4325E-12
4	.1638E-06	-.4323E-01	.8312E-02	.6979E-03	-.1965E-11	.2010E-11
5	.1261E-07	-.1305E+00	.1391E-01	.9875E-03	-.1774E-11	.6714E-11
6	.1320E-07	-.1515E+00	.1391E-01	.1164E-02	-.2124E-11	.7921E-11
7	.1721E-07	-.8510E-01	.1391E-01	.6205E-03	-.1070E-11	.4098E-11
8	.7092E-08	-.1211E+00	.1391E-01	.8948E-03	-.1566E-11	.6171E-11

\*\*\*\*\*

FILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT FILE HEAD FOR PINNED FILES

\* INDICATES FILE FAILURE

# INDICATES CBF BASED ON MOMENTS DUE TO (F3\*EMIN) FOR CONCRETE FILES

B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
2	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
3	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
4	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
5	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
6	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
7	-0.2	0.0	-15.3	0.0	11.4	0.0	.26	.16	.91	.74
8	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
9	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
10	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
11	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
12	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
13	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
14	-0.2	0.0	-11.7	0.0	11.6	0.0	.20	.13	.93	.75
15	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
16	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
17	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
18	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
19	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
20	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
21	0.1	0.0	74.1	0.0	-7.8	0.0	.88	.15	1.26	1.09
22	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
23	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
24	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
25	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
26	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
27	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11
28	0.1	0.0	77.7	0.0	-7.6	0.0	.93	.17	1.27	1.11

LOAD CASE - 2

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
2	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
3	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
4	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
5	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
6	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
7	.0	.0	-29.8	.0	-.2	.0	.50	.27	.84	.70
8	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
9	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
10	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
11	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
12	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
13	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
14	.0	.0	2.1	.0	1.7	.0	.03	.24	.97	.82
15	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
16	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
17	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
18	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
19	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
20	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
21	.0	.0	60.3	.0	2.1	.0	.72	.14	1.19	1.05
22	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
23	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
24	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
25	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
26	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
27	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17
28	-.1	.0	92.1	.0	4.1	.0	1.10	.25	1.32	1.17

LOAD CASE - 3

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
2	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
3	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
4	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
5	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
6	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
7	.1	.0	-47.8	.0	-8.0	.0	.80	.45	.78	.61
8	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
9	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
10	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
11	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
12	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80



13	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
14	.1	.0	-1.3	.0	-5.1	.0	.02	.02	.96	.80
15	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
16	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
17	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
18	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
19	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
20	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
21	-.1	.0	35.7	.0	7.2	.0	.43	.19	1.11	.94
22	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
23	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
24	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
25	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
26	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
27	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12
28	-.1	.0	82.2	.0	10.1	.0	.98	.19	1.29	1.12

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
2	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
3	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
4	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
5	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
6	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
7	.2	.0	-59.5	.0	-17.4	.0	.99	.57	.75	.56
8	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
9	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
10	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
11	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
12	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
13	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
14	.2	.0	10.0	.0	-13.1	.0	.12	.23	1.01	.83
15	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
16	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
17	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
18	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
19	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
20	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
21	-.2	.0	24.5	.0	15.2	.0	.29	.21	1.07	.89
22	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15
23	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15
24	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15
25	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15
26	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15
27	-.3	.0	93.9	.0	19.5	.0	1.12	.26	1.35	1.15

28      -.3      .0      93.9      .0      19.5      .0 1.12    .26 1.35 1.15

LOAD CASE -      5

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
2	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
3	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
4	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
5	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
6	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
7	.6	.0	-7.8	.0	-41.9	.0	.13	.14	.99	.72
8	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
9	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
10	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
11	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
12	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
13	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
14	.5	.0	90.4	.0	-35.9	.0	1.08	.24	1.36	1.11
15	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
16	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
17	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
18	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
19	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
20	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
21	-.5	.0	-32.8	.0	39.5	.0	.55	.36	.88	.63
22	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
23	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
24	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
25	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
26	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
27	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00
28	-.6	.0	65.5	.0	45.5	.0	.78	.14	1.28	1.00

LOAD CASE -      6

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
2	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
3	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
4	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
5	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
6	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68
7	.7	.0	-16.8	.0	-49.2	.0	.28	.23	.96	.68

8	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
9	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
10	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
11	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
12	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
13	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
14	.6	.0	99.0	.0	-42.1	.0	1.18	.28	1.40	1.14
15	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
16	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
17	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
18	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
19	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
20	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
21	-.6	.0	-41.4	.0	45.6	.0	.69	.45	.86	.58
22	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
23	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
24	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
25	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
26	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
27	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03
28	-.7	.0	74.4	.0	52.7	.0	.89	.15	1.32	1.03

LOAD CASE - 7

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
2	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
3	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
4	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
5	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
6	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
7	.4	.0	9.0	.0	-26.5	.0	.11	.25	1.03	.81
8	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
9	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
10	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
11	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
12	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
13	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
14	.3	.0	70.7	.0	-22.7	.0	.84	.13	1.26	1.06
15	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
16	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
17	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
18	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
19	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
20	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
21	-.4	.0	-13.1	.0	26.2	.0	.22	.16	.94	.72
22	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96

23	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96
24	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96
25	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96
26	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96
27	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96
28	-.4	.0	48.7	.0	30.0	.0	.58	.16	1.19	.96

LOAD CASE - 8

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
2	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
3	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
4	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
5	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
6	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
7	.5	.0	-1.5	.0	-38.6	.0	.02	.07	1.01	.75
8	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
9	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
10	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
11	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
12	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
13	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
14	.5	.0	87.6	.0	-33.1	.0	1.04	.22	1.35	1.11
15	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
16	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
17	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
18	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
19	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
20	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
21	-.5	.0	-29.9	.0	36.6	.0	.50	.33	.89	.64
22	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
23	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
24	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
25	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
26	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
27	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98
28	-.6	.0	59.1	.0	42.1	.0	.70	.15	1.25	.98

\*\*\*\*\*

FILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

FILE	FX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	7.0	-13.7	.0	.0	.0
2	.0	7.0	-13.7	.0	.0	.0
3	.0	7.0	-13.7	.0	.0	.0
4	.0	7.0	-13.7	.0	.0	.0
5	.0	7.0	-13.7	.0	.0	.0
6	.0	7.0	-13.7	.0	.0	.0
7	.0	7.0	-13.7	.0	.0	.0
8	.0	5.4	-10.4	.0	.0	.0
9	.0	5.4	-10.4	.0	.0	.0
10	.0	5.4	-10.4	.0	.0	.0
11	.0	5.4	-10.4	.0	.0	.0
12	.0	5.4	-10.4	.0	.0	.0
13	.0	5.4	-10.4	.0	.0	.0
14	.0	5.4	-10.4	.0	.0	.0
15	.0	33.2	66.2	.0	.0	.0
16	.0	33.2	66.2	.0	.0	.0
17	.0	33.2	66.2	.0	.0	.0
18	.0	33.2	66.2	.0	.0	.0
19	.0	33.2	66.2	.0	.0	.0
20	.0	33.2	66.2	.0	.0	.0
21	.0	33.2	66.2	.0	.0	.0
22	.0	34.8	69.5	.0	.0	.0
23	.0	34.8	69.5	.0	.0	.0
24	.0	34.8	69.5	.0	.0	.0
25	.0	34.8	69.5	.0	.0	.0
26	.0	34.8	69.5	.0	.0	.0
27	.0	34.8	69.5	.0	.0	.0
28	.0	34.8	69.5	.0	.0	.0

LOAD CASE - 2

FILE	FX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	13.3	-26.6	.0	.0	.0
2	.0	13.3	-26.6	.0	.0	.0
3	.0	13.3	-26.6	.0	.0	.0
4	.0	13.3	-26.6	.0	.0	.0
5	.0	13.3	-26.6	.0	.0	.0
6	.0	13.3	-26.6	.0	.0	.0
7	.0	13.3	-26.6	.0	.0	.0
8	.0	-.9	1.9	.0	.0	.0
9	.0	-.9	1.9	.0	.0	.0
10	.0	-.9	1.9	.0	.0	.0
11	.0	-.9	1.9	.0	.0	.0

12	.0	-1.9	1.9	.0	.0	.0
13	.0	-1.9	1.9	.0	.0	.0
14	.0	-1.9	1.9	.0	.0	.0
15	.0	26.9	53.9	.0	.0	.0
16	.0	26.9	53.9	.0	.0	.0
17	.0	26.9	53.9	.0	.0	.0
18	.0	26.9	53.9	.0	.0	.0
19	.0	26.9	53.9	.0	.0	.0
20	.0	26.9	53.9	.0	.0	.0
21	.0	26.9	53.9	.0	.0	.0
22	.0	41.1	82.4	.0	.0	.0
23	.0	41.1	82.4	.0	.0	.0
24	.0	41.1	82.4	.0	.0	.0
25	.0	41.1	82.4	.0	.0	.0
26	.0	41.1	82.4	.0	.0	.0
27	.0	41.1	82.4	.0	.0	.0
28	.0	41.1	82.4	.0	.0	.0

LOAD CASE - 3

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	21.3	-42.8	.0	.0	.0
2	.0	21.3	-42.8	.0	.0	.0
3	.0	21.3	-42.8	.0	.0	.0
4	.0	21.3	-42.8	.0	.0	.0
5	.0	21.3	-42.8	.0	.0	.0
6	.0	21.3	-42.8	.0	.0	.0
7	.0	21.3	-42.8	.0	.0	.0
8	.0	.5	-1.2	.0	.0	.0
9	.0	.5	-1.2	.0	.0	.0
10	.0	.5	-1.2	.0	.0	.0
11	.0	.5	-1.2	.0	.0	.0
12	.0	.5	-1.2	.0	.0	.0
13	.0	.5	-1.2	.0	.0	.0
14	.0	.5	-1.2	.0	.0	.0
15	.0	15.9	32.0	.0	.0	.0
16	.0	15.9	32.0	.0	.0	.0
17	.0	15.9	32.0	.0	.0	.0
18	.0	15.9	32.0	.0	.0	.0
19	.0	15.9	32.0	.0	.0	.0
20	.0	15.9	32.0	.0	.0	.0
21	.0	15.9	32.0	.0	.0	.0
22	.0	36.7	73.6	.0	.0	.0
23	.0	36.7	73.6	.0	.0	.0
24	.0	36.7	73.6	.0	.0	.0
25	.0	36.7	73.6	.0	.0	.0
26	.0	36.7	73.6	.0	.0	.0

27	.0	36.7	73.6	.0	.0	.0
28	.0	36.7	73.6	.0	.0	.0

## LOAD CASE - 4

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	26.4	-53.3	.0	.0	.0
2	.0	26.4	-53.3	.0	.0	.0
3	.0	26.4	-53.3	.0	.0	.0
4	.0	26.4	-53.3	.0	.0	.0
5	.0	26.4	-53.3	.0	.0	.0
6	.0	26.4	-53.3	.0	.0	.0
7	.0	26.4	-53.3	.0	.0	.0
8	.0	-4.6	8.8	.0	.0	.0
9	.0	-4.6	8.8	.0	.0	.0
10	.0	-4.6	8.8	.0	.0	.0
11	.0	-4.6	8.8	.0	.0	.0
12	.0	-4.6	8.8	.0	.0	.0
13	.0	-4.6	8.8	.0	.0	.0
14	.0	-4.6	8.8	.0	.0	.0
15	.0	10.8	22.0	.0	.0	.0
16	.0	10.8	22.0	.0	.0	.0
17	.0	10.8	22.0	.0	.0	.0
18	.0	10.8	22.0	.0	.0	.0
19	.0	10.8	22.0	.0	.0	.0
20	.0	10.8	22.0	.0	.0	.0
21	.0	10.8	22.0	.0	.0	.0
22	.0	41.8	84.1	.0	.0	.0
23	.0	41.8	84.1	.0	.0	.0
24	.0	41.8	84.1	.0	.0	.0
25	.0	41.8	84.1	.0	.0	.0
26	.0	41.8	84.1	.0	.0	.0
27	.0	41.8	84.1	.0	.0	.0
28	.0	41.8	84.1	.0	.0	.0

## LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	3.0	-7.2	.0	.0	.0
2	.0	3.0	-7.2	.0	.0	.0
3	.0	3.0	-7.2	.0	.0	.0
4	.0	3.0	-7.2	.0	.0	.0
5	.0	3.0	-7.2	.0	.0	.0
6	.0	3.0	-7.2	.0	.0	.0

7	.0	3.0	-7.2	.0	.0	.0
8	.0	-40.9	80.7	.0	.0	.0
9	.0	-40.9	80.7	.0	.0	.0
10	.0	-40.9	80.7	.0	.0	.0
11	.0	-40.9	80.7	.0	.0	.0
12	.0	-40.9	80.7	.0	.0	.0
13	.0	-40.9	80.7	.0	.0	.0
14	.0	-40.9	80.7	.0	.0	.0
15	.0	-15.1	-29.1	.0	.0	.0
16	.0	-15.1	-29.1	.0	.0	.0
17	.0	-15.1	-29.1	.0	.0	.0
18	.0	-15.1	-29.1	.0	.0	.0
19	.0	-15.1	-29.1	.0	.0	.0
20	.0	-15.1	-29.1	.0	.0	.0
21	.0	-15.1	-29.1	.0	.0	.0
22	.0	28.7	58.8	.0	.0	.0
23	.0	28.7	58.8	.0	.0	.0
24	.0	28.7	58.8	.0	.0	.0
25	.0	28.7	58.8	.0	.0	.0
26	.0	28.7	58.8	.0	.0	.0
27	.0	28.7	58.8	.0	.0	.0
28	.0	28.7	58.8	.0	.0	.0

LOAD CASE - 6

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	6.9	-15.3	.0	.0	.0
2	.0	6.9	-15.3	.0	.0	.0
3	.0	6.9	-15.3	.0	.0	.0
4	.0	6.9	-15.3	.0	.0	.0
5	.0	6.9	-15.3	.0	.0	.0
6	.0	6.9	-15.3	.0	.0	.0
7	.0	6.9	-15.3	.0	.0	.0
8	.0	-44.8	88.3	.0	.0	.0
9	.0	-44.8	88.3	.0	.0	.0
10	.0	-44.8	88.3	.0	.0	.0
11	.0	-44.8	88.3	.0	.0	.0
12	.0	-44.8	88.3	.0	.0	.0
13	.0	-44.8	88.3	.0	.0	.0
14	.0	-44.8	88.3	.0	.0	.0
15	.0	-19.1	-36.7	.0	.0	.0
16	.0	-19.1	-36.7	.0	.0	.0
17	.0	-19.1	-36.7	.0	.0	.0
18	.0	-19.1	-36.7	.0	.0	.0
19	.0	-19.1	-36.7	.0	.0	.0
20	.0	-19.1	-36.7	.0	.0	.0
21	.0	-19.1	-36.7	.0	.0	.0



22	.0	32.6	66.9	.0	.0	.0
23	.0	32.6	66.9	.0	.0	.0
24	.0	32.6	66.9	.0	.0	.0
25	.0	32.6	66.9	.0	.0	.0
26	.0	32.6	66.9	.0	.0	.0
27	.0	32.6	66.9	.0	.0	.0
28	.0	32.6	66.9	.0	.0	.0

LOAD CASE - 7

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	-4.3	7.9	.0	.0	.0
2	.0	-4.3	7.9	.0	.0	.0
3	.0	-4.3	7.9	.0	.0	.0
4	.0	-4.3	7.9	.0	.0	.0
5	.0	-4.3	7.9	.0	.0	.0
6	.0	-4.3	7.9	.0	.0	.0
7	.0	-4.3	7.9	.0	.0	.0
8	.0	-31.9	63.1	.0	.0	.0
9	.0	-31.9	63.1	.0	.0	.0
10	.0	-31.9	63.1	.0	.0	.0
11	.0	-31.9	63.1	.0	.0	.0
12	.0	-31.9	63.1	.0	.0	.0
13	.0	-31.9	63.1	.0	.0	.0
14	.0	-31.9	63.1	.0	.0	.0
15	.0	-6.2	-11.5	.0	.0	.0
16	.0	-6.2	-11.5	.0	.0	.0
17	.0	-6.2	-11.5	.0	.0	.0
18	.0	-6.2	-11.5	.0	.0	.0
19	.0	-6.2	-11.5	.0	.0	.0
20	.0	-6.2	-11.5	.0	.0	.0
21	.0	-6.2	-11.5	.0	.0	.0
22	.0	21.4	43.7	.0	.0	.0
23	.0	21.4	43.7	.0	.0	.0
24	.0	21.4	43.7	.0	.0	.0
25	.0	21.4	43.7	.0	.0	.0
26	.0	21.4	43.7	.0	.0	.0
27	.0	21.4	43.7	.0	.0	.0
28	.0	21.4	43.7	.0	.0	.0

LOAD CASE - 8

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	.2	-1.5	.0	.0	.0

2	.0	.2	-1.5	.0	.0	.0
3	.0	.2	-1.5	.0	.0	.0
4	.0	.2	-1.5	.0	.0	.0
5	.0	.2	-1.5	.0	.0	.0
6	.0	.2	-1.5	.0	.0	.0
7	.0	.2	-1.5	.0	.0	.0
8	.0	-39.6	78.1	.0	.0	.0
9	.0	-39.6	78.1	.0	.0	.0
10	.0	-39.6	78.1	.0	.0	.0
11	.0	-39.6	78.1	.0	.0	.0
12	.0	-39.6	78.1	.0	.0	.0
13	.0	-39.6	78.1	.0	.0	.0
14	.0	-39.6	78.1	.0	.0	.0
15	.0	-13.8	-26.5	.0	.0	.0
16	.0	-13.8	-26.5	.0	.0	.0
17	.0	-13.8	-26.5	.0	.0	.0
18	.0	-13.8	-26.5	.0	.0	.0
19	.0	-13.8	-26.5	.0	.0	.0
20	.0	-13.8	-26.5	.0	.0	.0
21	.0	-13.8	-26.5	.0	.0	.0
22	.0	25.9	53.1	.0	.0	.0
23	.0	25.9	53.1	.0	.0	.0
24	.0	25.9	53.1	.0	.0	.0
25	.0	25.9	53.1	.0	.0	.0
26	.0	25.9	53.1	.0	.0	.0
27	.0	25.9	53.1	.0	.0	.0
28	.0	25.9	53.1	.0	.0	.0

## PLANTERS - STATION ADDITION

## STABILITY ANALYSIS FOR SWL = 9.5 NGVD:

- FOR FAILURE SURFACE (B) (2), Vertical Pressure Req'd = 1520 psf

slab thickness = 2'-6"

$$wt = (2.5)(150 - 117) = 82.5 \text{ psf}$$

machinery floor = 3'

$$wt = (3)(150) = 450 \text{ psf}$$

$$\text{total wt} = 82.5 + 450 = 532.5 \quad \underline{\text{N.G.}}$$


- piles do not have tension connectors,

$\therefore$  T-wall is Req'd

LOCATION: <sup>75' (5)</sup> 95' from existing T-wall

- at edge of existing discharge basin slab

12 782  
12 783  
42 382  
42 383  
42 384  
42 385  
42 386  
42 387  
42 388  
42 389  
42 390  
42 391  
42 392  
42 393  
42 394  
42 395  
42 396  
42 397  
42 398  
42 399  
42 400  
42 401  
42 402  
42 403  
42 404  
42 405  
42 406  
42 407  
42 408  
42 409  
42 410  
42 411  
42 412  
42 413  
42 414  
42 415  
42 416  
42 417  
42 418  
42 419  
42 420  
42 421  
42 422  
42 423  
42 424  
42 425  
42 426  
42 427  
42 428  
42 429  
42 430  
42 431  
42 432  
42 433  
42 434  
42 435  
42 436  
42 437  
42 438  
42 439  
42 440  
42 441  
42 442  
42 443  
42 444  
42 445  
42 446  
42 447  
42 448  
42 449  
42 450  
42 451  
42 452  
42 453  
42 454  
42 455  
42 456  
42 457  
42 458  
42 459  
42 460  
42 461  
42 462  
42 463  
42 464  
42 465  
42 466  
42 467  
42 468  
42 469  
42 470  
42 471  
42 472  
42 473  
42 474  
42 475  
42 476  
42 477  
42 478  
42 479  
42 480  
42 481  
42 482  
42 483  
42 484  
42 485  
42 486  
42 487  
42 488  
42 489  
42 490  
42 491  
42 492  
42 493  
42 494  
42 495  
42 496  
42 497  
42 498  
42 499  
42 500  
42 501  
42 502  
42 503  
42 504  
42 505  
42 506  
42 507  
42 508  
42 509  
42 510  
42 511  
42 512  
42 513  
42 514  
42 515  
42 516  
42 517  
42 518  
42 519  
42 520  
42 521  
42 522  
42 523  
42 524  
42 525  
42 526  
42 527  
42 528  
42 529  
42 530  
42 531  
42 532  
42 533  
42 534  
42 535  
42 536  
42 537  
42 538  
42 539  
42 540  
42 541  
42 542  
42 543  
42 544  
42 545  
42 546  
42 547  
42 548  
42 549  
42 550  
42 551  
42 552  
42 553  
42 554  
42 555  
42 556  
42 557  
42 558  
42 559  
42 560  
42 561  
42 562  
42 563  
42 564  
42 565  
42 566  
42 567  
42 568  
42 569  
42 570  
42 571  
42 572  
42 573  
42 574  
42 575  
42 576  
42 577  
42 578  
42 579  
42 580  
42 581  
42 582  
42 583  
42 584  
42 585  
42 586  
42 587  
42 588  
42 589  
42 590  
42 591  
42 592  
42 593  
42 594  
42 595  
42 596  
42 597  
42 598  
42 599  
42 600  
42 601  
42 602  
42 603  
42 604  
42 605  
42 606  
42 607  
42 608  
42 609  
42 610  
42 611  
42 612  
42 613  
42 614  
42 615  
42 616  
42 617  
42 618  
42 619  
42 620  
42 621  
42 622  
42 623  
42 624  
42 625  
42 626  
42 627  
42 628  
42 629  
42 630  
42 631  
42 632  
42 633  
42 634  
42 635  
42 636  
42 637  
42 638  
42 639  
42 640  
42 641  
42 642  
42 643  
42 644  
42 645  
42 646  
42 647  
42 648  
42 649  
42 650  
42 651  
42 652  
42 653  
42 654  
42 655  
42 656  
42 657  
42 658  
42 659  
42 660  
42 661  
42 662  
42 663  
42 664  
42 665  
42 666  
42 667  
42 668  
42 669  
42 670  
42 671  
42 672  
42 673  
42 674  
42 675  
42 676  
42 677  
42 678  
42 679  
42 680  
42 681  
42 682  
42 683  
42 684  
42 685  
42 686  
42 687  
42 688  
42 689  
42 690  
42 691  
42 692  
42 693  
42 694  
42 695  
42 696  
42 697  
42 698  
42 699  
42 700  
42 701  
42 702  
42 703  
42 704  
42 705  
42 706  
42 707  
42 708  
42 709  
42 710  
42 711  
42 712  
42 713  
42 714  
42 715  
42 716  
42 717  
42 718  
42 719  
42 720  
42 721  
42 722  
42 723  
42 724  
42 725  
42 726  
42 727  
42 728  
42 729  
42 730  
42 731  
42 732  
42 733  
42 734  
42 735  
42 736  
42 737  
42 738  
42 739  
42 740  
42 741  
42 742  
42 743  
42 744  
42 745  
42 746  
42 747  
42 748  
42 749  
42 750  
42 751  
42 752  
42 753  
42 754  
42 755  
42 756  
42 757  
42 758  
42 759  
42 760  
42 761  
42 762  
42 763  
42 764  
42 765  
42 766  
42 767  
42 768  
42 769  
42 770  
42 771  
42 772  
42 773  
42 774  
42 775  
42 776  
42 777  
42 778  
42 779  
42 780  
42 781  
42 782  
42 783  
42 784  
42 785  
42 786  
42 787  
42 788  
42 789  
42 790  
42 791  
42 792  
42 793  
42 794  
42 795  
42 796  
42 797  
42 798  
42 799  
42 800  
42 801  
42 802  
42 803  
42 804  
42 805  
42 806  
42 807  
42 808  
42 809  
42 810  
42 811  
42 812  
42 813  
42 814  
42 815  
42 816  
42 817  
42 818  
42 819  
42 820  
42 821  
42 822  
42 823  
42 824  
42 825  
42 826  
42 827  
42 828  
42 829  
42 830  
42 831  
42 832  
42 833  
42 834  
42 835  
42 836  
42 837  
42 838  
42 839  
42 840  
42 841  
42 842  
42 843  
42 844  
42 845  
42 846  
42 847  
42 848  
42 849  
42 850  
42 851  
42 852  
42 853  
42 854  
42 855  
42 856  
42 857  
42 858  
42 859  
42 860  
42 861  
42 862  
42 863  
42 864  
42 865  
42 866  
42 867  
42 868  
42 869  
42 870  
42 871  
42 872  
42 873  
42 874  
42 875  
42 876  
42 877  
42 878  
42 879  
42 880  
42 881  
42 882  
42 883  
42 884  
42 885  
42 886  
42 887  
42 888  
42 889  
42 890  
42 891  
42 892  
42 893  
42 894  
42 895  
42 896  
42 897  
42 898  
42 899  
42 900  
42 901  
42 902  
42 903  
42 904  
42 905  
42 906  
42 907  
42 908  
42 909  
42 910  
42 911  
42 912  
42 913  
42 914  
42 915  
42 916  
42 917  
42 918  
42 919  
42 920  
42 921  
42 922  
42 923  
42 924  
42 925  
42 926  
42 927  
42 928  
42 929  
42 930  
42 931  
42 932  
42 933  
42 934  
42 935  
42 936  
42 937  
42 938  
42 939  
42 940  
42 941  
42 942  
42 943  
42 944  
42 945  
42 946  
42 947  
42 948  
42 949  
42 950  
42 951  
42 952  
42 953  
42 954  
42 955  
42 956  
42 957  
42 958  
42 959  
42 960  
42 961  
42 962  
42 963  
42 964  
42 965  
42 966  
42 967  
42 968  
42 969  
42 970  
42 971  
42 972  
42 973  
42 974  
42 975  
42 976  
42 977  
42 978  
42 979  
42 980  
42 981  
42 982  
42 983  
42 984  
42 985  
42 986  
42 987  
42 988  
42 989  
42 990  
42 991  
42 992  
42 993  
42 994  
42 995  
42 996  
42 997  
42 998  
42 999  
43 000



FLOODWALL SHEET PILE TYPE

I-WALLS @ GATES

MAX MOMENT = 19.2 <sup>k</sup>/ft wall

(from Eustis Report)

$$S_{req'd} = \frac{M}{0.65 f_y} = \frac{(19.2)(12)}{0.65(50)}$$

$$= 7.09 \text{ in}^3/\text{ft}$$

- use Casted CZ 67 S = 10.69 in<sup>3</sup>/ftBC#2 M<sub>MAX</sub> = 46 <sup>k</sup>·ft / ft wall


$$S_{req'd} = \frac{(46)(12)}{0.65(50)}$$

$$= 16.98 \text{ in}^3/\text{ft wall}$$

- use Casted CZ 107 S = 17.48 in<sup>3</sup>/ft wall

NO SHEETS ENTER  
42,381  
42,382  
42,383  
42,384  
42,385  
42,386  
42,387  
42,388  
42,389  
42,390  
42,391  
42,392  
42,393  
42,394  
42,395  
42,396  
42,397  
42,398  
42,399  
42,400  
42,401  
42,402  
42,403  
42,404  
42,405  
42,406  
42,407  
42,408  
42,409  
42,410  
42,411  
42,412  
42,413  
42,414  
42,415  
42,416  
42,417  
42,418  
42,419  
42,420  
42,421  
42,422  
42,423  
42,424  
42,425  
42,426  
42,427  
42,428  
42,429  
42,430  
42,431  
42,432  
42,433  
42,434  
42,435  
42,436  
42,437  
42,438  
42,439  
42,440  
42,441  
42,442  
42,443  
42,444  
42,445  
42,446  
42,447  
42,448  
42,449  
42,450  
42,451  
42,452  
42,453  
42,454  
42,455  
42,456  
42,457  
42,458  
42,459  
42,460  
42,461  
42,462  
42,463  
42,464  
42,465  
42,466  
42,467  
42,468  
42,469  
42,470  
42,471  
42,472  
42,473  
42,474  
42,475  
42,476  
42,477  
42,478  
42,479  
42,480  
42,481  
42,482  
42,483  
42,484  
42,485  
42,486  
42,487  
42,488  
42,489  
42,490  
42,491  
42,492  
42,493  
42,494  
42,495  
42,496  
42,497  
42,498  
42,499  
42,500  
42,501  
42,502  
42,503  
42,504  
42,505  
42,506  
42,507  
42,508  
42,509  
42,510  
42,511  
42,512  
42,513  
42,514  
42,515  
42,516  
42,517  
42,518  
42,519  
42,520  
42,521  
42,522  
42,523  
42,524  
42,525  
42,526  
42,527  
42,528  
42,529  
42,530  
42,531  
42,532  
42,533  
42,534  
42,535  
42,536  
42,537  
42,538  
42,539  
42,540  
42,541  
42,542  
42,543  
42,544  
42,545  
42,546  
42,547  
42,548  
42,549  
42,550  
42,551  
42,552  
42,553  
42,554  
42,555  
42,556  
42,557  
42,558  
42,559  
42,560  
42,561  
42,562  
42,563  
42,564  
42,565  
42,566  
42,567  
42,568  
42,569  
42,570  
42,571  
42,572  
42,573  
42,574  
42,575  
42,576  
42,577  
42,578  
42,579  
42,580  
42,581  
42,582  
42,583  
42,584  
42,585  
42,586  
42,587  
42,588  
42,589  
42,590  
42,591  
42,592  
42,593  
42,594  
42,595  
42,596  
42,597  
42,598  
42,599  
42,600  
42,601  
42,602  
42,603  
42,604  
42,605  
42,606  
42,607  
42,608  
42,609  
42,610  
42,611  
42,612  
42,613  
42,614  
42,615  
42,616  
42,617  
42,618  
42,619  
42,620  
42,621  
42,622  
42,623  
42,624  
42,625  
42,626  
42,627  
42,628  
42,629  
42,630  
42,631  
42,632  
42,633  
42,634  
42,635  
42,636  
42,637  
42,638  
42,639  
42,640  
42,641  
42,642  
42,643  
42,644  
42,645  
42,646  
42,647  
42,648  
42,649  
42,650  
42,651  
42,652  
42,653  
42,654  
42,655  
42,656  
42,657  
42,658  
42,659  
42,660  
42,661  
42,662  
42,663  
42,664  
42,665  
42,666  
42,667  
42,668  
42,669  
42,670  
42,671  
42,672  
42,673  
42,674  
42,675  
42,676  
42,677  
42,678  
42,679  
42,680  
42,681  
42,682  
42,683  
42,684  
42,685  
42,686  
42,687  
42,688  
42,689  
42,690  
42,691  
42,692  
42,693  
42,694  
42,695  
42,696  
42,697  
42,698  
42,699  
42,700  
42,701  
42,702  
42,703  
42,704  
42,705  
42,706  
42,707  
42,708  
42,709  
42,710  
42,711  
42,712  
42,713  
42,714  
42,715  
42,716  
42,717  
42,718  
42,719  
42,720  
42,721  
42,722  
42,723  
42,724  
42,725  
42,726  
42,727  
42,728  
42,729  
42,730  
42,731  
42,732  
42,733  
42,734  
42,735  
42,736  
42,737  
42,738  
42,739  
42,740  
42,741  
42,742  
42,743  
42,744  
42,745  
42,746  
42,747  
42,748  
42,749  
42,750  
42,751  
42,752  
42,753  
42,754  
42,755  
42,756  
42,757  
42,758  
42,759  
42,760  
42,761  
42,762  
42,763  
42,764  
42,765  
42,766  
42,767  
42,768  
42,769  
42,770  
42,771  
42,772  
42,773  
42,774  
42,775  
42,776  
42,777  
42,778  
42,779  
42,780  
42,781  
42,782  
42,783  
42,784  
42,785  
42,786  
42,787  
42,788  
42,789  
42,790  
42,791  
42,792  
42,793  
42,794  
42,795  
42,796  
42,797  
42,798  
42,799  
42,800  
42,801  
42,802  
42,803  
42,804  
42,805  
42,806  
42,807  
42,808  
42,809  
42,810  
42,811  
42,812  
42,813  
42,814  
42,815  
42,816  
42,817  
42,818  
42,819  
42,820  
42,821  
42,822  
42,823  
42,824  
42,825  
42,826  
42,827  
42,828  
42,829  
42,830  
42,831  
42,832  
42,833  
42,834  
42,835  
42,836  
42,837  
42,838  
42,839  
42,840  
42,841  
42,842  
42,843  
42,844  
42,845  
42,846  
42,847  
42,848  
42,849  
42,850  
42,851  
42,852  
42,853  
42,854  
42,855  
42,856  
42,857  
42,858  
42,859  
42,860  
42,861  
42,862  
42,863  
42,864  
42,865  
42,866  
42,867  
42,868  
42,869  
42,870  
42,871  
42,872  
42,873  
42,874  
42,875  
42,876  
42,877  
42,878  
42,879  
42,880  
42,881  
42,882  
42,883  
42,884  
42,885  
42,886  
42,887  
42,888  
42,889  
42,890  
42,891  
42,892  
42,893  
42,894  
42,895  
42,896  
42,897  
42,898  
42,899  
42,900  
42,901  
42,902  
42,903  
42,904  
42,905  
42,906  
42,907  
42,908  
42,909  
42,910  
42,911  
42,912  
42,913  
42,914  
42,915  
42,916  
42,917  
42,918  
42,919  
42,920  
42,921  
42,922  
42,923  
42,924  
42,925  
42,926  
42,927  
42,928  
42,929  
42,930  
42,931  
42,932  
42,933  
42,934  
42,935  
42,936  
42,937  
42,938  
42,939  
42,940  
42,941  
42,942  
42,943  
42,944  
42,945  
42,946  
42,947  
42,948  
42,949  
42,950  
42,951  
42,952  
42,953  
42,954  
42,955  
42,956  
42,957  
42,958  
42,959  
42,960  
42,961  
42,962  
42,963  
42,964  
42,965  
42,966  
42,967  
42,968  
42,969  
42,970  
42,971  
42,972  
42,973  
42,974  
42,975  
42,976  
42,977  
42,978  
42,979  
42,980  
42,981  
42,982  
42,983  
42,984  
42,985  
42,986  
42,987  
42,988  
42,989  
42,990  
42,991  
42,992  
42,993  
42,994  
42,995  
42,996  
42,997  
42,998  
42,999  
43,000


Made in U.S.A.



# PLANTERS - ORIGINAL STATION - PUMPS 1-5

- PUT T-WALL AT EDGE OF EXISTING DISCHARGE BASIN SLAB.


500 SHEETS FULL SIZE SQUARE  
 400 SHEETS FULL SIZE SQUARE  
 300 SHEETS FULL SIZE SQUARE  
 200 SHEETS FULL SIZE SQUARE  
 100 SHEETS FULL SIZE SQUARE  
 50 SHEETS FULL SIZE SQUARE  
 20 SHEETS FULL SIZE SQUARE  
 10 SHEETS FULL SIZE SQUARE  
 5 SHEETS FULL SIZE SQUARE  
 2 SHEETS FULL SIZE SQUARE  
 1 SHEET FULL SIZE SQUARE  
 200 RECYCLED WHITE  
 200 RECYCLED WHITE  
 Made in U.S.A.



T-WALL LOADING CASES:

- Case I: Static water pressure to SWL, no wind, impervious sheet pile cut-off (100% forces)
- Case II: Static water pressure to SWL, no wind, pervious sheet pile cut-off (100% forces)
- Case III: Static water pressure to SWL+2', no wind, impervious sheet pile (75% forces)
- Case IV: Static water pressure to SWL+2', no wind, pervious sheet pile (75% forces)
- Case V: water at low water level, no wind, (100% forces)
- Case VI: Water at low water level, wind from flood side (75%)

NATIONAL BRAND  
 MANUFACTURED BY THE  
 NATIONAL BRAND STEEL PILING COMPANY  
 INC. 2001 JEFFERSON AVENUE  
 ST. LOUIS, MO 63103  
 PHONE (314) 862-1000  
 FAX (314) 862-1001  
 WWW.NATIONALBRAND.COM



## DEAD LOADS (PER LINEAR FT.)

STEM:  $(22')(2')(0.150 \text{ }^{\circ}/\text{ft}^2) =$

6.6  $^{\circ}/\text{ft}$

BASE  $(15)(2.5)(0.150) =$

5.63

## WATER OVER BASE:

SWL:  $(11)(20)(0.064) =$

14.08

SWL+2':  $(11)(22)(0.064) =$

15.49

LOW WATER:  $(11)(10.5)(0.064) =$

7.39

## SAND ON P/S:

$(2')(4')(0.120) =$

0.96  $^{\circ}/\text{ft}$

13 797  
43 360  
43 362  
43 368  
43 392  
43 393  
43 395

200 SHEETS FULL  
50 SHEETS FULL  
100 SHEETS FULL  
200 SHEETS FULL  
100 REFLECTED WHITE  
200 REFLECTED WHITE


3 SQUARE  
5 SQUARE  
5 SQUARE  
5 SQUARE  
5 SQUARE

Manufactured in U.S.A.



WATER LOADS:

SWL = 9.5 NGVD :




@SWL:  
 $p = (22.5)(.064)$   
 $= 1.44 \text{ c/ft ft}$

@SWL + 2':  
 $p = (24.5)(.064)$   
 $= 1.57 \text{ c/ft ft}$



@LOW WATER:  
 $p = (13)(.064)$   
 $= 0.83 \text{ c/ft ft}$

100 SHEETS FULL 8 SQUARE  
 100 SHEETS FULL 5 SQUARE  
 100 SHEETS FULL 3 SQUARE  
 200 SHEETS EYE-EASE 5 SQUARE  
 42-388 100 RECYCLED WHITE 5 SQUARE  
 42-392 200 RECYCLED WHITE 3 SQUARE  
 Made in U.S.A.



SWL + 2'

LOW WATER: (EL. 0.0 NGVD)





WIND LOADS:

FROM FLOOD SIDE @ LOW WATER:

(50 psf)(11.5') = 575 #/FT

50 SHEETS FULL 1/2 SQUARE  
50 SHEETS 1/4 LEAD 3/4 SQUARE  
100 SHEETS 1/4 LEAD 3/4 SQUARE  
200 SHEETS 1/4 LEAD 3/4 SQUARE  
200 SHEETS 1/4 LEAD 3/4 SQUARE  
200 RECYCLED WHITE 3/4 SQUARE

15 IN  
42 361  
42 361  
42 369  
42 399  
42 399  
MADE IN U.S.A.






LOAD COMBINATIONS

LOADING CASE	DESCRIPTION	FORCES		MOMENTS
		F <sub>x</sub>	F <sub>z</sub>	M <sub>y-y</sub>
I	DL		27.27	-7.79
	DL, SWL, IMP. S/P	16.20		-121.5
	100%		-7.92	-37.62
	TOTAL	16.20	19.35	-166.91
	FOR 52'	842.4	1006.20	-8679.32
II	DL		27.27	-7.79
	DL, SWL, PER S/P	16.20		-121.5
	100%		-10.80	-27.00
	TOTAL	16.20	16.47	-156.40
	FOR 52'	842.4	856.44	-8132.80
III	DL		28.68	-4.96
	DL, SWL+2', IMP. S/P	19.23		-157.11
	75%		-8.64	-41.04
	TOTAL	19.23	20.04	-203.11
	75%	14.42	15.03	-152.33
	FOR 52'	749.84	781.56	-7921.16
IV	DL		28.68	-4.96
	DL, SWL+2', PER. S/P	19.23		-157.11
	75%		-11.78	-29.45
	TOTAL	19.23	16.90	-191.52
	75%	14.42	12.68	-143.64
	FOR 52'	749.84	659.36	-7469.27
V	DL		20.58	-21.16
	DL, LOW WATER, IMP. S/P	5.40		-23.38
	100%		-4.56	-21.66
	TOTAL	5.40	16.02	-66.20
	FOR 52'	280.8	833.04	-3442.40
VI	DL		20.58	-21.16
	DL, LOW WATER, IMP. S/P, WIND	5.40		-23.38
	75%		-4.56	-21.66
	WIND	0.58		-10.88
	TOTAL	5.98	16.02	-77.08
	75%	4.48	12.02	-57.81
	FOR 52'	232.96	625.04	-3006.12

500 SHEETS FULLER 8 SQUARE  
 100 SHEETS FULLER 12 SQUARE  
 100 SHEETS FULLER 18 SQUARE  
 100 SHEETS FULLER 24 SQUARE  
 200 SHEETS EYE CASE 8 SQUARE  
 200 SHEETS EYE CASE 12 SQUARE  
 200 RECYCLED WHITE 8 SQUARE  
 200 RECYCLED WHITE 12 SQUARE  
 200 RECYCLED WHITE 18 SQUARE  
 200 RECYCLED WHITE 24 SQUARE  
 Made in U.S.A.



00

SOIL CONSTANT:

-PILE CAPACITY ABOVE EL. -31.5 IS TO BE IGNORED.

-CALCULATE ES USING WEIGHTED AVERAGE BELOW EL. -31.5:

$$\frac{K_h \times B}{DC} = \frac{[(167)(8.5') + (178)(15) + (222)(5) + 311(11)]}{39.5'}$$

$$\frac{K_h \times B}{DC} = 218$$

$$C = 1.0$$

$$D = 0.21$$

- use 14 piles @ 4' spacing:

$$AB = 48''$$

$$14A = 48$$


$$A = 3.43$$

$$ES = K_h \times B = 218(1)(.21) = 45.78$$

$\frac{D}{A}$	$\frac{A}{D}$
.25	3
0.21	3.43
.40	4

- run CPGA FOR A 52' LENGTH OF WALL

100 SHEETS FULLER SQUARE  
 50 SHEETS W/LEASER SQUARE  
 100 SHEETS W/LEASER SQUARE  
 200 SHEETS W/LEASER SQUARE  
 200 SHEETS W/LEASER SQUARE  
 200 RECYCLED WHITE SQUARE  
 200 RECYCLED WHITE SQUARE  
 Made in U.S.A.



AXIAL AND HORIZONTAL RESISTANCE OF BATTER PILES

ESTIMATED FROM ALLOWABLE VERTICAL LOAD CAPACITY

L = VERTICAL COMPONENT OF BATTER PILE EMBEDMENT LENGTH

V = ESTIMATED ALLOWABLE SINGLE PILE LOAD CAPACITY OF A PILE DRIVEN VERTICALLY WITH EMBEDMENT LENGTH, L.

B = BATTER OF PILE EXPRESSED AS A RATIO OF VERTICAL DISTANCE TO ONE FOOT HORIZONTAL DISTANCE.

H = HORIZONTAL RESISTANCE OF BATTER PILE ESTIMATED AS FOLLOWS:

$$H = \frac{V}{B}$$


A = ALLOWABLE AXIAL PILE LOAD CAPACITY OF A SINGLE BATTER PILE ESTIMATED AS FOLLOWS:

$$A = \sqrt{V^2 \left(1 + \frac{1}{B^2}\right)}$$

$$A = \sqrt{(72)^2 (1.25)} = 80^k$$


$$A = \sqrt{(54)^2 (1.25)} = 60^k$$

NOTE: THE AXIAL LOAD RESISTANCE OF A VERTICAL PILE, V, IS DEPENDENT ON THE TYPE OF LOADING--TENSION OR COMPRESSION. CAUTION SHOULD BE EXERCISED TO INSURE THAT THE CORRECT VERTICAL CAPACITY IS USED.





PILE SPACINGS

13-782 600 SHEETS FULLER 5 SQUARE  
42-381 50 SHEETS EYE-GLASS 6 SQUARE  
42-382 100 SHEETS EYE-GLASS 6 SQUARE  
42-383 100 SHEETS EYE-GLASS 6 SQUARE  
42-384 100 SHEETS EYE-GLASS 6 SQUARE  
42-385 100 RECYCLED WHITE 5 SQUARE  
42-386 200 RECYCLED WHITE 5 SQUARE  
Made in U.S.A.



1	6	-24.375	0
2		-20.625	
3		-16.875	
4		-13.125	
5		-9.375	
6		-5.625	
7		1.875	
8			
9			
10			
11			
12			
13			
14			
15	2	-22.50	
16		-15	
17		-7.5	
18		0	
19			
20			
21			
22	-6	-22.5	
23		-18	
24		-13.5	
25		-9	
26		-4.5	
27		0	
28			
29			
30			
31			
32			



#	x	y
1	6	23.375
2	6	19.125
3	6	14.875
4	6	10.625
5	6	6.375
6	6	2.125
7	6	-2.125
8	6	-6.375
9	6	-10.625
10	6	-14.875
11	6	-19.125
12	6	-23.375
13	2	-21.25
14	2	-12.75
15	2	+4.25
16	2	-4.25
17	2	-12.75
18	2	-21.25
19	-6	24
20	-6	20
21	-6	16
22	-6	12
23	-6	8
24	-6	4
25	-6	0
26	-6	-4
27	-6	-8
28	-6	-12
29	-6	-16
30	-6	-20
31	-6	-24

14 7 11 = 32

# PRELIMINARY

U.S ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA

REACH 3

ALLOWABLE PILE LOAD CAPACITIES  
SQUARE PRECAST, PRESTRESSED CONCRETE PILES  
TOP OF PILE AND DREDGE DEPTH AT EL -10.5

SIZE	PILE TIP ELEVATION IN FEET NGVD	ALLOWABLE PILE LOAD CAPACITY IN TONS FACTOR OF SAFETY $\approx 2$	
		COMPRESSION	TENSION
12-In. Square	-39	12	9
	-49	16	12
	-59	23	16
	-69	30	22
14-In. Square	-39	15	11
	-49	20	15
	-59	27	20
	-69	36	27
16-In. Square	-39	17	12
	-49	23	16
	-59	31	23
	-69	41	30

These allowable pile load capacities are suitable for piles supporting new T-wall at Units 1 through 5 of Planters Pump Station.

# PRELIMINARY

EUSTIS ENGINEERING COMPANY, INC.

1010 PLANTERS PUMP STATION FRONTAL PROTECTION TWALL  
1020 PROP 4030 3201 3201 196 2 0 ALL  
1030 SOIL ES 0.046 LEN 63 0 ALL  
1040 PIN ALL  
1050 DLS S 80 60 600.2 223.1 132.6 1510 1166.8 H 14 ALL  
1060 ASC S 196 457 0.816 0.856 2 0 ALL  
1070 BATTER 2 ALL  
1080 ANGLE 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
1085 ANGLE 0 16 17 18 19 20 21  
1090 ANGLE 180 22 23 24 25 26 27 28 29 30 31 32  
1110 PILE 1 6 -24.375 0  
1111 PILE 2 6 -20.625 0  
1112 PILE 3 6 -16.875 0  
1113 PILE 4 6 -13.125 0  
1114 PILE 5 6 -9.375 0  
1120 PILE 6 6 -5.625 0  
1121 PILE 7 6 -1.875 0  
1122 PILE 8 6 1.875 0  
1123 PILE 9 6 5.625 0  
1124 PILE 10 6 9.375 0  
1130 PILE 11 6 13.125 0  
1131 PILE 12 6 16.875 0  
1132 PILE 13 6 20.625 0  
1133 PILE 14 6 24.375 0  
1134 PILE 15 2 -20.5 0  
1140 PILE 16 2 -15.0 0  
1141 PILE 17 2 -7.5 0  
1142 PILE 18 2 0 0  
1143 PILE 19 2 7.5 0  
1144 PILE 20 2 15.0 0  
1150 PILE 21 2 20.5 0  
1151 PILE 22 -6 -22.5 0  
1152 PILE 23 -6 -18.0 0  
1153 PILE 24 -6 -13.5 0  
1154 PILE 25 -6 -9.0 0  
1160 PILE 26 -6 -4.5 0  
1161 PILE 27 -6 0 0  
1162 PILE 28 -6 4.5 0  
1163 PILE 29 -6 9 0  
1164 PILE 30 -6 13.5 0  
1170 PILE 31 -6 18 0  
1180 PILE 32 -6 22.5 0  
1210 LOAD 1 842.4 0 1006.2 0 -8679.32 0  
1220 LOAD 2 842.4 0 856.44 0 -8132.8 0  
1230 LOAD 3 749.84 0 781.56 0 -7921.16 0  
1240 LOAD 4 749.84 0 659.36 0 -7469.28 0  
1250 LOAD 5 280.8 0 833.04 0 -3442.4 0  
1260 LOAD 6 232.96 0 625.04 0 -3006.12 0  
1280 FOUT 1 2 3 4 5 6 7 PPSOUT1  
1290 PFO ALL  
1300 FPL PPSOUT2



\*\*\*\*\*  
 \* CORPS PROGRAM # X0080 \* CPGA - CASE PILE GROUP ANALYSIS PROGRAM  
 \* VERSION NUMBER # 86/09/02-A \* RUN DATE 01-23-98 RUN TIME 16:28:30  
 \*\*\*\*\*

PLANTERS PUMP STATION FRONTAL PROTECTION TWALL

THERE ARE 32 PILES AND  
 6 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = {  $\begin{matrix} X & Y & Z \\ \hline -6.00 & -24.38 & .00 \\ 6.00 & 24.38 & .00 \end{matrix}$  }

\*\*\*\*\*

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40300E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.46000E-01	L	.63000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	6.00	-24.38	.00	2.00	.00	63.00	P
2	6.00	-20.63	.00	2.00	.00	63.00	P
3	6.00	-16.88	.00	2.00	.00	63.00	P
4	6.00	-13.13	.00	2.00	.00	63.00	P
5	6.00	-9.38	.00	2.00	.00	63.00	P
6	6.00	-5.63	.00	2.00	.00	63.00	P

7	6.00	-1.88	.00	2.00	.00	63.00	P
8	6.00	1.88	.00	2.00	.00	63.00	P
9	6.00	5.63	.00	2.00	.00	63.00	P
10	6.00	9.38	.00	2.00	.00	63.00	P
11	6.00	13.13	.00	2.00	.00	63.00	P
12	6.00	16.88	.00	2.00	.00	63.00	P
13	6.00	20.63	.00	2.00	.00	63.00	P
14	6.00	24.38	.00	2.00	.00	63.00	P
15	2.00	-20.50	.00	2.00	.00	63.00	P
16	2.00	-15.00	.00	2.00	.00	63.00	P
17	2.00	-7.50	.00	2.00	.00	63.00	P
18	2.00	.00	.00	2.00	.00	63.00	P
19	2.00	7.50	.00	2.00	.00	63.00	P
20	2.00	15.00	.00	2.00	.00	63.00	P
21	2.00	20.50	.00	2.00	.00	63.00	P
22	-6.00	-22.50	.00	2.00	180.00	63.00	P
23	-6.00	-18.00	.00	2.00	180.00	63.00	P
24	-6.00	-13.50	.00	2.00	180.00	63.00	P
25	-6.00	-9.00	.00	2.00	180.00	63.00	P
26	-6.00	-4.50	.00	2.00	180.00	63.00	P
27	-6.00	.00	.00	2.00	180.00	63.00	P
28	-6.00	4.50	.00	2.00	180.00	63.00	P
29	-6.00	9.00	.00	2.00	180.00	63.00	P
30	-6.00	13.50	.00	2.00	180.00	63.00	P
31	-6.00	18.00	.00	2.00	180.00	63.00	P
32	-6.00	22.50	.00	2.00	180.00	63.00	P
						-----	
						2016.00	

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	842.4	.0	1006.2	.0	-8679.3	.0
2	842.4	.0	856.4	.0	-8132.8	.0
3	749.8	.0	781.6	.0	-7921.2	.0
4	749.8	.0	659.4	.0	-7469.3	.0
5	280.8	.0	833.0	.0	-3442.4	.0
6	233.0	.0	625.0	.0	-3006.1	.0

\*\*\*\*\*

ORIGINAL FILE GROUP STIFFNESS MATRIX

.13481E+05	.40109E-03	.83417E+04	.00000E+00	-.16416E+07	.00000E+00
.40109E-03	.13469E+03	-.80218E-03	-.37253E-08	-.57757E-01	.16163E+04
.83417E+04	-.80218E-03	.53521E+05	.15625E+00	-.64226E+06	.62500E-01
.15625E-01	-.37253E-08	.15625E+00	.16449E+10	-.20000E+01	-.28525E+09
-.16416E+07	-.57757E-01	-.64226E+06	.00000E+00	.22351E+09	.00000E+00
-.62500E-01	.16163E+04	.46875E-01	-.28525E+09	-.50000E+01	.41490E+09

LOAD CASE 1. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 11.  
LOAD CASE 2. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 11.

LOAD CASE 3. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 11.  
 LOAD CASE 4. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 11.  
 LOAD CASE 5. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 0.  
 LOAD CASE 6. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 7.

\*\*\*\*\*

PILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.2380E-01	-.1094E-06	.1201E-01	-.1993E-11	-.2567E-03	-.1810E-11
2	.7284E-01	-.1315E-06	.6037E-02	.1125E-11	.1157E-03	.1297E-10
3	.1369E-01	-.1162E-06	.8878E-02	-.1930E-11	-.2992E-03	-.3420E-11
4	.5415E-01	-.1342E-06	.3978E-02	.6380E-12	.8127E-05	.8767E-11
5	-.6218E-01	.4105E-07	.1818E-01	-.5783E-11	-.5893E-03	-.2266E-10
6	-.5864E-01	.2305E-07	.1420E-01	-.5041E-11	-.5513E-03	-.2064E-10

\*\*\*\*\*

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3\*EMIN) FOR CONCRETE PILES  
 B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
2	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
3	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
4	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
5	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
6	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
7	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
8	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
9	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
10	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
11	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
12	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
13	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
14	.0	.0	79.2	.0	-1.9	.0	.99	.37	1.26	1.22	#
15	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
16	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
17	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#

18	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
19	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
20	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
21	.1	.0	56.2	.0	-3.3	.0	.70	.18	1.15	1.10	#
22	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
23	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
24	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
25	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
26	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
27	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
28	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
29	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
30	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
31	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#
32	.1	.0	-34.3	.0	4.6	.0	.57	.43	.69	.63	#

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
2	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
3	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
4	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
5	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
6	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
7	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
8	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
9	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
10	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
11	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
12	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
13	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
14	.3	.0	63.8	.0	-16.4	.0	.80	.24	1.22	1.11	#
15	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
16	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
17	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
18	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
19	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
20	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
21	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
22	.3	.0	74.2	.0	-15.8	.0	.93	.33	1.27	1.16	#
23	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
24	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
25	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
26	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
27	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
28	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
29	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
30	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
31	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#
32	.3	.0	-41.2	.0	17.8	.0	.69	.54	.68	.57	#

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
------	---------	---------	---------	------------	------------	------------	-----	-----	------------	------------



21	..2	.0	57.7	.0	-11.6	.0	.72	.19	1.18	1.08	#
22	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
23	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
24	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
25	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
26	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
27	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
28	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
29	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
30	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
31	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	
32	..2	.0	-42.1	.0	12.5	.0	.70	.54	.67	.57	

LOAD CASE - 5

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
2	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
3	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
4	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
5	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
6	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
7	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
8	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
9	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
10	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
11	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
12	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
13	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
14	..3	.0	55.2	.0	20.5	.0	.69	.17	1.18	1.05	#
15	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
16	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
17	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
18	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
19	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
20	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
21	..3	.0	2.3	.0	17.4	.0	.03	.25	.91	.79	#
22	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
23	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
24	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
25	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
26	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
27	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
28	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
29	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
30	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
31	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#
32	..3	.0	12.8	.0	-16.5	.0	.16	.20	.96	.85	#

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	..3	.0	45.9	.0	19.0	.0	.57	.13	1.13	1.01	#
2	..3	.0	45.9	.0	19.0	.0	.57	.13	1.13	1.01	#

3		.00	45	.00	19	.00	.57	.13	1.13	1.01
4		.00	45	.00	19	.00	.57	.13	1.13	1.01
5		.00	45	.00	19	.00	.57	.13	1.13	1.01
6		.00	45	.00	19	.00	.57	.13	1.13	1.01
7		.00	45	.00	19	.00	.57	.13	1.13	1.01
8		.00	45	.00	19	.00	.57	.13	1.13	1.01
9		.00	45	.00	19	.00	.57	.13	1.13	1.01
10		.00	45	.00	19	.00	.57	.13	1.13	1.01
11		.00	45	.00	19	.00	.57	.13	1.13	1.01
12		.00	45	.00	19	.00	.57	.13	1.13	1.01
13		.00	45	.00	19	.00	.57	.13	1.13	1.01
14		.00	45	.00	19	.00	.57	.13	1.13	1.01
15		.00	33	.00	16	.11	.06	.08	.87	.76
16		.00	33	.00	16	.11	.06	.08	.87	.76
17		.00	33	.00	16	.11	.06	.08	.87	.76
18		.00	33	.00	16	.11	.06	.08	.87	.76
19		.00	33	.00	16	.11	.06	.08	.87	.76
20		.00	33	.00	16	.11	.06	.08	.87	.76
21		.00	33	.00	16	.11	.06	.08	.87	.76
22		.00	7	.00	15	.88	.09	.22	.93	.82
23		.00	7	.00	15	.88	.09	.22	.93	.82
24		.00	7	.00	15	.88	.09	.22	.93	.82
25		.00	7	.00	15	.88	.09	.22	.93	.82
26		.00	7	.00	15	.88	.09	.22	.93	.82
27		.00	7	.00	15	.88	.09	.22	.93	.82
28		.00	7	.00	15	.88	.09	.22	.93	.82
29		.00	7	.00	15	.88	.09	.22	.93	.82
30		.00	7	.00	15	.88	.09	.22	.93	.82
31		.00	7	.00	15	.88	.09	.22	.93	.82
32		.00	7	.00	15	.88	.09	.22	.93	.82

\*\*\*\*\*

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	33	.00	70.9	.00	.00	.00
2	33	.00	70.9	.00	.00	.00
3	33	.00	70.9	.00	.00	.00
4	33	.00	70.9	.00	.00	.00
5	33	.00	70.9	.00	.00	.00
6	33	.00	70.9	.00	.00	.00
7	33	.00	70.9	.00	.00	.00
8	33	.00	70.9	.00	.00	.00
9	33	.00	70.9	.00	.00	.00
10	33	.00	70.9	.00	.00	.00
11	33	.00	70.9	.00	.00	.00
12	33	.00	70.9	.00	.00	.00
13	33	.00	70.9	.00	.00	.00
14	33	.00	70.9	.00	.00	.00
15	33	.00	50.2	.00	.00	.00
16	33	.00	50.2	.00	.00	.00
17	33	.00	50.2	.00	.00	.00

18	25.2	.0	50.2	.0	.0	.0
19	25.2	.00	50.2	.00	.00	.00
20	25.2	.00	50.2	.00	.00	.00
21	25.2	.00	50.2	.00	.00	.00
22	15.4	.00	-30.7	.00	.00	.00
23	15.4	.00	-30.7	.00	.00	.00
24	15.4	.00	-30.7	.00	.00	.00
25	15.4	.00	-30.7	.00	.00	.00
26	15.4	.00	-30.7	.00	.00	.00
27	15.4	.00	-30.7	.00	.00	.00
28	15.4	.00	-30.7	.00	.00	.00
29	15.4	.00	-30.7	.00	.00	.00
30	15.4	.00	-30.7	.00	.00	.00
31	15.4	.00	-30.7	.00	.00	.00
32	15.4	.00	-30.7	.00	.00	.00

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	28.8	.0	56.9	.0	.0	.0
2	28.8	.00	56.9	.00	.00	.00
3	28.8	.000	56.9	.000	.000	.000
4	28.8	.0000	56.9	.0000	.0000	.0000
5	28.8	.00000	56.9	.00000	.00000	.00000
6	28.8	.000000	56.9	.000000	.000000	.000000
7	28.8	.0000000	56.9	.0000000	.0000000	.0000000
8	28.8	.00000000	56.9	.00000000	.00000000	.00000000
9	28.8	.000000000	56.9	.000000000	.000000000	.000000000
10	28.8	.0000000000	56.9	.0000000000	.0000000000	.0000000000
11	28.8	.00000000000	56.9	.00000000000	.00000000000	.00000000000
12	28.8	.000000000000	56.9	.000000000000	.000000000000	.000000000000
13	28.8	.0000000000000	56.9	.0000000000000	.0000000000000	.0000000000000
14	28.8	.00000000000000	56.9	.00000000000000	.00000000000000	.00000000000000
15	33.4	.00	66.2	.00	.00	.00
16	33.4	.00	66.2	.00	.00	.00
17	33.4	.00	66.2	.00	.00	.00
18	33.4	.00	66.2	.00	.00	.00
19	33.4	.00	66.2	.00	.00	.00
20	33.4	.00	66.2	.00	.00	.00
21	33.4	.00	66.2	.00	.00	.00
22	18.7	.00	-36.7	.00	.00	.00
23	18.7	.00	-36.7	.00	.00	.00
24	18.7	.00	-36.7	.00	.00	.00
25	18.7	.00	-36.7	.00	.00	.00
26	18.7	.00	-36.7	.00	.00	.00
27	18.7	.00	-36.7	.00	.00	.00
28	18.7	.00	-36.7	.00	.00	.00
29	18.7	.00	-36.7	.00	.00	.00
30	18.7	.00	-36.7	.00	.00	.00
31	18.7	.00	-36.7	.00	.00	.00
32	18.7	.00	-36.7	.00	.00	.00

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
------	---------	---------	---------	------------	------------	------------



1	31.1	.0	62.3	.0	.0	.0
2	31.1	.0	62.3	.0	.0	.0
3	31.1	.0	62.3	.0	.0	.0
4	31.1	.0	62.3	.0	.0	.0
5	31.1	.0	62.3	.0	.0	.0
6	31.1	.0	62.3	.0	.0	.0
7	31.1	.0	62.3	.0	.0	.0
8	31.1	.0	62.3	.0	.0	.0
9	31.1	.0	62.3	.0	.0	.0
10	31.1	.0	62.3	.0	.0	.0
11	31.1	.0	62.3	.0	.0	.0
12	31.1	.0	62.3	.0	.0	.0
13	31.1	.0	62.3	.0	.0	.0
14	31.1	.0	62.3	.0	.0	.0
15	19.2	.0	38.3	.0	.0	.0
16	19.2	.0	38.3	.0	.0	.0
17	19.2	.0	38.3	.0	.0	.0
18	19.2	.0	38.3	.0	.0	.0
19	19.2	.0	38.3	.0	.0	.0
20	19.2	.0	38.3	.0	.0	.0
21	19.2	.0	38.3	.0	.0	.0
22	16.3	.0	26.6	.0	.0	.0
23	16.3	.0	26.6	.0	.0	.0
24	16.3	.0	26.6	.0	.0	.0
25	16.3	.0	26.6	.0	.0	.0
26	16.3	.0	26.6	.0	.0	.0
27	16.3	.0	26.6	.0	.0	.0
28	16.3	.0	26.6	.0	.0	.0
29	16.3	.0	26.6	.0	.0	.0
30	16.3	.0	26.6	.0	.0	.0
31	16.3	.0	26.6	.0	.0	.0
32	16.3	.0	26.6	.0	.0	.0

LOAD CASE - 4

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	25.6	.0	50.8	.0	.0	.0
2	25.6	.0	50.8	.0	.0	.0
3	25.6	.0	50.8	.0	.0	.0
4	25.6	.0	50.8	.0	.0	.0
5	25.6	.0	50.8	.0	.0	.0
6	25.6	.0	50.8	.0	.0	.0
7	25.6	.0	50.8	.0	.0	.0
8	25.6	.0	50.8	.0	.0	.0
9	25.6	.0	50.8	.0	.0	.0
10	25.6	.0	50.8	.0	.0	.0
11	25.6	.0	50.8	.0	.0	.0
12	25.6	.0	50.8	.0	.0	.0
13	25.6	.0	50.8	.0	.0	.0
14	25.6	.0	50.8	.0	.0	.0
15	26.0	.0	51.5	.0	.0	.0
16	26.0	.0	51.5	.0	.0	.0
17	26.0	.0	51.5	.0	.0	.0
18	26.0	.0	51.5	.0	.0	.0
19	26.0	.0	51.5	.0	.0	.0
20	26.0	.0	51.5	.0	.0	.0

21	26.0	.0	51.5	.0	.0	.0
22	19.0	.00	-37.5	.00	.00	.00
23	19.0	.00	-37.5	.00	.00	.00
24	19.0	.00	-37.5	.00	.00	.00
25	19.0	.00	-37.5	.00	.00	.00
26	19.0	.00	-37.5	.00	.00	.00
27	19.0	.00	-37.5	.00	.00	.00
28	19.0	.00	-37.5	.00	.00	.00
29	19.0	.00	-37.5	.00	.00	.00
30	19.0	.00	-37.5	.00	.00	.00
31	19.0	.00	-37.5	.00	.00	.00
32	19.0	.0	-37.5	.0	.0	.0

LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	24.4	.0	49.5	.0	.0	.0
2	24.4	.00	49.5	.00	.00	.00
3	24.4	.00	49.5	.00	.00	.00
4	24.4	.00	49.5	.00	.00	.00
5	24.4	.00	49.5	.00	.00	.00
6	24.4	.00	49.5	.00	.00	.00
7	24.4	.00	49.5	.00	.00	.00
8	24.4	.00	49.5	.00	.00	.00
9	24.4	.00	49.5	.00	.00	.00
10	24.4	.00	49.5	.00	.00	.00
11	24.4	.00	49.5	.00	.00	.00
12	24.4	.00	49.5	.00	.00	.00
13	24.4	.00	49.5	.00	.00	.00
14	24.4	.00	49.5	.00	.00	.00
15	.8	.00	2.2	.00	.00	.00
16	.8	.00	2.2	.00	.00	.00
17	.8	.00	2.2	.00	.00	.00
18	.8	.00	2.2	.00	.00	.00
19	.8	.00	2.2	.00	.00	.00
20	.8	.00	2.2	.00	.00	.00
21	.8	.00	2.2	.00	.00	.00
22	-6.0	.00	11.3	.00	.00	.00
23	-6.0	.00	11.3	.00	.00	.00
24	-6.0	.00	11.3	.00	.00	.00
25	-6.0	.00	11.3	.00	.00	.00
26	-6.0	.00	11.3	.00	.00	.00
27	-6.0	.00	11.3	.00	.00	.00
28	-6.0	.00	11.3	.00	.00	.00
29	-6.0	.00	11.3	.00	.00	.00
30	-6.0	.00	11.3	.00	.00	.00
31	-6.0	.00	11.3	.00	.00	.00
32	-6.0	.0	11.3	.0	.0	.0

LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	20.3	.0	41.2	.0	.0	.0
2	20.3	.0	41.2	.0	.0	.0



MAX LOAD: = 79.2<sup>k</sup> C (LOAD CASE - 1)  
 = 42.1<sup>k</sup> T (LOAD CASE 4)

ALLOWABLES = 80<sup>k</sup> C = 79.2 OK  
 60<sup>k</sup> T = 42.1 OK


13-762 500 SHEETS PER 5 SQUARE  
 42-381 50 SHEETS PER 5 SQUARE  
 42-382 100 SHEETS PER 5 SQUARE  
 42-383 200 SHEETS PER 5 SQUARE  
 42-384 100 RECYCLED WHITE 5 SQUARE  
 42-385 200 RECYCLED WHITE 5 SQUARE



Made in U.S.A.

Addition

DESIGN OF T-WALL.



- 1219 PSF EL 9.5
- 1344 PSF EL 11.5
- 625 PSF EL 0.

CROSS-SECTION

SCALE 1" = 5.0'

WATER PR ON F/S

SWL 9.5      $P = 62.5 \times 19.5 = 1219 \text{ PSF}$   
 HWL 11.5      $P = 62.5 \times 21.5 = 1344 \text{ PSF}$   
 LWL 0.0      $P = 62.5 \times 10 = 625 \text{ PSF}$

Soil Pr. @ REST ON P/S

$= 0.55 \times 120 \times 6' = 396 \text{ PSF}$


13-742 500 SHEETS, FULLER 5 SQUARE  
 42-381 50 SHEETS, EYE-BARS 5 SQUARE  
 100-981 100 SHEETS, EYE-BARS 5 SQUARE  
 42-382 100 SHEETS, EYE-BARS 5 SQUARE  
 42-383 100 SHEETS, EYE-BARS 5 SQUARE  
 100-982 100 SHEETS, RECYCLED WHITE 5 SQUARE  
 42-389 200 SHEETS, RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.





13-782 500 SHEETS, MILLER & SQUARE  
42-381 50 SHEETS EYE-EASE® 5 SQUARE  
42-382 100 SHEETS EYE-EASE® 1 SQUARE  
42-389 200 SHEETS EYE-EASE® 5 SQUARE  
42-392 100 RECYCLED WHITE 5 SQUARE  
42-399 200 RECYCLED WHITE 5 SQUARE  
Made in U.S.A.

PROTECTED SIDE



FLOOD SIDE

MS

PLANTERS RAMP STA


3/26/98

2


B LOADS ON T.WALL.

- Clockwise  
+ Anticlockwise

500 SHEETS, FILLER 3 SQUARE  
 300 SHEETS, FILLER 2 SQUARE  
 400 SHEETS, FILLER 1 SQUARE  
 100 SHEETS, FILLER 0 SQUARE  
 200 SHEETS, FILLER 4 SQUARE  
 400 SHEETS, FILLER 5 SQUARE  
 1000 SHEETS, FILLER 6 SQUARE  
 400 SHEETS, FILLER 7 SQUARE  
 400 SHEETS, FILLER 8 SQUARE  
 400 SHEETS, FILLER 9 SQUARE  
 MADE IN U.S.A.




LOAD CASE NO	DESCRIPTION	+ F <sub>y</sub> KIPS	+ F <sub>z</sub> KIPS	- Y FT	- Z FT	MOMENT KX MX
1	DEAD LOAD					
	STEM: 1.0 X 19.0 X .15		2.85	2.0		+ 5.70 ↗
	1/2 X 1.5 X 19 X .15		2.14	3.00		+ 6.42 ↗
	BASE: 12 X 2.5 X .15		4.50	-	-	—
	TOTAL		9.49			+ 12.12 ↗
2	<u>WATER &amp; SOIL FORCES.</u> F/S.					
	S.W. L. EL 9.50					
	a) WT. OF WATER ON F/S 7.5' x 17' x .0625	-	7.97	-2.25	-	-17.93 ↘
	b) WT. OF SOIL ON F/S.	-	-	-	-	—
	c) LATERAL WATER PR. 1/2 X 1.219 X 19.5 @ EL. -3.50	11.89			6.5	+ 77.29 ↗
	2(a+b+c)	11.89	7.97			+ 59.36 ↗
3	<u>SOIL FORCES</u> P/S.					
	a) 2 x 3.5' x .120 KCF		0.84	5.0		+ 4.2 ↗
	b) 1/2 x .28' x 3.5' x .12		0.06	3.91		+ 0.23 ↗
	c) LATERAL SOIL PR. $\frac{.396}{2} \times 6'$	-1.2			2.0	- 3.6 KCF ↘
	3 a + b + c	-1.2	0.90			+ 0.83 ↗



-CLOCKWISE  
+ ANTICLOCKWISE

LD CASE	DESCRIPTION	+F <sub>y</sub>	+F <sub>z</sub>	$\bar{y}$ FT	$\bar{z}$ FT	MOMENT IK M <sub>x</sub>
4	<u>UPLIFT FORCES</u> W.S. EL 9.5					
	a) IMPERVIOUS SHEETPILE 1.219 x 4.25		-5.18	3.87		+ 20.05 ↷
	b) PERVIOUS SHEETPILE 1/2 x 1.219 x 12.0		-7.32	2.0		+ 14.68 ↷
5	<u>WATER + SOIL FORCES</u> F/S. H.W.-L. EL 11.50					
	a) WT. OF WATER ON F/S 7.5' x 19' x .0625		8.91	-2.25		20.05
	b) soil	-	-	-	-	-
	c) LATERAL WATER PR 1/2 x 1.344 x 21.5'	14.45			7.17	103.6
	5 a+b+c	14.45	8.91			123.65 ↷
6	<u>UPLIFT FORCES</u> W.S. EL 13.5					
	a) IMPERVIOUS SHEET PILE 1.344 x 4.25		-5.71	3.87		- 22.10 ↷
	b) PERVIOUS SHEETPILE 1/2 x 1.344 x 12.0		-8.06	2.0		- 16.12 ↷

13-762  
42-361  
42-362  
42-363  
42-364  
42-365  
42-366  
42-367  
42-368  
42-369  
42-370  
42-371  
42-372  
42-373  
42-374  
42-375  
42-376  
42-377  
42-378  
42-379  
42-380  
42-381  
42-382  
42-383  
42-384  
42-385  
42-386  
42-387  
42-388  
42-389  
42-390  
42-391  
42-392  
42-393  
42-394  
42-395  
42-396  
42-397  
42-398  
42-399  
42-400  
42-401  
42-402  
42-403  
42-404  
42-405  
42-406  
42-407  
42-408  
42-409  
42-410  
42-411  
42-412  
42-413  
42-414  
42-415  
42-416  
42-417  
42-418  
42-419  
42-420  
42-421  
42-422  
42-423  
42-424  
42-425  
42-426  
42-427  
42-428  
42-429  
42-430  
42-431  
42-432  
42-433  
42-434  
42-435  
42-436  
42-437  
42-438  
42-439  
42-440  
42-441  
42-442  
42-443  
42-444  
42-445  
42-446  
42-447  
42-448  
42-449  
42-450  
42-451  
42-452  
42-453  
42-454  
42-455  
42-456  
42-457  
42-458  
42-459  
42-460  
42-461  
42-462  
42-463  
42-464  
42-465  
42-466  
42-467  
42-468  
42-469  
42-470  
42-471  
42-472  
42-473  
42-474  
42-475  
42-476  
42-477  
42-478  
42-479  
42-480  
42-481  
42-482  
42-483  
42-484  
42-485  
42-486  
42-487  
42-488  
42-489  
42-490  
42-491  
42-492  
42-493  
42-494  
42-495  
42-496  
42-497  
42-498  
42-499  
42-500  
42-501  
42-502  
42-503  
42-504  
42-505  
42-506  
42-507  
42-508  
42-509  
42-510  
42-511  
42-512  
42-513  
42-514  
42-515  
42-516  
42-517  
42-518  
42-519  
42-520  
42-521  
42-522  
42-523  
42-524  
42-525  
42-526  
42-527  
42-528  
42-529  
42-530  
42-531  
42-532  
42-533  
42-534  
42-535  
42-536  
42-537  
42-538  
42-539  
42-540  
42-541  
42-542  
42-543  
42-544  
42-545  
42-546  
42-547  
42-548  
42-549  
42-550  
42-551  
42-552  
42-553  
42-554  
42-555  
42-556  
42-557  
42-558  
42-559  
42-560  
42-561  
42-562  
42-563  
42-564  
42-565  
42-566  
42-567  
42-568  
42-569  
42-570  
42-571  
42-572  
42-573  
42-574  
42-575  
42-576  
42-577  
42-578  
42-579  
42-580  
42-581  
42-582  
42-583  
42-584  
42-585  
42-586  
42-587  
42-588  
42-589  
42-590  
42-591  
42-592  
42-593  
42-594  
42-595  
42-596  
42-597  
42-598  
42-599  
42-600  
42-601  
42-602  
42-603  
42-604  
42-605  
42-606  
42-607  
42-608  
42-609  
42-610  
42-611  
42-612  
42-613  
42-614  
42-615  
42-616  
42-617  
42-618  
42-619  
42-620  
42-621  
42-622  
42-623  
42-624  
42-625  
42-626  
42-627  
42-628  
42-629  
42-630  
42-631  
42-632  
42-633  
42-634  
42-635  
42-636  
42-637  
42-638  
42-639  
42-640  
42-641  
42-642  
42-643  
42-644  
42-645  
42-646  
42-647  
42-648  
42-649  
42-650  
42-651  
42-652  
42-653  
42-654  
42-655  
42-656  
42-657  
42-658  
42-659  
42-660  
42-661  
42-662  
42-663  
42-664  
42-665  
42-666  
42-667  
42-668  
42-669  
42-670  
42-671  
42-672  
42-673  
42-674  
42-675  
42-676  
42-677  
42-678  
42-679  
42-680  
42-681  
42-682  
42-683  
42-684  
42-685  
42-686  
42-687  
42-688  
42-689  
42-690  
42-691  
42-692  
42-693  
42-694  
42-695  
42-696  
42-697  
42-698  
42-699  
42-700  
42-701  
42-702  
42-703  
42-704  
42-705  
42-706  
42-707  
42-708  
42-709  
42-710  
42-711  
42-712  
42-713  
42-714  
42-715  
42-716  
42-717  
42-718  
42-719  
42-720  
42-721  
42-722  
42-723  
42-724  
42-725  
42-726  
42-727  
42-728  
42-729  
42-730  
42-731  
42-732  
42-733  
42-734  
42-735  
42-736  
42-737  
42-738  
42-739  
42-740  
42-741  
42-742  
42-743  
42-744  
42-745  
42-746  
42-747  
42-748  
42-749  
42-750  
42-751  
42-752  
42-753  
42-754  
42-755  
42-756  
42-757  
42-758  
42-759  
42-760  
42-761  
42-762  
42-763  
42-764  
42-765  
42-766  
42-767  
42-768  
42-769  
42-770  
42-771  
42-772  
42-773  
42-774  
42-775  
42-776  
42-777  
42-778  
42-779  
42-780  
42-781  
42-782  
42-783  
42-784  
42-785  
42-786  
42-787  
42-788  
42-789  
42-790  
42-791  
42-792  
42-793  
42-794  
42-795  
42-796  
42-797  
42-798  
42-799  
42-800  
42-801  
42-802  
42-803  
42-804  
42-805  
42-806  
42-807  
42-808  
42-809  
42-810  
42-811  
42-812  
42-813  
42-814  
42-815  
42-816  
42-817  
42-818  
42-819  
42-820  
42-821  
42-822  
42-823  
42-824  
42-825  
42-826  
42-827  
42-828  
42-829  
42-830  
42-831  
42-832  
42-833  
42-834  
42-835  
42-836  
42-837  
42-838  
42-839  
42-840  
42-841  
42-842  
42-843  
42-844  
42-845  
42-846  
42-847  
42-848  
42-849  
42-850  
42-851  
42-852  
42-853  
42-854  
42-855  
42-856  
42-857  
42-858  
42-859  
42-860  
42-861  
42-862  
42-863  
42-864  
42-865  
42-866  
42-867  
42-868  
42-869  
42-870  
42-871  
42-872  
42-873  
42-874  
42-875  
42-876  
42-877  
42-878  
42-879  
42-880  
42-881  
42-882  
42-883  
42-884  
42-885  
42-886  
42-887  
42-888  
42-889  
42-890  
42-891  
42-892  
42-893  
42-894  
42-895  
42-896  
42-897  
42-898  
42-899  
42-900  
42-901  
42-902  
42-903  
42-904  
42-905  
42-906  
42-907  
42-908  
42-909  
42-910  
42-911  
42-912  
42-913  
42-914  
42-915  
42-916  
42-917  
42-918  
42-919  
42-920  
42-921  
42-922  
42-923  
42-924  
42-925  
42-926  
42-927  
42-928  
42-929  
42-930  
42-931  
42-932  
42-933  
42-934  
42-935  
42-936  
42-937  
42-938  
42-939  
42-940  
42-941  
42-942  
42-943  
42-944  
42-945  
42-946  
42-947  
42-948  
42-949  
42-950  
42-951  
42-952  
42-953  
42-954  
42-955  
42-956  
42-957  
42-958  
42-959  
42-960  
42-961  
42-962  
42-963  
42-964  
42-965  
42-966  
42-967  
42-968  
42-969  
42-970  
42-971  
42-972  
42-973  
42-974  
42-975  
42-976  
42-977  
42-978  
42-979  
42-980  
42-981  
42-982  
42-983  
42-984  
42-985  
42-986  
42-987  
42-988  
42-989  
42-990  
42-991  
42-992  
42-993  
42-994  
42-995  
42-996  
42-997  
42-998  
42-999  
43-000




Made in U.S.A.



LP CASE	DESCRIPTION	+F <sub>y</sub> K	+F <sub>z</sub> K	-y ft	-z ft	MOMENT MK
7	<u>WIND FORCE FROM F/S</u> 50 PSF X 11.8 @ EL 5.75	.58	-		15.75	9.06 <sup>IK</sup> ↷
8	<u>WIND FORCE FROM P/S</u> 50 PSF X 15.5' @ EL 3.75	.78	-		13.75	- 10.73 <sup>IK</sup> ↷
9	<u>WATER &amp; SOIL FORCES F/S</u> W.S. EL 0.0. LWL					
	a) WT. OF WATER ON F/S 7.5' X 7.5' X .0625		+3.52	-2.25		- 7.92 ↷
	b) WT. OF SOIL ON F/S	-	-	-	-	-
	c) LATERAL WATER PR 1/2 X .625 X 10.0' @ EL -6.67	3.13			3.33	10.42 ↷
	9 (a + b + c)	3.13	3.52			2.50 ↷
10	<u>UPLIFT FORCES</u>					
	a) Imp. sheet piles .625 X 4.25		-2.66	3.87		- 10.28 ↷
	b) Perw. sheet piles 1/2 X .625 X 12.0		-3.75	2.0		- 7.5 ↷

13.782 240 SHEETS FULLER 5 SQUARE  
 42.381 50 SHEETS EYE LEASE 5 SQUARE  
 42.382 100 SHEETS EYE LEASE 5 SQUARE  
 42.383 100 SHEETS EYE LEASE 5 SQUARE  
 42.384 100 SHEETS EYE LEASE 5 SQUARE  
 42.385 100 SHEETS EYE LEASE 5 SQUARE  
 42.386 100 SHEETS EYE LEASE 5 SQUARE  
 42.387 100 SHEETS EYE LEASE 5 SQUARE  
 42.388 100 SHEETS EYE LEASE 5 SQUARE  
 42.389 100 SHEETS EYE LEASE 5 SQUARE  
 42.390 100 SHEETS EYE LEASE 5 SQUARE  
 42.391 100 SHEETS EYE LEASE 5 SQUARE  
 42.392 100 SHEETS EYE LEASE 5 SQUARE  
 42.393 100 SHEETS EYE LEASE 5 SQUARE  
 42.394 100 SHEETS EYE LEASE 5 SQUARE  
 42.395 100 SHEETS EYE LEASE 5 SQUARE  
 42.396 100 SHEETS EYE LEASE 5 SQUARE  
 42.397 100 SHEETS EYE LEASE 5 SQUARE  
 42.398 100 SHEETS EYE LEASE 5 SQUARE  
 42.399 100 SHEETS EYE LEASE 5 SQUARE  
 42.400 100 SHEETS EYE LEASE 5 SQUARE  
 42.401 100 SHEETS EYE LEASE 5 SQUARE  
 42.402 100 SHEETS EYE LEASE 5 SQUARE  
 42.403 100 SHEETS EYE LEASE 5 SQUARE  
 42.404 100 SHEETS EYE LEASE 5 SQUARE  
 42.405 100 SHEETS EYE LEASE 5 SQUARE  
 42.406 100 SHEETS EYE LEASE 5 SQUARE  
 42.407 100 SHEETS EYE LEASE 5 SQUARE  
 42.408 100 SHEETS EYE LEASE 5 SQUARE  
 42.409 100 SHEETS EYE LEASE 5 SQUARE  
 42.410 100 SHEETS EYE LEASE 5 SQUARE  
 42.411 100 SHEETS EYE LEASE 5 SQUARE  
 42.412 100 SHEETS EYE LEASE 5 SQUARE  
 42.413 100 SHEETS EYE LEASE 5 SQUARE  
 42.414 100 SHEETS EYE LEASE 5 SQUARE  
 42.415 100 SHEETS EYE LEASE 5 SQUARE  
 42.416 100 SHEETS EYE LEASE 5 SQUARE  
 42.417 100 SHEETS EYE LEASE 5 SQUARE  
 42.418 100 SHEETS EYE LEASE 5 SQUARE  
 42.419 100 SHEETS EYE LEASE 5 SQUARE  
 42.420 100 SHEETS EYE LEASE 5 SQUARE  
 42.421 100 SHEETS EYE LEASE 5 SQUARE  
 42.422 100 SHEETS EYE LEASE 5 SQUARE  
 42.423 100 SHEETS EYE LEASE 5 SQUARE  
 42.424 100 SHEETS EYE LEASE 5 SQUARE  
 42.425 100 SHEETS EYE LEASE 5 SQUARE  
 42.426 100 SHEETS EYE LEASE 5 SQUARE  
 42.427 100 SHEETS EYE LEASE 5 SQUARE  
 42.428 100 SHEETS EYE LEASE 5 SQUARE  
 42.429 100 SHEETS EYE LEASE 5 SQUARE  
 42.430 100 SHEETS EYE LEASE 5 SQUARE  
 42.431 100 SHEETS EYE LEASE 5 SQUARE  
 42.432 100 SHEETS EYE LEASE 5 SQUARE  
 42.433 100 SHEETS EYE LEASE 5 SQUARE  
 42.434 100 SHEETS EYE LEASE 5 SQUARE  
 42.435 100 SHEETS EYE LEASE 5 SQUARE  
 42.436 100 SHEETS EYE LEASE 5 SQUARE  
 42.437 100 SHEETS EYE LEASE 5 SQUARE  
 42.438 100 SHEETS EYE LEASE 5 SQUARE  
 42.439 100 SHEETS EYE LEASE 5 SQUARE  
 42.440 100 SHEETS EYE LEASE 5 SQUARE  
 42.441 100 SHEETS EYE LEASE 5 SQUARE  
 42.442 100 SHEETS EYE LEASE 5 SQUARE  
 42.443 100 SHEETS EYE LEASE 5 SQUARE  
 42.444 100 SHEETS EYE LEASE 5 SQUARE  
 42.445 100 SHEETS EYE LEASE 5 SQUARE  
 42.446 100 SHEETS EYE LEASE 5 SQUARE  
 42.447 100 SHEETS EYE LEASE 5 SQUARE  
 42.448 100 SHEETS EYE LEASE 5 SQUARE  
 42.449 100 SHEETS EYE LEASE 5 SQUARE  
 42.450 100 SHEETS EYE LEASE 5 SQUARE  
 42.451 100 SHEETS EYE LEASE 5 SQUARE  
 42.452 100 SHEETS EYE LEASE 5 SQUARE  
 42.453 100 SHEETS EYE LEASE 5 SQUARE  
 42.454 100 SHEETS EYE LEASE 5 SQUARE  
 42.455 100 SHEETS EYE LEASE 5 SQUARE  
 42.456 100 SHEETS EYE LEASE 5 SQUARE  
 42.457 100 SHEETS EYE LEASE 5 SQUARE  
 42.458 100 SHEETS EYE LEASE 5 SQUARE  
 42.459 100 SHEETS EYE LEASE 5 SQUARE  
 42.460 100 SHEETS EYE LEASE 5 SQUARE  
 42.461 100 SHEETS EYE LEASE 5 SQUARE  
 42.462 100 SHEETS EYE LEASE 5 SQUARE  
 42.463 100 SHEETS EYE LEASE 5 SQUARE  
 42.464 100 SHEETS EYE LEASE 5 SQUARE  
 42.465 100 SHEETS EYE LEASE 5 SQUARE  
 42.466 100 SHEETS EYE LEASE 5 SQUARE  
 42.467 100 SHEETS EYE LEASE 5 SQUARE  
 42.468 100 SHEETS EYE LEASE 5 SQUARE  
 42.469 100 SHEETS EYE LEASE 5 SQUARE  
 42.470 100 SHEETS EYE LEASE 5 SQUARE  
 42.471 100 SHEETS EYE LEASE 5 SQUARE  
 42.472 100 SHEETS EYE LEASE 5 SQUARE  
 42.473 100 SHEETS EYE LEASE 5 SQUARE  
 42.474 100 SHEETS EYE LEASE 5 SQUARE  
 42.475 100 SHEETS EYE LEASE 5 SQUARE  
 42.476 100 SHEETS EYE LEASE 5 SQUARE  
 42.477 100 SHEETS EYE LEASE 5 SQUARE  
 42.478 100 SHEETS EYE LEASE 5 SQUARE  
 42.479 100 SHEETS EYE LEASE 5 SQUARE  
 42.480 100 SHEETS EYE LEASE 5 SQUARE  
 42.481 100 SHEETS EYE LEASE 5 SQUARE  
 42.482 100 SHEETS EYE LEASE 5 SQUARE  
 42.483 100 SHEETS EYE LEASE 5 SQUARE  
 42.484 100 SHEETS EYE LEASE 5 SQUARE  
 42.485 100 SHEETS EYE LEASE 5 SQUARE  
 42.486 100 SHEETS EYE LEASE 5 SQUARE  
 42.487 100 SHEETS EYE LEASE 5 SQUARE  
 42.488 100 SHEETS EYE LEASE 5 SQUARE  
 42.489 100 SHEETS EYE LEASE 5 SQUARE  
 42.490 100 SHEETS EYE LEASE 5 SQUARE  
 42.491 100 SHEETS EYE LEASE 5 SQUARE  
 42.492 100 SHEETS EYE LEASE 5 SQUARE  
 42.493 100 SHEETS EYE LEASE 5 SQUARE  
 42.494 100 SHEETS EYE LEASE 5 SQUARE  
 42.495 100 SHEETS EYE LEASE 5 SQUARE  
 42.496 100 SHEETS EYE LEASE 5 SQUARE  
 42.497 100 SHEETS EYE LEASE 5 SQUARE  
 42.498 100 SHEETS EYE LEASE 5 SQUARE  
 42.499 100 SHEETS EYE LEASE 5 SQUARE  
 42.500 100 SHEETS EYE LEASE 5 SQUARE



LOAD COMBINATIONS.

- clockwise  
+ anticlock

LD. COMB NO.	DESCRIPTION	$\leftarrow$ + F <sub>y</sub>	+ F <sub>z</sub> ↓	MOMENT M <sub>XX</sub>
1	Static Water pr with water at SWL. No wind, Imp. sheet pile plus soil on p/s.			
	LOAD CASE NO. 1		9.49	+ 12.12
	" 2(a+b+c)	+11.89	7.97	+ 59.36
	" 3(a+b+c)	-1.2	0.90	+ 0.83
	" 4 a)		- 5.18	+ 20.05
	TOTAL PER LFT	10.69	13.18	92.36
	TOTAL PER 40'	427.6	527.2	3694.4
2	Static Water pr. With water at SWL. No wind, perw. sheet piles with soil on p/s.			
	LOAD CASE NO. 1		9.49	+ 12.12
	" 2(a+b+c)	+11.89	7.97	+ 59.36
	" 3(a+b+c)	-1.2	0.90	+ 0.83
	" 4 (b)		- 7.32	+ 14.68
	TOTAL PER LFT	10.69	11.04	86.99
	TOTAL PER 40'0"	427.6	441.6	3479.6

LOAD COMBINATIONS.


LD. COMB NO.	DESCRIPTION	← +F <sub>y</sub>	+F <sub>z</sub> ↓	MOMENT M <sub>XX</sub>
3	Static water pr. with water at EL 11.5, No Wind Imp. sheet piles plus soil on P/s.  LOAD CASE NO. 1 5 (a+b+c) 3 (a+b+c) 6 a		9.49 8.91 0.90 -5.71	+12.12 +123.65 + 0.83 - 22.10
	TOTAL PER LFT 75% → TOTAL PER 40' x .75	13.25 397.5	13.59 407.7	114.50 3,435.0
4	Static water pr. with water at EL 11.5, No wind, Perw. sheet piles plus soil on P/s  LOAD CASE NO. 1 5 (a+b+c) 3 (a+b+c) 6 b		9.49 8.91 0.90 -8.06	+12.12 +123.65 + 0.83 -16.12
	TOTAL PER LFT 75% → TOTAL PER 40' x .75	13.25 397.5	11.24 337.2	120.48 3614.4

31,301  
 31,302  
 31,303  
 31,304  
 31,305  
 31,306  
 31,307  
 31,308  
 31,309  
 31,310  
 31,311  
 31,312  
 31,313  
 31,314  
 31,315  
 31,316  
 31,317  
 31,318  
 31,319  
 31,320  
 31,321  
 31,322  
 31,323  
 31,324  
 31,325  
 31,326  
 31,327  
 31,328  
 31,329  
 31,330  
 31,331  
 31,332  
 31,333  
 31,334  
 31,335  
 31,336  
 31,337  
 31,338  
 31,339  
 31,340  
 31,341  
 31,342  
 31,343  
 31,344  
 31,345  
 31,346  
 31,347  
 31,348  
 31,349  
 31,350  
 31,351  
 31,352  
 31,353  
 31,354  
 31,355  
 31,356  
 31,357  
 31,358  
 31,359  
 31,360  
 31,361  
 31,362  
 31,363  
 31,364  
 31,365  
 31,366  
 31,367  
 31,368  
 31,369  
 31,370  
 31,371  
 31,372  
 31,373  
 31,374  
 31,375  
 31,376  
 31,377  
 31,378  
 31,379  
 31,380  
 31,381  
 31,382  
 31,383  
 31,384  
 31,385  
 31,386  
 31,387  
 31,388  
 31,389  
 31,390  
 31,391  
 31,392  
 31,393  
 31,394  
 31,395  
 31,396  
 31,397  
 31,398  
 31,399  
 31,400  
 31,401  
 31,402  
 31,403  
 31,404  
 31,405  
 31,406  
 31,407  
 31,408  
 31,409  
 31,410  
 31,411  
 31,412  
 31,413  
 31,414  
 31,415  
 31,416  
 31,417  
 31,418  
 31,419  
 31,420  
 31,421  
 31,422  
 31,423  
 31,424  
 31,425  
 31,426  
 31,427  
 31,428  
 31,429  
 31,430  
 31,431  
 31,432  
 31,433  
 31,434  
 31,435  
 31,436  
 31,437  
 31,438  
 31,439  
 31,440  
 31,441  
 31,442  
 31,443  
 31,444  
 31,445  
 31,446  
 31,447  
 31,448  
 31,449  
 31,450  
 31,451  
 31,452  
 31,453  
 31,454  
 31,455  
 31,456  
 31,457  
 31,458  
 31,459  
 31,460  
 31,461  
 31,462  
 31,463  
 31,464  
 31,465  
 31,466  
 31,467  
 31,468  
 31,469  
 31,470  
 31,471  
 31,472  
 31,473  
 31,474  
 31,475  
 31,476  
 31,477  
 31,478  
 31,479  
 31,480  
 31,481  
 31,482  
 31,483  
 31,484  
 31,485  
 31,486  
 31,487  
 31,488  
 31,489  
 31,490  
 31,491  
 31,492  
 31,493  
 31,494  
 31,495  
 31,496  
 31,497  
 31,498  
 31,499  
 31,500  
 31,501  
 31,502  
 31,503  
 31,504  
 31,505  
 31,506  
 31,507  
 31,508  
 31,509  
 31,510  
 31,511  
 31,512  
 31,513  
 31,514  
 31,515  
 31,516  
 31,517  
 31,518  
 31,519  
 31,520  
 31,521  
 31,522  
 31,523  
 31,524  
 31,525  
 31,526  
 31,527  
 31,528  
 31,529  
 31,530  
 31,531  
 31,532  
 31,533  
 31,534  
 31,535  
 31,536  
 31,537  
 31,538  
 31,539  
 31,540  
 31,541  
 31,542  
 31,543  
 31,544  
 31,545  
 31,546  
 31,547  
 31,548  
 31,549  
 31,550  
 31,551  
 31,552  
 31,553  
 31,554  
 31,555  
 31,556  
 31,557  
 31,558  
 31,559  
 31,560  
 31,561  
 31,562  
 31,563  
 31,564  
 31,565  
 31,566  
 31,567  
 31,568  
 31,569  
 31,570  
 31,571  
 31,572  
 31,573  
 31,574  
 31,575  
 31,576  
 31,577  
 31,578  
 31,579  
 31,580  
 31,581  
 31,582  
 31,583  
 31,584  
 31,585  
 31,586  
 31,587  
 31,588  
 31,589  
 31,590  
 31,591  
 31,592  
 31,593  
 31,594  
 31,595  
 31,596  
 31,597  
 31,598  
 31,599  
 31,600  
 31,601  
 31,602  
 31,603  
 31,604  
 31,605  
 31,606  
 31,607  
 31,608  
 31,609  
 31,610  
 31,611  
 31,612  
 31,613  
 31,614  
 31,615  
 31,616  
 31,617  
 31,618  
 31,619  
 31,620  
 31,621  
 31,622  
 31,623  
 31,624  
 31,625  
 31,626  
 31,627  
 31,628  
 31,629  
 31,630  
 31,631  
 31,632  
 31,633  
 31,634  
 31,635  
 31,636  
 31,637  
 31,638  
 31,639  
 31,640  
 31,641  
 31,642  
 31,643  
 31,644  
 31,645  
 31,646  
 31,647  
 31,648  
 31,649  
 31,650  
 31,651  
 31,652  
 31,653  
 31,654  
 31,655  
 31,656  
 31,657  
 31,658  
 31,659  
 31,660  
 31,661  
 31,662  
 31,663  
 31,664  
 31,665  
 31,666  
 31,667  
 31,668  
 31,669  
 31,670  
 31,671  
 31,672  
 31,673  
 31,674  
 31,675  
 31,676  
 31,677  
 31,678  
 31,679  
 31,680  
 31,681  
 31,682  
 31,683  
 31,684  
 31,685  
 31,686  
 31,687  
 31,688  
 31,689  
 31,690  
 31,691  
 31,692  
 31,693  
 31,694  
 31,695  
 31,696  
 31,697  
 31,698  
 31,699  
 31,700  
 31,701  
 31,702  
 31,703  
 31,704  
 31,705  
 31,706  
 31,707  
 31,708  
 31,709  
 31,710  
 31,711  
 31,712  
 31,713  
 31,714  
 31,715  
 31,716  
 31,717  
 31,718  
 31,719  
 31,720  
 31,721  
 31,722  
 31,723  
 31,724  
 31,725  
 31,726  
 31,727  
 31,728  
 31,729  
 31,730  
 31,731  
 31,732  
 31,733  
 31,734  
 31,735  
 31,736  
 31,737  
 31,738  
 31,739  
 31,740  
 31,741  
 31,742  
 31,743  
 31,744  
 31,745  
 31,746  
 31,747  
 31,748  
 31,749  
 31,750  
 31,751  
 31,752  
 31,753  
 31,754  
 31,755  
 31,756  
 31,757  
 31,758  
 31,759  
 31,760  
 31,761  
 31,762  
 31,763  
 31,764  
 31,765  
 31,766  
 31,767  
 31,768  
 31,769  
 31,770  
 31,771  
 31,772  
 31,773  
 31,774  
 31,775  
 31,776  
 31,777  
 31,778  
 31,779  
 31,780  
 31,781  
 31,782  
 31,783  
 31,784  
 31,785  
 31,786  
 31,787  
 31,788  
 31,789  
 31,790  
 31,791  
 31,792  
 31,793  
 31,794  
 31,795  
 31,796  
 31,797  
 31,798  
 31,799  
 31,800  
 31,801  
 31,802  
 31,803  
 31,804  
 31,805  
 31,806  
 31,807  
 31,808  
 31,809  
 31,810  
 31,811  
 31,812  
 31,813  
 31,814  
 31,815  
 31,816  
 31,817  
 31,818  
 31,819  
 31,820  
 31,821  
 31,822  
 31,823  
 31,824  
 31,825  
 31,826  
 31,827  
 31,828  
 31,829  
 31,830  
 31,831  
 31,832  
 31,833  
 31,834  
 31,835  
 31,836  
 31,837  
 31,838  
 31,839  
 31,840  
 31,841  
 31,842  
 31,843  
 31,844  
 31,845  
 31,846  
 31,847  
 31,848  
 31,849  
 31,850  
 31,851  
 31,852  
 31,853  
 31,854  
 31,855  
 31,856  
 31,857  
 31,858  
 31,859  
 31,860  
 31,861  
 31,862  
 31,863  
 31,864  
 31,865  
 31,866  
 31,867  
 31,868  
 31,869  
 31,870  
 31,871  
 31,872  
 31,873  
 31,874  
 31,875  
 31,876  
 31,877  
 31,878  
 31,879  
 31,880  
 31,881  
 31,882  
 31,883  
 31,884  
 31,885  
 31,886  
 31,887  
 31,888  
 31,889  
 31,890  
 31,891  
 31,892  
 31,893  
 31,894  
 31,895  
 31,896  
 31,897  
 31,898  
 31,899  
 31,900  
 31,901  
 31,902  
 31,903  
 31,904  
 31,905  
 31,906  
 31,907  
 31,908  
 31,909  
 31,910  
 31,911  
 31,912  
 31,913  
 31,914  
 31,915  
 31,916  
 31,917  
 31,918  
 31,919  
 31,920  
 31,921  
 31,922  
 31,923  
 31,924  
 31,925  
 31,926  
 31,927  
 31,928  
 31,929  
 31,930  
 31,931  
 31,932  
 31,933  
 31,934  
 31,935  
 31,936  
 31,937  
 31,938  
 31,939  
 31,940  
 31,941  
 31,942  
 31,943  
 31,944  
 31,945  
 31,946  
 31,947  
 31,948  
 31,949  
 31,950  
 31,951  
 31,952  
 31,953  
 31,954  
 31,955  
 31,956  
 31,957  
 31,958  
 31,959  
 31,960  
 31,961  
 31,962  
 31,963  
 31,964  
 31,965  
 31,966  
 31,967  
 31,968  
 31,969  
 31,970  
 31,971  
 31,972  
 31,973  
 31,974  
 31,975  
 31,976  
 31,977  
 31,978  
 31,979  
 31,980  
 31,981  
 31,982  
 31,983  
 31,984  
 31,985  
 31,986  
 31,987  
 31,988  
 31,989  
 31,990  
 31,991  
 31,992  
 31,993  
 31,994  
 31,995  
 31,996  
 31,997  
 31,998  
 31,999  
 32,000  
 32,001  
 32,002  
 32,003  
 32,004  
 32,005  
 32,006  
 32,007  
 32,008  
 32,009  
 32,010  
 32,011  
 32,012  
 32,013  
 32,014  
 32,015  
 32,016  
 32,017  
 32,018  
 32,019  
 32,020  
 32,021  
 32,022  
 32,023  
 32,024  
 32,025  
 32,026  
 32,027  
 32,028  
 32,029  
 32,030  
 32,031  
 32,032  
 32,033  
 32,034  
 32,035  
 32,036  
 32,037  
 32,038  
 32,039  
 32,040  
 32,041  
 32,042  
 32,043  
 32,044  
 32,045  
 32,046  
 32,047  
 32,048  
 32,049  
 32,050  
 32,051  
 32,052  
 32,053  
 32,054  
 32,055  
 32,056  
 32,057  
 32,058  
 32,059  
 32,060  
 32,061  
 32,062  
 32,063  
 32,064  
 32,065  
 32,066  
 32,067  
 32,068  
 32,069  
 32,070  
 32,071  
 32,072  
 32,073  
 32,074  
 32,075  
 32,076  
 32,077  
 32,078  
 32,079  
 32,080  
 32,081  
 32,082  
 32,083  
 32,084  
 32,085  
 32,086  
 32,087  
 32,088  
 32,089  
 32,090  
 32,091  
 32,092  
 32,093  
 32,094  
 32,095  
 32,096  
 32,097  
 32,098  
 32,099  
 32,100  
 32,101  
 32,102  
 32,103  
 32,104  
 32,105  
 32,106  
 32,107  
 32,108  
 32,109  
 32,110  
 32,111  
 32,112  
 32,113  
 32,114  
 32,115  
 32,116  
 32,117  
 32,118  
 32,119  
 32,120  
 32,121  
 32,122  
 32,123  
 32,124  
 32,125  
 32,126  
 32,127  
 32,128  
 32,129  
 32,130  
 32,131  
 32,132  
 32,133  
 32,134  
 32,135  
 32,136  
 32,137  
 32,138  
 32,139  
 32,140  
 32,141  
 32,142  
 32,143  
 32,144  
 32,145  
 32,146  
 32,147  
 32,148  
 32,149  
 32,150  
 32,151  
 32,152  
 32,153  
 32,154  
 32,155  
 32,156  
 32,157  
 32,158  
 32,159  
 32,160  
 32,161  
 32,162  
 32,163  
 32,164  
 32,165  
 32,166  
 32,167  
 32,168  
 32,169  
 32,170  
 32,171  
 32,172  
 32,173  
 32,174  
 32,175  
 32,176  
 32,177  
 32,178  
 32,179  
 32,180  
 32,181  
 32,182  
 32,183  
 32,184  
 32,185  
 32,186  
 32,187  
 32,188  
 32,189  
 32,190  
 32,191  
 32,192  
 32,193  
 32,194  
 32,195  
 32,196  
 32,197  
 32,198  
 32,199  
 32,200  
 32,201  
 32,202  
 32,203  
 32,204  
 32,205  
 32,206  
 32,207  
 32,208  
 32,209  
 32,210  
 32,211  
 32,212  
 32,213  
 32,214  
 32,215  
 32,216  
 32,217  
 32,218  
 32,219  
 32,220  
 32,221  
 32,222  
 32,223  
 32,224  
 32,225  
 32,226  
 32,227  
 32,228  
 32,229  
 32,230  
 32,231  
 32,232  
 32,233  
 32,234  
 32,235  
 32,236  
 32,237  
 32,238  
 32,239  
 32,240  
 32,241  
 32,242  
 32,243  
 32,244  
 32,245  
 32,246  
 32,247  
 32,248  
 32,249  
 32,250  
 32,251  
 32,252  
 32,253  
 32,254  
 32,255  
 32,256  
 32,257  
 32,258  
 32,259  
 32,260  
 32,261  
 32,262  
 32,263  
 32,264  
 32,265  
 32,266  
 32,267  
 32,268  
 32,269  
 32,270  
 32,271  
 32,272  
 32,273  
 32,274  
 32,275  
 32,276  
 32,277  
 32,278  
 32,279  
 32,280  
 32,281  
 32,282  
 32,283  
 32,284  
 32,285  
 32,286  
 32,287  
 32,288  
 32,289  
 32,290  
 32,291  
 32,292  
 32,293  
 32,294  
 32,295  
 32,296  
 32,297  
 32,298  
 32,29

LOAD COMBINATIONS.

LD. COMB NO.	DESCRIPTION	← +F <sub>1</sub>	+F <sub>2</sub> ↓	MOMENT M <sub>XX</sub>
5	Static water pr. with water at LWL. NO wind imp sheet piles w/ soil on P/s.			
	LOAD CASE 1		9.49	+12.12
	" 9(a+b+c)	3.13	3.52	2.50
	" 3(a+b+c)	-1.2	0.90	+0.83
	" 10 a		-2.5	-10.0
	TOTAL PER LFT TOTAL PER 40'	1.93 77.2	11.41 456.4	5.45 218.0
6	Static water pr. with water @ LWL NO wind perw. sheet piles w/ soil on P/s.			
	LOAD CASE 1		9.49	+12.12
	" 9(a+b+c)	3.13	3.52	2.50
	" 3(a+b+c)	-1.2	0.90	+0.83
	" 10 b		-3.75	-7.50
	TOTAL PER LFT TOTAL PER 40'0"	1.93 77.2	10.16 406.4	7.95 318.0

11.00  
 12.00  
 13.00  
 14.00  
 15.00  
 16.00  
 17.00  
 18.00  
 19.00  
 20.00  
 21.00  
 22.00  
 23.00  
 24.00  
 25.00  
 26.00  
 27.00  
 28.00  
 29.00  
 30.00  
 31.00  
 32.00  
 33.00  
 34.00  
 35.00  
 36.00  
 37.00  
 38.00  
 39.00  
 40.00  
 41.00  
 42.00  
 43.00  
 44.00  
 45.00  
 46.00  
 47.00  
 48.00  
 49.00  
 50.00  
 51.00  
 52.00  
 53.00  
 54.00  
 55.00  
 56.00  
 57.00  
 58.00  
 59.00  
 60.00  
 61.00  
 62.00  
 63.00  
 64.00  
 65.00  
 66.00  
 67.00  
 68.00  
 69.00  
 70.00  
 71.00  
 72.00  
 73.00  
 74.00  
 75.00  
 76.00  
 77.00  
 78.00  
 79.00  
 80.00  
 81.00  
 82.00  
 83.00  
 84.00  
 85.00  
 86.00  
 87.00  
 88.00  
 89.00  
 90.00  
 91.00  
 92.00  
 93.00  
 94.00  
 95.00  
 96.00  
 97.00  
 98.00  
 99.00  
 100.00



LOAD COMBINATIONS.

42 781  
42 801  
42 811  
42 821  
42 831  
42 841  
42 851  
42 861  
42 871  
42 881  
42 891  
42 901  
42 911  
42 921  
42 931  
42 941  
42 951  
42 961  
42 971  
42 981  
42 991



LD. COMB NO.	DESCRIPTION	← + Fy	+ Fz ↓	MOMENT Mxx
7	Static Water pr. with water @ LWL Wind from F/s, new sheet piles soil on P/s.			
	LOAD COMB 5	1.93	10.16	7.95
	LOAD CASE 7	0.58		9.06
TOTAL PER LFT		2.51	10.16	17.01
TOTAL PER 40'		100.4	427.6	612
8	Static Water pr. with water @ LWL Wind from P/s, Imp sheet piles soil on P/s			
	LOAD COMB 5	1.93	11.41	5.45
	LOAD CASE 8	-0.78		-10.73
TOTAL PER LFT		1.15	11.41	- 5.28
TOTAL PER 40' 0"		46.0	456.40	- 211.20

PLANTER'S PUMP STA

11



10

100 Planters Pump Station T Wall

200 Prop 4074 3201 3201 196 2.0 0.0 ALL

300 SOI ES .039 LEN 60 0 ALL

320 AN ALL

410 DLS S 72 54 600 223 133 1510 1167 H 14  
 430 ASC S 196 457 0.816 0.856 1.75 0.0 ALL

440 BAT 2.0 ALL

450 AN4 270 1 TO 5

455 AN4 90 6 TO 20

460 PL 1 -17.5 -4.5 0.0

461 PIL 2 -17.5 1.0 0.0

463 PIL 11 -17.5 -4.5 0.0

465 Row X 6 1 5 @ 7.0

480 Row X 5 7 4 @ 8.75

485 Row X 6 12 5 @ 7.0

500 LoA 1 0 427.6 560.4 3605 0 0

510 LoA 2 0 427.6 462.8 3411.2 0 0

520 LoA 3 0 397.5 433.5 3402 0 0

530 LoA 4 0 397.5 353.1 3563 0 0

600 Fou 1 2 3 4 5 6 TWALLP01

610 PFO ALL

620 FPL N

42-303 AN UNCLIPPED LANS 3 SQUARE  
 42-304 UNRECYCLED WHITE 3 SQUARE  
 42-305 UNRECYCLED WHITE 3 SQUARE  
 Made in U.S.A.

FROM  
 PILE  
 LIBRARY  
 SUPP.  
 BY COE

SUMMARY OF PILE LOADS.

REF. FILE PPSTW10

DT MAR. 30 - 98  
(11:22:34)

	DESCRIPTION	MAX. COMP	MAX. TENS.	CBF	MAX. COMP STR	MAX TENS. STR
1	FLOODSIDE PILES	33.8 (5)	-51.8 (4)	0.65 (4)	1.04 (15)	-
2	MIDDLE ROW	38.9 (8)	-0.6 (4)	0.21 (3)	1.06 (8)	-
3	PROTECTED SIDE.	71.7 (1)	-	0.25 (4)	1.24 (1)	-

$$\text{Max. Axial Compression} = 71.7 \cdot K = 36.0 \text{ Ton}$$

$$\text{Vertical component} = 32.2 \text{ Tons.}$$

$\sin 63.4 = 0.89$

$$\begin{aligned} \text{Pile Tip Req'd} & -65.0 \text{ Using FOS} \\ \text{Cut-off} & -9.25 \quad -2.0 \end{aligned}$$

Per Soil Report (Preliminary, EUSTHS  
Engg.)

$$\begin{aligned} \text{Length of pile} &= (55'-9") \cdot 1.12 \\ &= \underline{62'-6"} \end{aligned}$$

# PRELIMINARY

U.S ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA

## REACH 3

ALLOWABLE PILE LOAD CAPACITIES  
SQUARE PRECAST, PRESTRESSED CONCRETE PILES  
TOP OF PILE AND DREDGE DEPTH AT EL -10.5

SIZE	PILE TIP ELEVATION IN FEET NGVD	ALLOWABLE PILE LOAD CAPACITY IN TONS FACTOR OF SAFETY $\approx 2$	
		COMPRESSION	TENSION
12-In. Square	-39	12	9
	-49	16	12
	-59	23	16
	-69	30	22
14-In. Square	-39	15	11
	-49	20	15
	-59	27	20
	-69	36	27
16-In. Square	-39	17	12
	-49	23	16
	-59	31	23
	-69	41	30

These allowable pile load capacities are suitable for piles supporting new T-wall at Units 1 through 5 of Planters Pump Station.

# PRELIMINARY

EUSTIS ENGINEERING COMPANY, INC.



U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA

MODULUS OF HORIZONTAL SUBGRADE REACTION  
REACH 3

ELEVATION IN FEET	$\frac{K_h \times B}{DC}$
10 to 0	169
0 to -19	155
-19 to -40	167
-40 to -45	178
-45 to -50	222
-56 to -67	311

- Where:
- $K_h$  = Modulus of horizontal subgrade reaction (lbs/in.<sup>3</sup>)
  - B = Diameter of pile (inches)
  - C = Reduction factor for cyclic loading
    - C = 0.5 for cyclic loading
    - C = 1.0 for initial loading
  - D = Reduction factor for effect of group action

**PRELIMINARY**

D	PILE SPACING IN DIRECTION OF LOADING
1.0	8B
0.85	7B
0.7	6B
0.55	5B
0.40	4B
0.25	3B

T-WALL LOADING CASES:

Case I: Static water pressure to SWL, no wind, impervious sheet pile cut-off (100% forces)

Case II: Static water pressure to SWL, no wind, pervious sheet pile cut-off (100% forces)

Case III: Static water pressure to SWL + 2', no wind, impervious sheet pile (75% forces)

Case IV: Static water pressure to SWL + 2', no wind, pervious sheet pile (75% forces)


Case V: water at low water level, no wind, (100% forces)

Case VI: Water at low water level, wind from flood side (75%)

NATIONAL BOARD OF FIRE UNDERWRITERS  
 1515 K STREET, N.W.  
 WASHINGTON, D.C. 20004  
 (202) 462-6000  
 FAX (202) 462-6001  
 WWW.NBFU.ORG



S  
I  
P  
E  
=  
A  
I  
T  
F  
E  
S  
I  
R  
E  
B  
E



# PRELIMINARY

Strata No	Soil Type	Unit Weight Pcf	Unfactored		Safety Factor = 1.28			
			Friction Angle Degrees	Cohesion PSI	Friction Angle Degree	Cohesion PSI	Average	Bottom
1	Sand Backfill	120	30	0	24	0	0	
2	Clay, Silty Clay, Organic Clay and Humus	102	0	350	0	273	273	
3	Sandy Silt	117	25	0	20	0	0	
4	Clay	103	0	400	0	312	312	
5	Clay	103	0	500	0	391	468	

Scale: 1" = 20'

Failure Surface	ER Resisting 161ft	ED Driving 161ft	ER-ED	Change in Net Force 161ft
A1	5351	8223	-2872	
A2	70426	73245	-2819	-3
A3	105854	94392	11462	14331

Failure Surface	Summation of Forces 161ft		Factor of Safety
	Resisting	Driving	
B1	41579	28923	1.44
B2	53601	41370	1.30
B3	29532	54062	1.44

Notes: 1) Analysis indicates no unbalanced force beneath the base of the proposed T wall at El. -9.0 to maintain stability with respect to a factor of safety of 1.28. A small unbalanced load is indicated if a factor of safety of 1.30 is used. A factor of safety of 1.28 is considered acceptable.

2) Sheet pile cutoff must penetrate to El. -31.5 or below to have a factor of safety of 4.0 against piping using the Harr Method of seepage analysis.

3) T Wall pressures must be carried by a batter pile foundation.

4) Reach 3 soil parameters were used for these analyses. The location of Stratum 3 is based on Boring ALGW-7.

Stability and T Wall Analyses  
Units 6 through 9  
Planters Pump Station  
U.S. Army Corps of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, LA

EE 14630 TJS

D:\FILE\FFSTW01

03/30/98

Last Modified: 03-30-98 at 11:22:34

00 PLANTERS PUMP STATION T WALL  
200 PROF 4074 3201 3201 196 2 0 ALL  
300 SOIL ES 0.039 LEN 60 0 ALL  
320 PIN ALL  
410 DLS S 72 54 600 223 132 1510 1166 H 14 ALL  
430 ASC S 196 457 .816 .856 1.75 0 ALL  
440 BAT 2 ALL  
450 ANG 270 1 2 3 4 5  
455 ANG 90 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20  
460 PILE 1 -17.5 -4.5 0 6 -17.5 1.0 0 11 -18.0 4.5 0  
465 ROW X 5 1 4 AT 8.75  
480 ROW X 5 6 4 AT 8.75  
485 ROW X 10 11 9 AT 4.0  
500 LOA 1 0 427.6 527.2 3694.4 0 0  
510 LOA 2 0 427.6 441.6 3479.6 0 0  
520 LOA 3 0 397.5 407.7 3435 0 0  
530 LOA 4 0 397.5 337.2 3614.4 0 0  
540 LOA 5 0 77.2 456.4 218 0 0  
550 LOA 6 0 77.2 406.4 318 0 0  
560 LOA 7 0 100.4 456.4 612 0 0  
570 LOA 8 0 46 456.4 -211.2 0 0  
610 FOU 1 2 3 4 5 6 7 FFSTW10  
620 PFD ALL  
630 PFL N

```

*****
* CORPS PROGRAM # X0080 * CPGA - CASE FILE GROUP ANALYSIS PROGRAM
* VERSION NUMBER # 86/09/02-A * RUN DATE 03-30-98 RUN TIME 11:22:57
*****

```

PLANTERS PUMP STATION T WALL

THERE ARE 20 FILES AND 8 LOAD CASES IN THIS RUN.

ALL FILE COORDINATES ARE CONTAINED WITHIN A BOX

```

                X           Y           Z
                ---          ---          ---
WITH DIAGONAL COORDINATES = (  -18.00 ,  -4.50 ,  .00 )
                             (   18.00 ,   4.50 ,  .00 )

```

\*\*\*\*\*

FILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40740E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE FILE PROPERTIES APPLY TO THE FOLLOWING FILES -

ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.39000E-01	L	.60000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING FILES -

ALL

\*\*\*\*\*

FILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	-17.50	-4.50	.00	2.00	270.00	60.00	F
2	-8.75	-4.50	.00	2.00	270.00	60.00	F
3	.00	-4.50	.00	2.00	270.00	60.00	F
4	8.75	-4.50	.00	2.00	270.00	60.00	F
5	17.50	-4.50	.00	2.00	270.00	60.00	F
6	-17.50	1.00	.00	2.00	90.00	60.00	F
7	-8.75	1.00	.00	2.00	90.00	60.00	F
8	.00	1.00	.00	2.00	90.00	60.00	F
9	8.75	1.00	.00	2.00	90.00	60.00	F
10	17.50	1.00	.00	2.00	90.00	60.00	F
11	-18.00	4.50	.00	2.00	90.00	60.00	F
12	-14.00	4.50	.00	2.00	90.00	60.00	F
13	-10.00	4.50	.00	2.00	90.00	60.00	F
14	-6.00	4.50	.00	2.00	90.00	60.00	F
15	-2.00	4.50	.00	2.00	90.00	60.00	F
16	2.00	4.50	.00	2.00	90.00	60.00	F
17	6.00	4.50	.00	2.00	90.00	60.00	F
18	10.00	4.50	.00	2.00	90.00	60.00	F
19	14.00	4.50	.00	2.00	90.00	60.00	F
20	18.00	4.50	.00	2.00	90.00	60.00	F

-----  
1200.00

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	Px K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	.0	427.6	527.2	3694.4	.0	.0
2	.0	427.6	441.6	3479.6	.0	.0
3	.0	397.5	407.7	3435.0	.0	.0
4	.0	397.5	337.2	3614.4	.0	.0
5	.0	77.2	456.4	218.0	.0	.0
6	.0	77.2	406.4	318.0	.0	.0
7	.0	100.4	456.4	612.0	.0	.0
8	.0	46.0	456.4	-211.2	.0	.0

\*\*\*\*\*

ORIGINAL FILE GROUP STIFFNESS MATRIX

.74583E+02    -.31678E-03    -.52794E-03    -.26082E-01    .18626E-08    -.12306E+04

-.31678E-03	.89319E+04	.88573E+04	.77059E+06	.62500E-01	.00000E+00
-.52794E-03	.88573E+04	.35504E+05	.58582E+06	.12500E+00	-.31250E-01
-.26082E-01	.77059E+06	.58582E+06	.78925E+08	.60000E+01	.10000E+01
.93132E-09	.46875E-01	.93750E-01	.60000E+01	.72886E+09	-.16836E+09
-.12306E+04	.15625E-01	-.15625E-01	.10000E+01	-.16836E+09	.18353E+09

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	10.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	7.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	8.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.

\*\*\*\*\*

FILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.2160E-06	-.2307E-01	.8683E-02	.7225E-03	-.7018E-11	-.6223E-11
2	.2062E-06	.6098E-02	.3612E-02	.4427E-03	-.6075E-11	-.6814E-11
3	.1919E-06	-.1392E-01	.4667E-02	.6235E-03	-.6294E-11	-.6302E-11
4	.1847E-06	-.2519E-01	.3027E-02	.7730E-03	-.6680E-11	-.6700E-11
5	.7716E-07	.7004E-02	.1332E-01	-.1341E-03	-.8213E-12	.1032E-11
6	.7197E-07	.1708E-02	.1196E-01	-.5712E-04	-.1007E-11	.7435E-12
7	.8626E-07	-.1078E-01	.1399E-01	.9453E-04	-.1753E-11	.5636E-12
8	.6517E-07	.2095E-01	.1314E-01	-.3342E-03	.1033E-12	.1688E-11

\*\*\*\*\*

FILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR FINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO  
 (F3\*EMIN) FOR CONCRETE PILES

## B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.1	.0	-37.3	.0	-7.9	.0	.69	.47	.68	.61
2	.1	.0	-37.3	.0	-7.9	.0	.69	.47	.68	.61
3	.1	.0	-37.3	.0	-7.9	.0	.69	.47	.68	.61
4	.1	.0	-37.3	.0	-7.9	.0	.69	.47	.68	.61
5	.1	.0	-37.3	.0	-7.9	.0	.69	.47	.68	.61
6	-.1	.0	11.5	.0	6.5	.0	.16	.20	.93	.86 #
7	-.1	.0	11.5	.0	6.5	.0	.16	.20	.93	.86 #
8	-.1	.0	11.5	.0	6.5	.0	.16	.20	.93	.86 #
9	-.1	.0	11.5	.0	6.5	.0	.16	.20	.93	.86 #
10	-.1	.0	11.5	.0	6.5	.0	.16	.20	.93	.86 #
11	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
12	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
13	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
14	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
15	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
16	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
17	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
18	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
19	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #
20	-.2	.0	71.7	.0	9.6	.0	1.00	.31	1.24	1.16 #

LOAD CASE - 2

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	-46.3	.0	-.8	.0	.86	.56	.62	.58
2	.0	.0	-46.3	.0	-.8	.0	.86	.56	.62	.58
3	.0	.0	-46.3	.0	-.8	.0	.86	.56	.62	.58
4	.0	.0	-46.3	.0	-.8	.0	.86	.56	.62	.58
5	.0	.0	-46.3	.0	-.8	.0	.86	.56	.62	.58
6	.0	.0	23.8	.0	-.3	.0	.33	.18	.98	.94 #
7	.0	.0	23.8	.0	-.3	.0	.33	.18	.98	.94 #
8	.0	.0	23.8	.0	-.3	.0	.33	.18	.98	.94 #
9	.0	.0	23.8	.0	-.3	.0	.33	.18	.98	.94 #
10	.0	.0	23.8	.0	-.3	.0	.33	.18	.98	.94 #
11	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12 #
12	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12 #
13	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12 #
14	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12 #



15	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12
16	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12
17	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12
18	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12
19	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12
20	.0	.0	60.6	.0	1.6	.0	.84	.22	1.17	1.12

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.1	.0	-43.7	.0	-5.8	.0	.81	.54	.65	.58
2	.1	.0	-43.7	.0	-5.8	.0	.81	.54	.65	.58
3	.1	.0	-43.7	.0	-5.8	.0	.81	.54	.65	.58
4	.1	.0	-43.7	.0	-5.8	.0	.81	.54	.65	.58
5	.1	.0	-43.7	.0	-5.8	.0	.81	.54	.65	.58
6	-.1	.0	10.3	.0	4.1	.0	.14	.21	.92	.86
7	-.1	.0	10.3	.0	4.1	.0	.14	.21	.92	.86
8	-.1	.0	10.3	.0	4.1	.0	.14	.21	.92	.86
9	-.1	.0	10.3	.0	4.1	.0	.14	.21	.92	.86
10	-.1	.0	10.3	.0	4.1	.0	.14	.21	.92	.86
11	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
12	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
13	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
14	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
15	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
16	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
17	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
18	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
19	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12
20	-.1	.0	62.3	.0	6.8	.0	.86	.23	1.19	1.12

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.1	.0	-51.8	.0	-9.1	.0	.96	.65	.61	.53
2	.1	.0	-51.8	.0	-9.1	.0	.96	.65	.61	.53
3	.1	.0	-51.8	.0	-9.1	.0	.96	.65	.61	.53
4	.1	.0	-51.8	.0	-9.1	.0	.96	.65	.61	.53
5	.1	.0	-51.8	.0	-9.1	.0	.96	.65	.61	.53
6	-.1	.0	-.6	.0	6.4	.0	.01	.02	.87	.80
7	-.1	.0	-.6	.0	6.4	.0	.01	.02	.87	.80
8	-.1	.0	-.6	.0	6.4	.0	.01	.02	.87	.80
9	-.1	.0	-.6	.0	6.4	.0	.01	.02	.87	.80
10	-.1	.0	-.6	.0	6.4	.0	.01	.02	.87	.80

11	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
12	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
13	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
14	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
15	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
16	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
17	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
18	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
19	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#
20	-1.2	.0	63.8	.0	9.8	.0	.89	.25	1.20	1.12	#

LOAD CASE - 5

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	-1.1	.0	33.8	.0	3.6	.0	.47	.15	1.04	.98	#
2	-1.1	.0	33.8	.0	3.6	.0	.47	.15	1.04	.98	#
3	-1.1	.0	33.8	.0	3.6	.0	.47	.15	1.04	.98	#
4	-1.1	.0	33.8	.0	3.6	.0	.47	.15	1.04	.98	#
5	-1.1	.0	33.8	.0	3.6	.0	.47	.15	1.04	.98	#
6	.0	.0	30.2	.0	-1.2	.0	.42	.16	1.01	.97	#
7	.0	.0	30.2	.0	-1.2	.0	.42	.16	1.01	.97	#
8	.0	.0	30.2	.0	-1.2	.0	.42	.16	1.01	.97	#
9	.0	.0	30.2	.0	-1.2	.0	.42	.16	1.01	.97	#
10	.0	.0	30.2	.0	-1.2	.0	.42	.16	1.01	.97	#
11	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
12	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
13	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
14	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
15	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
16	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
17	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
18	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
19	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#
20	.0	.0	19.0	.0	-1.8	.0	.26	.19	.95	.91	#

LOAD CASE - 6

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.0	.0	28.2	.0	1.9	.0	.39	.17	1.00	.96	#
2	.0	.0	28.2	.0	1.9	.0	.39	.17	1.00	.96	#
3	.0	.0	28.2	.0	1.9	.0	.39	.17	1.00	.96	#
4	.0	.0	28.2	.0	1.9	.0	.39	.17	1.00	.96	#
5	.0	.0	28.2	.0	1.9	.0	.39	.17	1.00	.96	#
6	.0	.0	24.1	.0	.8	.0	.33	.18	.98	.94	#

7	.0	.0	24.1	.0	.8	.0	.33	.18	.98	.94
8	.0	.0	24.1	.0	.8	.0	.33	.18	.98	.94
9	.0	.0	24.1	.0	.8	.0	.33	.18	.98	.94
10	.0	.0	24.1	.0	.8	.0	.33	.18	.98	.94
11	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
12	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
13	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
14	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
15	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
16	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
17	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
18	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
19	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91
20	.0	.0	19.3	.0	.6	.0	.27	.19	.96	.91

LOAD CASE - 7

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	28.3	.0	-1.3	.0	.39	.17	1.00	.96
2	.0	.0	28.3	.0	-1.3	.0	.39	.17	1.00	.96
3	.0	.0	28.3	.0	-1.3	.0	.39	.17	1.00	.96
4	.0	.0	28.3	.0	-1.3	.0	.39	.17	1.00	.96
5	.0	.0	28.3	.0	-1.3	.0	.39	.17	1.00	.96
6	-.1	.0	19.3	.0	3.8	.0	.27	.19	.96	.91
7	-.1	.0	19.3	.0	3.8	.0	.27	.19	.96	.91
8	-.1	.0	19.3	.0	3.8	.0	.27	.19	.96	.91
9	-.1	.0	19.3	.0	3.8	.0	.27	.19	.96	.91
10	-.1	.0	19.3	.0	3.8	.0	.27	.19	.96	.91
11	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
12	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
13	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
14	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
15	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
16	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
17	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
18	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
19	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95
20	-.1	.0	27.2	.0	4.2	.0	.38	.17	1.00	.95

LOAD CASE - 8

FILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-.1	.0	41.1	.0	7.5	.0	.57	.14	1.08	1.01
2	-.1	.0	41.1	.0	7.5	.0	.57	.14	1.08	1.01

3	-1	.0	41.1	.0	7.5	.0	.57	.14	1.08	1.01
4	-1	.0	41.1	.0	7.5	.0	.57	.14	1.08	1.01
5	-1	.0	41.1	.0	7.5	.0	.57	.14	1.08	1.01
6	.1	.0	38.9	.0	-3.4	.0	.54	.14	1.06	1.01
7	.1	.0	38.9	.0	-3.4	.0	.54	.14	1.06	1.01
8	.1	.0	38.9	.0	-3.4	.0	.54	.14	1.06	1.01
9	.1	.0	38.9	.0	-3.4	.0	.54	.14	1.06	1.01
10	.1	.0	38.9	.0	-3.4	.0	.54	.14	1.06	1.01
11	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
12	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
13	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
14	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
15	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
16	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
17	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
18	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
19	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86
20	.1	.0	11.1	.0	-4.8	.0	.15	.20	.92	.86

\*\*\*\*\*

FILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	16.6	-33.4	.0	.0	.0
2	.0	16.6	-33.4	.0	.0	.0
3	.0	16.6	-33.4	.0	.0	.0
4	.0	16.6	-33.4	.0	.0	.0
5	.0	16.6	-33.4	.0	.0	.0
6	.0	5.1	10.4	.0	.0	.0
7	.0	5.1	10.4	.0	.0	.0
8	.0	5.1	10.4	.0	.0	.0
9	.0	5.1	10.4	.0	.0	.0
10	.0	5.1	10.4	.0	.0	.0
11	.0	31.9	64.2	.0	.0	.0
12	.0	31.9	64.2	.0	.0	.0
13	.0	31.9	64.2	.0	.0	.0
14	.0	31.9	64.2	.0	.0	.0
15	.0	31.9	64.2	.0	.0	.0
16	.0	31.9	64.2	.0	.0	.0
17	.0	31.9	64.2	.0	.0	.0
18	.0	31.9	64.2	.0	.0	.0
19	.0	31.9	64.2	.0	.0	.0

20 .0 31.9 64.2 .0 .0 .0

LOAD CASE - 2

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	20.7	-41.4	.0	.0	.0
2	.0	20.7	-41.4	.0	.0	.0
3	.0	20.7	-41.4	.0	.0	.0
4	.0	20.7	-41.4	.0	.0	.0
5	.0	20.7	-41.4	.0	.0	.0
6	.0	10.6	21.2	.0	.0	.0
7	.0	10.6	21.2	.0	.0	.0
8	.0	10.6	21.2	.0	.0	.0
9	.0	10.6	21.2	.0	.0	.0
10	.0	10.6	21.2	.0	.0	.0
11	.0	27.1	54.3	.0	.0	.0
12	.0	27.1	54.3	.0	.0	.0
13	.0	27.1	54.3	.0	.0	.0
14	.0	27.1	54.3	.0	.0	.0
15	.0	27.1	54.3	.0	.0	.0
16	.0	27.1	54.3	.0	.0	.0
17	.0	27.1	54.3	.0	.0	.0
18	.0	27.1	54.3	.0	.0	.0
19	.0	27.1	54.3	.0	.0	.0
20	.0	27.1	54.3	.0	.0	.0

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	19.5	-39.2	.0	.0	.0
2	.0	19.5	-39.2	.0	.0	.0
3	.0	19.5	-39.2	.0	.0	.0
4	.0	19.5	-39.2	.0	.0	.0
5	.0	19.5	-39.2	.0	.0	.0
6	.0	4.5	9.2	.0	.0	.0
7	.0	4.5	9.2	.0	.0	.0
8	.0	4.5	9.2	.0	.0	.0
9	.0	4.5	9.2	.0	.0	.0
10	.0	4.5	9.2	.0	.0	.0
11	.0	27.7	55.7	.0	.0	.0
12	.0	27.7	55.7	.0	.0	.0
13	.0	27.7	55.7	.0	.0	.0
14	.0	27.7	55.7	.0	.0	.0
15	.0	27.7	55.7	.0	.0	.0

16	.0	27.7	55.7	.0	.0	.0
17	.0	27.7	55.7	.0	.0	.0
18	.0	27.7	55.7	.0	.0	.0
19	.0	27.7	55.7	.0	.0	.0
20	.0	27.7	55.7	.0	.0	.0

## LOAD CASE - 4

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	23.0	-46.4	.0	.0	.0
2	.0	23.0	-46.4	.0	.0	.0
3	.0	23.0	-46.4	.0	.0	.0
4	.0	23.0	-46.4	.0	.0	.0
5	.0	23.0	-46.4	.0	.0	.0
6	.0	-.4	-.5	.0	.0	.0
7	.0	-.4	-.5	.0	.0	.0
8	.0	-.4	-.5	.0	.0	.0
9	.0	-.4	-.5	.0	.0	.0
10	.0	-.4	-.5	.0	.0	.0
11	.0	28.4	57.2	.0	.0	.0
12	.0	28.4	57.2	.0	.0	.0
13	.0	28.4	57.2	.0	.0	.0
14	.0	28.4	57.2	.0	.0	.0
15	.0	28.4	57.2	.0	.0	.0
16	.0	28.4	57.2	.0	.0	.0
17	.0	28.4	57.2	.0	.0	.0
18	.0	28.4	57.2	.0	.0	.0
19	.0	28.4	57.2	.0	.0	.0
20	.0	28.4	57.2	.0	.0	.0

## LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	-15.1	30.3	.0	.0	.0
2	.0	-15.1	30.3	.0	.0	.0
3	.0	-15.1	30.3	.0	.0	.0
4	.0	-15.1	30.3	.0	.0	.0
5	.0	-15.1	30.3	.0	.0	.0
6	.0	13.5	27.0	.0	.0	.0
7	.0	13.5	27.0	.0	.0	.0
8	.0	13.5	27.0	.0	.0	.0
9	.0	13.5	27.0	.0	.0	.0
10	.0	13.5	27.0	.0	.0	.0
11	.0	8.5	17.0	.0	.0	.0

12	.0	8.5	17.0	.0	.0	.0
13	.0	8.5	17.0	.0	.0	.0
14	.0	8.5	17.0	.0	.0	.0
15	.0	8.5	17.0	.0	.0	.0
16	.0	8.5	17.0	.0	.0	.0
17	.0	8.5	17.0	.0	.0	.0
18	.0	8.5	17.0	.0	.0	.0
19	.0	8.5	17.0	.0	.0	.0
20	.0	8.5	17.0	.0	.0	.0

LOAD CASE - 6

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	-12.6	25.2	.0	.0	.0
2	.0	-12.6	25.2	.0	.0	.0
3	.0	-12.6	25.2	.0	.0	.0
4	.0	-12.6	25.2	.0	.0	.0
5	.0	-12.6	25.2	.0	.0	.0
6	.0	10.8	21.5	.0	.0	.0
7	.0	10.8	21.5	.0	.0	.0
8	.0	10.8	21.5	.0	.0	.0
9	.0	10.8	21.5	.0	.0	.0
10	.0	10.8	21.5	.0	.0	.0
11	.0	8.6	17.3	.0	.0	.0
12	.0	8.6	17.3	.0	.0	.0
13	.0	8.6	17.3	.0	.0	.0
14	.0	8.6	17.3	.0	.0	.0
15	.0	8.6	17.3	.0	.0	.0
16	.0	8.6	17.3	.0	.0	.0
17	.0	8.6	17.3	.0	.0	.0
18	.0	8.6	17.3	.0	.0	.0
19	.0	8.6	17.3	.0	.0	.0
20	.0	8.6	17.3	.0	.0	.0

LOAD CASE - 7

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	-12.7	25.3	.0	.0	.0
2	.0	-12.7	25.3	.0	.0	.0
3	.0	-12.7	25.3	.0	.0	.0
4	.0	-12.7	25.3	.0	.0	.0
5	.0	-12.7	25.3	.0	.0	.0
6	.0	8.6	17.3	.0	.0	.0
7	.0	8.6	17.3	.0	.0	.0

8	.0	8.6	17.3	.0	.0	.0
9	.0	8.6	17.3	.0	.0	.0
10	.0	8.6	17.3	.0	.0	.0
11	.0	12.1	24.3	.0	.0	.0
12	.0	12.1	24.3	.0	.0	.0
13	.0	12.1	24.3	.0	.0	.0
14	.0	12.1	24.3	.0	.0	.0
15	.0	12.1	24.3	.0	.0	.0
16	.0	12.1	24.3	.0	.0	.0
17	.0	12.1	24.3	.0	.0	.0
18	.0	12.1	24.3	.0	.0	.0
19	.0	12.1	24.3	.0	.0	.0
20	.0	12.1	24.3	.0	.0	.0

LOAD CASE - 8



PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	.0	-18.3	36.8	.0	.0	.0
2	.0	-18.3	36.8	.0	.0	.0
3	.0	-18.3	36.8	.0	.0	.0
4	.0	-18.3	36.8	.0	.0	.0
5	.0	-18.3	36.8	.0	.0	.0
6	.0	17.4	34.8	.0	.0	.0
7	.0	17.4	34.8	.0	.0	.0
8	.0	17.4	34.8	.0	.0	.0
9	.0	17.4	34.8	.0	.0	.0
10	.0	17.4	34.8	.0	.0	.0
11	.0	5.0	9.8	.0	.0	.0
12	.0	5.0	9.8	.0	.0	.0
13	.0	5.0	9.8	.0	.0	.0
14	.0	5.0	9.8	.0	.0	.0
15	.0	5.0	9.8	.0	.0	.0
16	.0	5.0	9.8	.0	.0	.0
17	.0	5.0	9.8	.0	.0	.0
18	.0	5.0	9.8	.0	.0	.0
19	.0	5.0	9.8	.0	.0	.0
20	.0	5.0	9.8	.0	.0	.0



# PLANTER'S PUMP STATION

## LEGEND

BATTER 2:1  
□  
PILE NUMBER



14' x 14' ~~sq~~  
P.P.C. PILES

DISPLAY OF PILE LAYOUT

01-APR-1998

16.57.15

S&amp;WB# 13 UNITS 1-3 STABILITY ANALYSIS

SWL = 9.5

- FAILURE SURFACE (B)(4) - Reg'd Pressure = 1211 psf

$$wt = 663 \text{ psf}$$

$$\text{remaining pressure} = 1211 - 663 = 548 \text{ psf}$$

$$\text{area} = 1043.34$$

$$\text{total load} = (1043.34)(548)/1000 = 572^k$$

$$\# \text{ piles} = 86$$

$$\text{load/pile} = 572/86 = 6.6^k/\text{pile}$$

$$\text{allowable} = 20^k \quad \underline{\underline{OK}}$$

- FAILURE SURFACE (C)(8), reg'd pressure = 1008

$$wt = 663$$

$$\text{remaining wt} = 1008 - 663 = 345 \text{ psf}$$

$$\text{area} = 1513 \text{ sf}$$

$$\text{total load} = (345)(1513)/1000 = 522^k$$

$$\# \text{ piles} = 119$$

$$\text{load/pile} = 522/119 = 4.4^k \quad \underline{\underline{OK}}$$

- station is stable, no T-wall reg'd

S&WB # 13 - STABILITY ANALYSIS FOR UNITS 4-7

$SWL = 9.5 \text{ NGVD}$

- FOR FAILURE SURFACE (B)(3), Reg'd Pressure = 1478 psf

total wt = 865.7 psf

Pressure to be taken by tension piles =  $1478 - 865.7$   
 $= 612.3 \text{ psf}$

area = 907.5 sf

Total load to be taken by piles =  $\frac{612.3(907.5)}{1000} = 555.6 \text{ K}$

# piles = 66 , tension/pile =  $555.6/66 = 8.4 \text{ K/pile}$

- need 8.4 K/pile - capacity below 40

Capacity =  $13^T = 26 \text{ K}$  OK

- FAILURE SURFACE (B)(4) - Pressure = 778 psf

wt = 222.5 psf

remaining wt =  $778 - 222.5 = 555.2 \text{ psf}$

area = 1028.5 sf

total load =  $555.2(1028.5)/1000 = 571.3 \text{ K}$

# piles = 25

load/pile =  $571.3/25 = 22.8 \text{ K}$

Capacity =  $26 \text{ K}$  OK

10 100 SHEETS (5' x 10') 5 SQUARE  
 10 100 SHEETS (5' x 10') 5 SQUARE  
 42 389 100 SHEETS (4' x 8') 5 SQUARE  
 42 389 100 SHEETS (4' x 8') 5 SQUARE  
 42 389 100 RECYCLED WHITE 5 SQUARE  
 42 389 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



- FAILURE SURFACE ©©, Reg'd Pressure = 971 psf

$$wt = 865$$

$$\text{Remaining wt} = 971 - 865 = 106 \text{ psf}$$

OK

- FAILURE SURFACE ©⑦, Reg'd Pressure = 389

$$wt = 222.5$$

$$\text{Remaining wt} = 389 - 222.5 = 166.5 \text{ psf}$$

$$\text{area} = 2238.5$$

$$\text{total load} = (166.5)(2238.5)/1000 = 372.7 \text{ K}$$

$$\# \text{ piles} = 82$$

$$\text{load/pile} = 372.7/82 = 4.5 \text{ K/pile}$$

$$\text{allowable} = 22 \text{ K} \quad \underline{\underline{OK}}$$

-NO T-wall needed

## SEWERAGE &amp; WATER BOARD #13:

## STATION ADDITION:

TOP OF DISCHARGE TUBE - EL. 33.0 C.D. = 12.57 NGVD.

## ORIGINAL STATION:

TOP OF CONCRETE DISCHARGE TUBE - 33.00 C.D. = 12.57

TOP OF WALL @ VERTICAL PUMPS : 33.00 C.D. = 12.57

TOP OF WALL OUTSIDE OF PUMP AREA = 33.00 = 12.57 NGVD.

TOP OF BASE SLAB = 26.31 C.D. = 5.88

- Top of Level = 9.5

- transition to H:1V →

vertical difference = 9.5 - 5.88 = 3.62

need 36.2' for transition.

→ have 100' - OK

SWB # 11 - WEST STATION - MODIFIED BY ADDING CONCRETE  
DISCHARGE TUBE

SWL = 9.5 NGVD

- FOR FAILURE SURFACE (B) (1), Req'd Pressure = 2110 psf

$$wt = 319 \text{ psf}$$

$$\text{Remaining wt} = 2110 - 319 = 1791 \text{ psf}$$

$$\begin{aligned} \text{total load/pile} &= (1791)(13')(71')/1000(\text{sq}) \\ &= 25^k/\text{pile} \end{aligned}$$

$$\text{Allowable} = 22^k \text{ N.G.}$$

- Fwall is req'd

13782  
42-391  
42-390  
42-389  
42-388  
42-387

200 SHEETS PER PILE  
200 SHEETS PER PILE  
200 SHEETS PER PILE  
200 SHEETS PER PILE  
200 SHEETS PER PILE  
200 RECYCLED WHITE  
200 RECYCLED WHITE

Made in U.S.A.



S&amp;WB# 11

$$SWL = 9.5$$

T-Wall Analysis still requires vertical pressure:

HORIZONTAL PUMP STATION (NEW STATION)

Failure Surface (B)(2) requires pressure of 278 psf

$$\text{-total wt of station} = 266 \text{ psf}$$

$$\text{difference of } 278 - 266 = 12 \text{ psf} - \text{ say } \underline{\underline{ok}}$$

EAST

Failure Surface (C)(4) requires pressure of 249 psf

$$\text{-total wt of station} = 266 \text{ psf} > 249 \quad \underline{\underline{ok}}$$

ORIGINAL STATION:

STABILITY ANALYSIS OF STATION ONLY:

FAILURE SURFACE (A)(1) requires pressure of 2585 psf

$$\text{total wt of station} = 319 \text{ psf}$$

$$\text{Pressure to be taken by tension piles} = 2585 - 319 = 2266 \text{ psf}$$

$$\# \text{ piles in passive wedge area} = 66$$

$$\text{Tension per pile} = \frac{(2266)(13)(71')}{1000(66)} = 32 \text{ K per pile}$$

$$\text{Allowable tension per pile} = 22 \text{ K N.G.}$$

- T-WALL IS NEEDED. ~63' from edge of building

WEST





## SEWERAGE &amp; WATER BOARD # 11

FLOODWALL TO EL. 12.75  
EXCEPT WINDOWS

## ORIGINAL STATION

FAILURE SURFACE (A)①:

$$\text{REQ'D PRESSURE} = 1668 \text{ psf}$$

$$\text{BASE SLAB THICKNESS} = 22''$$

$$wt = (150 \text{ pcf} - 92 \text{ pcf}) (22/12) = 106.33 \text{ psf}$$

(92 pcf = wt. soil used by Eustis in stability analysis)

$$\text{FLOOR SLAB THICKNESS} = 8''$$

$$wt = (150) (8/12) = 100 \text{ psf}$$

$$\text{WALLS: } 2 \text{ WALLS } @ 14'' \text{ THICK } \times 21.25'$$

$$wt = (14/12) (21.25) (150) (2) = 7437.5 \text{ p/lp} / 66.08' = 112.5 \text{ psf}$$

$$\text{TOTAL} = 106.33 + 100 + 112.5 = 318.83 \text{ psf}$$

$$\text{Pressure to be taken by tension piles} = 1668 - 317 = 1349 \text{ psf}$$

$$\# \text{ piles in passive wedge area (13' width)} \\ = 66$$

$$\text{Total load in passive wedge area} = (1349 \text{ psf}) (13') (71') / 1000 \\ = 1245 \text{ k}$$

$$\text{Ave req'd tension load per pile} = 1245 / 66 = 18.9 \text{ k/pile}$$

$$\rightarrow \text{Available tension per pile below el. -21} = 22 \text{ k/pile}$$

$$22 > 18.9 \quad \underline{\text{OK}}$$

- Station is stable at SPH Levels, NO T-WALL IS NEEDED.
- MODIFY EXISTING FLOODWALL TO EL. 9.5



SEWB# 1:1

PILE ANCHORS

8'-11"



5'-4"

3'-0"

Edge of Base Stabilization Slab

ALL PILES SHOWN HEREON ARE UNTREATED PILES. FOR THE LOCATION AND CUT OFF ELEVATIONS OF THE NINE (9) TREATED TIMBER PILES UNDER THE CISTERN AND THE FUEL OIL STORAGE TANK SEE DRAWING NO. H-4-18428/27.

50'-0"



SEWB# 1:1  
ORIGINAL  
STATION

SEWERAGE & WATER BOARD # 11 (CONT.)

FLOODWALL TO 3250.0  
(TOP OF DISCHARGE  
TUBE)

NEW STATION:

FOR FAILURE SURFACE (B)(2):

REQUIRED PRESSURE = 942 psf

BASE SLAB THICKNESS = 2'-0"

$w_t = (150 - 92)(2) = 116 \text{ psf}$

FLOOR SLAB THICKNESS = 1'-0"

$w_t = 150 \text{ psf}$

TOTAL  $w_t = 266 \text{ psf}$

Pressure to be taken by tension piles =  $942 - 266 = 676 \text{ psf}$

Passive wedge area is  $21' \times 60.5' = 1270.5 \text{ sf}$

Total <sup>tension</sup> load in passive wedge =  $676(1270.5)/1000 = 859 \text{ K}$

# piles =  $85 \div \frac{1}{2}(12) = 91$

Total tension req'd per pile =  $859/91 = 9.4 \text{ K}$

- below el - 40

- Tension capacity (by Ewot's) =  $18 \text{ K}$

$18 > 9.4 \text{ OK.}$

- Station is stable for failure surface (B)(2) - NO T WALL NEEDED.

- Tension connectors? - call NY Associates - 885-0500

MR. LOGAN  
NY Assoc.  
11-11-97

→ - THERE ARE NO TENSION CONNECTORS FOR PILES UNDER THE BASE SLAB

13 782  
42 381  
42 389  
42 392  
42 395  
500 SHEETS, FILLER, 2 SQUARE  
50 SHEETS, FILLER, 2 SQUARE  
50 SHEETS, FILLER, 2 SQUARE  
100 SHEETS, FILLER, 2 SQUARE  
200 SHEETS, FILLER, 2 SQUARE  
200 SHEETS, FILLER, 2 SQUARE  
200 RECYCLED WHITE, 2 SQUARE  
200 RECYCLED WHITE, 2 SQUARE  
Made in U.S.A.



S&amp;WB # 11 (CONT.)

FAILURE SURFACE (C)4 - Req'd Pressure = 699 psf

Total wt = 266 psf

Pressure to be taken by tension piles =  $699 - 266 = 433$  psfPassive wedge area =  $30' \times 60.5' = 1815$  sfTotal tension load in passive wedge area =  $433(1815)/1000 = 786$  K# PILES =  $\frac{1}{2}(12) + 12(8) + 8(2) = 118$ Req'd tension per pile =  $786/118 = 6.6$  K / pile

below failure surface el. -50

Tension capacity (by Ewotis) =  $14$  K $14 > 6.6$  OK

FAILURE SURFACE (D)7: Req'd pressure = 300 psf


total wt = 266 psf

Pressure to be taken by tension piles =  $300 - 266 = 34$  psfPassive wedge area =  $40' \times 60.5' = 2420$  sfTotal tension load on passive wedge =  $34(2420)/1000 = 82$  K# piles =  $9(8) + 8 + \frac{1}{2}(12) = 86$ Req'd tension per pile =  $82/86 = 1$  K / pile

- below failure surface el -60

EXISTING CONCRETE

ADDITION



13.762 200 RECYCLED WHITE 3 SQUARE  
 42.381 200 RECYCLED WHITE 3 SQUARE  
 42.382 200 RECYCLED WHITE 3 SQUARE  
 42.389 200 RECYCLED WHITE 3 SQUARE  
 42.395 200 RECYCLED WHITE 3 SQUARE  
 Made in U.S.A.



LEAD LOADS:

STEM: ① (20.5')(1')(1.50) = 3.08 <sup>k/ft</sup>  
 ② (2')(1.5')(20.5')(1.50) = 2.31

BASE: (2.5')(14')(1.50) = 5.25

WATER OVER BASE:

F/S: SWL: (18.5')(9.5')(1.0625) = 10.98 <sup>k/ft</sup>  
 SWL+2' (20.5')(9.5')(1.0625) = 12.17  
 LWL: (9')(9.5')(1.0625) = 5.34

P/S: (10')(2')(1.0625) = 1.25

WATER PRESSURE:


F/S: SWL: (21')(1.0625) = 1.31 <sup>k/ft-ft</sup>  
 SWL+2': (23')(1.0625) = 1.44  
 LWL: (11.5')(1.0625) = 0.72

P/S: (10.0)(1.0625) = 0.63

WIND PRESSURE ABOVE E.L.: D P/S:

(10.5')(50 psf) = 0.52 <sup>k/ft</sup>

13 702 500 SHEETS, FILLER 5 SQUARE  
 42 381 50 SHEETS, CYE-EASE 5 SQUARE  
 42 382 100 SHEETS, CYE-EASE 5 SQUARE  
 42 383 200 SHEETS, CYE-EASE 5 SQUARE  
 42 384 100 RECYCLED WHITE 5 SQUARE  
 42 399 200 RECYCLED WHITE 5 SQUARE  
 Made in U.S.A.



## T-WALL LOADING CASES:

- I: STATIC WATER PRESSURE TO SWL, NO WIND, IMPERVIOUS SHEET PILE CUTOFF (100% FORCES)
- II: STATIC WATER PRESSURE TO SWL, NO WIND, PERVIOUS SHEET PILE CUTOFF (100% FORCES)
- III: STATIC WATER PRESSURE TO SWL+2', NO WIND, IMPERVIOUS SHEET PILE CUTOFF (75% FORCES)
- IV: STATIC WATER PRESSURE TO SWL+2', NO WIND, PERVIOUS SHEET PILE CUTOFF (75% FORCES)
- V: WATER @ LOW WATER LEVEL, NO WIND (100% FORCES)
- VI: WATER @ LOW WATER LEVEL, WIND FROM P/S (75% FORCES)

42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS  
42 200 200 SHEETS WITH 2.500 SHEETS



T-WALL FORCE TABULATION

+↓

DESCRIPTION	FORCES (KIPS)		LEVER ARM		MOMENTS
	F <sub>x</sub>	F <sub>y</sub>	x	z	M <sub>y</sub>
<b>DEAD LOADS:</b>					
STEM		3.08	3.0		-9.24
		2.31	4.0		-9.24
BASE		5.25	0		0
SWL		10.98	-2.25		+ 24.71
SWL+2'		12.17	-2.25		+ 27.38
LWL		5.34	-2.25		+ 12.02
P/S		1.25	6.0		- 7.50
<b>WATER LOADS</b>					
SWL					
½(1.31)(21)	13.76			-7.0	-96.32
Buoyancy:					
impervious:					
(1.31)(5.0)		-6.55	-4.5		-29.48
pervious:					
(½)(1.31)(14)		-9.17	-2.33		-21.37
SWL+2'					
½(1.44)(23)	16.56			-7.67	-127.02
Buoyancy:					
impervious					
(1.44)(5)		-7.2	-4.5		-32.40
pervious					
(½)(1.44)(14)		-10.08	-2.33		-23.49
LWL:					
½(.72)(11.5)	4.14			3.83	-15.86
Buoyancy:					
impervious:					
(.72)(5)		-3.6	-4.5		-16.20
pervious:					
(½)(.72)(14)		-5.04	-2.33		-11.74
WATER ON P/S:					
(½)(.63)(10.0)	-3.15			-5.83	+18.36
WIND ON P/S					
(.52)(10.5)	-1.52			-17.75	+9.23

12,782 500 SHEETS PILELH 5 SQUARE  
42,361 50 SHEETS LYE CASE 5 SQUARE  
42,362 100 SHEETS EYE CASE 5 SQUARE  
42,363 100 SHEETS PILELH 5 SQUARE  
42,364 100 SHEETS LYE CASE 5 SQUARE  
42,365 100 SHEETS EYE CASE 5 SQUARE  
42,366 100 SHEETS PILELH 5 SQUARE  
42,367 100 SHEETS LYE CASE 5 SQUARE  
42,368 100 SHEETS EYE CASE 5 SQUARE  
42,369 200 RECYCLED WHITE 5 SQUARE  
42,370 200 RECYCLED WHITE 5 SQUARE  
Made in U.S.A.





LOAD COMBINATIONS

LOADING CASE	DESCRIPTION	FORCES		MOMENTS
		F <sub>x</sub>	F <sub>z</sub>	M <sub>y</sub>
I	DL, SWL, IMP S/P	DL	22.87	-1.27
	100%	SWL	10.61	-77.96
		IMP	-6.55	-29.48
	TOTAL	10.61	16.32	-108.71
	FOR 40'	424.4	652.8	-4348.4
II	DL, SWL, PER S/P	DL	22.87	-1.27
	100%	SWL	10.61	-77.96
		PER	-9.17	-21.37
	TOTAL	10.61	13.70	-100.60
	FOR 40'	424.4	548.0	-4024.0
III	DL, SWL+2', IMP	DL	24.06	+1.4
	75%	SWL+2'	13.41	-108.66
		IMP	-7.2	-32.40
	TOTAL	13.41	16.86	-139.66
	75%	10.06	12.65	-104.75
	FOR 40'	402.4	505.8	-4189.8
IV	DL, SWL+2', PER	DL	24.06	+1.4
	75%	SWL+2'	13.41	-108.66
		PER	-10.08	-23.49
	TOTAL	13.41	13.98	-130.75
	75%	10.06	10.49	-98.04
	FOR 40'	402.4	419.4	-3922.5
V	DL, LWL, IMP	DL	17.23	-13.96
	100%	LWL	0.99	2.50
		IMP	-3.6	-16.20
	TOTAL	0.99	13.63	-27.66
	FOR 40'	39.6	545.2	-1104.4
VI	DL, LWL, WIND	DL	17.23	-13.96
	75%	LWL	0.99	2.50
		IMP	-3.6	-16.20
		WIND	-0.52	9.23
	TOTAL	0.47	13.63	-18.43
	75%	0.35	10.22	-13.82
	FOR 40'	14.1	408.9	-552.9

782 500 SHEETS FILLER 5 SQUARE  
47 481 50 SHEETS EYE CASE 5 SQUARE  
48 389 100 SHEETS EYE CASE 5 SQUARE  
49 397 100 SHEETS EYE CASE 5 SQUARE  
42 392 100 RECYCLED WHITE 5 SQUARE  
42 799 200 RECYCLED WHITE 5 SQUARE  
MADE IN U.S.A.



LINE 300 SOIL = ES

E SOIL  $E_s = K_h B$ 

$$\text{FROM EUSTIS: } \frac{K_h E}{D C} = 213$$

$$C = 1.0$$

D: -14" PILES @ 4'-0" spacing

$$\text{SPACING: } \frac{48}{14} = 3.43$$

$$D = 0.25 + (3.43 - 2.5)(.4)$$

$$= 0.31$$

$$K_h B = (213)(0.31)(1.0)$$

$$= 66 \text{ psi} = 0.066 \text{ RSC}$$

## PILE CAPACITY (FROM EUSTIS)

14"  $\square$  , PILE TIP -69 N.G.U.D. , TOP OF PILE @ -11.5

COMP = 32 TONS  
TENS = 24 TONS } VERTICAL CAPACITY

$$\text{VERTICAL LENGTH} = 69 - 11.5 = 57.5'$$

BATTER : 2 V : 1 H

$$\text{OVERALL LENGTH} = \sqrt{(57.5)^2 + \left(\frac{57.5}{2}\right)^2} = 64'$$

$$\text{OVERALL CAPACITY. COMP: } \sqrt{(32)^2 + \left(\frac{32}{2}\right)^2} = 35.8^T = 71.6^K$$

$$\text{TENS: } \sqrt{(24)^2 + (12)^2} = 26.8^T = 53.6^K$$

FIELD BOOK

100	S&WB# 11 EAST	T-WALL							
200	PROP 4074	3201	3201	196	2.0	0.0	ALL		
300	SOIL ES	0.066	LEN	64	0	ALL			
320	PIN	ALL							
400	DLS 5 72	54	600	223	133	1510	1127	H	14 ALL
420	ASC 5 196	457	0.816	0.856	1.75	0.0	ALL		
440	BAT	2.0	ALL						
450	ANG	<del>180</del> 2 1	to	<u>15</u>					
455	ANG	<del>16</del> 2 16	to	<u>20</u>					
460	PILE	1	5.5	<u>-18</u>	0				
465	PILE	11	1.5	<u>-18</u>	0				
470	PILE	16	-5.5	<u>-18</u>	0				
475	ROW Y	10	1	9	AT	4.0			
480	ROW Y	5	11	4	AT	9.0			
485	ROW Y	5	16	4	AT	9.0			
500	LOAD	1	424.4	0	652.8	0	-4348.4	0	
510	LOAD	2	424.4	0	548.0	0	-4024.0	0	
520	LOAD	3	402.4	0	505.8	0	-4189.8	0	
530	LOAD	4	402.4	0	419.4	0	-3923.5	0	
540	LOAD	5	39.6	0	545.2	0	-1106.4	0	
550	LOAD	6	14.1	0	408.9	0	-552.9	0	
600	FOUT	1 2 3 4 5 6 7							SWEETED
610	PROP	ALL							
620	FPL	SWEETED							

13 782  
42 381  
42 382  
42 383  
42 384  
42 385  
42 386  
42 387  
42 388  
42 389  
42 390



50 SHEETS FILER 5 SQUARE  
50 SHEETS FIVE EASE 5 SQUARE  
100 SHEETS FIVE EASE 5 SQUARE  
100 SHEETS FIVE EASE 5 SQUARE  
100 RECYCLED WHITE 5 SQUARE  
200 RECYCLED WHITE 5 SQUARE  
MADE IN U.S.A.

SUMMARY OF PILE LOADS:

	MAX C	MAX T
PROTECTED SIDE	73.9 <sup>k</sup>	—
MIDDLE ROW	35.7 <sup>k</sup>	-28.0 <sup>k</sup>
FLOOD SIDE	48.8 <sup>k</sup>	-43.0 <sup>k</sup>

ALLOWABLE C = 71.0<sup>k</sup>

T = 53.6<sup>k</sup>

$(73.9 - 71.0) / 71.0 = 3.21\%$  over

- i. use top elevation slightly deeper than -69 NS/D
- use -72 NS/D, - add note to verify w/ deeper boring during final design.

13 782 500 SHEETS FULLER 5 SQUARE  
47 381 50 SHEETS EYE-EASE 5 SQUARE  
42 382 100 SHEETS EYE-EASE 5 SQUARE  
42 383 200 SHEETS EYE-EASE 5 SQUARE  
42 384 100 SHEETS EYE-EASE 5 SQUARE  
42 385 200 SHEETS EYE-EASE 5 SQUARE  
42 386 100 RECYCLED WHITE 5 SQUARE  
42 387 200 RECYCLED WHITE 5 SQUARE  
Made in U.S.A.



100 S&WB #11 EAST T-WALL  
200 PROP 4074 3201 3201 196 2.0 0.0 ALL  
300 SOIL ES 0.066 LEN 64 0 ALL  
320 PIN ALL  
400 DLS S 72 54 600 223 133 1510 1167 H 14 ALL  
420 ASC S 196 457 0.816 0.856 1.75 0.0 ALL  
440 BAT 2.0 ALL  
450 ANG 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
455 ANG 180 16 17 18 19 20  
460 PILE 1 5.5 -18 0  
465 PILE 11 1.5 -18 0  
470 PILE 16 -5.5 -18 0  
475 ROW Y 10 1 9 AT 4.0  
480 ROW Y 5 11 4 AT 9.0  
485 ROW Y 5 16 4 AT 9.0  
500 LOAD 1 424.4 0 652.8 0 -4348.4 0  
510 LOAD 2 424.4 0 548.0 0 -4024.0 0  
520 LOAD 3 402.4 0 505.8 0 -4189.8 0  
530 LOAD 4 402.4 0 419.4 0 -3922.5 0  
540 LOAD 5 39.6 0 545.2 0 -1106.4 0  
550 LOAD 6 14.1 0 408.9 0 -552.9 0  
600 FOUT 1 2 3 4 5 6 7 SWB11EO  
610 PFO ALL  
620 FPL SWB11EP

\*\*\*\*\*  
 \* CORPS PROGRAM # X0080 \* CPGA - CASE PILE GROUP ANALYSIS PROGRAM  
 \* VERSION NUMBER # 86/09/02-A \* RUN DATE 03-31-98 RUN TIME 13:19:53  
 \*\*\*\*\*

S&WB #11 EAST T-WALL

THERE ARE 20 PILES AND  
 6 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = {  $\begin{matrix} X & Y & Z \\ \hline -5.50 & -18.00 & .00 \\ 5.50 & 18.00 & .00 \end{matrix}$  }

\*\*\*\*\*

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40740E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.66000E-01	L	.64000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -

ALL

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	5.50	-18.00	.00	2.00	.00	64.00	P
2	5.50	-14.00	.00	2.00	.00	64.00	P
3	5.50	-10.00	.00	2.00	.00	64.00	P
4	5.50	-6.00	.00	2.00	.00	64.00	P
5	5.50	-2.00	.00	2.00	.00	64.00	P
6	5.50	2.00	.00	2.00	.00	64.00	P

7	5.50	6.00	.00	2.00	.00	64.00	P
8	5.50	10.00	.00	2.00	.00	64.00	P
9	5.50	14.00	.00	2.00	.00	64.00	P
10	5.50	18.00	.00	2.00	.00	64.00	P
11	1.50	-18.00	.00	2.00	.00	64.00	P
12	1.50	-9.00	.00	2.00	.00	64.00	P
13	1.50	.00	.00	2.00	.00	64.00	P
14	1.50	9.00	.00	2.00	.00	64.00	P
15	1.50	18.00	.00	2.00	.00	64.00	P
16	-5.50	-18.00	.00	2.00	180.00	64.00	P
17	-5.50	-9.00	.00	2.00	180.00	64.00	P
18	-5.50	.00	.00	2.00	180.00	64.00	P
19	-5.50	9.00	.00	2.00	180.00	64.00	P
20	-5.50	18.00	.00	2.00	180.00	64.00	P

-----  
1280.00

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	424.4	.0	652.8	.0	-4348.4	.0
2	424.4	.0	548.0	.0	-4024.0	.0
3	402.4	.0	505.8	.0	-4189.8	.0
4	402.4	.0	419.4	.0	-3922.5	.0
5	39.6	.0	545.2	.0	-1106.4	.0
6	14.1	.0	408.9	.0	-552.9	.0

\*\*\*\*\*

ORIGINAL PILE GROUP STIFFNESS MATRIX

.84063E+04	.18131E-03	.82956E+04	-.15625E-01	-.89593E+06	-.15625E-01
.18131E-03	.11066E+03	-.36261E-03	.00000E+00	-.23932E-01	.23239E+04
.82956E+04	-.36261E-03	.33293E+05	-.31250E-01	-.69916E+06	.31250E-01
-.15625E-01	.00000E+00	-.31250E-01	.70475E+09	.00000E+00	-.15768E+09
-.89593E+06	-.23932E-01	-.69916E+06	.00000E+00	.11147E+09	.00000E+00
.00000E+00	.23239E+04	.31250E-01	-.15768E+09	.00000E+00	.17831E+09

LOAD CASE 1. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
LOAD CASE 2. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
LOAD CASE 3. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
LOAD CASE 4. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
LOAD CASE 5. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
LOAD CASE 6. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.

\*\*\*\*\*



FILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	-.2627E-01	-.4038E-07	.1369E-01	-.4916E-12	-.5934E-03	-.2308E-11
2	.1419E-01	-.5907E-07	.7166E-02	.6528E-12	-.2742E-03	-.9128E-13
3	-.2021E-01	-.6036E-07	.8458E-02	-.2850E-12	-.5604E-03	-.9478E-12
4	.1313E-01	-.7577E-07	.3079E-02	.6581E-12	-.2974E-03	.1030E-11
5	-.1148E+00	.8622E-07	.2660E-01	-.3315E-11	-.8747E-03	-.8718E-11
6	-.7649E-01	.7129E-07	.1979E-01	-.2247E-11	-.5502E-03	-.6383E-11

\*\*\*\*\*

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3\*EMIN) FOR CONCRETE PILES  
 B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
2	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
3	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
4	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
5	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
6	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
7	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
8	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
9	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
10	-.3	.0	73.9	.0	14.1	.0	1.03	.33	1.26	1.16
11	-.2	.0	20.9	.0	10.3	.0	1.03	.33	1.26	1.16
12	-.2	.0	20.9	.0	10.3	.0	.29	.18	.99	.90
13	-.2	.0	20.9	.0	10.3	.0	.29	.18	.99	.90
14	-.2	.0	20.9	.0	10.3	.0	.29	.18	.99	.90
15	-.2	.0	20.9	.0	10.3	.0	.29	.18	.99	.90
16	-.2	.0	20.9	.0	10.3	.0	.29	.18	.99	.90
17	.2	.0	-22.9	.0	-10.4	.0	.42	.30	.76	.68
18	.2	.0	-22.9	.0	-10.4	.0	.42	.30	.76	.68
19	.2	.0	-22.9	.0	-10.4	.0	.42	.30	.76	.68
20	.2	.0	-22.9	.0	-10.4	.0	.42	.30	.76	.68

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	60.2	.0	-.4	.0	.84	.21	1.16	1.12
2	.0	.0	60.2	.0	-.4	.0	.84	.21	1.16	1.12

3											
4											
5											
6											
7											
8											
9											
10											
11											
12											
13											
14											
15											
16											
17											
18											
19											
20											

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-	.0	65.7	.0	11.5	.0	.91	.26	1.22	1.13
2	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
3	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
4	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
5	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
6	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
7	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
8	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
9	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
10	-	.00	65.7	.00	11.5	.00	.91	.26	1.22	1.13
11	-	.00	15.7	.00	7.9	.00	.22	.19	.95	.88
12	-	.00	15.7	.00	7.9	.00	.22	.19	.95	.88
13	-	.00	15.7	.00	7.9	.00	.22	.19	.95	.88
14	-	.00	15.7	.00	7.9	.00	.22	.19	.95	.88
15	-	.00	15.7	.00	7.9	.00	.22	.19	.95	.88
16	-	.00	-34.3	.00	-9.2	.00	.63	.44	.70	.62
17	-	.00	-34.3	.00	-9.2	.00	.63	.44	.70	.62
18	-	.00	-34.3	.00	-9.2	.00	.63	.44	.70	.62
19	-	.00	-34.3	.00	-9.2	.00	.63	.44	.70	.62
20	-	.00	-34.3	.00	-9.2	.00	.63	.44	.70	.62

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	54.4	.0	.5	.0	.76	.17	1.13	1.09
2	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
3	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
4	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
5	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
6	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
7	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09
8	.00	.00	54.4	.00	.5	.00	.76	.17	1.13	1.09

9											
10	0.00	0.00	54.4	0.00	1.1	0.00	0.76	.17	1.13	1.00	##
11	0.00	0.00	54.4	0.00	1.1	0.00	.76	.17	1.13	1.00	##
12	0.00	0.00	27.9	0.00	2.4	0.00	.39	.17	1.00	1.00	##
13	0.00	0.00	27.9	0.00	2.4	0.00	.39	.17	1.00	1.00	##
14	0.00	0.00	27.9	0.00	2.4	0.00	.39	.17	1.00	1.00	##
15	0.00	0.00	27.9	0.00	2.4	0.00	.39	.17	1.00	1.00	##
16	0.00	0.00	27.9	0.00	2.4	0.00	.39	.17	1.00	1.00	##
17	0.00	0.00	-43.0	0.00	1.3	0.00	.80	.52	.64	.59	##
18	0.00	0.00	-43.0	0.00	1.3	0.00	.80	.52	.64	.59	##
19	0.00	0.00	-43.0	0.00	1.3	0.00	.80	.52	.64	.59	##
20	0.00	0.00	-43.0	0.00	1.3	0.00	.80	.52	.64	.59	##

LOAD CASE - 5

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
2	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
3	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
4	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
5	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
6	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
7	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
8	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
9	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
10	8	0	50.1	0	41.9	0	.70	.13	1.20	.98	##
11	7	0	28.0	0	36.3	0	.52	.42	.79	.59	##
12	7	0	28.0	0	36.3	0	.52	.42	.79	.59	##
13	7	0	28.0	0	36.3	0	.52	.42	.79	.59	##
14	7	0	28.0	0	36.3	0	.52	.42	.79	.59	##
15	7	0	28.0	0	36.3	0	.52	.42	.79	.59	##
16	6	0	48.8	0	34.8	0	.68	.12	1.18	.99	##
17	6	0	48.8	0	34.8	0	.68	.12	1.18	.99	##
18	6	0	48.8	0	34.8	0	.68	.12	1.18	.99	##
19	6	0	48.8	0	34.8	0	.68	.12	1.18	.99	##
20	6	0	48.8	0	34.8	0	.68	.12	1.18	.99	##

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
2	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
3	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
4	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
5	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
6	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
7	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
8	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
9	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
10	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
11	5	0	33.2	0	27.9	0	.46	.16	1.09	.92	##
12	5	0	15.9	0	24.4	0	.29	.25	.83	.68	##
13	5	0	15.9	0	24.4	0	.29	.25	.83	.68	##
14	5	0	15.9	0	24.4	0	.29	.25	.83	.68	##

15	-.5	.0	-15.9	.0	24.4	.0	.29	.25	.83	.68
16	.4	.0	40.4	.0	-22.6	.0	.56	.14	1.11	.97
17	.4	.0	40.4	.0	-22.6	.0	.56	.14	1.11	.97
18	.4	.0	40.4	.0	-22.6	.0	.56	.14	1.11	.97
19	.4	.0	40.4	.0	-22.6	.0	.56	.14	1.11	.97
20	.4	.0	40.4	.0	-22.6	.0	.56	.14	1.11	.97

\*\*\*\*\*

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	32.8	.0	66.2	.0	.0	.0
2	32.8	.0	66.2	.0	.0	.0
3	32.8	.0	66.2	.0	.0	.0
4	32.8	.0	66.2	.0	.0	.0
5	32.8	.0	66.2	.0	.0	.0
6	32.8	.0	66.2	.0	.0	.0
7	32.8	.0	66.2	.0	.0	.0
8	32.8	.0	66.2	.0	.0	.0
9	32.8	.0	66.2	.0	.0	.0
10	32.8	.0	66.2	.0	.0	.0
11	9.2	.0	18.8	.0	.0	.0
12	9.2	.0	18.8	.0	.0	.0
13	9.2	.0	18.8	.0	.0	.0
14	9.2	.0	18.8	.0	.0	.0
15	9.2	.0	18.8	.0	.0	.0
16	10.1	.0	-20.6	.0	.0	.0
17	10.1	.0	-20.6	.0	.0	.0
18	10.1	.0	-20.6	.0	.0	.0
19	10.1	.0	-20.6	.0	.0	.0
20	10.1	.0	-20.6	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	26.9	.0	53.8	.0	.0	.0
2	26.9	.0	53.8	.0	.0	.0
3	26.9	.0	53.8	.0	.0	.0
4	26.9	.0	53.8	.0	.0	.0
5	26.9	.0	53.8	.0	.0	.0
6	26.9	.0	53.8	.0	.0	.0
7	26.9	.0	53.8	.0	.0	.0
8	26.9	.0	53.8	.0	.0	.0
9	26.9	.0	53.8	.0	.0	.0
10	26.9	.0	53.8	.0	.0	.0
11	16.0	.0	31.9	.0	.0	.0
12	16.0	.0	31.9	.0	.0	.0
13	16.0	.0	31.9	.0	.0	.0
14	16.0	.0	31.9	.0	.0	.0

15	16.0	.0	31.9	.0	.0	.0
16	15.0	.00	-30.0	.00	.00	.00
17	15.0	.00	-30.0	.00	.00	.00
18	15.0	.00	-30.0	.00	.00	.00
19	15.0	.00	-30.0	.00	.00	.00
20	15.0	.00	-30.0	.00	.00	.00

LOAD CASE - 3

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	29.2	.0	58.9	.0	.0	.0
2	29.2	.00	58.9	.00	.00	.00
3	29.2	.00	58.9	.00	.00	.00
4	29.2	.00	58.9	.00	.00	.00
5	29.2	.00	58.9	.00	.00	.00
6	29.2	.00	58.9	.00	.00	.00
7	29.2	.00	58.9	.00	.00	.00
8	29.2	.00	58.9	.00	.00	.00
9	29.2	.00	58.9	.00	.00	.00
10	29.2	.00	58.9	.00	.00	.00
11	6.9	.00	14.1	.00	.00	.00
12	6.9	.00	14.1	.00	.00	.00
13	6.9	.00	14.1	.00	.00	.00
14	6.9	.00	14.1	.00	.00	.00
15	6.9	.00	14.1	.00	.00	.00
16	15.2	.00	-30.7	.00	.00	.00
17	15.2	.00	-30.7	.00	.00	.00
18	15.2	.00	-30.7	.00	.00	.00
19	15.2	.00	-30.7	.00	.00	.00
20	15.2	.00	-30.7	.00	.00	.00

LOAD CASE - 4

FILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	24.4	.0	48.7	.0	.0	.0
2	24.4	.00	48.7	.00	.00	.00
3	24.4	.00	48.7	.00	.00	.00
4	24.4	.00	48.7	.00	.00	.00
5	24.4	.00	48.7	.00	.00	.00
6	24.4	.00	48.7	.00	.00	.00
7	24.4	.00	48.7	.00	.00	.00
8	24.4	.00	48.7	.00	.00	.00
9	24.4	.00	48.7	.00	.00	.00
10	24.4	.00	48.7	.00	.00	.00
11	12.5	.00	24.9	.00	.00	.00
12	12.5	.00	24.9	.00	.00	.00
13	12.5	.00	24.9	.00	.00	.00
14	12.5	.00	24.9	.00	.00	.00
15	12.5	.00	24.9	.00	.00	.00
16	19.2	.00	-38.4	.00	.00	.00
17	19.2	.00	-38.4	.00	.00	.00
18	19.2	.00	-38.4	.00	.00	.00
19	19.2	.00	-38.4	.00	.00	.00
20	19.2	.00	-38.4	.00	.00	.00


## LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	21.7	.0	45.2	.0	.0	.0
2	21.7	.0	45.2	.0	.0	.0
3	21.7	.0	45.2	.0	.0	.0
4	21.7	.0	45.2	.0	.0	.0
5	21.7	.0	45.2	.0	.0	.0
6	21.7	.0	45.2	.0	.0	.0
7	21.7	.0	45.2	.0	.0	.0
8	21.7	.0	45.2	.0	.0	.0
9	21.7	.0	45.2	.0	.0	.0
10	21.7	.0	45.2	.0	.0	.0
11	-13.1	.0	-24.7	.0	.0	.0
12	-13.1	.0	-24.7	.0	.0	.0
13	-13.1	.0	-24.7	.0	.0	.0
14	-13.1	.0	-24.7	.0	.0	.0
15	-13.1	.0	-24.7	.0	.0	.0
16	-22.4	.0	43.4	.0	.0	.0
17	-22.4	.0	43.4	.0	.0	.0
18	-22.4	.0	43.4	.0	.0	.0
19	-22.4	.0	43.4	.0	.0	.0
20	-22.4	.0	43.4	.0	.0	.0

## LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	14.4	.0	29.9	.0	.0	.0
2	14.4	.0	29.9	.0	.0	.0
3	14.4	.0	29.9	.0	.0	.0
4	14.4	.0	29.9	.0	.0	.0
5	14.4	.0	29.9	.0	.0	.0
6	14.4	.0	29.9	.0	.0	.0
7	14.4	.0	29.9	.0	.0	.0
8	14.4	.0	29.9	.0	.0	.0
9	14.4	.0	29.9	.0	.0	.0
10	14.4	.0	29.9	.0	.0	.0
11	-7.5	.0	-14.0	.0	.0	.0
12	-7.5	.0	-14.0	.0	.0	.0
13	-7.5	.0	-14.0	.0	.0	.0
14	-7.5	.0	-14.0	.0	.0	.0
15	-7.5	.0	-14.0	.0	.0	.0
16	-18.4	.0	35.9	.0	.0	.0
17	-18.4	.0	35.9	.0	.0	.0
18	-18.4	.0	35.9	.0	.0	.0
19	-18.4	.0	35.9	.0	.0	.0
20	-18.4	.0	35.9	.0	.0	.0

ELEVATION IN FEET N.G.V.D.




2) The Low Weighted Creep Ratio is 3.8 for a new T wall cut off wall tip at EL -35. This is considered acceptable protection against potential piping.

4) T wall analysis indicates no unbalanced forces beneath base of proposed new T wall at EL -11.0. Batter piles must be used to carry the indicated T-wall pressure.

NOTE: 1) "P" IS REQUIRED VERTICAL PRESSURE ACROSS TOP OF PASSIVE WEDGES TO ACHIEVE A CALCULATED FACTOR OF SAFETY OF 1.3 OR MORE AGAINST A STABILITY FAILURE.

2) SEEPAGE ANALYSIS BY HARR METHOD INDICATES A FACTOR OF SAFETY OF 6 OR MORE AGAINST PIPING WHICH IS CONSIDERED ACCEPTABLE.

3) REACH & SOIL PARAMETERS WERE USED FOR THESE ANALYSES. LOCATION OF STRATUM 2 IS BASED ON BORING ALCW-7.



Global Stability of Pump Station

FAILURE SURFACE	SUMMATION OF FORCES LB/FT		FACTOR OF SAFETY	VERTICAL PRESSURE, P, IN PSF TO ACHIEVE FACTOR OF SAFETY - 1.3
	RESISTING	DRIVING		
<del>(A)-(1)</del>	<del>34145</del>	<del>16088</del>	<del>2.13</del>	
(A)-(2)	51147	45140	1.13	278 942
(A)-(3)	61163	58748	1.04	
(B)-(4)	73287	45185	1.62	
(B)-(5)	22308	39158	1.14	249 699
(C)-(6)	69247	60989	1.14	
(C)-(7)	69263	74848	1.18	
(D)-(8)	90182	60902	1.48	
(D)-(9)	90106	74858	1.33	
(E)-(10)	87474	74754	1.30	
(E)-(11)	97133	73152	1.33	
(E)-(12)	97150	86872	1.12	
(F)-(13)	110000	86736	1.36	300

STRATUM NO.	SOIL TYPE	UNIT WEIGHT IN PCF	Unfactored		Factor of Safety = 1.3		
			FRICTION ANGLE DEGREES	COHESION - PSF	Fraction Angle Degrees	Cohesion Average	PSF Bottom
1	CLAY, SILTY CLAY, ORGANIC CLAY & HUMUS	92.0	0	AVERAGE: 350 BOTTOM: 350	0	269	269
2	CLAY	101.0	0	350	0	269	269
3	CLAY	101.0	0	400	0	308	308
4	CLAY	101.0	0	480	0	369	431

T-wall Analysis

Failure Surface	ER Resisting lb/ft	ED Driving lb/ft	ER-ED	Change in Net Force, lb/ft
(D)-(8)	4142	8357	-4185	
(E)-(11)	51110	51916	-806	3379
(E)-(12)	66784	66066	718	1520

SLOPE STABILITY ANALYSES OF EAST PUMP STATION AT N.O. S&WB PUMP STATION NO. 11 East

U.S. ARMY CORPS OF ENGINEERS  
EAST OF HARVEY CANAL  
HURRICANE PROTECTION PROJECT  
JEFFERSON PARISH, LOUISIANA

U.S ARMY CORPS OF ENGINEERS  
 EAST OF HARVEY CANAL  
 HURRICANE PROTECTION PROJECT  
 JEFFERSON PARISH, LOUISIANA

Proposed T Wall  
 SWB P. Station ~~11~~ East

ALLOWABLE PILE LOAD CAPACITIES  
 SQUARE PRECAST, PRESTRESSED CONCRETE PILES  
 TOP OF PILE AT EL ~~1~~ -10

SIZE	PILE TIP ELEVATION IN FEET NGVD	ALLOWABLE PILE LOAD CAPACITY IN TONS FACTOR OF SAFETY ≈ 2	
		COMPRESSION	TENSION
12-In. Square	-39	12 16	9 12
	-49	16 20	12 16
	-59	21 26	16 20
	-69	27 32	20 24
14-In. Square	-39	17 19	10 14
	-49	19 24	14 18
	-59	25 30	18 23
	-69	32 37	24 28








13-782 500 SHEETS, FILLER 5 SQUARE  
42-381 50 SHEETS EYE EASE® 5 SQUARE  
42-382 100 SHEETS EYE EASE® 5 SQUARE  
42-389 200 SHEETS EYE EASE® 5 SQUARE  
42-392 100 RECYCLED WHITE 5 SQUARE  
42-399 200 RECYCLED WHITE 5 SQUARE  
Made in U.S.A.

MS

3004

T-WALL ANALYSIS

PROTECTED SIDE




FLOODSIDE

- CLOCKWISE  
+ ANTICLOCK

BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- y FT	- z FT	MOMENT IK
1	<u>DEAD LOAD</u> <hr/> <u>WT. OF STEM &amp; BASE</u> <hr/> <p style="text-align: center;">STEM 20.5' X 1' X .15'                      1/2' X 20.5' X 1.5' X .15'                      BASE 14' X 2.5' X .15'</p>		3.08 2.31 5.25 <hr/> 10.64 ↓	3.0 4.0 <hr/>	9.5 <hr/>	9.24 ↷ 9.24 ↷ - <hr/> 18.48 ↷
2	<u>WATER ON FLOODSIDE</u> <hr/> <hr/> <p style="text-align: center;">SWL 9.50</p> <p>a) VERTICAL 9.5' X 18.5' X .0625</p> <p>b) LATERAL 1/2' X 13.13' X 21</p>	13.8 <hr/> 13.8 ←	10.98 <hr/> 10.98 ↓	2.25 <hr/> 7.0		24.7 ↷ 96.6 ↷ <hr/> 71.9 ↷
	Total					


NATIONAL BRAND  
 MANUFACTURED IN U.S.A.  
 100% COTTON FIBER  
 42-44  
 44-46  
 46-48  
 48-50  
 50-52  
 52-54  
 54-56  
 56-58  
 58-60  
 60-62  
 62-64  
 64-66  
 66-68  
 68-70  
 70-72  
 72-74  
 74-76  
 76-78  
 78-80  
 80-82  
 82-84  
 84-86  
 86-88  
 88-90  
 90-92  
 92-94  
 94-96  
 96-98  
 98-100



- CLOCKWISE  
+ ANTICLOCK

BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- ȳ FT	- ȳ FT	MOMENT IK
3	<p><u>BUOYANCY</u> <u>SWL EL 9.50</u></p> <p>a) <u>PERVIOUS</u> <u>1/2 X 1313 X 14'</u></p> <p>b) <u>IMPERVIOUS</u> <u>1313 X 5</u></p>		<p>-9.2</p> <p>-6.56</p>	<p>2.33</p> <p>4.5</p>		<p>21.44 ↷</p> <p>29.5 ↷</p>
4)	<p><u>SOIL ON PROTECTED</u> <u>SIDE</u></p> <p>a) VERT. <sup>KCF</sup> 2' X 9' X .105 1/2 X .66' X 9' X .105</p> <p>b) Lateral soil 1/2 X .664 X 11.5'</p>	<p>-3.82</p>	<p>1.89</p> <p>0.31</p>	<p>6.0</p> <p>4.78</p>	<p>3.83</p>	<p>+ 11.34 ↷</p> <p>+ 1.48 ↷</p> <p>- 15.21 ↷</p>
		<p>-3.82 →</p>	<p>2.20 ↓</p>			<p>- 2.39 ↷</p>

1. ALL DIMENSIONS ARE IN FEET UNLESS OTHERWISE SPECIFIED  
2. ALL WEIGHTS ARE IN KILOPOUNDS UNLESS OTHERWISE SPECIFIED  
3. ALL ANGLES ARE IN DEGREES UNLESS OTHERWISE SPECIFIED  
4. ALL SURFACES ARE TO BE FINISHED UNLESS OTHERWISE SPECIFIED  
5. ALL DIMENSIONS ARE TO FACE UNLESS OTHERWISE SPECIFIED  
6. ALL DIMENSIONS ARE TO CENTERLINE UNLESS OTHERWISE SPECIFIED  
7. ALL DIMENSIONS ARE TO CENTERLINE UNLESS OTHERWISE SPECIFIED  
8. ALL DIMENSIONS ARE TO CENTERLINE UNLESS OTHERWISE SPECIFIED  
9. ALL DIMENSIONS ARE TO CENTERLINE UNLESS OTHERWISE SPECIFIED  
10. ALL DIMENSIONS ARE TO CENTERLINE UNLESS OTHERWISE SPECIFIED



- CLOCKWISE  
+ ANTICLOCK

BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y FT	- Z FT	MOMENT IK
5)	<u>WATER ON FLOODSIDE</u> <u>EL. SWL +2.0</u> <u>W.S. EL. 11.5</u>  a) VERTICAL 9.5 x 20.5' x .0625  b) LATERAL 1/2 x 1.438 x 23.0   Total	16.54 ←	12.18 ↓	2.25	7.67	27.40 ↘ 126.86 ↗ 99.46 ↗
6)	<u>BUOYANCY</u> <u>W.S. EL 11.50</u>  a) PEROUS 1/2 x 1.438 x 14'  b) IMPERVIOUS 1.438 x 5'		-10.07	2.33		23.46 ↘ 32.4 ↘

11.0K  
 11.5K  
 12.0K  
 12.5K  
 13.0K  
 13.5K  
 14.0K  
 14.5K  
 15.0K  
 15.5K  
 16.0K  
 16.5K  
 17.0K  
 17.5K  
 18.0K  
 18.5K  
 19.0K  
 19.5K  
 20.0K  
 20.5K  
 21.0K  
 21.5K  
 22.0K  
 22.5K  
 23.0K  
 23.5K  
 24.0K  
 24.5K  
 25.0K  
 25.5K  
 26.0K  
 26.5K  
 27.0K  
 27.5K  
 28.0K  
 28.5K  
 29.0K  
 29.5K  
 30.0K  
 30.5K  
 31.0K  
 31.5K  
 32.0K  
 32.5K  
 33.0K  
 33.5K  
 34.0K  
 34.5K  
 35.0K  
 35.5K  
 36.0K  
 36.5K  
 37.0K  
 37.5K  
 38.0K  
 38.5K  
 39.0K  
 39.5K  
 40.0K  
 40.5K  
 41.0K  
 41.5K  
 42.0K  
 42.5K  
 43.0K  
 43.5K  
 44.0K  
 44.5K  
 45.0K  
 45.5K  
 46.0K  
 46.5K  
 47.0K  
 47.5K  
 48.0K  
 48.5K  
 49.0K  
 49.5K  
 50.0K






MS.

- CLOCKWISE  
+ ANTICLOCK

BASIC LOAD COND	DESCRIPTION	+ ← F <sub>y</sub> KIPS	+ ↓ F <sub>z</sub> KIPS	- Y FT	- Z FT	MOMENT IK	
9)	WIND FROM F/S						
		11.5 x .05	0.58		17.25	10.00 ↷	
			0.58 ←				10.00 ↷
10)	WIND FROM P/S						
		11.5 x .05	0.58		17.25	10.00 ↷	
			0.58 →				10.00 ↷


11/67  
40 WT  
42 WT  
44 WT  
46 WT  
48 WT  
50 WT  
52 WT  
54 WT  
56 WT  
58 WT  
60 WT  
62 WT  
64 WT  
66 WT  
68 WT  
70 WT  
72 WT  
74 WT  
76 WT  
78 WT  
80 WT  
82 WT  
84 WT  
86 WT  
88 WT  
90 WT  
92 WT  
94 WT  
96 WT  
98 WT  
100 WT  
102 WT  
104 WT  
106 WT  
108 WT  
110 WT  
112 WT  
114 WT  
116 WT  
118 WT  
120 WT  
122 WT  
124 WT  
126 WT  
128 WT  
130 WT  
132 WT  
134 WT  
136 WT  
138 WT  
140 WT  
142 WT  
144 WT  
146 WT  
148 WT  
150 WT  
152 WT  
154 WT  
156 WT  
158 WT  
160 WT  
162 WT  
164 WT  
166 WT  
168 WT  
170 WT  
172 WT  
174 WT  
176 WT  
178 WT  
180 WT  
182 WT  
184 WT  
186 WT  
188 WT  
190 WT  
192 WT  
194 WT  
196 WT  
198 WT  
200 WT



LOAD COMBINATIONS.

LD. COMB NO.	DESCRIPTION	$\leftarrow$ F <sub>y</sub>	F <sub>z</sub> ↓	MOMENT M <sub>XX</sub>
1	SWL @ EL 9.5 PERV. SH. PILE, SOIL @ PROT. SIDE UPTO EL 0.0, NO WIND			
	1) DL.		10.64	18.48 ↗
	2) Water F/s	13.8	10.98	71.9 ↗
	3 a) Buoy Perw.		-9.2	21.44 ↗
	4) Soil PROT. SIDE	-3.97	2.20	-2.39 ↘
	unbalanced soil	+2.1		
	TOTAL PER LFT	11.93	14.62	109.43 ↗
	TOTAL PER 40'	477.2	584.8	4377.2
2	SWL @ EL 9.5, IMP. SH. PILE, SOIL @ PROT. SIDE UPTO EL 0.0. NO WIND			
	1) D.L.		10.64	18.48 ↗
	2) WATER F/s	13.8	10.98	71.9 ↗
	3 b) Buoy IMP		-6.56	29.5 ↗
	4) SOIL P/s	-3.97	2.20	-2.39 ↘
	unbalanced soil	+2.1		
	TOTAL PER LFT	11.93	17.26	117.49 ↗
	TOTAL PER 40' 0"	477.2	690.4	4,700 ↗

11 76  
11 77  
11 78  
11 79  
11 80  
11 81  
11 82  
11 83  
11 84  
11 85  
11 86  
11 87  
11 88  
11 89  
11 90  
11 91  
11 92  
11 93  
11 94  
11 95  
11 96  
11 97  
11 98  
11 99  
12 00  
12 01  
12 02  
12 03  
12 04  
12 05  
12 06  
12 07  
12 08  
12 09  
12 10  
12 11  
12 12  
12 13  
12 14  
12 15  
12 16  
12 17  
12 18  
12 19  
12 20  
12 21  
12 22  
12 23  
12 24  
12 25  
12 26  
12 27  
12 28  
12 29  
12 30  
12 31  
12 32  
12 33  
12 34  
12 35  
12 36  
12 37  
12 38  
12 39  
12 40  
12 41  
12 42  
12 43  
12 44  
12 45  
12 46  
12 47  
12 48  
12 49  
12 50  
12 51  
12 52  
12 53  
12 54  
12 55  
12 56  
12 57  
12 58  
12 59  
12 60  
12 61  
12 62  
12 63  
12 64  
12 65  
12 66  
12 67  
12 68  
12 69  
12 70  
12 71  
12 72  
12 73  
12 74  
12 75  
12 76  
12 77  
12 78  
12 79  
12 80  
12 81  
12 82  
12 83  
12 84  
12 85  
12 86  
12 87  
12 88  
12 89  
12 90  
12 91  
12 92  
12 93  
12 94  
12 95  
12 96  
12 97  
12 98  
12 99  
13 00  
13 01  
13 02  
13 03  
13 04  
13 05  
13 06  
13 07  
13 08  
13 09  
13 10  
13 11  
13 12  
13 13  
13 14  
13 15  
13 16  
13 17  
13 18  
13 19  
13 20  
13 21  
13 22  
13 23  
13 24  
13 25  
13 26  
13 27  
13 28  
13 29  
13 30  
13 31  
13 32  
13 33  
13 34  
13 35  
13 36  
13 37  
13 38  
13 39  
13 40  
13 41  
13 42  
13 43  
13 44  
13 45  
13 46  
13 47  
13 48  
13 49  
13 50  
13 51  
13 52  
13 53  
13 54  
13 55  
13 56  
13 57  
13 58  
13 59  
13 60  
13 61  
13 62  
13 63  
13 64  
13 65  
13 66  
13 67  
13 68  
13 69  
13 70  
13 71  
13 72  
13 73  
13 74  
13 75  
13 76  
13 77  
13 78  
13 79  
13 80  
13 81  
13 82  
13 83  
13 84  
13 85  
13 86  
13 87  
13 88  
13 89  
13 90  
13 91  
13 92  
13 93  
13 94  
13 95  
13 96  
13 97  
13 98  
13 99  
14 00  
14 01  
14 02  
14 03  
14 04  
14 05  
14 06  
14 07  
14 08  
14 09  
14 10  
14 11  
14 12  
14 13  
14 14  
14 15  
14 16  
14 17  
14 18  
14 19  
14 20  
14 21  
14 22  
14 23  
14 24  
14 25  
14 26  
14 27  
14 28  
14 29  
14 30  
14 31  
14 32  
14 33  
14 34  
14 35  
14 36  
14 37  
14 38  
14 39  
14 40  
14 41  
14 42  
14 43  
14 44  
14 45  
14 46  
14 47  
14 48  
14 49  
14 50  
14 51  
14 52  
14 53  
14 54  
14 55  
14 56  
14 57  
14 58  
14 59  
14 60  
14 61  
14 62  
14 63  
14 64  
14 65  
14 66  
14 67  
14 68  
14 69  
14 70  
14 71  
14 72  
14 73  
14 74  
14 75  
14 76  
14 77  
14 78  
14 79  
14 80  
14 81  
14 82  
14 83  
14 84  
14 85  
14 86  
14 87  
14 88  
14 89  
14 90  
14 91  
14 92  
14 93  
14 94  
14 95  
14 96  
14 97  
14 98  
14 99  
15 00  
15 01  
15 02  
15 03  
15 04  
15 05  
15 06  
15 07  
15 08  
15 09  
15 10  
15 11  
15 12  
15 13  
15 14  
15 15  
15 16  
15 17  
15 18  
15 19  
15 20  
15 21  
15 22  
15 23  
15 24  
15 25  
15 26  
15 27  
15 28  
15 29  
15 30  
15 31  
15 32  
15 33  
15 34  
15 35  
15 36  
15 37  
15 38  
15 39  
15 40  
15 41  
15 42  
15 43  
15 44  
15 45  
15 46  
15 47  
15 48  
15 49  
15 50  
15 51  
15 52  
15 53  
15 54  
15 55  
15 56  
15 57  
15 58  
15 59  
15 60  
15 61  
15 62  
15 63  
15 64  
15 65  
15 66  
15 67  
15 68  
15 69  
15 70  
15 71  
15 72  
15 73  
15 74  
15 75  
15 76  
15 77  
15 78  
15 79  
15 80  
15 81  
15 82  
15 83  
15 84  
15 85  
15 86  
15 87  
15 88  
15 89  
15 90  
15 91  
15 92  
15 93  
15 94  
15 95  
15 96  
15 97  
15 98  
15 99  
16 00  
16 01  
16 02  
16 03  
16 04  
16 05  
16 06  
16 07  
16 08  
16 09  
16 10  
16 11  
16 12  
16 13  
16 14  
16 15  
16 16  
16 17  
16 18  
16 19  
16 20  
16 21  
16 22  
16 23  
16 24  
16 25  
16 26  
16 27  
16 28  
16 29  
16 30  
16 31  
16 32  
16 33  
16 34  
16 35  
16 36  
16 37  
16 38  
16 39  
16 40  
16 41  
16 42  
16 43  
16 44  
16 45  
16 46  
16 47  
16 48  
16 49  
16 50  
16 51  
16 52  
16 53  
16 54  
16 55  
16 56  
16 57  
16 58  
16 59  
16 60  
16 61  
16 62  
16 63  
16 64  
16 65  
16 66  
16 67  
16 68  
16 69  
16 70  
16 71  
16 72  
16 73  
16 74  
16 75  
16 76  
16 77  
16 78  
16 79  
16 80  
16 81  
16 82  
16 83  
16 84  
16 85  
16 86  
16 87  
16 88  
16 89  
16 90  
16 91  
16 92  
16 93  
16 94  
16 95  
16 96  
16 97  
16 98  
16 99  
17 00  
17 01  
17 02  
17 03  
17 04  
17 05  
17 06  
17 07  
17 08  
17 09  
17 10  
17 11  
17 12  
17 13  
17 14  
17 15  
17 16  
17 17  
17 18  
17 19  
17 20  
17 21  
17 22  
17 23  
17 24  
17 25  
17 26  
17 27  
17 28  
17 29  
17 30  
17 31  
17 32  
17 33  
17 34  
17 35  
17 36  
17 37  
17 38  
17 39  
17 40  
17 41  
17 42  
17 43  
17 44  
17 45  
17 46  
17 47  
17 48  
17 49  
17 50  
17 51  
17 52  
17 53  
17 54  
17 55  
17 56  
17 57  
17 58  
17 59  
17 60  
17 61  
17 62  
17 63  
17 64  
17 65  
17 66  
17 67  
17 68  
17 69  
17 70  
17 71  
17 72  
17 73  
17 74  
17 75  
17 76  
17 77  
17 78  
17 79  
17 80  
17 81  
17 82  
17 83  
17 84  
17 85  
17 86  
17 87  
17 88  
17 89  
17 90  
17 91  
17 92  
17 93  
17 94  
17 95  
17 96  
17 97  
17 98  
17 99  
18 00  
18 01  
18 02  
18 03  
18 04  
18 05  
18 06  
18 07  
18 08  
18 09  
18 10  
18 11  
18 12  
18 13  
18 14  
18 15  
18 16  
18 17  
18 18  
18 19  
18 20  
18 21  
18 22  
18 23  
18 24  
18 25  
18 26  
18 27  
18 28  
18 29  
18 30  
18 31  
18 32  
18 33  
18 34  
18 35  
18 36  
18 37  
18 38  
18 39  
18 40  
18 41  
18 42  
18 43  
18 44  
18 45  
18 46  
18 47  
18 48  
18 49  
18 50  
18 51  
18 52  
18 53  
18 54  
18 55  
18 56  
18 57  
18 58  
18 59  
18 60  
18 61  
18 62  
18 63  
18 64  
18 65  
18 66  
18 67  
18 68  
18 69  
18 70  
18 71  
18 72  
18 73  
18 74  
18 75  
18 76  
18 77  
18 78  
18 79  
18 80  
18 81  
18 82  
18 83  
18 84  
18 85  
18 86  
18 87  
18 88  
18 89  
18 90  
18 91  
18 92  
18 93  
18 94  
18 95  
18 96  
18 97  
18 98  
18 99  
19 00  
19 01  
19 02  
19 03  
19 04  
19 05  
19 06  
19 07  
19 08  
19 09  
19 10  
19 11  
19 12  
19 13  
19 14  
19 15  
19 16  
19 17  
19 18  
19 19  
19 20  
19 21  
19 22  
19 23  
19 24  
19 25  
19 26  
19 27  
19 28  
19 29  
19 30  
19 31  
19 32  
19 33  
19 34  
19 35  
19 36  
19 37  
19 38  
19 39  
19 40  
19 41  
19 42  
19 43  
19 44  
19 45  
19 46  
19 47  
19 48  
19 49  
19 50  
19 51  
19 52  
19 53  
19 54  
19 55  
19 56  
19 57  
19 58  
19 59  
19 60  
19 61  
19 62  
19 63  
19 64  
19 65  
19 66  
19 67  
19 68  
19 69  
19 70  
19 71  
19 72  
19 73  
19 74  
19 75  
19 76  
19 77  
19 78  
19 79  
19 80  
19 81  
19 82  
19 83  
19 84  
19 85  
19 86  
19 87  
19 88  
19 89  
19 90  
19 91  
19 92  
19 93  
19 94  
19 95  
19 96  
19 97  
19 98  
19 99  
20 00





LOAD COMBINATIONS.

LD. COMB NO.	DESCRIPTION	← F <sub>Y</sub>	F <sub>Z</sub> ↓	MOMENT M <sub>XX</sub>
3	<u>W.S. EL 11.5, PERV. SH. PILE, SOIL</u> <u>ON P/S UPTO EL 0.0 NO WIND</u> <hr/> 1) D.L. 5) WATER F/S 6a) BUOY PERV 4) SOIL P/S Unbalanced Soil	16.54 -3.97	10.64 12.18 -10.07 2.20	18.48 ↗ 99.46 ↗ 23.46 ↗ -2.39 ↘ 139.01 ↗ 4170.3 ↗
	TOTAL PER LFT	12.57	14.95	139.01 ↗
	TOTAL PER 40' X .75	377.1	448.5	4170.3 ↗
4	<u>W.S. EL 11.5, IMP. SH. PILE, SOIL</u> <u>ON P/S UPTO EL 0.0 NO WIND.</u> <hr/> 1) D.L. 5) Water F/S 6b) BUOY IMP 4) SOIL P/S Unbalanced soil	16.54 -3.97	10.64 12.18 -7.2 2.20	18.48 ↗ 99.46 ↗ 32.4 ↗ -2.39 ↘ 147.95 ↗ 4439 ↗
	TOTAL PER LFT	12.57	17.82	147.95 ↗
	TOTAL PER 40' X .75	377.1	534.6	4439 ↗

1) 10' 2) 10' 3) 10' 4) 10' 5) 10' 6) 10' 7) 10' 8) 10' 9) 10' 10) 10'  
 11) 10' 12) 10' 13) 10' 14) 10' 15) 10' 16) 10' 17) 10' 18) 10' 19) 10'  
 20) 10' 21) 10' 22) 10' 23) 10' 24) 10' 25) 10' 26) 10' 27) 10' 28) 10'  
 29) 10' 30) 10' 31) 10' 32) 10' 33) 10' 34) 10' 35) 10' 36) 10' 37) 10'  
 38) 10' 39) 10' 40) 10' 41) 10' 42) 10' 43) 10' 44) 10' 45) 10' 46) 10'  
 47) 10' 48) 10' 49) 10' 50) 10' 51) 10' 52) 10' 53) 10' 54) 10' 55) 10'  
 56) 10' 57) 10' 58) 10' 59) 10' 60) 10' 61) 10' 62) 10' 63) 10' 64) 10'  
 65) 10' 66) 10' 67) 10' 68) 10' 69) 10' 70) 10' 71) 10' 72) 10' 73) 10'  
 74) 10' 75) 10' 76) 10' 77) 10' 78) 10' 79) 10' 80) 10' 81) 10' 82) 10'  
 83) 10' 84) 10' 85) 10' 86) 10' 87) 10' 88) 10' 89) 10' 90) 10' 91) 10'  
 92) 10' 93) 10' 94) 10' 95) 10' 96) 10' 97) 10' 98) 10' 99) 10' 100) 10'



APRIL16

April 20, 1998

Page 1

RECEIVED

APR 20 1998

MEMO

TO:DEI

ATTENTION: MS APRIL HURRY

FROM:EUSTIS ENGINEERING

TOM STREMLAU

SUBJECT: PREL INFO OF MODIFIED S &WB STATION 11 WEST  
ALGIERS CANAL PROJECT

I HAVE ENCLOSED PREL PENCILED COPIES OF SLOPE STABILITY AND T WALL ANALYSES  
FOR A MODIFIED P STATION 11 WEST WITH A NEW T WALL 63' FROM FACE OF PUMP  
HOUSE.

ALSO I INCLUDED PILE CAPACITY INFO FOR PILES SUPPORTING NEW T WALL.

D. E. I.

FILE \_\_\_\_\_  
DISTRIBUTION \_\_\_\_\_  
MB \_\_\_\_\_  
JH \_\_\_\_\_  
AH ✓



Project PRELIMINARY

Subject \_\_\_\_\_


US Army Corps of Engineers  
East of Harvey Canal  
Hurricane Protection Project  
Jefferson Parish, La.

Allowable Pile Load Capacities  
T. Wall Foundation

Modified S + WB station 11 West

Pile Type	Pile Tip Elevation	Estimated Allowable Single Pile Load Capacity in Tons Factor of Safety = 2.0	
		Compression	Tension
14 in. Sq. Precast, Prestressed Concrete	-80	25	18
	-90	37	27
	-100	50	37
	-110	60	48
16 in. Sq. Precast, Prestressed Concrete	-80	29	21
	-90	43	31
	-100	57	42
	-110	68	55

Note: 1) Capacity contribution to E1-47 has been ignored.  
 2) Reach 4 soil parameters have been used for this analysis. However, soil parameters below E1-80 have been assumed. Soil borings must be performed to confirm soil conditions below this level for final design.



**PRELIMINARY**

Stability of Pump Station

Stratum No.	Soil type	Unit Weight PCF	Soil Parameters		Safety factor = 1.3		Failure Surface	Summation of Forces		Factor of safety	Vertical Pressure, P, in PSF to Achieve Factor of Safety of 1.3 *
			Unfactored		Safety factor = 1.3			Resisting	Driving		
			Friction Angle Degrees	Cohesion PSF	Friction Angle Degrees	Cohesion PSF					
1	Fill Clay	105.0	0	350	0	269	269	33613	26724	1.26	193
2	Clay, silty Clay, organic Clay, Humus	92.0	0	350	0	269	269	44113	26724	1.65	—
3	Clay	101.0	0	350	0	269	269	54529	49310	1.11	327
4	Clay	101.0	0	400	0	308	308	63279	49310	1.28	28
5	Clay	101.0	0	480	0	369	437	72208	60590	1.19	155
6	Clay	101.0	0	630	0	485	538	79808	60590	1.32	—

\* Using unfactor soil parameters  
 Notes: 1) Sheetpile beneath T wall must penetrate to EI-47.0 to satisfy moment equilibrium  
 2) Maximum moment occurs at EI - 27 and is 17.2 ft. Kips/ft of wall.  
 3) Calculated anchor force, F<sub>A</sub>, at EI - 10.5 is 2.1 Kips/ft of wall.

T Wall Analysis

Failure Surface	ER Resisting lbs/ft	ED Driving lbs/ft	ER-ED lbs/ft	Change in Net Force lbs/ft	Equivalent Pressure PSF
X 7	18561	10650	7911	—	—
Y 8	52993	48932	4061	-3850	-130
Z 9	68823	62307	6516	2455	246

4) The anchor load and T wall pressure must be carried by driven batter piles. Axial capacity of batter piles carrying these lateral loads must be ignored above EI - 47.0.  
 5) Separate analysis by Hans Method indicates a factor of safety of 4.6 which is considered acceptable.  
 6) "P" is required vertical pressure across top of passive wedges to achieve a calculated factor of safety of 1.3 or more against a stability failure.

Slope Stability and T Wall Analyses  
 Modified S+WB Pump Station II West  
 US Army Corps of Engineers  
 East of Harvey Canal  
 Hurricane Protection Project  
 Jefferson Parish, La.

Fig

EE 14638/175


THE PETER ENGINEERING CORPORATION  
 MADE IN U.S.A.

**PUMPING STATION MECHANICAL  
CALCULATIONS**





BR. H.P.	EFF. %	N.P.S.H. HEAD FT.	IMPELLER DIAMETER 5 1/2 IN.	RATING: GPM	FT. HD.	RPM 2720
			PATTERN NO. D-0039	PUMP TYPE MF	SIZE 5 1/2 x 7 1/2	CERTIFIED TEST BY <i>J. J. Kelly</i>
Design Conditions 250 GFS (112,000 GPM) 27.22 Ft. 1 270 GFS (122,000 GPM) 25.55 Ft. 2 350 GFS (157,000 GPM) 15.43 Ft. 3 370 GFS (166,000 GPM) 13.84 Ft. 4						
WITNESSED BY <i>J. J. Kelly</i>						



BELLE CHASSE NO. 2 PUMPING STATION  
PUMP CURVE

Page 14

22-115 - CROSS SECTION - 10 SQUARES TO INCH

4-29-1998 2:01PM

FROM PRESQUITT FULLETT 5045221185

1-2

# Calculations

# Planters Pumping Station

## Head and Horsepower requirements

1) 72 inch (310 cfs) pumps - station addition

a) Pipe friction - 64 ft. Tube extension

$$\Delta H_f = \frac{64 \text{ ft}}{100} (.2083) \left(\frac{100}{140}\right)^{1.86} \left(\frac{[310(448.8)]^{1.86}}{84^{4.866}}\right) = \underline{0.114 \text{ ft}}$$

b) horse power

$$Hp = \frac{(310)(448.8)(0.114 \text{ ft})}{3960 (.78)(1)} = \underline{5.13 \text{ h.p.}}$$

2) 72 inch (290 cfs) pumps - original station

a) Pipe friction - 64 ft Tube extension

$$\Delta H_f = \frac{64}{100} (.2083) \left(\frac{100}{140}\right)^{1.86} \left(\frac{[290(448.8)]^{1.86}}{78^{4.866}}\right) = \underline{0.144 \text{ ft}}$$

b) horse power

$$Hp = \frac{(290)(448.8)(0.144 \text{ ft})}{3960 (.81)(1)} = \underline{5.84 \text{ h.p.}}$$

3) 36 inch (50 cfs) vertical pump

a) Pipe friction - 64 ft tube extension

$$\Delta H_f = \frac{64}{100} (.2083) \left(\frac{100}{140}\right)^{1.86} \left(\frac{[50(448.8)]^{1.86}}{36^{4.866}}\right) = \underline{0.236 \text{ ft}}$$

b) horsepower


$$Hp = \frac{(50)(448.8)(0.236 \text{ ft})}{3960 (.75)(1)} = \underline{1.78 \text{ h.p.}}$$



New Orleans Sewerage & Water Board STA. # 11  
Calculations on 100" wood Propeller Pumps

Scope - Replace steel conical Discharge tube w/  
Flaring Concrete discharge - Determine head  
loss change and affect on pump operation

Method - Calculate total head loss attributed to the  
pump by the existing mitered elbow and  
cone. Calculate the total head losses that  
would be attributed to the pump when  
using the flared concrete discharge. By  
taking the difference in these arrangements  
we can add these losses to the operating  
point on the curve and determine flow  
changes as well as new horsepower demand



1) Up leg of Siphon

$$h_f = L \left( \frac{V}{C R^{2/3}} \right)^2$$

$$C = 1.486/n \quad n = 0.012$$

105"  $\phi$  Discharge to 3.5' x 20'

$$R = W \cdot D / (W + 2D)$$

$$C = \frac{1.486}{0.012} = 123.83$$

	105" $\phi$	3.5' x 20'	Average
Area	60.13 ft <sup>2</sup>	70.00	65.07
R	2.188	2.59	2.389
$\sqrt{250 \text{ cfs}} \text{ } \frac{Q}{A}$	4.16	3.57	3.87
$\sqrt{230 \text{ cfs}}$	3.83	3.29	3.56
$\sqrt{210 \text{ cfs}}$	3.49	3.00	3.25

use L = length = 45'

$$h_f = \left( \frac{Q/65.07}{(123.83)(2.389)^{2/3}} \right)^2 \cdot 45 \Rightarrow h_f = \underline{\underline{2.17 \times 10^{-7} Q^2}}$$

2) Down leg of Siphon - 3.5' x 20' to 6' x 20'

	3.5' x 20'	6' x 20'	Avg.
Area	70.0	120	95.0
R	2.59	3.75	3.17
$\sqrt{250 \text{ cfs}}$	3.57	2.083	2.83
$\sqrt{230 \text{ cfs}}$	3.29	1.917	2.60
$\sqrt{210 \text{ cfs}}$	3.00	1.75	2.38

L = 26'

$$h_f = \left[ \frac{(Q/95.0)}{(123.83)(3.17)^{2/3}} \right]^2 \cdot 26$$

$$h_f = \underline{\underline{4.0 \times 10^{-8} Q^2}}$$

3) Siphon Crown Elbow

$$h_f = 0.25 \sqrt{\Delta/90} \left( \frac{V^2}{2g} \right)$$

$$\text{where } \Delta = 45^\circ \text{ \& } V = Q/A = (Q/70)$$

$$h_f = 0.25 \sqrt{45/90} \left( \frac{(Q/70)^2}{2 \cdot 32.2} \right)$$

$$h_f = \underline{5.60 \times 10^{-7} Q^2}$$

4. Exit loss  $6' \times 20' = 120 \text{ ft}^2$

$$h_f = \frac{V^2}{2g} = \frac{(Q/A)^2}{2g} = \frac{(Q/120)^2}{2 \cdot 32.2}$$

$$= \underline{1.078 \times 10^{-6} Q^2}$$

Total losses in new concrete discharge =

$$H_f = 2.17 \times 10^{-7} Q^2 + 4.0 \times 10^{-8} Q^2 + 5.6 \times 10^{-7} Q^2 + 1.078 \times 10^{-6} Q^2$$

$$H_{f \text{ TOTAL}} = \underline{8.28 \times 10^{-7} Q^2} \quad \text{or} \quad 0.652 \text{ ft @ } 250 \text{ cfs}$$

### 3) Exit Loss

$$K = 1.0 \quad \text{Area} = \pi/4 (L \times w) = \pi/4 \times 17 \times 12 = 160.22$$

$$A = 160.22 \text{ ft}^2$$

$$V = Q/A = Q/160.22$$

$$H_f = 1.0 \left[ \frac{Q^2/A^2}{2.32.2} \right] = 1.0 \left[ \frac{Q^2/160.22^2}{64.4} \right]$$

$$H_f = 6.05 \times 10^{-7} Q^2$$

$$\begin{aligned} H_{f \text{ TOTAL}} &= 5.54 \times 10^{-7} Q^2 + 1.16 \times 10^{-6} Q^2 + 6.05 \times 10^{-7} Q^2 \\ &= \underline{\underline{2.319 \times 10^{-6} Q^2}} \quad \text{or } 0.45 \text{ ft @ } 250 \text{ cfs} \end{aligned}$$

Difference in head losses between new system and existing discharge.

$$\begin{aligned} \Delta H_f &= H_f \text{ proposed} - H_f \text{ existing} \\ &= 8.28 \times 10^{-7} Q^2 - 2.319 \times 10^{-6} Q^2 \\ &= \underline{\underline{-1.491 \times 10^{-6} Q^2}} \end{aligned}$$

Therefore the discharge system proposed will actually reduce the friction losses in the total pump system. In terms of feet of friction losses which equates to feet of additional pool to pool head available, it is as follows

$$\Delta H_f_{250 \text{ cfs}} = 1.491 \times 10^{-6} (250^2) = 0.093 \text{ ft}$$

Calculations

P.S. # 13

Vertical Pumps

1) Estimated Priming Horsepower 72"  $\phi$  pumps

$$\text{STATIC EL.} - 10.00 \text{ to EL. } 1.88 \text{ (top of pipe)} = 22.88$$

$$\text{Velocity Head } \frac{v^2}{2g} = \frac{[200/28.27]^2}{2 \cdot 32.2} = 6.78$$

$$\text{Frictional Head } \frac{128/100 [0.2083] \left[ \frac{100}{140} \right]^{1.86} \left[ \frac{90,000^{1.86}}{72^{4.866}} \right]}{2} = 0.20$$

$$\text{Total } \underline{23.86}$$

$$\text{Priming Horse power} = \frac{(23.86)(90,000 \text{ gpm})}{(3960)(0.72)(1)} = 753 \text{ h.p.}$$

2) Additional head loss due to extended discharge (72")

$$H_f = \frac{40'}{100} [0.2083] \left[ \frac{100}{140} \right]^{1.86} \left[ \frac{(250 \cdot 448.8)^{1.86}}{(72)^{4.866}} \right] = 0.100 \text{ ft}$$


3) Horsepower due to extended pipe (72")

$$\text{H.P.} = \frac{(0.100)(112,200 \text{ gpm})}{(3960)(0.76)(1)} = 3.76 \text{ H.P.}$$

Calculations: Plaquemines Pump STA (NO.1)  
132" Worthington Pumps

Scope: Replace Existing Concrete discharge tubes with Flaring Steel Discharge - Determine Differential Head loss between each system

1) Losses in Existing Concrete Discharge



A) Upleg of siphon (132"Ø to 12.5' x 13.5')

$$h_f = L \left( \frac{V}{CR^{2/3}} \right)^2 \quad C = \frac{1.486}{n} \quad n = 0.012 \quad C = 123.83$$

$$R = \frac{w^D}{w+2D} \quad \text{or} \quad R = \frac{r}{2}$$

	132"Ø	12.5' x 13.5'	Avg.
Area	95.03 ft <sup>2</sup>	168.75	131.89
R		4.27	3.51
$\sqrt{400Cfs}$	9.47 fps	5.33	7.40

Length = 15'

$$h_f = \left( \frac{Q / 131.89}{(123.83) 7.40^{2/3}} \right)^2 \times 15' \quad h_f = \underline{4.0 \times 10^{-9} Q^2}$$

	12.5 x 13.5	16.5 x 16.5	Avg
Area	168.75	272.25	220.5
R	4.27	5.50	4.89
$V_{900\text{ cfs}}$	5.33	3.31	4.32

Length = 26'

$$H_f = \left[ \frac{(Q/220.5)}{(123.83)(4.32)^{2/3}} \right]^2 \times 26' = \underline{5.0 \times 10^{-9} Q^2}$$

c) Siphon Crown Elbow

$$h_f = 0.25 \sqrt{\Delta/90} \frac{V^2}{2g} \quad \text{where } \Delta = 115^\circ \quad V = Q/A = Q/162.5$$

$$h_f = 0.25 \sqrt{115/90} \frac{(Q/162.5)^2}{64.4} = \underline{1.66 \times 10^{-7} Q^2}$$

d) Exit Loss

$$16.5 \text{ ft} \times 16.5 \text{ ft} = 272.25 \text{ ft}^2$$

$$h_f = \frac{V^2}{2g} = \frac{(Q/A)^2}{2g} = \frac{(Q/272.25)^2}{64.4}$$

$$h_f = \underline{2.09 \times 10^{-7} Q^2}$$

Total Friction losses in Existing Concrete Tubes

$$H_f = 4.0 \times 10^{-9} Q^2 + 5.0 \times 10^{-9} Q^2 + 1.66 \times 10^{-7} Q^2 + 2.09 \times 10^{-7} Q^2$$

$$H_{f \text{ TOTAL}} = \underline{\underline{3.84 \times 10^{-7} Q^2}}$$


## Belle Chase #1

### 12 Foot Diameter Original Wood Horizontal Pumps

Scope - Replace Steel Conical Discharge Tube with Flared steel Cone including offsets to achieve the minimum 9.50 NGVD Flood Protection

Method - Calculate the head loss in the existing steel cone to be replaced. Calculate the losses in the replacement discharge arrangement. By taking the difference in head losses for the two arrangements we can determine what additional head is place on the pump. Since the existing engines are already overloaded at higher pool to pool heads, whatever additional head would only decrease this available pool to pool operating envelope.

### Existing Cone






1) 35° Mitered Joint use  $K = 0.129$

$$\begin{aligned}
 H_f &= K \frac{v^2}{2g} \quad v = Q/A \\
 &= (0.129) \left( \frac{Q^2/A^2}{2 \cdot 32.2} \right) \Rightarrow A = \frac{12.16^2 \pi}{4} = 116.26 \text{ ft}^2 \\
 &= (0.129) \left( \frac{Q^2}{116.26^2 / 64.4} \right) \\
 &= \underline{1.48 \times 10^{-7} Q^2}
 \end{aligned}$$

2) Loss thru Cone

$$\begin{aligned}
 H_f &= K \left[ 1 - \left( \frac{D_1}{D_2} \right)^2 \right]^2 \frac{v^2}{2g} & A &= 116.26 \\
 & & & \text{From HI III B-6} \\
 & & & K = 0.50 \\
 H_f &= 0.50 \left[ 1 - \left( \frac{12.17}{15.56} \right)^2 \right]^2 \frac{Q^2 / 116.26^2}{64.4} \\
 H_f &= \underline{8.4 \times 10^{-8} Q^2}
 \end{aligned}$$

3) Exit Loss




$$\text{Area} = \pi/4 (L \times w) = (\pi/4) (20.5 + 16.5) = 265.66 \text{ ft}^2$$

$$\begin{aligned}
 H_f &= K \frac{v^2}{2g} \quad \text{where } K = 1.0 \text{ and } v = Q/A \\
 &= (1.0) \left( \frac{Q^2/A^2}{2g} \right) = 1.0 \left( \frac{Q^2 / 265.66^2}{64.4} \right) \\
 &= \underline{2.20 \times 10^{-7} Q^2}
 \end{aligned}$$

$$\begin{aligned}
 H_{f \text{ TOTAL}} &= 1.48 \times 10^{-7} Q^2 + 8.4 \times 10^{-8} Q^2 + 2.20 \times 10^{-7} Q^2 \\
 &= \underline{4.52 \times 10^{-7} Q^2}
 \end{aligned}$$

# Replacement Discharge Cone



1) Mitered losses 146" I.D. Pipe

a) 2- 30° 3 piece miters  $K = 0.112$

b) 1- 35° 1 piece miter  $K = 0.129$

$$\text{Total Mitered losses} = K \frac{V^2}{2g} \quad K = (2)(0.112) + (1)(0.129)$$

$$V = Q/A \quad K = 0.353$$

$$A = \pi (12.17^2/4) =$$

$$H_f = 0.353 \frac{Q^2/A^2}{64.4} = 0.353 \frac{Q^2/114,26^2}{64.4} =$$

$$H_f = \underline{4.06 \times 10^{-7} Q^2}$$

2) Straight Pipe 12'-2"  $\varnothing$  x 20' = Long)

$$V = Q/A \quad E = 0.0002 \quad A = \pi \frac{(12.17)^2}{4} = 116.26 \quad \frac{E}{D} = 0.00016$$

$$NRE = \frac{VD}{\nu} \quad \text{where } V = 6.88 \text{ ft/sec } D = 12.17 \quad \nu = 0.0001217$$

$$NRE = \frac{(6.88)(12.17)}{0.0001217} = 6.88 \times 10^6$$

$$\text{From FIG III A-3 } f = 0.0096$$

$$H_f = f \left( \frac{L}{D} \right) \left( \frac{V^2}{2g} \right) \quad \text{where } V = Q/A$$

$$= (0.0096) \left( \frac{20}{12.17} \right) \frac{Q^2 / 116.26^2}{64.4}$$

$$= \underline{1.80 \times 10^{-8} Q^2}$$

3) Cone

$$h_f = K \left( 1 - \left( \frac{D_1}{D_2} \right)^2 \right)^2 \frac{V^2}{2g}$$

$$\Rightarrow K = 0.30 \quad A = 116.26$$


$$h_f = 0.30 \left( 1 - \left( \frac{12.17}{17.62} \right)^2 \right)^2 \frac{Q^2 / 116.26^2}{64.4}$$

$$= \underline{9.40 \times 10^{-8} Q^2}$$

4) Exit loss

$$\text{Area} = \frac{\pi}{4} (L \times w) = \frac{\pi}{4} (26.52 \times 17.13)$$

$$A = 356.73$$



$$H_f = K \left( \frac{V^2}{2g} \right) \quad \text{where } K = 1.0 \quad \text{and } V = Q/A$$

$$= 1.0 \left( \frac{Q^2 / 356.73^2}{2 \cdot 32.2} \right)$$

$$H_f = \underline{1.22 \times 10^{-7} Q^2}$$

Total Losses in 12ft Wood Pump Replacement Discharge

$$\begin{aligned} H_{f \text{ TOTAL}} &= 4.06 \times 10^{-7} Q^2 + 1.80 \times 10^{-8} Q^2 + 9.40 \times 10^{-8} Q^2 \\ &\quad + 1.22 \times 10^{-7} Q^2 \\ &= \underline{\underline{6.40 \times 10^{-7} Q^2}} \end{aligned}$$

Therefore the difference in head losses between the two systems are:

$$\begin{aligned} \Delta H_{f \text{ total}} &= H_{f \text{ proposed}} - H_{f \text{ existing}} \\ &= 6.40 \times 10^{-7} Q^2 - 4.52 \times 10^{-7} Q^2 \\ &= \underline{\underline{1.88 \times 10^{-7} Q^2}} \end{aligned}$$

Therefore at its nominal flow rate of 800 cfs


$$H_{f \text{ additional}} = 1.88 \times 10^{-7} (800)^2 = 0.120 \text{ ft.}$$

Additional Horsepower due to additional friction loss

$$\text{H.P.} = \frac{(800)(448.8)(0.12)}{(3960)(0.68)} = 16.0 \text{ h.p.}$$

Plaquemines Pump Station (No. 1)

2) Replacement Discharge Cone - 132"  $\phi$  Pumps



A) Expansion 132"  $\phi$  to 146"  $\phi$

$$A_{132"} = 95.03 \text{ ft}^2$$

$$A_{146"} = 116.26 \text{ ft}^2$$

$$H_f = \frac{(V_1 - V_2)^2}{2g} = \frac{\left(\frac{Q}{A_1} - \frac{Q}{A_2}\right)^2}{2g} = Q^2 \left(\frac{1}{A_1} - \frac{1}{A_2}\right)^2$$

$$H_f = \frac{Q^2 \left(\frac{1}{95.03} - \frac{1}{116.26}\right)^2}{2 \cdot 32.2} = \underline{5.7 \times 10^{-8} Q^2}$$

B) Mitered Losses 146"  $\phi$  Pipe

a) 2- 36° 3 piece Miters  $K = 0.112$

b) 1- 35° 1 piece Miter  $K = 0.129$

$$\text{Total Mitered losses} = K \frac{V^2}{2g} \Rightarrow K(2)(0.112) + (1)(0.129) = 0.353$$

$$H_f = 0.353 \frac{Q^2/A^2}{64.4} = 0.353 \frac{Q^2}{116.26^2 \cdot 64.4}$$

$$H_f = \underline{4.06 \times 10^{-7} Q^2}$$

c) straight Pipe 146"  $\phi$  x 20' long

$$V = Q/A \quad \epsilon = 0.0002 \quad A = \frac{\pi (12.17)^2}{4} = 116.26 \quad \epsilon/\pi = 0.00016$$

$$NRE = \frac{VD}{\nu} \quad \text{where } V = 6.88 \text{ fps} \quad D = 12.17 \quad \nu = 0.00001217$$

$$NRE = (6.88)(12.17)/(0.00001217) = 6.88 \times 10^6$$

From H.I. Fig III A-3  $f = 0.0096$

$$\begin{aligned} H_f &= f \left(\frac{L}{D}\right) \left(\frac{V^2}{2g}\right) \quad \text{where } V = Q/A \\ &= (0.0096) \left(\frac{20}{12.17}\right) \left(\frac{Q^2}{116.26^2}\right) / 64.4 \\ &= \underline{1.80 \times 10^{-8} Q^2} \end{aligned}$$

d) Cone

$$h_f = K \left(1 - \left(\frac{D_1}{D_2}\right)^2\right)^2 \frac{V^2}{2g}$$

$$K = 0.30 \quad A = 116.26$$


$$h_f = 0.30 \left(1 - \left(\frac{12.17}{17.62}\right)^2\right)^2 \left(\frac{Q^2/116.26^2}{64.4}\right)$$

$$h_f = \underline{9.40 \times 10^{-8} Q^2}$$

e) Exit Loss - Cone

$$\text{Area} = \frac{\pi}{4} (L \times w) = \frac{\pi}{4} (26.52 \times 17.13)$$

$$= 356.73 \text{ ft}^2$$



$$\begin{aligned} H_f &= K \left(\frac{V^2}{2g}\right) \quad K = 1.0 \quad V = Q/A \\ &= 1.0 \left(\frac{Q^2/A^2}{64.4}\right) = \frac{Q^2/356.73^2}{64.4} \\ &= \underline{1.22 \times 10^{-7} Q^2} \end{aligned}$$

$$\begin{aligned} \text{Total Losses} &= 5.7 \times 10^{-8} Q^2 + 4.06 \times 10^{-7} Q^2 + 1.80 \times 10^{-8} Q^2 \\ &\quad + 9.4 \times 10^{-8} Q^2 + 1.22 \times 10^{-7} Q^2 \\ &= \underline{6.97 \times 10^{-7} Q^2} \end{aligned}$$

Therefore the difference in head losses between the proposed discharge tube and that of the existing is as follows

$$\begin{aligned}\Delta H_f &= H_{f \text{ proposed}} - H_{f \text{ Existing}} \\ &= 6.97 \times 10^{-7} Q^2 - 3.84 \times 10^{-7} Q^2 \\ &= 3.13 \times 10^{-7} Q^2\end{aligned}$$

At the nominal flow rate of 900 cfs, the additional head seen by the pump is:

$$H_{f 900} = 3.13 \times 10^{-7} (900)^2 = 0.253 \text{ ft.}$$

Additional Horsepower Required

$$\text{H.P.} = \frac{(900 \text{ cfs})(448.8)(0.253 \text{ ft})}{(3960)(0.68)} = 37.95 \text{ H.P.}$$

SECTION IV

PUMPING EQUIPMENT MODIFICATIONS AND OPERATION

The purpose of this Phase I Report is to provide methods of rehabilitating the existing pumping equipment and to propose additional pump priming capacity to accelerate the start up procedure. These proposals will enhance the overall drainage resulting in quicker response during pump priming, enhance the flow rate of the oldest pumping equipment such that full rated capacity can be obtained at all operating water levels, and return the old equipment to new condition thereby extending their productive life by perhaps another 10 to 15 years. Consideration is also being given to adding pump capacity to the plant in an effort to compensate for increased runoff. Twenty years have passed since the newest pumps were installed, normal development, land subsidence, lowering of water tables, all contribute to usual gradual increase in station capacity demands. It should be noted that we have considered replacement of the two 1953 diesel engines with new engines of the same horsepower but the initial cost would be excessive (approximately \$900,000) and we believe that the existing engines can be rebuilt to give at least 10 to 15 years additional service.

We have obtained copies of the original "Horsepower Performance Test" for the Baldwin-Hamilton engines and these tests define the original engine horsepower for both engines. During these "tests" the engine demand for these original pumping conditions were established and



the throttle control blocked at a point ten percent (10%) above the required horsepower. This information was given by Mr. Rentschler of Baldwin-Hamilton. See letter dated August 3, 1983 (Appendix). The purpose of this setting was to guarantee against engine overload if for some reason the pump propeller was jammed by debris.

These engines, in the proposed rehabilitation process, will have their speed-horsepower control recalibrated to meet the present operating conditions.

During a heavy rainstorm this spring the oldest equipment was placed into operation and after several hours of pumping at full capacity the engine speed deteriorated. Flow capacity was reduced by approximately thirty-five (35%) percent by this speed reduction. It is the general opinion of Mr. Rentschler, and this office, that this speed change was caused by the need for engine overhaul and the locked in throttle setting. After engine work is completed and the required adjustments made we can expect design pump speed during operation at normal hydraulic head conditions.

We have directed most of our study toward the oldest pumps and engines since their need for performance improvement is the most apparent. We plan also to recommend that all existing engines and pumps be inspected for damage or wear which may reduce their capacity. This will require that pump inspection ports be opened and pump propellers,

diffusers, along with other internals subject to wear or damage be thoroughly checked. These individual pieces should be compared to the manufacturer's drawings or operational manuals to insure conformity.

The newest four diesel engines will also be inspected along with tabulating their approximate hours of operation. This information will then be studied to establish a predictable preventative maintenance program or rehabilitate the equipment if this need is indicated.

Since this pumping station is the total and only means of providing drainage for the Belle Chasse area it is the recommendation of this report that all equipment be returned to top efficiency condition. Only with the plant in first class operating condition can adequate and reliable drainage be provided for the drainage district.

Operational requirements have resulted in increases in the power demand for pumping with the original 144 inch drainage pumps. These changes, which have taken place in steps since the early years of this station's operation have steadily increased the differential pressure against which the engines must perform. This fact is the primary reason for the need to rehabilitate the equipment and increase the power capabilities of the existing diesel engines.

The original pumping station drawings indicate suction basin design high water elevation as EL - 4.0 Ft. and low water elevation as EL - 6.0

Ft. the outfall basin water elevation is indicated as EL +4.0 Ft.

The National Geodetic departments charged with maintaining vertical datum control have adjusted the reference bench marks in this entire area in recent years. We have not yet run a level loop to the Plaquemines Pumping Station but we estimate this elevation correction as 1.3 Ft. downward. As listed in an earlier section the original design water levels when corrected are:

Suction Basin High Water Level.....	EL -5.3 Ft.
Suction Basin Low Water Level.....	EL -7.3 Ft.
Discharge Basin High Water Level.....	EL +2.7 Ft.
Pool to Pool Pumping Head.....	8.0 Ft.
Present Suction Basin Low Water .....	EL -8.0 Ft.
Present Suction Basin High Water.....	EL -6.0 Ft.*
Discharge Basin "Hurricane Tide" Water.....	EL +6.0 Ft.*
Pool to Pool at Extreme Conditions.....	12.0 Ft.

\*Hurricane Conditions

The water levels listed in Mr. Olano's April 18, 1983 (See Appendix) letter are assumed to be recorded in accordance with the new corrected elevations. We feel that his datum for water levels is relatively up to date because the drainage system has several automatic recording water level gages and these must have been corrected recently. We will work with corrected current water levels as:

Suction Basin High Water (Pumps Put Into Operation).....EL - 8.0 Ft.  
Suction Basin Low Water (Pumps Shutdown).....EL - 9.0 Ft.

Initially these pumps were operating with a total pool to pool differential of 8.0 Ft. (-5.3 Ft. to +2.7 Ft.) and a maximum of 10.0 Ft. (-7.3 Ft. to +2.7 Ft.) Presently they should be operating under normal drainage situations with a total pool to pool differential of 10.7 Ft. (-8.0 Ft. to +2.7 Ft.) and a maximum differential under normal drainage of 11.7 Ft. (-9.0 Ft. to +2.7 Ft.). This differential head increase is expanded by the possibility of "Hurricane Tide" discharge basin level. In the event of a Hurricane Tide the outfall elevation is predicted to reach EL. +6.0 Ft. Under these conditions the suction basin water level would be higher than the normal -8.0 Ft. elevation possibly -6.0. Even with minimal "overbank storage" the pool to pool pumping head would equal or exceed 10.0 Ft.

Under the normal drainage conditions the additional pool to pool differential of 1.7 Ft. (say two feet) represents twenty-five percent of the original pool to pool. The expected differential under hurricane conditions could increase the power demand further. From a horsepower demand viewpoint this is an increase equal to the existing available reserve power.

Presently these pumps "should be" operating at these higher heads; because of other considerations the station operators have devised the

methods mentioned in the previous sections to circumvent this higher demand on the equipment. On those occasions when flooding rains required the use of all equipment the pump's diesel engine drives were unable to maintain full pump speed. When these engines are rehabilitated and produce the necessary horsepower under these circumstances the pumps will be capable of producing design pumping capacity at all regular operating conditions.

The following tabulation of pump capacity; pool to pool water levels, and required horsepower was taken from pump curves for 12 Ft. Wood Screw Pump -61.56" pitch at 97 R.P.M. (Engine Speed 625 R.P.M.):

<u>Pool To Pool</u>	<u>C.F.S.</u>	<u>G.P.M.</u>	<u>H.P.</u>
8.0 Ft.	820	368,000	1100
10.0 Ft.	780	350,100	1280
10.7 Ft.	760	341,100	1340
11.7 Ft.	750	336,600	1420

The "Engine Manual" and "Rating Curves for Baldwin Series 600 Engines" lists various rated horsepower for these engines. This information was used to predict the future usefulness of these pump drives. Horsepower ratings are generally a function of the engine design features, permissible B.M.E.P. levels, combined with the manufacturer's desire for a long life product. The Baldwin engine curves at 140 B.M.E.P. lists 1315 as its maximum horsepower rating. The engine manual

lists 1200 H.P. under the heading "H.P. for traction". Since these engines were originally used in diesel locomotive applications this traction H.P. is 10% derating of the 140 B.M.E.P. rating. The derating is a conservative approach because of the long operational hours at high horsepower demand that locomotive service requires.

We propose to have the engine throttle and governor reset to provide for 10% increase in horsepower above the 1315 listed. Increasing these settings will provide adequate power at all pumping situations including the highest hydraulic head condition and still will be, we feel, within the engines capabilities.

This increase of 10% would mean that the engine rated B.M.E.P. is increase from 140 which is listed to 154 B.M.E.P. Since drainage pumping equipment seldom is called upon to operate at maximum horsepower for extended time periods we are not concerned that using the higher rated B.H.P. (Brake Horsepower) will accelerate engine wear. After the engines have been totally rehabilitated we feel that this ten percent overload caused from pumping at 11.7 Ft. pool to pool could be handled without equipment damage.

B.M.E.P. which stands for Brake Mean Effective Pressure is a measure of performance of a diesel engine. It is a difficult term to appreciate since it has only a theoretical existence. It is stated as being the average (or mean) effective pressure inside the cylinder

during the power stroke which would produce power equal to the engine horsepower. This average pressure times the piston area will develop the force necessary to produce power. The higher the B.M.E.P. the higher the demands on the engine components and the lower the B.M.E.P. the lower the demands on the engines. Naturally the engine power pressures are higher at the top of the stroke and lower at the end giving an average pressure to produce the required power.

The engine application at this station does not require that this equipment run at the Higher B.M.E.P. situation on a regular basis. Only when the suction level reaches elevation -9.0 and the discharge basin level at elevation +2.7 or under hurricane tide and high water suction levels will the power demand be a maximum. In short it is our opinion that these engines can safely be expected to perform satisfactorily at all of the water level situations mentioned in this report.

The engine rehabilitation contemplated for this application is extensive but can be accomplished at the site. In order for these two engines to be rebuilt to "as new" capabilities all of the areas where age or normal wear could be expected to reduce the horsepower must be replaced. Since they are presently in running condition without evidence of misalignment or broken components we feel that the exchange of existing major components for factory rebuilt components is the most economical method to propose. The general listing illustrate the extent of these replacement parts.

- a. Replace cylinder heads with factory exchange rebuilt units.
- b. Replace with new all cylinder liners.
- c. Inspect crankshaft for wear; if necessary regrind all journal areas.
- d. Install all new main bearings.
- e. Install new bearings on all engine drive train components.  
(Camshaft, camshaft drive, water pump drive, etc.)
- f. Replace turbocharger assembly with factory reconditioned unit.
- g. Replace all six fuel injectors with factory reconditioned units.
- h. Replace engine governor with factory reconditioned unit.
- i. Replace water pump with factory reconditioned unit.
- j. Replace lubricating oil pump with new unit.
- k. Replace fuel oil transfer pump, recondition strainer and fuel filters. Inspect entire fuel transfer system for leaks or obstructions.
- l. Inspect and recondition engine starting system.

After the engines are disassembled some additional areas of repair may come to light. Since the direction of this program is to return these engines to "new" condition we are recommending complete rebuilding to factory tolerances instead of repairing the obvious damage only. When complete they are expected to develop their design B.H.P. and with the modifications mentioned to accept the ten percent extra occasional demand.



When the engines begin developing their rated horsepower on a regular basis the rejected heat from the jacket water system must be transferred thru the heat exchanges to waste. The existing atmospheric (open) heat exchangers presently in use have been trouble free to this time but an increase in horsepower demand must be accompanied by some increase in heat transfer capacity. This can be accomplished by adding water flow thru the basin. The mechanics of these alterations should not be extremely costly and will be detailed when final planning is accomplished.

The attached bar graph illustrates the estimated time scheduling which will be necessary to accomplish the rehabilitation with a minimum of equipment "out of service" at one time. The "inspection" which can be done without disassembly is shown separately from the more involved "condition survey". Inspection of the original pumping station engines will be completed first. As the necessary rehabilitation is being done and the involved equipment "out of service" these speed reduction drives and horizontal pumps will be completely surveyed. All information from this survey will be studied and recommendations made for whatever corrective measures appear to be required.

All rehabilitation work on the original station equipment will be complete before the newer units are scheduled for any inspection or survey of condition.

The cost of this engine, cooling system and related rehabilitation are estimated (for budget purposes) to be approximately \$150,000.00 for each unit. It is our opinion from conversations with persons who are knowledgeable about these pumps and engines that this rehabilitation will return the equipment to its original capabilities.

The work outlined in this report for the original pumping station equipment and through inspection of the newer equipment units will serve to expand the pumping station ability from its present strained capacity to its original 3800 C.F.S.

Sections II and III of this report outline the hydraulic operation of this drainage district and give an insight into its history and design. These sections are perhaps a tribute to the Operations Department who manipulate the water levels to avoid flooding during heavy rains. The manipulation of water levels enhances the pumping capacity, it does not however replace capacity. It is our opinion that the existing pumps could be more quickly brought into operation if additional vacuum pump capacity were added to the present system.

The existing vacuum pump system consists of two Nash liquid seal pumps driven by diesel engines for servicing all four horizontal drainage pumps. The vacuum priming piping is interconnected by a manifold at the pumps which makes it possible to use both vacuum pumps for priming each drainage pump. This is the most efficient use of the existing

equipment but the drainage pumps can only be put into service by a series start-up; one after the other. The priming time for all four pumps under these conditions is very long and can be a burden to the system if rapid runoff is the initial situation.

It is our recommendation that two new vacuum pumps be added to serve primarily the 1963 addition pumps. The existing priming equipment would remain where it is to serve the renovated system. The new and existing piping would, of course, be interconnected to guarantee continuity in case of equipment failure. These two new vacuum priming pumps with their related piping and accessories would cost approximately \$60,000.00 for each installation. (Total Cost \$120,000.)

We feel that these two new Vacuum Priming pumps would prove to be a most valuable addition to the overall pumping station operation. It does not add to the existing drainage pump capacity but it provides the means whereby the existing pumps can be brought into service quickly when the need is imminent.

The attached "Time Schedule" bar graph for the recommended work illustrates the estimated time required for each phase of the project. The fact that several phases of this renovation are being accomplished at one time is apparent from this type graph. Each individual project has a time period for "Inspection", "Design", "Specifications", and "Bidding". These separated divisions of each project make it possible

to monitor the work as it progresses which with renovation is very important.

The Phase II section of the Report to be submitted subsequent to this Phase I Report will deal with what further improvements might be recommended at the Plaquemines Pumping Station. Some of these considerations would include long term pumping requirements with additional pumping capacity, repowering the existing pumps for the higher pool to pool heads, methods to improve trash screen cleaning procedures and other general recommendations for the "long term".

The Phase I recommendations should be thought of as "short term" (less than 20 years) improvements to maximize the pumping capability of the existing Plaquemines Pumping Station until the end of the 20th century.

SECTION V  
CONCLUSIONS

As a result of our study of the existing condition of the pumping equipment in the original (1953) portion of the Plaquemines Pumping Station we have reached the following conclusion:

- 1.) Main diesel engine in the 1953 portion of the station are no longer adequate for developing full capacity of the two 144" diameter horizontal pumps.
- 2.) Priming time for all four (4) horizontal pumps can be shortened by installing two (2) additional priming pumps which will improve the pumping capability of the station.
- 3.) There is a reliable source of new or reconditioned parts for the engines driving the 144" diameter horizontal pumps (1953).
- 4.) There are a sufficient number of machine shops in the general area who could make the necessary replacements at the site.
- 5.) Replacement of the major engine components of the 1953 engines is preferable to random repair of parts that are obviously worn out on these engines.
- 6.) Replacement of 1953 diesel engines with new engines of equivalent horsepower is not cost effective at this time.
- 7.) At some future date replacement of the 1953 engines with higher horsepower with matching reduction gears may be warranted due to higher

pool to pool requirements resulting from lowering of suction side water levels.

8.) Rebuilding the existing engines for the 1953 horizontal pumps should extend the life of these engines by 10 to 15 years at which time they probably should be totally replaced as outlined in conclusion No.7.

9.) Lowering suction bells on 1953 horizontal pumps would not be cost effective at this time. When the 1953 engines are replaced with new larger engines, lowering the bells would be required and cost effective.

10.) Additional pumping capacity of at least 500 c.f.s. would be desirable at this time however the Phase II Report will define more clearly the need for additional capacity at the Plaquemines Pumping Station.

11.) At present the 1963 pumping equipment appears to be functioning properly however a complete inspection of this equipment could reveal areas needing preventative maintenance.

12.) The water cooling system for the 1953 engines may be insufficient after the engines are rebuilt and operated at higher speeds.

SECTION VI  
RECOMMENDATIONS AND COST ESTIMATE

Based on the conclusions outlined in Section V the following recommendations can be made:

1.) Inspect all existing mechanical equipment in the entire station as outlined below:

INSPECTION OF EXISTING EQUIPMENT

- a. Inspect Original Station Diesel Engines for repair requirements.
  - b. Condition Survey of Vacuum Priming Equipment and System.
  - c. Condition Survey of Original Station Drainage Pumps.
  - d. Condition Survey of Original Station Speed Reduction Gear Drives.
  - e. Condition Survey of Original Station Pump Suction and Discharge Piping.
  - f. Condition Survey of Suction Basin Trash Screens.
  - g. Condition Survey of Emergency Generator and Electrical system.
  - h. Condition Survey of Newer Station Addition Diesel Engines.
  - i. Condition Survey of Newer Station Addition Drainage Pumps.
  - j. Condition Survey of Newer Station Addition Speed Reduction Gear Drives.
- 2.) Rebuild, at the site, the two (2) main diesel engines that drive the 1953 - 144" horizontal pumps.
- 3.) Rebuild or repair any other equipment components including trash screens that may need replacement or adjustment.

- 4.) Modify and expand station engine cooling system.
- 5.) Install two (2) vacuum pumps and piping system for 1963 portion of the station. Existing vacuum pumps would be interconnected with new vacuum pumps but would be basically dedicated to 1953 pumps.

CONSTRUCTION COST ESTIMATE

<u>Item</u>	<u>Cost</u>
1. Rebuild Original Station Diesel Engines	\$ 300,000.00
* New Engines (Not Recommended)	(\$ 900,000.00)
2. Modify Original Station Engine Cooling System	\$ 40,000.00
3. Purchase and Install Two New Vacuum Pumps and Associated Piping System	\$ 120,000.00
4. Inspection and Condition Survey by Equipment Representative or equivalent	\$ 20,000.00
5. Engineering Inspection, Design and Specification	\$ <u>60,000.00</u>
ESTIMATED TOTAL COST FOR REHABILITATION	\$ 540,000.00

The Time Schedule in Section IV shows graphically the time estimated for each separate division of the work from "Inspection" thru "Test". The final five months are devoted to a condition survey of the 1960 addition equipment. It is apparent from this schedule that eighteen months will be required for the project. This is a minimum time estimate and is dependent upon each phase moving in a positive direction quickly and as predicted. The time schedule therefore is an



optimistic approach to upgrading the pumping station. The schedule does not list all inspection work to be included, only those areas we feel must be renovated are shown.

The Pumping Station is the only means of providing drainage for the Belle Chasse area. The work proposed will return the pumping equipment to its original capacity of 3800 C.F.S. Unless additional pumping capacity is added to the system we will only have that which existed in 1963. Phase II of this report will address the problem of run-off increases, future development, and related necessary drainage system improvements.

NAME PLATE DATA FOR PUMPING STATION EQUIPMENT

Horizontal Propeller Pump No. 1  
Order No. RR-335 (Installed 1955) Unit No. 1  
Capacity 800 CFS      Static Head 8 Ft.      RPM - 97  
Built By:  
    Hardie-Tynes Manufacturing Company  
    Birmingham, Alabama

Westinghouse Horizontal Pedestal Gear for Pump No. 1  
Serial No. 112214  
Ratio 6.429:1.0      Size 50      Type LMR  
Style PH-13629-1      Service Factor 1.25  
Pinion Speed .625 RPM  
Catalog Rating H.P. 1500  
Service Rating H.P. 1200

Diesel Engine No. 1  
Model 606A      Rated BHP 1200      625 RPM  
Serial No. 7031      12-3/4" Bore X 15½" stroke  
Build 7th Month 1952  
Baldwin Lima Hamilton Corporation  
Philadelphia, Pennsylvania

Horizontal Propeller Pump No. 2  
Order No. RR-335 (Installed 1955) Unit No. 2  
Capacity 800 CFS      Static Head 8 Ft.      RPM - 97  
Built By:  
    Hardie-Tynes Manufacturing Company  
    Birmingham, Alabama

Westinghouse Horizontal Pedestal Gear for Pump No. 2  
Serial No. 112215  
Ratio 6.429:1.0      Size 50      Type LMR  
Style PH-13629-1      Service Factor 1.25  
Pinion Speed .625 RPM  
Catalog Rating H.P. 1500  
Service Rating H.P. 1200

Diesel Engine No. 2  
Model 606A      Rated BHP 1200      625 RPM  
Serial No. 7032      12-3/4" Bore X 15½" stroke  
Built 7th Month 1952  
Baldwin Lima Hamilton Corporation  
Philadelphia, Pennsylvania

Vertical Pump - Pump No. 3  
Fairbanks Morse Pump Company  
Contract No. - DA-16-047-ENG-1774  
Serial No. 794401 Built 7th Month 1953  
Size 54 6310 Pump  
150 CFS at 8 Ft. Hd. 248 RPM  
Pomona Works - Pomona, California


Right Angle Gear For Pump No. 3  
Universal Gear Corporation  
Model PRV-25 Ratio 2.9:1  
Serial No. 42113-1

Diesel Engine No. 3  
Fairbanks Morse Engine Company  
Model 31A6 $\frac{1}{2}$   
H.P. = 240 RPM - 720  
Serial No. 960807

No. of Cylinders


6

8



RATING CURVES FOR BALDWIN SERIES 600

Supercharged Diesel Engines  
Bore 12-5/4" Stroke 16-1/2"



12 FT. DODD SCREEN PUMP  
 61.56" R.P.H. 97 S.F.  
 ANTICIPATED PERFORMANCE

SEWERAGE & WATER BOARD

STATIC LIFT IN FEET 10-25-50

GEN. SUPT.

DRAWING NO. 10102-11-22

A-4

# Baldwin-Hamilton

an Company

BALDWIN-HAMILTON COMPANY  
One Country View Road  
Malvern, PA 19355  
Phone 215-647-9900  
Telex 83-1395

August 3, 1983

Prescott Follett & Associates Inc.  
Consulting Engineers  
822 Baronne Street  
New Orleans, LA 70113  
ATTN: Mr. James A.Tocho

RE: Plaquemines Pumping Station  
Diesel Engines  
Serial Numbers 7031 & 7032

Dear Sir:

With reference to your July 11 letter describing the operation of subject diesel engines, a review of the application would indicate that we should give more thought to the matter before making a definite decision regarding the future for these engines.

The engine manual that was published for these units shows the pumps to be rated at 800 C.F.S. with an 8 Ft. head. Your letter states this is now a 10 Ft. head and you anticipate a 3 Ft. change in water level differential which will increase the total dynamic head and the horsepower demand.

We made a review of the engine block-test record and note that the engines were tested for 1220 HP at 100% load and 1340 HP at 110% load. These values would place the engine load within normal demands at present but will not allow for future load demands which you anticipate will go to 1500 HP. We do not recommend operating these engines at 1500 HP.

You mentioned that during a flooding rain this past spring that the engines were not maintaining their governed speed of 625 RPM. This could be an indication of engine overloading and not necessarily an indication of the need for overhaul. We note that at 110% load, or 1340 HP, the rack millimeter is 30 mm on engine 7031 and 29mm on engine 7032. It is normal practice to operate the engine at 110% load when on the test block and then take note of the mm reading on the No. 1 pump rack, add one mm and install a stop collar on the pump rack in the rear of the pump. This prevents loading the engine beyond 1340 HP. If the load demand should exceed 1340 HP, the fuel delivery will be restricted and the engine speed will drop off with any further increase in the loading. We should mention also that the #1 pump may have been changed at some time and the stop collar applied at a lower setting. The pump control linkage must be free to allow the pump rack to open-up to 30 mm or whatever the maximum load demands.

Mr. James Atocho

August 3, 1983

Page Two

Baldwin-Hamilton

8270

When on the test block, the engines are connected to a generator. The load on the engine can then be set accurately to any desired value by adjusting the field for the desired output. When connected directly to the pump drive it is difficult to determine the actual horsepower demand. It would need to be calculated on the basis of the pump design data. We are sending herewith, copies of the test figures taken when the engines were checked out on the test block. By taking note of the fuel pump millimeter reading and the exhaust temperature of the engine, a comparison can be made against the test record and a close approximation of the horsepower can be determined.

We hope you will find the actual pump demand within the load capabilities of the engine so that we can count on keeping the units in service.

Regarding your request for a list of "parts for complete overhaul"; you will find herewith a complete engine parts list. In each area we indicated with an "X" those parts that most likely need to be replaced due to normal wear or deterioration.

In order to make a realistic recommendation on overhaul requirements, it would be necessary to have specific information on the conditions of major engine components. Inasmuch as this information is not usually available until the engine is disassembled, cleaned and inspected it would appear that serious consideration be given toward a major overhaul, especially if total accumulated running time has exceeded 20,000 hours. In order that you will have some idea of what is involved, we are enclosing eight sheets of form 01 which we would use for the initial inspection process (make extra copies for your file). We would then use this information to itemize the parts and material requirements. The approximate time required to tear-down an engine would be 300 man hours. The approximate time required to re-assemble an engine would be 700 man hours.

We no longer have shop facilities to perform the work, however we have re-built a number of Baldwin engines at a shop in South Carolina. Obviously even a major overhaul would cost much less than new engines.

This information, although not resolving any problems, will give you a good enough view of the overall picture and enable you to arrive at the correct solution. Please do not hesitate to contact Mr. Matt Gray as questions arise.

Very truly yours,

HAR:par  
Enclosures

Henry A. Rentschler  
President

CC: Matt Gray - Baldwin-Hamilton (Malvern)

# **FLOODGATE CALCULATIONS**



EAST OF HARVEY FOM

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.  
9551-01

Designed By:  
R. CHOPIN

Date:  
4/29/98

Checked By:

Page /  
of 18

DEAD LOADS:

(1'-10" FLOOD WALLS EITHER SIDE)

$$(8.5' \times 1.8333' \times 4.5')(150 \text{ pcf}) = 10,519^{\#} = \underline{10.52^{\text{K}}}$$

(2'-6" PILASTERS EITHER SIDE)

$$(2.5' \times 2.5' \times 9.25')(150 \text{ pcf}) = 8,672^{\#} = \underline{8.67^{\text{K}}}$$

(MONOLITH BASE)

$$(8' \times 40' \times 2.5')(150 \text{ pcf}) = 120,000^{\#} = \underline{120^{\text{K}}}$$

(FLOOD GATE)

$$\begin{aligned} & (2 \times 28.5' \times 62^{\#/\text{ft}}) + \left[ \left( \frac{0.3125''}{12''} \times 27.167' \times 8.5' \right) + \left( 6 \times 7.333' \times 0.3333' \times \frac{0.375''}{12''} \right) \right. \\ & + \left( 2 \times 7.9167' \times 1.9792' \times \frac{0.5''}{12''} \right) + \left( 6 \times 7.9167' \times 0.5' \times \frac{0.5''}{12''} \right) \\ & + \left( 4 \times 7.9167' \times 2' \times \frac{0.375''}{12''} \right) + \left( 28.5' \times 0.5' \times \frac{0.5''}{12''} \right) \\ & \left. + \left( 2 \times 29.5' \times \frac{0.4418 \text{ in}^2}{141.25 \text{ ft}^2} \right) \right] (490 \text{ pcf}) = 5,646^{\#} = \underline{5.65^{\text{K}}} \end{aligned}$$

HORIZONTAL REACTION ON HINGES

$$\left( 5.65^{\text{K}} \times \frac{28.5'}{2} \right) / 7.5833' = \underline{10.62^{\text{K}}} \quad \begin{array}{l} \text{TENSION ON TOP} \\ \text{COMPRESSION ON BOTTOM} \end{array}$$

VERTICAL REACTION ON HINGES

$$= \underline{2.825^{\text{K}}} \text{ ON TOP \& BOTTOM}$$

EAST OF HARVEY FOM

**BURK-KLEINPETER, INC.**

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOOD GATES PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 2

of 18

DEAD LOAD FORCES ABOUT THE ORIGIN:

$$\sum F_z = 2 \times 10.52^k + 2 \times 8.67^k + 120^k + 5.65^k = \underline{164.03^k}$$

$$\sum F_y = 0$$
$$\sum F_x = 0$$

(HINGES CANCEL OUT)

$$\sum M_x = 5.65' \times 14.25' - 2.825^k \times 10.7083' + 2.825^k \times 3.125' = \underline{59.09 \text{ F.K.}}$$

(GATE CLOSED)

$$\sum M_x = 5.65' \times 14.25' + 2.825^k \times 10.7083' - 2.825^k \times 3.125' = \underline{101.94 \text{ F.K.}}$$

(GATE OPEN)

$$\sum M_y = 2 \times 10.52^k \times -0.9167' + 2 \times 8.67^k \times -1.25' + 5.65^k \times -0.3333' = \underline{-42.85 \text{ F.K.}}$$

$$\sum M_z = 0$$


EAST OF HARVEY FDM

FLOODGATES PILE DESIGN

**BURK-KLEINPETER, INC.**

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

Job No.	Designed By:	Date:	Checked By:	Page 3
9551-01	R. CHOPIN	4/29/98		of 18



EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551.01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 4

of 18

LOAD CASE I:GATE REACTIONS

$$TOP = R \times 1.545' / 7.5833' = 0.2037 R$$

$$BOTTOM = R - 0.2037R = 0.7963 R$$

$$TOTAL TOP REACTION = (27.167') (0.2037) (1.32^k) = 7.31^k$$

$$TOTAL BOTTOM REACTION = (27.167') (0.7963) (1.32^k) = 28.56^k$$

LIVE LOADS ABOUT ORIGIN:

$$\sum F_x = (40') (0.21^k + 2.53^k + 0.41^k) = 93.2^k$$

$$\sum F_y = 0$$

$$\sum F_z = (40') (1.62^k - 2.25^k - 0.62^k) = -50^k$$

$$\sum M_x = 0$$

$$\begin{aligned} \sum M_y &= (-0.21^k \times 0.8333' - 2.53^k \times 3' + 1.62^k \times 2' - 2.25^k \times 2' + 0.62^k \times 2' + 0.41^k \times 0.8333') (40') \\ &= -297.73 \text{ FT.K} \end{aligned}$$

$$\sum M_z = 0$$

TOTAL LOADS ABOUT ORIGIN

$$\sum F_x = 0 + 93.2^k = \boxed{93.2^k}$$

$$\sum F_y = 0 + 0 = \boxed{0}$$

$$\sum F_z = 164.03^k - 50^k = \boxed{114.03^k}$$

$$\sum M_x = 59.09 \text{ FT.K} + 0 = \boxed{59.09 \text{ FT.K}}$$

$$\sum M_y = -42.85 \text{ FT.K} - 297.73 \text{ FT.K} = \boxed{-340.58 \text{ FT.K}}$$

$$\sum M_z = 0 + 0 = \boxed{0}$$


**BURK-KLEINPETER, INC.**

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

EAST OF HARVEY FDM

FLOODGATES PILE DESIGN

Job No.	Designed By:	Date:	Checked By:	Page 5
9551-01	R. CHOPIN	4/29/98		of 18



EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHAPIN

Date:

4/29/98

Checked By:

Page 6

of 18

LOAD CASE II:LIVE LOADS ABOUT ORIGIN:

$$\sum F_x = (40') (0.21^k + 2.53^k - 0.41^k) = \underline{93.2^k}$$

$$\sum F_y = \underline{0}$$

$$\sum F_z = (40') (1.62^k - 1.62^k - 1.25^k) = \underline{-50^k}$$

$$\sum M_x = \underline{0}$$

$$\begin{aligned} \sum M_y &= (40') (-0.21^k \times 0.8333' - 2.53^k \times 3' + 1.62^k \times 2' - 1.62^k \times 1.3333' + 1.25^k \times 0 + 0.41^k \times 0.8333') \\ &= \underline{-253.73 \text{ FT.K}} \end{aligned}$$

$$\sum M_z = \underline{0}$$

TOTAL LOADS ABOUT ORIGIN

$$\sum F_x = 0 + 93.2^k = \boxed{93.2^k}$$

$$\sum F_y = 0 + 0 = \boxed{0}$$

$$\sum F_z = 164.03^k - 50^k = \boxed{114.03^k}$$

$$\sum M_x = 59.09 \text{ FT.K} + 0 = \boxed{59.09 \text{ FT.K}}$$

$$\sum M_y = -42.85 \text{ FT.K} - 253.73 \text{ FT.K} = \boxed{-296.58 \text{ FT.K}}$$

$$\sum M_z = 0 + 0 = \boxed{0}$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.  
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.  
9551-01

Designed By:  
R. CHOPIN

Date:  
4/29/78


Checked By:

Page 7  
of 18

LOAD CASE III

FLOOD SIDE

PROTECTED SIDE



EAST OF HARVEY FDM

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 8

of 18

LOAD CASE III:LIVE LOADS ABOUT ORIGIN:

$$\sum F_x = (40') (0.21^k + 3.78^k - 0.41^k) = \underline{143.2^k}$$

$$\sum F_y = \underline{0}$$

$$\sum F_z = (40') (2.12^k - 2.75^k - 0.62^k) = \underline{-50^k}$$

$$\sum M_x = \underline{0}$$

$$\begin{aligned} \sum M_y &= (40') (-0.21^k \times 0.8333' - 3.78^k \times 3.67' + 2.12^k \times 2' - 2.75^k \times 2' + 0.62^k \times 2' + 0.41^k \times 0.8333') \\ &= \underline{-549.04 \text{ FT.K}} \end{aligned}$$

$$\sum M_z = \underline{0}$$

TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (0 + 143.2^k)(0.75) = \underline{107.4^k}$$

$$\sum F_y = 0 + 0 = \underline{0}$$

$$\sum F_z = (164.03^k - 50^k)(0.75) = \underline{85.52^k}$$

$$\sum M_x = (59.09 \text{ FT.K} + 0)(0.75) = \underline{44.32 \text{ FT.K}}$$

$$\sum M_y = (-42.85 \text{ FT.K} - 549.04 \text{ FT.K})(0.75) = \underline{-443.92 \text{ FT.K}}$$

$$\sum M_z = 0 + 0 = \underline{0}$$




EAST OF HARVEY FDM

FLOODGATES PILE DESIGN

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

Job No.	Designed By:	Date:	Checked By:	Page 9
9551-01	R. CHOPIN	4/29/98		of 18



EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 10

of 18

LOAD CASE IV :LIVE LOADS ABOUT ORIGIN :

$$\sum F_x = (40') (0.21^k + 3.78^k - 0.41^k) = \underline{143.2^k}$$

$$\sum F_y = \underline{0}$$

$$\sum F_z = (40') (2.12^k - 2.12^k - 1.25^k) = \underline{-50^k}$$

$$\sum M_x = \underline{0}$$

$$\begin{aligned} \sum M_y &= (40') (-0.21^k \times 0.8333' - 3.78^k \times 3.67' + 2.12^k \times 2' - 2.12^k \times 1.3333' + 1.25^k \times 0 + 0.41^k \times 0.8333') \\ &= \underline{-491.70 \text{ FT}\cdot\text{K}} \end{aligned}$$

$$\sum M_z = \underline{0}$$

TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (0 + 143.2^k)(0.75) = \underline{107.4^k}$$

$$\sum F_y = 0 + 0 = \underline{0}$$

$$\sum F_z = (164.03^k - 50^k)(0.75) = \underline{85.52^k}$$

$$\sum M_x = (59.09 \text{ FT}\cdot\text{K} + 0)(0.75) = \underline{44.32 \text{ FT}\cdot\text{K}}$$

$$\sum M_y = (-42.85 \text{ FT}\cdot\text{K} - 491.70 \text{ FT}\cdot\text{K})(0.75) = \underline{-400.91 \text{ FT}\cdot\text{K}}$$

$$\sum M_z = 0 + 0 = \underline{0}$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 11

of 18

LOAD CASE V: GATE OPEN, No WIND, TRUCK ON PROTECTED SIDE EDGE OF  
BASE SLAB.

LIVE LOADS ABOUT ORIGIN: (ONE TRUCK TOWARDS HINGE SIDE OF GATE OPENING)

$$\sum F_x = 0$$

$$\sum F_y = 0$$

$$\sum F_z = 32^k$$

$$\sum M_x = 16^k \times 11' + 16^k \times 5' = 256 \text{ FT.K}$$

$$\sum M_y = -32^k \times 4' = -128 \text{ FT.K}$$

$$\sum M_z = 0$$

TOTAL LOADS ABOUT ORIGIN:

$$\sum F_x = 0 + 0 = 0$$

$$\sum F_y = 0 + 0 = 0$$

$$\sum F_z = 164.03^k + 32^k = 196.03^k$$

$$\sum M_x = 101.94 \text{ FT.K} + 256 \text{ FT.K} = 357.94 \text{ FT.K}$$

$$\sum M_y = -42.85 \text{ FT.K} - 128 \text{ FT.K} = -170.85 \text{ FT.K}$$

$$\sum M_z = 0 + 0 = 0$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.  
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 12

of 18

LOAD CASE VI:

GATE OPEN, No WIND, 2-TRUCKS ON PROTECTED SIDE FACE OF BASE SLAB.

LIVE LOADS ABOUT ORIGIN:

$$\sum F_x = 0$$

$$\sum F_y = 0$$

$$\sum F_z = 32^k + 32^k = 64^k$$

$$\sum M_x = 16^k \times 11' + 16^k \times 5' + 16^k \times 1' - 16^k \times 5' = 192 \text{ FT.K}$$

$$\sum M_y = -64^k \times 4' = -256 \text{ FT.K}$$

$$\sum M_z = 0$$

TOTAL LOADS ABOUT ORIGIN:

$$\sum F_x = 0$$

$$\sum F_y = 0$$

$$\sum F_z = 164.03^k + 64^k = 228.03^k$$

$$\sum M_x = 101.94 \text{ FT.K} + 192 \text{ FT.K} = 293.94 \text{ FT.K}$$

$$\sum M_y = -42.85 \text{ FT.K} - 256 \text{ FT.K} = -298.85 \text{ FT.K}$$

$$\sum M_z = 0$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.  
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.  
9551-01

Designed By:  
R. CHOPIN

Date:  
4/29/98

Checked By:

Page 14  
of 18

LOAD CASE VIII:

GATE OPEN, NO WIND, 2 - TRUCKS ON FLOOD SIDE FACE  
OF BASE SLAB.

LIVE LOADS ABOUT ORIGIN:

$$\sum F_x = 0$$

$$\sum F_y = 0$$

$$\sum F_z = 64^k$$

$$\sum M_x = 192 \text{ FT.K}$$

$$\sum M_y = 64^k \times 4' = 256 \text{ FT.K}$$

$$\sum M_z = 0$$

TOTAL LOADS ABOUT ORIGIN:

$$\sum F_x = 0$$

$$\sum F_y = 0$$

$$\sum F_z = 228.03^k$$

$$\sum M_x = 293.94 \text{ FT.K}$$

$$\sum M_y = -42.85 \text{ FT.K} + 256 \text{ FT.K} = 213.15 \text{ FT.K}$$

$$\sum M_z = 0$$

EAST OF HARVEY FDM

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PIVE DESIGN

Job No. 9551-01

Designed By: R. CHOPIN

Date: 4/29/98


Checked By:

Page 15  
of 18

WIND LOADING FOR  
LOAD CASES IX + X

FLOOD SIDE

PROTECTED SIDE



40'-0" MONOLITH  
26'-0" GATE OPENING

WIND LOADING ABOUT ORIGIN

$$\sum F_x = (-50 \text{ psf})(8.5')(17') = -5.95^k$$

$$\sum F_y = 0$$

$$\sum F_z = 0$$

$$\sum M_x = 0$$

$$\sum M_y = 5.95^k \times 6.75' = 40.16 \text{ ft.k}$$

$$\sum M_z = 0$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOLIN

Date:

4/29/98

Checked By:

Page 16

of 18

LOAD CASE IX : GATE OPEN, WIND FROM REAR/SIDE, TRUCK ON FLOOD SIDE  
EDGE OF BASE SLAB.

TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (0 - 5.95^k)(0.75) = \boxed{-4.46^k}$$

$$\sum F_y = 0 + 0 = \boxed{0}$$

$$\sum F_z = (196.03^k + 0)(0.75) = \boxed{147.02^k}$$

$$\sum M_x = (357.94 \text{ FT.K} + 0)(0.75) = \boxed{268.46 \text{ FT.K}}$$

$$\sum M_y = (85.15 \text{ FT.K} + 40.16 \text{ FT.K})(0.75) = \boxed{93.98 \text{ FT.K}}$$

$$\sum M_z = 0 + 0 = \boxed{0}$$

LOAD CASE X : GATE OPEN, WIND FROM REAR/SIDE, 2-TRUCKS ON FLOOD SIDE  
EDGE OF BASE SLAB.

TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = \boxed{-4.46^k}$$

$$\sum F_y = \boxed{0}$$

$$\sum F_z = (228.03^k + 0)(0.75) = \boxed{171.02^k}$$

$$\sum M_x = (293.94 \text{ FT.K} + 0)(0.75) = \boxed{220.46 \text{ FT.K}}$$

$$\sum M_y = (213.15 \text{ FT.K} + 40.16 \text{ FT.K})(0.75) = \boxed{189.98 \text{ FT.K}}$$

$$\sum M_z = \boxed{0}$$

EAST OF HARVEY FDM

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No. 9551-01

Designed By: R. CHOPIN

Date: 1/29/98


Checked By:

Page 17  
of 18

WIND LOADING FOR  
LOAD CASES XI + XII

FLOOD SIDE

PROTECTED SIDE



4'-0" MONOLITH  
2'-6" GATE OPENING

WIND LOADING ABOUT ORIGIN.

$$\sum F_x = (50 \text{ psf}) (8.5' \times 7' + 8.5' \times 27.167/2) = 8.75^k$$

$$\sum F_y = 0$$

$$\sum F_z = 0$$

$$\sum M_x = 0$$

$$\sum M_y = -8.75^k \times 6.75' = -59.06 \text{ FT.K}$$

$$\sum M_z = (-50 \text{ psf}) (8.5' \times \frac{27.167}{2}) (14.25') + (50 \text{ psf}) (8.5' \times 7') (16.5') = -33.18 \text{ FT.K}$$



EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

4/29/98

Checked By:

Page 18

of 18

LOAD CASE XI:GATE OPEN, WIND FROM FLOOD SIDE, TRUCK ON PROTECTED SIDE  
EDGE OF BASE SLAB.TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (0 + 8.75^k)(0.75) = 6.56^k$$

$$\sum F_y = 0$$

$$\sum F_z = (196.03^k + 0)(0.75) = 147.02^k$$

$$\sum M_x = (357.94 \text{ ft.k} + 0)(0.75) = 268.46 \text{ ft.k}$$

$$\sum M_y = (-170.85 \text{ ft.k} - 59.06 \text{ ft.k})(0.75) = -172.43 \text{ ft.k}$$

$$\sum M_z = (0 - 33.18 \text{ ft.k})(0.75) = -24.89 \text{ ft.k}$$

LOAD CASE XII:GATE OPEN, WIND FROM FLOOD SIDE, 2-TRUCKS ON PROTECTED SIDE  
EDGE OF BASE SLAB.TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = 6.56^k$$

$$\sum F_y = 0$$

$$\sum F_z = (228.03^k + 0)(0.75) = 171.02^k$$

$$\sum M_x = (293.94 \text{ ft.k} + 0)(0.75) = 220.46 \text{ ft.k}$$

$$\sum M_y = (-298.85 \text{ ft.k} - 59.06 \text{ ft.k})(0.75) = -268.43 \text{ ft.k}$$

$$\sum M_z = (0 - 33.18 \text{ ft.k})(0.75) = -24.89 \text{ ft.k}$$

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

PILE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

5/1/98

Checked By:

Page 1Ba  
of 1BaLOAD CASE XIII: GATE CLOSED, WIND FROM PROTECTED SIDE

WIND LOADING ABOUT ORIGIN:

$$\sum F_x = (-50 \text{ psf})(8.5') (40') = -17^k$$

$$\sum F_y = 0$$

$$\sum F_z = 0$$

$$\sum M_x = 0$$

$$\sum M_y = 17^k \times 6.75' = 114.75 \text{ ft.k}$$

$$\sum M_z = 0$$

TOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (-17^k + 0)(0.75) = -12.75^k$$

$$\sum F_y = 0 + 0 = 0$$

$$\sum F_z = 0 + 0 = 0$$

$$\sum M_x = (0 + 59.09 \text{ ft.k})(0.75) = 44.32 \text{ ft.k}$$

$$\sum M_y = (114.75 \text{ ft.k} - 42.85 \text{ ft.k})(0.75) = 53.93 \text{ ft.k}$$

$$\sum M_z = 0 + 0 = 0$$

LOAD CASE XIV: GATE CLOSED, WIND FROM FLOOD SIDETOTAL LOADS ABOUT ORIGIN (75% FORCES USED)

$$\sum F_x = (17^k + 0)(0.75) = 12.75^k$$

$$\sum F_y = 0 + 0 = 0$$

$$\sum F_z = 0 + 0 = 0$$

$$\sum M_x = (0 + 59.09 \text{ ft.k})(0.75) = 44.32 \text{ ft.k}$$


$$\sum M_y = (-114.75 \text{ ft.k} - 42.85 \text{ ft.k})(0.75) = -118.2 \text{ ft.k}$$

$$\sum M_z = 0 + 0 = 0$$

WALLS #6 @ 12" E.F. VERT.  
 11- #5 E.F. HORIZ. REIN.

PILASTERS 3- #8 E.F.  
 #4 TIES @ 12" O.C.

BASE TRANS. #7 @ 12" O.C. TOP & BOT.  
 LONG. #7



FLOOD GATES	REINFORCE DETAILS	EAST OF HARVEY FDM			
		BURK-KLEINPETER, INC. ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS NEW ORLEANS, LA. BATON ROUGE, LA. TUSCALOOSA, AL			
Job No.	9551-01	Designed By:	R. CHAPMAN	Date:	5/4/58
Checked By:		Page	1	of	2

EAST OF HARVEY FDM

BURK-KLEINPETER, INC.  
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES REINFORCING DETAILS

Job No. 9551-01

Designed By: R. CHOPIN


Date: 5/4/98

Checked By:

Page 2 of 2

FLOOD SIDE

PROTECTED SIDE



NOTE TO DRAFTERMAN SPACE 9-#7 BARS TO MISS PILES IN BOTTOM

NOTE: BURN HOLES IN SHEET PILING TO PASS REINFORCEMENT

SECTION A-A

FLOOD GATES CONCRETE DESIGN

Job No.

9551-01

Designed By:

R. CHAPIN

Date:

5/4/98

Checked By:

Page /


of 7

WALL DESIGN:

$$f'_c = 4,000 \text{ psi}$$

$$E_y = 60,000 \text{ psi}$$

BY INSPECTION LOAD CASE III WILL GOVERN.



$$M = (2,254 \text{ #/ft})(2.8333') = 6,386 \text{ ft. #/ft}$$

$$V = 2,254 \text{ #/ft}$$

$$M_u = (1.7)(1.3)(6,386 \text{ ft. #/ft}) = 14,113 \text{ ft. #/ft}$$

$$V_u = (1.7)(1.3)(2,254 \text{ #/ft}) = 4,981 \text{ #/ft.}$$

FLEXURE DESIGN:

$$S_{min} = \frac{200}{60,000} = 0.0033$$

$$S_b = \left( \frac{0.85 \beta_1 f'_c}{f_y} \right) \left( \frac{87,000}{87,000 + E_y} \right) \quad \beta_1 = 0.85 \text{ FOR } f'_c = 4,000 \text{ psi}$$

$$S_b = \left( \frac{(0.85)(0.85)(4,000)}{60,000} \right) \left( \frac{87,000}{87,000 + 60,000} \right) = 0.0285$$

$$S_{MAX \text{ RECOMMENDED}} = 0.25 \times 0.0285 = 0.0071$$

$$S_{MAX \text{ PERMITTED}} = 0.375 \times 0.0285 = 0.0107$$

$$d = 22" - 3" - \left( \frac{7}{8} \right) \left( \frac{1}{2} \right) = 18.56" \text{ COVER } \#7 \text{ BARS}$$

$$R_n = \frac{M_u}{\phi b d^2} = \frac{(14,113 \text{ ft. #})(12 \text{ in.})}{(0.9)(12 \text{ in.})(18.56 \text{ in.})^2} = 45.52$$

$$S = \frac{0.85 f'_c}{f_y} \left( 1 - \sqrt{1 - \frac{2R_n}{0.85 f'_c}} \right) = 0.0008 < S_{min} = 0.0033$$

$$\text{USE } \frac{1}{3} \text{ INCREASE } S = 1.33 \times 0.0008 = 0.0011$$

EAST OF HARVEY FOM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

CONCRETE DESIGN

Job No.

7551-01

Designed By:

R. CHOPIN

Date:

5/4/98

Checked By:

Page 2

of 7

$$A_{S_{LEAD}} = (0.0011)(12'')(18.56'') = 0.245 \text{ in}^2/\text{FT}$$

$$\text{MIN. } A_{TEMP} \text{ E.F.} = \frac{0.0028 \times 22'' \times 12''}{2} = 0.37 \text{ in}^2/\text{FT}$$

USE #6 BARS @ 12" O.C. (E.F.) IN WALLS

CHECK SHEAR ACROSS BASE OF THE WALL:

$$V_U = 4,981 \text{ #/FT}$$

$$\phi V_c = \phi 2 \sqrt{f'_c} b d = (0.85)(2) \sqrt{4,000} (12'')(18.56'') = 23,946 \text{ #}$$

$$23,946 \text{ #} > 4,981 \text{ #} \quad \text{O.K.}$$

TEMPERATURE & SHRINKAGE REINFORCEMENT:

$$A_{TEMP} = 0.0028 \times 22'' \times 8.5' \times 12'' = 6.283 \text{ in}^2$$

$$A_{TEMP \text{ EACH FACE}} = \frac{6.283 \text{ in}^2}{2} = 3.142 \text{ in}^2/\text{FACE}$$

USE 11 - #5 BARS E.F.

PILASTER DESIGN:

(2'-6" X 2'-6" PILASTERS)

GATE REACTIONS:


$$\text{TOP} = R \times 2.2083' / 7.5833' = 0.2912 R$$

$$\text{BOTTOM} = R - 0.2912 R = 0.7088 R$$

TOTAL GATE REACTIONS ON PILASTERS

$$\text{TOP} = (0.2912)(2,254 \text{ #/FT})(27.167'/2) = 8,915.7 \text{ #}$$

$$\text{BOTTOM} = (0.7088)(2,254 \text{ #/FT})(27.167'/2) = 21,701.5 \text{ #}$$



EAST OF HARVEY FDM

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

CONCRETE DESIGN

Job No.

9551-01

Designed By:

R. CHAPIN

Date:

5/4/98

Checked By:

Page 3

of 7

$$M = 8,915.7^{\#} \times 8.2083' + 21,701.5^{\#} \times 0.625' = 86,747 \text{ ft.}\cdot\#$$

$$V = 8,915.7^{\#} + 21,701.5^{\#} = 30,617^{\#}$$

$$M_u = (1.7)(1.3)(86,747 \text{ ft.}\cdot\#) = 191,711 \text{ ft.}\cdot\#$$

$$V_u = (1.7)(1.3)(30,617^{\#}) = 67,664^{\#}$$

$$d = 30'' - 3'' - \underbrace{(1'')}_{\text{CONC}} \underbrace{(\frac{1}{2})}_{\#8 \text{ BARS}} = 26.5''$$

$$R_n = \frac{M_u}{\phi b d^2} = \frac{(191,711 \text{ ft.}\cdot\#)(12'')}{(0.9)(30'')(26.5'')^2} = 121.33$$

$$\rho = 0.0021 < \rho_{min} = 0.0033$$

$$\text{USE } \frac{1}{3} \text{ INCREASE} \quad 1.33 \times 0.0021 = 0.0028$$

$$A_{s \text{ REQ'D.}} = (0.0028)(30'')(26.5'') = 2.23 \text{ in}^2$$

3 - #8 E.F.
-------------

CHECK SHEAR AT BASE OF P.LASTER:


$$V_u = 67,664^{\#}$$

$$\phi V_c = (0.85)(2)\sqrt{4,000}(30'')(26.5'') = 85,476^{\#} > 67,664^{\#} \text{ O.K.}$$

USE #4 TIES @ 12" O.C. Also #8 VERTICAL BARS
--

BASE DESIGN: (LOOK AT 8'-9" WIDE SECTION OF BASE)

[USE AVERAGE PILE REACTIONS FROM COMPUTER OUTPUT WITHOUT 75% REDUCTION ∴ INCREASE AVERAGE PILE REACTIONS BY 1/3.]





EAST OF HARVEY FDM

**BURK-KLEINPETER, INC.**  
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

CONCRETE DESIGN

Job No.

Designed By:

Date:

Checked By:

Page 5


9551-01

R. CHOPIN


5/5/78

of 7

V (K)



M (K.F)



EAST OF HARVEY FDM

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

FLOODGATES

CONCRETE DESIGN

Job No.

9551-01

Designed By:

R. CHOPIN

Date:

5/5/98

Checked By:

Page 6  
of 7TRANSVERSE FLEXURE DESIGN:

$$M_u = (1.7)(1.3)(47.703 \text{ FT.K}) = 106 \text{ FT.K} \quad (\text{POSITIVE MOMENT})$$

$$M_u = (1.7)(1.3)(-42.6276 \text{ FT.K}) = -95 \text{ FT.K} \quad (\text{NEGATIVE MOMENT})$$

$$d_{\text{POS}} = 30'' - 9'' - \frac{1}{2}'' = 20.5''$$

No. BARS

$$d_{\text{NEG}} = 30'' - 3'' - \frac{1}{2}'' = 26.5''$$

$$R_{n_{\text{POS}}} = \frac{(106 \text{ FT.K})(12''/k)(1,000 \text{ #/K})}{(0.9)(105'')(20.5'')^2} = 32.03$$

$$R_{n_{\text{NEG}}} = \frac{(95 \text{ FT.K})(12''/k)(1,000 \text{ #/K})}{(0.9)(105'')(26.5'')^2} = 17.18$$

$$S_{\text{POS}} = 0.0005 < S_{\text{MIN}} = 0.0033 \quad \text{USE } 1.33 \times 0.0005 = 0.0007$$

$$A_{s_{\text{POS}}} = (0.0007)(105'')(20.5'') = 1.54 \text{ IN}^2$$

$$S_{\text{NEG}} = 0.0003 \quad \text{USE } 1.33 \times 0.0003 = 0.0004$$

$$A_{s_{\text{NEG}}} = (0.0004)(105'')(26.5'') = 1.12 \text{ IN}^2$$

CHECK TEMPERATURE AND SHRINKAGE REQUIREMENTS IN SAME DIRECTION

$$A_{s_{\text{TEMP}}} = (0.0028 \times 30'' \times 105'') / 2 = 4.41 \text{ IN}^2 \quad \leftarrow \text{GOVERNS}$$

TOP + BOT

USE # 7 @ 12" O.C. TOP + BOTTOM

LONGITUDINAL FLEXURE DESIGN:

(GATE OPEN WITH TRUCKS CROSSING)

$$M_{\text{MAX POS. TRUCK}} = 16.5 \text{ FT.K}$$

$$M_{\text{MAX NEG. TRUCK}} = -24.5 \text{ FT.K}$$

$$V_{\text{MAX TRUCK}} = 16.3 \text{ K}$$

FLOODGATES

CONCRETE DESIGN

Job No.

9551-01

Designed By:

R. CHAPIN

Date:

5/5/98

Checked By:

Page 7

of 7

$$M_{u_{POST.}} = (1.7)(1.3) \left[ 3^{1/2} \text{ft} \times (8.75')^2 / 10 + 16.5 \text{ ft.k} \right] = 87.2 \text{ ft.k}$$

$$M_{u_{NEG}} = (1.7)(1.3) \left[ 3^{1/2} \text{ft} \times (8.75')^2 / 10 + 24.5 \text{ ft.k} \right] = 105 \text{ ft.k}$$

$$R_{n_{POS}} = \frac{(87.2 \text{ ft.k})(12\%)(1,000 \text{ #/k})}{(0.9)(96\text{'}) (20.5\text{'})^2} = 28.82$$

$$R_{n_{NEG}} = \frac{(105 \text{ ft.k})(12\%)(1,000 \text{ #/k})}{(0.9)(96\text{'}) (26.5\text{'})^2} = 20.77$$

$$P_{POS} = 0.0005 \quad \text{USE } 1.33 \times 0.0005 = 0.0007$$

$$A_{s_{POS}} = (0.0007)(96\text{'}) (20.5\text{'}) = 1.38 \text{ in}^2$$

$$P_{NEG} = 0.0003 \quad \text{USE } 1.33 \times 0.0003 = 0.0005$$

$$A_{s_{NEG}} = (0.0005)(96\text{'}) (26.5\text{'}) = 1.28 \text{ in}^2$$

CHECK TEMPERATURE AND SHRINKAGE REQUIREMENTS IN SAME DIRECTION

$$A_{s_{TEMP}} = (0.0028 \times 96\text{'}) (30\text{'}) / 2 = 4.03 \text{ in}^2$$

USE 9-#7 BARS TOP + BOTTOM

CHECK BASE FT TORSION

MAX. TORSION AT FACE OF PILE SUPPORTS

TORSION PER FOOT OF WALL

$$(55.885 \text{ ft.k} + 52.286 \text{ ft.k}) / 8.75' = 12.37 \text{ ft.k/ft}$$

$$T_u = (1.7)(1.3) (12.37 \text{ ft.k/ft}) (4.375') = 119.6 \text{ ft.k}$$

TORSIONAL STRENGTH OF CONCRETE

$$\phi T_c = \phi (0.5 \sqrt{f'_c} \Sigma x^2 y) \quad \text{WHERE } \phi = 0.85$$

$$= (0.85)(0.5) \sqrt{4,000} (96\text{'})^2 (30\text{'}) = 7,431,605 \text{ in.k}$$

$$= 619 \text{ ft.k} > 119.6 \text{ ft.k.} \quad \text{O.K.}$$

BY INSPECTION PUNCHING & BEAM SHEAR O.K.


EAST OF HARVEY FOM

FLOODGATES

**BURK-KLEINPETER, INC.**  
 ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS  
 NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

Job No. 9551-01	Designed By: R. Chapin	Date: 5/1/98	Checked By:	Page of
--------------------	---------------------------	-----------------	-------------	------------

INR5 FILE "EG2" 14" x 70" L&W



1000 FG2 5/1/1998 BKI 9551 FLOODGATE MONOLITH -  
 1005 CONCRETE PILES 14 INCH (2 PILE / 8 FT. BASE 8.75 FT. SPACING) 70' PILES  
 1010 PIN ALL  
 1020 BIJ 29.532 29.532 1901.2 0 0 0 0 0 3 8  
 1030 BIJ 29.532 29.532 1798.4 0 0 0 0 0 1 2 4 TO 7 9 10  
 1040 TENSION 1.0 ALL  
 1050 DLS S 70.0 54.0 736.0 210.7 173.0 1548.7 1123.5 H 14 3 8  
 1060 DLS S 73.8 56.9 736.0 210.7 173.0 1548.7 1123.5 H 14 1 2 4 TO 7 9 10  
 1070 ASC S 196 457.3 0.822 0.901 1.75 0.00 ALL  
 1080 PMAXMOM 30.85 30.85 ALL  
 1090 BATTER 3.0 1 2 4 TO 7 9 10  
 1100 ANGLE 180 1 TO 5  
 1110 ANGLE 0 6 TO 10  
 1120 PILE 1 -2.50 17.50 0.00 6 2.50 17.50 0.00  
 1130 ROW Y 5 1 4 AT -8.7500  
 1140 ROW Y 5 6 4 AT -8.7500  
 1150 LOAD 1 93.20 0.00 114.03 59.09 -340.58 0.00  
 1160 LOAD 2 93.20 0.00 114.03 59.09 -296.58 0.00  
 1170 LOAD 3 107.40 0.00 85.52 44.32 -443.92 0.00  
 1180 LOAD 4 107.40 0.00 85.52 44.32 -400.91 0.00  
 1190 LOAD 5 0.00 0.00 196.03 357.94 -170.85 0.00  
 1200 LOAD 6 0.00 0.00 228.03 293.94 -298.85 0.00  
 1210 LOAD 7 0.00 0.00 196.03 357.94 85.15 0.00  
 1220 LOAD 8 0.00 0.00 228.03 293.94 213.15 0.00  
 1230 LOAD 9 -4.46 0.00 147.02 268.46 93.98 0.00  
 1240 LOAD 10 -4.46 0.00 171.02 220.46 189.98 0.00  
 1250 LOAD 11 6.56 0.00 147.02 268.46 -172.43 -24.89  
 1260 LOAD 12 6.56 0.00 171.02 220.46 -268.43 -24.89  
 1261 LOAD 13 -12.75 0.00 0.00 44.32 53.93 0.00  
 1262 LOAD 14 12.75 0.00 0.00 44.32 -118.20 0.00  
 1270 TOUT 1 2 3 4 5 7  
 1280 FOUT 1 2 3 4 5 6 7 OFG2  
 1290 PSO 1  
 1300 PFO ALL  
 1310 FPL PFG2

FG2 1/11

\*\*\*\*\*  
 \* CORPS PROGRAM # X0080 \* CPGA - CASE PILE GROUP ANALYSIS PROGRAM  
 \* VERSION NUMBER # 90/11/30 \* RUN DATE 98/05/01 RUN TIME 10.16.36  
 \*\*\*\*\*

FG2 5/1/1998 BKI 9551 FLOODGATE MONOLITH  
 CONCRETE PILES 14 INCH (2 PILE / 8 FT. BASE 8.75 FT. SPACING)

THERE ARE 10 PILES AND  
 14 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

	X	Y	Z
	-----	-----	-----
WITH DIAGONAL COORDINATES = (	-2.50 ,	-17.50 ,	.00 )
	( 2.50 ,	17.50 ,	.00 )

\*\*\*\*\*

PILE STIFFNESSES AS INPUT

.29532E+02	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.29532E+02	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.19012E+04	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00

THIS MATRIX APPLIES TO THE FOLLOWING PILES -

3 8

.29532E+02	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.29532E+02	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.17984E+04	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00
.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00	.00000E+00

THIS MATRIX APPLIES TO THE FOLLOWING PILES -

1 2 4 5 6 7 9 10

\*\*\*\*\*

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X FT	Y FT	Z FT	BATTER	ANGLE	LENGTH FT	FIXITY
1	-2.50	17.50	.00	3.00	180.00		P
2	-2.50	8.75	.00	3.00	180.00		P

FGZ 2/11

3	-2.50	.00	.00	V	180.00	P
4	-2.50	-8.75	.00	3.00	180.00	P
5	-2.50	-17.50	.00	3.00	180.00	P
6	2.50	17.50	.00	3.00	.00	P
7	2.50	8.75	.00	3.00	.00	P
8	2.50	.00	.00	V	.00	P
9	2.50	-8.75	.00	3.00	.00	P
10	2.50	-17.50	.00	3.00	.00	P

\*\*\*\*\*

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	93.2	.0	114.0	59.1	-340.6	.0
2	93.2	.0	114.0	59.1	-296.6	.0
3	107.4	.0	85.5	44.3	-443.9	.0
4	107.4	.0	85.5	44.3	-400.9	.0
5	.0	.0	196.0	357.9	-170.9	.0
6	.0	.0	228.0	293.9	-298.9	.0
7	.0	.0	196.0	357.9	85.2	.0
8	.0	.0	228.0	293.9	213.2	.0
9	-4.5	.0	147.0	268.5	94.0	.0
10	-4.5	.0	171.0	220.5	190.0	.0
11	6.6	.0	147.0	268.5	-172.4	-24.9
12	6.6	.0	171.0	220.5	-268.4	-24.9
13	-12.8	.0	.0	44.3	53.9	.0
14	12.8	.0	.0	44.3	-118.2	.0

\*\*\*\*\*

ORIGINAL PILE GROUP STIFFNESS MATRIX

.17104E+04	.61856E-04	.84128E-11	.00000E+00	-.12736E+06	-.18557E-02
.61856E-04	.29532E+03	-.18557E-03	-.17347E-17	-.55670E-02	-.16280E-09
.81855E-11	-.18557E-03	.16775E+05	.00000E+00	.14552E-10	.55670E-02
.00000E+00	.00000E+00	.00000E+00	.35754E+09	.00000E+00	-.22352E-06
-.12736E+06	-.55670E-02	.14552E-10	.00000E+00	.15097E+08	.16701E+00
-.18557E-02	-.16189E-09	.55670E-02	-.23097E-06	.16701E+00	.45781E+08

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	5.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	1.
LOAD CASE	7.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	8.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	1.

LOAD CASE 9. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 0.  
 LOAD CASE 10. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 0.  
 LOAD CASE 11. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 0.  
 LOAD CASE 12. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 1.  
 LOAD CASE 13. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.  
 LOAD CASE 14. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 5.

\*\*\*\*\*

PILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.9233E-01	-.5488E-08	.6798E-02	.1983E-05	.5082E-03	.1062E-11
2	.9933E-01	-.5181E-08	.6798E-02	.1983E-05	.6022E-03	.1003E-11
3	.9821E-01	-.8400E-08	.5098E-02	.1487E-05	.4756E-03	.1626E-11
4	.1051E+00	-.8101E-08	.5098E-02	.1487E-05	.5676E-03	.1568E-11
5	-.2719E-01	.6154E-08	.1169E-01	.1201E-04	-.3652E-03	-.1191E-11
6	-.4757E-01	.6463E-08	.1359E-01	.9865E-05	-.6388E-03	-.1251E-11
7	.1355E-01	.7936E-08	.1169E-01	.1201E-04	.1820E-03	-.1536E-11
8	.3393E-01	.1002E-07	.1359E-01	.9865E-05	.4556E-03	-.1940E-11
9	.7946E-02	.6515E-08	.8764E-02	.9010E-05	.1417E-03	-.1261E-11
10	.2323E-01	.8082E-08	.1020E-01	.7399E-05	.3469E-03	-.1564E-11
11	-.1713E-01	.3787E-08	.8764E-02	.9010E-05	-.2816E-03	-.6524E-05
12	-.3241E-01	.4019E-08	.1020E-01	.7399E-05	-.4868E-03	-.6524E-05
13	-.1146E-01	.1386E-08	.2106E-16	.1487E-05	-.5383E-04	-.2682E-12
14	.1233E-02	-.1833E-08	-.2093E-16	.1487E-05	-.8355E-04	.3548E-12

\*\*\*\*\*

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES  
 \* INDICATES PILE FAILURE  
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3\*EMIN) FOR CONCRETE PILES  
 B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-2.8	.0	-14.2	.0	86.3	.0	.25	.39	1.02	.56
2	-2.8	.0	-14.5	.0	86.2	.0	.26	.39	1.02	.56
3	-2.7	.0	41.9	.0	84.1	.0	.60	.24	1.30	.56
4	-2.8	.0	-15.3	.0	86.1	.0	.27	.40	1.01	.56
5	-2.8	.0	-15.6	.0	86.0	.0	.27	.41	1.01	.55



FB2 4/11

6	2.7	.0	38.8	.0	-82.1	.0	.53	.25	1.28	.84
7	2.7	.0	38.5	.0	-82.2	.0	.52	.25	1.28	.84
8	2.7	.0	-16.1	.0	-84.1	.0	.30	.41	1.00	.56
9	2.7	.0	37.7	.0	-82.3	.0	.51	.26	1.27	.83
10	2.7	.0	37.4	.0	-82.4	.0	.51	.26	1.27	.83

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-3.0	.0	-13.4	.0	93.1	.0	.23	.40	1.04	.55
2	-3.0	.0	-13.7	.0	93.1	.0	.24	.40	1.03	.55
3	-2.9	.0	47.3	.0	90.5	.0	.68	.23	1.34	.87
4	-3.0	.0	-14.4	.0	93.0	.0	.25	.41	1.03	.55
5	-3.0	.0	-14.8	.0	92.9	.0	.26	.41	1.03	.54
6	2.9	.0	38.0	.0	-89.0	.0	.51	.27	1.29	.82
7	2.9	.0	37.6	.0	-89.0	.0	.51	.27	1.29	.82
8	2.9	.0	-21.4	.0	-90.5	.0	.40	.49	.99	.51
9	2.9	.0	36.9	.0	-89.2	.0	.50	.27	1.28	.82
10	2.9	.0	36.6	.0	-89.2	.0	.50	.27	1.28	.81

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-2.9	.0	-22.3	.0	90.6	.0	.39	.50	.99	.51
2	-2.9	.0	-22.5	.0	90.5	.0	.40	.51	.98	.51
3	-2.9	.0	36.8	.0	89.5	.0	.53	.27	1.28	.81
4	-2.9	.0	-23.1	.0	90.4	.0	.41	.51	.98	.51
5	-2.9	.0	-23.3	.0	90.4	.0	.41	.52	.98	.51
6	2.8	.0	40.7	.0	-87.4	.0	.55	.25	1.30	.84
7	2.8	.0	40.5	.0	-87.5	.0	.55	.25	1.30	.84
8	2.9	.0	-17.4	.0	-89.5	.0	.32	.44	1.01	.54
9	2.8	.0	39.9	.0	-87.6	.0	.54	.26	1.30	.83
10	2.8	.0	39.7	.0	-87.6	.0	.54	.26	1.29	.83

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-3.2	.0	-21.5	.0	97.3	.0	.38	.51	1.00	.50
2	-3.2	.0	-21.7	.0	97.2	.0	.38	.51	1.00	.50
3	-3.1	.0	42.1	.0	95.7	.0	.60	.26	1.32	.83
4	-3.1	.0	-22.3	.0	97.1	.0	.39	.52	1.00	.50
5	-3.1	.0	-22.5	.0	97.1	.0	.40	.52	1.00	.49
6	3.1	.0	39.9	.0	-94.1	.0	.54	.27	1.31	.82
7	3.1	.0	39.7	.0	-94.2	.0	.54	.27	1.31	.82
8	3.1	.0	-22.7	.0	-95.7	.0	.42	.52	.99	.50
9	3.1	.0	39.1	.0	-94.3	.0	.53	.27	1.31	.82
10	3.1	.0	38.9	.0	-94.3	.0	.53	.27	1.31	.81

LOAD CASE - 5

FBZ 5/1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.7	.0	21.0	.0	-22.6	.0	.28	.24	1.06	.8
2	.7	.0	18.9	.0	-22.9	.0	.26	.24	1.05	.8
3	.8	.0	1.4	.0	-24.8	.0	.02	.31	.96	.7
4	.8	.0	14.6	.0	-23.7	.0	.20	.25	1.03	.84
5	.8	.0	12.4	.0	-24.0	.0	.17	.26	1.02	.83
6	-1.0	.0	27.5	.0	30.8	.0	.37	.22	1.11	.89
7	-1.0	.0	25.3	.0	30.4	.0	.34	.23	1.10	.88
8	-.8	.0	43.0	.0	24.8	.0	.61	.20	1.17	.99
9	-1.0	.0	21.0	.0	29.7	.0	.28	.24	1.07	.86
10	-.9	.0	18.9	.0	29.3	.0	.26	.24	1.06	.85

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	1.4	.0	21.1	.0	-42.1	.0	.29	.26	1.10	.84
2	1.4	.0	19.3	.0	-42.4	.0	.26	.27	1.09	.83
3	1.4	.0	-10.6	.0	-43.3	.0	.20	.24	.94	.67
4	1.4	.0	15.8	.0	-43.0	.0	.21	.28	1.08	.81
5	1.4	.0	14.0	.0	-43.3	.0	.19	.29	1.07	.80
6	-1.7	.0	32.4	.0	51.1	.0	.44	.23	1.18	.88
7	-1.6	.0	30.6	.0	50.8	.0	.41	.23	1.17	.87
8	-1.4	.0	62.3	.0	43.3	.0	.89	.16	1.31	1.04
9	-1.6	.0	27.1	.0	50.3	.0	.37	.25	1.15	.85
10	-1.6	.0	25.3	.0	50.0	.0	.34	.25	1.14	.84

LOAD CASE - 7

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-.6	.0	25.9	.0	17.4	.0	.35	.23	1.07	.92
2	-.6	.0	23.7	.0	17.0	.0	.32	.23	1.06	.91
3	-.4	.0	32.6	.0	12.3	.0	.47	.21	1.09	.96
4	-.5	.0	19.4	.0	16.3	.0	.26	.24	1.04	.89
5	-.5	.0	17.2	.0	15.9	.0	.23	.24	1.02	.88
6	.3	.0	22.6	.0	-9.2	.0	.31	.23	1.04	.92
7	.3	.0	20.5	.0	-9.6	.0	.28	.24	1.03	.91
8	.4	.0	11.8	.0	-12.3	.0	.17	.25	.99	.86
9	.3	.0	16.2	.0	-10.3	.0	.22	.24	1.01	.88
10	.3	.0	14.0	.0	-10.6	.0	.19	.25	1.00	.87

LOAD CASE - 8

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-1.2	.0	30.8	.0	37.8	.0	.42	.22	1.14	.90
2	-1.2	.0	29.0	.0	37.5	.0	.39	.22	1.13	.89
3	-1.0	.0	51.8	.0	30.9	.0	.74	.18	1.23	1.02
4	-1.2	.0	25.5	.0	36.9	.0	.34	.23	1.11	.8
5	-1.2	.0	23.7	.0	36.6	.0	.32	.24	1.10	.8
6	.9	.0	22.7	.0	-28.7	.0	.31	.23	1.08	.87

FG2 6/11

7	.9	.0	20.9	.0	-29.0	.0	.28	.24	1.07	.87	#
8	1.0	.0	-.1	.0	-30.9	.0	.00	.08	.97	.75	
9	1.0	.0	17.4	.0	-29.6	.0	.24	.25	1.05	.85	
10	1.0	.0	15.6	.0	-29.9	.0	.21	.26	1.05	.84	

LOAD CASE - 9

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	-.4	.0	20.9	.0	11.2	.0	.28	.24	1.03	.90	#
2	-.4	.0	19.3	.0	10.9	.0	.26	.24	1.02	.90	#
3	-.2	.0	24.7	.0	7.2	.0	.35	.23	1.04	.93	#
4	-.3	.0	16.1	.0	10.3	.0	.22	.24	1.01	.88	#
5	-.3	.0	14.5	.0	10.1	.0	.20	.25	1.00	.87	#
6	.2	.0	15.4	.0	-5.0	.0	.21	.25	.99	.89	#
7	.2	.0	13.8	.0	-5.3	.0	.19	.25	.98	.88	#
8	.2	.0	8.6	.0	-7.2	.0	.12	.26	.96	.85	#
9	.2	.0	10.6	.0	-5.8	.0	.14	.25	.97	.86	#
10	.2	.0	9.0	.0	-6.1	.0	.12	.26	.96	.85	#

LOAD CASE - 10

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	-.9	.0	24.6	.0	26.5	.0	.33	.23	1.08	.89	#
2	-.9	.0	23.3	.0	26.2	.0	.32	.23	1.08	.88	#
3	-.7	.0	39.2	.0	21.2	.0	.56	.20	1.15	.98	#
4	-.8	.0	20.6	.0	25.8	.0	.28	.24	1.06	.87	#
5	-.8	.0	19.3	.0	25.6	.0	.26	.24	1.06	.86	#
6	.6	.0	15.5	.0	-19.7	.0	.21	.25	1.02	.86	#
7	.6	.0	14.2	.0	-19.9	.0	.19	.25	1.02	.85	
8	.7	.0	-.4	.0	-21.2	.0	.01	.06	.95	.77	
9	.7	.0	11.5	.0	-20.4	.0	.16	.26	1.00	.84	
10	.7	.0	10.2	.0	-20.6	.0	.14	.27	1.00	.83	

LOAD CASE - 11

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.4	.0	12.7	-.2	-13.0	.0	.17	.25	.99	.86	#
2	.4	.0	11.5	-.2	-13.9	.0	.16	.25	.99	.85	#
3	.5	.0	.6	-.2	-15.6	.0	.01	.30	.94	.79	
4	.5	.0	9.1	-.2	-15.6	.0	.12	.26	.98	.83	
5	.5	.0	7.8	-.2	-16.4	.0	.11	.27	.98	.83	
6	-.6	.0	23.6	-.2	19.1	.0	.32	.23	1.06	.90	#
7	-.6	.0	21.6	-.2	19.4	.0	.29	.23	1.05	.89	#
8	-.5	.0	32.7	-.2	15.6	.0	.47	.21	1.10	.95	#
9	-.7	.0	17.6	-.2	20.1	.0	.24	.24	1.04	.87	#
10	-.7	.0	15.6	-.2	20.4	.0	.21	.25	1.03	.86	#

LOAD CASE - 12

PILE	F1	F2	F3	M1	M2	M3	ALF	CBF	ASC	AST	
------	----	----	----	----	----	----	-----	-----	-----	-----	--

FBZ 7/11

	K	K	K	IN-K	IN-K	IN-K			KSI	KSI
1	.9	.0	12.8	-.2	-27.7	.0	.17	.27	1.03	.83
2	.9	.0	11.8	-.2	-28.5	.0	.16	.27	1.02	.8
3	1.0	.0	-8.4	-.2	-29.5	.0	.16	.18	.92	.7
4	1.0	.0	10.0	-.2	-30.1	.0	.14	.28	1.02	.81
5	1.0	.0	9.0	-.2	-30.9	.0	.12	.29	1.02	.80
6	-1.1	.0	27.3	-.2	34.4	.0	.37	.22	1.12	.89 #
7	-1.1	.0	25.6	-.2	34.8	.0	.35	.23	1.11	.88 #
8	-1.0	.0	47.1	-.2	29.5	.0	.67	.19	1.21	1.00 #
9	-1.2	.0	22.2	-.2	35.5	.0	.30	.24	1.09	.86
10	-1.2	.0	20.4	-.2	35.9	.0	.28	.25	1.08	.85

LOAD CASE - 13

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.3	.0	4.3	.0	-10.3	.0	.06	.27	.95	.82
2	.3	.0	4.0	.0	-10.3	.0	.05	.28	.94	.82
3	.3	.0	-3.1	.0	-10.4	.0	.06	.06	.91	.78
4	.3	.0	3.5	.0	-10.4	.0	.05	.28	.94	.82
5	.3	.0	3.2	.0	-10.5	.0	.04	.28	.94	.82
6	-.3	.0	-3.2	.0	10.5	.0	.06	.07	.91	.78
7	-.3	.0	-3.5	.0	10.4	.0	.06	.07	.91	.78
8	-.3	.0	3.1	.0	10.4	.0	.04	.28	.94	.81
9	-.3	.0	-4.0	.0	10.3	.0	.07	.08	.90	.78
10	-.3	.0	-4.3	.0	10.3	.0	.08	.08	.90	.78

LOAD CASE - 14

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	.0	.0	-4.4	.0	.4	.0	.08	.06	.88	.80
2	.0	.0	-4.7	.0	.4	.0	.08	.06	.88	.80
3	.0	.0	-4.8	.0	1.1	.0	.09	.06	.88	.80
4	.0	.0	-5.2	.0	.3	.0	.09	.07	.87	.79
5	.0	.0	-5.5	.0	.3	.0	.10	.07	.87	.79
6	.0	.0	5.5	.0	-.3	.0	.07	.26	.93	.85 #
7	.0	.0	5.2	.0	-.3	.0	.07	.26	.93	.85 #
8	.0	.0	4.8	.0	-1.1	.0	.07	.27	.93	.84 #
9	.0	.0	4.7	.0	-.4	.0	.06	.27	.93	.85 #
10	.0	.0	4.4	.0	-.4	.0	.06	.27	.92	.84 #

\*\*\*\*\*

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	7.1	.0	-12.6	.0	.0	.0

FBZ 8/11

2	7.3	.0	-12.9	.0	.0	.0
3	2.7	.0	41.9	.0	.0	.0
4	7.5	.0	-13.6	.0	.0	.0
5	7.6	.0	-13.9	.0	.0	.0
6	14.8	.0	36.0	.0	.0	.0
7	14.7	.0	35.6	.0	.0	.0
8	2.7	.0	-16.1	.0	.0	.0
9	14.5	.0	35.0	.0	.0	.0
10	14.4	.0	34.6	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	7.1	.0	-11.7	.0	.0	.0
2	7.2	.0	-12.1	.0	.0	.0
3	2.9	.0	47.3	.0	.0	.0
4	7.4	.0	-12.7	.0	.0	.0
5	7.5	.0	-13.1	.0	.0	.0
6	14.7	.0	35.1	.0	.0	.0
7	14.6	.0	34.8	.0	.0	.0
8	2.9	.0	-21.4	.0	.0	.0
9	14.4	.0	34.1	.0	.0	.0
10	14.3	.0	33.8	.0	.0	.0

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	9.8	.0	-20.2	.0	.0	.0
2	9.9	.0	-20.5	.0	.0	.0
3	2.9	.0	36.8	.0	.0	.0
4	10.1	.0	-21.0	.0	.0	.0
5	10.2	.0	-21.2	.0	.0	.0
6	15.6	.0	37.8	.0	.0	.0
7	15.5	.0	37.5	.0	.0	.0
8	2.9	.0	-17.4	.0	.0	.0
9	15.3	.0	37.0	.0	.0	.0
10	15.2	.0	36.7	.0	.0	.0

LOAD CASE - 4

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	9.8	.0	-19.4	.0	.0	.0
2	9.9	.0	-19.6	.0	.0	.0
3	3.1	.0	42.1	.0	.0	.0
4	10.0	.0	-20.1	.0	.0	.0
5	10.1	.0	-20.4	.0	.0	.0
6	15.5	.0	36.9	.0	.0	.0
7	15.4	.0	36.7	.0	.0	.0
8	3.1	.0	-22.7	.0	.0	.0
9	15.3	.0	36.2	.0	.0	.0
10	15.2	.0	35.9	.0	.0	.0

FBZ 9/11

LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-7.3	.0	19.7	.0	.0	.0
2	-6.7	.0	17.7	.0	.0	.0
3	-.8	.0	1.4	.0	.0	.0
4	-5.3	.0	13.6	.0	.0	.0
5	-4.7	.0	11.5	.0	.0	.0
6	7.7	.0	26.4	.0	.0	.0
7	7.1	.0	24.3	.0	.0	.0
8	-.8	.0	43.0	.0	.0	.0
9	5.7	.0	20.2	.0	.0	.0
10	5.1	.0	18.2	.0	.0	.0

LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-8.0	.0	19.6	.0	.0	.0
2	-7.4	.0	17.9	.0	.0	.0
3	-1.4	.0	-10.6	.0	.0	.0
4	-6.3	.0	14.5	.0	.0	.0
5	-5.8	.0	12.8	.0	.0	.0
6	8.7	.0	31.2	.0	.0	.0
7	8.1	.0	29.6	.0	.0	.0
8	-1.4	.0	62.3	.0	.0	.0
9	7.0	.0	26.2	.0	.0	.0
10	6.5	.0	24.5	.0	.0	.0

LOAD CASE - 7

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-7.6	.0	24.7	.0	.0	.0
2	-7.0	.0	22.7	.0	.0	.0
3	.4	.0	32.6	.0	.0	.0
4	-5.6	.0	18.6	.0	.0	.0
5	-5.0	.0	16.5	.0	.0	.0
6	7.4	.0	21.4	.0	.0	.0
7	6.8	.0	19.3	.0	.0	.0
8	.4	.0	11.8	.0	.0	.0
9	5.4	.0	15.2	.0	.0	.0
10	4.8	.0	13.2	.0	.0	.0

LOAD CASE - 8

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-8.6	.0	29.6	.0	.0	.0
2	-8.0	.0	27.9	.0	.0	.0

F62 10/11

3	1.0	.0	51.8	.0	.0	.0
4	-6.9	.0	24.5	.0	.0	.0
5	-6.4	.0	22.8	.0	.0	.0
6	8.1	.0	21.2	.0	.0	.0
7	7.5	.0	19.6	.0	.0	.0
8	1.0	.0	-.1	.0	.0	.0
9	6.4	.0	16.2	.0	.0	.0
10	5.9	.0	14.5	.0	.0	.0

LOAD CASE - 9

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-6.3	.0	20.0	.0	.0	.0
2	-5.8	.0	18.4	.0	.0	.0
3	.2	.0	24.7	.0	.0	.0
4	-4.8	.0	15.4	.0	.0	.0
5	-4.3	.0	13.8	.0	.0	.0
6	5.0	.0	14.6	.0	.0	.0
7	4.5	.0	13.1	.0	.0	.0
8	.2	.0	8.6	.0	.0	.0
9	3.5	.0	10.0	.0	.0	.0
10	3.0	.0	8.5	.0	.0	.0

LOAD CASE - 10

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-7.0	.0	23.6	.0	.0	.0
2	-6.6	.0	22.3	.0	.0	.0
3	.7	.0	39.2	.0	.0	.0
4	-5.7	.0	19.8	.0	.0	.0
5	-5.3	.0	18.6	.0	.0	.0
6	5.5	.0	14.5	.0	.0	.0
7	5.1	.0	13.2	.0	.0	.0
8	.7	.0	-.4	.0	.0	.0
9	4.3	.0	10.7	.0	.0	.0
10	3.9	.0	9.5	.0	.0	.0

LOAD CASE - 11

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-4.4	.0	11.9	.0	.0	.0
2	-4.1	.0	10.8	.0	.0	.0
3	-.5	.0	.6	.0	.0	.0
4	-3.3	.0	8.4	.0	.0	.0
5	-3.0	.0	7.3	.0	.0	.0
6	6.9	.0	22.6	.0	.0	.0
7	6.2	.0	20.7	.0	.0	.0
8	-.5	.0	32.7	.0	.0	.0
9	5.0	.0	16.9	.0	.0	.0
10	4.3	.0	15.0	.0	.0	.0

FGZ 11/11

LOAD CASE - 12

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-4.9	.0	11.8	.0	.0	.0
2	-4.6	.0	10.9	.0	.0	.0
3	-1.0	.0	-8.4	.0	.0	.0
4	-4.1	.0	9.2	.0	.0	.0
5	-3.8	.0	8.3	.0	.0	.0
6	7.6	.0	26.3	.0	.0	.0
7	7.0	.0	24.6	.0	.0	.0
8	-1.0	.0	47.1	.0	.0	.0
9	5.9	.0	21.4	.0	.0	.0
10	5.4	.0	19.8	.0	.0	.0

LOAD CASE - 13

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	-1.7	.0	4.0	.0	.0	.0
2	-1.6	.0	3.7	.0	.0	.0
3	-.3	.0	-3.1	.0	.0	.0
4	-1.4	.0	3.2	.0	.0	.0
5	-1.3	.0	3.0	.0	.0	.0
6	-1.3	.0	-3.0	.0	.0	.0
7	-1.4	.0	-3.2	.0	.0	.0
8	-.3	.0	3.1	.0	.0	.0
9	-1.6	.0	-3.7	.0	.0	.0
10	-1.7	.0	-4.0	.0	.0	.0

LOAD CASE - 14

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	1.4	.0	-4.2	.0	.0	.0
2	1.5	.0	-4.5	.0	.0	.0
3	.0	.0	-4.8	.0	.0	.0
4	1.7	.0	-5.0	.0	.0	.0
5	1.8	.0	-5.2	.0	.0	.0
6	1.8	.0	5.2	.0	.0	.0
7	1.7	.0	5.0	.0	.0	.0
8	.0	.0	4.8	.0	.0	.0
9	1.5	.0	4.5	.0	.0	.0
10	1.4	.0	4.2	.0	.0	.0



**FILL QUANTITY SPEADSHEETS**

**Reach 1 -- East Bank**

<b>Excavation and Embankment Quantities</b>						
<i>Station</i>		<i>TOTAL Excavation (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Excavation (VOL YD<sup>3</sup>)*</i>		<i>TOTAL Embankment (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Embankment (VOL YD<sup>3</sup>)*</i>
318+06.06						
318+07.06			0		23.48	0.43
320+06.68			0		53.76	285.53
322+06.56			0		67.49	448.8
324+06.55			0		60.76	474.98
326+06.49			0		61.96	454.38
328+06.44			0		60.45	453.26
330+06.38			0		72.54	492.41
332+38.79			0		2.62	323.48
332+65.			0		2.47	2.47
332+88.			0		1.51	1.7
333+11.			0		0	0.64
333+34.			0		0	0
333+57.			0		0	0
334+06.32			0		0	0
336+06.32			0		0	0
338+06.32			0		87.64	324.59
340+06.32			0		42.89	483.44
342+06.32			0		34.03	284.89
344+06.32			0		27.96	229.59
346+06.32			0		16.66	165.26
348+06.32			0		34.47	189.37
350+06.32			0		31.95	246
352+06.32			0		46.43	290.3
354+06.32			0		36.15	305.85
356+06.32			0		8.77	166.37
358+06.32			0		37	169.52
360+06.32			0		38	277.78
362+06.34			0		48.99	322.22
364+06.34			0		21.3	260.33
366+06.32			0		80.62	377.44
368+06.34			0		96.72	656.88
370+06.34			0		83.33	666.85
372+06.32			0		62.1	538.58
374+06.34			0		72.51	498.61
376+06.34			0		79.45	562.81

377+60.01			0	76.1	442.65
378+06.34			0	72.78	127.73
380+06.34			0	67.54	519.7
382+06.34			0	58.92	468.37
384+06.37			0	94.08	566.75
386+06.34			0	164.95	959.23
388+06.34			0	160.66	1205.96
390+06.34			0	157.15	1177.07
392+06.34			0	143.95	1115.19
394+06.34			0	99.88	903.07
396+06.34			0	69.07	625.74
397+64.			0	66.49	395.78
397+88.			0	42.25	48.33
398+06.34			0	48.06	30.67
400+06.34			0	76.8	462.44
401+80.			0	115.39	618.07
402+06.34			0	6.23	59.32
404+06.34			0	21.46	102.56
406+06.34			0	10.64	118.89
406+11.			0	0	0.92
406+18.			0	16.86	2.19
406+25.			0	0	2.19
406+55.41			0	0	0
408+06.34			0	25.62	86.04
408+05.77			0	25.67	71.48
410+05.77			0	20.51	171.04
412+05.77			0	17.15	139.48
414+06.37			0	19.41	135.81
416+06.34			0	51.15	261.29
418+05.77			0	82.81	494.73
420+05.77			0	119.84	750.56
422+05.77			0	117.24	878.07
424+05.77			0	89.37	765.22
426+05.77			0	101.82	708.11
428+05.77			0	66.62	623.85
430+05.77			0	64.82	486.81
432+05.77			0	26.07	336.63
434+05.77			0	44.31	260.67
436+05.77			0	64.7	403.74
438+05.77			0	45.43	407.89

<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>		<b>Fill (C.Y.)</b>	<b>26,889.00</b>

Reach 1 -- West Bank

Excavation and Embankment Quantities							
Station			TOTAL Excavation (Area Ft <sup>2</sup> )*	TOTAL Excavation (VOL YD <sup>3</sup> )*		TOTAL Embankment (Area Ft <sup>2</sup> )*	TOTAL Embankment (VOL YD <sup>3</sup> )*
1111+06.11							
1111+06.28		#		0		66.62	0.21
1113+06.28		#		0		58.57	463.67
1115+06.28		#		0		83.49	526.15
1117+06.28		#		0		69.38	566.19
1119+11.81		#		0		52.85	465.22
1121+34.47		#		0		33.9	357.7
1123+11.81		#		0		65.27	325.68
1125+11.81		#		0		81.63	544.07
1125+71.11		#		0		49.78	144.31
1126+08.61		#		0		55.92	73.4
1127+11.81		#		0		91.67	282.06
1129+11.81		#		0		99.99	709.85
1131+11.81		#		0		73.44	642.33
1133+11.81		#		0		70.36	532.59
1135+11.81		#		0		33.84	385.93
1137+11.81		#		0		52.39	319.37
1139+11.81		#		0		48.75	374.59
1141+11.81		#		0		90.07	514.15
1143+12.27		#		0		102.59	715.2
1145+12.27		#		0		76.87	664.67
1147+12.27		#		0		124.42	745.52
1149+12.27		#		0		77.39	747.44
1150+35.		#		0		43.03	273.69
1150+53.5		#		0		0	14.74
1150+65.		#		0		37.71	8.03
1151+12.27		#		0		44.56	72.02
1153+12.27		#		0		79.57	459.74
1153+42.27		#		0		45.54	69.51
1153+72.27		#		0		47.99	51.96
1154+02.27		#		0		66.88	63.82
1154+29.77		#		0		75.57	72.54
1154+56.87		#		0		72.57	74.34
1154+70.		#		0		56.51	31.39
1154+92.5		#		0		0	23.55
1155+12.27		#		0		60.92	22.3
1157+12.27		#		0		136.25	730.26

1159+12.27	#	0	94.28	853.81
1161+19.67	#	0	103.09	758.05
1163+12.27	#	0	110.5	761.8
1165+26.16	#	0	46	619.88
1167+12.27	#	0	125.04	589.49
1169+12.27	#	0	127.11	933.89
1171+12.27	#	0	59.92	692.7
1173+11.49	#	0	59.92	442.12
1174+15.	#	0	73.13	255.04
1174+33.6	#	0	66.33	48.04
1175+11.49	#	0	78.2	208.47
1177+11.49	#	0	58.12	504.89
1179+11.49	#	0	60.31	438.63
1181+11.49	#	0	95.19	575.93
1182+36.27	#	0	34.4	299.45
1183+11.49	#	0	58.13	128.89
1184+00.32	#	0	46.22	171.66
1185+11.49	#	0	140.33	384.05
1187+11.49	#	0	46.27	691.11
1189+23.32	#	0	47.12	366.35
1191+11.49	#	0	61	376.76
1193+11.49	#	0	67.78	476.96
1194+41.99	#	0	37.61	254.69
1195+11.49	#	0	33.75	91.84
1197+11.49	#	0	32.94	247
1199+11.49	#	0	24.7	213.48
1201+01.49	#	0	29.68	191.34
1203+46.23	#	0	53.58	377.35
1205+01.09	#	0	43.5	278.4
1207+11.49	#	0	23.45	260.86
1209+11.49	#	0	13.87	138.22
1210+36.33	#	0	25.83	91.78
1211+11.48	#	0	32.93	81.77
1213+11.48	#	0	16.24	182.11
1215+17.34	#	0	30.82	179.4
1217+23.14	#	0	18.8	189.11
1219+28.94	#	0	26.85	173.98
1220+96.11	#	0	20.7	147.2
1221+48.23	#	0	18.14	37.49
1223+48.23	#	0	32.98	189.33
1225+48.23	#	0	36.8	258.44
1225+87.27	#	0	38.51	54.45
1227+52.26	#	0	35	224.6
1229+52.26	#	0	37.49	268.48

1230+43.21	#	0	41.24	132.6
<b>TOTAL</b>	<b>Cut (C.Y.)</b>	<b>0</b>	<b>Fill (C.Y.)</b>	<b>26,910.08</b>

**Reach 2 -- East Bank**

<b>Excavation and Embankment Quantities</b>						
<i>Station</i>		<i>TOTAL Excavation (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Excavation (VOL YD<sup>3</sup>)*</i>		<i>TOTAL Embankment (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Embankment (VOL YD<sup>3</sup>)*</i>
438+06.34						
440+05.77			0		58.14	214.72
442+05.77			0		78.81	507.22
444+05.77			0		96.04	647.59
446+05.77			0		138.42	868.37
448+05.77			0		129.99	994.11
449+05.77			0		143.47	506.41
450+05.77			0		135.91	517.37
452+05.77			0		130.59	987.04
454+05.77			0		150.98	1042.85
456+05.77			0		127.3	1030.67
458+05.77			0		149.4	1024.81
460+05.77			0		175.26	1202.44
488+05.21			0		179.68	18400.62
490+05.21			0		168.04	1287.85
491+11.95			0		188.51	704.78
492+05.13			0		192.79	657.95
494+05.13			0		99.92	1084.11
496+04.2			0		126.19	833.55
496+06.21		Belle Chasse Pumping			0	4.7
499+68.		Station No. 1			0	0
499+68.17			0		137.44	1776.92
500+89.58			0		141.15	626.36
501+98.71			0		99.87	487.08
503+98.71			0		151.88	932.41
506+11.71			0		112.67	1043.5
507+98.71			0		132.26	848.18
510+17.82			0		95.7	924.97
510+46.63			0		114.41	112.1
511+98.63			0		143.03	724.65
513+98.63			0		117.43	964.67
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>		<b>Fill (C.Y.)</b>	<b>40,958.00</b>



Reach 2 -- West Bank

Excavation and Embankment Quantities							
Station			TOTAL Excavation (Area Ft <sup>2</sup> )*	TOTAL Excavation (VOL YD <sup>3</sup> )*		TOTAL Embankment (Area Ft <sup>2</sup> )*	TOTAL Embankment (VOL YD <sup>3</sup> )*
1038+43.							
1038+43.05				0		117.43	0.11
1040+42.4				0		159.19	1021.19
1042+42.4				0		146.41	1131.85
1044+42.4				0		115.28	969.22
1045+89.96				0		102.02	593.79
1046+23.94				0		118.22	138.59
1046+42.4				0		168.05	97.86
1046+42.4				0		169.23	0
1047+51.94				0		152.85	653.35
1047+89.94				0		104.4	181.03
1048+42.4				0		91.69	190.5
1049+21.83				0		84.35	258.94
1049+45.91				0		95.73	80.3
1050+42.4				0		73.25	301.94
1051+61.48				0		15.89	196.57
1052+94.08				0		49.64	160.91
1053+61.41				0		51.96	126.68
1055+61.41				0		20.68	269.04
1055+73.09				0		18.23	8.42
1055+97.09				0		90.85	48.48
1057+18.99				0		45.68	308.2
1058+88.77				0		2.78	152.36
1060+83.17				0		30.89	121.21
1062+57.67				0		33.49	208.04
1062+77.58				0		0	12.35
1062+97.67				0		34.05	12.67
1064+22.85				0		23.17	132.64
1064+72.06				0		4.92	25.6
1066+41.16				0		32.14	116.05
1081+06.44				0		195.56	6178.6
1081+65.98				0		155.58	387.16
1081+92.98				0		0	77.79
1082+19.98				0		121.98	60.99
1082+46.98				0		0	60.99
1082+74.37				0		121.6	61.68
1083+06.34				0		0	71.99

1083+38.41			0	142.11	84.4
1085+06.44			0	129.4	844.85
1087+06.44			0	127.86	952.81
1089+51.88			0	91.94	999.03
1091+31.08			0	35.52	422.98
1092+12.32			0	82.02	176.83
1093+06.33			0	54.64	237.91
1093+14.45			0	33.41	13.24
1094+65.94			0	71.22	293.53
1097+06.28			0	94.75	738.69
1097+53.26			0	0	82.43
1099+06.33			0	110.8	314.08
1101+06.28			0	154.02	980.57
1103+06.28			0	111.42	983.11
1105+06.28			0	147.74	959.85
1107+06.28			0	77.91	835.74
1109+06.28			0	72.4	556.7
1111+06.28			0	66.62	514.89
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>	<b>Fill (C.Y.)</b>	<b>24,408.73</b>

**Reach 3 -- East Bank**

<b>Excavation and Embankment Quantities</b>						
<i>Station</i>		<i>TOTAL Excavation (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Excavation (VOL YD<sup>3</sup>)*</i>		<i>TOTAL Embankment (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Embankment (VOL YD<sup>3</sup>)*</i>
514+00.						
515+98.73			0		178.58	657.21
517+98.63			0		141.28	1184.07
519+98.63			0		169.19	1149.89
521+98.63			0		152.35	1190.89
523+98.63			0		118.61	1003.56
525+98.63			0		96.21	795.63
527+98.63			0		106.45	750.59
529+98.63			0		105.47	784.89
531+13.63			0		41.2	312.35
532+17.2			0		121	311.09
533+98.47			0		90.96	711.52
535+98.47			0		55.51	542.48
537+98.47			0		36.1	339.3
539+98.47			0		69.98	392.89
541+98.47			0		88.13	585.59
543+98.47			0		95.99	681.93
545+98.47			0		104.69	743.26
547+98.47			0		137.85	898.3
549+98.47			0		136.84	1017.37
551+98.47			0		142.42	1034.3
553+98.47			0		154.05	1098.04
555+98.47			0		160.84	1166.26
557+98.47			0		151.15	1155.52
559+98.47			0		160.64	1154.78
561+98.47			0		104.91	983.52
563+98.47			0		83.3	697.07
565+98.47			0		62.86	541.33
567+98.47			0		47.43	408.48
569+82.			0		69.3	396.73
570+11.97			0		0	38.46
570+36.97			0		43.63	20.2
570+81.47			0		76.67	99.14
571+98.47			0		83.33	346.67
572+39.47			0		29.34	85.55
572+48.92			0		8.66	6.65

573+98.15			0	150.79	440.64
575+98.15			0	60.87	783.93
577+98.15			0	80.19	522.44
579+98.15			0	25.28	390.63
581+98.15			0	41.57	247.59
583+48.15			0	39.84	226.14
583+68.15			0	0	14.76
583+98.15			0	54.19	30.11
585+98.15			0	90.1	534.41
587+98.15			0	63.36	568.37
589+98.15			0	29.74	344.81
591+98.15			0	14.52	163.93
593+98.15			0	29.27	162.19
595+98.15			0	40.56	258.63
597+98.15			0	34.05	276.33
599+98.15			0	19.5	198.33
600+58.15			0	0	21.67
600+75.3			0	0	0
600+88.15			0	0	0
601+98.15			0	10.7	21.8
603+98.15			0	0	39.63
605+98.15			0	9.62	35.63
607+98.15			0	11.78	79.26
609+98.15			0	7.85	72.7
611+98.15			0	8.27	59.7
613+98.15			0	0	30.63
615+98.15			0	0	0
617+98.15			0	0	0
619+98.15			0	0	0
621+98.15			0	17.59	65.15
623+98.15			0	63.61	300.74
625+98.15			0	75.88	516.63
626+41.65			0	0	61.13
626+66.65			0	0	0
626+91.65			0	0	0
627+18.52			0	63.18	31.44
627+60.53		Belle Chasse Pumping		0	49.15
629+00.		Station No. 2		0	0
627+28.21			0	0	11.34
629+47.71			0	79.1	321.53
630+83.21			0	0	198.48
631+08.21			0	0	0
631+33.21			0	0	0

631+58.21			0		32.69	15.13
631+97.71			0		57.53	65.99
633+97.71			0		98.27	577.04
635+97.71			0		118.9	804.33
637+97.71			0		124.17	900.26
639+97.71			0		109.55	865.63
641+97.71			0		120.92	853.59
643+97.71			0		140.8	969.33
645+97.71			0		148.68	1072.15
647+97.71			0		148.66	1101.26
649+97.71			0		154.53	1122.93
651+97.71			0		163.77	1178.89
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>		<b>Fill (C.Y.)</b>	<b>39,891.89</b>

**Reach 3 -- West Bank**

<b>Excavation and Embankment Quantities</b>						
<i>Station</i>		<i>TOTAL Excavation (Area Ft^2)*</i>	<i>TOTAL Excavation (VOL YD^3)*</i>		<i>TOTAL Embankment (Area Ft^2)*</i>	<i>TOTAL Embankment (VOL YD^3)*</i>
897+02.65						
897+09.			0		188.94	22.22
899+09.			0		204.21	1456.11
900+58.41			0		190.87	1093.13
901+09.75			0		190.76	362.83
903+09.75			0		131.68	1194.22
905+09.75			0		126.72	957.04
907+09.75			0		162.75	1072.11
909+09.75			0		143.74	1135.15
911+09.75			0		148.92	1083.93
913+09.75			0		211.42	1334.59
915+09.75			0		129.98	1264.44
917+09.75			0		104.58	868.74
919+09.75			0		85.17	702.78
921+09.75			0		103.51	698.81
923+09.75			0		129.67	863.63
923+87.49			0		97.31	326.77
924+63.			0		16.08	158.56
925+38.22			0		48.72	90.26
927+39.38		Planters Pumping			0	181.49
932+46.79		Station			0	0
950+43.4			0		4.45	2466.67
952+43.4			0		13.49	66.44
954+43.4			0		21.79	130.67
956+43.4			0		40.61	231.11
958+43.4			0		36.19	284.44
960+43.4			0		21.59	214
962+43.4			0		32.4	199.96
963+29.88			0		43.02	120.78
964+43.41			0		33.25	160.35
966+43.41			0		63.78	359.37
968+43.41			0		112.41	652.56
968+99.41			0		16.4	133.58
970+41.41			0		48.87	171.64
971+52.78			0		18.16	138.24
972+43.41			0		70.39	148.62

974+90.91			0	95.47	760.19
975+14.69			0	70.54	73.11
975+44.69			0	63.39	74.41
977+42.9			0	28.48	337.21
978+13.29			0	0	37.12
978+42.5			0	36.25	19.61
979+13.			0	110.19	191.19
979+83.5			0	64	227.41
979+92.64			0	51.83	19.61
981+95.			0	53.64	395.24
982+20.06			0	19.47	33.93
982+45.			0	30.28	22.98
984+00.			0	46.97	221.74
984+13.47			0	5.01	12.97
984+29.47			0	76.96	24.29
984+47.49			0	71.54	49.56
986+47.49			0	52.88	460.81
988+47.49			0	86.39	515.81
990+47.49			0	108.22	720.78
990+93.82			0	85.76	166.43
991+18.82			0	26.13	51.8
991+43.82			0	71.9	45.38
992+22.46			0	24.81	140.84
992+47.49			0	63.88	41.11
993+29.69			0	90.39	234.83
993+59.69			0	54.86	80.69
993+89.69			0	114.25	93.95
994+47.49			0	132.91	264.55
996+47.49			0	100.44	864.26
998+47.49			0	91.71	711.67
1000+47.49			0	107.65	738.37
1001+51.91			0	50.57	305.95
1002+47.49			0	103.33	272.4
1003+19.72			0	58.27	216.15
1003+84.76			0	0	70.18
1004+43.29			0	86.28	93.52
1004+62.32			0	77.2	57.61
1004+72.32			0	45.58	22.74
1004+82.32			0	76.81	22.66
1005+57.22			0	66.33	198.54
1005+67.22			0	45.89	20.78
1005+77.22			0	72.54	21.93
1006+43.29			0	72.5	177.46

1008+04.			0	58.94	391.18
1008+43.29			0	107.03	120.76
1010+43.29			0	110.63	806.15
1011+04.9			0	105	246.02
1012+43.29			0	120.84	578.78
1014+43.29			0	107.37	845.22
1016+60.78			0	41.95	601.4
1017+14.26			0	65.78	106.69
1017+24.26			0	59.79	23.25
1017+34.26			0	77.79	25.48
1018+43.29			0	109.09	377.32
1019+30.62			0	82.95	310.57
1019+50.62			0	42.67	46.53
1019+70.62			0	62.24	38.86
1020+24.36			0	61.14	122.79
1022+43.29			0	125.96	758.55
1022+58.93			0	104.42	66.72
1022+73.93			0	67.35	47.71
1022+88.93			0	95.83	45.33
1023+53.18			0	69.28	196.45
1024+43.29			0	40.53	183.24
1026+43.29			0	82.64	456.19
1027+46.8			0	49.58	253.45
1028+43.29			0	90.86	250.95
1028+52.37			0	89.38	30.31
1029+50.26			0	82.43	311.45
1030+43.29			0	139.29	381.97
1032+43.29			0	182.97	1193.56
1032+96.76			0	183.63	363
1033+06.76			0	169.4	65.38
1033+16.76			0	180.08	64.72
1034+32.72			0	174.09	760.55
1034+52.72			0	132.49	113.55
1034+72.72			0	174.08	113.54
1035+24.74			0	145.65	308.01
1036+62.05			0	195.77	868.16
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>	<b>Fill (C.Y.)</b>	<b>40,930.80</b>



Reach 4 -- East Bank

Excavation and Embankment Quantities						
Station		TOTAL Excavation (Area Ft <sup>2</sup> )*	TOTAL Excavation (VOL YD <sup>3</sup> )*		TOTAL Embankment (Area Ft <sup>2</sup> )*	TOTAL Embankment (VOL YD <sup>3</sup> )*
652+00.						
653+97.71			0		138.69	507.79
655+97.71			0		112.96	932.04
657+97.91			0		136.14	1507.4
659+97.71			0		136.98	1010.54
661+97.71			0		117.54	942.67
663+29.57			0		117.02	572.76
664+00.			0		101.41	284.89
666+00.			0		84.46	688.41
668+00.			0		37.13	450.33
670+00.			0		27.86	240.7
672+00.			0		108.6	505.41
672+81.52			0		120.88	346.43
673+55.89			0		1.85	169.03
674+00.			0		89.01	74.22
676+00.			0		132.19	819.26
678+00.			0		104.13	875.26
680+00.			0		73.51	657.93
682+00.			0		59.53	492.74
684+00.			0		37.18	358.19
686+00.			0		52.24	331.19
686+48.74			0		73.13	113.16
688+00.			0		67.58	394.14
690+00.			0		35.85	383.07
692+00.			0		64.45	371.48
694+00.			0		85.25	554.44
696+00.			0		71.39	580.15
698+00.			0		66.89	512.15
700+00.			0		98.51	612.59
702+00.			0		97.03	724.22
704+00.			0		141.88	884.85
704+87.95			0		143.05	464.07
706+00.			0		181.85	674.17
708+00.			0		201.75	1420.74
710+00.			0		218.69	1557.19
712+00.			0		174.02	1454.48

714+00.			0	182.07	1318.85
715+22.46			0	150.83	754.94
716+00.			0	133.51	408.29
718+00.			0	46.96	668.41
720+00.			0	125.68	639.41
721+08.91			0	158.92	574
722+00.			0	143.43	510.02
724+00.			0	163.94	1138.41
725+77.71			0	171.8	1104.9
726+32.91			0	196.66	376.65
728+00.			0	167.41	1126.53
730+00.			0	162.32	1221.22
732+00.			0	163.61	1207.15
734+00.			0	176.39	1259.26
734+94.21			0	130.41	535.25
735+31.12			0	130.93	178.63
735+54.67			0	67.24	86.42
736+00.			0	99.78	140.2
738+00.			0	124.09	829.15
740+00.			0	121.86	910.93
742+00.			0	148.32	1000.67
742+72.99			0	126.98	372.11
744+23.		NOS&WB Pumping		0	352.75
792+73.		Station No. 11		0	0
748+00.			0	149.28	2696.14
749+24.3			0	69.85	504.4
750+09.4			0	144	337.01
752+00.			0	105.63	881.1
752+55.			0	147.79	258.11
752+74.7			0	170.22	116.01
752+95.			0	164.47	125.82
753+49.			0	153.89	318.36
754+00.			0	146.6	283.8
754+28.3			0	24.98	89.92
755+11.68			0	0	38.57
756+00.			0	112.18	183.48
758+00.			0	103.31	798.11
760+00.			0	100.2	753.74
762+00.			0	87.48	695.11
764+00.			0	85.33	640.04
766+00.			0	106.15	709.19
766+52.97			0	118.36	220.23
768+00.			0	122.55	655.94

769+12.93			0		0	256.29
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>		<b>Fill (C.Y.)</b>	<b>48,303.78</b>

### Reach 4 -- West Bank

<b>Excavation and Embankment Quantities</b>						
<i>Station</i>		<i>TOTAL Excavation (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Excavation (VOL YD<sup>3</sup>)*</i>		<i>TOTAL Embankment (Area Ft<sup>2</sup>)*</i>	<i>TOTAL Embankment (VOL YD<sup>3</sup>)*</i>
775+00.						
775+97.25			0		159.49	287.23
776+90.92			0		181.63	591.72
778+90.92			0		188.94	1372.48
780+90.92			0		204.21	1456.11
782+90.92			0		190.87	1463.26
784+90.92			0		190.76	1413.44
785+51.19			0		131.68	359.88
786+49.35			0		126.72	469.71
787+48.55			0		162.75	531.77
788+90.92			0		143.74	808.06
790+90.51			0		148.92	1081.7
792+90.11			0		211.42	1331.92
794+66.05			0		129.98	1112.33
796+21.27			0		104.58	674.23
798+21.27			0		85.17	702.78
799+07.69			0		103.51	301.96
800+95.43			0		129.67	810.69
802+95.43			0		97.31	840.67
804+95.43			0		16.08	419.96
805+37.23			0		48.72	50.16
805+62.31			0		4.45	24.69
805+86.89			0		13.49	8.17
806+95.43			0		21.79	70.91
808+95.43			0		40.61	231.11
810+95.43			0		36.19	284.44
812+95.43			0		21.59	214
814+95.43			0		32.4	199.96
816+95.43			0		43.02	279.33
818+95.43			0		33.25	282.48
820+02.07			0		63.78	191.62
821+86.23			0		112.41	600.87
823+70.39			0		16.4	439.29
824+96.92			0		48.87	152.94
826+96.92			0		18.16	248.26
828+96.92			0		70.39	327.96

829+87.87			0	95.47	279.35
830+96.93			0	70.54	335.28
832+96.93			0	63.39	496.04
834+96.93			0	28.48	340.26
836+56.28			0	0	84.04
838+10.31			0	36.25	103.4
839+31.54			0	110.19	328.76
840+55.78			0	64	400.77
841+80.02			0	51.83	266.49
842+96.49			0	53.64	227.48
844+12.96			0	19.47	157.69
845+24.28			0	30.28	102.56
846+63.37			0	46.97	198.98
848+02.46			0	5.01	133.89
849+07.88			0	76.96	160.02
850+13.3			0	71.54	289.9
851+89.3			0	52.88	405.52
853+77.24			0	86.39	484.71
855+00.84			0	108.22	445.44
856+24.45			0	85.76	444.03
857+42.93			0	26.13	245.49
859+40.36			0	71.9	358.41
861+41.7			0	24.81	360.59
863+43.03			0	63.88	330.67
865+43.03			0	90.39	571.37
867+43.03			0	54.86	537.96
869+43.04			0	114.25	626.36
869+76.36			0	132.91	152.51
869+94.36			0	100.44	77.78
870+81.1			0	91.71	308.65
871+27.06			0	107.65	169.68
871+67.82			0	50.57	119.43
871+89.72			0	103.33	62.41
873+10.72			0	58.27	362.1
874+63.63		NOS&WB Pumping		0	165
880+50.1		Station No. 13		0	0
882+49.46			0	0	1012.97
883+20.52			0	86.28	113.54
883+42.82			0	77.2	67.51
883+70.47			0	45.58	62.87
883+89.82			0	76.81	43.86
884+78.03			0	66.33	233.82
885+86.23			0	45.89	224.86

887+09.			0	72.54	269.25
889+09.			0	72.5	537.19
891+09.			0	58.94	486.81
893+09.			0	159.49	809
895+09.			0	181.63	1263.41
897+09.			0	188.94	1372.48
<b>TOTAL</b>		<b>Cut (C.Y.)</b>	<b>0</b>	<b>Fill (C.Y.)</b>	<b>36,266.68</b>