


**WEST BANK OF THE MISSISSIPPI RIVER
IN THE VICINITY OF NEW ORLEANS, LA
EAST OF HARVEY CANAL
HURRICANE PROTECTION PROJECT**

DESIGN MEMORANDUM NO. 3

**COUSINS PUMPING STATION
COMPLEX**

**IN TWO VOLUMES
VOLUME I**



**DEPARTMENT OF THE ARMY
NEW ORLEANS DISTRICT, CORPS OF ENGINEERS
NEW ORLEANS, LOUISISANA
OCTOBER 1999**

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW
ORLEANS, LA EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX

TABLE OF CONTENTS

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
PROJECT AUTHORIZATION		
1.	Authority	1
2.	Purpose and Scope	1
3.	Other Pertinent Projects	1
4.	Local Cooperation	2
5.	Status of Local Cooperation	2
6.	Project Document Investigations	2
LOCATION OF PROJECT AND TRIBUTARY AREA		
7.	Project Location	3
PROJECT PLAN		
8.	General	3
HYDROLOGY AND HYDRAULICS		
9.	Hydrology	4
10.	Hydraulics	5
GEOLOGY		
11.	General	10
SOILS AND FOUNDATIONS INVESTIGATION AND DESIGN		
12.	General	10
DESCRIPTION OF PROPOSED STRUCTURES AND IMPROVEMENTS		
13.	Pump Station and Appurtenances	10
14.	Culvert	18
15.	Destrehan Bridge Extension	18
16.	Roller Gates	18
17.	Floodwalls	19

TABLE OF CONTENTS (Continued)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
STRUCTURAL DESIGN		
18.	Criteria for Structural Design	19
19.	Basic Data	19
20.	Design Methods	20
21.	Pumping Station	21
22.	Culvert and Sheet Pile Cut Off Wall	22
23.	Destrehan Avenue Bridge Extension	25
24.	Bottom Roller Gates and Gate Monoliths	26
25.	I-Type Floodwall	26
26.	Cantilevered Sheet Pile Floodwall	27
27.	Pumping Station Frontal Protection	27
28.	Closure Wall	28
29.	Cathodic Protection and Corrosion Control	28
METHOD OF CONSTRUCTION		
30.	General	29
ACCESS ROAD		
31.	General	32
RELOCATIONS		
32.	General	32
ENVIRONMENTAL EFFECTS		
33.	General	33
COMPLIANCE WITH ENVIRONMENTAL LAWS		
34.	General	34
COORDINATION WITH OTHER AGENCIES		
35.	General	35
REAL ESTATE REQUIREMENTS		
36.	General	35
OPERATION AND MAINTENANCE		
37.	General	35
SCHEDULE FOR DESIGN AND CONSTRUCTION		
38.	Schedule for Design and Construction	36

TABLE OF CONTENTS (Continued)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
ESTIMATE OF INCREMENTAL COSTS		
39.	General	37
40.	Funds Required by Fiscal Year	38
RECOMMENDATIONS		
41.	Recommendations	38

TABLES

<u>Title</u>	<u>Page</u>
TABLE 1 Design Criteria for Cousins Discharge Channel	6
TABLE 2 Down Stream Elevations at Harvey Canal Considered for HEC-2 Model	6
TABLE 3 Description of HEC-2 Model Runs for First Avenue Canal	7
TABLE 4 Description of HEC-2 Model Runs for Cousins Discharge Channel	8
TABLE 5 Relevant Structural Design Data	20
TABLE 6 Pertinent Stresses for Reinforced Concrete Design	21
TABLE 7 Utility Relocation Schedule	32
TABLE 8 Schedule for Design and Construction East of Harvey Hurricane Protection Project Cousins Pumping Station Complex 2000 cfs	36

TABLE OF CONTENTS (Continued)

<u>Title</u>	<u>Page</u>
TABLE 9 Breakdown of Cost Between East of Harvey Project and SELA Projects	37
TABLE 10 Federal and Non-Federal Funding by Fiscal Year	38

PLATES

<u>Subject</u>	<u>Plate No.</u>	<u>Title</u>
General	G-1	Project Location Map Vicinity Map
	G-2	Overall Site Plan
	G-3	Existing Site Plan
	G-4	Required Site Plan
	G-5	Right-of-Way Plan
Cousins Pumping Station	P-1	Cousins Pumping Station Piling Plan
	P-2	Cousins Pumping Station Section
	P-3	Cousins Pumping Station Intake Basin
	P-4	Pumping Station Wingwalls
	P-5	Pumping Station Wingwalls
	P-6	2000 CFS Building Elevations
	P-7	Mechanical Piping Diagram
	P-8	Mechanical Equipment Layout
	P-9	Pumping Station Section
Destrehan Ave. Bridge	B-1	Destrehan Avenue Bridge
	B-2	Destrehan Avenue Bridge Details
Flood Gate	R-1	Bottom Roller Gate
	R-2	Bottom Roller Gate Sections
	R-3	Bottom Roller Gate Seal Details
	R-4	Bottom Roller Gate Latch Details - 1
	R-5	Bottom Roller Gate Latch Details - 2
Floodwalls	F-1	Frontal Protection Profile
	F-2	Existing Pump Station Section - 1
	F-3	Existing Pump Station Section - 2

TABLE OF CONTENTS (Continued)

<u>Subject</u>	<u>Plate No.</u>	<u>Title</u>
	F-4	T-Wall Section and Details
	F-5	North Floodwall Profile
	F-6	South Floodwall Profile
	F-7	Typical I-Wall & Cantilevered Sheet Pile Wall
	F-8	Typical Wall Joint (1 of 2)
	F-9	Typical Wall Joint (2 of 2)
	F-10	Utility Crossing Detail
	F-11	Closure Wall Plan
	F-12	Closure Wall Section and Utility Crossing
Channel	CH-1	First Avenue Canal Plan 1
	CH-2	First Avenue Canal Plan 2
	CH-3	First Avenue Canal Plan 3
	CH-4	First Avenue Canal Typical Sections
	CH-5	First Avenue Canal Existing Sections 1
	CH-6	First Avenue Canal Existing Sections 2
	CH-7	Discharge Channel Cross Sections (1 of 2)
	CH-8	Discharge Channel Cross Sections (2 of 2)
Electrical	E-1	Electrical Site Plan
	E-2	Proposed One Line Drawing
Culverts	C-1	Discharge Channel Culvert General Site Plan
	C-2	Discharge Channel Culvert Plan Elevation and Details
	C-3	Discharge Channel Culvert Connector Pile Plan and Details
	C-4	Discharge Channel Culvert Joint Detail
	C-5	Discharge Channel Culvert Panel Detail
	C-6	Discharge Channel Culvert Dredging Plan And R.O.W.
	C-7	Discharge Channel Culvert Dredging Profiles
	C-8	Discharge Channel Culvert Cross Section at Lapalco Bridge
	C-9	Discharge Channel Culvert Cut-Off/Retaining Wall and Detail

TABLE OF CONTENTS (Continued)

Appendices

Volume I

Appendix-A

Detailed Estimate of Incremental Cost

Appendix-B

HEC-2 Model Results

Appendix-C

Mechanical Machinery

Appendix-D

Physical Model

Appendix-E

Design Calculations

Volume II

Appendix-F

Geotechnical Investigation

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX

PROJECT AUTHORIZATION

1. Authority. The West Bank of the Mississippi River in the Vicinity of New Orleans (East of Harvey Canal), Louisiana project was authorized by Section 101(a)(17) of the Water Resources Development Act of 1996 (Public Law 104-303).
2. Purpose and Scope. The purpose of this Design Memorandum (DM) is to present the assumptions, criteria, and computations for developing the plan, design and cost estimates for constructing the Cousins Pumping Station Complex portion of the East of Harvey Canal Hurricane Protection features of the West Bank of the Mississippi River in the Vicinity of New Orleans, Louisiana Project. The recommended designs contained in this DM reflect the least costly method of providing the authorized standard project hurricane (SPH) protection. The basis for the recommended project is detailed in the West Bank of the Mississippi River in the Vicinity of New Orleans, LA (East of the Harvey Canal) Feasibility Report and Environmental Impact Statement dated August, 1994. The plan detailed in this DM consists of modifications to the Cousins Pumping Station to accommodate an additional 2,000 cfs. The outfall canal will be enlarged and diverted to discharge adjacent to navigable floodgate. A U-Frame Culvert will be constructed under Lapalco Bridge through which the outfall discharge will be routed. Parallel protection along the outfall canal will be provided. The connecting canal (First Avenue Canal) between the Harvey and Cousins Pumping Stations will be enlarged. The Destrehan Avenue Bridge will be extended by one span (60 feet) to accommodate the enlargement of Cousins outfall canal. Roller gates will be constructed on either side of the Destrehan Avenue Bridge to facilitate closing the bridge during flood conditions.
3. Other Pertinent Projects.
 - A. Mississippi River Levees. The Mississippi River levees below New Orleans, Louisiana are included in the comprehensive plan for the protection of the alluvial valley of the river between the Head of Passes, Louisiana and Cape Girardeau, Missouri, as authorized by the Flood Control Act of 15 May 1928 and subsequent acts.
 - B. Algiers Lock and Canal. The Algiers Lock and Canal Project was authorized by the River and Harbor Act of 2 March 1945, Public Law No. 14, 79th Congress, 1st Session. The project recommended modification of the existing project for the Gulf

Intracoastal Waterway between Apalachee Bay, Florida and the Mexican Border to provide an alternate waterway connection with the Mississippi River in the vicinity of Algiers, La.

C. Westwego to Harvey. The Westwego to Harvey project provides for SPH hurricane protection to the West Bank of the Mississippi River in Jefferson Parish between Westwego and the Harvey Canal. The project was authorized by the Water Resources Development Act of 1986 (Public Law 99-662). East of Harvey Canal was authorized as a modification to this project.

D. Southeast Louisiana. The Southeast Louisiana Project was authorized by Section 10 of the Fiscal Year 1996 Appropriations Act. The purpose of this project is to reduce flood damage on Jefferson, Orleans and St. Tammany Parishes.

4. Local Cooperation. In accordance with the cost sharing and financing concepts reflected in the Water Resources Development Act of 1986 (Public Law 99-662), and the authorizing documents, the non-Federal Sponsor must comply with the following requirements.

A. Provide lands, easements, and rights-of-way, and borrow and excavated material disposal area.

B. Accomplish all alterations and relocations to utilities and facilities (other than railroad bridges) necessary for construction of the project.

C. Pay 34.75 percent of the first cost allocated to hurricane protection. Funds provided by non-Federal interests for the interim hurricane protection may be considered beneficial expenditures and may be credited as part of the non-Federal contribution of the project pursuant to the Water Resources Development Act of 1986.

D. Bear all costs of operation, maintenance and replacement of all features of hurricane protection facilities.

5. Status of Local Cooperation. The Louisiana Department of Transportation and Development is the non-Federal Sponsor for construction of this project. A Project Cooperation Agreement (PCA) is being developed and will be signed before initiation of project construction.

6. Project Document Investigations.

A. General. A Feasibility Report entitled "West Bank of the Mississippi River in the Vicinity of New Orleans, LA. (East of the Harvey Canal)" dealing with providing hurricane protection for the West Bank of the Mississippi River in the vicinity of New Orleans for the area east of Harvey Canal was completed in August 1994. This study

recommended SPH level protection consisting of a navigable floodgate in the Harvey Canal, a 1,000 cfs increase in capacity at the Cousins Pumping Station, a combination of levees and floodwalls on the east side of Harvey Canal from the floodgate to Hero Pumping Station and raising the existing protection along the east and west sides of Algiers Canal and Hero Canal. Studies, investigations and planning made for this DM include the following:

- (1) surveys,
- (2) soils investigations including general and undisturbed type borings,
- (3) detail design studies for construction of the pumping station, fronting protection and floodwalls,
- (4) determination of real estate requirements and costs,
- (5) determination of required relocations and coordination with affected facility owners; determination of relocation costs,
- (6) cost estimates for the pumping station, fronting protection, floodwalls and levees.

B. Future investigations required. Future investigations to be performed include field surveys and soil borings in connection with the Plans and Specifications for the project.

LOCATION OF PROJECT AND TRIBUTARY AREA

7. **Project Location.** The Cousins Pumping Station Complex portion of the East of Harvey Hurricane Protection features of the West Bank of the Mississippi River in the Vicinity of New Orleans, Louisiana Project is located in southeast Louisiana in Jefferson Parish, on the west bank of the Mississippi River (Plate G-1).

PROJECT PLAN

8. **General.** The project work will consist of raising the flood protection along the Cousins Outfall Canal to the SPH level. Both the First Avenue Canal and the Cousins Pumping Station will be enlarged to accommodate an additional 2,000 cfs. A frontal protection T-wall will be provided on the discharge side of the Cousins Pumping Station. The outfall canal will be enlarged, and parallel protection I-walls will be provided. The Destrehan Avenue Bridge will be lengthened by one (1) sixty-foot span, and floodgates will be constructed at each end of the bridge. A required closure wall in the existing outfall canal will route the outfall discharge through required flume under the Lapalco Bridge into the Harvey Canal.

The authorized plan called for the addition of 1,000 cfs pumping capacity at the Cousins Pumping Station and modification of First Avenue Canal to accommodate an additional 1,000 cfs. Addition of another 1,000 cfs of pumping capacity was authorized under the Southeast Louisiana Project. This document contains designs for the addition of 2,000 cfs to the Cousins Pumping Station. Separate cost estimates are provided for the 1,000 and 2,000 cfs additions. The Ease of Harvey Project will pay for the addition of the first 1,000 cfs and the Southeast Louisiana Project will pay for the addition of the second 1,000 cfs.

HYDROLOGY AND HYDRAULICS

9. Hydrology.

A. General. The hydrology and hydraulic analysis for the East of Harvey Hurricane Protection features of the West Bank of the Mississippi River in the vicinity of New Orleans, Louisiana Project was presented in the Feasibility Report entitled West Bank of the Mississippi River in the Vicinity of New Orleans, La. (East of the Harvey Canal), August 1994. This document presented detailed descriptions and analyses of the hydrologic regime of the area and detailed descriptions and analyses of the hydraulic methods and procedures used in design of the features of this plan. Also included were essential data, assumptions and criteria used and results of studies that provide the basis for determining surges, routings, wind tides, wave runup and overtopping and frequencies. All basic hydraulic information required for design of the East and West of Algiers feature of the East of Harvey HPP project is included in this report.

B. Design Hurricane. The design hurricane is the SPH. The SPH represents the most severe combination of hurricane parameters that is reasonable characteristic of the area, excluding extremely rare combinations. The hurricane would approach each individual site at such a rate of movement as to produce the maximum hurricane surge at each location of interest. The SPH has a central pressure index of 27.4 inches of mercury, a maximum 5 minute average wind velocity offshore (in the Gulf of Mexico) of 100 knots 30 feet above the surface at a radius of 30 nautical miles, and a forward speed of 11 knots along a path critical to each location of interest.

C. Design Heights of Protected Structures. Predicted hurricane surge height for existing conditions along Harvey Canal is +7.5 NGVD and design elevation for protective structures is +9.5 NGVD. Historical evidence of sea level rise and subsidence indicates the need for a projection of storm surge stages and their effect on this project's effectiveness. Sea level rise of 0.5 foot per century along the Gulf Coast is recommended by the latest Corp's guidance. Estimates of subsidence in coastal Louisiana were developed by COE geologists from radio carbon dating of buried marsh deposits. Using the projected sea level rise of 0.25 foot in the next 50 years and the appropriate subsidence rate in the coastal zones bordering the project area, hurricane surge heights, which could be expected in the year 2040, were computed.

Predicted surge height for 50-yr. future conditions is +9.3 NGVD and elevation for protected structures is +11.5 NGVD.

10. Hydraulics.

A. General. Water from Cousins Canal and First Avenue Canal will be pumped to Cousins Discharge Channel, which will flow into Harvey Canal. The existing and design flow in Cousins Canal is 2,000 cfs. Existing flow in First Avenue Canal is 1,000 cfs. Two alternate design flows are considered for First Avenue Canal. Alternate 1 involves an additional 1,000 cfs flow in First Avenue Canal (total 2,000 cfs). Alternate 2 involves an additional 2,000 cfs discharge in First Avenue Canal (Total 3,000 cfs).

The existing flow in Cousins Discharge Channel is 3,000 cfs. The design flow in Cousins Discharge Channel will be 4,000 cfs according to Alternate 1 and 5,000 cfs according to Alternate 2.

HEC-2 Model runs were performed to determine water surface elevations and velocities in First Avenue Canal and Cousins Discharge Channel. Detailed HEC -2 model results are presented in Appendix B.

In addition, a physical model was built by Alden Research Laboratories, Massachusetts, for the Cousins Canal, First Avenue Canal and Cousins Discharge Channel. The results of the physical model are incorporated in the design. Description and results of physical model are presented in Appendix D.

B. Design Criteria. The design criteria for the First Avenue Canal and Cousins Discharge Channel are described in the following subsections.

1) Design Criteria for First Avenue Canal. The design criteria for the First Avenue Canal as per the Jefferson Parish Master Drainage Plan is to flow 2,100 or 3,100 cfs. The desired water surface elevation at the downstream side of First Avenue Canal (near Cousins Pump Station forebay) is -6.7 NGVD and on the upstream side of the First Avenue Canal (near Harvey Pump station) is -6.3 NGVD.

2) Design Criteria for Cousins Discharge Channel. HEC-2 Model run was performed to determine the water surface profiles in Cousins Discharge Channel for the following discharges that were based on the Jefferson Parish Master Drainage Plan:

TABLE 1
Design Criteria for Cousins Discharge Channel

DISCHARGE*	SCENARIO
1) 3,000 cfs	Existing discharge of 2,000 cfs through Cousins Canal and existing discharge of 1,000 cfs through First Avenue Canal
2) 4,000 cfs	Existing discharge of 2,000 cfs Through Cousins Canal and proposed discharge of 2,000 cfs through First Avenue Canal
3) 5,000 cfs	Existing discharge of 2,000 cfs through Cousins Canal + proposed discharge of 2,000 cfs through First Avenue Canal + an additional 1,000 cfs capacity in Cousins Pump Station

*Rounded to nearest thousand

The following down stream elevations are considered at Harvey Canal, which were based on the previous HEC-2 model runs performed by the Corps of Engineers:

TABLE 2
Down Stream Elevations at Harvey Canal Considered for HEC-2 Model

Number	Elevation in feet NGVD	Description
1.	-1.0	Maximum Drawdown Stage from the Standard Project Hurricane not on critical path
2.	0.0	99 % Duration Stage
3.	1.0	Approximate Low Mean Stage
4.	2.0	Approximate Normal Water Level
5.	3.0	Max. Elevation at which the Sector Gate would be operated
6.	4.0	0.1% Duration Stage
7.	5.0	Highest Stage of Record
8.	7.5	Hurricane Stage

C. Improvements to First Avenue Canal. The First Avenue Canal will be widened from the Harvey Pumping Station to the Cousins Pumping Station to accommodate an additional 2,000 cfs. The additional 2,000 cfs is required to bypass the Harvey Pumping Station when the proposed sector gate is closed during storm events. The current capacity of the Harvey Pumping Station is 1,000 cfs and an additional 1,000 cfs is added to First Avenue Canal as a result of improvements made under the Southeast Louisiana Project.

1) General. HEC-2 model runs were performed for First Avenue Canal for the following cases:

TABLE 3
Description of HEC-2 Model Runs for First Avenue Canal

Case No.	Channel Description	Elevation at Cousins P/S (ft. NGVD)	Discharge First Ave. (cfs)
Case 1	Existing channel cross sections and profile	-6.7	1,000, 2,100 and 3,100
Case 2	Design channel cross-section: bottom width 68' with 1V to 3H slope for approximately 1,000 ft from the Cousins P/S and bottom width 50' and 1V to 6H side slope for the remaining part of the Canal	-6.7	1,000, 2,100 and 3,100
Case 3	Design channel cross-section: bottom width 108' with 1V to 3H slope for approximately 1,000 ft from the Cousins P/S and bottom width 91' and 1V to 6H side slope for the remaining part of the canal	-6.7	1,000, 2,100 and 3,100

2) Results and Discussion for Case 1. The HEC-2 results for Case 1 indicated that the First Avenue Canal is capable of delivering a discharge of up to 3,000 cfs without overtopping the banks. However, it will not meet the Jefferson Parish Master Drainage Plan criteria of -6.3 NGVD (+14.13 C.D.) elevation at the upstream (near Harvey Pump Station). Therefore the First Avenue Canal needs to be improved.

3) Results and Discussion for Case 2. The results for Case 2 indicated that the First Avenue Canal, with the proposed cross-section, will deliver the 2,100 cfs discharge close to the Master Drainage Plan criteria. However, it will fail to meet the criteria with 3,100 cfs.

4) Results and Discussion for Case 3. The results for Case 3 indicated that the proposed cross section will deliver a discharge of 3,100 cfs with a water surface elevation at the upstream of the First Avenue Canal of -6.2 NGVD, which is close to the Master Drainage Plan criteria and is acceptable to Jefferson Parish.

D. Improvements to Cousins Canal. Improvements to the Cousins Canal are being done under a separate project included in the Southeast Louisiana Project.

E. Improvements to Cousins Discharge Channel. HEC-2 model runs were performed for Cousins Discharge Channel for the following cases:

TABLE 4
Description of HEC-2 Model Runs for Cousins Discharge Channel

Case Number	Channel Description	Elevations at Harvey Canal (ft. NGVD)	Discharge (Cousins Discharge Channel) (cfs)
Case 1	Existing channel cross sections and profile	-1 to +7.5	3,000, 4,000 and 5,000
Case 2	Design channel cross-section and profile (channel bottom -8 NGVD and -9 NGVD)	-1 to +7.5	4,000 and 5,000
Case 3	Sensitivity analysis. i.e., by varying Manning's 'n' and contraction and expansion coefficients using design channel cross-section and profile (channel bottom -9 NGVD)	-1 to +7.5	5,000
Case 4	Corps of Engineer's design of channel and culvert	-1 to +7.5	5,000

1) Results and Discussion for Case 1. The results of these runs indicated that, in some cases, the downstream elevations considered at Harvey Canal are higher than the existing bank elevations of the Cousins Discharge Channel. Therefore, the computed water surface elevations show overtopping of the banks. The water surface profiles for lower elevations (-1.0, 0.0, and 1.0 NGVD) at Harvey Canal showed unsteady flow pattern in sections close to Harvey Canal. It was observed

that the discharge channel bottom at those sections exhibit reverse slope with significant reduction in the channel cross-section. Hence, it is recommended that the channel cross-section be modified to reduce the velocity of water and turbulence as it meets the Harvey Canal. It was also observed that the computed water velocities in these sections are significantly higher than the previous sections. This may be attributed to the fact that the existing channel cross-sections at these sections are significantly constricted because of reduced depth of the channel. The Destrehan Avenue Bridge crosses the discharge channel between the pump station and the Harvey Canal was considered in these model runs for possible flow restrictions in the channel. It was determined that the flow in the Cousins Discharge Channel would be impeded by the bottom girder when the elevations at Harvey Canal are higher and/or the discharges through the channel are higher.

2) Results and Discussion for Case 2. Since the existing Cousins Discharge Channel showed very high velocities and water surface elevations for certain cases, it was determined that the Cousins Discharge Channel must be improved. Therefore, two alternate designs were proposed for channel improvement by considering the depth to -8 and -9 NGVD. The results indicated that, compared to both existing conditions and design with a channel bottom of -8 NGVD, a design channel bottom of -9 NGVD will significantly reduce the water surface elevations and velocities all along the Cousins Discharge Channel and in particular, near the Destrehan Avenue Bridge and the proposed culvert.

3) Results and Discussion for Case 3. Sensitivity Analyses was performed by running additional HEC-2 model runs by varying the Manning's coefficient and the contraction and expansion coefficients. Additional cross-sections were also incorporated at the proposed Cousins Discharge Channel bend. The results of these runs indicated a head loss of less than 6 inches between the discharge basin and the proposed culvert, except for some extreme instances where the Manning's coefficient and/or the contraction and expansion coefficients were higher than normal and the water surface elevations in the Harvey Canal were lower than normal conditions.

4) Results and Discussion for Case 4. HEC-2 model runs were performed for using the preliminary design shown in the West Bank of the Mississippi River in the Vicinity of New Orleans, La. (East of the Harvey Canal) - Feasibility Report. The Feasibility Report design has shorter reach of the Cousins Discharge Channel by pass and uses two box culverts between Lapalco Bridge piers. Due to this reason the estimated velocities at the culvert location are significantly higher as compared to the velocities at the location of the culvert proposed in this Design Memorandum for a 5,000 cfs discharge.

F. Improvements to Cousins Pump Station. The proposed project consists of an addition to Cousins Pumping Station. The addition consists of two (2) 1,000 cfs

horizontal pumps which will be constructed on the north side of the existing station. The additional 2,000 cfs is required to bypass the Harvey Pumping Station when the proposed sector gate is closed during storm events. The current capacity of the Harvey Pumping Station is 1,000 cfs with an additional 1,000 cfs called for in the Jefferson Parish Master Drainage Plan. Based on the results of the Alden Research Laboratory report, modifications will be made to the existing intake basin to smooth flow into the pump station.

GEOLOGY

11. General. The Geotechnical Investigation included drilling undisturbed borings, soil mechanics laboratory tests, and engineering analyses. Engineering analyses, based on the soil borings and laboratory test results, were made to determine recommendations regarding allowable pile load capacities, estimates of settlement, wall pressures, levee stability analyses, I-wall and T-wall analyses, overall pump station stability, canal stability, and construction recommendations. The results of the soil borings, laboratory tests, and analyses, together with appropriate recommendations, are included in the report of the Geotechnical Investigation (See Geotechnical Appendix Volume II).

SOILS AND FOUNDATIONS INVESTIGATION AND DESIGN

12. General. Soils and foundation investigation included drilling undisturbed borings, soil mechanics laboratory tests, and engineering analyses. Engineering analyses, based on the soil borings and laboratory test results, were made to determine recommendations regarding allowable pile load capacities, estimates of settlement, wall pressures, levee stability analyses, I-wall and T-wall analyses, overall pump station stability, canal stability, and construction recommendations. The results of the soil borings, laboratory tests, and analyses, together with appropriate recommendations, are included in Volume II.

DESCRIPTION OF PROPOSED STRUCTURES AND IMPROVEMENTS

13. Pump Station and Appurtenances.

A. Cousins Pump Station. This design memorandum covers two (2) alternates for the modifications to Cousins Pumping Station. Alternate No. 1 is the addition of one (1) 1,050 cfs horizontal pump into the existing Cousins Complex. The additional 1,000 cfs is needed to replace the current capacity of the Harvey Pumping Station when the sector gate in the Harvey Canal is closed. The Harvey Pumping Station currently discharges 1,000 cfs into the Harvey Canal north of the proposed sector gate. Alternate No. 2 is the addition of two (2) 1,050 cfs horizontal pumps into the existing Cousins Complex. The additional 2,100 cfs is for the existing 1,000 cfs at the Harvey Pumping Station and proposed 1,000 cfs addition to the Harvey Pumping Station which is authorized under the Southeast Louisiana Project.

1) Alternate No. 1 - 1,050 cfs addition

Scope: Under this alternate a single horizontal pump with associate drive equipment shall be installed in a new pump station addition to the north of the original Cousins Station. The station will house all the accessories that are needed to support a single one (1) 1,050 cfs horizontal pump.* The Accessories shall include:

- (a) One (1) Parallel Reduction Gear*
- (b) One (1) 3400 BHP (Continuous) @ 900 rpm Diesel Engine*
- (c) One (1) Air Cooled Engine Radiator*
- (d) One (1) 1,000 gallon Elevated Fuel Oil Storage Tank
- (e) One (1) Electric Motor driven Air Compressor
- (f) One (1) Diesel Engine driven Air Compressor
- (g) One (1) 2100 cfm Elect. Motor Driven Vacuum Pump
- (h) One (1) 2100 cfm Diesel Engine Driven Vacuum Pump
- (i) One (1) 750 gallon (100 ft³) Elevated starting Air Storage Tank
- (j) One (1) 750 gallon waste Lube Oil Tank
- (k) One (1) waste Lube Oil Transfer Pump
- (l) One (1) 350 cubic Feet Barometric Tank
- (m) One (1) Engine Control Panel*
- (n) One (1) Exhaust Silencer*
- (o) One (1) Air Intake Filler & Silencer*
- (p) Three (3) 20,000 gallon Fuel Oil Storage Tank
- (q) One (1) Duplex Fuel Oil Transfer Pump w/ Separator & Strainers
- (r) One (1) 30 feet Wide Trash Screen w/ Climber Type Rake
- (s) Four (4) Electric Exhaust Fans
- (t) Three (3) 250 gallon Elevated Fuel Oil Day Tank (Cousins No. 1)

* Denotes equipment to be supplied by Pump Manufacturer/Supplier under a separate contract. Regardless of which alternate is chosen, the description of the equipment for the installation of a single 1,050 cfs pump is identical to that of two (2) 1,050 cfs horizontal pumps.

2) Alternate No. 2 - 2,100 cfs addition

Scope: Under this alternate Two 1,050 cfs horizontal pumps with all associated drive equipment shall be installed in a new pump station addition constructed to the north of the original Cousins Station. The new station will house all accessories that are needed to support two (2) 1,050 cfs horizontal pumps.* These Accessories shall include:

- (a) Two (2) Parallel Reduction Gears*
- (b) Two (2) 3400 BHP (Continuous) @ 900 rpm Diesel Engine*

- (c) Two (2) Air Cooled Engine Radiator
- (d) Two(2) 1,000 gallon Elevated Fuel Oil Storage Tank
- (e) One (1) Electric Motor driven Air Compressor
- (f) One (1) Diesel Engine driven Air Compressor
- (g) One (1) 2100 cfm Elect. Motor Driven Vacuum Pump
- (h) One (1) 2100 cfm Diesel Engine Driven Vacuum Pump
- (i) Two (2) 750 gallon (100 ft³) Elevated Starting Air Storage Tank
- (j) One (1) 750 gallon waste Lube Oil Tank
- (k) One (1) waste Lube Oil Transfer Pump
- (l) Two (2) 350 cubic feet Barometric Tank
- (m) Three (3) 20,000 gallon Fuel Oil Storage Tank
- (n) One (1) Duplex Fuel Oil Transfer Pump w/ Separator & Strainers
- (o) Two (2) 30 feet Wide Trash Screen w/ Climber Type Rake
- (p) Six (6) Electric Exhaust Fans
- (q) Two (2) Engine Control Panels*
- (r) Two (2) Exhaust Silencers*
- (s) Two (2) Air Intake Fillers & Silencers*
- (t) Three (3) 250 gallon Elevated Fuel Oil Day Tank (Cousins No. 1)

* Denotes equipment to be supplied by Pump Manufacturer/Supplier under a separate contract. Regardless of which alternate is chosen, the description of the equipment for the installation of a single 1,050 cfs pump is identical to that of two (2) 1,050 cfs horizontal pumps.

3) Pump Operation. It is the intent of this document to propose equipment that when designed and constructed operates to meet the requirements set forth and follows the guidelines of operation for the similar pumps in the adjoining station. The horizontal pump shall provide a minimum pump capacity of 1,050 cfs at nominal intake and tidal head conditions. This pumping equipment selection will be capable of continuous pumping at both the current +7.50 NGVD storm surge requirements as well as the future projected storm surge of +9.50 NGVD.

4) Pump Tidal Protection. The discharge tube(s) proposed for the station addition will have a high invert of +9.50 NGVD for protection against the current and projected prediction of tidal surge events. The existing horizontal pumps have a discharge high invert of +5.07 NGVD. Based on this current protection, an intake tube ceiling elevation at its lowest invert of -16.50 and a 0.5 foot buffer or safety factor, the intake canal can be at elevation -11.57 NGVD or higher and continue to be protected against a +9.50 surge by using air suppression. The original Cousins Station that houses the three (3) 72 inch diameter and one (1) 36 inch diameter verticals have discharge pipe high inverts of +5.39 NGVD. At this elevation and the fact that the intake bells are below El. -20.00, air suppression could be considered for tidal protection on the verticals. Suppression would be a valid method of protection to intake elevations in excess of -15.00 when considering a +9.50 surge and a 0.50 foot buffer. However, since the discharge tubes of these pumps must be extended approximately 35 feet to accommodate the

new flood wall construction, it is more practical to install butterfly valves in both 72 inch and 36 inch discharges when the pipe is extended. To extend each of these discharges the existing discharge bells must be relocated to the flood side of the discharge flood wall. This will require the relocation of the vacuum breaker system and construction of an access catwalk to the protected side of the new flood wall. The 72 inch diameter discharge tubes should be fitted with a 24 inch diameter air release check valve and the 36 inch tubes with a 12 inch air release valve. These valves should be placed at the high point of the discharge just upstream of the discharge bell mitered elbow.

5) Pumping Equipment. The pumping equipment package which is composed of a 1,000 cfs, 132 inch diameter horizontal pump, a parallel reduction gear, diesel drive engine, engine control panel, exhaust silencer, intake air filler and silencer are all part of an equipment package to be supplied by others outside the scope of this contract. The equipment selected is described in the technical specifications in Appendix C, Mechanical Machinery. This equipment will be purchased under separate contract but installed under the construction contract for this station. The selection of the equipment type reflects the philosophies and desires by Jefferson Parish Department of Public Works as well as the design requirements set forth by the U.S. Corps of Engineers. The selection of remote mounted air cooled radiators versus Keel Coolers was one request made by the Parish. It was their feeling that remote radiators could be more easily maintained than the submerged Keel Coolers especially since there will be a 25 ton crane installed to service the pump rotating element regardless.

6) Overhead Cranes. The pumping station will be equipped with two overhead bridge type traveling cranes. A crane with 25 tons capacity will be installed inside the building to handle the engines, gears, vacuum pumps and other equipment located in the building. A crane with a capacity of 25 tons will be installed outside the building, over the 1,050 cfs pumps and will be used to handle these and other miscellaneous equipment in the area. The cranes will be controlled by pendant from the trolley with weatherproof controls.

B. Bar Screen and Mechanical Trash Rake

1) Bar Screen. Bar screens constructed of 0.5 inch x 9 inch galvanized steel flat bars on 4 inch centers and located at the inlet to the pump station preventing trash and debris from entering and damaging the pump or getting into the outfall canal.

2) Mechanical Trash Rake. Trash rakes will be provided to remove debris that accumulates on the bar screen. This trash rake will be of the climber type and will consist of a continuous unit. The unit will consist of vertical raking members mounted between two steel side frames.

A pin rack designed to mesh with two (2) cog wheels will be installed in each side frame. Debris will be removed from the 9 inch bar screen by a stainless steel rake assembly that is designed to mesh with the bar screen and span the entire channel.

The rake shall be driven by two (2) 10.0 horsepower, totally enclosed severe duty motors and shall be controlled by both local and remote control panels which shall be capable of either manual or automatic activation.

C. Fuel Oil Systems

1) General. The fuel oil systems for each pumping plant will include fuel oil storage tanks, transfer pumps, day tanks, piping control and alarms.

The new station will require the replacement of the four existing 10,000 gallon ground storage tanks to construct the new station. The existing fuel tanks will be replaced with three (3) new 20,000 gallon horizontal tanks to obtain a total fuel capacity of 60,000 gallons. This will include providing new elevated day tanks for the existing station to match the fuel delivery system proposed for the new station. Currently, the existing stations use exterior transfer pumps to pump to a floor mounted day tank which supplies fuel to and returns fuel back from the pump, compressor, generator and vacuum pump diesel engines. To circulate fuel back to the main storage tanks, a fuel pump out pump must be used. Under the new arrangement a new duplex transfer pump will be installed near the new and relocated storage tanks. Each pump will have its own dedicated discharge that can supply fuel to each day tank at each station. The new day tanks will be elevated to provide a positive head of fuel to the engines and gravity return or overflow back to the storage tanks. To provide uniformity in the method of operation, the existing original and station addition shall be equally reconfigured. This will require elevating the day tanks and repiping the fuel system to achieve the same operations as the proposed station.

2) Fuel Oil Storage Tanks. An additional 10,000 gallon fuel tank for each 1,000 cfs pump will be installed adjacent to the area proposed for relocation of the existing 10,000 gallon tanks. This capacity will provide sufficient fuel for all pumping operations for no less than three (3) days operation without refueling.

3) Fuel Oil Day Tanks. The pump engine will have a 1,000 gallon capacity fuel oil day tank. The day tank will be constructed of carbon steel in accordance with the National Fire Protection Association and have fill, overflow, drain, vent and outlet connections, level indicating gauge, and float switch to automatically control the fuel inlet solenoid valve and fuel oil transfer pump which fills all of the day tanks from the storage tanks. High and low level alarms will also be provided. In addition to the 1,000 gallon day tanks at the new station addition, three (3) 250 gallon elevated day tanks will be installed at Cousins No. 1 and two (2) 1,000 gallon elevated day tanks will be installed at Cousins No. 2 so that the

entire fuel system will operate by pumped fuel to the day tanks and return fuel to the supply tanks by means of gravity.

4) Fuel Oil Transfer Pumps. The existing Fuel Oil Transfer Pumps will be relocated and re-piped to provide fuel transfer from the fuel oil storage tanks to the station Day Tanks (including the existing stations).

D. Vacuum Priming Systems.

1) General. The vacuum priming system will provide vacuum priming for the 1,050 cfs pump, vacuum breaker valves to prevent back siphoning when a pump is stopped, and low pressure compressed air to depress the water level in all existing horizontal pump discharge tubes or lines under emergency conditions. The vacuum priming system for the 1,050 cfs pump will consist of one electric motor driven vacuum pump complete with barometric tanks, piping valves and controls. The vacuum breaker valves which will be located at the high point of the discharge tubes, will be pneumatically operated with a spring to open/air to close diaphragm valves and capable of automatic or manual operation.

2) Vacuum Pumps. An electric motor driven vacuum pump will be the primary vacuum pump to prime the 1,050 cfs pump system in the station. The pump will be a complete integral unit with the pump and motor mounted on a skid base. The pump will have a continuous rating of 2,100 cfm at 20 inches of mercury and will be driven by a 125 H.P. electric motor. The pump will be of the centrifugal water displacement type, single stage, capable of handling slugs of water without damaging the pump. The pumps will be Nash Engineering Co. Model CL-2002 or equal. The standby or emergency vacuum pump will be the same model and capacity as the electric driven pumps, but will be driven by a diesel engine through a reduction gear and clutch. The diesel engine will have a 175 continuous horsepower rating and will be radiator cooled. The pump, engine and reduction gear will be a complete integral unit mounted on a skid.

3) Vacuum Breaker Valves. One pneumatically operated and one manually operated (for emergency) vacuum breaker valves and associated piping will be located at the high point of all pump discharge tubes. The automatic operation of the vacuum breaker valve will be initiated by a RPM sensor on the pump input shaft.

4) Air Suppression System. The primary source of suppression air to depress the water level in the existing horizontal pump discharge tubes under emergency conditions will be the two 2,100 cfm vacuum pumps acting as low pressure air compressors. This reversal of air flow is accomplished by manually operated valves in the vacuum piping system. The suppression air pressure is 3.5 to 4.0 psig. The entire system is protected against excessive vacuum or pressure by a combination vacuum and pressure relief valve.

Connection to existing system although the new 1,000 cfs pump will have its own dedicated primary and backup vacuum pumps for priming and air suppression purposes, it shall also be connected to the existing vacuum pumps to create redundancy and increased capacity. Because of its proximity, the addition of air suppression to the proposed pumps can simply be accomplished by connecting to the vacuum prime system. Therefore, the new pumps will have suppression capability also.

E. Compressed Air System

1) General. The compressed air system will provide air to three pressure levels. Air will be compressed and stored at 250 psig. The highest pressure system will be used for starting the diesel engines driving the 1,000 cfs pump. Pressure reducing stations will be provided to reduce pressure from the highest level to 160 psig for general plant use, to 30 psi for instrument air. Two air compressors, one electric motor driven and one diesel engine driven, will provide air for all systems. As with the vacuum breaker system, the new compressed air system will provide redundancy and increased air capacity when connected to the compressed air system of the existing station. Compressed air, reduced to 3.5 psig will also serve as a back up to the air suppression system supplied by the vacuum pumps.

2) Air Compressors. The two air compressors will be two-stage, air-cooled, reciprocating type with air-cooled intercoolers. The capacity of each compressor will be 600 cfm at a minimum continuous discharge pressure of 250 psig. The electric drive unit will be driven by a 20 H.P., 1,800 RPM 480 volt, 3-phase, 60 hertz ball bearing induction motor.

The diesel drive unit will be driven by a 25 H.P., 2,000 RPM diesel engine. Each unit will be skid mounted and a complete package completely pre-wired with all required controls which will be the dual type combination of automatic start-stop or constant speed pressure unloader with manual selection switch.

3) Air Storage Tanks and Piping. Two (2) 750 gallon (100 ft³) storage tanks will be provided at the new station. Tanks will be designed for and ASME and National Board Stamped for an operating pressure of 300 psig. Piping will be Scheduled 80 galvanized steel pipe with socket welded fittings. Air tanks will be elevated to provide additional floor space for pump operation and floor space efficiency.

F. Ventilation System. Forced ventilation will be required in order to prevent temperatures within the building from reaching critical levels. Six (6) 42 inch direct drive panel fans will be required to provide exhaust functions. The fans shall have a capacity of 23,200 cfm at 0.25 inch static pressure standard air. The drive shall be a three horsepower, 1160 RPM, NEMA Design B direct drive electric motor. This

motor shall be a heavy duty, industrial continuous duty motor suitable for operation on 230/460 volts, 3 phase, 60 hertz.

Two hundred seventy five (275) square feet (gross area) of intake louvers will be provided on the East face of the buildings. This will provide approximately 138 square feet of free intake area. With the six exhaust fans operating at full capacity, this will provide a louver air velocity within the station of 1,000 feet per minute. The intake louvers shall be designed to be self draining and sized for free air velocity to be at least 200 fpm below the point of beginning water penetration of 2 oz. of water per square foot of free area. The intake louvers shall be manually operated.

G. Site Utilities.

To complete the station addition, several utilities must be relocated due to its current location being near the proposed station location. These utilities are as follows:

1) Emergency Well Water. The existing water well is located just adjacent to the fuel tank farm. Its location may require the well to be abandoned to facilitate construction. If relocation is required as established by final design, a new well of equal size will be located adjacent to the new fuel farm location. The submersible pump will be re-used in the well and the existing well will be plugged and abandoned.

2) Mechanical Sewer Treatment Plant. The location of the existing mechanical sewer treatment plant requires it to be relocated prior to construction of the new station. The plant will be up sized to handle the additional sewer flow attributed to the new bathroom facility required for the new station addition.

3) Propane Tanks. The propane tanks located north of Cousins No. 1 must be likewise abandoned and relocated to provide the area needed for construction of the station addition.

H. Electrical Distribution System. Cousins Pumping Station is presently served by an 800A, 480V, 3Ø, 3W underground service. The service pole is located on Lapalco Boulevard side with a bank of 3-167.5 kVA transformers. The underground service is terminated in the Motor Control Center in a metal building. This service feeds both the original pumping station (1973) and the addition (1983). The total connected load is 475kVA. The existing emergency generator is located inside the metal building (1983) and rated at 420kW, 480V, 3Ø, 3W.

Both the normal and emergency services are loaded to their maximums. Major alterations to existing normal service would be required if the new pumping station were to be fed from the present service. A more economical approach would be to feed the new pumping station from a separate pole located as indicated on the site

plan. New emergency generator proposed is 400kW, 480V, 3Ø, 3W located as indicated on site plan. The One-Line diagram on Sheet E-2 indicated the proposed distribution system.

14. Culvert. The HEC-2 model runs performed using the preliminary design shown in the West Bank of the Mississippi River in the Vicinity of New Orleans, LA. (East of the Harvey Canal) – Feasibility Report show high velocities at the culvert location. The Feasibility report called for two (2) Box culverts between piers of the Lapalco Bridge. From the perspective of hydraulics, this design will increase the velocities not only due to the obstruction caused by the pier but also due to the shorter reach of the modified Cousins Discharge Channel. Therefore, the culvert location is proposed to be moved closer to the Harvey Canal, adding approximately 150 feet to the Cousins Discharge Channel reach. The site is located directly below the Lapalco Boulevard Bridge on the west side of the main bridge piers, as shown on PLATE C-1.

Two construction methodologies were considered for the culvert (flume) structure: conventional cofferdam, pile-supported, cast in place, concrete structure and a float-in, pile-supported, concrete-gravity structure. The cost of the cast in place structure was estimated at \$3,123,679.00 (see Appendix E sheet S-12). The cost estimate of the pile-supported, float-in, concrete-gravity structure was considerably less at \$2,448,732.00 (see Appendix A Detail Estimate of Incremental Cost page A-9).

Therefore the design discharge flume included in this Design Memorandum consists of a pile-supported, float-in type, concrete-gravity-structure; whose function is to provide proper hydraulic flow from the Cousins Pump Station while providing anti-scour protection to the West piers of the Lapalco Bridge.

The float-in culvert is simply an “open-culvert” when installed, and due to the “flow-through” design, the Load Case scenario of dewatering was eliminated from consideration and not considered for cost projections.

The culvert will have a clear opening of 107.67 feet with a sill elevation of -9.00 NGVD. The seven and one half foot deep hull is installed at elevation - 16.50 NGVD, allowing a sill elevation of - 9.00 NGVD. The wing walls are 8 feet wide and 111 feet long, and extend to an elevation of +9.50 NGVD with a design elevation of +11.50 to allow for the 50 year subsidence, as shown on PLATE C-2.

15. Destrehan Bridge Extension. Destrehan Avenue Bridge will be lengthened by the addition of one sixty-foot span to accommodate the widening of the Cousins Pumping Station discharge channel. A bottom roller floodgate will be provided at each end of the bridge. For bridge details, see Plates B-1 and B-2.
16. Roller Gates. Bottom roller type floodgates will be provided at each end of the Destrehan Avenue Bridge at the following stations:

Gate Number	Centerline Station	Gate Opening Width
1	2+46.63 North Wall Line	40 feet
2	3+03.19 South Wall Line	40 feet

*See Plates R-1 to R-5 for details.

17. Floodwalls.

A. I-type Floodwalls.

The project includes 1123 feet of I-type floodwall protection along the banks of the Cousins Pumping Station discharge channel. The I-walls include two (2) bottom roller floodgates and ties into the pump station frontal protection on the west end of the discharge channel and the closure wall/cantilevered sheet pile wall on the east end of the discharge channel. The detailed alignment of the proposed I-wall is shown on Plate G-4. Typical I-wall design sections are shown on Plates F-7 through F-10.

B. Cantilevered Sheet Pile Wall.

The project includes 184 feet of cantilevered sheet pile wall protection along the Cousins Pumping Station discharge channel. The cantilevered sheet pile wall is located on the south side of the discharge channel and ties into the I-wall on the west end and the concrete culvert on the west end. The detailed alignment of the proposed I-wall is shown on Plate G-4. The typical cantilevered steel sheet pile wall design section is shown on Plates F-7.

STRUCTURAL DESIGN

18. Criteria for Structural Design. The structural design presented herein complies with standard engineering practice and criteria set forth in Engineering Manuals and Engineering Technical Letters for Civil Works Construction published by the Office of the Chief of Engineers, subject to modifications indicated by engineering judgement and experience to meet local conditions.

19. Basic Data. Basic data relevant to the design of the protective works are described in the following table:

TABLE 5
RELEVANT STRUCTURAL DESIGN DATA

Water Elevations

	<u>Elevations</u> (Feet N.G.V.D.)
Still Water Level (Harvey Canal)	7.5
Still Water Level + 2 feet Freeboard (Harvey Canal)	9.5
Low Water Level (Harvey Canal)	0.0
Cousins Pumping Station Intake	-8.5

Levee and Floodwall Net Grades

I-Walls, Cantilevered. Sheet Pile Wall, Bottom Roller Floodgates*	11.5
Pumping Station Frontal Protection T-Wall	11.5
Culvert	11.5
Discharge Channel Closure Wall	11.5

* Note: Structural design for the foundations of I-walls, cantilevered. sheet pile wall and bottom roller floodgates have been analyzed to an elevation of 11.50 NGVD with a still water elevation of 9.50 NGVD to accommodate future sea-level rise. Proposed construction of these items provide protection to an elevation of 9.50 NGVD, which is the current Standard Project Hurricane.

20. Design Methods:

A. Reinforced Concrete. The design of reinforced concrete structures is in accordance with the requirements of the strength design method of the current ACI Building Code, as modified by the guidelines of EM 1110-2-2104 "Strength Design Criteria for Reinforced Concrete Hydraulic Structures", dated January 1990. The basic minimum compressive strength of concrete will be 3,000 psi, except for prestressed concrete piling, where the minimum will be 5,000 psi, and for the culvert structure, where the minimum will be 6,000 psi. For convenient reference, pertinent stresses are tabulated below:

TABLE 6
Pertinent Stresses for Reinforced Concrete Design

Reinforced Concrete

fc' (bridge and gate substructure)	3,000 psi
fc' (bridge and superstructure)	3,200 psi
fc' (pump station and floodwalls)	4,000 psi
fc' (prestressed piles and culvert)	6,000 psi
fy (Grade 60)	60,000 psi
Maximum Flexural Reinforcement Ratio	0.25x balance ratio
Minimum Flexural Reinforcement Ratio	200/fy
fu (Prestressing Strands, Grade 250)	250,000 psi
fu (Prestressing Strands, Grade 270)	270,000 psi

B. Prestressed Concrete. (Panels)

P/S Tendons 0.50 inch diameter 270 KSI steel stress relieved strand, tensioned to 28.9 kips, init. 0.60 inch diameter 270 KSI, as spec.

C. Post Tension.

P/T Conduit - 1.66 x .072 diameter steel tubing
P/T Tendons (Same as above)
P/T Grout 10 KSI.

21. **Pumping Station.** The proposed pumping station will consist of a reinforced concrete structure on a pile supported foundation. The superstructure will consist of rigid structural steel frames and steel framing. Typical sections are shown on Plates P-1 to P-7.

Brief general construction specifications for the structure items are as follows:

A. Foundation Piling. All piling shall be Class B timber piles of Southern Yellow Pine or Douglas Fir conforming to American Society for Testing and Materials Standard Specifications for Round Timber Piles Designation D-25, latest revision thereof. For pile length of 54 feet and less, minimum tip diameter shall be 7 inches and minimum butt diameter shall be 12 inches. For pile lengths 55 feet to 74 feet, inclusive, minimum tip diameter shall be 7 inches and minimum butt diameter shall be 13 inches.

B. Steel Sheet Piling. All steel sheet piling for the temporary cofferdams and permanent steel sheet pile walls shall meet the requirements of the Standard

Specification for Steel Sheet Piling of the American Society of Testing and Materials, ASTM Designation A 328, latest revision thereof.

C. Concrete. In advance of any concrete operations, all materials proposed for use in concrete will be sampled and tested to determine their compliance with specifications. All concrete shall be designed, proportioned, mixed, placed and cured in accordance with the American Concrete Institute Specification ACE 301 and the Portland Cement Association's Bulletin A Design and Control of Concrete Mixture.

All concrete for the pump station shall have a minimum 28-day compressive strength of 4,000 psi.

D. Reinforcing Steel. All reinforcing steel shall be ASTM A615, Grade 60, New Billet Steel Bars with deformations conforming to ASTM A305 and shall be detailed, fabricated, installed and accessories provided in accordance with the latest revisions of ACI 318 and ACI 301.

E. Structural Steel And Miscellaneous Iron. Standards for the erection of steel and the furnishing of material for the work shall conform to the following American Institute of Steel Construction Publications:

- 1) Code of Standard Practice for Steel Buildings and Bridges
- 2) Specification for the Design, Fabrication and Erection of Structural Steel for Buildings
- 3) American Society for Testing and Materials:
 - Structural Steel shall conform to ASTM A-36
 - Hot dip galvanizing shall conform to ASTM A-123.

22. Culvert and Sheet Pile Cut Off Wall.

A. Culvert.

1) General. The proposed culvert consists of a pile-supported, "float-in" type concrete gravity structure. Appendix "E" includes all of the spread sheet calculations for the culvert design S-1 through S-7. Spreadsheet S-1 calculates the weight and draft of the seven and a half-foot deep hull with the design elevation of +11.50 NGVD.

Calculations for determining the hogging moment at launch are shown on S-2 and S-3. Determination of hogging moment is necessary because of the eccentric load

caused by the weight and center of gravity of the upper wing walls, which are located at the extreme ends of the hull. The hogging moment calculated, without ballast, is -14,402 feet (kips). The equivalent hogging moment stress is 240 psi. The prestress in the sill of the hull is 520 psi, as shown on S-3, therefore, final prestress due to hogging moment, without ballast is 280 psi.

The transverse moment of inertia is calculated for use in the hogging moment stress calculations in spreadsheet S-3. Sheet S-4 and S-6 calculates the various load cases analyzed, and Sheet S-5 and S-7 calculates the Floatation Factor of Safety.

2) Load Cases. Three load cases were analyzed, as follows:

a. Load Case I: The launching scenario wherein the completed 7 feet deep hull with the 18.5 feet wing walls above the hull deck, or "sill", is floated out of a graving dock.

b. Load Case II: Develops the hull stresses and soil bearing values at water elevation of - 1.00 NGVD. The hull is installed with full ballast in the seven-foot section, and a minimum of 8 feet of water will exist in the wing walls due to the free-flooding feature of the hull wing walls. In this condition, a hogging moment of - 11,505 feet kips is developed, causing a tension in the sill at - 9.00 feet elevation of 188 psi, or approximately 50 psi less tension than the floating hull prior to installation. The soil bearing is 184 psf.

c. Load Case III: Calculates similar values for a flood tide of +9.50 feet and +11.5 NGVD.

(i) Design Elevation +9.50 NGVD: The hogging moment at the center of the hull is reduced to -5,103 feet kips in this condition, while another-6,489 feet kips of hogging moment is caused by the internal channel head against the wing walls, resulting in a final hogging moment of -14,191 feet kips. This results in a sill tension of 288 psf versus the original 520 psf prestress, so that the hull or sill does not have any tension in any of its components during a flood tide. The soil bearing stress is reduced to 163 psf, with only 2 feet of wing wall exposed above the flood tide.

(ii) Elevation +11.50 NGVD: The hogging moment at the center of the hull is reduced to 5,187 feet kips in this condition, while another 9,187 feet kips of hogging moment is caused by the internal channel head against the wing walls, resulting in a final hogging moment of 16,165 feet kips. This results in a sill tension of 257 psf versus the original 520 psf prestress, so that the hull or sill does not have any tension in any of its components during a flood tide. The soil bearing stress is reduced to 159 psf, with only 2 feet of wing wall exposed above the flood tide.

(iii) Factor of Safety. The factor of safety against floatation SFF is calculated on Sheet S-5, and S-7 for 9.5 and 11.5 design flood elevations respectfully in accordance with the USACOE Engineer Technical Letter No. 1110 2-307 for external pressure loading as well as for buoyancy of the submerged hull. In all load cases the factor of safety against floatation exceeded the recommended minimum value of 1.30.

3) Pile & Soil Bearing Analysis.

- a. Soil Bearing Analysis, Sheet S-5, Piling Required: none.
- b. Pile Supported Alternate – No Dewatering, Sheet S-6, Piling Required: 24-24 inch piles x 80 feet in 30 inch sleeves.
- c. Pile Supported Alternate, With Dewatering and With Water Ballast, Sheet S-7, Piling Required: 24-36 inch piles x 115 feet in 42 inch sleeves.
- d. Pile Supported Alternate, With Dewatering and With Concrete Ballast, Sheet S-8, Piling Required: 24-36 inch piles x 140 feet in 42 inch sleeves.

B. Connector Piles. Review of the proceeding three Load Cases indicates that the worse case scenario for the structure is Load Case II. To eliminate soil bearing, without dewatering, the analysis of this case showed that due to the soil bearing pressure of 184 to 200 psf the structure would require 24-24 inch diameter piles of 60 ton capacity, installed in and grouted to 30 inch diameter connector sleeves. These connector sleeves are cast into the hull grid. The analysis of this case is shown on Sheet S-6. Sheets S-7 and S-8 are based on a dewatering scenario, which, has been eliminated as a design scenario due to the open culvert design.

The sleeves are 30 inche diameter pipe of a minimum 0.5 inch wall thickness, and are anchored to the basic hull with welded studs on the outside of the sleeve, which are fully encased by the concrete pour in the appropriate cells, as shown on plate C-3.

The 30 inch sleeves are 6.5 feet long, having welded studs on the outside to transmit the 60 ton shear to the basic hull, with 0.75 inch x 2 inche flat bars vertically installed on 120 degree spacing to act as “spiders” to center the 36 inch pile.

The top of the 30 inch sleeves are equipped with a 1 inch thick flange equipped with 16 – 1 inch round bolts, with the head of the bolt on the bottom of the flange and the threaded portion extending up 4 inches. This flange is cast level with the hull “sill” of the barge.

Then a 30 inch diameter sleeve is bolted to the installed bolts, and these sleeves extend up to an elevation + 2.00 NGVD, with the hull sill at 9 feet below the specified water line. These upper sleeves are equipped with a rubber gasket to seal the flanges together. Twelve of these units are shipped, installed on the sill deck of the barge hull before installation. The 12–36 inch connector piles are then driven, and fully grouted by pumping out the water in the 3 inch interstice and casting a non-shrink tremy concrete in between.

The 12 upper sleeves are then unbolted by divers, and installed on the other side of the hull, (and bridge) for the driving of the remaining 12 connector piles.

Once the float-in structure is installed, the entire hull will be free-flooded, so that all compartments, including the wing walls, will always be filled with water.

C. Sheet Pile Cut Off Wall.

1) General. Steel sheet piles will be driven on either side of the proposed location of the float-in structure in the discharge channel to an Elevation of –39.0 NGVD, as shown in plate C-8.

Also, the sheet piling is driven only on the parallel sides of the channel section and the area of excavation is not closed off by sheet piling across the proposed channel.

2) Loading Cases. Analysis shown on sheet S-4.

23. Destrehan Avenue Bridge Extension.

A. General. Destrehan Avenue Bridge will be lengthened by the addition of one sixty-foot span. Modifications to the bridge will include a new north abutment, and the addition of two 16 inch prestressed concrete piles to the existing north abutment. New bearing seats will be constructed on the existing north abutment to support the required superstructure. The superstructure consists of 5 – 60 feet Type III precast prestressed concrete girders supporting a 7 inch deck. Required barrier railing will match the existing.

B. Loading Cases. The lengthening of Destrehan Avenue Bridge was designed in accordance with AASHTO requirements for HS-20 loading. The following load cases were considered:

Group 1: Dead Load+Live Load+Impact
100% of Allowable Stress Used

Group 3: Dead Load+Live Load+Impact+Wind+Longitudinal Force
125% of Allowable Stressed Used

24. Bottom Roller Gates and Gate Monoliths.

A. General. Bottom Roller Gates will be constructed at locations described in Paragraph 19. The gate monoliths for the bottom roller gates will consist of a reinforced concrete stem on a monolithic concrete base supported on prestressed concrete piles. A continuous steel sheet pile seepage cutoff wall will be provided beneath the base slab for seepage cutoff purposes.

B. Loading Cases. The pile designs for the bottom roller gate monoliths, based on the use of a pile test, are designed with a factor of safety = 2.0. The following load cases were used for preliminary design of the bottom roller gate monoliths:

- (1) Case I: Gate closed, static water pressure to SWL, no wind, impervious sheet pile cutoff, no dynamic wave force (100% forces used).
- (2) Case II: Gate closed, static water pressure to SWL, no wind, pervious sheet pile cutoff, no dynamic wave force (100% forces used).
- (3) Case III: Gate closed, static water pressure to SWL +2 feet, no wind, impervious sheet pile cutoff, no dynamic wave force (75% forces used).
- (4) Case IV: Gate closed, static water pressure to SWL +2 feet, no wind, pervious sheet pile cutoff, no dynamic wave force (75% forces used).
- (5) Case V: Gate closed, wind from protected side (75% forces used).
- (6) Case VI: Gate closed, winds from flood side (75% forces used).
- (7) Case VII: Gate open, no wind, and truck on protected side edge of base slab (100% forces used).
- (8) Case VIII: Gate open, no wind, and truck on flood side edge of base slab (100% forces used).
- (9) Case IX: Gate open, wind from protected side, and truck on flood side edge of base slab (75% forces used).
- (10) Case X: Gate open, wind from flood side, and truck on protected side edge of base slab (75% forces used).

25. I-Type Floodwall.

A. General. The I-walls consist of steel sheet piling driven into the existing earthen embankment. The upper portion of the sheet piling will be capped with concrete. The sheet piling will be driven to the required depth with 9 inches of the sheet piling

extending above the finished ground elevation. The concrete portion of the floodwall will extend from 2 feet below the finished ground elevation to the required protection height. A typical I-wall section is shown on Plate F-7.

B. Loading Cases. In the design of the I-walls, the following loading cases were considered:

- (1) Case I: Water SWL, Q-Case, F.S. = 1.5
- (2) Case II: Water to SWL + 2 feet, Q-Case, F.S. = 1.0
- (3) Case III: Water to SWL, S-Case, F.S. = 1.2
- (4) Case IV: Water to LPL with lateral earth pressure

C. Joints. Expansion joints in the I-walls will be spaced at approximately 32.5 feet apart, adjusted to fall at the steel sheet pile interlocks. To compensate for expansion, contraction, or displacement, three-bulb waterstops and premolded expansion joint fillers will be provided. Where the I-wall joins the T-wall, the deflection of the I-wall will produce a lateral displacement. To compensate for this displacement, a special sheet pile connection detail and a waterstop seal located in a notch in the I-wall have been designed to prevent water from flowing through this joint.

26. Cantilevered Sheet Pile Floodwall.

A. General. The cantilevered sheet pile wall consists of steel sheet piling driven into the existing earthen embankment to an elevation of 9.5 NGVD. The sheet piling will be capped with a 2 feet x 2 feet concrete cap to an elevation of 10.00 NGVD. A typical cantilevered sheet pile wall section is shown on Plate F-7.

B. Loading Cases. In the design of the cantilevered sheet pile wall, the following loading cases were considered:

- 1) Case I: Water to SWL, Q-Case, F.S. = 1.5
- 2) Case II: Water to SWL + 2 feet, Q-Case, F.S. = 1.0
- 3) Case III: Water to SWL, S-Case, F.S. = 1.2
- 4) Case IV: Water to LPL with lateral earth pressure

27. Pumping Station Frontal Protection.

A. General. Pumping Station Frontal Protection will be provided by a T-wall. The T-wall will consist of a reinforced concrete stem on a monolithic concrete base of varying width supported on prestressed concrete piles. The base of the T-wall will be constructed on a four-inch concrete stabilization slab. A continuous steel sheet pile wall will be provided beneath the base for seepage cutoff purposes.

B. Loading Cases. The T-walls were designed for the following load conditions:

- 1) Case I: Static water pressure to SWL, no wind, impervious sheet pile cutoff (100% of forces used)
- 2) Case II: Static water pressure to SWL, no wind, pervious sheet pile cutoff (100% of forces used)
- 3) Case III: Static water pressure to SWL +2 feet, no wind, impervious sheet pile cutoff (75% of forces used)
- 4) Case IV: Static water pressure to SWL +2 feet, no wind, pervious sheet pile cutoff (75% of forces used)
- 5) Case V: Water at low water level, no wind (100% of forces used)
- 6) Case VI: Water at low water level, wind from protected side (75% of forces used)

C. Joints. Expansion joints in the T-wall will be spaced not more than 40 feet apart. To compensate for expansion, contraction, or displacement, three-bulb waterstops and premolded expansion joint fillers will be provided.

28. Closure Wall.

A. General. The closure wall will consist of two rows of 84 inch Ø cylinder piles filled with sand. The floodside of the wall will be lined with steel sheet pile. An 18 feet by 4 feet cast-in-place concrete cap will connect the cylinder piles to the sheet piles.

B. Loading Cases. In the design of the closure wall, the following loading cases were considered:

- 1) Case I: Water to SWL, Q-Case, F.S. = 1.5
- 2) Case II: Water to SWL + 2 feet, Q-Case, F.S. = 1.0

C. Joints. Expansion joints in the concrete cap will be spaced approximately 33 feet apart, adjusted to fall at the steel sheet pile interlocks. To compensate for expansion, contraction, or displacement, three-bulb waterstops and premolded expansion joint fillers will be provided.

29. Cathodic Protection and Corrosion Control.

A. Cathodic Protection for Steel Sheet Piling. All steel sheet piling will be bonded together to obtain electrical continuity and no corrosion protection measures will be provided. Cathodic protection can be installed in the future if the need arises. The

sheet piles will be bonded together with a No. 6 reinforcing bar welded to the top of each pile. Flexible jumpers insulated with cross-linked polyethylene will be welded or brazed to adjacent sheet piles at the monolith joints, 2 to 3 inches below the bottom of the concrete.

B. Corrosion Control. All exposed ferrous metal components will be either galvanized or stainless steel to provide for corrosion control.

METHOD OF CONSTRUCTION

30. General

A. Cousins Pumping Station. Prior to beginning construction on the addition to Cousins Pumping Station, the existing fuel tanks shall be relocated. A bypass fuel system shall be maintained at all times during relocation so that the existing pumps remain operational. The addition to the pumping station shall be constructed prior to modifications to the existing station. The intent of the construction schedule shall be to keep the existing station operational during the construction of the proposed pump(s). Once the new pump(s) are operational, the original station can be taken out of service and all needed modifications made. Upon completion of work on the original station, the existing station addition can be taken out of service for needed modifications. At no time shall the original station and existing station addition be out of service at the same time.

B. Culvert. The connector pile supported, float-in concrete structure will consist of a concrete hull with an integral concrete wingwall superstructure that extends 18.5 feet above the sill deck. The overall dimensions of the float-in structure are 111 feet width by 127 feet length by 26 feet overall height of side, including wingwalls, with a hull depth of 7.5 feet. The wingwalls are 8.0 feet thick and extend 18.5 feet above the sill. When this structure is in position and ballasted, the bottom of the float-in structure will rest beneath the canal bottom at -16.50 NGVD elevation. The sill will be continuous with the canal bottom at -9 NGVD elevation.

After installation of the cutoff/retaining sheet pile walls, walers, and tie rods the area will be excavated to -18 NGVD, with slopes as shown on Plate C-6. Eighteen inches of limestone will be added as a leveling bed prior to the float-in culvert installation, as shown on plate C-7. The float-in culvert has a hull depth of 7.5 feet and a draft of approximately 5.44 feet. The wing walls are 8 feet thick and extend 18.5 feet above the sill which will be approximately +1.5 elevation while being towed to the site.

- 1) Basic Construction. The hull will be constructed with 20 watertight compartments (see Plate C-2). All of the compartments will be accessible from the top of the wingwall structure. Each of the compartments can be emptied of ballast water individually by integrated piping and venting system for the purpose of internal hull inspection. Watertight doors will allow

passage between compartments on grid lines 2 and 12. The hull and wingwalls will have 3 structural levels: the bottom at Level 1, the sill at Level 2, and the wingwall upper deck at Level 3. The ballast manifolds will be located on Level 3.

a) A structural, sanded-mix, semi-lightweight concrete will be used for construction of all of the bottom, top sill, and vertical panels, and columns.

The construction process will begin with the bottom (see Plate C-4). The bottom slab will be cast with a formed perimeter lip or chine. Precast concrete wall panels (see Plate C-5) will be erected on the bottom slab at all exterior wall and interior compartment wall locations. The panels will be spaced apart at their nodal junctions to accept poured-in-place octagonal concrete columns (see Plate C-4). After the columns forms are placed in position, a second layer of concrete will be poured on the bottom slab to bring the bottom to full design thickness, and to bond the wall panels to the hull. The columns will be cast before the bottom has set. Wall panels and columns will be topped with pre-cast concrete wafer panels at levels 2 and 3. The wafers will not butt together tightly but are spaced to allow wall and column reinforcing dowels to pass through the joints. The joints will be filled when a second layer of concrete is poured over the wafer panels to form a finished level. Horizontal diaphragm panels will be provided in wingwalls at Level 2.

Typical concrete design specifications are listed below:

Bottom slab 1st pour – 4-1/2" - 6500 PSI

Bottom slab 2nd pour – 3-1/2" - Semi-lightweight sanded mix - 6500 PSI

Wall panel:

Exterior - 6" - Semi-lightweight sanded mix - 6500 PSI

Interior - 5" - Semi-lightweight sanded mix - 6500 PSI

Sill Wafer - 3" - Semi-lightweight sanded mix - 6500 PSI

Sill top pour - 5" - Semi-lightweight sanded mix - 6500 PSI

Column thickness, varies ~24" - Semi-lightweight sanded mix – 6500 PSI

(b) Reinforcement: The structure will embody an integrated system of bonded reinforcing, bonded pre-tensioning, and bonded post-tensioning which will tie the pre-cast and cast-in-place concrete components into a unified whole. Bonded reinforcement will be provided by standard dowel, column, and spiral matrix components. Bonded pre-tensioning will be provided by embedded seven-wire strand and applied at a design schedule determined for the particular assembly.

Bonded post-tensioning will be provided by seven wire strand tendons encased in conduit. During fabrication of the hull, pipe conduit will be

routed through both the pre-cast panels and through the poured columns and horizontal components to accept post-tensioning cable. The cable will be threaded through the conduit and tensioned to a design schedule determined for the particular assembly. After tensioning, grout will be pumped under pressure into the conduit to bond the matrix permanently. Details and location of reinforcing, pre-stressing, and post-tensioning are shown in Plates C-4 and C-5.

2) Installation. Prior to the installation of the float-in concrete gravity structure, a cutoff/retaining wall with forty 40 feet long steel sheet piles will be driven to -39.0 NGVD, as shown on plate C-8. After the installation of the cutoff/retaining steel sheet pile wall, walers and tie-rods, the area will be excavated to -18 NGVD, with slope as shown on plate C-6. Eighteen inches of limestone will be added as a leveling bed prior to the float-in culvert installation as shown on plate C-7.

After proper alignment positioning the culvert structure will then be ballasted with water, being kept level at all times by manipulation of the pumps and manifolding, so that the floating is uniform.

The culvert will be fully ballasted to a -9.00 feet elevation, allowed to stabilize on the bottom, then sealed in place with 12 feet of tremie concrete between the 24 inch space between the 40 feet sheet pile wall and the wing-wall hull sides. The hull has a 13 inch "lip" at the hull bottom that will provide uplift gravitational reaction to the structure, resulting in a factor of safety against floatation of 1.32 when fully free-flooded under a +11.50 NGVD flood tide in the discharge channel of the Cousins Pump Station.

3) Flood Wall and Culvert Tie-in. The floodwalls are constructed as specified in prior sections. The floodwall culvert tie-in will consist of a vertical concrete abutment column cast integral with the hull wingwall at either side of the structure. The column is grooved vertically with a dovetail sectioned slot containing an embedded sheet pile. The abutting sheet pile of the floodwall will be driven into this slot interlocked with the embedded sheet pile and the joint will be filled with grout (see Plate C-2).

C. Destrehan Bridge Extension. The Destrehan Avenue Bridge lengthening shall be constructed prior to the widening of the Cousins Discharge Channel.

D. Roller Gates. The bottom roller gates shall be constructed concurrently with the Destrehan Avenue Bridge lengthening to minimize closure of Destrehan Avenue.

E. Floodwalls. The closure wall shall be constructed after the installation of the culverts and the construction of the South Floodwall.

ACCESS ROAD

31. General: Vehicular access to the Cousins Pump Station, Destrehan Avenue Bridge, First Avenue Canal, Cousins Canal and Cousins Outfall Canal is possible via Lapalco Blvd. and West Bank Expressway via Destrehan Ave. Also, from Peters Rd. via Lapalco Blvd. Site for the culverts must be accessed by Harvey Canal. The Contractor will be required to comply with all local ordinances regarding hauling over public roads. Additionally, the Contractor will be responsible for maintenance to the roads utilized in the hauling operations.

RELOCATIONS

32. General. Under the authorizing law, local interest are responsible for the accomplishment "...of all necessary alterations and relocations to roads, railroads, pipelines, cables, wharves, drainage structures and other facilities made necessary by the construction work,...". For the area covered in this memorandum, there are no residences required. A summary of the existing utilities requiring relocation is shown in Table 7.

TABLE 7

Utility Relocation Schedule

Station	Item/Description	Disposition
7+43.70 South Wall Line	16 inch H.P. Gas Line	Raise/relocate over floodwall
7+89.37 South Wall Line	16 inch H.P. Gas Line	Raise/relocate over floodwall
6+58 South Wall Line	Electrical Power Lines	Raise/relocate over floodwall

The above list of pipelines will be relocated by the local interests in accordance with criteria set forth for hurricane protection levee and floodwall crossings. These criteria will be furnished to local interests.

ENVIRONMENTAL EFFECTS

33. General.

A. Environmental Assessment. Resources described as significant in the West Bank of the Mississippi River in the Vicinity of New Orleans, LA (East of the Harvey Canal) Feasibility Report and Environmental Impact Statement included bottomland hardwoods; swamps; aquatic resources; wildlife; endangered species; recreation; National Register of Historic Places; hazardous, toxic, and radiological wastes (HTRW); and socio-economic resources. Because of concern for aquatic resources and contaminants that may be released during construction of the sector gate, the top two feet of material that is excavated from the Harvey Canal would be hauled to an industrial landfill. Bottomland hardwoods and wooded swamp would be impacted by construction of the project. The project, as originally designed, would impact 233 acres of bottomland hardwoods and 46 acres of wooded swamp. Changes are currently underway in design of the project on the west side of the proposed sector gate in the Harvey Canal that would result in significant reduction of impacts to wooded lands. Subsequent to the anticipated official approval of the design change, project impacts would change to approximately 69.5 acres of bottomland hardwoods and 46 acres of wooded swamp.

B. Mitigation. The approved habitat mitigation feature I the authorized plan consists of the acquisition of 312 acres of bottomland hardwood forest in the Bayou Piquant finger ridge area of St. Charles Parish. Mitigation would include habitat development to develop the required habitat value and would include operation and maintenance of that area to maintain the required habitat value. Changes are underway to relocate the mitigation area to within the guide levees of the Davis Pond Freshwater Diversion Project area that is currently under construction. The mitigation for the East of Harvey project would be accomplished in the same general area as the mitigation for the Westwego to Harvey Hurricane Protection Project.

C. Hazardous, Toxic, and Radioactive Wastes. An initial assessment for HTRW was completed on 9 August 1994. The assessment concluded that the risk of encountering HTRW sites along the Harvey Canal, Algiers Canal, and Hero canal levee segments is minimal. The 1994 report recommends that upon final selection of an alignment, a meeting should be arranged with appropriate offices of the Louisiana Department of Environmental Quality (LDEQ) to evaluate the selected alignment and construction methods, to insure implementation of a safe project. Current 1998 protocol would first subject the final selected alignment and construction methods, to insure implementation of a safe project. Current 1998 protocol would first subject the final selected alignment to a contract Certified Industrial Hygienist investigation after which the necessity of any additional coordination with LDEQ and other agencies will be determined.

COMPLIANCE WITH ENVIRONMENTAL LAWS

34. General.

- A. National Environmental Policy Act. The final Environmental Impact Statement was filed on 30 September 1994. Proposed project changes reflecting a reduction of project impacts and the relocation of the mitigation area, will be documented in an Environmental Assessment and an expected Finding of No Significant Impact, as well as related documents.
- B. Clean Water Act. A Section 404(b)(1) evaluation was completed on 19 August 1994. Section 401, State Water Quality Certification, was granted by letter, dated 30 August 1994, from the State of Louisiana Department of Environmental Quality.
- C. Coastal Zone Management Act. A letter from the Louisiana Department of Natural Resources, dated 1 August 1994, granted consistency with the State of Louisiana's approved Coastal Resources Program.
- D. National Historic Preservation Act. Cultural resources investigations were completed as part of the feasibility study. The results of the investigations were included in the report entitled West Bank of the Mississippi River in the Vicinity of New Orleans, LA (East of the Harvey Canal) Feasibility Report and Environmental Impact Statement, dated August 1994. Cultural resources investigations for the 312-acre Bayou Bois Piquant mitigation area were completed during 1994 as part of the Davis Pond Freshwater Diversion Project, St. Charles Parish, Louisiana. Cultural resources efforts were coordinated with Louisiana's State Historic Preservation Officer (SHPO). Construction of the project will not impact National Register of Historic Places properties or significant cultural resources and no further cultural resources investigations are warranted. The SHPO has concurred with these recommendations.
- E. Recreation. The land use of the area within the project boundaries is largely urban and industrial. Very little water oriented recreation exists within the project zone of influence. Recreation activities within the area can be categorized as non-consumptive or passive: walking, driving, sightseeing. Pedestrian access to the levee in the vicinity of the Gulf Intracoastal Waterway and Hero Canal is limited due to its isolation from roadways and areas of public access. Minimal recreational sport fishing and boating occur in the GIWW due to the presence of large vessel traffic and more desirable fishing and boating areas in the vicinity.

In the rural environment west of the Harvey Canal, recreational fishing and hunting are popular activities. Hiking, bird watching, camping, and many nature-oriented activities also occur. Contributing to recreational success in the area are three major recreation areas. The Lake Salvador Wildlife Management Area, Jean Lafitte

National Historic Park, and Bayou Segnette State Park provide quality recreation experiences to residents of the area.

COORDINATION WITH OTHER AGENCIES

35. General.

Coordination with other agencies shall be provided by the West Jefferson Levee District.

REAL ESTATE REQUIREMENTS

36. General. Appurtenances follow the existing 1st Avenue Canal and drainage canal. All proposed work falls within the existing right-of-way, and no additional right-of-way will need to be acquired. In the event that right-of-way or construction easements would need to be acquired, the West Jefferson Levee District would acquire said right-of-ways and construction easements without cost to the United States. Right-of-way limits are shown on Plate G-5. Local interest are required to assume cost of relocation assistance to persons and business displaced by such acquisitions pursuant to the requirement of Public Law 91-646. However, no relocations of this type are contemplated for the recommended plan.

OPERATION AND MAINTENANCE

37. General. The Cousins Pumping Station Complex Hurricane Protection will be maintained and operated at the expense of local interests (Jefferson Parish and West Jefferson Levee District) as a feature of local cooperation for the project. The estimate of the annual operation and maintenance costs for the protection features, which are detailed in this Design Memorandum, are as follows:

A. Bottom Roller Floodgate	\$18,000/year
(Involves operating rollergates 4 times/year, spot painting 2 times/year, miscellaneous routine maintenance 4 times/year, and complete repainting of both floodgates every 10 years)	
B. Destrehan Avenue Bridge Extension	\$22,500/year
C. Cousins Pumping Station Addition	\$1,633,000/year
D. Floodwall Maintenance	\$6,000/year
E. Culvert	\$3,780/year

F. Mitigation Feature. Operation and maintenance of the habitat mitigation would consist of maintenance of existing forested wetland habitat, continued development of forested wetland habitat quality goals not achieved in the initial habitat development

period, and protection of the area from any activity not described in the jointly approved habitat development plan. The jointly approved plan would consist of a plan approved by representatives of the Louisiana Department of Wildlife and Fisheries, the U.S. Fish and Wildlife Service, and the U.S. Army Corps of Engineers.

F. Mitigation Feature. Operation and maintenance of the habitat mitigation would consist of maintenance of existing forested wetland habitat, continued development of forested wetland habitat quality goals not achieved in the initial habitat development period, and protection of the area from any activity not described in the jointly approved habitat development plan. The jointly approved plan would consist of a plan approved by representatives of the Louisiana Department of Wildlife and Fisheries, the U.S. Fish and Wildlife Service, and the U.S. Army Corps of Engineers.

SCHEDULE FOR DESIGN AND CONSTRUCTION

38. Schedule for Design and Construction. The sequence of contracts and Schedule for Design and Construction for the recommended plan are shown in Table 8 below.

TABLE 8
Schedule for Design for Construction East of Harvey Hurricane Protection
Project Cousins Pumping Station Complex 2000 cfs

Contracts	Plans & Specs		Advert.	Construction		Const/Cost
	<u>Start</u>	<u>Complete</u>		<u>Award</u>	<u>Complete</u>	
Cousins Pumping Station Contract 1	Jan-99	Jul-00	Nov-00	Feb-01	Feb-03	\$14,214,472
Destrehan Bridge Contract 2	Jan-99	Oct-99	Jan-00	Apr-00	Jan-01	\$1,140,000
Canals & Channels Contract 3	Feb-99	Oct-99	Jan-00	Jul-00	Jul-01	\$3,416,935
Floodwalls Contract 4	Feb-99	Jun-00	Sept-00	Dec-00	Dec-01	\$2,202,924
Culvert Structure Contract 5	Jan-99	Sept-99	Jan-00	Apr-00	Feb-01	\$2,448,732
Closure Wall/Relocation/Floodwall Contract 6	Apr-99	Apr-00	Sept-00	Dec-00	Dec-01	\$5,822,688

ESTIMATE OF INCREMENTAL COSTS

39. General. Based on May 1998 price levels, the estimated first cost for construction of the Cousins Pumping Station Complex Project is \$36,616,000. Of this cost \$14,214,472 is for the modification and renovation of the Cousins Pumping Station, \$1,140,000 is for the modification of the Destrehan Bridge which includes two Bottom Roller Floodgates, \$3,416,935 is for the improvements of the First Avenue canal and Pump Station discharge channel, \$2,202,924 is for floodwalls and frontal protection, \$2,448,732 is for a U-Frame Culvert, \$5,522,688 is for a closure wall on the existing discharge channel, \$300,000 is for relocations, \$350,949.01 is for Construction Engineering and Design, \$3,509,490.10 is for Plans and Specifications, and \$3,509,490.10 is for Construction Administration.

Table 9

Breakdown of Cost Between East of Harvey Project and SELA Projects

Item	Description	Flood Protection	Drainage	2000 CFS
		East of Harvey	SELA	Total Cost
1	Pump Station	\$8,267,256.00	\$5,947,216.00	\$14,214,472.00
2	Destrehan Ave. Bridge	\$1,140,000.00		\$ 1,140,000.00
3	Canals & Channels	\$3,416,935.00		\$ 3,416,935.00
4	Floodwalls	\$2,202,924.00		\$ 2,202,924.00
5	Culvert Structure	\$2,448,732.00		\$ 2,448,732.00
6	Closure Wall	\$5,312,688.00	\$ 210,000.00	\$ 5,522,688.00
7	Relocations	\$ 300,000.00		\$ 300,000.00
	Construction First Cost Total	\$23,088,535.00	\$6,157,216.00	\$29,245,751.00
Project Cost for SELA				
1	Constr. Cost			\$6,157,216.00
2	Const. E&D	\$61,572.16	\$12,314.43	\$ 73,886.60
3	P&S	\$615,721.60	\$123,144.32	\$ 738,865.92
4	Constr. Admin.	\$615,721.60	\$123,144.32	\$ 738,865.92
	Total			\$7,708,834.40
Project Cost for WJLD				
1	Constr. Cost			\$23,088,535.00
2	Const. E&D	\$230,885.35	\$46,177.07	\$277,062.42
3	P&S	\$2,308,853.50	\$461,770.70	\$2,770,624.20
4	Constr. Admin.	\$2,308,853.50	\$461,770.70	\$2,770,624.20
	Total			\$28,906,845.00

Summation of SELA & WJLD's Costs

1	Constr. Cost			\$29,245,751.00
2	Const. E&D	\$292,457.51	\$58,491.50	\$ 350,949.01
3	P&S	\$2,924,575.10	\$584,915.02	\$ 3,509,490.10
4	Constr. Admin.	\$2,924,575.10	\$584,915.02	\$ 3,509,490.10
	Total			\$36,615,680.00
	Total (rounded)			\$36,616,000.00

A detailed cost estimate is shown in Appendix A.


40. Funds Required by Fiscal Year. To maintain the schedule for design and construction for the Cousins Pumping Station Complex of the East of Harvey Hurricane Protection Project as shown in Table 8 above, Federal and Non-Federal funds will be required by Fiscal Year as follows:

TABLE 10
Federal and Non-Federal Funding by Fiscal Year

Funds Required	FY 99/00	\$4,334,457
Funds Required	FY 00/01	\$16,140,611
Funds Required	FY 01/02	\$11,298,428
Funds Required	FY 02/03	\$4,842,184
	TOTAL (rounded)	\$36,616,000

RECOMMENDATIONS

41. Recommendations. The plan of improvement presented herein is the least costly plan that provides the authorized level of protection, uses the minimum acquisition of right-of-way and achieves a high degree of flood protection and pumping capacity, early on, for the developed area of the Harvey Canal. It is recommended that the 2000 CFS Plan be approved as the basis of preparing plans and specifications for this project.




Safety is a Part of Your Contract

PROJECT LOCATION
SCALE: 1" = 3000'




VICINITY MAP
SCALE OF MILES



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
PROJECT LOCATION MAP-VICINITY MAP

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: GAD	CHECKED BY: GAD	DATE:	FILE NO. H-2-44070
--	------------------	--------------------	-------	-----------------------




E: 3680715.03
 N: 500610.92
 59+32.37-184.12' RT.
 BBHC 22 MONUMENT

E: 3680947.42
 N: 500670.98
 61+70.90-210.95' RT.
 BBHC 21 MONUMENT

HARVEY CANAL
 (INTRACOASTAL WATERWAY)


SITE PLAN
 SCALE: 1" = 200'



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
OVERALL SITE PLAN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY:	PLAT SCALE:	FEET DATE:	CARD FILE:
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	1" = 400'	1/99	3003001
DATE:	DRAWN BY:	CHECKED BY:	FILE NO.:
JANUARY 1999	ME	AK	H-2-44870



HARVEY CANAL
(INTRACOASTAL WATERWAY)


EXISTING SITE PLAN
SCALE: 1" = 50'

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
EXISTING SITE PLAN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY:	PROJECT NO.:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	109	3063000
DATE: JANUARY 1998	DRAWN BY:	FILE NO.:
	AD	H-2-44870

MATCH LINE STA. 12+57.68



HARVEY CANAL (INTRACOASTAL WATERWAY)

REQUIRED SITE PLAN

SCALE: 1" = 50'

E: 3680947.42
 N: 500670.88
 61+70.90-210.95' RT.
 BB HC 21 MONUMENT


WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
REQUIRED SITE PLAN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY:	PLANT SCALE:	PLOT DATE:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	1" = 50'	JAN 1998	
DATE:	CHECKED BY:	FILE NO.:	ISSUED:
JAN 1998	AL	H-2-344900	



MATCH LINE STA. 12+57.68



DESCRIPTION	LEGEND	AREA (ACRES)
REQUIRED RIGHT-OF-WAY	---	2.65
REQUIRED PERMANENT SERVITUDE	---	0.26
REQUIRED CONSTRUCTION EASEMENT	---	43.95

RIGHT-OF-WAY PLAN
SCALE: 1" = 50'


HARVEY CANAL
(INTRACOASTAL WATERWAY)


WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
RIGHT-OF-WAY PLAN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: [Signature] DATE: JANUARY 1998
DRAWN BY: [Signature] CHECKED BY: [Signature]
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP

PLAT NO. 3003088
FILE NO. H-2-44870






PUMP STATION PILING PLAN

SCALE: 1/8" = 1'-0"

NOTE:


ALL PILES ARE CLASS B ASTM D25 TREATED TIMBER PILES




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
**COUSINS PUMPING STATION
PILING PLAN**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: AZ	CHECKED BY: AZ	DATE: JANUARY 1999	PLAT SCALE: 1" = 15'	PLAT DATE: 1/99	DWG FILE: 3003-000	FILE NO. H-2-44970
--	-----------------	-------------------	-----------------------	-------------------------	--------------------	-----------------------	-----------------------





SECTION E
SCALE: 1/8" = 1'-0" P-1 P-2



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
COUSINS PUMPING STATION SECTION

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: JANUARY 1995	PLANT SCALE: 1/8" = 1'-0"	DRY DATE: 1/95	CHD NO. 3030-100
FILE NO. 444970				




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
INTAKE BASIN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PROJECT NO.: 1-8	DATE: JANUARY 1990	PLAT DATE: 1-89	CHECKED BY: AL	FILE NO.: H-2-44970
--	---------------------	-----------------------	--------------------	-------------------	------------------------




SECTION A
SCALE: 3/4" = 1'-0"



SECTION B
SCALE: 3/4" = 1'-0"



AREA BETWEEN STRUCTURES AT NOSE OF PROPOSED WINGWALL
SCALE: 3/16" = 1'-0"




MODIFICATIONS TO EXISTING NOSE OF WINGWALL
SCALE: 3/16" = 1'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 1
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
PUMPING STATION WINGWALLS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	PLLOT SCALE: 1/8"	PLLOT DATE: 12/15/00	PLLOT FILE: C:\A-D	GRID FILE: CAL.PLE
DRAWN BY: SAD	CHECKED BY: SJA	FILE NO.:	H-2-44970		



ELEVATION
SOUTH WALL EXIST. SUCTION BASIN
 SCALE: 1/2" = 1'- 0"




SECTION 1
 SCALE: 1/2" = 1'- 0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
PUMPING STATION WINGWALLS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLANT SCALE: DATE:	PLANT DATE: DATE:	GRID FILE: FILE NO. H-2-44970
--	-----------------------	----------------------	-------------------------------------




EAST ELEVATION
SCALE: 1/8" = 1'-0"



NORTH ELEVATION
SCALE: 1/8" = 1'-0"



WEST ELEVATION
SCALE: 1/8" = 1'-0"



SOUTH ELEVATION
SCALE: 1/8" = 1'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 1
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA

2000 CFS BUILDING ELEVATIONS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLANNED BY: SAB	CHECKED BY: J.M.	DATE: 04/97	CHG FILE: H-2-44970	ISSUED BY: H-2-44970
--	--------------------	---------------------	----------------	------------------------	-------------------------



- ① FLOW SWITCH AND NORMALLY CLOSED 120 V.A.C. SOLENOID VALVE REQUIRED IN WATER SUPPLY FOR GEAR REDUCER HEAT EXCHANGER AND PUMP STUFFING BOX.
- ② 3 WAY 120 V.A.C. NORMALLY CLOSED SOLENOID VALVE REQUIRED IN VACUUM BREAKER AIR SYSTEM
- ③ CONTROL PANEL TO HAVE MANUAL OVERRIDE SWITCH TO OPEN 120 V.A.C. SOLENOID VALVE MANUALLY.

PIPING LEGEND


- COMPRESSED AIR - CA**
 CA-S STORAGE
 CA-SA STARTING AIR
 CA-AS AIR SUPPRESSION
 CA-IA INSTRUMENT AIR
 CA-E EXHAUST
 CA-VB VACUUM BREAKER
- WASTE LUBE OIL - WLO**
 WLO-D DISCHARGE
 WLO-S SUCTION
 WLO-C COLLECTION
- DIESEL FUEL - DF**
 DF-R RETURN
 DF-S SUPPLY
- ATMOSPHERIC VENT - AV**
 AV-FO FUEL OIL
 AV-LO LUBE OIL
- ENGINE COOLANT - EC**
 EC-R RETURN
 EC-S SUPPLY
 EC-D DRAIN
- GEAR OIL - GO**
 GO-R RETURN
 GO-S SUPPLY
- BEARING WATER - BW**
 BW-S SUPPLY
 BW-D DRAIN
- VACUUM SYSTEM - VP**
 VP-S SUCTION
 VP-SP SUPPRESSION

* SUPPLIED BY OTHERS UNDER SEPARATE CONTRACT

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 1
 SECTOR GATE COMPLEX - HARVEY CANAL FLOODGATE
 JEFFERSON PARISH, LOUISIANA
MECHANICAL PIPING DIAGRAM

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLAT SCALE: 3/8" = 1'-0"	PLAT DATE: JUN 95	DATE FILED: JUN 95
DRAWN BY: SAB	CHECKED BY: JAA	DATE: JUN 95	FILE NO. H-2-44920





WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 1
COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
MECHANICAL EQUIPMENT LAYOUT

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY:
 WEST JEFFERSON ENGINEERING SERVICES
 - A JOINT VENTURE GROUP -

PLAT SCALE AS SHOWN	PLAT DATE JUN 88	CHNG FILE FILE NO.	CHG FILE DATE
DRAWN BY BAR	CHECKED BY JJA	FILE NO. H-2-44920	






SECTION G
 SCALE: 1/4" = 1'-0" P-2P-9




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
 PUMPING STATION SECTION

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	PLOT SCALE: 1/4" = 1'-0"	PLOT DATE: JANUARY 1993
DRAWN BY: M.S.	CHECKED BY: A.S.	CAD FILE: 908-105
DATE: JANUARY 1993	FILE NO.: H-2-44970	P-2-44970



PLAN
SCALE: 1" = 20'



PROFILE
SCALE: HORIZ. 1" = 20'
VERT. 1" = 4'



SECTION A-A
SCALE: 1/4" = 1'-0"



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
DESTREHAN AVENUE BRIDGE

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: ML	CHECKED BY: AP	DATE: JANUARY 1996	PROJ. NO.: 11-40	PROJ. DATE: 1/96	CADD FILE: 2000-011	FILE NO.: 11-2-44970
--	-----------------	-------------------	-----------------------	---------------------	---------------------	------------------------	-------------------------











TABLE OF ELEVATIONS
LOCATION | ELEVATION

A	3.11
B	2.98
C	2.85
D	2.72
E	2.59

TABLE OF ELEVATIONS
LOCATION | ELEVATION

A	3.11
B	2.98
C	2.85
D	2.72
E	2.59



REMOVE 5'-0" OF ABUTMENT CAP
LEAVE 2'-0" OF HORIZONTAL REBAR
EXPOSED, DRIVE 16" SQUARE P.P.C.
PILE AT 3:12 BATTER, CAST-IN-PLACE
8'-0" CAP MATCHING EXISTING CAP
REBAR AND DIMENSIONS (TYPICAL).

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
DESTREHAN AVENUE BRIDGE
DETAILS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES
DRAWN BY: A JOINT VENTURE GROUP

PLANT SCALE: 1" = 6'


PLOT DATE: 11/19/70

CHECKED BY: ALL

FILE NO.: H-2-45970




PLAN AT TOP OF WALL
 SCALE: 1/2" = 1'-0"




FLOOD SIDE ELEVATION
 SCALE: 1/2" = 1'-0"

SCHEDULE OF ELEVATIONS		
LOCATION	ELEV. A	ELEV. B
NORTH GATE	4.50	2.00
SOUTH GATE	5.00	2.50




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
BOTTOM ROLLER GATE
 U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	FILED SCALE: 1" = 4'	PLAT DATE: 1/20/00	DRAWN BY: M.E.	CHECKED BY: A.L.	DATE: JANUARY 2000	DWG. FILE: 3000001	FILE NO. H-2-44970
--	-------------------------	-----------------------	-------------------	---------------------	-----------------------	-----------------------	-----------------------



GATE MONOLITH PILING PLAN
SCALE: 1/4" = 1'-0"




STORAGE MONOLITH
SCALE: 1" = 1'-0"



GATE MONOLITH
SCALE: 1" = 1'-0"


NOTE:
FOR SCHEDULE OF ELEVATIONS, SEE PLATE NO. R-1.




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
BOTTOM ROLLER GATE
SECTIONS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLANT SCALE: 1" = 3'	PLANT DATE: 1/89	CADD FILE: 0000007
DRAWN BY: ML	CHECKED BY: ML	FILE NO.:	
DATE: JANUARY 1993			11-2-44970






SECTION THRU ROLLER GATE

SCALE: 1 1/2" = 1' - 0"





VERTICAL SEAL
PLAN AT END OF GATE BELOW W

SCALE: 6" = 1' - 0"



TYPICAL SECTION THRU BOTTOM SEAL



SCALE: 12" = 1' - 0"





WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
**BOTTOM ROLLER GATE
SEAL DETAILS**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA



DESIGNED BY:	PLotted SCALE:	PLotted DATE:	PLotted FILE:	PLotted NUMBER:
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	1 - 2	1/80		
	DRAWN BY:	CHECKED BY:	FILE NO.:	
	DATE:	JANUARY 1980		H-2-44970



DETAIL ②
SCALE: 3" = 1' - 0"




DETAIL ③
SCALE: 3" = 1' - 0"



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
**BOTTOM ROLLER GATE
LATCH DETAILS - 1**


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	PLOT SCALE: 1" = 1'	PLOT DATE: 1/98	CADD FILE: 0003-1460
DRAWN BY: M.J.	CHECKED BY: A.L.	FILE NO. H-2-44570	




ELEVATION

DETAIL 1
LATCHING DEVICE
SCALE: 3" = 1' - 0"




SECTION A



PLAN


SECTION AT C/L OF LATCHING DEVICE



PLAN

ELEVATION

LATCHING EYE BOLT W/ EYE HOOK
SCALE: 3" = 1' - 0"



PLAN

ELEVATION

LATCHING HANDLE
SCALE: 3" = 1' - 0"







PLATE WASHER

SCALE: 6" = 1' - 0"



DOUBLE END STUD

SCALE: 12" = 1' - 0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
BOTTOM ROLLER GATE
LATCH DETAILS - 2

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP	PLAT SCALE: AS SHOWN	PLAT DATE: JAN 1996	CHRG. PROJ. NO.:	FILE NO.:
	DRAWN BY: WJ	CHECKED BY: JAL		
	DATE: JANUARY 1996			H-2-44970

ELEVATIONS IN FEET REFER TO N.G.V.D.




ELEVATIONS IN FEET REFER TO N.G.V.D.

NOTE:
 ALL STATIONING REFERS TO
 FRONTAL PROTECTION WALL SECTION.
 SEE PLATE G-4 FOR PLAN VIEW.

STATIONING ALONG FLOOD SIDE OF WALL

**COUSINS PUMP STATION
 FRONTAL PROTECTION PROFILE**


SCALE: HORIZ. 1" = 20'
 VERT. 1" = 5'



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
FRONTAL PROTECTION PROFILE


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY:	DRAWN BY:	CHECKED BY:	DATE:	PLOT SCALE:	PLOT DATE:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES	WEST JEFFERSON ENGINEERING SERVICES	WEST JEFFERSON ENGINEERING SERVICES	JANUARY 1999	1" = 40'	1/99	3008-016
- A JOINT VENTURE GROUP -						FILE NO. H-2-44970



REQUIRED PILE TIP ELEV. = -73.00 N.G.V.D.


72"Ø VERTICAL PUMP
SCALE: 1/4" = 1'-0"





WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
EXISTING COUSINS PUMP STATION
SECTION - 1

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY:	PROJ. NO.:	PLAT. DATE:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	16-2-44970	02	16-2-44970




EXISTING COUSINS PUMPING STATION 
 SCALE: 1/8" = 1'-0"



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
EXISTING COUSINS PUMPING STATION
 SECTION - 2


 U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP	DRAWN BY: M.J.	CHECKED BY: J.P.	DATE: JANUARY 1993	PROJ. NO.: 14-0-4487D	FILE NO.:
--	-------------------	---------------------	-----------------------	--------------------------	-----------




DISCHARGE BASIN SLAB

SCALE: 1/2" = 1'-0"




DISCHARGE TUBE SUPPORT DETAIL

SCALE: 1/2" = 1'-0"




SECTION (D)

SCALE: 1" = 1'-0"




T-WALL PILING PLAN

SCALE: 1/4" = 1'-0"




FACE PLATE DETAIL FOR 72" DISCHARGE PIPE

SCALE: 1/2" = 1'-0"



FACE PLATE DETAIL FOR 36" DISCHARGE PIPE

SCALE: 1/2" = 1'-0"




SECTION (C)

SCALE: 1/2" = 1'-0" F-1/F-4


PROTECTED SIDE

FLOOD SIDE



T-WALL SECTION


SCALE: 1/2" = 1'-0"



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
T-WALL SECTION AND DETAILS
 U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	DRAWN BY: ML	CHECKED BY: AM	DATE: JANUARY 1994	PROJECT NO.: 10-2-4487D	SHEET NO.: F-4
--	-----------------	-------------------	-----------------------	----------------------------	-------------------

NOTE: ALL STATIONING REFERS TO NORTH WALL STATION. SEE PLATE C-4 FOR PLAN VIEW.





NORTH FLOODWALL PROFILE
SCALE: 1" = 20'-0"

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
NORTH FLOODWALL PROFILE
U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	DATE:	DATE:	DATE:	DATE:
DRAWN BY: D.A.P.	CHECKED BY: J.A.R.	FILE NO. H-2-44970	GRID FILE: NORTHWALL		



NOTE: ALL STATIONING REFERS TO SOUTH WALL STATIONS. SEE PLATE G-4 FOR PLAN VIEW.



SOUTH FLOODWALL PROFILE
SCALE: 1" = 20'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA

SOUTH FLOODWALL PROFILE

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	DATE:	DATE:	FILE NO. H-2-44970
--	-------	-------	-------	-----------------------






TYPICAL I-WALL SECTION
SCALE: 1" = 1'-0"

SCHEDULE OF ELEVATIONS

PROPOSED GROUND EL.	EL. "A"	EL. "B"	EL. "C"
EL. 2.00	3.75	0.25	3.00
EL. 4.00	5.75	2.25	5.00




TYPICAL CANTILEVER SHEET PILE WALL
SCALE: 1" = 1'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 1
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
TYP. I-WALL & CANT. SHT. PILE WALL
U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: S.A.A.	CHECKED BY: S.A.A.	DATE:	FILE NO. H-2-44970
--	---------------------	-----------------------	-------	-----------------------




NOTE:
FOR ELEVATIONS,
SEE PROFILE


**FLOOD SIDE ELEVATION
I-WALL TO GATE MONOLITH**
SCALE: 3/4" = 1' - 0"




THREE BULB WATERSTOP
SCALE: 12" = 1' - 0"




I-WALL TO GATE MONOLITH
SCALE: 3" = 1' - 0"



SEAL RETAINING BAR
SCALE: 12" = 1' - 0"



"L" TYPE WATERSTOP
SCALE: 12" = 1' - 0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
TYPICAL WALL JOINT (1 OF 2)


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	PLotted BY: SAB	DATE:	CHECKED BY: SAB	DATE:	DATE FILED: H-2-44970
--	-------	--------------------	-------	--------------------	-------	--------------------------







TYPICAL T-WALL JOINT
SCALE: 3/4" = 1'-0"





SECTION A
SCALE: 3" = 1'-0"



TYPICAL I-WALL JOINT
SCALE: 3/4" = 1'-0"




SECTION B
SCALE: 3" = 1'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
TYPICAL WALL JOINT (2 OF 2)

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY:	PLT SCALE:	PLT DATE:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES	18	10/1/01	WAL2008
- A JOINT VENTURE GROUP -	DRAWN BY:	CHECKED BY:	FILE NO.
	SAJ	SAJ	H-2-44970
	DATE:	DATE:	




ELEVATION
TYPICAL PIPE THRU I-WALL



SECTION A



ELEVATION
TYPICAL GAS PIPE THRU I-WALL




SECTION B



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
FEATURE DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
UTILITY CROSSING DETAILS

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLAT SCALE: DRAWN BY: DATE:	PLAT DATE: CHECKED BY: DATE:	CADD FILE: UTILD/002 FILE NO. H-2-44970
--	-----------------------------------	------------------------------------	---





COUSINS OUTFALL CANAL

HARVEY CANAL
(INTRACOASTAL WATERWAY)

CLOSURE WALL PLAN
SCALE: 1" = 20'


WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS, LOUISIANA			
EAST OF HARVEY CANAL HURRICANE PROTECTION DESIGN MEMORANDUM NO. 3			
COUSINS PUMPING STATION COMPLEX			
CLOSURE WALL PLAN			
U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS CORPS OF ENGINEERS NEW ORLEANS, LOUISIANA			
DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP	PLAT SCALE: DRAWN BY: ME	PLAT DATE: CHECKED BY: AT	ORD. FILE: 3003-021 FILE NO. H-2-44970
DATE: JANUARY 1999			





DIVERSION CHANNEL TYPICAL UTILITY CROSSING
 SCALE: 1" = 5'


CLOSURE WALL SECTION
 SCALE: 1/2" = 1'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
**CLOSURE WALL SECTION
 AND UTILITY CROSSING**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLAT SCALE: 1" = 5'	PLAT DATE: 1/98	CADD FILE: 3003-000
DATE: JANUARY 1998	DRAWN BY: M.L.	CHECKED BY: P.H.	FILE NO. H-2-44970




FIRST AVENUE CANAL
SCALE: 1" = 50'




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
FIRST AVENUE CANAL
PLAN - 1

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PLAT SCALE: 1" = 10'	PROJ. DATA: DATE: JANUARY 1980	FILE NO.: H-2-4467D
--	-------------------------	-----------------------------------	------------------------




FIRST AVENUE CANAL
SCALE: 1" = 50'



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
FIRST AVENUE CANAL
PLAN - 2

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY:	SCALE:	DATE:	FILE NO.
WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	1" = 50'	JANUARY 1999	11-2-4487D



EXISTING RIGHT-OF-WAY

45+00

50+00

MATCH LINE STA. 40+34.60
91' CHANNEL BOTTOM

REQUIRED TOP OF BANK

REQUIRED CHANNEL BOTTOM

EXISTING TOP OF BANK

FIRST AVENUE CANAL

REQUIRED CHANNEL BOTTOM

EXISTING TOP OF BANK

C/L CANAL

EXISTING CANAL BOTTOM

REQUIRED TOP OF BANK
BASELINE C
N15°41'53"W

EXISTING LEVEL

EXISTING RIGHT-OF-WAY

TWO MILE CANAL

FIRST AVENUE CANAL

HARVEY PUMP STATION

FIRST AVENUE CANAL

SCALE: 1" = 50'

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
FIRST AVENUE CANAL
PLAN - 3


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY:	PLAT SCALE:	PLAT DATE:	CAD FILE:	NO. 104
DRAWN BY:	DATE:	CHECKED BY:	FILE NO.:	
DATE:	DATE:	DATE:	DATE:	DATE:

WEST JEFFERSON ENGINEERING SERVICES
- A JOINT VENTURE GROUP -


DATE: JANUARY 1999

FILE NO. H-2-44970




**FIRST AVENUE CANAL
TYPICAL SECTION**

STA. 9+00.00 TO STA. 19+00.00
(SECTION TAKEN AT STA. 9+69.77)
SCALE: 1" = 20'-0"



**FIRST AVENUE CANAL
TYPICAL SECTION**

STA. 20+00.00 TO STA. 51+00.00
(SECTION TAKEN AT STA. 30+00.44)
SCALE: 1" = 20'-0"




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX


**FIRST AVENUE CANAL
TYPICAL SECTION**


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JETTERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PROJECT SCALE: 1" = 40'	PROJECT DATE: 1995	SHEET NO.: 3063-017
DATE: JANUARY 1995	CHECKED BY: [Signature]	FILE NO.:	H-2-44870



LEGEND

REQUIRED DREDGING 




REQUIRED FILL 



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
FIRST AVENUE CANAL
EXISTING SECTION - 1




U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: JANUARY 1990	DRAWN BY: JES	CHECKED BY: JAN	SCALE: 1" = 30'	PART DATE: 1/90	DATE PLOT: 1/90	FILE NO. H-2-44970
--	-----------------------	------------------	--------------------	--------------------	--------------------	--------------------	-----------------------



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMPING STATION COMPLEX
**FIRST AVENUE CANAL
EXISTING SECTION - 2**
U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: JANUARY 1990	PLAT SCALE: 1" = 20'	FILE NO.:H-2-4487	PROJECT DATE: 1989	CADW FILE: 200027
--	-----------------------	-------------------------	-------------------	-----------------------	----------------------







WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA

**DISCHARGE
 CHANNEL CROSS-SECTIONS (1 OF 2)**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: SAB	CHECKED BY: SAB	DATE: DAK	PROJECT NO. H-2-44970	FILE NO. H-2-44970
--	------------------	--------------------	--------------	--------------------------	-----------------------







WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 3
 COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA

**DISCHARGE
 CHANNEL CROSS-SECTIONS (2 OF 2)**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	DATE:	DATE:	DATE:
DRAWN BY: SAB	CHECKED BY: SAB	FILE NO. H-2-44970	CADD FILE: 4498.000	








WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 1
COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
ELECTRICAL SITE PLAN

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

PERRIN & CARTER, INC.
 ENGINEERS, ARCHITECTS, & PLANNERS
 3501 Ridgeland Dr., Metairie, La 70002


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: 4/15/98	PROJECT NO.: 1-107	DATE: 4/15/98	CADD FILE: E-1
		DRAWN BY: [Signature]	CHECKED BY: [Signature]	FILE NO. E-1



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 FEATURE DESIGN MEMORANDUM NO. 1
 COUSINS PUMPING STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
PROPOSED ONE LINE DIAGRAM
 U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

PERRIN & CARTER, INC.
 ENGINEERS, ARCHITECTS, & PLANNERS
 3501 Ridgeway Dr., Metairie, La 70002


DESIGNED BY:	PLT SCALE:	PLT DATE:	CADD FILE:
WEST JEFFERSON ENGINEERING SERVICES	1/2"	4/15/08	E-1
- A JOINT VENTURE GROUP -	DRAWN BY:	CHECKED BY:	FILE NO.
	BT	BT	E-2
	DATE:	4/15/08	




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
**DISCHARGE CHANNEL CULVERT
 GENERAL SITE PLAN**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: 08/28/88	PLAT SCALE: AS SHOWN	PLAT DATE: 01/28/89	CHG# FILE#: 1287-01288
		DRAWN BY: G.L.P.	CHECKED BY: G.L.P.	FILE NO.:
				H-2-44970







NOTE:
 DESIGN ELEV. = +11.5' N.G.V.D.
 CONSTRUCTION ELEV. = +9.5' N.G.V.D.

PLAN OF HULL COMPARTMENTATION

NOTE:
 ALL COMPARTMENTS 10' BAYS. 4" Ø VENT LINES AT TOP AND BOTTOM OF HULL VENTED UP VERTICALLY OUTBOARD OF W-5 PANEL.




ELEVATION OF HULL



SIDE ELEVATION


PANEL SCHEDULE					
PANEL	t	W	H	No.	PANEL
W-1	6"	6'-10"	24'-5"	4	SOLID
W-2	5"	6'-10"	24'-5"	10	SOLID
W-3	6"	9'-10"	24'-5"	20	SOLID
W-4	6"	9'-10"	24'-5"	8	OPEN
W-5	6"	9'-10"	24'-5"	20	OPEN
P-1	6"	9'-10"	6'	20	SOLID
P-2	5"	9'-10"	6'	60	SOLID
P-3	5"	9'-10"	6'	120	OPEN



STEEL SHEETPILE CUT-OFF AND FLOOD WALLS
 NOT TO SCALE

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA
**DISCHARGE CHANNEL CULVERT
 PLAN, ELEVATIONS AND DETAILS**
 U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA


DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -
 DATE: 09/29/98
 CHECKED BY: [Signature]
 DATE: 09/29/98
 PLOT DATE: 09/29/98
 DRAWING NO.: 1387-03040
 FILE NO.: H-2-44872




NOTE:
 DESIGN ELEV. = +11.5' N.G.V.D.
 CONSTRUCTION ELEV. = +9.5' N.G.V.D.

PLAN OF HULL COMPARTMENTATION


NOTE:
 ALL COMPARTMENTS 10' BAYS. 4" Ø VENT LINES AT TOP AND BOTTOM OF HULL VENTED UP VERTICALLY OUTBOARD OF W-5 PANEL.



ELEVATION OF HULL




SIDE ELEVATION




PLAN


PLAN



ELEVATION SECTION A-A CONNECTOR PILE INSTALLATION
 (TYPICAL 24 PLACES)



ELEVATION GROUTING SLEEVE
 (20 REQUIRED)






WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA




**DISCHARGE CHANNEL CULVERT
 CONNECTOR PILE PLAN AND DETAILS**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA




DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE: 08/26/98	PROJECT NO. 107-03-000	FILE NO. 107-03-000
--	-------------------	---------------------------	------------------------




TYPICAL CORNER COL. POUR
NOT TO SCALE



TYPICAL EXTERIOR COL. POUR
NOT TO SCALE



TYPICAL INTERIOR COL. POUR
NOT TO SCALE




- C-1 - #90 COLUMN REINFORCEMENT
- C-2 - #90 DOWEL (BEND 6"x30")
- T-1 - #5 GAUGE SPIRAL @ 12" PITCH
- P-6 - .60" POST TENSIONED TENDONS IN 1 1/4" STD PIPE CONDUIT STAGGERED WITH NUMBERED PANELS


- △: POUR △ 6,500 PSI @ 150 PCF HR
- △: POUR △ 6,500 PSI @ 122 PCF SLWT
- △: POUR △ 6,500 PSI @ 122 PCF SLWT
- △: POUR △ 6,500 PSI @ 150 PCF HR

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS,
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMP STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
**DISCHARGE CHANNEL CULVERT
JOINT DETAILS**


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS,
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	DATE: 08/26/98	CHECKED BY: [Signature]	DATE: 08/26/98	CADD FILE: 1807-0408	FILE NO.:
--	-------------------	----------------------------	-------------------	-------------------------	-----------







INTERIOR BARGE HULL PANEL
SCALE: 3/8" = 1'-0"




EXTERIOR BARGE HULL PANEL
SCALE: 3/8" = 1'-0"




INTERIOR BARGE WING WALL PANEL
SCALE: 3/8" = 1'-0"




EXTERIOR BARGE WING WALL PANEL
SCALE: 3/8" = 1'-0"




INTERIOR BARGE WING WALL PANEL
SCALE: 3/8" = 1'-0"



EXTERIOR BARGE WING WALL PANEL
SCALE: 3/8" = 1'-0"



TYPICAL BARGE PANEL REINFORCING AND PRE-STRESSING
NOT TO SCALE




SECTION AT PANEL TOP
SCALE: 3/32" = 1'-0"

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMP STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
**DISCHARGE CHANNEL CULVERT
PANEL DETAILS**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	DATE: 08/26/98	SCALE: 3/32" = 1'-0"	FIG. NO. / SHEET NO. / SHEET TOTAL: 11-2-44970 / 11-2-44970 / 11-2-44970
--	-------------------	-------------------------	---



295'-0" (LIMITS OF EXCAVATION)

190'-0" (LIMITS OF EXCAVATION)

190'-0" (LIMITS OF EXCAVATION)

CULVERT

DISCHARGE CHANNEL

3:1 SLOPE

3:1 SLOPE

10:1 SLOPE

10:1 SLOPE


3:1 SLOPE

3:1 SLOPE


FOUNDATION MAT
EL. (-)18.0' N.G.V.D.
WITH 2.0 FT CRUSHED
LIMESTONE TO
EL. (-)16.0' N.G.V.D.

295'-0" (LIMITS OF EXCAVATION)

DREDGING PLAN AND RIGHT-OF-WAY





NATURAL CHANNEL
EL. (-)10.0' N.G.V.D.
WITH 1.0 FT RIP-RAFF
TO EL. (-)9.0' N.G.V.D.



WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMP STATION COMPLEX
JEFFERSON PARISH, LOUISIANA
DISCHARGE CHANNEL CULVERT
DREDGING PLAN AND RIGHT-OF-WAY


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES A JOINT VENTURE GROUP	PROJECT NO. 08/26/98	DATE	FILE NO. 1-2-44920
--	-------------------------	------	-----------------------



DREDGING PROFILES

VOLUME OF MATERIAL:	
CRUSHED LIMESTONE:	+/-1,750 Tons
RIP-RAP:	+/-5,950 Tons
TOTAL:	+/-7,700 Tons




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA

**DISCHARGE CHANNEL CULVERT
 DREDGING PROFILES**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY:	WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DATE:	05/26/99
CHECKED BY:		DATE:	
FILE NO.:	11-2-44570		




CROSS-SECTION AT LAPALCO BRIDGE




WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
 EAST OF HARVEY CANAL HURRICANE PROTECTION
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION COMPLEX
 JEFFERSON PARISH, LOUISIANA

**DISCHARGE CHANNEL CULVERT
 CROSS-SECTION AT LAPALCO BRIDGE**


U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
 CORPS OF ENGINEERS
 NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	DRAWN BY: Jade	CHECKED BY: Jade	DATE: 05/26/98	FILE NO. H-2-41970
--	-------------------	---------------------	-------------------	-----------------------





DETAIL 1
NOT TO SCALE




SECTION A-A
NOT TO SCALE

WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF NEW ORLEANS
EAST OF HARVEY CANAL HURRICANE PROTECTION
DESIGN MEMORANDUM NO. 3
COUSINS PUMP STATION COMPLEX
JEFFERSON PARISH, LOUISIANA

**DISCHARGE CHANNEL CULVERT
CUT-OFF/RETAINING WALL AND DETAIL**

U.S. ARMY ENGINEER DISTRICT, NEW ORLEANS
CORPS OF ENGINEERS
NEW ORLEANS, LOUISIANA

DESIGNED BY: WEST JEFFERSON ENGINEERING SERVICES - A JOINT VENTURE GROUP -	PROJECT NO. V-27-93-01	DATE 01/26/90	PROJECT DATE 08/08/89	DRAWN BY S.E.P.	CHECKED BY S.E.P.	SCALE AS SHOWN	FILE NO. H-2-44870
--	---------------------------	------------------	--------------------------	--------------------	----------------------	-------------------	-----------------------



CUT-OFF / RETAINING WALL

2" TIE-BACK RODS
@ 12'-0" O.C.

TEMPORARY EXCAVATION WALL
40 FT. LG. STEEL SHEETPILE

PERMANENT SHEETPILE
CUT-OFF WALL

SEE DETAIL 1
THIS SHEET

EL. (+)5.0' N.G.V.D.

CONCRETE BRIDGE
FOUNDATION

2" TIE-BACK RODS
@ 12.0' O.C.

C12x25
WALER BEAM

MC 18
EL. (+)7.0' N.G.V.D.
TOP OF PILE

EL. (+)6.00' N.G.V.D.

1" HEX BOLT w/
O.G. WASHER (TYP.)

PLZ-23 STEEL
SHEETPILE

2" TIE-BACK RODS
@ 12'-0" O.C.

C12x25
WALER BEAM

1" HEX BOLT w/
O.G. WASHER (TYP.)

PLZ-23 STEEL
SHEETPILE

300' TIMBER
GUIDE WALL

HARVEY CANAL

SECTION A-A

DISCHARGE
CHANNEL /
CULVERT

LAPALCO BLVD.

40'-0"

48'-6"

APPENDIX A
DETAILED ESTIMATE OF
INCREMENTAL COST

**WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
NEW ORLEANS, LOUISIANA
EAST OF HARVEY HURRICANE PROTECTION PROJECT
DESIGN MEMORANDUM NO. 3
COUSINS PUMP STATION
DETAILED ESTIMATE OF FIRST COST
(MAY 1998 PRICE LEVELS)
1000 CFS**

Item	Description	Total	Contingency	Project Cost
1	Pump Station	\$ 7,210,130.00	\$ 1,057,126.00	\$ 8,267,256.00
2	Destrahan Ave. Bridge	\$ 950,000.00	\$ 190,000.00	\$ 1,140,000.00
3	Canals & Channels	\$ 2,847,446.00	\$ 569,489.00	\$ 3,416,935.00
4	Floodwalls	\$ 1,835,770.00	\$ 367,154.00	\$ 2,202,924.00
5	Culvert Structure	\$ 2,020,960.00	\$ 427,772.00	\$ 2,448,732.00
6	Closure Wall	\$ 4,427,240.00	\$ 885,448.00	\$ 5,312,688.00
7	Relocations	\$ 250,000.00	\$ 50,000.00	\$ 300,000.00
	Construction First Cost Total	\$ 19,541,546.00	\$ 3,546,989.00	\$ 23,088,535.00
 PROJECT COST				
1	Construction Cost	\$ 19,541,546.00	\$ 3,546,989.00	\$ 23,088,535.00
2	Constr. Engineering and Design	\$ 230,885.35	\$ 46,177.07	\$ 277,062.42
3	Plans and Specifications	\$ 2,308,853.50	\$ 461,770.70	\$ 2,770,624.20
4	Construction Administration	\$ 2,308,853.50	\$ 461,770.70	\$ 2,770,624.20
	Total	\$ 24,390,138.35	\$ 4,516,707.47	\$ 28,906,845.82
	Total (rounded)			\$ 28,907,000.00

**DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX
1,000 CFS**

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
1	Pump Station (1000 CFS)						
1.1	Mobilization & Demobilization						
1.1.1	Mob/demob (for pump station)	LS	LS	\$ 200,000.00	\$ 200,000	\$ 40,000	\$ 240,000
1.2	Earthwork for Structure						
1.2.1	Structure Excavation	20,000	cy	\$ 10.00	\$ 200,000	\$ 50,000	\$ 250,000
1.2.2	Cofferdam	LS	LS	\$ 700,000.00	\$ 700,000	\$ 140,000	\$ 840,000
1.3	Pumping Station Structure						
1.3.1	Structural Concrete	3,400	cy	\$ 375.00	\$ 1,275,000	\$ 255,000	\$ 1,530,000
1.3.2	Concrete Discharge Tube	450	cy	\$ 600.00	\$ 270,000	\$ 54,000	\$ 324,000
1.3.3	Timber Piles	35,500	lf	\$ 10.00	\$ 355,000	\$ 71,000	\$ 426,000
1.3.4	Pile Test	LS	LS	\$ 36,000.00	\$ 36,000	\$ 7,200	\$ 43,200
1.3.5	Building (including Office & Bathroom)	3,150	sf	\$ 40.00	\$ 126,000	\$ 25,200	\$ 151,200
1.4	Pumping Station Mechanical						
1.4.1	1000 cfs Horizontal Pump	1	ea	\$ 891,000.00	\$ 891,000	\$ -	\$ 891,000
1.4.2	Horizontal Reduction Gear	1	ea	\$ 283,500.00	\$ 283,500	\$ -	\$ 283,500
1.4.3	3,400 h.p. Diesel Engine	1	ea	\$ 747,000.00	\$ 747,000	\$ -	\$ 747,000
1.4.4	Engine Cooling System	1	ea	\$ 120,000.00	\$ 120,000	\$ 24,000	\$ 144,000
1.4.5	Vacuum Pump System	LS	LS	\$ 110,000.00	\$ 110,000	\$ 22,000	\$ 132,000
1.4.6	Air System	LS	LS	\$ 35,000.00	\$ 35,000	\$ 7,000	\$ 42,000
1.4.7	Fuel Oil System	LS	LS	\$ 70,000.00	\$ 70,000	\$ 14,000	\$ 84,000
1.4.8	Crane	2	ea	\$ 90,000.00	\$ 180,000	\$ 36,000	\$ 216,000
1.4.9	Mechanical Trash Rakes	1	ea	\$ 450,000.00	\$ 450,000	\$ 90,000	\$ 540,000
1.4.10	Mechanical Installation	LS	LS	\$ 425,000.00	\$ 425,000	\$ 85,000	\$ 510,000
1.4.11	Waste Oil System	LS	LS	\$ 13,000.00	\$ 13,000	\$ 2,600	\$ 15,600
1.4.12	Potable Water System	LS	LS	\$ 4,000.00	\$ 4,000	\$ 800	\$ 4,800
1.4.13	Ventillation System	LS	LS	\$ 18,000.00	\$ 18,000	\$ 3,600	\$ 21,600
1.4.14	Electrical	LS	LS	\$ 300,000.00	\$ 300,000	\$ 60,000	\$ 360,000
1.4.15	Controls	LS	LS	\$ 38,000.00	\$ 38,000	\$ -	\$ 38,000
1.4.16	Services of Erecting Engineer	20	Day	\$ 1,200.00	\$ 24,000	\$ -	\$ 24,000
1.4.17	Field Services	6	Day	\$ 1,200.00	\$ 7,200	\$ -	\$ 7,200
1.5	Intake Modifications						
1.5.1	Excavation	2,500	cy	\$ 6.75	\$ 16,875	\$ 4,219	\$ 21,094
1.5.2	Steel Sheet Piling	14,373	sf	\$ 15.00	\$ 215,595	\$ 43,119	\$ 258,714
1.5.3	Coating	6,020	sf	\$ 2.00	\$ 12,040	\$ 2,408	\$ 14,448
1.5.4	Concrete Cap (Including Reinforcing)	50	cy	\$ 300.00	\$ 15,000	\$ 3,000	\$ 18,000
1.5.5	Tie-Back System	LS	LS	\$ 25,000.00	\$ 25,000	\$ 5,000	\$ 30,000
1.5.6	Sand Back Fill	735	cy	\$ 12.00	\$ 8,820	\$ 2,205	\$ 11,025
1.5.7	Rip Rap	1,700	ton	\$ 23.00	\$ 39,100	\$ 9,775	\$ 48,875
	Sub-total Pump Station				\$ 7,210,130	\$ 1,057,126	\$ 8,267,256

**DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX
1,000 CFS**

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
2	DESTRAHAN AVENUE BRIDGE						
2.1	Destrahan Ave. Bridge Extension (Includes Structural Excavation and Backfill, Prestressed Concrete Piles, Class A and Class AA Concrete, Type III Prestressed Girders, and Misc. Items)						
2.1.1	Destrahan Ave. Bridge Extension	1	LS	\$ 250,000.00	\$250,000	\$50,000	\$300,000
2.2	Bottom Roller Floodgates (Includes Structural Steel, Concrete, Steel Sheet Piling, Prestressed Concrete Piles, Timber Piles, and Misc. Items, Gate Monolith and Storage Monolith)						
2.2.1	40' Wide Opening	2	EA	\$ 350,000.00	\$700,000	\$140,000	\$840,000
	Sub-total Destrahan Ave. Bridge				\$ 950,000	\$ 190,000	\$ 1,140,000
3	CANALS AND CHANNELS						
3.1	First Ave. Canal Widening						
3.1.1	Excavation	310000	CY	\$ 6.75	\$2,092,500	\$418,500	\$2,511,000
3.2	Discharge Channel Modifications						
3.2.1	Excavation	47,826	cy	\$ 6.75	\$ 322,826	\$ 64,565	\$ 387,391
3.2.2	Compacted Fill	912	cy	\$ 12.00	\$ 10,944	\$ 2,189	\$ 13,133
3.2.3	Rip Rap	18,312	ton	\$ 23.00	\$ 421,176	\$ 84,235	\$ 505,411
	Sub-total Canals				\$2,847,446	\$569,489	\$3,416,935
4	FLOODWALLS						
4.1	I-Type Floodwalls (Includes Steel Sheet Piling, Concrete Cap and Misc. Items)						
4.1.1	6' High Above Ground	336	lf	\$ 400.00	\$ 134,400	\$ 26,880	\$ 161,280
4.1.2	8' High Above Ground	750	lf	\$ 600.00	\$ 450,000	\$ 90,000	\$ 540,000
4.2	Frontal Protection T-Wall (Includes Structural Excavation and Backfill, Steel Sheet Piling, Prestressed Concrete Piles, Concrete, and Misc. Items)						
4.2.1	22.5' High Above Ground	355	LF	\$ 2,500.00	\$887,500	\$177,500	\$1,065,000
4.2.1	Discharge Basin Slab (Includes Structural Excavaton, Concrete, Timber Piles & Misc. Items)	4160	SF	\$ 45.00	\$187,200	\$37,440	\$224,640
4.3	Cantilevered Sheet Pile Wall						
4.3.1	Steel Sheet Piling	10,330	sf	\$ 15.00	\$ 154,950	\$ 30,990	\$ 185,940
4.3.2	Concrete Cap (Including Reinforcing)	28	cy	\$ 300.00	\$ 8,400	\$ 1,680	\$ 10,080
4.3.3	Coating	6,660	sf	\$ 2.00	\$ 13,320	\$ 2,664	\$ 15,984
	Sub-total Floodwalls				\$1,835,770	\$367,154	\$2,202,924

**DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX
1,000 CFS**

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
5	CULVERT STRUCTURE						
5.1	Mobilization & demobilization						
5.1.1	Mob/demob (for culvert structure)	LS	LS	\$ 25,000.00	\$ 25,000	\$ 5,000	\$ 30,000
5.2	Earth work for structures						
5.2.1	Structure excavation	3,600	cy	\$ 6.75	\$ 24,300	\$ 4,860	\$ 29,160
5.2.2	Geotextile	1,700	sy	\$ 4.50	\$ 7,650	\$ 1,530	\$ 9,180
5.2.3	Leveling bed	1,350	tons	\$ 25.00	\$ 33,750	\$ 6,750	\$ 40,500
5.3	Approach channels						
5.3.1	Excavation	3,200	cy	\$ 6.75	\$ 21,600	\$ 4,320	\$ 25,920
5.3.2	Geotextile	2,600	sy	\$ 4.50	\$ 11,700	\$ 2,340	\$ 14,040
5.3.3	Bedding	900	cy	\$ 28.00	\$ 25,200	\$ 5,040	\$ 30,240
5.3.4	Riprap	7,800	ton	\$ 23.00	\$ 179,400	\$ 35,880	\$ 215,280
5.4	Concrete gravity structure						
5.4.1	Semi-lightweight concrete	600	cy	\$ 375.00	\$ 225,000	\$ 45,000	\$ 270,000
5.4.2	Hardrock concrete	660	cy	\$ 250.00	\$ 165,000	\$ 33,000	\$ 198,000
5.4.3	Post-tensioning system	80,000	lf	\$ 1.50	\$ 120,000	\$ 24,000	\$ 144,000
5.4.4	Reinforcing	168,000	lb	\$ 0.45	\$ 75,600	\$ 15,120	\$ 90,720
5.4.5	6" & 5" Panel PS/PC	450	cy	\$ 300.00	\$ 135,000	\$ 27,000	\$ 162,000
5.4.6	30" Connector Pile Sleeves	365	lf	\$ 120.00	\$ 43,800	\$ 8,760	\$ 52,560
5.4.7	Installation	LS	LS	\$ 75,000.00	\$ 75,000	\$ 15,000	\$ 90,000
5.5	Foundation work						
5.5.1	24" Connector Piles	2,160	lf	\$ 210.00	\$ 453,600	\$ 113,400	\$ 567,000
5.5.2	Concrete Cap	120	cy	\$ 150.00	\$ 18,000	\$ 4,500	\$ 22,500
5.5.3	Sheet pile cut-off wall (Retaining wall)	8,400	sf	\$ 15.00	\$ 126,000	\$ 25,200	\$ 151,200
5.5.4	Fabricated channel cap	210	lf	\$ 20.00	\$ 4,200	\$ 840	\$ 5,040
5.5.5	High density mix	950	cy	\$ 50.00	\$ 47,500	\$ 9,500	\$ 57,000
5.5.6	Pile testing	LS	LS	\$ 40,000.00	\$ 40,000	\$ 8,000	\$ 48,000
5.6	Tie-Back/Retaining Wall						
5.6.1	Sheet piles	6,000	sf	\$ 8.50	\$ 51,000	\$ 10,200	\$ 61,200
5.6.2	Walers	840	lf	\$ 24.00	\$ 20,160	\$ 4,032	\$ 24,192
5.6.3	Miscellaneous hardware	LS	LS	\$ 5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.7	Special construction						
5.7.1	Instrumentation	LS	LS	\$ 5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.8	Mechanical system						
5.8.1	Piping and manifolds	LS	LS	\$ 35,000.00	\$ 35,000	\$ 7,000	\$ 42,000
5.8.2	Pumps	LS	LS	\$ 30,000.00	\$ 30,000	\$ 6,000	\$ 36,000
5.9	Power and lighting system						
5.9.1	Electrical services/work	LS	LS	\$ 5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.9.2	Other electrical work	LS	LS	\$ 10,000.00	\$ 10,000	\$ 2,000	\$ 12,000
5.10	Associated general items						
5.10.1	Tile gages	LS	LS	\$ 2,500.00	\$ 2,500	\$ 500	\$ 3,000
	Sub-total Culvert				\$ 2,020,960	\$ 427,772	\$ 2,448,732

**DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX
1,000 CFS**

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
6	CLOSURE WALL						
6.1.1	Steel Sheet Piling	16416	SF	\$ 15.00	\$246,240	\$49,248	\$295,488
6.1.2	66" Diameter Prestressed Concrete Cylinder Piles	14900	LF	\$ 250.00	\$3,725,000	\$745,000	\$4,470,000
6.1.3	Concrete Cap (Includes Reinforcing)	1216	CY	\$ 375.00	\$456,000	\$91,200	\$547,200
	Sub-total Closure Wall				\$4,427,240	\$885,448	\$5,312,688
7	RELOCATION						
7.1	16" High Pressure Gas Line	2	LS	\$ 75,000.00	\$ 150,000	\$30,000	\$180,000
7.1.2	Electrical Power Lines	1	LS	\$ 100,000.00	\$ 100,000	\$20,000	\$120,000
	Sub-total Relocation				\$ 250,000	\$ 50,000	\$ 300,000
	Construction Cost Total				\$ 19,541,546	\$ 3,546,989	\$ 23,088,534

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
	PROJECT COST						
1	Construction Cost				\$ 19,541,546	\$ 3,546,989	\$ 23,088,534
2	Constr. Engineering and design				\$ 230,885	\$ 46,177	\$ 277,062
3	Plans and specifications				\$ 2,308,853	\$ 461,771	\$ 2,770,624
4	Construction administration				\$ 2,308,853	\$ 461,771	\$ 2,770,624
	Total				\$ 24,390,138	\$ 4,516,707	\$ 28,906,845
	TOTAL (rounded)						\$ 28,907,000

**WEST BANK OF THE MISSISSIPPI RIVER IN THE VICINITY OF
 NEW ORLEANS, LOUISIANA
 EAST OF HARVEY HURRICANE PROTECTION PROJECT
 DESIGN MEMORANDUM NO. 3
 COUSINS PUMP STATION
 DETAILED ESTIMATE OF FIRST COST
 (MAY 1998 PRICE LEVELS)
 2000 CFS**

Item	Description	Total	Contingency	Project Cost
1	Pump Station	\$ 12,488,785.00	\$ 1,725,687.00	\$ 14,214,472.00
2	Destrahan Ave. Bridge	\$ 950,000.00	\$ 190,000.00	\$ 1,140,000.00
3	Canals & Channels	\$ 2,847,446.00	\$ 569,489.00	\$ 3,416,935.00
4	Floodwalls	\$ 1,835,770.00	\$ 367,154.00	\$ 2,202,924.00
5	Culvert Structure	\$ 2,020,960.00	\$ 427,772.00	\$ 2,448,732.00
6	Closure Wall	\$ 4,602,240.00	\$ 920,448.00	\$ 5,522,688.00
7	Relocations	\$ 250,000.00	\$ 50,000.00	\$ 300,000.00
	Construction First Cost Total	\$ 24,995,201.00	\$ 4,250,550.00	\$ 29,245,751.00

PROJECT COST

1	Construction Cost	\$ 24,995,201.00	\$ 4,250,550.00	\$ 29,245,751.00
2	Constr. Engineering and Design	\$ 292,457.51	\$ 58,491.50	\$ 350,949.01
3	Plans and Specifications	\$ 2,924,575.10	\$ 584,915.02	\$ 3,509,490.12
4	Construction Administration	\$ 2,924,575.10	\$ 584,915.02	\$ 3,509,490.12
	Total	\$ 31,136,808.71	\$ 5,478,871.54	\$ 36,615,680.25

Total (rounded) **\$36,616,000.00**

DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX

2,000 CFS

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
1	Pump Station (2000 CFS)						
1.1	Mobilization & Demobilization						
1.1.1	Mob/demob (for pump station)	LS	LS	250,000.00	\$ 250,000	\$ 50,000	\$ 300,000
1.2	Earthwork for Structure						
1.2.1	Structure Excavation	33,333	cy	10.00	\$ 333,330	\$ 83,333	\$ 416,663
1.2.2	Cofferdam	LS	LS	891,000.00	\$ 891,000	\$ 178,200	\$ 1,069,200
1.3	Pumping Station Structure						
1.3.1	Structural Concrete	5,650	cy	375.00	\$ 2,118,750	\$ 423,750	\$ 2,542,500
1.3.2	Concrete Discharge Tube	900	cy	600.00	\$ 540,000	\$ 108,000	\$ 648,000
1.3.3	Timber Piles	57,680	lf	10.00	\$ 576,800	\$ 115,360	\$ 692,160
1.3.4	Pile Test	LS	LS	36,000.00	\$ 36,000	\$ 7,200	\$ 43,200
1.3.5	Building (including Office & Bathroom)	5,050	sf	40.00	\$ 202,000	\$ 40,400	\$ 242,400
1.4	Pumping Station Mechanical						
1.4.1	1000 cfs Horizontal Pump	2	ea	891,000.00	\$ 1,782,000	\$ -	\$ 1,782,000
1.4.2	Horizontal Reduction Gear	2	ea	283,500.00	\$ 567,000	\$ -	\$ 567,000
1.4.3	3400 h.p. Diesel Engine	2	ea	747,000.00	\$ 1,494,000	\$ -	\$ 1,494,000
1.4.4	Engine Cooling System	2	ea	120,000.00	\$ 240,000	\$ 48,000	\$ 288,000
1.4.5	Vacuum Pump System	LS	LS	130,000.00	\$ 130,000	\$ 26,000	\$ 156,000
1.4.6	Air System	LS	LS	45,000.00	\$ 45,000	\$ 9,000	\$ 54,000
1.4.7	Fuel Oil System	LS	LS	90,000.00	\$ 90,000	\$ 18,000	\$ 108,000
1.4.8	Crane	2	ea	105,000.00	\$ 210,000	\$ 42,000	\$ 252,000
1.4.9	Mechanical Trash Rakes	3	ea	375,000.00	\$ 1,125,000	\$ 225,000	\$ 1,350,000
1.4.10	Mechanical Installation	2	ea	425,000.00	\$ 850,000	\$ 170,000	\$ 1,020,000
1.4.11	Waste Oil System	LS	LS	15,000.00	\$ 15,000	\$ 3,000	\$ 18,000
1.4.12	Potable Water System	LS	LS	5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
1.4.13	Ventillation System	2	ea	18,000.00	\$ 36,000	\$ 7,200	\$ 43,200
1.4.14	Relocate Water Well	LS	LS	95,000.00	\$ 95,000	\$ 19,000	\$ 114,000
1.4.15	Electrical	LS	LS	375,000.00	\$ 375,000	\$ 75,000	\$ 450,000
1.4.16	Controls	LS	LS	76,000.00	\$ 76,000	\$ -	\$ 76,000
1.4.17	Services of Erecting Engineer	32	Day	1,200.00	\$ 37,800	\$ -	\$ 37,800
1.4.18	Field Services	8	Day	1,200.00	\$ 9,600	\$ -	\$ 9,600
1.5	Intake Modifications						
1.5.1	Excavation	5,000	cy	6.75	\$ 33,750	\$ 8,438	\$ 42,188
1.5.2	Steel Sheet Piling	14,373	sf	15.00	\$ 215,595	\$ 43,119	\$ 258,714
1.5.3	Coating	6,020	sf	2.00	\$ 12,040	\$ 2,408	\$ 14,448
1.5.4	Concrete Cap (Including Reinforcing)	50	cy	300.00	\$ 15,000	\$ 3,000	\$ 18,000
1.5.5	Tie-Back System	LS	LS	25,000.00	\$ 25,000	\$ 5,000	\$ 30,000
1.5.6	Sand Back Fill	735	cy	12.00	\$ 8,820	\$ 2,205	\$ 11,025
1.5.7	Rip Rap	2,100	ton	23.00	\$ 48,300	\$ 12,075	\$ 60,375
	Sub-total Pump Station				\$ 12,488,785	\$ 1,725,687	\$ 14,214,472

DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX

2,000 CFS

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
2	DESTRAHAN AVENUE BRIDGE						
2.1	Destrahan Ave. Bridge Extension (Includes Structural Excavation and Backfill, Prestressed Concrete Piles, Class A and Class AA Concrete, Type III Prestressed Girders, and Misc. Items)						
2.1.1	Destrahan Ave. Bridge Extension	1	LS	250,000.00	\$250,000	\$50,000	\$300,000
2.2	Bottom Roller Floodgates (Includes Structural Steel, Concrete, Steel Sheet Piling, Prestressed Concrete Piles, Timber Piles, and Misc. Items, Gate Monolith and Storage Monolith)						
2.2.1	40' Wide Opening	2	EA	350,000.00	\$700,000	\$140,000	\$840,000
	Sub-total Destrahan Ave. Bridge				\$ 950,000	\$ 190,000	\$ 1,140,000
3	CANALS AND CHANNELS						
3.1	First Ave. Canal Widening						
3.1.1	Excavation	310000	CY	6.75	\$2,092,500	\$418,500	\$2,511,000
3.2	Discharge Channel Modifications						
3.2.1	Excavation	47,826	cy	6.75	\$ 322,826	\$ 64,565	\$ 387,391
3.2.2	Compacted Fill	912	cy	12.00	\$ 10,944	\$ 2,189	\$ 13,133
3.2.3	Rip Rap	18,312	ton	23.00	\$ 421,176	\$ 84,235	\$ 505,411
	Sub-total Canals				\$2,847,446	\$569,489	\$3,416,935
4	FLOODWALLS						
4.1	I-Type Floodwalls (Includes Steel Sheet Piling, Concrete Cap and Misc. Items)						
4.1.1	6' High Above Ground	336	lf	400.00	\$ 134,400	\$ 26,880	\$ 161,280
4.1.2	8' High Above Ground	750	lf	600.00	\$ 450,000	\$ 90,000	\$ 540,000
4.2	Frontal Protection T-Wall (Includes Structural Excavation and Backfill, Steel Sheet Piling, Prestressed Concrete Piles, Concrete, and Misc. Items)						
4.2.1	22.5' High Above Ground	355	LF	2,500.00	\$887,500	\$177,500	\$1,065,000
4.2.1	Discharge Basin Slab (Includes Structural Excavaton, Concrete, Timber Piles & Misc. Items)	4160	SF	45.00	\$187,200	\$37,440	\$224,640
4.3	Cantilevered Sheet Pile Wall						
4.3.1	Steel Sheet Piling	10,330	sf	15.00	\$ 154,950	\$ 30,990	\$ 185,940

**DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX**

2,000 CFS

Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
4.3.2	Concrete Cap (Including Reinforcing)	28	cy	300.00	\$ 8,400	\$ 1,680	\$ 10,080
4.3.3	Coating	6,660	sf	2.00	\$ 13,320	\$ 2,664	\$ 15,984
Sub-total Floodwalls					\$1,835,770	\$367,154	\$2,202,924
5	CULVERT STRUCTURE						
5.1	Mobilization & demobilization						
5.1.1	Mob/demob (for culvert structure)	LS	LS	25,000.00	\$ 25,000	\$ 5,000	\$ 30,000
5.2	Earth work for structures						
5.2.1	Structure excavation	3,600	cy	6.75	\$ 24,300	\$ 4,860	\$ 29,160
5.2.2	Geotextile	1,700	sy	4.50	\$ 7,650	\$ 1,530	\$ 9,180
5.2.3	Leveling bed	1,350	tons	25.00	\$ 33,750	\$ 6,750	\$ 40,500
5.3	Approach channels						
5.3.1	Excavation	3,200	cy	6.75	\$ 21,600	\$ 4,320	\$ 25,920
5.3.2	Geotextile	2,600	sy	4.50	\$ 11,700	\$ 2,340	\$ 14,040
5.3.3	Bedding	900	cy	28.00	\$ 25,200	\$ 5,040	\$ 30,240
5.3.4	Riprap	7,800	ton	23.00	\$ 179,400	\$ 35,880	\$ 215,280
5.4	Concrete gravity structure						
5.4.1	Semi-lightweight concrete	600	cy	375.00	\$ 225,000	\$ 45,000	\$ 270,000
5.4.2	Hardrock concrete	660	cy	250.00	\$ 165,000	\$ 33,000	\$ 198,000
5.4.3	Post-tensioning system	80,000	lf	1.50	\$ 120,000	\$ 24,000	\$ 144,000
5.4.4	Reinforcing	168,000	lb	0.45	\$ 75,600	\$ 15,120	\$ 90,720
5.4.5	6" & 5" Panel PS/PC	450	cy	300.00	\$ 135,000	\$ 27,000	\$ 162,000
5.4.6	30" Connector Pile Sleeves	365	lf	120.00	\$ 43,800	\$ 8,760	\$ 52,560
5.4.7	Installation	LS	LS	75,000.00	\$ 75,000	\$ 15,000	\$ 90,000
5.5	Foundation work						
5.5.1	24" Connector Piles	2,160	lf	210.00	\$ 453,600	\$ 113,400	\$ 567,000
5.5.2	Concrete Cap	120	cy	150.00	\$ 18,000	\$ 4,500	\$ 22,500
5.5.3	Sheet pile cut-off wall (Retaining wall)	8,400	sf	15.00	\$ 126,000	\$ 25,200	\$ 151,200
5.5.4	Fabricated channel cap	210	lf	20.00	\$ 4,200	\$ 840	\$ 5,040
5.5.5	High density mix	950	cy	50.00	\$ 47,500	\$ 9,500	\$ 57,000
5.5.6	Pile testing	LS	LS	40,000.00	\$ 40,000	\$ 8,000	\$ 48,000
5.6	Tie-Back/Retaining Wall						
5.6.1	Sheet piles	6,000	sf	8.50	\$ 51,000	\$ 10,200	\$ 61,200
5.6.2	Walers	840	lf	24.00	\$ 20,160	\$ 4,032	\$ 24,192
5.6.3	Miscellaneous hardware	LS	LS	5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.7	Special construction						
5.7.1	Instrumentation	LS	LS	5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.8	Mechanical system						
5.8.1	Piping and manifolds	LS	LS	35,000.00	\$ 35,000	\$ 7,000	\$ 42,000
5.8.2	Pumps	LS	LS	30,000.00	\$ 30,000	\$ 6,000	\$ 36,000
5.9	Power and lighting system						

DETAILED ESTIMATE OF INCREMENTAL COST
COUSINS PUMPING STATION COMPLEX

		2,000 CFS					
Item	Description	Quantity	Unit	Unit cost	Total	Contingency	Project cost
5.9.1	Electrical services/work	LS	LS	5,000.00	\$ 5,000	\$ 1,000	\$ 6,000
5.9.2	Other electrical work	LS	LS	10,000.00	\$ 10,000	\$ 2,000	\$ 12,000
5.10	Associated general items						
5.10.1	Tile gages	LS	LS	2,500.00	\$ 2,500	\$ 500	\$ 3,000
	Sub-total Culvert				\$ 2,020,960	\$ 427,772	\$ 2,448,732
6	CLOSURE WALL						
6.1.1	Steel Sheet Piling	16416	SF	15.00	\$246,240	\$49,248	\$295,488
6.1.2	84" Diameter Prestressed Concrete Cylinder Piles	15600	LF	250.00	\$3,900,000	\$780,000	\$4,680,000
6.1.3	Concrete Cap (Includes Reinforcing)	1216	CY	375.00	\$456,000	\$91,200	\$547,200
	Sub-total Closure Wall				\$4,602,240	\$920,448	\$5,522,688
7	RELOCATION						
7.1	16" High Pressure Gas Line	2	LS	75,000.00	\$ 150,000	\$30,000	\$180,000
7.1.2	Electrical Power Lines	1	LS	100,000.00	\$ 100,000	\$20,000	\$120,000
	Sub-total Relocation				\$ 250,000	\$ 50,000	\$ 300,000
	Construction Cost Total				\$ 24,995,201	\$ 4,250,550	\$ 29,245,751
	PROJECT COST						
1	Construction Cost				\$ 24,995,201	\$ 4,250,550	\$ 29,245,751
2	Constr. Engineering and Design				\$ 292,458	\$ 58,492	\$ 350,949
3	Plans and Specifications				\$ 2,924,575	\$ 584,915	\$ 3,509,490
4	Construction Administration				\$ 2,924,575	\$ 584,915	\$ 3,509,490
	Total				\$ 31,136,808	\$ 5,478,872	\$ 36,615,680
	TOTAL (rounded)						\$ 36,616,000

APPENDIX B
HEC-2 MODEL RESULTS

TABLE OF CONTENTS

1. First Avenue Canal: Summary Output Tables of HEC-2 Model runs are enclosed for the First Avenue Canal for the following cases:

Case Number	Channel Description	Elevation at Cousins P/S (ft. NGVD)	Discharge (cfs)
Case 1	Existing channel cross-sections and profile	-6.7	1,000; 2,100 and 3,100
Case 2	Design channel cross-section: bottom width 68' with 1V to 3H slope for approximately 1,000 ft from the Cousins P/S and bottom width 50' and 1V to 6H side slope for the remaining part of the Canal.	-6.7	1,000; 2,100 and 3,100
Case 3	Design channel cross-section: bottom width 108' with 1V to 3H slope for approximately 1,000 ft from the Cousins P/S and bottom width 91' and 1V to 6H side slope for the remaining part of the Canal.	-6.7	1,000; 2,100 and 3,100

2. Cousins Discharge Channel: Summary Output Tables of HEC-2 Model runs are enclosed for the Cousins Discharge Channel for the following cases:

Case Number	Channel Description	El. at Harvey Canal, ft. (NGVD)	Discharge (cfs)
Case 1	Existing channel cross-sections and profile	-1 to +7.5	3,000; 4,000 and 5,000
Case 2	Design channel cross-section and profile (channel bottom -8' NGVD and -9' NGVD)	-1 to +7.5	4,000 and 5,000
Case 3	Sensitivity analysis. i.e., by varying Manning's 'n' and contraction and expansion coefficients using design channel cross-section and profile (channel bottom -9' NGVD)	-1 to +7.5	5,000
Case 4	Corps of Engineer's design of channel and culvert	-1 to +7.5	5,000

3. Cousins Canal: Summary Output Tables of HEC-2 Model runs for the Cousins Canal are enclosed for the existing conditions.

ABBREVIATIONS

SECNO	Cross-section number
QCH	Discharge in the channel
AREA	Area of flow
XLCH	Length of the channel between cross-sections
TOPWID	Top width of water in the channel
ELMIN	Lowest point of the channel in the cross-section
XLBL	Left bank elevation
RLBL	Right bank elevation
DEPTH	Water depth in the channel
CWSEL	Water surface elevation in the channel
VCH	Velocity of the water in the channel


FIRST AVENUE CANAL

CASE 1

FIRAVE

INPUT FILE: FIRAVE.DAT											
SUMMARY PRINTOUT											
DATE: 10-08-97											
	SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
	1	1000	996.82	0	138.05	-19.01	-3.93	-2.31	12.31	-6.7	1
	1	2000	996.82	0	138.05	-19.01	-3.93	-2.31	12.31	-6.7	2.01
	1	3000	996.82	0	138.05	-19.01	-3.93	-2.31	12.31	-6.7	3.01
*	2	1000	813.85	1000	144.45	-18.37	-0.97	-2.07	11.71	-6.66	1.23
	2	2000	830.55	1000	145.31	-18.37	-0.97	-2.07	11.82	-6.55	2.41
	2	3000	856.33	1000	146.64	-18.37	-0.97	-2.07	11.99	-6.38	3.5
*	3	1000	321.84	1000	94.25	-13.2	0.82	3.2	6.6	-6.6	3.11
*	3	2000	352.04	1000	96.58	-13.2	0.82	3.2	6.91	-6.29	5.68
*	3	3000	400.47	1000	100.21	-13.2	0.82	3.2	7.4	-5.8	7.49
	4	1000	331.2	1000	86.66	-12.04	-2.09	2.49	6.16	-5.88	3.02
*	4	2000	450.46	1000	94.35	-12.04	-2.09	2.49	7.48	-4.56	4.44
*	4	3000	568.62	1000	102.71	-12.04	-2.09	2.49	8.68	-3.36	5.28
	5	1000	392.74	1053	94.68	-11.02	2.04	1.42	5.72	-5.3	2.55
	5	2000	554.61	1053	102.2	-11.02	2.04	1.42	7.37	-3.65	3.61
	5	3000	699.03	1053	108.6	-11.02	2.04	1.42	8.73	-2.29	4.29

Water Surface Profiles in First Avenue Canal (Elevation at Pump Station fixed at -6.7 NGVD)



FIRST AVENUE CANAL

CASE 2

FIRST AVENUE CANAL

INPUT FILE: FAM2100.DAT

SUMMARY OUTPUT

DISCHARGE: 2100 CFS

(1000 & 3100 CFS ARE INCLUDED FOR COMPARISON PURPOSES)

CROSS SECTIONS TAKEN FROM DEI'S 50% SUBMITTAL
 BOTTOM WIDTH 68' WITH 1V TO 3H SLOPE FOR SECTIONS 1 AND 2
 BOTTOM WIDTH 50' WITH 1V TO 6H SLOPE FOR REST OF THE SECTIONS
 TRANSITION BETWEEN SECTIONS 2 AND 3
 SECTION 1 NEAR PUMP STATION

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	2100	954.52	0	126.8	-16.5	-3.12	-3.12	9.8	-6.7	2.2
2	2100	970.33	900	127.55	-16.5	-3.12	-3.12	9.92	-6.58	2.16
3	2100	1090.84	100	169.35	-16.5	1.96	1.96	9.95	-6.55	1.93
4	2100	1114.26	1000	171.01	-16.5	1.96	1.96	10.08	-6.42	1.88
5	2100	1135.03	1000	172.46	-16.5	1.96	1.96	10.2	-6.3	1.85
6	2100	1155.7	1053	173.89	-16.5	1.96	1.96	10.32	-6.18	1.82
1	1000	954.52	0	126.8	-16.5	-3.12	-3.12	9.8	-6.7	1.05
2	1000	958.1	900	126.97	-16.5	-3.12	-3.12	9.83	-6.67	1.04
3	1000	1071.52	100	167.98	-16.5	1.96	1.96	9.83	-6.67	0.93
4	1000	1077.29	1000	168.39	-16.5	1.96	1.96	9.87	-6.63	0.93
5	1000	1082.31	1000	168.75	-16.5	1.96	1.96	9.9	-6.6	0.92
6	1000	1087.56	1053	169.12	-16.5	1.96	1.96	9.93	-6.57	0.92
1	3100	954.52	0	126.8	-16.5	-3.12	-3.12	9.8	-6.7	3.25
2	3100	989.1	900	128.43	-16.5	-3.12	-3.12	10.07	-6.43	3.13
3	3100	1122.88	100	171.61	-16.5	1.96	1.96	10.13	-6.37	2.76
4	3100	1167.73	1000	174.72	-16.5	1.96	1.96	10.39	-6.11	2.65
5	3100	1208.35	1000	177.48	-16.5	1.96	1.96	10.62	-5.88	2.57
6	3100	1247.34	1053	180.1	-16.5	1.96	1.96	10.84	-5.66	2.49

FIRST AVENUE CANAL

CASE 3

FIRST AVENUE CANAL

INPUT FILE: FAM3100.DAT

SUMMARY OUTPUT

DISCHARGE: 3100 CFS

(1000 & 2100 CFS ARE INCLUDED FOR COMPARISON PURPOSES)

CROSS SECTIONS TAKEN FROM DEI'S 50% SUBMITTAL
 BOTTOM WIDTH 108' WITH 1V TO 3H SLOPE FOR SECTIONS 1 AND 2
 BOTTOM WIDTH 91' WITH 1V TO 6H SLOPE FOR REST OF THE SECTIONS
 TRANSITION BETWEEN SECTIONS 2 AND 3
 SECTION 1 NEAR PUMP STATION

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	3100	1346.52	0	166.8	-16.5	-3.13	-3.13	9.8	-6.7	2.3
2	3100	1367.1	900	167.54	-16.5	-3.13	-3.13	9.92	-6.58	2.27
3	3100	1498.17	100	210.33	-16.5	1.96	1.96	9.95	-6.55	2.07
4	3100	1527.03	1000	211.97	-16.5	1.96	1.96	10.08	-6.42	2.03
5	3100	1553.31	1000	213.45	-16.5	1.96	1.96	10.2	-6.3	2
6	3100	1579.36	1053	214.91	-16.5	1.96	1.96	10.32	-6.18	1.96
1	1000	1346.52	0	166.8	-16.5	-3.13	-3.13	9.8	-6.7	0.74
2	1000	1348.66	900	166.88	-16.5	-3.13	-3.13	9.81	-6.69	0.74
3	1000	1471.03	100	208.77	-16.5	1.96	1.96	9.82	-6.68	0.68
4	1000	1474.28	1000	208.96	-16.5	1.96	1.96	9.83	-6.67	0.68
5	1000	1477.21	1000	209.13	-16.5	1.96	1.96	9.84	-6.66	0.68
6	1000	1480.27	1053	209.3	-16.5	1.96	1.96	9.86	-6.64	0.68
1	2100	1346.52	0	166.8	-16.5	-3.13	-3.13	9.8	-6.7	1.56
2	2100	1355.95	900	167.14	-16.5	-3.13	-3.13	9.86	-6.64	1.55
3	2100	1481.21	100	209.36	-16.5	1.96	1.96	9.87	-6.63	1.42
4	2100	1495.37	1000	210.17	-16.5	1.96	1.96	9.93	-6.57	1.4
5	2100	1507.94	1000	210.88	-16.5	1.96	1.96	9.99	-6.51	1.39
6	2100	1520.79	1053	211.61	-16.5	1.96	1.96	10.05	-6.45	1.38

COUSINS DISCHARGE CHANNEL

CASE 1

INPUT FILE: COUDISS.DAT										
SUMMARY PRINTOUT										
DATE: 10-2-97										
SECNO	OCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	3000	409.28	0	115.98	-8.32	4.31	2.78	5.32		-1 7.33
1	3000	528.82	0	124.44	-8.32	4.31	2.78	8.32	0	5.87
1	3000	680.33	0	138.57	-8.32	4.31	2.78	7.32	1	4.54
1	3000	800.11	0	140.99	-8.32	4.31	2.78	8.32	2	3.75
1	3000	942.29	0	143.14	-8.32	4.31	2.78	8.32	3	3.18
1	3000	1088	0	144.33	-8.32	4.31	2.78	10.32	4	2.78
1	3000	1230.7	0	144.7	-8.32	4.31	2.78	11.32	5	2.44
2	3000	327.5	100	127.94	-3.51	4.85	2.03	3.15	-0.38	9.16
2	3000	371.82	100	133.85	-3.51	4.85	2.03	3.48	-0.03	8.07
2	3000	517.51	100	142.41	-3.51	4.85	2.03	4.52	1.01	5.8
2	3000	662.99	100	151.17	-3.51	4.85	2.03	5.52	2.01	4.52
2	3000	815.32	100	154.07	-3.51	4.85	2.03	6.52	3.01	3.68
2	3000	971.78	100	158.85	-3.51	4.85	2.03	7.52	4.01	3.09
2	3000	1130	100	159.15	-3.51	4.85	2.03	8.52	5.01	2.85
3	3000	585.25	100	150.22	-3.74	2	1.63	4.71	0.97	5.13
3	3000	582.28	100	150.13	-3.74	2	1.63	4.88	0.94	5.15
3	3000	649.9	100	152.87	-3.74	2	1.63	5.14	1.4	4.82
3	3000	772.97	100	155.57	-3.74	2	1.63	5.93	2.19	3.88
3	3000	914.76	100	155.57	-3.74	2	1.63	8.85	3.11	3.28
3	3000	1063.7	100	155.57	-3.74	2	1.63	7.8	4.06	2.82
3	3000	1214.4	100	155.57	-3.74	2	1.63	8.78	5.04	2.47
4	3000	729.97	100	163.57	-4.71	1.05	2.34	5.97	1.26	4.11
4	3000	726.09	100	163.56	-4.71	1.05	2.34	5.94	1.23	4.13
4	3000	787.4	100	163.73	-4.71	1.05	2.34	6.32	1.61	3.81
4	3000	904.32	100	164.05	-4.71	1.05	2.34	7.03	2.32	3.32
4	3000	1045.8	100	164.06	-4.71	1.05	2.34	7.89	3.18	2.87
4	3000	1198.4	100	164.06	-4.71	1.05	2.34	8.83	4.12	2.5
4	3000	1354.9	100	164.06	-4.71	1.05	2.34	9.79	5.08	2.21
5	3000	879.18	100	158.44	-6.24	0.78	1.87	7.85	1.41	3.41
5	3000	875.95	100	158.42	-6.24	0.78	1.87	7.83	1.39	3.42
5	3000	929.93	100	158.7	-6.24	0.78	1.87	7.97	1.73	3.23
5	3000	1038.3	100	158.7	-6.24	0.78	1.87	8.84	2.4	2.89
5	3000	1187.2	100	158.7	-6.24	0.78	1.87	9.48	3.24	2.57
5	3000	1312.4	100	158.7	-6.24	0.78	1.87	10.39	4.15	2.29
5	3000	1462.9	100	158.7	-6.24	0.78	1.87	11.34	5.1	2.05
6	3000	882.48	29	158.48	-6.24	0.78	1.67	7.87	1.43	3.4
6	3000	879.32	29	158.44	-6.24	0.78	1.67	7.85	1.41	3.41
6	3000	932.58	29	158.7	-6.24	0.78	1.67	7.99	1.75	3.22
6	3000	1038.1	29	158.7	-6.24	0.78	1.67	8.85	2.41	2.89
6	3000	1189.8	29	158.7	-6.24	0.78	1.67	9.48	3.24	2.56
6	3000	1314	29	158.7	-6.24	0.78	1.67	10.39	4.15	2.28
6	3000	1484.8	29	158.7	-6.24	0.78	1.67	11.34	5.1	2.05
7	3000	883.91	33	158.47	-6.24	0.78	1.87	7.88	1.44	3.39
7	3000	880.78	33	158.45	-6.24	0.78	1.87	7.86	1.42	3.41
7	3000	933.93	33	158.7	-6.24	0.78	1.87	8	1.78	3.21
7	3000	1039.2	33	158.7	-6.24	0.78	1.87	8.88	2.42	2.89
7	3000	1173.2	33	158.7	-6.24	0.78	1.87	9.51	3.27	2.56
7	3000	1321.1	33	158.7	-6.24	0.78	1.87	10.44	4.2	2.27
7	3000	1474.3	33	158.7	-6.24	0.78	1.87	11.4	5.18	2.03
8	3000	773.17	38	170.21	-8.12	2.21	1.09	7.55	1.43	3.88
8	3000	769.74	38	170.13	-8.12	2.21	1.09	7.53	1.41	3.9
8	3000	827.83	38	171.39	-8.12	2.21	1.09	7.87	1.75	3.62
8	3000	944.48	38	173.11	-8.12	2.21	1.09	8.54	2.42	3.18
8	3000	1091.4	38	173.11	-8.12	2.21	1.09	9.38	3.26	2.75
8	3000	1252.3	38	173.11	-8.12	2.21	1.09	10.32	4.2	2.4
8	3000	1419.2	38	173.11	-8.12	2.21	1.09	11.28	5.18	2.11
9	3000	1199.8	100	224.14	-8.11	1.14	1.04	7.73	1.82	2.5
9	3000	1195.8	100	224.14	-8.11	1.14	1.04	7.72	1.81	2.51
9	3000	1264.8	100	224.14	-8.11	1.14	1.04	8.02	1.91	2.37
9	3000	1404.3	100	224.14	-8.11	1.14	1.04	8.85	2.54	2.14
9	3000	1588.4	100	224.14	-8.11	1.14	1.04	9.48	3.35	1.89
9	3000	1780.4	100	224.14	-8.11	1.14	1.04	10.37	4.28	1.68
9	3000	2003.5	100	224.14	-8.11	1.14	1.04	11.32	5.21	1.5
10	3000	2037.6	100	223.04	-13	2	2.07	14.7	1.7	1.47
10	3000	2033.7	100	222.87	-13	2	2.07	14.89	1.89	1.48
10	3000	2100.4	100	225.78	-13	2	2.07	14.98	1.98	1.43
10	3000	2237.8	100	225.94	-13	2	2.07	15.59	2.59	1.34
10	3000	2417.9	100	225.94	-13	2	2.07	18.39	3.39	1.24
10	3000	2619.3	100	225.94	-13	2	2.07	17.29	4.29	1.15
10	3000	2832.8	100	225.94	-13	2	2.07	18.23	5.23	1.06

INPUT FILE: COUDIS4.DAT										
SUMMARY PRINTOUT										
DATE: 10/2/97										
SECNO	QCH	AREA	XLCH	TOPWD	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	4000	409.28	0	115.98	-6.32	4.31	2.78	5.32	-1	9.77
1	4000	528.82	0	124.44	-6.32	4.31	2.78	6.32	0	7.58
1	4000	660.33	0	138.57	-6.32	4.31	2.78	7.32	1	6.08
1	4000	800.11	0	140.99	-6.32	4.31	2.78	8.32	2	5
1	4000	942.29	0	143.14	-6.32	4.31	2.78	9.32	3	4.24
1	4000	1086	0	144.33	-6.32	4.31	2.78	10.32	4	3.88
1	4000	1230.7	0	144.7	-6.32	4.31	2.78	11.32	5	3.25
2	4000	409.93	100	140.83	-3.51	4.85	2.03	3.77	0.26	9.78
2	4000	409.94	100	140.83	-3.51	4.85	2.03	3.77	0.26	9.78
2	4000	519.98	100	142.44	-3.51	4.85	2.03	4.54	1.03	7.89
2	4000	664.44	100	151.27	-3.51	4.85	2.03	5.53	2.02	6.02
2	4000	816.38	100	154.09	-3.51	4.85	2.03	6.52	3.01	4.9
2	4000	971.4	100	156.84	-3.51	4.85	2.03	7.52	4.01	4.12
2	4000	1130.6	100	159.15	-3.51	4.85	2.03	8.52	5.01	3.54
3	4000	692.04	100	154.2	-3.74	2	1.83	5.41	1.67	5.78
3	4000	692.03	100	154.2	-3.74	2	1.83	5.41	1.67	5.78
3	4000	705.81	100	154.57	-3.74	2	1.83	5.49	1.75	5.87
3	4000	799.49	100	155.57	-3.74	2	1.83	6.1	2.36	5
3	4000	928.69	100	155.57	-3.74	2	1.83	6.94	3.2	4.31
3	4000	1072	100	155.57	-3.74	2	1.83	7.86	4.12	3.73
3	4000	1221	100	155.57	-3.74	2	1.83	8.82	5.08	3.28
4	4000	850.9	100	163.9	-4.71	1.05	2.34	6.71	2	4.7
4	4000	850.9	100	163.9	-4.71	1.05	2.34	6.71	2	4.7
4	4000	861.28	100	163.93	-4.71	1.05	2.34	6.77	2.08	4.84
4	4000	946.24	100	164.08	-4.71	1.05	2.34	7.29	2.58	4.23
4	4000	1070.1	100	164.08	-4.71	1.05	2.34	8.04	3.33	3.74
4	4000	1213.8	100	164.08	-4.71	1.05	2.34	8.92	4.21	3.3
4	4000	1366.2	100	164.08	-4.71	1.05	2.34	9.85	5.14	2.93
5	4000	1000.1	100	158.7	-6.24	0.78	1.87	8.42	2.18	4
5	4000	1000.1	100	158.7	-6.24	0.78	1.87	8.42	2.18	4
5	4000	1009.9	100	158.7	-6.24	0.78	1.87	8.48	2.24	3.98
5	4000	1084.4	100	158.7	-6.24	0.78	1.87	8.95	2.71	3.89
5	4000	1187.6	100	158.7	-6.24	0.78	1.87	9.86	3.42	3.34
5	4000	1330.3	100	158.7	-6.24	0.78	1.87	10.51	4.27	3.01
5	4000	1475.4	100	158.7	-6.24	0.78	1.87	11.42	5.18	2.71
6	4000	1003.8	29	158.7	-6.24	0.78	1.87	8.43	2.19	3.98
6	4000	1003.8	29	158.7	-6.24	0.78	1.87	8.43	2.19	3.98
6	4000	1013.5	29	158.7	-6.24	0.78	1.87	8.5	2.28	3.95
6	4000	1087.1	29	158.7	-6.24	0.78	1.87	8.96	2.72	3.68
6	4000	1199.5	29	158.7	-6.24	0.78	1.87	9.67	3.43	3.33
6	4000	1333.1	29	158.7	-6.24	0.78	1.87	10.51	4.27	3
6	4000	1477.4	29	158.7	-6.24	0.78	1.87	11.42	5.18	2.71
7	4000	1006.4	33	158.7	-6.24	0.78	1.87	8.46	2.22	3.97
7	4000	1006.4	33	158.7	-6.24	0.78	1.87	8.46	2.22	3.97
7	4000	1018	33	158.7	-6.24	0.78	1.87	8.52	2.28	3.94
7	4000	1089.3	33	158.7	-6.24	0.78	1.87	8.98	2.74	3.87
7	4000	1207.5	33	158.7	-6.24	0.78	1.87	9.72	3.46	3.31
7	4000	1348.8	33	158.7	-6.24	0.78	1.87	10.6	4.36	2.97
7	4000	1495	33	158.7	-6.24	0.78	1.87	11.53	5.29	2.68
8	4000	905.87	38	173.08	-6.12	2.21	1.09	8.32	2.2	4.42
8	4000	905.87	38	173.08	-6.12	2.21	1.09	8.32	2.2	4.42
8	4000	916.47	38	173.11	-6.12	2.21	1.09	8.38	2.26	4.36
8	4000	987.23	38	173.11	-6.12	2.21	1.09	8.85	2.73	4.01
8	4000	1128.4	38	173.11	-6.12	2.21	1.09	9.6	3.48	3.55
8	4000	1280.7	38	173.11	-6.12	2.21	1.09	10.48	4.36	3.12
8	4000	1442.2	38	173.11	-6.12	2.21	1.09	11.42	5.3	2.77
9	4000	1383.1	100	224.14	-6.11	1.14	1.04	8.55	2.44	2.89
9	4000	1383.1	100	224.14	-6.11	1.14	1.04	8.55	2.44	2.89
9	4000	1395.3	100	224.14	-6.11	1.14	1.04	8.61	2.5	2.87
9	4000	1480.1	100	224.14	-6.11	1.14	1.04	9.03	2.92	2.68
9	4000	1647.1	100	224.14	-6.11	1.14	1.04	9.73	3.62	2.43
9	4000	1835.9	100	224.14	-6.11	1.14	1.04	10.57	4.46	2.18
9	4000	2040.3	100	224.14	-6.11	1.14	1.04	11.48	5.37	1.98
10	4000	2228.8	100	225.94	-13	2	2.07	15.54	2.54	1.8
10	4000	2228.8	100	225.94	-13	2	2.07	15.54	2.54	1.8
10	4000	2238.4	100	225.94	-13	2	2.07	15.59	2.69	1.78
10	4000	2330.7	100	225.94	-13	2	2.07	16	3	1.72
10	4000	2484.7	100	225.94	-13	2	2.07	16.88	3.68	1.61
10	4000	2671.5	100	225.94	-13	2	2.07	17.51	4.51	1.5
10	4000	2874.8	100	225.94	-13	2	2.07	18.41	5.41	1.39


INPUT FILE: COUDIS3.DAT

SUMMARY PRINTOUT


DATE: 10-02-97

SECNO	QCH	AREA	XLCH	TOPWD	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	5000	447.18	0	118.06	-8.32	4.31	2.78	5.84	-0.68	11.18
1	5000	528.82	0	124.44	-8.32	4.31	2.78	8.32	0	9.46
1	5000	660.33	0	138.57	-8.32	4.31	2.78	7.32	1	7.57
1	5000	800.11	0	140.99	-8.32	4.31	2.78	8.32	2	6.25
1	5000	942.29	0	143.14	-8.32	4.31	2.78	9.32	3	5.31
1	5000	1086	0	144.33	-8.32	4.31	2.78	10.32	4	4.6
1	5000	1230.7	0	144.7	-8.32	4.31	2.78	11.32	5	4.06
2	5000	477.71	100	141.88	-3.51	4.85	2.03	4.25	0.74	10.47
2	5000	477.12	100	141.85	-3.51	4.85	2.03	4.24	0.73	10.48
2	5000	524.62	100	142.51	-3.51	4.85	2.03	4.57	1.06	9.53
2	5000	666.68	100	151.39	-3.51	4.85	2.03	5.54	2.03	7.5
2	5000	817.87	100	154.12	-3.51	4.85	2.03	6.53	3.02	6.11
2	5000	972.55	100	158.86	-3.51	4.85	2.03	7.53	4.02	5.14
2	5000	1130.3	100	159.15	-3.51	4.85	2.03	8.53	5.02	4.42
3	5000	785.5	100	155.57	-3.74	2	1.63	6.02	2.28	6.37
3	5000	785.87	100	155.57	-3.74	2	1.63	6.02	2.28	6.36
3	5000	780.21	100	155.57	-3.74	2	1.63	5.98	2.24	6.41
3	5000	837.23	100	155.57	-3.74	2	1.63	6.34	2.8	5.97
3	5000	947.99	100	155.57	-3.74	2	1.63	7.06	3.32	5.27
3	5000	1083.1	100	155.57	-3.74	2	1.63	7.93	4.19	4.82
3	5000	1228	100	155.57	-3.74	2	1.63	8.86	5.12	4.07
4	5000	957.28	100	164.06	-4.71	1.05	2.34	7.35	2.64	5.22
4	5000	957.39	100	164.06	-4.71	1.05	2.34	7.36	2.65	5.22
4	5000	952.94	100	164.06	-4.71	1.05	2.34	7.33	2.62	5.25
4	5000	1000.3	100	164.06	-4.71	1.05	2.34	7.82	2.91	5
4	5000	1102.1	100	164.06	-4.71	1.05	2.34	8.24	3.53	4.54
4	5000	1233.5	100	164.06	-4.71	1.05	2.34	9.04	4.33	4.05
4	5000	1379.4	100	164.06	-4.71	1.05	2.34	9.93	5.22	3.62
5	5000	1106.3	100	158.7	-8.24	0.78	1.67	9.09	2.85	4.52
5	5000	1106.5	100	158.7	-8.24	0.78	1.67	9.09	2.85	4.52
5	5000	1102.7	100	158.7	-8.24	0.78	1.67	9.08	2.82	4.53
5	5000	1143.8	100	158.7	-8.24	0.78	1.67	9.32	3.08	4.37
5	5000	1234.9	100	158.7	-8.24	0.78	1.67	9.9	3.88	4.05
5	5000	1355.9	100	158.7	-8.24	0.78	1.67	10.86	4.42	3.69
5	5000	1492.7	100	158.7	-8.24	0.78	1.67	11.52	5.28	3.35
6	5000	1110.4	29	158.7	-8.24	0.78	1.67	9.11	2.87	4.5
6	5000	1110.5	29	158.7	-8.24	0.78	1.67	9.11	2.87	4.5
6	5000	1106.8	29	158.7	-8.24	0.78	1.67	9.08	2.84	4.52
6	5000	1147.4	29	158.7	-8.24	0.78	1.67	9.34	3.1	4.36
6	5000	1237.6	29	158.7	-8.24	0.78	1.67	9.91	3.87	4.04
6	5000	1357.8	29	158.7	-8.24	0.78	1.67	10.87	4.43	3.68
6	5000	1494.1	29	158.7	-8.24	0.78	1.67	11.53	5.29	3.35
7	5000	1115.5	33	158.7	-8.24	0.78	1.67	9.14	2.9	4.48
7	5000	1115.7	33	158.7	-8.24	0.78	1.67	9.14	2.9	4.48
7	5000	1111.6	33	158.7	-8.24	0.78	1.67	9.12	2.88	4.5
7	5000	1156	33	158.7	-8.24	0.78	1.67	9.4	3.16	4.33
7	5000	1253.2	33	158.7	-8.24	0.78	1.67	10.01	3.77	3.99
7	5000	1380.4	33	158.7	-8.24	0.78	1.67	10.81	4.57	3.62
7	5000	1522.5	33	158.7	-8.24	0.78	1.67	11.71	5.47	3.28
8	5000	1025.2	38	173.11	-8.12	2.21	1.09	9.01	2.89	4.88
8	5000	1025.3	38	173.11	-8.12	2.21	1.09	9.01	2.89	4.88
8	5000	1020.8	38	173.11	-8.12	2.21	1.09	8.99	2.87	4.9
8	5000	1069.9	38	173.11	-8.12	2.21	1.09	9.27	3.15	4.67
8	5000	1176.7	38	173.11	-8.12	2.21	1.09	9.89	3.77	4.25
8	5000	1317.2	38	173.11	-8.12	2.21	1.09	10.69	4.57	3.8
8	5000	1472.8	38	173.11	-8.12	2.21	1.09	11.59	5.47	3.39
9	5000	1548.8	100	224.14	-8.11	1.14	1.04	9.28	3.17	3.23
9	5000	1548.9	100	224.14	-8.11	1.14	1.04	9.28	3.17	3.23
9	5000	1541.8	100	224.14	-8.11	1.14	1.04	9.28	3.15	3.24
9	5000	1598.4	100	224.14	-8.11	1.14	1.04	9.51	3.4	3.13
9	5000	1725	100	224.14	-8.11	1.14	1.04	10.08	3.97	2.9
9	5000	1894.8	100	224.14	-8.11	1.14	1.04	10.83	4.72	2.64
9	5000	2088	100	224.14	-8.11	1.14	1.04	11.7	5.59	2.39
10	5000	2395.8	100	225.94	-13	2	2.07	18.29	3.29	2.09
10	5000	2396	100	225.94	-13	2	2.07	18.29	3.29	2.09
10	5000	2391	100	225.94	-13	2	2.07	18.27	3.27	2.09
10	5000	2445.7	100	225.94	-13	2	2.07	18.51	3.51	2.04
10	5000	2569	100	225.94	-13	2	2.07	17.06	4.06	1.85
10	5000	2735.8	100	225.94	-13	2	2.07	17.8	4.8	1.83
10	5000	2927	100	225.94	-13	2	2.07	18.84	5.64	1.71


Water Surface Profiles in Cousins Discharge Channel (Discharge 3,000 cfs)



Water Surface Profiles in Cousins Discharge Channel (Discharge 4,000 cfs)



Water Surface Profiles in Cousins Discharge Channel (Discharge 5,000 cfs)



COUSINS DISCHARGE CHANNEL

CASE 2

COUSINS DISCHARGE CHANNEL

SUMMARY OUTPUT
 INPUT FILE: DIS5K-9.DAT
 DISCHARGE: 5000 CFS
 CHANNEL BOTTOM AT -9.0

P.S. TO DSTRHN BRIDGE: TOP WIDTH OF CHANNEL TAKEN FROM DEI'S 50% SUBMITTAL
 DSTRHN BRIDGE TO HARVEY CANAL: TOP WIDTH OF CHANNEL TAKEN FROM CEEC'S LAYOUT
 ALL CROSS SECTIONS HAVE 15' BERM AT +2.0 ON THE LAPALCO BLVD SIDE
 SIDE SLOPE 1 VERTICAL TO 3 HORIZONTAL FROM +2.0 TO BOTTOM
 VERTICAL WALL CONSIDERED FROM +2.0 TO +9.5
 CULVERT (BETWEEN SECTIONS 2 AND 3) UNDER LAPALCO BRIDGE CONSIDERED 108' WIDE
 DESTRAHAN BRIDGE BETWEEN SECTIONS 6 AND 7
 SECTION 10 NEAR PUMP STATION

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
1	5000	984	0	147	-9	9.5	9.5	8	-1	5.08	
*	2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-1.04	5.82
*	3	5000	865.17	100	108	-9	9.5	9.5	8.01	-0.99	5.78
4	5000	1062.03	395.08	150.15	-9	9.5	9.5	8.52	-0.48	4.71	
5	5000	1075.14	103	150.67	-9	9.5	9.5	8.6	-0.4	4.65	
6	5000	1087.55	137	151.17	-9	9.5	9.5	8.7	-0.3	4.6	
7	5000	1093.62	33	151.41	-9	9.5	9.5	8.73	-0.27	4.57	
*	8	5000	1778.79	26.48	225.29	-9	9.5	9.5	8.97	-0.03	2.81
9	5000	2129.03	75	263.11	-9	9.5	9.5	9.02	0.02	2.35	
10	5000	2132.24	70	263.19	-9	9.5	9.5	9.03	0.03	2.34	
*	1	5000	1134	0	153	-9	9.5	9.5	9	0	4.41
*	2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	-0.05	5.17
*	3	5000	970.53	100	108	-9	9.5	9.5	8.98	-0.02	5.15
4	5000	1190.39	395.08	155.2	-9	9.5	9.5	9.37	0.37	4.2	
5	5000	1199.95	103	155.56	-9	9.5	9.5	9.42	0.42	4.17	
6	5000	1209.1	137	155.92	-9	9.5	9.5	9.49	0.49	4.14	
7	5000	1213.5	33	156.09	-9	9.5	9.5	9.51	0.51	4.12	
*	8	5000	1945.44	26.48	229.69	-9	9.5	9.5	9.7	0.7	2.57
9	5000	2318.14	75	267.39	-9	9.5	9.5	9.74	0.74	2.16	
10	5000	2323.13	70	267.5	-9	9.5	9.5	9.75	0.75	2.15	
1	5000	1290	0	159	-9	9.5	9.5	10	1	3.88	
*	2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	0.95	4.65
*	3	5000	1077.19	100	108	-9	9.5	9.5	9.97	0.97	4.64
4	5000	1332.43	395.08	160.59	-9	9.5	9.5	10.27	1.27	3.75	
5	5000	1339.57	103	160.86	-9	9.5	9.5	10.3	1.3	3.73	
6	5000	1346.28	137	161.11	-9	9.5	9.5	10.35	1.35	3.71	
7	5000	1349.52	33	161.23	-9	9.5	9.5	10.37	1.37	3.71	
*	8	5000	2135.63	26.48	234.61	-9	9.5	9.5	10.52	1.52	2.34
9	5000	2537.21	75	272.26	-9	9.5	9.5	10.55	1.55	1.97	
10	5000	2541.4	70	272.36	-9	9.5	9.5	10.56	1.56	1.97	

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
	1	5000	1452	0	165	-9	9.5	9.5	11	2	3.44
*	2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	1.95	4.23
*	3	5000	1184.53	100	108	-9	9.5	9.5	10.97	1.97	4.22
	4	5000	1489.33	395.08	180	-9	9.5	9.5	11.21	2.21	3.36
	5	5000	1495.47	103	180	-9	9.5	9.5	11.24	2.24	3.34
	6	5000	1501.73	137	180	-9	9.5	9.5	11.28	2.28	3.33
	7	5000	1504.39	33	180	-9	9.5	9.5	11.29	2.29	3.32
*	8	5000	2352.16	26.48	252.5	-9	9.5	9.5	11.41	2.41	2.13
	9	5000	2786.09	75	290	-9	9.5	9.5	11.43	2.43	1.79
	10	5000	2789.69	70	290	-9	9.5	9.5	11.44	2.44	1.79
	1	5000	1632	0	180	-9	9.5	9.5	12	3	3.06
*	2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	2.95	3.87
*	3	5000	1292.16	100	108	-9	9.5	9.5	11.96	2.96	3.87
	4	5000	1660.51	395.08	180	-9	9.5	9.5	12.16	3.16	3.01
	5	5000	1665.05	103	180	-9	9.5	9.5	12.18	3.18	3
	6	5000	1669.23	137	180	-9	9.5	9.5	12.21	3.21	3
	7	5000	1671.33	33	180	-9	9.5	9.5	12.22	3.22	2.99
*	8	5000	2580.31	26.48	252.5	-9	9.5	9.5	12.31	3.31	1.94
	9	5000	3046.73	75	290	-9	9.5	9.5	12.33	3.33	1.64
	10	5000	3049.69	70	290	-9	9.5	9.5	12.34	3.34	1.64
	1	5000	1812	0	180	-9	9.5	9.5	13	4	2.76
*	2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	3.95	3.57
*	3	5000	1399.99	100	108	-9	9.5	9.5	12.96	3.96	3.57
	4	5000	1834.36	395.08	180	-9	9.5	9.5	13.12	4.12	2.73
	5	5000	1837.81	103	180	-9	9.5	9.5	13.14	4.14	2.72
	6	5000	1840.69	137	180	-9	9.5	9.5	13.16	4.16	2.72
	7	5000	1847.28	33	180	-9	9.5	9.5	13.2	4.2	2.71
*	8	5000	2822.6	26.48	252.5	-9	9.5	9.5	13.27	4.27	1.77
	9	5000	3323.97	75	290	-9	9.5	9.5	13.29	4.29	1.5
	10	5000	3326.42	70	290	-9	9.5	9.5	13.29	4.29	1.5
	1	5000	1992	0	180	-9	9.5	9.5	14	5	2.51
*	2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	4.96	3.32
*	3	5000	1508.04	100	108	-9	9.5	9.5	13.96	4.96	3.32
	4	5000	2009.98	395.08	180	-9	9.5	9.5	14.1	5.1	2.49
	5	5000	2012.66	103	180	-9	9.5	9.5	14.11	5.11	2.48
	6	5000	2014.7	137	180	-9	9.5	9.5	14.13	5.13	2.48
	7	5000	2024.69	33	180	-9	9.5	9.5	14.18	5.18	2.47
*	8	5000	3068.12	26.48	252.5	-9	9.5	9.5	14.24	5.24	1.63
	9	5000	3603.89	75	290	-9	9.5	9.5	14.26	5.26	1.39
	10	5000	3607.26	70	290	-9	9.5	9.5	14.26	5.26	1.39
	1	5000	2442	0	180	-9	9.5	9.5	16.5	7.5	2.05
*	2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.46	2.81
*	3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.47	2.81
	4	5000	2453.3	395.08	180	-9	9.5	9.5	16.56	7.56	2.04
	5	5000	2454.85	103	180	-9	9.5	9.5	16.57	7.57	2.04
	6	5000	2455.81	137	180	-9	9.5	9.5	16.58	7.58	2.04
	7	5000	2470.77	33	180	-9	9.5	9.5	16.66	7.66	2.02
*	8	5000	3688.57	26.48	252.5	-9	9.5	9.5	16.7	7.7	1.36
	9	5000	4315.7	75	290	-9	9.5	9.5	16.71	7.71	1.16
	10	5000	4318.04	70	290	-9	9.5	9.5	16.71	7.71	1.16

COUSINS DISCHARGE CHANNEL

SUMMARY OUTPUT
 INPUT FILE: DIS5K-8.DAT
 DISCHARGE: 5000 CFS
 CHANNEL BOTTOM AT -8.0

P.S. TO DSTRHN BRIDGE: TOP WIDTH OF CHANNEL TAKEN FROM DEI'S 50% SUBMITTAL
 DSTRHN BRIDGE TO HARVEY CANAL: TOP WIDTH OF CHANNEL TAKEN FROM CEEC'S LAYOUT
 ALL CROSS SECTIONS HAVE 15' BERM AT +2.0 ON THE LAPALCO BLVD SIDE
 SIDE SLOPE 1 VERTICAL TO 3 HORIZONTAL FROM +2.0 TO BOTTOM
 VERTICAL WALL CONSIDERED FROM +2.0 TO +9.5
 CULVERT (BETWEEN SECTIONS 2 AND 3) UNDER LAPALCO BRIDGE CONSIDERED 108' WIDE
 DESTRAHAN BRIDGE BETWEEN SECTIONS 6 AND 7
 SECTION 10 NEAR PUMP STATION

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH
1	5000	882	0	147	-8	9.5	9.5	7	-1	5.67
2	5000	748.62	111.61	108	-8	9.5	9.5	6.93	-1.07	6.68
3	5000	757.07	100	108	-8	9.5	9.5	7.01	-0.99	6.6
4	5000	997.54	395.08	151.64	-8	9.5	9.5	7.77	-0.23	5.01
5	5000	1012.28	103	152.22	-8	9.5	9.5	7.87	-0.13	4.94
6	5000	1029.65	137	152.91	-8	9.5	9.5	7.99	-0.01	4.86
7	5000	1037.27	33	153.21	-8	9.5	9.5	8.03	0.03	4.82
8	5000	1677.8	26.48	227.24	-8	9.5	9.5	8.29	0.29	2.98
9	5000	2004.82	75	265.11	-8	9.5	9.5	8.35	0.35	2.49
10	5000	2008.8	70	265.2	-8	9.5	9.5	8.36	0.36	2.49
1	5000	1032	0	153	-8	9.5	9.5	8	0	4.84
2	5000	856.17	111.61	108	-8	9.5	9.5	7.93	-0.07	5.84
3	5000	861.54	100	108	-8	9.5	9.5	7.98	-0.02	5.8
4	5000	1111.97	395.08	156.1	-8	9.5	9.5	8.52	0.52	4.5
5	5000	1124.04	103	156.57	-8	9.5	9.5	8.59	0.59	4.45
6	5000	1135.81	137	157.02	-8	9.5	9.5	8.67	0.67	4.4
7	5000	1141.23	33	157.23	-8	9.5	9.5	8.7	0.7	4.38
8	5000	1820.06	26.48	230.97	-8	9.5	9.5	8.91	0.91	2.75
9	5000	2165.02	75	268.71	-8	9.5	9.5	8.96	0.96	2.31
10	5000	2170.83	70	268.84	-8	9.5	9.5	8.97	0.97	2.3
1	5000	1188	0	159	-8	9.5	9.5	9	1	4.21
2	5000	964.38	111.61	108	-8	9.5	9.5	8.93	0.93	5.18
3	5000	967.96	100	108	-8	9.5	9.5	8.96	0.96	5.17
4	5000	1245.88	395.08	161.17	-8	9.5	9.5	9.36	1.36	4.01
5	5000	1254.61	103	161.49	-8	9.5	9.5	9.41	1.41	3.99
6	5000	1263.35	137	161.82	-8	9.5	9.5	9.47	1.47	3.96
7	5000	1267.29	33	161.96	-8	9.5	9.5	9.49	1.49	3.95
8	5000	1994.34	26.48	235.45	-8	9.5	9.5	9.66	1.66	2.51
9	5000	2365.11	75	273.14	-8	9.5	9.5	9.7	1.7	2.11
10	5000	2369.99	70	273.25	-8	9.5	9.5	9.71	1.71	2.11

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
	1	5000	1350	0	165	-8	9.5	9.5	10	2	3.7
*	2	5000	1072.82	111.61	108	-8	9.5	9.5	9.93	1.93	4.66
*	3	5000	1075.31	100	108	-8	9.5	9.5	9.96	1.96	4.65
	4	5000	1399.15	395.08	180	-8	9.5	9.5	10.27	2.27	3.57
	5	5000	1407.13	103	180	-8	9.5	9.5	10.31	2.31	3.55
	6	5000	1414.45	137	180	-8	9.5	9.5	10.36	2.36	3.53
	7	5000	1417.55	33	180	-8	9.5	9.5	10.38	2.38	3.53
*	8	5000	2202.45	26.48	252.5	-8	9.5	9.5	10.5	2.5	2.27
	9	5000	2603.66	75	290	-8	9.5	9.5	10.54	2.54	1.92
	10	5000	2607.82	70	290	-8	9.5	9.5	10.54	2.54	1.92
	1	5000	1530	0	180	-8	9.5	9.5	11	3	3.27
*	2	5000	1181.15	111.61	108	-8	9.5	9.5	10.94	2.94	4.23
*	3	5000	1183.01	100	108	-8	9.5	9.5	10.95	2.95	4.23
	4	5000	1566.5	395.08	180	-8	9.5	9.5	11.2	3.2	3.19
	5	5000	1572.28	103	180	-8	9.5	9.5	11.23	3.23	3.18
	6	5000	1577.1	137	180	-8	9.5	9.5	11.26	3.26	3.17
	7	5000	1580.57	33	180	-8	9.5	9.5	11.28	3.28	3.16
*	8	5000	2424.13	26.48	252.5	-8	9.5	9.5	11.38	3.38	2.06
	9	5000	2856.56	75	290	-8	9.5	9.5	11.41	3.41	1.75
	10	5000	2859.96	70	290	-8	9.5	9.5	11.41	3.41	1.75
	1	5000	1710	0	180	-8	9.5	9.5	12	4	2.92
*	2	5000	1289.61	111.61	108	-8	9.5	9.5	11.94	3.94	3.88
*	3	5000	1290.93	100	108	-8	9.5	9.5	11.95	3.95	3.87
	4	5000	1737.98	395.08	180	-8	9.5	9.5	12.16	4.16	2.88
	5	5000	1742.29	103	180	-8	9.5	9.5	12.17	4.17	2.87
	6	5000	1745.56	137	180	-8	9.5	9.5	12.2	4.2	2.86
	7	5000	1754.21	33	180	-8	9.5	9.5	12.25	4.25	2.85
*	8	5000	2662.5	26.48	252.5	-8	9.5	9.5	12.33	4.33	1.88
	9	5000	3129.08	75	290	-8	9.5	9.5	12.35	4.35	1.6
	10	5000	3131.86	70	290	-8	9.5	9.5	12.35	4.35	1.6
	1	5000	1890	0	180	-8	9.5	9.5	13	5	2.65
*	2	5000	1398.13	111.61	108	-8	9.5	9.5	12.95	4.95	3.58
*	3	5000	1399.11	100	108	-8	9.5	9.5	12.96	4.96	3.57
	4	5000	1912.06	395.08	180	-8	9.5	9.5	13.12	5.12	2.61
	5	5000	1915.35	103	180	-8	9.5	9.5	13.14	5.14	2.61
	6	5000	1917.63	137	180	-8	9.5	9.5	13.15	5.15	2.61
	7	5000	1930.21	33	180	-8	9.5	9.5	13.22	5.22	2.59
*	8	5000	2905.56	26.48	252.5	-8	9.5	9.5	13.29	5.29	1.72
	9	5000	3405.9	75	290	-8	9.5	9.5	13.31	5.31	1.47
	10	5000	3409.63	70	290	-8	9.5	9.5	13.31	5.31	1.47
	1	5000	2340	0	180	-8	9.5	9.5	15.5	7.5	2.14
*	2	5000	1669.34	111.61	108	-8	9.5	9.5	15.46	7.46	3
*	3	5000	1669.86	100	108	-8	9.5	9.5	15.46	7.46	2.99
*	4	5000	2353.37	395.08	180	-8	9.5	9.5	15.57	7.57	2.12
	5	5000	2355.21	103	180	-8	9.5	9.5	15.58	7.58	2.12
	6	5000	2356.24	137	180	-8	9.5	9.5	15.59	7.59	2.12
	7	5000	2374.21	33	180	-8	9.5	9.5	15.69	7.69	2.11
*	8	5000	3522.44	26.48	252.5	-8	9.5	9.5	15.73	7.73	1.42
	9	5000	4113.45	75	290	-8	9.5	9.5	15.74	7.74	1.22
	10	5000	4116.01	70	290	-8	9.5	9.5	15.74	7.74	1.21

COUSINS DISCHARGE CHANNEL

SUMMARY OUTPUT
 INPUT FILE DIS4K-8.DAT
 DISCHARGE: 4000 CFS
 CHANNEL BOTTOM AT -8.0

P.S. TO DSTRHN BRIDGE: TOP WIDTH OF CHANNEL TAKEN FROM DEI'S 50% SUBMITTAL
 DSTRHN BRIDGE TO HARVEY CANAL: TOP WIDTH OF CHANNEL TAKEN FROM CEEC'S LAYOUT
 ALL CROSS SECTIONS HAVE 15' BERM AT +2.0 ON THE LAPALCO BLVD SIDE
 SIDE SLOPE 1 VERTICAL TO 3 HORIZONTAL FROM +2.0 TO BOTTOM
 VERTICAL WALL CONSIDERED FROM +2.0 TO +9.5
 CULVERT (BETWEEN SECTIONS 2 AND 3) UNDER LAPALCO BRIDGE CONSIDERED 108' WIDE

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
*	1	4000	882	0	147	-8	9.5	9.5	7	-1	4.54
*	2	4000	751.47	111.61	108	-8	9.5	9.5	6.96	-1.04	5.32
*	3	4000	756.89	100	108	-8	9.5	9.5	7.01	-0.99	5.28
	4	4000	954.7	395.08	149.94	-8	9.5	9.5	7.49	-0.51	4.19
	5	4000	966.19	103	150.4	-8	9.5	9.5	7.56	-0.44	4.14
	6	4000	977.68	137	150.85	-8	9.5	9.5	7.65	-0.35	4.09
	7	4000	982.24	33	151.04	-8	9.5	9.5	7.67	-0.33	4.07
	8	4000	1579.3	26.48	224.63	-8	9.5	9.5	7.85	-0.15	2.53
	9	4000	1883.65	75	262.35	-8	9.5	9.5	7.9	-0.1	2.12
	10	4000	1888.58	70	262.47	-8	9.5	9.5	7.91	-0.09	2.12
*	1	4000	1032	0	153	-8	9.5	9.5	8	0	3.88
*	2	4000	859.14	111.61	108	-8	9.5	9.5	7.95	-0.05	4.66
*	3	4000	862.57	100	108	-8	9.5	9.5	7.98	-0.02	4.64
	4	4000	1082.21	395.08	154.96	-8	9.5	9.5	8.33	0.33	3.7
	5	4000	1090.87	103	155.29	-8	9.5	9.5	8.37	0.37	3.67
	6	4000	1098.48	137	155.59	-8	9.5	9.5	8.43	0.43	3.64
	7	4000	1101.66	33	155.71	-8	9.5	9.5	8.45	0.45	3.63
*	8	4000	1746.77	26.48	229.06	-8	9.5	9.5	8.59	0.59	2.29
	9	4000	2076.57	75	266.73	-8	9.5	9.5	8.63	0.63	1.93
	10	4000	2080.63	70	266.82	-8	9.5	9.5	8.64	0.64	1.92
	1	4000	1188	0	159	-8	9.5	9.5	9	1	3.37
*	2	4000	967.23	111.61	108	-8	9.5	9.5	8.96	0.96	4.14
*	3	4000	969.52	100	108	-8	9.5	9.5	8.98	0.98	4.13
	4	4000	1224.4	395.08	160.37	-8	9.5	9.5	9.23	1.23	3.27
	5	4000	1230.61	103	160.6	-8	9.5	9.5	9.26	1.26	3.25
	6	4000	1236.02	137	160.8	-8	9.5	9.5	9.3	1.3	3.24
	7	4000	1238.33	33	160.89	-8	9.5	9.5	9.31	1.31	3.23
*	8	4000	1939.33	26.48	234.05	-8	9.5	9.5	9.42	1.42	2.06
	9	4000	2298.57	75	271.68	-8	9.5	9.5	9.45	1.45	1.74
	10	4000	2301.89	70	271.75	-8	9.5	9.5	9.46	1.46	1.74

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
	1	4000	1350	0	165	-8	9.5	9.5	10	2	2.96
*	2	4000	1075.48	111.61	108	-8	9.5	9.5	9.96	1.96	3.72
*	3	4000	1077.07	100	108	-8	9.5	9.5	9.97	1.97	3.71
	4	4000	1381.08	395.08	180	-8	9.5	9.5	10.17	2.17	2.9
	5	4000	1386.26	103	180	-8	9.5	9.5	10.2	2.2	2.89
	6	4000	1391.22	137	180	-8	9.5	9.5	10.23	2.23	2.88
	7	4000	1393.09	33	180	-8	9.5	9.5	10.24	2.24	2.87
*	8	4000	2157.03	26.48	252.5	-8	9.5	9.5	10.32	2.32	1.85
	9	4000	2547.75	75	290	-8	9.5	9.5	10.35	2.35	1.57
	10	4000	2551.9	70	290	-8	9.5	9.5	10.35	2.35	1.57
	1	4000	1530	0	180	-8	9.5	9.5	11	3	2.61
*	2	4000	1183.67	111.61	108	-8	9.5	9.5	10.96	2.96	3.38
*	3	4000	1184.85	100	108	-8	9.5	9.5	10.97	2.97	3.38
	4	4000	1553.12	395.08	180	-8	9.5	9.5	11.13	3.13	2.58
	5	4000	1556.85	103	180	-8	9.5	9.5	11.15	3.15	2.57
	6	4000	1560.06	137	180	-8	9.5	9.5	11.17	3.17	2.56
	7	4000	1561.81	33	180	-8	9.5	9.5	11.18	3.18	2.56
*	8	4000	2388.92	26.48	252.5	-8	9.5	9.5	11.24	3.24	1.67
	9	4000	2813.02	75	290	-8	9.5	9.5	11.26	3.26	1.42
	10	4000	2816.48	70	290	-8	9.5	9.5	11.26	3.26	1.42
	1	4000	1710	0	180	-8	9.5	9.5	12	4	2.34
*	2	4000	1291.95	111.61	108	-8	9.5	9.5	11.96	3.96	3.1
*	3	4000	1292.8	100	108	-8	9.5	9.5	11.97	3.97	3.09
	4	4000	1727.75	395.08	180	-8	9.5	9.5	12.1	4.1	2.32
	5	4000	1730.52	103	180	-8	9.5	9.5	12.11	4.11	2.31
	6	4000	1732.67	137	180	-8	9.5	9.5	12.13	4.13	2.31
	7	4000	1737.92	33	180	-8	9.5	9.5	12.16	4.16	2.3
*	8	4000	2632.49	26.48	252.5	-8	9.5	9.5	12.21	4.21	1.52
	9	4000	3092.06	75	290	-8	9.5	9.5	12.22	4.22	1.29
	10	4000	3094.95	70	290	-8	9.5	9.5	12.22	4.22	1.29
	1	4000	1890	0	180	-8	9.5	9.5	13	5	2.12
*	2	4000	1400.27	111.61	108	-8	9.5	9.5	12.97	4.97	2.86
*	3	4000	1400.9	100	108	-8	9.5	9.5	12.97	4.97	2.86
	4	4000	1904.01	395.08	180	-8	9.5	9.5	13.08	5.08	2.1
	5	4000	1906.12	103	180	-8	9.5	9.5	13.09	5.09	2.1
	6	4000	1907.61	137	180	-8	9.5	9.5	13.1	5.1	2.1
	7	4000	1915.47	33	180	-8	9.5	9.5	13.14	5.14	2.09
*	8	4000	2879.03	26.48	252.5	-8	9.5	9.5	13.18	5.18	1.39
	9	4000	3374.75	75	290	-8	9.5	9.5	13.2	5.2	1.19
	10	4000	3377.19	70	290	-8	9.5	9.5	13.2	5.2	1.18
	1	4000	2340	0	180	-8	9.5	9.5	15.5	7.5	1.71
*	2	4000	1671.03	111.61	108	-8	9.5	9.5	15.47	7.47	2.39
*	3	4000	1671.36	100	108	-8	9.5	9.5	15.48	7.48	2.39
*	4	4000	2348.51	395.08	180	-8	9.5	9.5	15.55	7.55	1.7
	5	4000	2349.69	103	180	-8	9.5	9.5	15.55	7.55	1.7
	6	4000	2350.36	137	180	-8	9.5	9.5	15.56	7.56	1.7
	7	4000	2362.34	33	180	-8	9.5	9.5	15.62	7.62	1.69
*	8	4000	3502	26.48	252.5	-8	9.5	9.5	15.65	7.65	1.14
	9	4000	4089.61	75	290	-8	9.5	9.5	15.66	7.66	0.98
	10	4000	4091.27	70	290	-8	9.5	9.5	15.66	7.66	0.98

COUSINS DISCHARGE CHANNEL

SUMMARY OUTPUT
 INPUT FILE DIS4K-9.DAT
 DISCHARGE: 4000 CFS
 CHANNEL BOTTOM AT -9.0

P.S. TO DSTRHN BRIDGE: TOP WIDTH OF CHANNEL TAKEN FROM DEI'S 50% SUBMITTAL
 DSTRHN BRIDGE TO HARVEY CANAL: TOP WIDTH OF CHANNEL TAKEN FROM CEEC'S LAYOUT
 ALL CROSS SECTIONS HAVE 15' BERM AT +2.0 ON THE LAPALCO BLVD SIDE
 SIDE SLOPE 1 VERTICAL TO 3 HORIZONTAL FROM +2.0 TO BOTTOM
 VERTICAL WALL CONSIDERED FROM +2.0 TO +9.5
 CULVERT (BETWEEN SECTIONS 2 AND 3) UNDER LAPALCO BRIDGE CONSIDERED 108' WIDE

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
	1	4000	984	0	147	-9	9.5	9.5	8	-1	4.07
*	2	4000	861.11	111.61	108	-9	9.5	9.5	7.97	-1.03	4.65
*	3	4000	864.84	100	108	-9	9.5	9.5	8	-1	4.63
	4	4000	1032.98	395.08	148.99	-9	9.5	9.5	8.33	-0.67	3.87
	5	4000	1041.62	103	149.33	-9	9.5	9.5	8.38	-0.62	3.84
	6	4000	1050.35	137	149.68	-9	9.5	9.5	8.45	-0.55	3.81
	7	4000	1053.96	33	149.83	-9	9.5	9.5	8.47	-0.53	3.8
	8	4000	1703.41	26.48	223.28	-9	9.5	9.5	8.63	-0.37	2.35
	9	4000	2034.99	75	260.96	-9	9.5	9.5	8.67	-0.33	1.97
	10	4000	2039.13	70	261.06	-9	9.5	9.5	8.67	-0.33	1.96
	1	4000	1134	0	153	-9	9.5	9.5	9	0	3.53
*	2	4000	968.65	111.61	108	-9	9.5	9.5	8.97	-0.03	4.13
*	3	4000	971.13	100	108	-9	9.5	9.5	8.99	-0.01	4.12
	4	4000	1169.45	395.08	154.38	-9	9.5	9.5	9.23	0.23	3.42
	5	4000	1175.67	103	154.63	-9	9.5	9.5	9.27	0.27	3.4
	6	4000	1181.87	137	154.87	-9	9.5	9.5	9.31	0.31	3.38
	7	4000	1184.46	33	154.97	-9	9.5	9.5	9.33	0.33	3.38
*	8	4000	1888.71	26.48	228.2	-9	9.5	9.5	9.45	0.45	2.12
	9	4000	2249.26	75	265.84	-9	9.5	9.5	9.48	0.48	1.78
	10	4000	2252.66	70	265.92	-9	9.5	9.5	9.49	0.49	1.78
	1	4000	1290	0	159	-9	9.5	9.5	10	1	3.1
*	2	4000	1076.54	111.61	108	-9	9.5	9.5	9.97	0.97	3.72
*	3	4000	1078.26	100	108	-9	9.5	9.5	9.98	0.98	3.71
	4	4000	1316.74	395.08	160.01	-9	9.5	9.5	10.17	1.17	3.04
	5	4000	1321.35	103	160.18	-9	9.5	9.5	10.19	1.19	3.03
	6	4000	1325.81	137	160.35	-9	9.5	9.5	10.22	1.22	3.02
	7	4000	1327.73	33	160.42	-9	9.5	9.5	10.24	1.24	3.01
*	8	4000	2092.24	26.48	233.49	-9	9.5	9.5	10.33	1.33	1.91
	9	4000	2484.49	75	271.1	-9	9.5	9.5	10.36	1.36	1.61
	10	4000	2487.28	70	271.16	-9	9.5	9.5	10.36	1.36	1.61

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
	1	4000	1452	0	165	-9	9.5	9.5	11	2	2.75
*	2	4000	1184.59	111.61	108	-9	9.5	9.5	10.97	1.97	3.38
*	3	4000	1185.82	100	108	-9	9.5	9.5	10.98	1.98	3.37
	4	4000	1475.63	395.08	180	-9	9.5	9.5	11.13	2.13	2.71
	5	4000	1479.61	103	180	-9	9.5	9.5	11.15	2.15	2.7
	6	4000	1483.76	137	180	-9	9.5	9.5	11.18	2.18	2.7
	7	4000	1485.36	33	180	-9	9.5	9.5	11.19	2.19	2.69
*	8	4000	2315.39	26.48	252.5	-9	9.5	9.5	11.26	2.26	1.73
	9	4000	2740.52	75	290	-9	9.5	9.5	11.28	2.28	1.46
	10	4000	2744.16	70	290	-9	9.5	9.5	11.28	2.28	1.46
	1	4000	1632	0	180	-9	9.5	9.5	12	3	2.45
*	2	4000	1292.63	111.61	108	-9	9.5	9.5	11.97	2.97	3.09
*	3	4000	1293.57	100	108	-9	9.5	9.5	11.98	2.98	3.09
	4	4000	1650.08	395.08	180	-9	9.5	9.5	12.1	3.1	2.42
	5	4000	1653.01	103	180	-9	9.5	9.5	12.11	3.11	2.42
	6	4000	1655.75	137	180	-9	9.5	9.5	12.13	3.13	2.42
	7	4000	1656.95	33	180	-9	9.5	9.5	12.14	3.14	2.41
*	8	4000	2552.03	26.48	252.5	-9	9.5	9.5	12.2	3.2	1.57
	9	4000	3011.48	75	290	-9	9.5	9.5	12.21	3.21	1.33
	10	4000	3014.54	70	290	-9	9.5	9.5	12.22	3.22	1.33
	1	4000	1812	0	180	-9	9.5	9.5	13	4	2.21
*	2	4000	1400.77	111.61	108	-9	9.5	9.5	12.97	3.97	2.86
*	3	4000	1401.46	100	108	-9	9.5	9.5	12.98	3.98	2.85
	4	4000	1826.2	395.08	180	-9	9.5	9.5	13.08	4.08	2.19
	5	4000	1828.42	103	180	-9	9.5	9.5	13.09	4.09	2.19
	6	4000	1830.3	137	180	-9	9.5	9.5	13.1	4.1	2.19
	7	4000	1834.31	33	180	-9	9.5	9.5	13.12	4.12	2.18
*	8	4000	2797.85	26.48	252.5	-9	9.5	9.5	13.17	4.17	1.43
	9	4000	3293.27	75	290	-9	9.5	9.5	13.18	4.18	1.21
	10	4000	3295.85	70	290	-9	9.5	9.5	13.19	4.19	1.21
	1	4000	1992	0	180	-9	9.5	9.5	14	5	2.01
*	2	4000	1508.96	111.61	108	-9	9.5	9.5	13.97	4.97	2.65
*	3	4000	1509.48	100	108	-9	9.5	9.5	13.98	4.98	2.65
	4	4000	2003.43	395.08	180	-9	9.5	9.5	14.06	5.06	2
	5	4000	2005.15	103	180	-9	9.5	9.5	14.07	5.07	1.99
	6	4000	2006.48	137	180	-9	9.5	9.5	14.08	5.08	1.99
	7	4000	2012.73	33	180	-9	9.5	9.5	14.12	5.12	1.99
*	8	4000	3045.95	26.48	252.5	-9	9.5	9.5	14.15	5.15	1.31
	9	4000	3577.84	75	290	-9	9.5	9.5	14.16	5.16	1.12
	10	4000	3580.03	70	290	-9	9.5	9.5	14.17	5.17	1.12
	1	4000	2442	0	180	-9	9.5	9.5	16.5	7.5	1.64
*	2	4000	1779.49	111.61	108	-9	9.5	9.5	16.48	7.48	2.25
*	3	4000	1779.78	100	108	-9	9.5	9.5	16.48	7.48	2.25
	4	4000	2449.2	395.08	180	-9	9.5	9.5	16.54	7.54	1.63
	5	4000	2450.2	103	180	-9	9.5	9.5	16.54	7.54	1.63
	6	4000	2450.81	137	180	-9	9.5	9.5	16.55	7.55	1.63
	7	4000	2460.46	33	180	-9	9.5	9.5	16.6	7.6	1.63
*	8	4000	3670.57	26.48	252.5	-9	9.5	9.5	16.63	7.63	1.09
	9	4000	4294.71	75	290	-9	9.5	9.5	16.63	7.63	0.93
	10	4000	4296.23	70	290	-9	9.5	9.5	16.64	7.64	0.93

COUSINS DISCHARGE CHANNEL

CASE 3

East of Harvey Canal Hurricane Protection - Design Memorandum No. 3 - Cousins Pumping Station Complex





Summary Table of Sensitivity Analyses

**Additional HEC-2 Model Runs for the Discharge Channel from the Discharge Basin through 100' D/S of Proposed Culvert Under Lapalco
For Q of 5,000 cfs, Channel Bottom of -9' NGVD, with Varying Contraction and Expansion Coefficients, and Channel Mannings 'n'**

Water Surface	Run 1		Run 2		Run 3		Run 4		Run 5		Run 6		Run 7		Run 8		Run 9	
Elevation at	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG	EG
Harvey Canal, ft. NGVD	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S	D/S	U/S
-1.00	-0.60	0.07	-0.60	0.28	-0.60	0.78	-0.60	0.13	-0.60	0.34	-0.60	0.81	-0.60	0.23	-0.60	0.43	-0.60	0.90
0.00	0.30	0.30	0.30	0.95	0.30	1.33	0.30	0.85	0.30	1.00	0.30	1.38	0.30	0.93	0.30	1.08	0.30	1.45
1.00	1.23	1.60	1.23	1.72	1.23	2.02	1.23	1.65	1.23	1.77	1.23	2.06	1.23	1.71	1.23	1.83	1.23	2.12
2.00	2.18	2.47	2.18	2.57	2.18	2.80	2.18	2.51	2.18	2.60	2.18	2.84	2.18	2.56	2.18	2.66	2.18	2.89
3.00	3.15	3.37	3.15	3.44	3.15	3.63	3.15	3.40	3.15	3.47	3.15	3.66	3.15	3.45	3.15	3.52	3.15	3.71
4.00	4.12	4.32	4.12	4.38	4.12	4.53	4.12	4.35	4.12	4.41	4.12	4.55	4.12	4.39	4.12	4.44	4.12	4.59
5.00	5.10	5.29	5.10	5.33	5.10	5.45	5.10	5.31	5.10	5.35	5.10	5.47	5.10	5.34	5.10	5.39	5.10	5.50
7.50	7.57	7.73	7.57	7.76	7.57	7.83	7.57	7.75	7.57	7.77	7.57	7.84	7.57	7.77	7.57	7.80	7.57	7.86

Legend:

	Mannings 'n'	Contraction coeff.	Expansion coeff.
Run 1	0.03	0.10	0.30
Run 2	0.04	0.10	0.30
Run 3	0.06	0.10	0.30
Run 4	0.03	0.30	0.50
Run 5	0.04	0.30	0.50
Run 6	0.06	0.30	0.50
Run 7	0.03	0.60	0.80
Run 8	0.04	0.60	0.80
Run 9	0.06	0.60	0.80

EG	Energy Gradient
D/S	Down Stream (100' South of the proposed culvert under Lapalco Bridge)
U/S	Up Stream (Approximately 100' feet from the Cousins Pump Station)
	Head loss (difference in EG between U/S and D/S) less than 6" (0.5')
	Head loss (difference in EG between U/S and D/S) between 6" and 9" (0.5' to 0.75')
	Head loss (difference in EG between U/S and D/S) between 9" and 1' (0.75' to 1')
	Head loss (difference in EG between U/S and D/S) over 12" (1')

RUN 1 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.03 0.1 0.3

INPUT FILE NAME: DI5K-9M1.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.01	-0.47	-0.99	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.98	0.4	-0.02	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.97	1.31	0.97	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.24	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.96	3.2	2.96	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	919.79	33.2	113.5	-9	9.5	9.5	8.1	-0.44	-0.9	5.44
4	5000	1027.66	33.2	113.5	-9	9.5	9.5	9.05	0.42	0.05	4.87
4	5000	1137.96	33.2	113.5	-9	9.5	9.5	10.03	1.33	1.03	4.39
4	5000	1249.55	33.2	113.5	-9	9.5	9.5	11.01	2.26	2.01	4
4	5000	1361.74	33.2	113.5	-9	9.5	9.5	12	3.21	3	3.67
4	5000	1474.48	33.2	113.5	-9	9.5	9.5	12.99	4.17	3.99	3.39
4	5000	1587.56	33.2	113.5	-9	9.5	9.5	13.99	5.14	4.99	3.15
4	5000	1870.18	33.2	113.5	-9	9.5	9.5	16.48	7.6	7.48	2.67

5	5000	994.13	49	121	-9	9.5	9.5	8.22	-0.39	-0.78	5.03
5	5000	1105.61	49	121	-9	9.5	9.5	9.14	0.45	0.14	4.52
5	5000	1220.86	49	121	-9	9.5	9.5	10.09	1.35	1.09	4.1
5	5000	1338.21	49	121	-9	9.5	9.5	11.06	2.28	2.06	3.74
5	5000	1456.65	49	121	-9	9.5	9.5	12.04	3.22	3.04	3.43
5	5000	1575.98	49	121	-9	9.5	9.5	13.02	4.18	4.02	3.17
5	5000	1694.66	49	121	-9	9.5	9.5	14.02	5.15	5.02	2.95
5	5000	1996.09	49	121	-9	9.5	9.5	16.5	7.6	7.5	2.5
6	5000	1099.09	48.7	132	-9	9.5	9.5	8.33	-0.35	-0.67	4.55
6	5000	1217.21	48.7	132	-9	9.5	9.5	9.22	0.48	0.22	4.11
6	5000	1340.52	48.7	132	-9	9.5	9.5	10.16	1.37	1.16	3.73
6	5000	1466.81	48.7	132	-9	9.5	9.5	11.11	2.29	2.11	3.41
6	5000	1594.76	48.7	132	-9	9.5	9.5	12.08	3.23	3.08	3.14
6	5000	1723.99	48.7	132	-9	9.5	9.5	13.06	4.19	4.06	2.9
6	5000	1854.06	48.7	132	-9	9.5	9.5	14.05	5.16	5.05	2.7
6	5000	2180.17	48.7	132	-9	9.5	9.5	16.52	7.61	7.52	2.29
7	5000	1248.29	56.6	148	-9	9.5	9.5	8.43	-0.32	-0.57	4.01
7	5000	1377.16	56.6	148	-9	9.5	9.5	9.31	0.51	0.31	3.63
7	5000	1512.83	56.6	148	-9	9.5	9.5	10.22	1.39	1.22	3.31
7	5000	1652.56	56.6	148	-9	9.5	9.5	11.17	2.31	2.17	3.03
7	5000	1794.61	56.6	148	-9	9.5	9.5	12.13	3.25	3.13	2.79
7	5000	1938.44	56.6	148	-9	9.5	9.5	13.1	4.2	4.1	2.58
7	5000	2083.45	56.6	148	-9	9.5	9.5	14.08	5.17	5.08	2.4
7	5000	2447.61	56.6	148	-9	9.5	9.5	16.55	7.61	7.55	2.04
8	5000	1382.22	53.8	162.5	-9	9.5	9.5	8.51	-0.29	-0.49	3.62
8	5000	1521.19	53.8	162.5	-9	9.5	9.5	9.36	0.53	0.36	3.29
8	5000	1668.3	53.8	162.5	-9	9.5	9.5	10.27	1.41	1.27	3
8	5000	1820.35	53.8	162.5	-9	9.5	9.5	11.2	2.32	2.2	2.75
8	5000	1975.29	53.8	162.5	-9	9.5	9.5	12.16	3.26	3.16	2.53
8	5000	2130.91	53.8	162.5	-9	9.5	9.5	13.12	4.21	4.12	2.35
8	5000	2289.72	53.8	162.5	-9	9.5	9.5	14.1	5.17	5.1	2.18
8	5000	2690.32	53.8	162.5	-9	9.5	9.5	16.56	7.62	7.56	1.86
9	5000	1483.59	47.7	173.5	-9	9.5	9.5	8.55	-0.27	-0.45	3.37
9	5000	1630.28	47.7	173.5	-9	9.5	9.5	9.4	0.54	0.4	3.07
9	5000	1784.52	47.7	173.5	-9	9.5	9.5	10.29	1.42	1.29	2.8
9	5000	1946.19	47.7	173.5	-9	9.5	9.5	11.22	2.33	2.22	2.57
9	5000	2111.13	47.7	173.5	-9	9.5	9.5	12.17	3.26	3.17	2.37
9	5000	2278.51	47.7	173.5	-9	9.5	9.5	13.14	4.21	4.14	2.19
9	5000	2446.75	47.7	173.5	-9	9.5	9.5	14.11	5.18	5.11	2.04
9	5000	2873.83	47.7	173.5	-9	9.5	9.5	16.57	7.62	7.57	1.74

10	5000	1542.72	40.9	180	-9	9.5	9.5	8.58	-0.26	-0.42	3.24
10	5000	1694.08	40.9	180	-9	9.5	9.5	9.42	0.55	0.42	2.95
10	5000	1854.3	40.9	180	-9	9.5	9.5	10.31	1.42	1.31	2.7
10	5000	2021.45	40.9	180	-9	9.5	9.5	11.24	2.33	2.24	2.47
10	5000	2192.14	40.9	180	-9	9.5	9.5	12.19	3.27	3.19	2.28
10	5000	2365.47	40.9	180	-9	9.5	9.5	13.15	4.22	4.15	2.11
10	5000	2540.6	40.9	180	-9	9.5	9.5	14.12	5.18	5.12	1.97
10	5000	2983.03	40.9	180	-9	9.5	9.5	16.58	7.62	7.58	1.68
11	5000	1545.72	35	180	-9	9.5	9.5	8.59	-0.25	-0.41	3.23
11	5000	1696.4	35	180	-9	9.5	9.5	9.42	0.56	0.42	2.95
11	5000	1856.94	35	180	-9	9.5	9.5	10.32	1.43	1.32	2.69
11	5000	2023.58	35	180	-9	9.5	9.5	11.24	2.34	2.24	2.47
11	5000	2193.89	35	180	-9	9.5	9.5	12.19	3.27	3.19	2.28
11	5000	2366.93	35	180	-9	9.5	9.5	13.15	4.22	4.15	2.11
11	5000	2541.85	35	180	-9	9.5	9.5	14.12	5.18	5.12	1.97
11	5000	2983.89	35	180	-9	9.5	9.5	16.58	7.62	7.58	1.68
12	5000	1053.82	33.1	149.82	-9	9.5	9.5	8.47	-0.18	-0.53	4.74
12	5000	1185.7	33.1	155.01	-9	9.5	9.5	9.34	0.61	0.34	4.22
12	5000	1329.76	33.1	160.49	-9	9.5	9.5	10.25	1.47	1.25	3.76
12	5000	1486.42	33.1	180	-9	9.5	9.5	11.19	2.37	2.19	3.36
12	5000	1659.05	33.1	180	-9	9.5	9.5	12.15	3.29	3.15	3.01
12	5000	1833.7	33.1	180	-9	9.5	9.5	13.12	4.24	4.12	2.73
12	5000	2009.76	33.1	180	-9	9.5	9.5	14.1	5.19	5.1	2.49
12	5000	2454.8	33.1	180	-9	9.5	9.5	16.56	7.63	7.56	2.04
13	5000	1065.68	103	150.3	-9	9.5	9.5	8.55	-0.11	-0.45	4.69
13	5000	1192.61	103	155.28	-9	9.5	9.5	9.39	0.66	0.39	4.19
13	5000	1334.88	103	160.68	-9	9.5	9.5	10.29	1.5	1.29	3.75
13	5000	1490.13	103	180	-9	9.5	9.5	11.22	2.4	2.22	3.36
13	5000	1661.73	103	180	-9	9.5	9.5	12.17	3.31	3.17	3.01
13	5000	1835.7	103	180	-9	9.5	9.5	13.14	4.25	4.14	2.72
13	5000	2011.28	103	180	-9	9.5	9.5	14.11	5.21	5.11	2.49
13	5000	2454.37	103	180	-9	9.5	9.5	16.57	7.63	7.57	2.04
14	5000	1079.84	137	150.86	-9	9.5	9.5	8.65	-0.02	-0.35	4.63
14	5000	1204.48	137	155.74	-9	9.5	9.5	9.46	0.73	0.46	4.15
14	5000	1343.61	137	161.01	-9	9.5	9.5	10.34	1.55	1.34	3.72
14	5000	1498.83	137	180	-9	9.5	9.5	11.26	2.43	2.26	3.34
14	5000	1667.75	137	180	-9	9.5	9.5	12.2	3.34	3.2	3
14	5000	1840.01	137	180	-9	9.5	9.5	13.16	4.27	4.16	2.72
14	5000	2014.47	137	180	-9	9.5	9.5	14.13	5.22	5.13	2.48
14	5000	2456.01	137	180	-9	9.5	9.5	16.58	7.64	7.58	2.04

15	5000	1086.21	33	151.11	-9	9.5	9.5	8.69	0.01	-0.31	4.6
15	5000	1209.14	33	155.92	-9	9.5	9.5	9.49	0.75	0.49	4.14
15	5000	1346.99	33	161.14	-9	9.5	9.5	10.36	1.57	1.36	3.71
15	5000	1501.62	33	180	-9	9.5	9.5	11.28	2.45	2.28	3.33
15	5000	1669.87	33	180	-9	9.5	9.5	12.21	3.35	3.21	2.99
15	5000	1846.62	33	180	-9	9.5	9.5	13.19	4.31	4.19	2.71
15	5000	2024.48	33	180	-9	9.5	9.5	14.18	5.28	5.18	2.47
15	5000	2470.97	33	180	-9	9.5	9.5	16.66	7.72	7.66	2.02
16	5000	1768.54	26.48	225.02	-9	9.5	9.5	8.92	0.04	-0.08	2.83
16	5000	1939.35	26.48	229.53	-9	9.5	9.5	9.67	0.77	0.67	2.58
16	5000	2132.08	26.48	234.51	-9	9.5	9.5	10.5	1.59	1.5	2.35
16	5000	2348.39	26.48	252.5	-9	9.5	9.5	11.39	2.46	2.39	2.13
16	5000	2578.3	26.48	252.5	-9	9.5	9.5	12.3	3.36	3.3	1.94
16	5000	2821.68	26.48	252.5	-9	9.5	9.5	13.27	4.31	4.27	1.77
16	5000	3067.82	26.48	252.5	-9	9.5	9.5	14.24	5.28	5.24	1.63
16	5000	3688.85	26.48	252.5	-9	9.5	9.5	16.7	7.73	7.7	1.36
17	5000	2117.25	75	262.85	-9	9.5	9.5	8.97	0.06	-0.03	2.36
17	5000	2311.13	75	267.23	-9	9.5	9.5	9.72	0.79	0.72	2.16
17	5000	2533.12	75	272.17	-9	9.5	9.5	10.54	1.6	1.54	1.97
17	5000	2781.79	75	290	-9	9.5	9.5	11.42	2.47	2.42	1.8
17	5000	3044.43	75	290	-9	9.5	9.5	12.32	3.37	3.32	1.64
17	5000	3322.93	75	290	-9	9.5	9.5	13.28	4.32	4.28	1.5
17	5000	3603.55	75	290	-9	9.5	9.5	14.26	5.29	5.26	1.39
17	5000	4316.03	75	290	-9	9.5	9.5	16.71	7.73	7.71	1.16
18	5000	2120.51	70	262.92	-9	9.5	9.5	8.98	0.07	-0.02	2.36
18	5000	2316.15	70	267.35	-9	9.5	9.5	9.72	0.8	0.72	2.16
18	5000	2537.31	70	272.27	-9	9.5	9.5	10.54	1.6	1.54	1.97
18	5000	2785.4	70	290	-9	9.5	9.5	11.42	2.47	2.42	1.8
18	5000	3047.4	70	290	-9	9.5	9.5	12.33	3.37	3.33	1.64
18	5000	3325.37	70	290	-9	9.5	9.5	13.29	4.32	4.29	1.5
18	5000	3606.92	70	290	-9	9.5	9.5	14.26	5.29	5.26	1.39
18	5000	4318.37	70	290	-9	9.5	9.5	16.71	7.73	7.71	1.16

RUN 2 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL
SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.04 0.1 0.3

INPUT FILE NAME: DI5K-9M2.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.01	-0.47	-0.99	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.99	0.4	-0.01	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.31	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.14	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	923.9	33.2	113.5	-9	9.5	9.5	8.14	-0.41	-0.86	5.41
4	5000	1030.43	33.2	113.5	-9	9.5	9.5	9.08	0.44	0.08	4.85
4	5000	1139.92	33.2	113.5	-9	9.5	9.5	10.04	1.34	1.04	4.39
4	5000	1250.99	33.2	113.5	-9	9.5	9.5	11.02	2.27	2.02	4
4	5000	1362.82	33.2	113.5	-9	9.5	9.5	12.01	3.22	3.01	3.67
4	5000	1475.32	33.2	113.5	-9	9.5	9.5	13	4.18	4	3.39
4	5000	1588.23	33.2	113.5	-9	9.5	9.5	13.99	5.15	4.99	3.15
4	5000	1870.5	33.2	113.5	-9	9.5	9.5	16.49	7.6	7.49	2.67

5	5000	1002.36	49	121	-9	9.5	9.5	8.28	-0.33	-0.72	4.99
5	5000	1111.29	49	121	-9	9.5	9.5	9.18	0.5	0.18	4.5
5	5000	1224.92	49	121	-9	9.5	9.5	10.12	1.38	1.12	4.08
5	5000	1341.21	49	121	-9	9.5	9.5	11.08	2.3	2.08	3.73
5	5000	1458.93	49	121	-9	9.5	9.5	12.06	3.24	3.06	3.43
5	5000	1577.75	49	121	-9	9.5	9.5	13.04	4.2	4.04	3.17
5	5000	1696.11	49	121	-9	9.5	9.5	14.03	5.16	5.03	2.95
5	5000	1996.96	49	121	-9	9.5	9.5	16.51	7.61	7.51	2.5
6	5000	1111.19	48.7	132	-9	9.5	9.5	8.42	-0.27	-0.58	4.5
6	5000	1225.72	48.7	132	-9	9.5	9.5	9.29	0.54	0.29	4.08
6	5000	1346.67	48.7	132	-9	9.5	9.5	10.2	1.42	1.2	3.71
6	5000	1471.39	48.7	132	-9	9.5	9.5	11.15	2.33	2.15	3.4
6	5000	1598.25	48.7	132	-9	9.5	9.5	12.11	3.26	3.11	3.13
6	5000	1726.7	48.7	132	-9	9.5	9.5	13.08	4.21	4.08	2.9
6	5000	1856.22	48.7	132	-9	9.5	9.5	14.06	5.17	5.06	2.69
6	5000	2181.51	48.7	132	-9	9.5	9.5	16.53	7.62	7.53	2.29
7	5000	1264.79	56.6	148	-9	9.5	9.5	8.55	-0.21	-0.45	3.95
7	5000	1388.93	56.6	148	-9	9.5	9.5	9.38	0.59	0.38	3.6
7	5000	1521.42	56.6	148	-9	9.5	9.5	10.28	1.45	1.28	3.29
7	5000	1658.98	56.6	148	-9	9.5	9.5	11.21	2.35	2.21	3.01
7	5000	1799.53	56.6	148	-9	9.5	9.5	12.16	3.28	3.16	2.78
7	5000	1942.28	56.6	148	-9	9.5	9.5	13.12	4.23	4.12	2.57
7	5000	2086.51	56.6	148	-9	9.5	9.5	14.1	5.19	5.1	2.4
7	5000	2449.51	56.6	148	-9	9.5	9.5	16.56	7.62	7.56	2.04
8	5000	1402.63	53.8	162.5	-9	9.5	9.5	8.63	-0.17	-0.37	3.56
8	5000	1535.89	53.8	162.5	-9	9.5	9.5	9.45	0.62	0.45	3.26
8	5000	1679.1	53.8	162.5	-9	9.5	9.5	10.33	1.47	1.33	2.98
8	5000	1828.45	53.8	162.5	-9	9.5	9.5	11.25	2.37	2.25	2.73
8	5000	1979.88	53.8	162.5	-9	9.5	9.5	12.19	3.29	3.19	2.53
8	5000	2135.88	53.8	162.5	-9	9.5	9.5	13.15	4.24	4.15	2.34
8	5000	2293.68	53.8	162.5	-9	9.5	9.5	14.12	5.2	5.12	2.18
8	5000	2692.71	53.8	162.5	-9	9.5	9.5	16.58	7.63	7.58	1.86
9	5000	1507.16	47.7	173.5	-9	9.5	9.5	8.69	-0.14	-0.31	3.32
9	5000	1645.64	47.7	173.5	-9	9.5	9.5	9.49	0.64	0.49	3.04
9	5000	1797.26	47.7	173.5	-9	9.5	9.5	10.37	1.49	1.37	2.78
9	5000	1955.78	47.7	173.5	-9	9.5	9.5	11.28	2.38	2.28	2.56
9	5000	2118.49	47.7	173.5	-9	9.5	9.5	12.22	3.3	3.22	2.36
9	5000	2284.28	47.7	173.5	-9	9.5	9.5	13.17	4.25	4.17	2.19
9	5000	2451.4	47.7	173.5	-9	9.5	9.5	14.14	5.2	5.14	2.04
9	5000	2876.65	47.7	173.5	-9	9.5	9.5	16.59	7.63	7.59	1.74

10	5000	1568.72	40.9	180	-9	9.5	9.5	8.72	-0.12	-0.28	3.19
10	5000	1712.99	40.9	180	-9	9.5	9.5	9.52	0.65	0.52	2.92
10	5000	1868.36	40.9	180	-9	9.5	9.5	10.39	1.5	1.39	2.68
10	5000	2032.05	40.9	180	-9	9.5	9.5	11.3	2.39	2.3	2.46
10	5000	2200.3	40.9	180	-9	9.5	9.5	12.23	3.31	3.23	2.27
10	5000	2371.87	40.9	180	-9	9.5	9.5	13.18	4.25	4.18	2.11
10	5000	2545.71	40.9	180	-9	9.5	9.5	14.15	5.21	5.15	1.96
10	5000	2986.13	40.9	180	-9	9.5	9.5	16.59	7.64	7.59	1.67
11	5000	1572.85	35	180	-9	9.5	9.5	8.74	-0.1	-0.26	3.18
11	5000	1716.22	35	180	-9	9.5	9.5	9.53	0.67	0.53	2.91
11	5000	1871.61	35	180	-9	9.5	9.5	10.4	1.51	1.4	2.67
11	5000	2034.66	35	180	-9	9.5	9.5	11.3	2.4	2.3	2.46
11	5000	2202.43	35	180	-9	9.5	9.5	12.24	3.32	3.24	2.27
11	5000	2373.63	35	180	-9	9.5	9.5	13.19	4.26	4.19	2.11
11	5000	2547.19	35	180	-9	9.5	9.5	14.15	5.21	5.15	1.96
11	5000	2987.13	35	180	-9	9.5	9.5	16.6	7.64	7.6	1.67
12	5000	1078.94	33.1	150.83	-9	9.5	9.5	8.64	-0.03	-0.36	4.63
12	5000	1204.47	33.1	155.74	-9	9.5	9.5	9.46	0.72	0.46	4.15
12	5000	1344.04	33.1	161.03	-9	9.5	9.5	10.34	1.55	1.34	3.72
12	5000	1498.47	33.1	180	-9	9.5	9.5	11.26	2.43	2.26	3.34
12	5000	1668.27	33.1	180	-9	9.5	9.5	12.2	3.34	3.2	3
12	5000	1840.89	33.1	180	-9	9.5	9.5	13.16	4.28	4.16	2.72
12	5000	2015.48	33.1	180	-9	9.5	9.5	14.13	5.23	5.13	2.48
12	5000	2458.21	33.1	180	-9	9.5	9.5	16.58	7.65	7.58	2.03
13	5000	1098.43	103	151.6	-9	9.5	9.5	8.77	0.09	-0.23	4.55
13	5000	1218.77	103	156.29	-9	9.5	9.5	9.55	0.81	0.55	4.1
13	5000	1354.62	103	161.42	-9	9.5	9.5	10.4	1.61	1.4	3.69
13	5000	1506.37	103	180	-9	9.5	9.5	11.31	2.48	2.31	3.32
13	5000	1673.91	103	180	-9	9.5	9.5	12.24	3.38	3.24	2.99
13	5000	1844.4	103	180	-9	9.5	9.5	13.19	4.3	4.19	2.71
13	5000	2018.17	103	180	-9	9.5	9.5	14.15	5.25	5.15	2.48
13	5000	2458.47	103	180	-9	9.5	9.5	16.59	7.66	7.59	2.03
14	5000	1116.49	137	152.31	-9	9.5	9.5	8.89	0.2	-0.11	4.48
14	5000	1232.27	137	156.81	-9	9.5	9.5	9.63	0.89	0.63	4.06
14	5000	1366.41	137	161.86	-9	9.5	9.5	10.47	1.67	1.47	3.66
14	5000	1518.53	137	180	-9	9.5	9.5	11.36	2.53	2.36	3.29
14	5000	1682.42	137	180	-9	9.5	9.5	12.27	3.41	3.27	2.97
14	5000	1851.96	137	180	-9	9.5	9.5	13.21	4.33	4.21	2.7
14	5000	2023.76	137	180	-9	9.5	9.5	14.17	5.26	5.17	2.47
14	5000	2461.37	137	180	-9	9.5	9.5	16.6	7.67	7.6	2.03

15	5000	1121.39	33	152.5	-9	9.5	9.5	8.92	0.23	-0.08	4.46
15	5000	1236.02	33	156.95	-9	9.5	9.5	9.66	0.91	0.66	4.05
15	5000	1367.68	33	161.9	-9	9.5	9.5	10.48	1.69	1.48	3.66
15	5000	1519.47	33	180	-9	9.5	9.5	11.37	2.54	2.37	3.29
15	5000	1683.74	33	180	-9	9.5	9.5	12.29	3.42	3.29	2.97
15	5000	1857.18	33	180	-9	9.5	9.5	13.25	4.36	4.25	2.69
15	5000	2032.69	33	180	-9	9.5	9.5	14.23	5.32	5.23	2.46
15	5000	2475.6	33	180	-9	9.5	9.5	16.69	7.75	7.69	2.02
16	5000	1817.25	26.48	226.32	-9	9.5	9.5	9.14	0.25	0.14	2.75
16	5000	1976.87	26.48	230.51	-9	9.5	9.5	9.83	0.93	0.83	2.53
16	5000	2161.05	26.48	235.25	-9	9.5	9.5	10.63	1.71	1.63	2.31
16	5000	2372.68	26.48	252.5	-9	9.5	9.5	11.49	2.56	2.49	2.11
16	5000	2597.34	26.48	252.5	-9	9.5	9.5	12.38	3.44	3.38	1.93
16	5000	2836.27	26.48	252.5	-9	9.5	9.5	13.32	4.37	4.32	1.76
16	5000	3079.22	26.48	252.5	-9	9.5	9.5	14.29	5.33	5.29	1.62
16	5000	3695.31	26.48	252.5	-9	9.5	9.5	16.73	7.75	7.73	1.35
17	5000	2170.55	75	264.06	-9	9.5	9.5	9.19	0.27	0.19	2.3
17	5000	2354.34	75	268.2	-9	9.5	9.5	9.88	0.95	0.88	2.12
17	5000	2566.48	75	272.91	-9	9.5	9.5	10.66	1.72	1.66	1.95
17	5000	2809.51	75	290	-9	9.5	9.5	11.52	2.56	2.52	1.78
17	5000	3066.21	75	290	-9	9.5	9.5	12.4	3.44	3.4	1.63
17	5000	3339.63	75	290	-9	9.5	9.5	13.34	4.38	4.34	1.5
17	5000	3616.61	75	290	-9	9.5	9.5	14.3	5.33	5.3	1.38
17	5000	4323.44	75	290	-9	9.5	9.5	16.74	7.76	7.74	1.16
18	5000	2176.21	70	264.19	-9	9.5	9.5	9.2	0.28	0.2	2.3
18	5000	2359.18	70	268.31	-9	9.5	9.5	9.88	0.95	0.88	2.12
18	5000	2570.57	70	273	-9	9.5	9.5	10.67	1.72	1.67	1.95
18	5000	2813.04	70	290	-9	9.5	9.5	11.52	2.57	2.52	1.78
18	5000	3069.13	70	290	-9	9.5	9.5	12.4	3.44	3.4	1.63
18	5000	3342.05	70	290	-9	9.5	9.5	13.34	4.38	4.34	1.5
18	5000	3619.96	70	290	-9	9.5	9.5	14.3	5.33	5.3	1.38
18	5000	4325.77	70	290	-9	9.5	9.5	16.74	7.76	7.74	1.16

RUN 3 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.06 0.1 0.3

INPUT FILE NAME: DI5K-9M3.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.89	100	108	-9	9.5	9.5	8.02	-0.46	-0.98	5.77
3	5000	970.53	100	108	-9	9.5	9.5	9	0.41	0	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.32	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.97	4.16	3.97	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.97	5.14	4.97	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	933.85	33.2	113.5	-9	9.5	9.5	8.23	-0.33	-0.77	5.35
4	5000	1037.24	33.2	113.5	-9	9.5	9.5	9.14	0.5	0.14	4.82
4	5000	1144.75	33.2	113.5	-9	9.5	9.5	10.09	1.38	1.09	4.37
4	5000	1254.55	33.2	113.5	-9	9.5	9.5	11.05	2.3	2.05	3.99
4	5000	1365.52	33.2	113.5	-9	9.5	9.5	12.03	3.24	3.03	3.66
4	5000	1477.41	33.2	113.5	-9	9.5	9.5	13.02	4.19	4.02	3.38
4	5000	1589.89	33.2	113.5	-9	9.5	9.5	14.01	5.16	5.01	3.14
4	5000	1871.29	33.2	113.5	-9	9.5	9.5	16.5	7.61	7.5	2.67

5	5000	1023.23	49	121	-9	9.5	9.5	8.46	-0.17	-0.54	4.89
5	5000	1126.02	49	121	-9	9.5	9.5	9.31	0.61	0.31	4.44
5	5000	1235.58	49	121	-9	9.5	9.5	10.21	1.47	1.21	4.05
5	5000	1349.14	49	121	-9	9.5	9.5	11.15	2.36	2.15	3.71
5	5000	1464.98	49	121	-9	9.5	9.5	12.11	3.29	3.11	3.41
5	5000	1581.26	49	121	-9	9.5	9.5	13.08	4.23	4.08	3.16
5	5000	1699.99	49	121	-9	9.5	9.5	14.06	5.19	5.06	2.94
5	5000	1999.31	49	121	-9	9.5	9.5	16.53	7.63	7.53	2.5
6	5000	1141.99	48.7	132	-9	9.5	9.5	8.65	-0.05	-0.35	4.38
6	5000	1247.94	48.7	132	-9	9.5	9.5	9.45	0.7	0.45	4.01
6	5000	1362.98	48.7	132	-9	9.5	9.5	10.33	1.53	1.33	3.67
6	5000	1483.63	48.7	132	-9	9.5	9.5	11.24	2.42	2.24	3.37
6	5000	1607.64	48.7	132	-9	9.5	9.5	12.18	3.33	3.18	3.11
6	5000	1734.06	48.7	132	-9	9.5	9.5	13.14	4.27	4.14	2.88
6	5000	1860.76	48.7	132	-9	9.5	9.5	14.11	5.22	5.11	2.69
6	5000	2185.17	48.7	132	-9	9.5	9.5	16.56	7.64	7.56	2.29
7	5000	1306.63	56.6	148	-9	9.5	9.5	8.83	0.06	-0.17	3.83
7	5000	1419.69	56.6	148	-9	9.5	9.5	9.59	0.79	0.59	3.52
7	5000	1544.28	56.6	148	-9	9.5	9.5	10.43	1.6	1.43	3.24
7	5000	1676.27	56.6	148	-9	9.5	9.5	11.33	2.46	2.33	2.98
7	5000	1812.87	56.6	148	-9	9.5	9.5	12.25	3.37	3.25	2.76
7	5000	1952.76	56.6	148	-9	9.5	9.5	13.19	4.3	4.19	2.56
7	5000	2093.4	56.6	148	-9	9.5	9.5	14.15	5.24	5.15	2.39
7	5000	2454.75	56.6	148	-9	9.5	9.5	16.59	7.66	7.59	2.04
8	5000	1454.21	53.8	162.5	-9	9.5	9.5	8.95	0.13	-0.05	3.44
8	5000	1574.26	53.8	162.5	-9	9.5	9.5	9.69	0.84	0.69	3.18
8	5000	1706.23	53.8	162.5	-9	9.5	9.5	10.51	1.64	1.51	2.93
8	5000	1848.88	53.8	162.5	-9	9.5	9.5	11.39	2.5	2.39	2.7
8	5000	1997.16	53.8	162.5	-9	9.5	9.5	12.3	3.4	3.3	2.5
8	5000	2149.49	53.8	162.5	-9	9.5	9.5	13.23	4.32	4.23	2.33
8	5000	2304.56	53.8	162.5	-9	9.5	9.5	14.19	5.26	5.19	2.17
8	5000	2698.57	53.8	162.5	-9	9.5	9.5	16.62	7.67	7.62	1.85
9	5000	1565.18	47.7	173.5	-9	9.5	9.5	9.03	0.19	0.03	3.19
9	5000	1690.67	47.7	173.5	-9	9.5	9.5	9.75	0.89	0.75	2.96
9	5000	1831.15	47.7	173.5	-9	9.5	9.5	10.56	1.68	1.56	2.73
9	5000	1981.64	47.7	173.5	-9	9.5	9.5	11.43	2.53	2.43	2.52
9	5000	2137.72	47.7	173.5	-9	9.5	9.5	12.33	3.42	3.33	2.34
9	5000	2299.38	47.7	173.5	-9	9.5	9.5	13.26	4.33	4.26	2.17
9	5000	2464.2	47.7	173.5	-9	9.5	9.5	14.21	5.27	5.21	2.03
9	5000	2884.43	47.7	173.5	-9	9.5	9.5	16.63	7.68	7.63	1.73

10	5000	1633.31	40.9	180	-9	9.5	9.5	9.08	0.23	0.08	3.06
10	5000	1761.57	40.9	180	-9	9.5	9.5	9.79	0.92	0.79	2.84
10	5000	1905.78	40.9	180	-9	9.5	9.5	10.59	1.7	1.59	2.62
10	5000	2060.67	40.9	180	-9	9.5	9.5	11.45	2.55	2.45	2.43
10	5000	2222.51	40.9	180	-9	9.5	9.5	12.35	3.43	3.35	2.25
10	5000	2389.41	40.9	180	-9	9.5	9.5	13.28	4.35	4.28	2.09
10	5000	2559.77	40.9	180	-9	9.5	9.5	14.22	5.28	5.22	1.95
10	5000	2994.69	40.9	180	-9	9.5	9.5	16.64	7.68	7.64	1.67
11	5000	1640.91	35	180	-9	9.5	9.5	9.12	0.26	0.12	3.05
11	5000	1767.67	35	180	-9	9.5	9.5	9.82	0.94	0.82	2.83
11	5000	1910.64	35	180	-9	9.5	9.5	10.61	1.72	1.61	2.62
11	5000	2064.57	35	180	-9	9.5	9.5	11.47	2.56	2.47	2.42
11	5000	2225.69	35	180	-9	9.5	9.5	12.36	3.44	3.36	2.25
11	5000	2392.01	35	180	-9	9.5	9.5	13.29	4.36	4.29	2.09
11	5000	2561.93	35	180	-9	9.5	9.5	14.23	5.29	5.23	1.95
11	5000	2996.1	35	180	-9	9.5	9.5	16.64	7.69	7.64	1.67
12	5000	1142.1	33.1	153.32	-9	9.5	9.5	9.05	0.35	0.05	4.38
12	5000	1253.36	33.1	157.61	-9	9.5	9.5	9.77	1.02	0.77	3.99
12	5000	1382.1	33.1	162.44	-9	9.5	9.5	10.57	1.78	1.57	3.62
12	5000	1530.92	33.1	180	-9	9.5	9.5	11.44	2.6	2.44	3.27
12	5000	1693.35	33.1	180	-9	9.5	9.5	12.34	3.48	3.34	2.95
12	5000	1860.62	33.1	180	-9	9.5	9.5	13.27	4.38	4.27	2.69
12	5000	2031.24	33.1	180	-9	9.5	9.5	14.22	5.31	5.22	2.46
12	5000	2467.67	33.1	180	-9	9.5	9.5	16.64	7.7	7.64	2.03
13	5000	1178.52	103	154.74	-9	9.5	9.5	9.29	0.57	0.29	4.24
13	5000	1281.69	103	158.69	-9	9.5	9.5	9.95	1.18	0.95	3.9
13	5000	1403.92	103	163.24	-9	9.5	9.5	10.71	1.9	1.71	3.56
13	5000	1550.53	103	180	-9	9.5	9.5	11.55	2.71	2.55	3.22
13	5000	1707.49	103	180	-9	9.5	9.5	12.42	3.55	3.42	2.93
13	5000	1869.65	103	180	-9	9.5	9.5	13.33	4.44	4.33	2.67
13	5000	2038.12	103	180	-9	9.5	9.5	14.26	5.36	5.26	2.45
13	5000	2469.85	103	180	-9	9.5	9.5	16.66	7.72	7.66	2.02
14	5000	1198.47	137	155.51	-9	9.5	9.5	9.42	0.69	0.42	4.17
14	5000	1297.57	137	159.29	-9	9.5	9.5	10.05	1.28	1.05	3.85
14	5000	1416.36	137	163.7	-9	9.5	9.5	10.78	1.98	1.78	3.53
14	5000	1561.71	137	180	-9	9.5	9.5	11.61	2.77	2.61	3.2
14	5000	1715.65	137	180	-9	9.5	9.5	12.46	3.6	3.46	2.91
14	5000	1877.14	137	180	-9	9.5	9.5	13.36	4.47	4.36	2.66
14	5000	2043.72	137	180	-9	9.5	9.5	14.29	5.38	5.29	2.45
14	5000	2474.79	137	180	-9	9.5	9.5	16.67	7.74	7.67	2.02

15	5000	1202.49	33	155.66	-9	9.5	9.5	9.44	0.71	0.44	4.16
15	5000	1300.83	33	159.41	-9	9.5	9.5	10.07	1.3	1.07	3.84
15	5000	1418.98	33	163.79	-9	9.5	9.5	10.8	1.99	1.8	3.52
15	5000	1563.93	33	180	-9	9.5	9.5	11.62	2.78	2.62	3.2
15	5000	1719.02	33	180	-9	9.5	9.5	12.48	3.61	3.48	2.91
15	5000	1884.48	33	180	-9	9.5	9.5	13.4	4.51	4.4	2.65
15	5000	2054.17	33	180	-9	9.5	9.5	14.35	5.44	5.35	2.43
15	5000	2487.89	33	180	-9	9.5	9.5	16.75	7.82	7.75	2.01
16	5000	1930.07	26.48	229.29	-9	9.5	9.5	9.63	0.74	0.63	2.59
16	5000	2067.48	26.48	232.86	-9	9.5	9.5	10.23	1.32	1.23	2.42
16	5000	2232.88	26.48	237.08	-9	9.5	9.5	10.93	2.01	1.93	2.24
16	5000	2433.3	26.48	252.5	-9	9.5	9.5	11.73	2.79	2.73	2.05
16	5000	2645.83	26.48	252.5	-9	9.5	9.5	12.57	3.63	3.57	1.89
16	5000	2873.99	26.48	252.5	-9	9.5	9.5	13.47	4.52	4.47	1.74
16	5000	3109.01	26.48	252.5	-9	9.5	9.5	14.4	5.44	5.4	1.61
16	5000	3712.44	26.48	252.5	-9	9.5	9.5	16.79	7.82	7.79	1.35
17	5000	2300.44	75	266.99	-9	9.5	9.5	9.68	0.75	0.68	2.17
17	5000	2458.72	75	270.53	-9	9.5	9.5	10.26	1.33	1.26	2.03
17	5000	2649.19	75	274.72	-9	9.5	9.5	10.96	2.02	1.96	1.89
17	5000	2878.72	75	290	-9	9.5	9.5	11.75	2.8	2.75	1.74
17	5000	3121.67	75	290	-9	9.5	9.5	12.59	3.63	3.59	1.6
17	5000	3382.82	75	290	-9	9.5	9.5	13.49	4.52	4.49	1.48
17	5000	3650.77	75	290	-9	9.5	9.5	14.42	5.45	5.42	1.37
17	5000	4343.1	75	290	-9	9.5	9.5	16.8	7.82	7.8	1.15
18	5000	2305.5	70	267.11	-9	9.5	9.5	9.68	0.76	0.68	2.17
18	5000	2463.17	70	270.63	-9	9.5	9.5	10.27	1.33	1.27	2.03
18	5000	2653.03	70	274.8	-9	9.5	9.5	10.97	2.02	1.97	1.88
18	5000	2882.07	70	290	-9	9.5	9.5	11.76	2.8	2.76	1.73
18	5000	3124.47	70	290	-9	9.5	9.5	12.59	3.63	3.59	1.6
18	5000	3385.18	70	290	-9	9.5	9.5	13.49	4.53	4.49	1.48
18	5000	3654.06	70	290	-9	9.5	9.5	14.42	5.45	5.42	1.37
18	5000	4345.41	70	290	-9	9.5	9.5	16.8	7.83	7.8	1.15

RUN 4 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.03 0.3 0.5

INPUT FILE NAME: DI5K-9M4.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.01	-0.47	-0.99	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.98	0.4	-0.02	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.97	1.31	0.97	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.24	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.96	3.2	2.96	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	921.56	33.2	113.5	-9	9.5	9.5	8.12	-0.42	-0.88	5.43
4	5000	1028.87	33.2	113.5	-9	9.5	9.5	9.06	0.43	0.06	4.86
4	5000	1138.85	33.2	113.5	-9	9.5	9.5	10.03	1.33	1.03	4.39
4	5000	1250.25	33.2	113.5	-9	9.5	9.5	11.02	2.26	2.02	4
4	5000	1362.3	33.2	113.5	-9	9.5	9.5	12	3.21	3	3.67
4	5000	1474.94	33.2	113.5	-9	9.5	9.5	13	4.17	4	3.39
4	5000	1587.96	33.2	113.5	-9	9.5	9.5	13.99	5.14	4.99	3.15
4	5000	1870.31	33.2	113.5	-9	9.5	9.5	16.49	7.6	7.49	2.67

5	5000	997.74	49	121	-9	9.5	9.5	8.25	-0.36	-0.75	5.01
5	5000	1108.18	49	121	-9	9.5	9.5	9.16	0.47	0.16	4.51
5	5000	1222.81	49	121	-9	9.5	9.5	10.11	1.37	1.11	4.09
5	5000	1339.76	49	121	-9	9.5	9.5	11.07	2.29	2.07	3.73
5	5000	1457.91	49	121	-9	9.5	9.5	12.05	3.23	3.05	3.43
5	5000	1577.03	49	121	-9	9.5	9.5	13.03	4.19	4.03	3.17
5	5000	1696.78	49	121	-9	9.5	9.5	14.02	5.16	5.02	2.95
5	5000	1996.54	49	121	-9	9.5	9.5	16.51	7.61	7.51	2.5
6	5000	1104.95	48.7	132	-9	9.5	9.5	8.37	-0.31	-0.63	4.53
6	5000	1221.53	48.7	132	-9	9.5	9.5	9.25	0.51	0.25	4.09
6	5000	1343.85	48.7	132	-9	9.5	9.5	10.18	1.4	1.18	3.72
6	5000	1469.48	48.7	132	-9	9.5	9.5	11.13	2.31	2.13	3.4
6	5000	1596.95	48.7	132	-9	9.5	9.5	12.1	3.25	3.1	3.13
6	5000	1725.82	48.7	132	-9	9.5	9.5	13.07	4.2	4.07	2.9
6	5000	1855.62	48.7	132	-9	9.5	9.5	14.06	5.17	5.06	2.69
6	5000	2181.06	48.7	132	-9	9.5	9.5	16.53	7.61	7.53	2.29
7	5000	1256.92	56.6	148	-9	9.5	9.5	8.49	-0.26	-0.51	3.98
7	5000	1383.67	56.6	148	-9	9.5	9.5	9.35	0.55	0.35	3.61
7	5000	1517.93	56.6	148	-9	9.5	9.5	10.26	1.42	1.26	3.29
7	5000	1656.68	56.6	148	-9	9.5	9.5	11.19	2.34	2.19	3.02
7	5000	1798.02	56.6	148	-9	9.5	9.5	12.15	3.27	3.15	2.78
7	5000	1941.3	56.6	148	-9	9.5	9.5	13.12	4.22	4.12	2.58
7	5000	2085.9	56.6	148	-9	9.5	9.5	14.09	5.18	5.09	2.4
7	5000	2450.67	56.6	148	-9	9.5	9.5	16.56	7.62	7.56	2.04
8	5000	1393.05	53.8	162.5	-9	9.5	9.5	8.57	-0.23	-0.43	3.59
8	5000	1529.47	53.8	162.5	-9	9.5	9.5	9.41	0.58	0.41	3.27
8	5000	1674.85	53.8	162.5	-9	9.5	9.5	10.31	1.45	1.31	2.99
8	5000	1825.66	53.8	162.5	-9	9.5	9.5	11.23	2.35	2.23	2.74
8	5000	1979.7	53.8	162.5	-9	9.5	9.5	12.18	3.28	3.18	2.53
8	5000	2136.13	53.8	162.5	-9	9.5	9.5	13.15	4.23	4.15	2.34
8	5000	2292.65	53.8	162.5	-9	9.5	9.5	14.12	5.19	5.12	2.18
8	5000	2692.4	53.8	162.5	-9	9.5	9.5	16.58	7.63	7.58	1.86
9	5000	1495.96	47.7	173.5	-9	9.5	9.5	8.62	-0.2	-0.38	3.34
9	5000	1639.82	47.7	173.5	-9	9.5	9.5	9.45	0.6	0.45	3.05
9	5000	1793.68	47.7	173.5	-9	9.5	9.5	10.34	1.46	1.34	2.79
9	5000	1952.1	47.7	173.5	-9	9.5	9.5	11.26	2.36	2.26	2.56
9	5000	2116.04	47.7	173.5	-9	9.5	9.5	12.2	3.29	3.2	2.36
9	5000	2282.66	47.7	173.5	-9	9.5	9.5	13.16	4.24	4.16	2.19
9	5000	2451.11	47.7	173.5	-9	9.5	9.5	14.13	5.2	5.13	2.04
9	5000	2876.24	47.7	173.5	-9	9.5	9.5	16.59	7.63	7.59	1.74

10	5000	1555.7	40.9	180	-9	9.5	9.5	8.65	-0.19	-0.35	3.21
10	5000	1704.12	40.9	180	-9	9.5	9.5	9.47	0.61	0.47	2.93
10	5000	1863.12	40.9	180	-9	9.5	9.5	10.36	1.47	1.36	2.68
10	5000	2027.83	40.9	180	-9	9.5	9.5	11.27	2.37	2.27	2.47
10	5000	2197.44	40.9	180	-9	9.5	9.5	12.22	3.3	3.22	2.28
10	5000	2369.96	40.9	180	-9	9.5	9.5	13.17	4.24	4.17	2.11
10	5000	2544.46	40.9	180	-9	9.5	9.5	14.14	5.2	5.14	1.97
10	5000	2985.77	40.9	180	-9	9.5	9.5	16.59	7.64	7.59	1.67
11	5000	1558.88	35	180	-9	9.5	9.5	8.66	-0.18	-0.34	3.21
11	5000	1706.6	35	180	-9	9.5	9.5	9.48	0.61	0.48	2.93
11	5000	1865.08	35	180	-9	9.5	9.5	10.36	1.47	1.36	2.68
11	5000	2030.22	35	180	-9	9.5	9.5	11.28	2.37	2.28	2.46
11	5000	2199.42	35	180	-9	9.5	9.5	12.22	3.3	3.22	2.27
11	5000	2371.61	35	180	-9	9.5	9.5	13.18	4.24	4.18	2.11
11	5000	2545.86	35	180	-9	9.5	9.5	14.14	5.2	5.14	1.96
11	5000	2986.75	35	180	-9	9.5	9.5	16.59	7.64	7.59	1.67
12	5000	1065.25	33.1	150.28	-9	9.5	9.5	8.55	-0.11	-0.45	4.69
12	5000	1194.76	33.1	155.36	-9	9.5	9.5	9.39	0.67	0.39	4.18
12	5000	1337.17	33.1	160.77	-9	9.5	9.5	10.3	1.51	1.3	3.74
12	5000	1493.18	33.1	180	-9	9.5	9.5	11.23	2.4	2.23	3.35
12	5000	1664.65	33.1	180	-9	9.5	9.5	12.18	3.32	3.18	3
12	5000	1838.42	33.1	180	-9	9.5	9.5	13.15	4.26	4.15	2.72
12	5000	2013.79	33.1	180	-9	9.5	9.5	14.12	5.22	5.12	2.48
12	5000	2457.67	33.1	180	-9	9.5	9.5	16.58	7.64	7.58	2.03
13	5000	1076.75	103	150.74	-9	9.5	9.5	8.62	-0.04	-0.38	4.64
13	5000	1201.53	103	155.63	-9	9.5	9.5	9.45	0.72	0.45	4.16
13	5000	1342.21	103	160.96	-9	9.5	9.5	10.33	1.55	1.33	3.73
13	5000	1496.84	103	180	-9	9.5	9.5	11.26	2.43	2.26	3.34
13	5000	1667.3	103	180	-9	9.5	9.5	12.2	3.34	3.2	3
13	5000	1840.4	103	180	-9	9.5	9.5	13.16	4.28	4.16	2.72
13	5000	2015.31	103	180	-9	9.5	9.5	14.13	5.23	5.13	2.48
13	5000	2457.24	103	180	-9	9.5	9.5	16.59	7.65	7.59	2.03
14	5000	1090.51	137	151.28	-9	9.5	9.5	8.72	0.05	-0.28	4.59
14	5000	1213.16	137	156.07	-9	9.5	9.5	9.52	0.78	0.52	4.12
14	5000	1350.81	137	161.28	-9	9.5	9.5	10.38	1.6	1.38	3.7
14	5000	1505.41	137	180	-9	9.5	9.5	11.3	2.47	2.3	3.32
14	5000	1673.25	137	180	-9	9.5	9.5	12.23	3.37	3.23	2.99
14	5000	1844.68	137	180	-9	9.5	9.5	13.18	4.3	4.18	2.71
14	5000	2018.47	137	180	-9	9.5	9.5	14.15	5.24	5.15	2.48
14	5000	2458.87	137	180	-9	9.5	9.5	16.59	7.66	7.59	2.03

15	5000	1096.93	33	151.54	-9	9.5	9.5	8.76	0.08	-0.24	4.56
15	5000	1217.88	33	156.25	-9	9.5	9.5	9.54	0.8	0.54	4.11
15	5000	1354.23	33	161.41	-9	9.5	9.5	10.4	1.61	1.4	3.69
15	5000	1508.23	33	180	-9	9.5	9.5	11.31	2.48	2.31	3.32
15	5000	1675.57	33	180	-9	9.5	9.5	12.24	3.38	3.24	2.98
15	5000	1851.41	33	180	-9	9.5	9.5	13.22	4.33	4.22	2.7
15	5000	2028.56	33	180	-9	9.5	9.5	14.2	5.3	5.2	2.46
15	5000	2473.79	33	180	-9	9.5	9.5	16.68	7.74	7.68	2.02
16	5000	1783.37	26.48	225.42	-9	9.5	9.5	8.99	0.11	-0.01	2.8
16	5000	1951.54	26.48	229.85	-9	9.5	9.5	9.72	0.83	0.72	2.56
16	5000	2142.22	26.48	234.77	-9	9.5	9.5	10.55	1.63	1.55	2.33
16	5000	2357.39	26.48	252.5	-9	9.5	9.5	11.43	2.5	2.43	2.12
16	5000	2586.13	26.48	252.5	-9	9.5	9.5	12.33	3.39	3.33	1.93
16	5000	2828.3	26.48	252.5	-9	9.5	9.5	13.29	4.34	4.29	1.77
16	5000	3073.49	26.48	252.5	-9	9.5	9.5	14.26	5.3	5.26	1.63
16	5000	3692.79	26.48	252.5	-9	9.5	9.5	16.72	7.74	7.72	1.35
17	5000	2134.29	75	263.23	-9	9.5	9.5	9.04	0.12	0.04	2.34
17	5000	2325.17	75	267.55	-9	9.5	9.5	9.77	0.84	0.77	2.15
17	5000	2544.8	75	272.43	-9	9.5	9.5	10.58	1.64	1.58	1.96
17	5000	2792.06	75	290	-9	9.5	9.5	11.46	2.5	2.46	1.79
17	5000	3053.39	75	290	-9	9.5	9.5	12.36	3.4	3.36	1.64
17	5000	3330.5	75	290	-9	9.5	9.5	13.31	4.35	4.31	1.5
17	5000	3610.04	75	290	-9	9.5	9.5	14.28	5.31	5.28	1.39
17	5000	4320.54	75	290	-9	9.5	9.5	16.73	7.75	7.73	1.16
18	5000	2137.48	70	263.31	-9	9.5	9.5	9.05	0.13	0.05	2.34
18	5000	2330.13	70	267.66	-9	9.5	9.5	9.78	0.85	0.78	2.15
18	5000	2548.96	70	272.52	-9	9.5	9.5	10.59	1.65	1.59	1.96
18	5000	2795.63	70	290	-9	9.5	9.5	11.46	2.51	2.46	1.79
18	5000	3056.34	70	290	-9	9.5	9.5	12.36	3.4	3.36	1.64
18	5000	3332.94	70	290	-9	9.5	9.5	13.31	4.35	4.31	1.5
18	5000	3613.4	70	290	-9	9.5	9.5	14.28	5.31	5.28	1.38
18	5000	4322.88	70	290	-9	9.5	9.5	16.73	7.75	7.73	1.16

RUN 5 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.04 0.3 0.5

INPUT FILE NAME: DI5K-9M5.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.02	-0.47	-0.98	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.99	0.4	-0.01	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.31	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.14	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	925.76	33.2	113.5	-9	9.5	9.5	8.16	-0.39	-0.84	5.4
4	5000	1031.69	33.2	113.5	-9	9.5	9.5	9.09	0.45	0.09	4.85
4	5000	1140.83	33.2	113.5	-9	9.5	9.5	10.05	1.35	1.05	4.38
4	5000	1251.7	33.2	113.5	-9	9.5	9.5	11.03	2.28	2.03	3.99
4	5000	1363.39	33.2	113.5	-9	9.5	9.5	12.01	3.22	3.01	3.67
4	5000	1475.79	33.2	113.5	-9	9.5	9.5	13	4.18	4	3.39
4	5000	1588.62	33.2	113.5	-9	9.5	9.5	14	5.15	5	3.15
4	5000	1870.63	33.2	113.5	-9	9.5	9.5	16.49	7.6	7.49	2.67

5	5000	1006.09	49	121	-9	9.5	9.5	8.31	-0.3	-0.69	4.97
5	5000	1113.93	49	121	-9	9.5	9.5	9.21	0.52	0.21	4.49
5	5000	1226.91	49	121	-9	9.5	9.5	10.14	1.4	1.14	4.08
5	5000	1342.78	49	121	-9	9.5	9.5	11.1	2.31	2.1	3.72
5	5000	1460.2	49	121	-9	9.5	9.5	12.07	3.25	3.07	3.42
5	5000	1578.81	49	121	-9	9.5	9.5	13.05	4.2	4.05	3.17
5	5000	1698.19	49	121	-9	9.5	9.5	14.03	5.17	5.03	2.94
5	5000	1997.42	49	121	-9	9.5	9.5	16.52	7.61	7.52	2.5
6	5000	1117.13	48.7	132	-9	9.5	9.5	8.46	-0.23	-0.54	4.48
6	5000	1230.08	48.7	132	-9	9.5	9.5	9.32	0.58	0.32	4.06
6	5000	1350.03	48.7	132	-9	9.5	9.5	10.23	1.44	1.23	3.7
6	5000	1474.07	48.7	132	-9	9.5	9.5	11.17	2.35	2.17	3.39
6	5000	1600.44	48.7	132	-9	9.5	9.5	12.12	3.28	3.12	3.12
6	5000	1728.54	48.7	132	-9	9.5	9.5	13.1	4.22	4.1	2.89
6	5000	1857.78	48.7	132	-9	9.5	9.5	14.07	5.19	5.07	2.69
6	5000	2182.4	48.7	132	-9	9.5	9.5	16.54	7.62	7.54	2.29
7	5000	1273.42	56.6	148	-9	9.5	9.5	8.6	-0.16	-0.4	3.93
7	5000	1395.45	56.6	148	-9	9.5	9.5	9.43	0.63	0.43	3.58
7	5000	1526.53	56.6	148	-9	9.5	9.5	10.31	1.48	1.31	3.28
7	5000	1663.11	56.6	148	-9	9.5	9.5	11.24	2.38	2.24	3.01
7	5000	1802.94	56.6	148	-9	9.5	9.5	12.18	3.3	3.18	2.77
7	5000	1945.15	56.6	148	-9	9.5	9.5	13.14	4.25	4.14	2.57
7	5000	2088.96	56.6	148	-9	9.5	9.5	14.11	5.2	5.11	2.39
7	5000	2452.52	56.6	148	-9	9.5	9.5	16.57	7.64	7.57	2.04
8	5000	1413.39	53.8	162.5	-9	9.5	9.5	8.7	-0.11	-0.3	3.54
8	5000	1544.15	53.8	162.5	-9	9.5	9.5	9.5	0.67	0.5	3.24
8	5000	1685.64	53.8	162.5	-9	9.5	9.5	10.37	1.51	1.37	2.97
8	5000	1833.77	53.8	162.5	-9	9.5	9.5	11.28	2.4	2.28	2.73
8	5000	1985.92	53.8	162.5	-9	9.5	9.5	12.22	3.32	3.22	2.52
8	5000	2141.01	53.8	162.5	-9	9.5	9.5	13.18	4.26	4.18	2.34
8	5000	2296.61	53.8	162.5	-9	9.5	9.5	14.14	5.22	5.14	2.18
8	5000	2694.8	53.8	162.5	-9	9.5	9.5	16.59	7.64	7.59	1.86
9	5000	1519.39	47.7	173.5	-9	9.5	9.5	8.76	-0.07	-0.24	3.29
9	5000	1656.85	47.7	173.5	-9	9.5	9.5	9.55	0.69	0.55	3.02
9	5000	1804.49	47.7	173.5	-9	9.5	9.5	10.41	1.53	1.41	2.77
9	5000	1961.67	47.7	173.5	-9	9.5	9.5	11.31	2.42	2.31	2.55
9	5000	2123.4	47.7	173.5	-9	9.5	9.5	12.25	3.33	3.25	2.35
9	5000	2288.44	47.7	173.5	-9	9.5	9.5	13.2	4.27	4.2	2.18
9	5000	2455.72	47.7	173.5	-9	9.5	9.5	14.16	5.22	5.16	2.04
9	5000	2879.06	47.7	173.5	-9	9.5	9.5	16.6	7.65	7.6	1.74

10	5000	1581.52	40.9	180	-9	9.5	9.5	8.79	-0.05	-0.21	3.16
10	5000	1722.96	40.9	180	-9	9.5	9.5	9.58	0.71	0.58	2.9
10	5000	1877.06	40.9	180	-9	9.5	9.5	10.43	1.54	1.43	2.66
10	5000	2038.41	40.9	180	-9	9.5	9.5	11.33	2.43	2.33	2.45
10	5000	2205.59	40.9	180	-9	9.5	9.5	12.26	3.34	3.26	2.27
10	5000	2376.35	40.9	180	-9	9.5	9.5	13.21	4.28	4.21	2.1
10	5000	2549.56	40.9	180	-9	9.5	9.5	14.17	5.23	5.17	1.96
10	5000	2988.87	40.9	180	-9	9.5	9.5	16.61	7.65	7.61	1.67
11	5000	1585.8	35	180	-9	9.5	9.5	8.81	-0.04	-0.19	3.15
11	5000	1726.31	35	180	-9	9.5	9.5	9.59	0.72	0.59	2.9
11	5000	1879.72	35	180	-9	9.5	9.5	10.44	1.55	1.44	2.66
11	5000	2041.28	35	180	-9	9.5	9.5	11.34	2.43	2.34	2.45
11	5000	2207.94	35	180	-9	9.5	9.5	12.27	3.35	3.27	2.26
11	5000	2378.3	35	180	-9	9.5	9.5	13.21	4.28	4.21	2.1
11	5000	2551.2	35	180	-9	9.5	9.5	14.17	5.23	5.17	1.96
11	5000	2989.99	35	180	-9	9.5	9.5	16.61	7.65	7.61	1.67
12	5000	1090.19	33.1	151.27	-9	9.5	9.5	8.71	0.04	-0.29	4.59
12	5000	1213.44	33.1	156.08	-9	9.5	9.5	9.51	0.78	0.51	4.12
12	5000	1351.41	33.1	161.3	-9	9.5	9.5	10.38	1.6	1.38	3.7
12	5000	1505.2	33.1	180	-9	9.5	9.5	11.3	2.47	2.3	3.32
12	5000	1673.84	33.1	180	-9	9.5	9.5	12.23	3.37	3.23	2.99
12	5000	1845.6	33.1	180	-9	9.5	9.5	13.19	4.3	4.19	2.71
12	5000	2019.5	33.1	180	-9	9.5	9.5	14.15	5.25	5.15	2.48
12	5000	2461.08	33.1	180	-9	9.5	9.5	16.6	7.66	7.6	2.03
13	5000	1109.11	103	152.02	-9	9.5	9.5	8.84	0.15	-0.16	4.51
13	5000	1227.45	103	156.62	-9	9.5	9.5	9.6	0.86	0.6	4.07
13	5000	1361.84	103	161.69	-9	9.5	9.5	10.45	1.66	1.45	3.67
13	5000	1512.99	103	180	-9	9.5	9.5	11.35	2.52	2.35	3.3
13	5000	1679.43	103	180	-9	9.5	9.5	12.27	3.41	3.27	2.98
13	5000	1849.08	103	180	-9	9.5	9.5	13.21	4.33	4.21	2.7
13	5000	2022.18	103	180	-9	9.5	9.5	14.17	5.27	5.17	2.47
13	5000	2461.33	103	180	-9	9.5	9.5	16.61	7.67	7.61	2.03
14	5000	1127.01	137	152.73	-9	9.5	9.5	8.95	0.26	-0.05	4.44
14	5000	1240.87	137	157.14	-9	9.5	9.5	9.69	0.94	0.69	4.03
14	5000	1373.53	137	162.12	-9	9.5	9.5	10.51	1.72	1.51	3.64
14	5000	1525.01	137	180	-9	9.5	9.5	11.4	2.56	2.4	3.28
14	5000	1687.87	137	180	-9	9.5	9.5	12.3	3.44	3.3	2.96
14	5000	1856.57	137	180	-9	9.5	9.5	13.24	4.35	4.24	2.69
14	5000	2027.74	137	180	-9	9.5	9.5	14.19	5.29	5.19	2.47
14	5000	2464.23	137	180	-9	9.5	9.5	16.62	7.68	7.62	2.03

15	5000	1131.78	33	152.91	-9	9.5	9.5	8.99	0.29	-0.01	4.42
15	5000	1244.55	33	157.28	-9	9.5	9.5	9.71	0.96	0.71	4.02
15	5000	1374.84	33	162.17	-9	9.5	9.5	10.53	1.73	1.53	3.64
15	5000	1525.99	33	180	-9	9.5	9.5	11.41	2.58	2.41	3.28
15	5000	1689.38	33	180	-9	9.5	9.5	12.32	3.45	3.32	2.96
15	5000	1861.95	33	180	-9	9.5	9.5	13.28	4.39	4.28	2.69
15	5000	2036.76	33	180	-9	9.5	9.5	14.25	5.34	5.25	2.45
15	5000	2478.41	33	180	-9	9.5	9.5	16.7	7.77	7.7	2.02
16	5000	1831.67	26.48	226.7	-9	9.5	9.5	9.2	0.32	0.2	2.73
16	5000	1988.79	26.48	230.82	-9	9.5	9.5	9.89	0.98	0.89	2.51
16	5000	2171.07	26.48	235.51	-9	9.5	9.5	10.67	1.75	1.67	2.3
16	5000	2381.56	26.48	252.5	-9	9.5	9.5	11.52	2.59	2.52	2.1
16	5000	2605.09	26.48	252.5	-9	9.5	9.5	12.41	3.47	3.41	1.92
16	5000	2842.85	26.48	252.5	-9	9.5	9.5	13.35	4.4	4.35	1.76
16	5000	3084.86	26.48	252.5	-9	9.5	9.5	14.31	5.35	5.31	1.62
16	5000	3699.23	26.48	252.5	-9	9.5	9.5	16.74	7.77	7.74	1.35
17	5000	2187.14	75	264.44	-9	9.5	9.5	9.25	0.33	0.25	2.29
17	5000	2368.07	75	268.51	-9	9.5	9.5	9.93	1	0.93	2.11
17	5000	2578.02	75	273.16	-9	9.5	9.5	10.7	1.76	1.7	1.94
17	5000	2819.65	75	290	-9	9.5	9.5	11.55	2.6	2.55	1.77
17	5000	3075.08	75	290	-9	9.5	9.5	12.43	3.47	3.43	1.63
17	5000	3347.17	75	290	-9	9.5	9.5	13.37	4.4	4.37	1.49
17	5000	3623.08	75	290	-9	9.5	9.5	14.32	5.35	5.32	1.38
17	5000	4327.94	75	290	-9	9.5	9.5	16.75	7.77	7.75	1.16
18	5000	2192.73	70	264.56	-9	9.5	9.5	9.26	0.34	0.26	2.28
18	5000	2372.86	70	268.62	-9	9.5	9.5	9.93	1	0.93	2.11
18	5000	2582.07	70	273.25	-9	9.5	9.5	10.71	1.77	1.71	1.94
18	5000	2823.15	70	290	-9	9.5	9.5	11.55	2.6	2.55	1.77
18	5000	3077.98	70	290	-9	9.5	9.5	12.43	3.47	3.43	1.62
18	5000	3349.58	70	290	-9	9.5	9.5	13.37	4.41	4.37	1.49
18	5000	3626.41	70	290	-9	9.5	9.5	14.33	5.35	5.33	1.38
18	5000	4330.27	70	290	-9	9.5	9.5	16.75	7.77	7.75	1.15

RUN 6 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL
SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.06 0.3 0.5

INPUT FILE NAME: DISK-9M6.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.96	100	108	-9	9.5	9.5	8.03	-0.46	-0.97	5.77
3	5000	970.53	100	108	-9	9.5	9.5	9	0.41	0	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.32	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.97	4.16	3.97	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.97	5.14	4.97	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	935.93	33.2	113.5	-9	9.5	9.5	8.25	-0.31	-0.75	5.34
4	5000	1038.6	33.2	113.5	-9	9.5	9.5	9.15	0.51	0.15	4.81
4	5000	1145.73	33.2	113.5	-9	9.5	9.5	10.09	1.39	1.09	4.36
4	5000	1255.29	33.2	113.5	-9	9.5	9.5	11.06	2.31	2.06	3.98
4	5000	1366.11	33.2	113.5	-9	9.5	9.5	12.04	3.24	3.04	3.66
4	5000	1477.89	33.2	113.5	-9	9.5	9.5	13.02	4.2	4.02	3.38
4	5000	1590.29	33.2	113.5	-9	9.5	9.5	14.01	5.16	5.01	3.14
4	5000	1872.67	33.2	113.5	-9	9.5	9.5	16.5	7.61	7.5	2.67

5	5000	1027.2	49	121	-9	9.5	9.5	8.49	-0.14	-0.51	4.87
5	5000	1128.8	49	121	-9	9.5	9.5	9.33	0.63	0.33	4.43
5	5000	1237.65	49	121	-9	9.5	9.5	10.23	1.48	1.23	4.04
5	5000	1350.75	49	121	-9	9.5	9.5	11.16	2.38	2.16	3.7
5	5000	1466.28	49	121	-9	9.5	9.5	12.12	3.3	3.12	3.41
5	5000	1583.54	49	121	-9	9.5	9.5	13.09	4.24	4.09	3.16
5	5000	1701.94	49	121	-9	9.5	9.5	14.07	5.2	5.07	2.94
5	5000	1999.77	49	121	-9	9.5	9.5	16.53	7.63	7.53	2.5
6	5000	1148.07	48.7	132	-9	9.5	9.5	8.7	-0.01	-0.3	4.36
6	5000	1252.41	48.7	132	-9	9.5	9.5	9.49	0.74	0.49	3.99
6	5000	1366.41	48.7	132	-9	9.5	9.5	10.35	1.56	1.35	3.66
6	5000	1486.35	48.7	132	-9	9.5	9.5	11.26	2.44	2.26	3.36
6	5000	1609.86	48.7	132	-9	9.5	9.5	12.2	3.35	3.2	3.11
6	5000	1735.91	48.7	132	-9	9.5	9.5	13.15	4.28	4.15	2.88
6	5000	1863.65	48.7	132	-9	9.5	9.5	14.12	5.23	5.12	2.68
6	5000	2186.05	48.7	132	-9	9.5	9.5	16.57	7.65	7.57	2.29
7	5000	1315.23	56.6	148	-9	9.5	9.5	8.89	0.11	-0.11	3.8
7	5000	1426.23	56.6	148	-9	9.5	9.5	9.64	0.83	0.64	3.51
7	5000	1549.42	56.6	148	-9	9.5	9.5	10.47	1.63	1.47	3.23
7	5000	1680.42	56.6	148	-9	9.5	9.5	11.35	2.49	2.35	2.98
7	5000	1816.29	56.6	148	-9	9.5	9.5	12.27	3.39	3.27	2.75
7	5000	1955.63	56.6	148	-9	9.5	9.5	13.21	4.32	4.21	2.56
7	5000	2097.32	56.6	148	-9	9.5	9.5	14.17	5.26	5.17	2.38
7	5000	2456.22	56.6	148	-9	9.5	9.5	16.61	7.67	7.61	2.04
8	5000	1464.74	53.8	162.5	-9	9.5	9.5	9.01	0.19	0.01	3.41
8	5000	1582.44	53.8	162.5	-9	9.5	9.5	9.74	0.89	0.74	3.16
8	5000	1714.36	53.8	162.5	-9	9.5	9.5	10.55	1.68	1.55	2.92
8	5000	1855.62	53.8	162.5	-9	9.5	9.5	11.42	2.53	2.42	2.69
8	5000	2001.22	53.8	162.5	-9	9.5	9.5	12.32	3.42	3.32	2.5
8	5000	2152.9	53.8	162.5	-9	9.5	9.5	13.26	4.34	4.26	2.32
8	5000	2307.48	53.8	162.5	-9	9.5	9.5	14.21	5.28	5.21	2.17
8	5000	2701.4	53.8	162.5	-9	9.5	9.5	16.63	7.68	7.63	1.85
9	5000	1578.4	47.7	173.5	-9	9.5	9.5	9.1	0.25	0.1	3.17
9	5000	1699.61	47.7	173.5	-9	9.5	9.5	9.8	0.94	0.8	2.94
9	5000	1838.33	47.7	173.5	-9	9.5	9.5	10.6	1.72	1.6	2.72
9	5000	1987.51	47.7	173.5	-9	9.5	9.5	11.46	2.56	2.46	2.52
9	5000	2143.44	47.7	173.5	-9	9.5	9.5	12.36	3.44	3.36	2.33
9	5000	2304.23	47.7	173.5	-9	9.5	9.5	13.29	4.36	4.29	2.17
9	5000	2467.56	47.7	173.5	-9	9.5	9.5	14.23	5.3	5.23	2.03
9	5000	2886.84	47.7	173.5	-9	9.5	9.5	16.65	7.69	7.65	1.73

10	5000	1646.4	40.9	180	-9	9.5	9.5	9.15	0.3	0.15	3.04
10	5000	1771.11	40.9	180	-9	9.5	9.5	9.85	0.97	0.85	2.82
10	5000	1913.43	40.9	180	-9	9.5	9.5	10.64	1.74	1.64	2.61
10	5000	2066.96	40.9	180	-9	9.5	9.5	11.49	2.58	2.49	2.42
10	5000	2227.8	40.9	180	-9	9.5	9.5	12.38	3.46	3.38	2.24
10	5000	2393.87	40.9	180	-9	9.5	9.5	13.3	4.37	4.3	2.09
10	5000	2563.58	40.9	180	-9	9.5	9.5	14.25	5.31	5.25	1.95
10	5000	2997.42	40.9	180	-9	9.5	9.5	16.66	7.7	7.66	1.67
11	5000	1653.3	35	180	-9	9.5	9.5	9.18	0.33	0.18	3.02
11	5000	1777.51	35	180	-9	9.5	9.5	9.87	1	0.87	2.81
11	5000	1918.57	35	180	-9	9.5	9.5	10.66	1.76	1.66	2.61
11	5000	2071.1	35	180	-9	9.5	9.5	11.51	2.6	2.51	2.41
11	5000	2231.16	35	180	-9	9.5	9.5	12.4	3.47	3.4	2.24
11	5000	2396.64	35	180	-9	9.5	9.5	13.31	4.38	4.31	2.09
11	5000	2565.9	35	180	-9	9.5	9.5	14.25	5.31	5.25	1.95
11	5000	2998.96	35	180	-9	9.5	9.5	16.66	7.7	7.66	1.67
12	5000	1152.88	33.1	153.74	-9	9.5	9.5	9.12	0.42	0.12	4.34
12	5000	1262.15	33.1	157.95	-9	9.5	9.5	9.82	1.07	0.82	3.96
12	5000	1389.37	33.1	162.71	-9	9.5	9.5	10.62	1.82	1.62	3.6
12	5000	1537.53	33.1	180	-9	9.5	9.5	11.48	2.64	2.48	3.25
12	5000	1698.87	33.1	180	-9	9.5	9.5	12.37	3.51	3.37	2.94
12	5000	1865.28	33.1	180	-9	9.5	9.5	13.3	4.41	4.3	2.68
12	5000	2035.23	33.1	180	-9	9.5	9.5	14.24	5.33	5.24	2.46
12	5000	2470.53	33.1	180	-9	9.5	9.5	16.65	7.72	7.65	2.02
13	5000	1188.38	103	155.12	-9	9.5	9.5	9.35	0.63	0.35	4.21
13	5000	1289.95	103	159	-9	9.5	9.5	10	1.23	1	3.88
13	5000	1410.89	103	163.5	-9	9.5	9.5	10.75	1.94	1.75	3.54
13	5000	1556.87	103	180	-9	9.5	9.5	11.58	2.74	2.58	3.21
13	5000	1712.87	103	180	-9	9.5	9.5	12.45	3.58	3.45	2.92
13	5000	1874.24	103	180	-9	9.5	9.5	13.35	4.46	4.35	2.67
13	5000	2042.07	103	180	-9	9.5	9.5	14.28	5.38	5.28	2.45
13	5000	2472.7	103	180	-9	9.5	9.5	16.68	7.74	7.68	2.02
14	5000	1208.18	137	155.88	-9	9.5	9.5	9.48	0.75	0.48	4.14
14	5000	1305.74	137	159.59	-9	9.5	9.5	10.1	1.33	1.1	3.83
14	5000	1423.28	137	163.95	-9	9.5	9.5	10.83	2.02	1.83	3.51
14	5000	1567.99	137	180	-9	9.5	9.5	11.64	2.8	2.64	3.19
14	5000	1720.99	137	180	-9	9.5	9.5	12.49	3.63	3.49	2.91
14	5000	1881.71	137	180	-9	9.5	9.5	13.39	4.5	4.39	2.66
14	5000	2047.65	137	180	-9	9.5	9.5	14.31	5.4	5.31	2.44
14	5000	2477.62	137	180	-9	9.5	9.5	16.69	7.75	7.69	2.02

15	5000	1212.1	33	156.03	-9	9.5	9.5	9.51	0.77	0.51	4.13
15	5000	1308.95	33	159.71	-9	9.5	9.5	10.12	1.35	1.12	3.82
15	5000	1425.87	33	164.05	-9	9.5	9.5	10.84	2.03	1.84	3.51
15	5000	1570.19	33	180	-9	9.5	9.5	11.66	2.81	2.66	3.18
15	5000	1724.51	33	180	-9	9.5	9.5	12.51	3.64	3.51	2.9
15	5000	1889.14	33	180	-9	9.5	9.5	13.43	4.54	4.43	2.65
15	5000	2058.17	33	180	-9	9.5	9.5	14.37	5.46	5.37	2.43
15	5000	2490.67	33	180	-9	9.5	9.5	16.77	7.83	7.77	2.01
16	5000	1943.49	26.48	229.64	-9	9.5	9.5	9.69	0.79	0.69	2.57
16	5000	2078.84	26.48	233.15	-9	9.5	9.5	10.27	1.36	1.27	2.41
16	5000	2242.52	26.48	237.32	-9	9.5	9.5	10.97	2.05	1.97	2.23
16	5000	2441.83	26.48	252.5	-9	9.5	9.5	11.76	2.83	2.76	2.05
16	5000	2653.38	26.48	252.5	-9	9.5	9.5	12.6	3.65	3.6	1.88
16	5000	2880.43	26.48	252.5	-9	9.5	9.5	13.5	4.55	4.5	1.74
16	5000	3114.55	26.48	252.5	-9	9.5	9.5	14.43	5.47	5.43	1.61
16	5000	3716.32	26.48	252.5	-9	9.5	9.5	16.81	7.84	7.81	1.35
17	5000	2315.89	75	267.34	-9	9.5	9.5	9.73	0.81	0.73	2.16
17	5000	2471.8	75	270.82	-9	9.5	9.5	10.31	1.38	1.31	2.02
17	5000	2660.29	75	274.96	-9	9.5	9.5	11	2.06	2	1.88
17	5000	2888.47	75	290	-9	9.5	9.5	11.79	2.83	2.79	1.73
17	5000	3130.3	75	290	-9	9.5	9.5	12.62	3.66	3.62	1.6
17	5000	3390.2	75	290	-9	9.5	9.5	13.52	4.55	4.52	1.47
17	5000	3657.13	75	290	-9	9.5	9.5	14.44	5.47	5.44	1.37
17	5000	4347.56	75	290	-9	9.5	9.5	16.82	7.84	7.82	1.15
18	5000	2320.89	70	267.45	-9	9.5	9.5	9.74	0.81	0.74	2.15
18	5000	2476.21	70	270.92	-9	9.5	9.5	10.32	1.38	1.32	2.02
18	5000	2664.21	70	290	-9	9.5	9.5	11.01	2.06	2.01	1.88
18	5000	2891.8	70	290	-9	9.5	9.5	11.79	2.84	2.79	1.73
18	5000	3133.09	70	290	-9	9.5	9.5	12.62	3.66	3.62	1.6
18	5000	3392.54	70	290	-9	9.5	9.5	13.52	4.55	4.52	1.47
18	5000	3660.4	70	290	-9	9.5	9.5	14.44	5.47	5.44	1.37
18	5000	4349.87	70	290	-9	9.5	9.5	16.82	7.84	7.82	1.15

RUN 7 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.03 0.6 0.8

INPUT FILE NAME: DI5K-9M7.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.01	-0.47	-0.99	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.98	0.4	-0.02	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.97	1.31	0.97	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.24	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.96	3.2	2.96	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	924.4	33.2	113.5	-9	9.5	9.5	8.14	-0.4	-0.86	5.41
4	5000	1030.77	33.2	113.5	-9	9.5	9.5	9.08	0.45	0.08	4.85
4	5000	1140.24	33.2	113.5	-9	9.5	9.5	10.05	1.34	1.05	4.39
4	5000	1251.32	33.2	113.5	-9	9.5	9.5	11.02	2.27	2.02	4
4	5000	1363.16	33.2	113.5	-9	9.5	9.5	12.01	3.22	3.01	3.67
4	5000	1475.65	33.2	113.5	-9	9.5	9.5	13	4.18	4	3.39
4	5000	1588.55	33.2	113.5	-9	9.5	9.5	14	5.15	5	3.15
4	5000	1871.69	33.2	113.5	-9	9.5	9.5	16.49	7.6	7.49	2.67

5	5000	1003.45	49	121	-9	9.5	9.5	8.29	-0.32	-0.71	4.98
5	5000	1112.2	49	121	-9	9.5	9.5	9.19	0.51	0.19	4.5
5	5000	1225.82	49	121	-9	9.5	9.5	10.13	1.39	1.13	4.08
5	5000	1342.12	49	121	-9	9.5	9.5	11.09	2.31	2.09	3.73
5	5000	1459.83	49	121	-9	9.5	9.5	12.06	3.25	3.06	3.43
5	5000	1578.62	49	121	-9	9.5	9.5	13.05	4.2	4.05	3.17
5	5000	1698.12	49	121	-9	9.5	9.5	14.03	5.17	5.03	2.94
5	5000	1998.54	49	121	-9	9.5	9.5	16.52	7.61	7.52	2.5
6	5000	1114.09	48.7	132	-9	9.5	9.5	8.44	-0.25	-0.56	4.49
6	5000	1228.19	48.7	132	-9	9.5	9.5	9.3	0.56	0.3	4.07
6	5000	1348.95	48.7	132	-9	9.5	9.5	10.22	1.43	1.22	3.71
6	5000	1473.54	48.7	132	-9	9.5	9.5	11.16	2.34	2.16	3.39
6	5000	1600.27	48.7	132	-9	9.5	9.5	12.12	3.27	3.12	3.12
6	5000	1728.59	48.7	132	-9	9.5	9.5	13.1	4.23	4.1	2.89
6	5000	1857.98	48.7	132	-9	9.5	9.5	14.08	5.19	5.08	2.69
6	5000	2184.04	48.7	132	-9	9.5	9.5	16.55	7.63	7.55	2.29
7	5000	1270.24	56.6	148	-9	9.5	9.5	8.58	-0.18	-0.42	3.94
7	5000	1393.64	56.6	148	-9	9.5	9.5	9.42	0.62	0.42	3.59
7	5000	1525.71	56.6	148	-9	9.5	9.5	10.31	1.48	1.31	3.28
7	5000	1662.93	56.6	148	-9	9.5	9.5	11.24	2.38	2.24	3.01
7	5000	1803.17	56.6	148	-9	9.5	9.5	12.18	3.3	3.18	2.77
7	5000	1945.63	56.6	148	-9	9.5	9.5	13.15	4.25	4.15	2.57
7	5000	2089.59	56.6	148	-9	9.5	9.5	14.12	5.21	5.12	2.39
7	5000	2453.27	56.6	148	-9	9.5	9.5	16.58	7.64	7.58	2.04
8	5000	1409.67	53.8	162.5	-9	9.5	9.5	8.67	-0.13	-0.33	3.55
8	5000	1542.11	53.8	162.5	-9	9.5	9.5	9.49	0.65	0.49	3.24
8	5000	1684.8	53.8	162.5	-9	9.5	9.5	10.37	1.5	1.37	2.97
8	5000	1833.71	53.8	162.5	-9	9.5	9.5	11.28	2.4	2.28	2.73
8	5000	1986.36	53.8	162.5	-9	9.5	9.5	12.22	3.32	3.22	2.52
8	5000	2141.75	53.8	162.5	-9	9.5	9.5	13.18	4.26	4.18	2.33
8	5000	2299.01	53.8	162.5	-9	9.5	9.5	14.15	5.22	5.15	2.17
8	5000	2695.53	53.8	162.5	-9	9.5	9.5	16.6	7.65	7.6	1.85
9	5000	1514.87	47.7	173.5	-9	9.5	9.5	8.73	-0.1	-0.27	3.3
9	5000	1654.33	47.7	173.5	-9	9.5	9.5	9.54	0.68	0.54	3.02
9	5000	1805.17	47.7	173.5	-9	9.5	9.5	10.4	1.52	1.4	2.77
9	5000	1963.02	47.7	173.5	-9	9.5	9.5	11.31	2.41	2.31	2.55
9	5000	2123.45	47.7	173.5	-9	9.5	9.5	12.25	3.33	3.25	2.35
9	5000	2288.92	47.7	173.5	-9	9.5	9.5	13.2	4.27	4.2	2.18
9	5000	2456.48	47.7	173.5	-9	9.5	9.5	14.17	5.23	5.17	2.04
9	5000	2880.76	47.7	173.5	-9	9.5	9.5	16.61	7.66	7.61	1.74

10	5000	1575.53	40.9	180	-9	9.5	9.5	8.76	-0.08	-0.24	3.17
10	5000	1719.38	40.9	180	-9	9.5	9.5	9.56	0.69	0.56	2.91
10	5000	1875.24	40.9	180	-9	9.5	9.5	10.42	1.54	1.42	2.67
10	5000	2038.52	40.9	180	-9	9.5	9.5	11.33	2.42	2.33	2.45
10	5000	2205.46	40.9	180	-9	9.5	9.5	12.26	3.34	3.26	2.27
10	5000	2376.73	40.9	180	-9	9.5	9.5	13.21	4.28	4.21	2.1
10	5000	2550.25	40.9	180	-9	9.5	9.5	14.18	5.23	5.18	1.96
10	5000	2989.9	40.9	180	-9	9.5	9.5	16.62	7.66	7.62	1.67
11	5000	1578.97	35	180	-9	9.5	9.5	8.77	-0.07	-0.23	3.17
11	5000	1722.11	35	180	-9	9.5	9.5	9.57	0.7	0.57	2.9
11	5000	1877.41	35	180	-9	9.5	9.5	10.43	1.54	1.43	2.66
11	5000	2040.28	35	180	-9	9.5	9.5	11.33	2.43	2.33	2.45
11	5000	2207.76	35	180	-9	9.5	9.5	12.27	3.35	3.27	2.26
11	5000	2378.66	35	180	-9	9.5	9.5	13.21	4.28	4.21	2.1
11	5000	2551.9	35	180	-9	9.5	9.5	14.18	5.24	5.18	1.96
11	5000	2991.05	35	180	-9	9.5	9.5	16.62	7.66	7.62	1.67
12	5000	1082.74	33.1	150.98	-9	9.5	9.5	8.66	-0.01	-0.34	4.62
12	5000	1208.56	33.1	155.9	-9	9.5	9.5	9.48	0.75	0.48	4.14
12	5000	1348.43	33.1	161.19	-9	9.5	9.5	10.36	1.58	1.36	3.71
12	5000	1503.4	33.1	180	-9	9.5	9.5	11.29	2.46	2.29	3.33
12	5000	1673.1	33.1	180	-9	9.5	9.5	12.23	3.37	3.23	2.99
12	5000	1845.53	33.1	180	-9	9.5	9.5	13.19	4.3	4.19	2.71
12	5000	2019.87	33.1	180	-9	9.5	9.5	14.15	5.25	5.15	2.48
12	5000	2461.98	33.1	180	-9	9.5	9.5	16.6	7.67	7.6	2.03
13	5000	1093.71	103	151.41	-9	9.5	9.5	8.74	0.06	-0.26	4.57
13	5000	1215.13	103	156.15	-9	9.5	9.5	9.53	0.8	0.53	4.11
13	5000	1353.36	103	161.37	-9	9.5	9.5	10.4	1.61	1.4	3.69
13	5000	1506.98	103	180	-9	9.5	9.5	11.31	2.49	2.31	3.32
13	5000	1675.71	103	180	-9	9.5	9.5	12.25	3.39	3.25	2.98
13	5000	1847.49	103	180	-9	9.5	9.5	13.2	4.31	4.2	2.71
13	5000	2021.38	103	180	-9	9.5	9.5	14.17	5.26	5.17	2.47
13	5000	2461.55	103	180	-9	9.5	9.5	16.61	7.67	7.61	2.03
14	5000	1106.9	137	151.93	-9	9.5	9.5	8.83	0.15	-0.17	4.52
14	5000	1226.4	137	156.58	-9	9.5	9.5	9.6	0.86	0.6	4.08
14	5000	1361.77	137	161.69	-9	9.5	9.5	10.45	1.66	1.45	3.67
14	5000	1515.36	137	180	-9	9.5	9.5	11.35	2.52	2.35	3.3
14	5000	1681.57	137	180	-9	9.5	9.5	12.28	3.41	3.28	2.97
14	5000	1851.72	137	180	-9	9.5	9.5	13.22	4.33	4.22	2.7
14	5000	2024.51	137	180	-9	9.5	9.5	14.18	5.28	5.18	2.47
14	5000	2463.17	137	180	-9	9.5	9.5	16.62	7.68	7.62	2.03

15	5000	1113.37	33	152.19	-9	9.5	9.5	8.86	0.18	-0.14	4.49
15	5000	1231.19	33	156.76	-9	9.5	9.5	9.63	0.88	0.63	4.06
15	5000	1365.24	33	161.81	-9	9.5	9.5	10.47	1.68	1.47	3.66
15	5000	1518.22	33	180	-9	9.5	9.5	11.37	2.54	2.37	3.29
15	5000	1684.19	33	180	-9	9.5	9.5	12.29	3.43	3.29	2.97
15	5000	1858.63	33	180	-9	9.5	9.5	13.26	4.37	4.26	2.69
15	5000	2034.71	33	180	-9	9.5	9.5	14.24	5.33	5.24	2.46
15	5000	2478.03	33	180	-9	9.5	9.5	16.7	7.76	7.7	2.02
16	5000	1806.13	26.48	226.02	-9	9.5	9.5	9.09	0.21	0.09	2.77
16	5000	1970.12	26.48	230.33	-9	9.5	9.5	9.81	0.91	0.81	2.54
16	5000	2157.64	26.48	235.17	-9	9.5	9.5	10.61	1.69	1.61	2.32
16	5000	2370.99	26.48	252.5	-9	9.5	9.5	11.48	2.55	2.48	2.11
16	5000	2597.96	26.48	252.5	-9	9.5	9.5	12.38	3.44	3.38	1.92
16	5000	2838.27	26.48	252.5	-9	9.5	9.5	13.33	4.38	4.33	1.76
16	5000	3082.02	26.48	252.5	-9	9.5	9.5	14.3	5.34	5.3	1.62
16	5000	3698.69	26.48	252.5	-9	9.5	9.5	16.74	7.77	7.74	1.35
17	5000	2160.45	75	263.83	-9	9.5	9.5	9.14	0.22	0.14	2.31
17	5000	2346.57	75	268.03	-9	9.5	9.5	9.85	0.92	0.85	2.13
17	5000	2562.55	75	272.82	-9	9.5	9.5	10.65	1.7	1.65	1.95
17	5000	2807.58	75	290	-9	9.5	9.5	11.51	2.56	2.51	1.78
17	5000	3066.91	75	290	-9	9.5	9.5	12.4	3.44	3.4	1.63
17	5000	3341.93	75	290	-9	9.5	9.5	13.35	4.38	4.35	1.5
17	5000	3619.82	75	290	-9	9.5	9.5	14.31	5.34	5.31	1.38
17	5000	4327.32	75	290	-9	9.5	9.5	16.75	7.77	7.75	1.16
18	5000	2163.53	70	263.9	-9	9.5	9.5	9.15	0.23	0.15	2.31
18	5000	2351.44	70	268.14	-9	9.5	9.5	9.86	0.93	0.86	2.13
18	5000	2566.65	70	272.91	-9	9.5	9.5	10.65	1.71	1.65	1.95
18	5000	2811.11	70	290	-9	9.5	9.5	11.51	2.56	2.51	1.78
18	5000	3069.83	70	290	-9	9.5	9.5	12.41	3.45	3.41	1.63
18	5000	3344.34	70	290	-9	9.5	9.5	13.35	4.39	4.35	1.5
18	5000	3623.17	70	290	-9	9.5	9.5	14.31	5.34	5.31	1.38
18	5000	4329.65	70	290	-9	9.5	9.5	16.75	7.77	7.75	1.15

RUN 8 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.04 0.6 0.8

INPUT FILE NAME: DI5K-9M8.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	865.17	100	108	-9	9.5	9.5	8.02	-0.46	-0.98	5.78
3	5000	970.53	100	108	-9	9.5	9.5	8.99	0.4	-0.01	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.31	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.96	4.16	3.96	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.96	5.14	4.96	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	928.75	33.2	113.5	-9	9.5	9.5	8.18	-0.37	-0.82	5.38
4	5000	1033.66	33.2	113.5	-9	9.5	9.5	9.11	0.47	0.11	4.84
4	5000	1142.26	33.2	113.5	-9	9.5	9.5	10.06	1.36	1.06	4.38
4	5000	1252.79	33.2	113.5	-9	9.5	9.5	11.04	2.29	2.04	3.99
4	5000	1364.27	33.2	113.5	-9	9.5	9.5	12.02	3.23	3.02	3.66
4	5000	1476.5	33.2	113.5	-9	9.5	9.5	13.01	4.19	4.01	3.39
4	5000	1589.23	33.2	113.5	-9	9.5	9.5	14	5.16	5	3.15
4	5000	1872.09	33.2	113.5	-9	9.5	9.5	16.49	7.6	7.49	2.67

5	5000	1011.96	49	121	-9	9.5	9.5	8.36	-0.26	-0.64	4.94
5	5000	1118.03	49	121	-9	9.5	9.5	9.24	0.55	0.24	4.47
5	5000	1229.97	49	121	-9	9.5	9.5	10.17	1.42	1.17	4.07
5	5000	1345.17	49	121	-9	9.5	9.5	11.12	2.33	2.12	3.72
5	5000	1462.14	49	121	-9	9.5	9.5	12.08	3.27	3.08	3.42
5	5000	1580.41	49	121	-9	9.5	9.5	13.06	4.22	4.06	3.16
5	5000	1699.54	49	121	-9	9.5	9.5	14.05	5.18	5.05	2.94
5	5000	1999.39	49	121	-9	9.5	9.5	16.52	7.62	7.52	2.5
6	5000	1126.39	48.7	132	-9	9.5	9.5	8.53	-0.16	-0.47	4.44
6	5000	1236.82	48.7	132	-9	9.5	9.5	9.37	0.62	0.37	4.04
6	5000	1355.17	48.7	132	-9	9.5	9.5	10.27	1.48	1.27	3.69
6	5000	1478.15	48.7	132	-9	9.5	9.5	11.2	2.38	2.2	3.38
6	5000	1603.78	48.7	132	-9	9.5	9.5	12.15	3.3	3.15	3.12
6	5000	1731.33	48.7	132	-9	9.5	9.5	13.12	4.25	4.12	2.89
6	5000	1860.15	48.7	132	-9	9.5	9.5	14.09	5.2	5.09	2.69
6	5000	2185.35	48.7	132	-9	9.5	9.5	16.56	7.64	7.56	2.29
7	5000	1286.73	56.6	148	-9	9.5	9.5	8.69	-0.07	-0.31	3.89
7	5000	1405.44	56.6	148	-9	9.5	9.5	9.5	0.69	0.5	3.56
7	5000	1534.33	56.6	148	-9	9.5	9.5	10.37	1.53	1.37	3.26
7	5000	1669.37	56.6	148	-9	9.5	9.5	11.28	2.42	2.28	3
7	5000	1808.1	56.6	148	-9	9.5	9.5	12.22	3.34	3.22	2.77
7	5000	1949.48	56.6	148	-9	9.5	9.5	13.17	4.27	4.17	2.56
7	5000	2092.65	56.6	148	-9	9.5	9.5	14.14	5.23	5.14	2.39
7	5000	2455.12	56.6	148	-9	9.5	9.5	16.59	7.65	7.59	2.04
8	5000	1429.87	53.8	162.5	-9	9.5	9.5	8.8	-0.01	-0.2	3.5
8	5000	1556.75	53.8	162.5	-9	9.5	9.5	9.58	0.74	0.58	3.21
8	5000	1695.58	53.8	162.5	-9	9.5	9.5	10.43	1.57	1.43	2.95
8	5000	1841.82	53.8	162.5	-9	9.5	9.5	11.33	2.45	2.33	2.71
8	5000	1992.59	53.8	162.5	-9	9.5	9.5	12.26	3.36	3.26	2.51
8	5000	2146.62	53.8	162.5	-9	9.5	9.5	13.21	4.29	4.21	2.33
8	5000	2302.89	53.8	162.5	-9	9.5	9.5	14.17	5.24	5.17	2.17
8	5000	2697.93	53.8	162.5	-9	9.5	9.5	16.61	7.66	7.61	1.85
9	5000	1538.07	47.7	173.5	-9	9.5	9.5	8.86	0.03	-0.14	3.25
9	5000	1671.27	47.7	173.5	-9	9.5	9.5	9.63	0.77	0.63	2.99
9	5000	1817.71	47.7	173.5	-9	9.5	9.5	10.48	1.59	1.48	2.75
9	5000	1972.48	47.7	173.5	-9	9.5	9.5	11.37	2.47	2.37	2.53
9	5000	2130.81	47.7	173.5	-9	9.5	9.5	12.29	3.38	3.29	2.35
9	5000	2294.69	47.7	173.5	-9	9.5	9.5	13.23	4.31	4.23	2.18
9	5000	2461.08	47.7	173.5	-9	9.5	9.5	14.19	5.26	5.19	2.03
9	5000	2882.69	47.7	173.5	-9	9.5	9.5	16.62	7.67	7.62	1.73

10	5000	1601.05	40.9	180	-9	9.5	9.5	8.9	0.06	-0.1	3.12
10	5000	1738.1	40.9	180	-9	9.5	9.5	9.66	0.79	0.66	2.88
10	5000	1889.14	40.9	180	-9	9.5	9.5	10.5	1.61	1.5	2.65
10	5000	2049.03	40.9	180	-9	9.5	9.5	11.39	2.48	2.39	2.44
10	5000	2213.59	40.9	180	-9	9.5	9.5	12.31	3.39	3.31	2.26
10	5000	2383.11	40.9	180	-9	9.5	9.5	13.25	4.32	4.25	2.1
10	5000	2555.34	40.9	180	-9	9.5	9.5	14.2	5.26	5.2	1.96
10	5000	2992.98	40.9	180	-9	9.5	9.5	16.63	7.68	7.63	1.67
11	5000	1605.55	35	180	-9	9.5	9.5	8.92	0.07	-0.08	3.11
11	5000	1741.66	35	180	-9	9.5	9.5	9.68	0.8	0.68	2.87
11	5000	1891.96	35	180	-9	9.5	9.5	10.51	1.62	1.51	2.64
11	5000	2051.29	35	180	-9	9.5	9.5	11.4	2.49	2.4	2.44
11	5000	2216.27	35	180	-9	9.5	9.5	12.31	3.39	3.31	2.26
11	5000	2385.34	35	180	-9	9.5	9.5	13.25	4.32	4.25	2.1
11	5000	2557.23	35	180	-9	9.5	9.5	14.21	5.27	5.21	1.96
11	5000	2994.29	35	180	-9	9.5	9.5	16.63	7.68	7.63	1.67
12	5000	1107.4	33.1	151.95	-9	9.5	9.5	8.83	0.14	-0.17	4.52
12	5000	1227.12	33.1	156.61	-9	9.5	9.5	9.6	0.86	0.6	4.07
12	5000	1362.61	33.1	161.72	-9	9.5	9.5	10.45	1.66	1.45	3.67
12	5000	1515.36	33.1	180	-9	9.5	9.5	11.35	2.52	2.35	3.3
12	5000	1682.26	33.1	180	-9	9.5	9.5	12.28	3.42	3.28	2.97
12	5000	1852.7	33.1	180	-9	9.5	9.5	13.23	4.34	4.23	2.7
12	5000	2025.57	33.1	180	-9	9.5	9.5	14.19	5.28	5.19	2.47
12	5000	2465.38	33.1	180	-9	9.5	9.5	16.62	7.69	7.62	2.03
13	5000	1125.5	103	152.67	-9	9.5	9.5	8.94	0.25	-0.06	4.44
13	5000	1240.7	103	157.13	-9	9.5	9.5	9.69	0.94	0.69	4.03
13	5000	1371.14	103	162.03	-9	9.5	9.5	10.52	1.72	1.52	3.65
13	5000	1522.98	103	180	-9	9.5	9.5	11.4	2.57	2.4	3.28
13	5000	1687.76	103	180	-9	9.5	9.5	12.32	3.45	3.32	2.96
13	5000	1856.14	103	180	-9	9.5	9.5	13.25	4.36	4.25	2.69
13	5000	2028.22	103	180	-9	9.5	9.5	14.21	5.3	5.21	2.47
13	5000	2465.63	103	180	-9	9.5	9.5	16.63	7.7	7.63	2.03
14	5000	1143.12	137	153.36	-9	9.5	9.5	9.06	0.36	0.06	4.37
14	5000	1254	137	157.64	-9	9.5	9.5	9.77	1.02	0.77	3.99
14	5000	1384.35	137	162.52	-9	9.5	9.5	10.58	1.78	1.58	3.61
14	5000	1534.82	137	180	-9	9.5	9.5	11.45	2.62	2.45	3.26
14	5000	1696.11	137	180	-9	9.5	9.5	12.35	3.49	3.35	2.95
14	5000	1863.54	137	180	-9	9.5	9.5	13.28	4.39	4.28	2.68
14	5000	2033.73	137	180	-9	9.5	9.5	14.23	5.32	5.23	2.46
14	5000	2468.51	137	180	-9	9.5	9.5	16.64	7.71	7.64	2.03

15	5000	1147.71	33	153.54	-9	9.5	9.5	9.09	0.38	0.09	4.36
15	5000	1257.57	33	157.77	-9	9.5	9.5	9.8	1.04	0.8	3.98
15	5000	1385.77	33	162.57	-9	9.5	9.5	10.6	1.8	1.6	3.61
15	5000	1535.85	33	180	-9	9.5	9.5	11.47	2.63	2.47	3.26
15	5000	1697.91	33	180	-9	9.5	9.5	12.37	3.5	3.37	2.94
15	5000	1869.13	33	180	-9	9.5	9.5	13.32	4.43	4.32	2.68
15	5000	2042.89	33	180	-9	9.5	9.5	14.28	5.38	5.28	2.45
15	5000	2482.63	33	180	-9	9.5	9.5	16.73	7.79	7.73	2.01
16	5000	1853.8	26.48	227.28	-9	9.5	9.5	9.3	0.41	0.3	2.7
16	5000	2006.98	26.48	231.29	-9	9.5	9.5	9.97	1.06	0.97	2.49
16	5000	2186.38	26.48	235.9	-9	9.5	9.5	10.73	1.81	1.73	2.29
16	5000	2394.99	26.48	252.5	-9	9.5	9.5	11.58	2.64	2.58	2.09
16	5000	2616.81	26.48	252.5	-9	9.5	9.5	12.45	3.51	3.45	1.91
16	5000	2852.78	26.48	252.5	-9	9.5	9.5	13.39	4.44	4.39	1.75
16	5000	3093.36	26.48	252.5	-9	9.5	9.5	14.34	5.38	5.34	1.62
16	5000	3705.11	26.48	252.5	-9	9.5	9.5	16.76	7.79	7.76	1.35
17	5000	2212.61	75	265.01	-9	9.5	9.5	9.35	0.42	0.35	2.26
17	5000	2389.03	75	268.98	-9	9.5	9.5	10.01	1.07	1.01	2.09
17	5000	2595.66	75	273.55	-9	9.5	9.5	10.77	1.82	1.77	1.93
17	5000	2834.98	75	290	-9	9.5	9.5	11.6	2.65	2.6	1.76
17	5000	3088.48	75	290	-9	9.5	9.5	12.48	3.52	3.48	1.62
17	5000	3358.54	75	290	-9	9.5	9.5	13.41	4.44	4.41	1.49
17	5000	3632.83	75	290	-9	9.5	9.5	14.36	5.39	5.36	1.38
17	5000	4334.69	75	290	-9	9.5	9.5	16.77	7.8	7.77	1.15
18	5000	2218.07	70	265.14	-9	9.5	9.5	9.35	0.43	0.35	2.25
18	5000	2393.73	70	269.08	-9	9.5	9.5	10.01	1.08	1.01	2.09
18	5000	2599.65	70	273.64	-9	9.5	9.5	10.77	1.83	1.77	1.92
18	5000	2838.44	70	290	-9	9.5	9.5	11.61	2.66	2.61	1.76
18	5000	3091.35	70	290	-9	9.5	9.5	12.48	3.52	3.48	1.62
18	5000	3360.93	70	290	-9	9.5	9.5	13.41	4.44	4.41	1.49
18	5000	3636.15	70	290	-9	9.5	9.5	14.36	5.39	5.36	1.38
18	5000	4337.01	70	290	-9	9.5	9.5	16.78	7.8	7.78	1.15

RUN 9 - SUMMARY OUTPUT

Date: 3/2/98

COUSINS DISCHARGE CHANNEL

SENSITIVITY ANALYSIS

NC RECORD BEFORE BEND AND BRIDGE 0.08 0.08 0.06 0.6 0.8

INPUT FILE NAME: DI5K-9M9.DAT

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH
1	5000	984	0	147	-9	9.5	9.5	8	-0.6	-1	5.08
1	5000	1134	0	153	-9	9.5	9.5	9	0.3	0	4.41
1	5000	1290	0	159	-9	9.5	9.5	10	1.23	1	3.88
1	5000	1452	0	165	-9	9.5	9.5	11	2.18	2	3.44
1	5000	1632	0	180	-9	9.5	9.5	12	3.15	3	3.06
1	5000	1812	0	180	-9	9.5	9.5	13	4.12	4	2.76
1	5000	1992	0	180	-9	9.5	9.5	14	5.1	5	2.51
1	5000	2442	0	180	-9	9.5	9.5	16.5	7.57	7.5	2.05
2	5000	859.35	111.61	108	-9	9.5	9.5	7.96	-0.52	-1.04	5.82
2	5000	966.66	111.61	108	-9	9.5	9.5	8.95	0.37	-0.05	5.17
2	5000	1074.51	111.61	108	-9	9.5	9.5	9.95	1.29	0.95	4.65
2	5000	1182.61	111.61	108	-9	9.5	9.5	10.95	2.23	1.95	4.23
2	5000	1290.68	111.61	108	-9	9.5	9.5	11.95	3.18	2.95	3.87
2	5000	1398.91	111.61	108	-9	9.5	9.5	12.95	4.15	3.95	3.57
2	5000	1507.23	111.61	108	-9	9.5	9.5	13.96	5.13	4.96	3.32
2	5000	1778.07	111.61	108	-9	9.5	9.5	16.46	7.59	7.46	2.81
3	5000	867.44	100	108	-9	9.5	9.5	8.03	-0.45	-0.97	5.76
3	5000	971.1	100	108	-9	9.5	9.5	9	0.41	0	5.15
3	5000	1077.19	100	108	-9	9.5	9.5	9.98	1.32	0.98	4.64
3	5000	1184.53	100	108	-9	9.5	9.5	10.97	2.25	1.97	4.22
3	5000	1292.16	100	108	-9	9.5	9.5	11.97	3.2	2.97	3.87
3	5000	1399.99	100	108	-9	9.5	9.5	12.97	4.16	3.97	3.57
3	5000	1508.04	100	108	-9	9.5	9.5	13.97	5.14	4.97	3.32
3	5000	1778.51	100	108	-9	9.5	9.5	16.47	7.59	7.47	2.81
4	5000	939.2	33.2	113.5	-9	9.5	9.5	8.27	-0.29	-0.73	5.32
4	5000	1040.72	33.2	113.5	-9	9.5	9.5	9.17	0.53	0.17	4.8
4	5000	1147.23	33.2	113.5	-9	9.5	9.5	10.11	1.4	1.11	4.36
4	5000	1256.43	33.2	113.5	-9	9.5	9.5	11.07	2.32	2.07	3.98
4	5000	1367.01	33.2	113.5	-9	9.5	9.5	12.04	3.25	3.04	3.66
4	5000	1478.62	33.2	113.5	-9	9.5	9.5	13.03	4.21	4.03	3.38
4	5000	1590.9	33.2	113.5	-9	9.5	9.5	14.02	5.17	5.02	3.14
4	5000	1873.09	33.2	113.5	-9	9.5	9.5	16.5	7.61	7.5	2.67

5	5000	1033.39	49	121	-9	9.5	9.5	8.54	-0.1	-0.46	4.84
5	5000	1133.1	49	121	-9	9.5	9.5	9.36	0.67	0.36	4.41
5	5000	1240.83	49	121	-9	9.5	9.5	10.25	1.51	1.25	4.03
5	5000	1353.21	49	121	-9	9.5	9.5	11.18	2.4	2.18	3.69
5	5000	1468.25	49	121	-9	9.5	9.5	12.13	3.31	3.13	3.41
5	5000	1585.17	49	121	-9	9.5	9.5	13.1	4.26	4.1	3.15
5	5000	1703.32	49	121	-9	9.5	9.5	14.08	5.21	5.08	2.94
5	5000	2000.46	49	121	-9	9.5	9.5	16.54	7.64	7.54	2.5
6	5000	1157.47	48.7	132	-9	9.5	9.5	8.77	0.06	-0.23	4.32
6	5000	1259.29	48.7	132	-9	9.5	9.5	9.54	0.78	0.54	3.97
6	5000	1371.66	48.7	132	-9	9.5	9.5	10.39	1.6	1.39	3.65
6	5000	1490.5	48.7	132	-9	9.5	9.5	11.29	2.47	2.29	3.35
6	5000	1613.24	48.7	132	-9	9.5	9.5	12.22	3.37	3.22	3.1
6	5000	1738.72	48.7	132	-9	9.5	9.5	13.17	4.3	4.17	2.88
6	5000	1866.03	48.7	132	-9	9.5	9.5	14.14	5.25	5.14	2.68
6	5000	2188.91	48.7	132	-9	9.5	9.5	16.58	7.66	7.58	2.28
7	5000	1328.38	56.6	148	-9	9.5	9.5	8.98	0.2	-0.02	3.76
7	5000	1436.22	56.6	148	-9	9.5	9.5	9.7	0.89	0.7	3.48
7	5000	1557.25	56.6	148	-9	9.5	9.5	10.52	1.68	1.52	3.21
7	5000	1686.71	56.6	148	-9	9.5	9.5	11.4	2.53	2.4	2.96
7	5000	1821.47	56.6	148	-9	9.5	9.5	12.31	3.42	3.31	2.75
7	5000	1959.97	56.6	148	-9	9.5	9.5	13.24	4.34	4.24	2.55
7	5000	2101.03	56.6	148	-9	9.5	9.5	14.2	5.28	5.2	2.38
7	5000	2460.21	56.6	148	-9	9.5	9.5	16.62	7.69	7.62	2.03
8	5000	1480.78	53.8	162.5	-9	9.5	9.5	9.11	0.29	0.11	3.38
8	5000	1594.89	53.8	162.5	-9	9.5	9.5	9.81	0.97	0.81	3.14
8	5000	1724.25	53.8	162.5	-9	9.5	9.5	10.61	1.74	1.61	2.9
8	5000	1863.65	53.8	162.5	-9	9.5	9.5	11.47	2.58	2.47	2.68
8	5000	2009.5	53.8	162.5	-9	9.5	9.5	12.37	3.46	3.37	2.49
8	5000	2159.94	53.8	162.5	-9	9.5	9.5	13.29	4.38	4.29	2.31
8	5000	2311.89	53.8	162.5	-9	9.5	9.5	14.24	5.31	5.24	2.16
8	5000	2704.54	53.8	162.5	-9	9.5	9.5	16.65	7.7	7.65	1.85
9	5000	1596.41	47.7	173.5	-9	9.5	9.5	9.2	0.35	0.2	3.13
9	5000	1715.35	47.7	173.5	-9	9.5	9.5	9.89	1.02	0.89	2.91
9	5000	1851.05	47.7	173.5	-9	9.5	9.5	10.67	1.78	1.67	2.7
9	5000	1996.38	47.7	173.5	-9	9.5	9.5	11.52	2.61	2.52	2.5
9	5000	2150.83	47.7	173.5	-9	9.5	9.5	12.4	3.49	3.4	2.32
9	5000	2310.47	47.7	173.5	-9	9.5	9.5	13.32	4.4	4.32	2.16
9	5000	2473.71	47.7	173.5	-9	9.5	9.5	14.26	5.33	5.26	2.02
9	5000	2890.46	47.7	173.5	-9	9.5	9.5	16.67	7.72	7.67	1.73

10	5000	1665.11	40.9	180	-9	9.5	9.5	9.26	0.4	0.26	3
10	5000	1786.76	40.9	180	-9	9.5	9.5	9.93	1.05	0.93	2.8
10	5000	1926.08	40.9	180	-9	9.5	9.5	10.71	1.81	1.71	2.6
10	5000	2076.5	40.9	180	-9	9.5	9.5	11.55	2.64	2.55	2.41
10	5000	2235.74	40.9	180	-9	9.5	9.5	12.43	3.51	3.43	2.24
10	5000	2400.6	40.9	180	-9	9.5	9.5	13.34	4.41	4.34	2.08
10	5000	2569.37	40.9	180	-9	9.5	9.5	14.28	5.34	5.28	1.95
10	5000	3001.53	40.9	180	-9	9.5	9.5	16.68	7.72	7.68	1.67
11	5000	1672.12	35	180	-9	9.5	9.5	9.29	0.43	0.29	2.99
11	5000	1792.43	35	180	-9	9.5	9.5	9.96	1.08	0.96	2.79
11	5000	1930.62	35	180	-9	9.5	9.5	10.73	1.83	1.73	2.59
11	5000	2080.99	35	180	-9	9.5	9.5	11.56	2.65	2.56	2.4
11	5000	2239.42	35	180	-9	9.5	9.5	12.44	3.52	3.44	2.23
11	5000	2403.64	35	180	-9	9.5	9.5	13.35	4.42	4.35	2.08
11	5000	2571.91	35	180	-9	9.5	9.5	14.29	5.35	5.29	1.94
11	5000	3003.24	35	180	-9	9.5	9.5	16.68	7.73	7.68	1.66
12	5000	1169.34	33.1	154.38	-9	9.5	9.5	9.23	0.51	0.23	4.28
12	5000	1275.47	33.1	158.45	-9	9.5	9.5	9.91	1.15	0.91	3.92
12	5000	1400.41	33.1	163.11	-9	9.5	9.5	10.69	1.88	1.69	3.57
12	5000	1547.54	33.1	180	-9	9.5	9.5	11.53	2.69	2.53	3.23
12	5000	1707.2	33.1	180	-9	9.5	9.5	12.42	3.55	3.42	2.93
12	5000	1872.33	33.1	180	-9	9.5	9.5	13.34	4.45	4.34	2.67
12	5000	2041.28	33.1	180	-9	9.5	9.5	14.27	5.37	5.27	2.45
12	5000	2474.82	33.1	180	-9	9.5	9.5	16.68	7.74	7.68	2.02
13	5000	1203.5	103	155.7	-9	9.5	9.5	9.45	0.72	0.45	4.15
13	5000	1302.5	103	159.47	-9	9.5	9.5	10.08	1.31	1.08	3.84
13	5000	1421.48	103	163.89	-9	9.5	9.5	10.81	2.01	1.81	3.52
13	5000	1566.48	103	180	-9	9.5	9.5	11.64	2.79	2.64	3.19
13	5000	1720.98	103	180	-9	9.5	9.5	12.49	3.63	3.49	2.91
13	5000	1881.18	103	180	-9	9.5	9.5	13.39	4.5	4.39	2.66
13	5000	2048.05	103	180	-9	9.5	9.5	14.32	5.41	5.32	2.44
13	5000	2476.99	103	180	-9	9.5	9.5	16.7	7.76	7.7	2.02
14	5000	1223.05	137	156.45	-9	9.5	9.5	9.58	0.83	0.58	4.09
14	5000	1318.15	137	160.06	-9	9.5	9.5	10.18	1.4	1.18	3.79
14	5000	1433.79	137	164.34	-9	9.5	9.5	10.89	2.08	1.89	3.49
14	5000	1577.5	137	180	-9	9.5	9.5	11.7	2.85	2.7	3.17
14	5000	1729.05	137	180	-9	9.5	9.5	12.54	3.67	3.54	2.89
14	5000	1888.6	137	180	-9	9.5	9.5	13.43	4.53	4.43	2.65
14	5000	2053.61	137	180	-9	9.5	9.5	14.34	5.43	5.34	2.43
14	5000	2481.89	137	180	-9	9.5	9.5	16.71	7.78	7.71	2.01

15	5000	1226.84	33	156.6	-9	9.5	9.5	9.6	0.86	0.6	4.08
15	5000	1321.29	33	160.18	-9	9.5	9.5	10.2	1.42	1.2	3.78
15	5000	1436.34	33	164.43	-9	9.5	9.5	10.9	2.09	1.9	3.48
15	5000	1579.66	33	180	-9	9.5	9.5	11.71	2.86	2.71	3.17
15	5000	1732.79	33	180	-9	9.5	9.5	12.56	3.69	3.56	2.89
15	5000	1896.18	33	180	-9	9.5	9.5	13.47	4.58	4.47	2.64
15	5000	2064.22	33	180	-9	9.5	9.5	14.4	5.49	5.4	2.42
15	5000	2494.86	33	180	-9	9.5	9.5	16.79	7.86	7.79	2
16	5000	1964.05	26.48	230.18	-9	9.5	9.5	9.78	0.88	0.78	2.55
16	5000	2096.11	26.48	233.59	-9	9.5	9.5	10.35	1.44	1.35	2.39
16	5000	2257.66	26.48	252.5	-9	9.5	9.5	11.03	2.11	2.03	2.21
16	5000	2454.78	26.48	252.5	-9	9.5	9.5	11.81	2.88	2.81	2.04
16	5000	2664.76	26.48	252.5	-9	9.5	9.5	12.64	3.7	3.64	1.88
16	5000	2890.17	26.48	252.5	-9	9.5	9.5	13.54	4.58	4.54	1.73
16	5000	3122.95	26.48	252.5	-9	9.5	9.5	14.46	5.5	5.46	1.6
16	5000	3722.16	26.48	252.5	-9	9.5	9.5	16.83	7.86	7.83	1.34
17	5000	2339.58	75	267.87	-9	9.5	9.5	9.82	0.89	0.82	2.14
17	5000	2491.69	75	271.26	-9	9.5	9.5	10.38	1.45	1.38	2.01
17	5000	2678.17	75	290	-9	9.5	9.5	11.06	2.12	2.06	1.87
17	5000	2903.26	75	290	-9	9.5	9.5	11.84	2.88	2.84	1.72
17	5000	3143.33	75	290	-9	9.5	9.5	12.67	3.7	3.67	1.59
17	5000	3401.35	75	290	-9	9.5	9.5	13.55	4.59	4.55	1.47
17	5000	3666.76	75	290	-9	9.5	9.5	14.47	5.5	5.47	1.36
17	5000	4354.26	75	290	-9	9.5	9.5	16.84	7.86	7.84	1.15
18	5000	2344.48	70	267.98	-9	9.5	9.5	9.83	0.9	0.83	2.13
18	5000	2496.02	70	271.35	-9	9.5	9.5	10.39	1.45	1.39	2
18	5000	2682.29	70	290	-9	9.5	9.5	11.07	2.12	2.07	1.86
18	5000	2906.55	70	290	-9	9.5	9.5	11.84	2.89	2.84	1.72
18	5000	3146.09	70	290	-9	9.5	9.5	12.67	3.71	3.67	1.59
18	5000	3403.68	70	290	-9	9.5	9.5	13.56	4.59	4.56	1.47
18	5000	3670.01	70	290	-9	9.5	9.5	14.48	5.5	5.48	1.36
18	5000	4356.56	70	290	-9	9.5	9.5	16.84	7.86	7.84	1.15

COUSINS DISCHARGE CHANNEL

CASE 4

SUMMARY OUTPUT
Date: 4/13/98
COUSINS DISCHARGE CHANNEL
CULVERT AS PER COE DESIGN
INPUT FILE NAME: DICOE.DAT
DISCHARGE 5,000 cfs

SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	EG	CWSEL	VCH	
1	5000	1243	0	226	-6.5	9.5	9.5	5.5	-0.75	-1	4.02	
1	5000	1469	0	226	-6.5	9.5	9.5	6.5	0.18	0	3.4	
1	5000	1695	0	226	-6.5	9.5	9.5	7.5	1.14	1	2.95	
1	5000	1921	0	226	-6.5	9.5	9.5	8.5	2.11	2	2.6	
1	5000	2147	0	226	-6.5	9.5	9.5	9.5	3.08	3	2.33	
1	5000	2373	0	226	-6.5	9.5	9.5	10.5	4.07	4	2.11	
1	5000	2599	0	226	-6.5	9.5	9.5	11.5	5.06	5	1.92	
1	5000	3164	0	226	-6.5	9.5	9.5	14	7.54	7.5	1.58	
2	5000	1259.35	100	226	-6.5	9.5	9.5	5.58	-0.68	-0.92	3.97	
2	5000	1478.48	100	226	-6.5	9.5	9.5	6.54	0.22	0.04	3.38	
2	5000	1700.95	100	226	-6.5	9.5	9.5	7.53	1.16	1.03	2.94	
2	5000	1924.96	100	226	-6.5	9.5	9.5	8.52	2.12	2.02	2.6	
2	5000	2149.76	100	226	-6.5	9.5	9.5	9.51	3.1	3.01	2.33	
2	5000	2375	100	226	-6.5	9.5	9.5	10.51	4.08	4.01	2.11	
2	5000	2600.49	100	226	-6.5	9.5	9.5	11.51	5.06	5.01	1.92	
2	5000	3164.8	100	226	-6.5	9.5	9.5	14	7.54	7.5	1.58	
3	5000	752.45	10	152.52	-6.5	9.5	9.5	5.36	-0.45	-1.14	6.64	CULVERT
3	5000	913.43	10	157.27	-6.5	9.5	9.5	6.4	0.37	-0.1	5.47	BEGINS
3	5000	1077.09	10	161.96	-6.5	9.5	9.5	7.43	1.26	0.93	4.64	
3	5000	1244.2	10	166.61	-6.5	9.5	9.5	8.45	2.2	1.95	4.02	
3	5000	1415.18	10	171.24	-6.5	9.5	9.5	9.46	3.15	2.96	3.53	
3	5000	1590.22	10	175.85	-6.5	9.5	9.5	10.47	4.12	3.97	3.14	
3	5000	1816.84	10	226	-6.5	9.5	9.5	11.48	5.09	4.98	2.75	
3	5000	2386.21	10	226	-6.5	9.5	9.5	13.99	7.56	7.49	2.1	
4	5000	764.69	120	152.89	-6.5	9.5	9.5	5.45	-0.38	-1.05	6.54	CULVERT
4	5000	920.1	120	157.47	-6.5	9.5	9.5	6.45	0.41	-0.05	5.43	ENDS
4	5000	1081.39	120	162.08	-6.5	9.5	9.5	7.45	1.29	0.95	4.62	
4	5000	1247.14	120	166.69	-6.5	9.5	9.5	8.46	2.21	1.96	4.01	
4	5000	1417.27	120	171.29	-6.5	9.5	9.5	9.47	3.16	2.97	3.53	
4	5000	1591.8	120	175.89	-6.5	9.5	9.5	10.47	4.13	3.97	3.14	
4	5000	1818.42	120	226	-6.5	9.5	9.5	11.48	5.1	4.98	2.75	
4	5000	2385.3	120	226	-6.5	9.5	9.5	13.99	7.56	7.49	2.1	

5	5000	1368.59	10	226	-6.5	9.5	9.5	6.05	-0.24	-0.45	3.65
5	5000	1544.71	10	226	-6.5	9.5	9.5	6.83	0.5	0.33	3.24
5	5000	1745.04	10	226	-6.5	9.5	9.5	7.72	1.35	1.22	2.87
5	5000	1956.13	10	226	-6.5	9.5	9.5	8.66	2.26	2.16	2.56
5	5000	2172.73	10	226	-6.5	9.5	9.5	9.61	3.2	3.11	2.3
5	5000	2392.45	10	226	-6.5	9.5	9.5	10.59	4.15	4.09	2.09
5	5000	2613.11	10	226	-6.5	9.5	9.5	11.56	5.12	5.06	1.91
5	5000	3170.83	10	226	-6.5	9.5	9.5	14.03	7.57	7.53	1.58
6	5000	1206.39	100	200	-6.5	9.5	9.5	6.03	-0.2	-0.47	4.14
6	5000	1363.43	100	200	-6.5	9.5	9.5	6.82	0.53	0.32	3.67
6	5000	1541.29	100	200	-6.5	9.5	9.5	7.71	1.37	1.21	3.24
6	5000	1728.53	100	200	-6.5	9.5	9.5	8.64	2.27	2.14	2.89
6	5000	1922.23	100	200	-6.5	9.5	9.5	9.6	3.21	3.1	2.6
6	5000	2116.66	100	200	-6.5	9.5	9.5	10.58	4.16	4.08	2.36
6	5000	2311.99	100	200	-6.5	9.5	9.5	11.55	5.13	5.05	2.16
6	5000	2806.33	100	200	-6.5	9.5	9.5	14.02	7.57	7.52	1.78
7	5000	1163.9	152	190	-6.5	9.5	9.5	6.13	-0.09	-0.37	4.3
7	5000	1304.81	152	190	-6.5	9.5	9.5	6.88	0.61	0.38	3.83
7	5000	1470.46	152	190	-6.5	9.5	9.5	7.74	1.42	1.24	3.4
7	5000	1645.72	152	190	-6.5	9.5	9.5	8.67	2.31	2.17	3.04
7	5000	1827.14	152	190	-6.5	9.5	9.5	9.62	3.24	3.12	2.74
7	5000	2011.45	152	190	-6.5	9.5	9.5	10.59	4.18	4.09	2.49
7	5000	2196.72	152	190	-6.5	9.5	9.5	11.56	5.14	5.06	2.28
7	5000	2665.38	152	190	-6.5	9.5	9.5	14.03	7.58	7.53	1.88
8	5000	1170.64	50	190	-6.5	9.5	9.5	6.17	-0.05	-0.33	4.27
8	5000	1311.22	50	190	-6.5	9.5	9.5	6.9	0.63	0.4	3.81
8	5000	1474.59	50	190	-6.5	9.5	9.5	7.76	1.44	1.26	3.39
8	5000	1648.99	50	190	-6.5	9.5	9.5	8.68	2.32	2.18	3.03
8	5000	1829.25	50	190	-6.5	9.5	9.5	9.63	3.24	3.13	2.73
8	5000	2012.86	50	190	-6.5	9.5	9.5	10.59	4.19	4.09	2.48
8	5000	2197.68	50	190	-6.5	9.5	9.5	11.57	5.15	5.07	2.28
8	5000	2665.75	50	190	-6.5	9.5	9.5	14.03	7.59	7.53	1.88
9	5000	1177.92	33	190	-6.5	9.5	9.5	6.2	-0.02	-0.3	4.24 BRIDGE
9	5000	1316.32	33	190	-6.5	9.5	9.5	6.93	0.65	0.43	3.8 BEGINS
9	5000	1478.07	33	190	-6.5	9.5	9.5	7.78	1.46	1.28	3.38
9	5000	1651.5	33	190	-6.5	9.5	9.5	8.69	2.33	2.19	3.03
9	5000	1855.12	33	190	-6.5	9.5	9.5	9.76	3.38	3.26	2.7
9	5000	2042.43	33	190	-6.5	9.5	9.5	10.75	4.34	4.25	2.45
9	5000	2230.07	33	190	-6.5	9.5	9.5	11.74	5.32	5.24	2.24
9	5000	2701.61	33	190	-6.5	9.5	9.5	14.22	7.77	7.72	1.85


10	5000	1221.24	26.48	219.95	-6.5	9.5	9.5	6.24	0	-0.26	4.09	BRIDGE
10	5000	1382.59	26.48	225.57	-6.5	9.5	9.5	6.96	0.67	0.46	3.62	ENDS
10	5000	1576.62	26.48	232.16	-6.5	9.5	9.5	7.81	1.47	1.31	3.17	
10	5000	1794.37	26.48	252.5	-6.5	9.5	9.5	8.72	2.34	2.22	2.79	
10	5000	2064.42	26.48	252.5	-6.5	9.5	9.5	9.79	3.38	3.29	2.42	
10	5000	2312.7	26.48	252.5	-6.5	9.5	9.5	10.78	4.35	4.28	2.16	
10	5000	2561.44	26.48	252.5	-6.5	9.5	9.5	11.76	5.32	5.26	1.95	
10	5000	3184.67	26.48	252.5	-6.5	9.5	9.5	14.24	7.77	7.74	1.57	
11	5000	1490.2	75	258.5	-6.5	9.5	9.5	6.38	0.05	-0.12	3.36	
11	5000	1669.85	75	263.84	-6.5	9.5	9.5	7.06	0.7	0.56	2.99	
11	5000	1888.92	75	270.21	-6.5	9.5	9.5	7.88	1.49	1.38	2.65	
11	5000	2136.94	75	290	-6.5	9.5	9.5	8.78	2.36	2.28	2.34	
11	5000	2442.56	75	290	-6.5	9.5	9.5	9.83	3.39	3.33	2.05	
11	5000	2722.17	75	290	-6.5	9.5	9.5	10.8	4.36	4.3	1.84	
11	5000	3006.63	75	290	-6.5	9.5	9.5	11.78	5.33	5.28	1.66	
11	5000	3723.05	75	290	-6.5	9.5	9.5	14.25	7.78	7.75	1.34	
12	5000	1500.59	70	258.81	-6.5	9.5	9.5	6.41	0.08	-0.09	3.33	
12	5000	1677.19	70	264.06	-6.5	9.5	9.5	7.09	0.72	0.59	2.98	
12	5000	1894	70	270.36	-6.5	9.5	9.5	7.9	1.51	1.4	2.64	
12	5000	2140.92	70	290	-6.5	9.5	9.5	8.79	2.37	2.29	2.34	
12	5000	2445.1	70	290	-6.5	9.5	9.5	9.84	3.4	3.34	2.04	
12	5000	2726.83	70	290	-6.5	9.5	9.5	10.81	4.36	4.31	1.83	
12	5000	3010.23	70	290	-6.5	9.5	9.5	11.79	5.33	5.29	1.66	
12	5000	3725.17	70	290	-6.5	9.5	9.5	14.25	7.78	7.75	1.34	

COUSINS CANAL
EXISTING CONDITIONS

COUSCAN

INPUT FILE: COUSCAN.DAT											
SUMMARY PRINTOUT											
DATE: 10-08-97											
SECNO	QCH	AREA	XLCH	TOPWID	ELMIN	XLBEL	RBEL	DEPTH	CWSEL	VCH	
1	2000	1391.56	0	183.86	-18.96	-1.8	-1.83	12.26	-6.7	1.44	
*	2	2000	861.44	110	130.66	-16.12	-3.49	-1.04	9.39	-6.73	2.32
	3	2000	763.19	105	109.6	-16.49	-3.69	-1.8	9.77	-6.72	2.62
*	4	2000	520.46	500	85.05	-17.22	-0.95	0.24	10.58	-6.64	3.84
*	5	2000	267.04	500	52.13	-14.62	2.1	1.15	8.07	-6.55	7.49
*	6	2000	333.22	500	52.06	-14.66	0.96	0.78	9.43	-5.23	6
	7	2000	277.46	500	47.57	-13.3	0.01	-0.11	8.78	-4.52	7.21

Water Surface Profile in Cousins Canal (Discharge 2,000 cfs)



APPENDIX C
MECHANICAL MACHINERY

APPENDIX C
MECHANICAL MACHINERY

SECTION C1 - DIESEL ENGINES

PART 1 - GENERAL

C1-1. **SCOPE.** The work provided for herein consists of furnishing all plant, labor, equipment and material and performing all operations required to design; manufacture; assemble; factory test; prepare for shipment and storage; deliver; provide instructions and supervision for erection by others under a separate contract; field test with the auxiliaries and accessories as specified; a minimum of one engine to be furnished under this contract for the horizontal pump(s) specified in Section C2. These requirements shall also apply for up to seven identical diesel engines if required.

C1-2. **QUALITY CONTROL.**

C1-2.1 **General.** The Contractor shall establish and maintain quality control for all manufacturing, fabrication, factory tests, preparation for shipment, shipment, erection instructions and supervision, and field testing to assure compliance with contract requirements and to maintain records of his/her quality control for all fabrication, erection, and testing operations, including but not limited to the following:

- (1) Shop welding, machine work and fabrication, and assembly.
- (2) Preparation for shipment and storage.
- (3) Factory tests before shipping.
- (4) Inspection at the work site for damage to and defects in material and equipment.

C1-2.2 **Reporting.** Two copies of the records of inspections, shop fabrication and assembly and tests as well as the corrective action taken, shall be furnished the Government as directed by the Contracting Officer.

C1-3. **DESCRIPTION OF WORK.**

C1-3.1 **General.** Except for paragraph C1-17, "SPECIAL TOOLS", and paragraph C1-16, "SPARE PARTS", the following paragraphs prescribe the minimum requirements for one

engine, but these requirements shall apply for up to seven engines to be furnished under these specifications. Similar parts of the engines shall be of the same materials and workmanship and, insofar as practicable, shall be interchangeable. The engine will be used to drive a pump through a speed reducer. The engine shall be adequately designed and conservatively rated to provide a reliable, efficient and smooth power source under all operating conditions.

C1-3.2 Standard Products. Except as otherwise specified herein, the engine shall be a new, currently manufactured standard production item of a manufacturer regularly engaged in the production of such equipment, as indicated by published information, commercially available prior to the date of advertisement of this solicitation. Information shall be furnished with each bid showing that the exact diesel engine proposed has a proven and satisfactory service record of not less than two (2) years operating at not less than 1200 hours per year, having the same bore and stroke and the same block, camshaft, main and connecting rod bearings, at the same brake horsepower, BMEP, piston speed and rotative speed as the engine offered.

C1-3.2.1 The engine shall be offered only at the speed and rating for which it has been designed, and shall operate on No. 2 diesel fuel. The engine shall conform to the standards set forth by the Diesel Engine Manufacturers Association. An experimental engine, one having a lesser or greater number of cylinders than the standard production engine, or one without a demonstrated satisfactory service record will be rejected.

C1-3.2.2 The manufacturer's representative shall maintain a local parts storage facility located within a 100 mile radius of the pumping station capable of supplying replacement parts and technical factory authorized service at the pumping station within 4 hours of being notified.

C1-3.2.3 The diesel engine with accessories, the engine control panel, the speed reducer, and the horizontal pump shall be supplied together as a complete pumping unit by the pump supplier in order to optimize the compatibility of components.

C1-3.2.4 The engine shall be similar and equal to the applicable models manufactured by Alco Power Inc., Fairbanks-Morse Division of Colt Industries, or General Motors, Electromotive Division, or approved equal.

C1-3.3 Engine Characteristics. A two cycle, turbo charged intercooled engine is preferred, however the engine provided under these specifications may be either a two or four cycle, straight start diesel engine, naturally aspirated or turbo charged, intercooled, with mechanical injection, compressed air start and remote radiator cooling capable of operating on No. 2 diesel fuel. The engine shall include all standard equipment and systems and shall be suitable for variable speed/variable load operation at all speeds from idle to maximum.

C1-3.4 Engine Rotation. The direction of rotation of the engine, pump and reduction gear shall be coordinated by the pump supplier. It is intended that the engine deliver power in only one direction. An anti-reverse backstop device shall be installed on the high speed shaft of

the speed reducer by the speed reducer manufacturer.

C1-3.5 Engine Skid. The engine shall be mounted on a steel skid type base structure upon which all engine auxiliary equipment and accessories shall be located and completely piped and wired, except for the engine control panel, the air inlet filter and the exhaust silencer. The mating surfaces between the skid and the engine shall be machined only after complete fabrication of the skid and stress relief of all welds. Final machining of mating surfaces on individual components of the skid prior to final assembly and stress relief of welds will be unacceptable. All shim material shall be stainless steel. The skid shall have an appropriately sized opening with a bolted cover plate to permit maintenance personnel to access the underside of the engine after its installation on the operating floor.

C1-3.6 Installation. The engine will be installed by others under a separate contract. It will be directly anchored and grouted to the concrete floor as shown on the drawings without the use of vibration isolators. All stainless steel anchor bolts, nuts, washers, sleeves, shims, wedge plates and other items required for the engine installation shall be supplied by the engine manufacturer.

C1-3.7 Power Takeoff. The engine will normally be started with a dry pump. Flooding or priming of the impeller will take place after the engine has reached operating speed. As a result, no clutch is required. A straight drive through the reduction gear is required for driving the pump. The engine manufacturer shall coordinate his/her flywheel requirements with the pump and speed reducer manufacturers. The reduction gear shall be coupled as close as possible to the engine power take-off through a coupling and shaft supplied by the speed reducer manufacturer as specified in Section C3.

C1-3.8 Emissions. The Contractor shall submit certified test reports which verify that the engine complies with all Federal and local regulations and restrictions regarding the limits of emissions such as carbon monoxide (CO), hydrocarbons (HC) and nitrous oxide (NOx).

C1-3.9 Service Platforms. Service platforms, hand railings and stairs to the main floor shall be provided for access to all engine controls and engine points requiring periodic inspection and maintenance.

C1-3.10 Guards. All exposed rotating and hot parts shall be guarded. All guards shall comply with the standards of the Occupational Safety and Health Administration (OSHA).

C1-3.11 Instruments, Meters, Gauges, Motors, and Heater Connections. The engine shall have the fittings necessary for the connection of instruments, meters, and gauges that will be mounted on the engine control panel. All conduit between the engine and control panel shall be stainless steel.

C1-3.11.1 The engine control panel shall be as specified in Section C4.

C1-3.11.2 A terminal box shall be provided on the engine skid in close proximity to the location of the engine control panel. The terminal box shall be provided with terminal blocks of ample capacity for the electrical conductors from the engine to the engine control panel. Conduits as required for the protection of electrical circuits shall be provided from the junction box on the engine skid to the connection points on the engine.

C1-3.11.3 A shut off valve shall be provided on all pressure lines. This shut off valve shall be conveniently located on the engine as near the source as possible. Tubing for pressure lines shall be provided from this shut off valve to a tubing terminal block located in the same area of the skid as the junction box.

C1-3.11.4 Connection between the engine mounted monitoring points, motors and heaters and their readouts and controls on the engine control panel shall be made at the electrical junction box and the tubing terminal block. Connection for the following instruments, meters, and gauges which will be mounted on the engine control panel shall be provided:

- (1) Fuel pressure gauge (downstream of pump).
- (2) Fuel differential pressure gauge (across filter).
- (3) Engine lubricating oil differential pressure gauge (across filter).
- (4) Engine lubricating oil (downstream of pump).
- (5) Engine jacket water pressure gauge.
- (6) Engine jacket water temperature gauges (inlet and outlet).
- (7) Engine lubricating oil temperature gauges (inlet and outlet).
- (8) Running time meter.
- (9) Electric tachometer.
- (10) Engine speed control.
- (11) Engine cylinder exhaust temperature pyrometer with a selector switch for each cylinder.
- (12) Engine starting air pressure gauge.
- (13) Lube oil keep warm system on/off switch.

- (14) Lube oil pre-lube pump indicating lights.
- (15) Fuel flow meter (gph).
- (16) Engine start/stop switch.
- (17) Emergency stop button.

C1-3.12 Painting. The engine, skid, its auxiliaries and accessories, except for the intake and exhaust silencers, the stainless steel flexible connectors and other components which will be subjected to high temperatures, and except for those interior surfaces which will be immersed in or otherwise continuously exposed to lubricating oil, shall be cleaned, treated, and primed, in accordance with the manufacturer's standard practice and then given two coats of the manufacturer's standard paint of a battleship gray color with total thickness not less than 3 mils primer and 4 mils enamel. Interior surfaces exposed to lubricating oil shall be cleaned and treated in accordance with the manufacturer's standard practice. Components which will be subject to high temperatures shall be cleaned and treated in accordance with the manufacturer's standard practice and given two coats of heat resistant aluminum paint meeting the applicable requirements of Fed. Spec. TT-P28G "Paint, Aluminum, Heat Resisting (1200 degrees F)." All openings shall be closed with either plastic closures or other lint free material before any priming or painting is done.

C1-3.13 Nameplate. The engine shall be identified by means of a separate nameplate permanently affixed in a conspicuous location. The plate shall bear the manufacturer's name, model designation, serial number, and any other pertinent information such as speed, horsepower, displacement, type, etc. The plate shall be made of stainless steel with raised or depressed lettering and contrasting background.

C1-3.14 Instruction Plates. The engine shall be equipped with suitably located instruction plates, including any warnings and cautions, describing any special and important procedures to be followed in starting, operating and servicing the equipment. Plates shall be made of stainless steel with raised or depressed lettering and contrasting background.

C1-3.15 Torsional Analysis. The entire pumping unit consisting of pump, speed reducer and engine shall operate free from critical speeds or harmful torsional vibrations at all speeds and loads required to obtain the guarantee points and other conditions of head and capacity as listed in paragraph C2-6.3. Before the pump, speed reducer, and engine are released for delivery, the engine supplier shall analyze the system for harmful torsional natural frequencies using mass elastic information supplied by the pump and speed reducer manufacturers. A natural frequency within 25% above or below a normal operating speed will be unacceptable.

PART 2 - PRODUCTS

C1-4. ENGINE. The engine shall be a complete, factory assembled, naturally aspirated or turbocharged/intercooled unit, with the engine and all auxiliaries, except the intake and exhaust silencers, and the engine control panel, mounted on a fabricated steel common base.

C1-4.1 Connections. All internal connections shall be made, and the only connections required to be made at the site of installation (under a separate contract by others) shall be external connections such as those for fuel, starting air, jacket water cooling, exhaust gases, and engine control. All openings shall be sealed with plastic caps, plugs or films, or by an equivalent lint-free technique.

C1-4.2 The engine shall be of the "V" type. The engine shall have a standard net continuous horsepower rating (prime power service) at the engine coupling, at all altitudes up to 500 feet above sea level, with an ambient temperature of 100 degrees F, with all engine driven accessories and speed reducer attached, of not less than that required to operate the pump at the speeds, capacities, and heads specified under paragraph C2-6.3. The net rating of the engine shall be the published long term continuous rating as defined by the Diesel Manufacturers Association Standards including all parasitic and gear losses. The engine shall be able to meet the maximum power requirements of the pumping unit at a maximum engine speed of 900 RPM and a maximum piston speed of 1600 FPM. The maximum Brake Mean Effective Pressure (BMEP) under maximum continuous horsepower ratings shall not exceed the following values:

- a. Two cycle, naturally aspirated.....90 psi
- b. Two cycle, turbocharged/intercooled.....150 psi
- c. Four cycle, naturally aspirated.....95 psi
- d. Four cycle, turbocharged/intercooled.....240 psi

C1-4.2.1 The engine shall be capable of operation at 110 percent of its standard net continuous brake horsepower rating for a period of at least two (2) continuous hours, out of any twenty-four (24) consecutive hours of operation with safe operating temperatures.

C1-5 ENGINE SYSTEMS. All materials shall be new and conform to the standards of The American Society for Testing Materials where such standards are applicable.

C1-5.1 Lubricating System. The engine shall be provided with a full pressure lubricating oil system, consisting of an oil pump, oil strainer, oil filter, oil cooler, oil level indicator or bayonet gauge, lubricating oil keep warm system, prelubricating pump, and sump all arranged to distribute oil to all moving parts of the engine under a predetermined and constant pressure at

rated RPM. The lube oil system shall be completely contained, piped and mounted on the engine skid complete with fill and drain lines.

C1-5.1.1. Lubricating Oil Pump. The engine driven lubricating oil pump or pumps shall be of standard manufacture, shall be easily replaceable as a unit without the necessity of dismantling the engine and shall be conservatively sized to supply the proper amount of oil under pressure to the main bearings, crankpin bearings, pistons, piston pins, timing gears, camshaft bearings, turbocharger bearings, and valve mechanism. The engine driven lubricating oil pump or pumps shall be of the positive displacement type and shall be driven in a positive manner from the engine crankshaft. The pump shall be protected by a relief valve to bypass the oil into the sump with a check valve on the discharge line. A pressure sensor shall be located downstream of the pump to provide signals for low lube oil pressure alarm and shutdown.

C1-5.1.2 Filter. The engine lubricating system shall include a full flow, replaceable cartridge type oil filter(s) with a spring loaded by-pass valve to ensure lubricating oil circulation in the event the filter(s) become clogged. The filter(s) shall have a minimum filtering capability of 10 to 15 microns. The filter(s) shall have the inlet and outlet connections clearly marked. The filter(s) shall be readily accessible and capable of being changed without disconnecting the piping or disturbing other components. An indicating differential pressure sensor shall be provided across the filter.

C1-5.1.3 Strainer. The engine lubricating system shall include a full flow oil strainer ahead of the engine, which shall be capable of filtering down to 80 micron size, or to a size that will prevent clogging or damage of engine components. Easy drainage of sludge shall be accomplished through a drain plug located near the bottom of the shell. A suitable by-pass relief valve shall also be provided.

C1-5.1.4 Oil Cooler. The engine shall be provided with a water cooled lube oil cooler and a thermostatically controlled bypass valve, to maintain the lube oil temperature within the specified limits. The lubricating oil cooler shall be a horizontal shell and tube heat exchanger with seamless copper-nickel tubes not less than 5/8 in. O.D. and cast iron or steel shell with cast iron water boxes and bronze or brass tube sheets. Velocity through the tubes shall not exceed five (5) fps. The tube bundle shall be removable to facilitate cleaning. Other types of coolers standard with the engine manufacturer and with a proven record of service may also be used. Complete data shall be submitted to the Contracting Officer for approval. The cooler shall be of sufficient capacity to maintain the lubricating oil at 185 degrees F regardless of load or ambient temperature. The heat exchanger shall be furnished complete with the necessary base and/or brackets, mounted on the engine base structure and completely piped into the engine lubricating oil system.

C1-5.1.5 Temperature Control Valve. The engine lubricating system shall include a three-way thermostatic bypass valve of appropriate size and temperature rating to maintain the oil temperature within the engine manufacturer's limits while the engine is operating

continuously at either rated or partial loads. The temperature control valve shall have a manual over-ride. Other methods of controlling the lube oil temperature shall be submitted in writing and in adequate detail for approval by the Contracting Officer.

C1-5.1.6 Drain Valve. An easily accessible oil drain valve shall be provided which will permit easy and complete drainage of the engine sump.

C1-5.1.7 Lubricating Oil Keep Warm System. The lubricating system shall include a thermostatically controlled and independently operating lube oil keep warm system complete with pump, immersion heater and all required components to maintain a constant lube oil temperature within the engine of approximately 120 degrees F under a minimum ambient temperature of 20 degrees F when the engine is not operating. The maximum watt density of the immersion heater shall not exceed 13 Watts per square inch of surface area. The immersion heater shall be rated for use in 480 V, 3 ph, 60 hz service. The pump shall be an electric motor driven oil pump with a capacity and head recommended by the engine manufacturer. The pump shall completely fill the oil lines and establish lubricating oil pressure prior to engine start. The pump shall incorporate a built-in relief valve directly connected to the motor and a check valve on the discharge line. The motor-pump assembly shall be mounted on a common cast iron or steel drip lip base, shall be furnished complete with all required controls and shall be suitable for operation on 480 V, 3 ph, 60 hz service. The motor shall be T.E.F.C. conforming to NEMA Standards and shall turn on ball bearings.

C1-5.1.8 Prelubricating Pump. A prelubricating system shall be incorporated to assure proper lubrication when starting and stopping the engine. It shall be interlocked with the engine starting sequence so that it is automatically actuated at each engine start. The pump shall be an electric motor driven oil pump with a capacity and head recommended by the engine manufacturer. The pump shall completely fill the oil lines and establish lubricating oil pressure prior to engine start. The pump shall incorporate a built-in relief valve directly connected to the motor and a check valve on the discharge line. The motor-pump assembly shall be mounted on a common cast iron or steel drip lip base, shall be furnished complete with all required controls and shall be suitable for operation on 480 V, 3 ph, 60 hz service. The motor shall be T.E.F.C. conforming to NEMA Standards and shall turn on ball bearings. If the engine is turbocharged, the turbocharger shall have a separate pump. The engine shall be furnished with the proper amount of clean lube oil in separate containers to match the engine's lube oil capacity.

C1-5.2 Cooling System. The engine cooling system shall be the closed loop, fresh water type, utilizing a 50 per cent ethylene glycol/water solution as coolant with rust inhibiting and water treatment chemicals.

C1-5.2.1 Jacket Water Pump. The engine shall be equipped with an engine driven centrifugal pump or pumps that shall circulate coolant through the engine jacket, cylinder head, intercooler (if used), lube oil cooler, and remote keel cooler (furnished and installed by others). The pump(s) shall be easily replaceable and equipped with shaft seals which will prevent

leakage. The shaft seals shall be of a material that is compatible with the coolant solution of ethylene glycol and which will not dry out in intermittent operation. The pump(s) shall be of sufficient head and capacity to match the engine plus the piping and keel cooler friction losses, assumed to be a maximum of 8 psi external to the engine.

C1-5.2.2 Temperature Control Valve. The cooling system shall contain a three-way thermostatic bypass valve with manual override to maintain the proper jacket water temperature, as specified by the engine manufacturer, under all load conditions. These units shall be mounted on the engine base structure and shall be completely piped and tested before shipment.

C1-5.2.3 An expansion tank shall be provided with the engine. Its volume shall be not less than 15% of the coolant volume in the total system. The tank shall be properly fitted for vent, overflow, expansion, and make up line, and shall be equipped with a sight glass with shut off valves on both ends. The tank shall be suitable for an operating temperature of 250 degrees F, and a working pressure of 125 psig. The tank shall be constructed of welded steel, hot-dipped galvanized inside and outside, fabricated, tested, and stamped in accordance with ASME Boiler and Pressure Vessel Code Section VIII Division I and registered with the National Board of Boiler and Pressure Vessel Inspectors. The tank shall be mounted so that the bottom of the tank is above the top of the engine. The tank shall be supported by steel legs or bases for vertical installation, or steel saddles for horizontal installation.

C1-5.2.4 Jacket Water Keep-Warm System. The cooling system shall be supplied with a thermostatically controlled keep-warm system complete with an immersion heater and all controls required to automatically maintain a jacket water temperature within the engine of 120 degrees F under an ambient temperature of 20 degrees F whenever the engine is not operating. Power for the immersion heater shall be 480V, 3ph, 60hz.

C1-5.2.5 Freeze Protection. The engine shall be furnished with the proper amounts of rust inhibiting and water treatment chemicals plus ethylene glycol, in separate containers, that will result in a 50% concentration of the engine's jacket water volume, plus 20% to accommodate the volume of the keel cooler and the supply and return lines.

C1-5.2.6 Additional Cooling Equipment. If the engine is turbo charged, any additional required heat exchanger or cooling equipment for the air intercoolers shall also be furnished complete with all required pumps, expansion tank, controls, water treating system, bleed-off system and heating system.

C1-5.2.7 Data. The engine manufacturer shall make available upon request all information (such as flow, head, heat rejection, maximum operating temperature, etc.) required for sizing the keel cooler.

C1-5.3 Fuel System. The engine shall operate on ASTM D-975 No. 2 diesel fuel with a minimum cetane No. of 40. The fuel system shall conform to the applicable requirements of

NFPA 37, National Fire Protection Association "Standard for the Installation and Use of Stationary Combustion Engines and Gas Turbines." Fuel supply shall be from an elevated 1,000 gallon day tank furnished by others, installed at a maximum height of 15 ft. above the station floor and a horizontal distance of 20 ft. It shall be equipped with a mechanical fuel injection system consisting of a fuel pump, strainer, filters, safety bypass valve, and an individual injection pump system with single orifice injection valves or unit injectors.

C1-5.3.1 Fuel Pump. The fuel pump shall be engine driven and of a positive displacement design. It shall have the capacity to transfer fuel from the day tank at a rate and pressure as required by the injectors under maximum load conditions, and to return excess fuel from injector manifold back to the day tank.

C1-5.3.2 Fuel Filter. The engine shall be supplied with a minimum of one duplex filter with transflow change over valve. The filter shall be located on the suction side of the fuel pump and shall have the inlet and outlet connections plainly marked. Indicating pressure gauges with connections to the engine control panel shall be provided on the inlet and discharge sides. The filter shall be capable of filtering particles down to 25 micron size.

C1-5.3.3 Strainer. A full flow strainer of the replaceable cartridge type shall be provided between the engine and the day tank, upstream of the fuel filter. An indicating differential pressure gauge with connections to the engine control panel shall be provided across the strainer. The strainer cartridge shall be capable of filtering out particles down to 125 micron size.

C1-5.3.4 Safety Bypass Valve. A safety bypass valve shall be provided next to the pump isolation valve to prevent buildup of excessive pressures if the discharge line or fuel pump filters become clogged. This bypass shall relieve at a pressure that will protect the fuel piping from over-pressurizing and return the fuel to the day tank.

C1-5.4 Starting System. The engine shall be provided with a compressed air starting system. The system shall consist of one or more air driven motors, a start-stop switch on the engine control panel which provides functions including testing, reset, manual-run/ start, manual stop and adjustable cranking and cooling down operation, and an air filter. Compressed air at 150 psig and 16 SCFM will be available.

C1-5.4.1 Air Driven Motor(s). The air driven motor(s) shall include a lubricator, a quick opening valve, a solenoid valve, a pressure reducing valve, a line strainer with a water trap and an automatic bleed off, and all interconnecting piping. Air starting exhaust piping shall terminate under the engine skid in a properly sized collector with a drain valve, to collect all trapped oil and water. The collector shall be located so as to be easily accessible from the front of the engine.

C1-5.5 Induction System. The engine shall be provided with one or more heavy duty,

replaceable element, dry type combination filter- silencer of sufficient capacity to effectively protect the engine from grit and dust. The filter shall be sized to provide the required combustion air under maximum load conditions within acceptable friction losses, while filtering out 95% of AC fine test dust. The filter and silencer shall be designed with a bottom inlet for external installation by others approximately 25 feet from the engine air intake, using 24 inch diameter line and two 90 degree elbows.

C1-5.6 Exhaust System. The engine shall be provided with a vertical exhaust silencer for external installation by others approximately 20 feet from the engine exhaust, using 24 inch diameter line and three 90 degree elbows. It shall be provided with a horizontal flanged inlet, a vertical outlet with a rain cap, and a drain cock. The silencer shall be of all welded construction, of aluminized steel on both internal and external surfaces. Welding electrodes shall be compatible with the silencer material. Any damage to the aluminized finish as a result of welding shall be repaired by wire brushing, cleaning, and protectively covering with a high heat resistant paint matching the aluminized finish. The silencer shall be provided with factory installed brackets for its installation, and a suitable corrugated stainless steel, flanged expansion joint sized to match the engine exhaust port. The pressure drop across the silencer shall not exceed the recommendations of the engine manufacturer under maximum operating conditions. The silencer shall be of the critical "400 level" type with minimum attenuation levels of 40-47 dB(A) under maximum operating conditions.

C1-6. ENGINE COMPONENTS.

C1-6.1 Engine Block. The engine block shall be fabricated of welded structural steel, final machined after all welds have been stress relieved.

C1-6.2 Crankcase. The crankcase shall have inspection covers through which main and connecting rod bearings can be checked and replaced. The engine shall be designed and constructed to withstand crankcase explosions without injury to personnel or damage to the engine. For that purpose several of the inspection covers shall be combination inspection covers and crankcase pressure relief valves. The total free area of the pressure relief valves shall be based on a ratio of not less than 1.5 square inches of relief area per cubic foot of crankcase volume. The combination inspection covers and crankcase pressure relief valves shall be designed to withstand a minimum explosive force of 25 psig. Each combination inspection cover and crankcase pressure relief valve shall incorporate an automatic shutdown device which will automatically shut down the engine when an explosion takes place. A manual reset button shall be provided with each shutdown device. The manual button must be operated on each and every shutdown device before the engine can be started after an explosion.

C1-6.3 Bearings. Main and connecting rod bearings shall be of the precision type with upper and lower removable shells and replaceable tri-metal or aluminum alloy inserts, precision fit with no shimming required.

C1-6.4 Crankshaft. The crankshaft shall be of forged carbon steel or high strength iron alloy of proper design, statically counterweighted and dynamically balanced, with a large thrust bearing and flange for connection to the flywheel at the drive end.

C1-6.5 Pistons. Pistons shall be trunk type made of close grain cast iron, and oil cooled. An aluminum body and skirt with steel cap type is also acceptable.

C1-6.6 Cylinders. The cylinders shall be equipped with full length, fully replaceable cylinder liners, individually cast of high grade cast iron, chrome plated and honed, of the wet type with steel or cast iron cooling jacket.

C1-6.7 Valves. All valves shall be fabricated of alloy steel with hard chrome-cobalt alloy facing, and valve seats (or replaceable inserts) of solid chrome-cobalt alloy. They shall be readily accessible for maintenance and shall be positively rotated each time they lift off the seat.

C1-6.8 Connecting Rods. The connecting rods shall be fabricated of one piece steel forgings with removable, replaceable bearings and bushings.

C1-6.9 Exhaust Manifold. The exhaust manifold shall be liquid cooled unless the engine is turbocharged. If not liquid cooled, the manifold shall be protected by stainless steel heat shields.

C1-6.10 Turbo Charger. If the engine is turbo charged, the turbo charger shall have a single exhaust outlet and replaceable turbine blades. Scavenging and/or turbo chargers shall be driven by the main engine and/or exhaust gasses. Separate electric motors or engine driven blowers and/or superchargers will not be acceptable.

C1-6.11 Barring Device. A hand-operated or pneumatic barring device to turn the engine for inspection or maintenance shall be furnished. If pneumatic, this device shall operate on the starting air pressure system and shall incorporate required safety devices to prevent engagement while the engine is operating.

C1-7. RESERVED.

C1-8. GOVERNOR AND CONTROLS.

C1-8.1 Speed Regulating Governor. An engine driven adjustable mechanical/ hydraulic type speed regulating governor shall be provided to maintain close speed regulation under all load conditions and speed settings from idle to full speed. The speed variation shall not exceed 6% of normal speed when full load is suddenly applied or resumed. The design of the governor shall be such that the engine speed may be changed by governor adjustment during engine operation under load to any speed between 80% and 110% of normal operating speed and the governor shall maintain that speed within 1/2%. The speed fluctuation at any load shall not exceed 2%.

C1-8.2 Overspeed Governor and Load Limit. An emergency governor with overspeed trip shall be provided on the engine to shut down the unit should the speed exceed a pre-determined rpm. The overspeed trip shall also provide an alarm signal for remote indication in the engine control panel. The emergency governor shall be independent of the regulating governor. When the overspeed stop has been tripped, the shutdown mechanism shall be such that the engine fuel or air supply is prevented in the shortest time practicable from entering the engine cylinders. The engine shall have an overload fuel limit set at 110% of full load rating.

C1-8.3 Mechanical Shutdown Device. The engine shall be equipped with a mechanical shutdown device that will, when manually actuated, shut down the engine in the shortest practicable time. This device shall not depend on any electrical device for its operation, and the lever or button used to actuate the mechanical shutdown device shall be mounted on the engine and be easily accessible to the operating personnel. The lever or button shall be clearly marked and identified.

C1-9. NORMAL AND EMERGENCY SHUTDOWN.

C1-9.1 General. Using the controls furnished with the engine control panel and the governors furnished with the engine, the engine shall be capable of automatic shutdown. There shall be two types of shutdown using the controls and governors: normal shutdown and emergency shutdown.

C1-9.2 Normal Shutdown. In the normal shutdown mode, the engine shall slow down to an idle speed setting, idle at this speed for a predetermined period of time, and then automatically shut down. Manually operating the "STOP" pushbutton in the engine control panel shall stop the engine in the normal shutdown mode.

C1-9.3 Emergency Shutdown. In the emergency shutdown mode, the engine's fuel supply shall be shut off to the cylinders and the engine shall come to a stop due to lack of fuel. Conditions that shall stop the engine using the emergency shutdown mode are: low reducer lubricating oil pressure, low engine lubricating oil pressure, high engine jacket water temperature, high engine crankcase pressure, engine overspeed, depressing the "EMERGENCY STOP" button on the engine control panel, and actuating the mechanical shutdown device on the engine. Concurrent with any emergency shutdown shall be visual and audible alarms.

PART 3 - EXECUTION

C1-10. FACTORY TESTS.

C1-10.1 General. One engine of each size supplied shall be subjected to a load test and a fuel consumption test. All engines shall be subjected to start and stop test, emergency shut down tests, governor test, and instrument test.

C1-10.1.1 The engine shall be tested essentially as hereinafter specified, in the manufacturer's or manufacturer's supplier's plant at his/her expense, and in the presence of a representative of the Contracting Officer. A minimum of two weeks notice prior to the test shall be given to the Contracting Officer to arrange for his/her representative to witness the tests.

C1-10.1.2 Major engine failure or repeated minor engine failures during the test will be cause for rejection of the engine. Components which fail or indicate inherent weakness during the test shall be replaced, and the test repeated.

C1-10.1.3 All test apparatus shall be inspected, tested, calibrated and the calibration certified in writing by a competent person or testing agency regularly engaged in that business. The tests shall be run using fuel as specified in paragraph C1-5.3 and using the same lubricating oil and at the pressure which will be used in service. All test results shall be recorded on printed forms standard with the engine manufacturer and which have been submitted to the Contracting Officer for approval prior to commencing the tests. Six bound and certified copies of the test results shall be provided to the Contracting Officer for his/her approval within one week of completion of the tests.

C1-10.1.4 Prior to completion of the first engine, the manufacturer, or manufacturer's supplier, shall submit for approval a description of the various test setups, sample calculation and test procedures he/she proposes to use to test all of the engines and shall include drawings of the test setups showing the test instruments and equipment. Each instrument shall be described in detail, giving all data pertinent or applicable, including but not limited to: Manufacturer's name, type, model number, its degree of accuracy, and certification.

C1-10.2 Load Test. The engine, complete with all attached auxiliaries and including the engine control panel, shall be connected to a calibrated load absorbing device such as a dynamometer, which can simulate accurately the load imposed by the reducer and pump over the full range of heads and capacities. For these tests, full load is interpreted to mean 100% of the power required to operate the pump and speed reducer at its normal rated speed and maximum power requirements.

C1-10.2.1 Exhaust back pressure and intake air friction shall be not less than 80% of the back pressure and friction which will exist after installation at the pumping station site. A mercury barometer, correct to within plus or minimum 0.05 inches of mercury, and subsequently further corrected for temperature, shall be used to obtain the barometric pressure at the test site. Wet and dry bulb temperatures shall be taken at a point near the engine air intake for determination of the true relative humidity of the entering air.

C1-10.2.2 Prior to running the load test, a check test shall be performed to determine that the engine is in suitable condition for tests and to allow a complete check of all instrumentation. Upon satisfactory completion of the check test, the engine shall be run in accordance with the following table.

RUN	FRACTION OF RATED ENGINE LOAD	DURATION HOURS	ENGINE SPEED
1	0	1/4	Min. recommended
2	0	1/4	3/4 x rated
3	1/4	2	3/4 x rated
4	2/4	4	Rated
5	3/4	5	Rated
6	4/4	6	Rated
7	0	1/2	Rated

During the load test the engine shall be closely attended and observed for evidence of excessive temperatures or unusual conditions which may cause damage. Upon satisfactory completion of the load test, the tests described in the following paragraphs shall be performed.

C1-10.3 Fuel Consumption Test. Fuel consumption tests shall be conducted at 2/4 engine load, 3/4 engine load, and 4/4 engine load. Duration of the test at each load condition shall be not less than one hour and may be conducted concurrently with the load test. Tests shall not commence until the engine temperatures and pressures have stabilized. Either the time-weight or the flowmeter technique may be used for this test. If the specified fuel consumption rates are exceeded, the engine shall be rejected, but may be retested after minor adjustment, injector replacement or fuel pump replacement.

C1-10.4 Governor Test. Start the engine, warm it up and while it is operating at rated speed, load it to the full load which it must carry in actual service. The load shall then be entirely removed, without touching the governor adjustment, and the speed measured at no load. Regulation shall be calculated by the formula:

$$R = ((NLS - RLS) \times 100) / RLS$$

where R = regulation in percent, NLS = no load speed, RLS = rated load speed. The test shall be repeated until consistent results are obtained, but not less than three times. Speeds shall be determined by a tachometer. If the regulation exceeds two percent, the governor shall be rejected and another governor installed and tested.

C1-10.5 Start and Stop Test. Using the controls provided with the engine, start and stop the engine not less than three times at minimum load. The engine must start easily and come up to normal idling speed under all ambient air temperatures between 20 degrees F and 110 degrees F. When the "STOP" button is actuated, the engine must slow down to idle and then, after a preset time, shut down. When the "EMERGENCY STOP" button is actuated, the engine must stop immediately.

C1-10.6 Overspeed Test. Disconnect, or otherwise render inoperative, the overspeed governor. Start the engine and slowly increase the speed to 110% of rated speed under maximum load. Maintain this overspeed for not less than 15 minutes. Any evidence of excessive noise or vibration during the test period, or any evidence of injury to, noticeable change in, or destruction of any part, shall be considered as failure of this test. Speed shall be determined by a tachometer.

C1-10.7 Overspeed Protection Device Test. With the overspeed governor operative, start the engine and slowly increase the speed under maximum load until the overspeed protection device goes into operation. The overspeed governor shall not permit operation at speeds greater than 110% of the full load rated speed. Otherwise, it shall be rejected and a new device installed and tested as described above. Speed shall be determined by a tachometer.

C1-10.8 Low Oil Pressure Protective Device Test. With the engine shut down, remove the low oil pressure protective device from the engine, but leave it electrically connected. Starting at the pressure tap on the engine for the protective device, connect in series, going away from the engine, 1) A shut-off valve, 2) The low oil pressure protective device, 3) A master oil pressure gauge, and 4) A bleed valve discharging to atmosphere. Start the engine, bring it up to idling speed and allow it to warm up. Open the bleed valve and purge any air from the test arrangement. Close the bleed valve and record the oil pressure. Close the shut-off valve. Gradually open the bleed valve, observing the pressure gauge, and record the pressure at which the protective device shuts down the engine. If this method of test is not applicable to the engine being tested, the procedure may be altered with the approval of the Contracting Officer. The protective device shall function within plus or minus 10% of the minimum operating pressure prescribed by the engine manufacturer. Otherwise it shall be rejected and a new device tested as described above.

C1-10.9 High Water Temperature Protective Test. Install a master thermometer or a master thermocouple/potentiometer type temperature indicating device at the water outlet connection between the engine and the test radiator or heat exchanger. Start the engine, bring it up to rated speed and record the water temperature once it has stabilized. Block or partially block the cooling water passing through the heat exchanger and load the engine as required to raise the coolant temperature. Record the temperature at which the high water temperature protective device functions. The device shall function within plus or minus 10% of the maximum operative water temperature prescribed by the engine manufacturer. Otherwise it shall be rejected and a new device installed and tested as described above.

C1-10.10 High Crankcase Pressure Limiting Device. Start the engine and bring it to operating speed. Manually trip the shut down device on one of the explosion relief valves. The engine shut down circuit must operate satisfactorily, and shut down the engine. The engine shall be incapable of restarting until the reset button on the explosion relief valve is pushed. Repeat this procedure for the remaining explosion relief valves but without the engine operating. The engine shut down circuit shall be actuated each time the shut down device is tripped. The engine starting circuit shall be incapable of being energized until the reset button is pushed. Any explosion relief valve shut down device that does not send the proper signal shall be rejected and a new device installed and tested as described above.

C1-10.11 Instrument Test. Perform this test from a cold start. Connect the master instruments in parallel with the engine control panel instruments. Set the panel instruments to zero or to the ambient conditions registered by the master instruments. Start the engine and bring it up to idle speed. Read both master and panel instruments concurrently in approximate 20% steps, for the full scale, as the engine comes up to normal operative temperatures and pressures. Variations of more than plus or minus 5% between the indication of the master and panel instruments shall be cause for rejection of the panel instruments. The master instruments shall be the calibrated tachometer thermometers, thermocouple/potentiometer, pressure gauges, fuel scales, flowmeters, and similar devices used for the other tests specified herein.

C1-10.12 Test Results. Upon satisfactory completion of the tests, the engine manufacturer shall certify the results and compile them in a bound book. One original and four copies shall be made available to the Government.

C1-11. FIELD TESTS. Refer to Section C5.

C1-12. PREPARATION FOR SHIPMENT AND PROCESSING FOR STORAGE.

C1-12.1 Shipment. All openings shall be sealed with plastic caps, plugs or films. The engines fabricated structural steel base may serve as a skid for loading, shipping and unloading. All auxiliaries and accessories not attached to engine shall be securely mounted on skids of ample size, and all small parts shall be boxed. The skid mounting and boxing shall be done in a manner which will prevent damage to the engine and its auxiliaries and accessories during loading, shipment, unloading, storage and subsequent handling. Weatherproof covers shall be provided to protect the engine and its auxiliaries and accessories during shipment. Any eyebolts, special slings or devices used in loading the equipment at the manufacturer's plant shall be furnished for unloading and handling at destination and shall become the property of the Government.

C1-12.2 Storage. The engine and all auxiliaries and accessories shall be protectively processed for not less than 12 months storage indoors at the destination. The pump machinery supplier through the engine manufacturer shall furnish for approval by the Contracting Officer a complete description of the processing method or methods used. The Contractor shall make

provisions for regular inspections and maintenance of the engine by an authorized representative of the manufacturer during the estimated 12-month storage period.

C1-13. INSTALLATION AND ERECTION INSTRUCTIONS.

C1-13.1 General. No later than 30 days prior to the time that the engine is delivered, the Contractor shall furnish the Contracting Officer, for approval, three copies of a typed or printed and bound manual describing the procedure to be followed by the erecting engineer in erecting, assembling and installing the engine. To the extent necessary and/or desirable, the description for the engine shall be coordinated and consolidated with the similar descriptions specified for the pump and speed reducer.

C1-13.2 Description Requirements. The description shall be a complete, orderly and step by step explanation of the various operations required, and shall also include such things as bolt torque values, permissible coupling misalignment, recommended instrument setup, recommended gauges and instruments, bearing clearances, and similar details. The description shall be complemented and supplemented by drawings, sketches, photographs, and similar material to whatever extent necessary or desirable to provide a procedure that will be comprehended by an engineer or mechanic without extensive experience in erecting or installing engines of this type.

C1-13.3 Changes. The Contracting Officer will make such changes and/or modifications in the manual as he/she deems necessary or desirable, and return one copy to the Contractor. Five copies of the corrected manual shall be furnished to Contracting Officer.

C1-14. OPERATION AND MAINTENANCE MANUAL AND PARTS LISTS.

C1-14.1 General. The operation and maintenance manual and parts list shall be bound separately, shall be approximately 8-1/2 inches by 11 inches, printed on good quality paper and bound between flexible, durable covers. Drawings incorporated in the manual and/or parts lists may be reduced to page size provided they are clear and easily legible, or may be folded into the manual to page size. Photographs and/or catalog cuts of components may be included for identification.

C1-14.2 Manual. The Contractor shall furnish for approval ten (10) copies of a detailed shop maintenance manual containing complete information in connection with the operation, lubrication, adjustment, routine and/or special maintenance, disassembly, repair and reassembly of the engine. The manual shall include a step by step procedure outline for starting, running, and stopping the engine. This outline shall incorporate the total machinery package, including the pump, gear, engine, and control panel. Included in the procedure outline shall be pre-start instructions such as oil checks, prelube, etc., starting instructions, stopping instructions, and post-operating instructions. The outline shall contain information on all safety and control devices, their function, set points, and resetting instruction. Instructions for shutting down the engine in

case of an emergency shall be included.

C1-14.3 Parts List. The Contractor shall furnish ten (10) copies of the manufacturer's spare parts lists and/or bulletins for the engine. These lists and/or bulletins shall clearly show all details and parts, and all parts shall be adequately described and have proper identification marks.

C1-15. SUBMITTALS.

C1-15.1 General. Within 15 days of receipt of notice of award, the Contractor shall furnish for approval by the Contracting Officer six copies of drawings and other information on the engine and its auxiliaries that he/she proposes to furnish. This information shall be in addition to the information submitted with the bid.

C1-15.2 Drawings. Outline drawings of the engine showing the principal dimensions, the location and size of piping, the location of the tubing terminal block and the electrical junction box on the skid, the size and location of the anchor bolts, the center of gravity of the engine and skid with all mounted accessories and auxiliaries (both dry and wet). A complete set of dimensional drawings, in reproducible form shall be submitted within 60 days of award indicating all above details.

C1-15.2.1 Drawings and descriptive literature of the intake and exhaust silencers, and of the expansion couplings for the exhaust, fuel and other systems, showing dimensions, and materials of construction. The descriptive literature of the exhaust silencer shall indicate the levels of attenuation at different frequencies.

C1-15.3 Descriptive Literature. Descriptive literature, with fully detailed and annotated schematics, describing the operation of all engine systems, including but not limited to the lube oil system, the fuel system, the cooling system, starting system, induction system, exhaust system, monitoring system and emergency shutdown system. The descriptive literature of each system shall include exploded drawings of the system showing and identifying all components.

C1-15.4 Data. The following data shall be submitted:

- (1) Make of engine.
- (2) Model No.
- (3) Number of cylinders.
- (4) Continuous horsepower rating.
- (5) Intermittent horsepower rating.
- (6) Maximum horsepower rating.
- (7) RPM
- (8) Strokes per cycle.
- (9) Turbocharged or naturally aspirated.

- (10) Bore and stroke (in.).
- (11) Displacement (cu. in.).
- (12) Piston speed (fps).
- (13) Maximum torque at rated speed (ft. lb.).
- (14) Compression ratio.
- (15) Brake mean effective pressure (psi).
- (16) Minimum idling speed (RPM).
- (17) Minimum operating speed (RPM).
- (18) Minimum load
- (19) Water cooled exhaust manifold (Yes or No).
- (20) Total weight, wet and dry (Lbs.).
- (21) Lube oil capacity (gallons)
- (22) Jacket water capacity (gallons).
- (23) Heat rejection of jacket water (BTU/min.).
- (24) Heat rejection lube oil cooling water (BTU/min.).
- (25) Heat rejection intercooler water (BTU/min.).
- (26) Heat rejection exhaust manifold (if water cooled) (BTU/ min.).
- (27) Total heat rejection to cooling water (BTU/min.).
- (28) Jacket cooling water (GPM) and optimum temperature (°F), in and out.
- (29) Lube oil cooler water (GPM) and optimum temperature (°F), in and out.
- (30) Intercooler water (GPM) and optimum temperature (°F), in and out.
- (31) Maximum safe jacket water temperature from engine (°F).
- (32) Required keel cooler in and out temperature (°F).
- (33) Allowable pressure drop in remote keel cooler and piping. (psig).
- (34) Fuel oil consumption (Lb./BHP/Hr).
- (35) Lube oil consumption (Gal./Hr).
- (36) Lube oil circulated (GPM) and optimum temperature, to and from engine (°F).
- (37) Maximum safe operating temperature of lube oil (°F).
- (38) Intake air volume (CFM) and allowable pressure drop (psi).
- (39) Exhaust temperature (°F).
- (40) Exhaust volume (CFM or Lb/Hr) and allowable pressure drop (psi).
- (41) Pressure and volume required for air starting system
- (42) Recommended exhaust silencer, critical level, pipe size, diameter.
- (43) Recommended Air Intake Filter.
- (44) Type of injector and Manufacturer.
- (45) Type of governor and Manufacturer.
- (46) Engine driven accessories and required horsepower.

C1-16. SPARE PARTS. The engine manufacturer shall provide, at the time the engine is delivered, the following spare parts:

ITEM	QTY	DESCRIPTION
1	3	Cylinder head complete with valves, cages, springs, etc.
2	3	Cylinder liner (w/liner jacket if applicable), or cylinders with all necessary water seal rings.
3	3	Air starter motor, complete
4	6	Sets of replacement oil filter element
5	6	Sets of replacement fuel oil filter element
6	6	Sets of replacement air filter element
7	3	Engine driven lube oil pump assembly
8	3	Engine driven jacket water pump assembly
9	3	Hydraulic governor

The spare parts shall include any other special items which the manufacturer deems necessary for the engine provided. All spare parts shall be duplicates of the original parts furnished and interchangeable therewith. All spare parts shall be enclosed in separate, sealed moisture proof bags with desiccant bags, and packed in containers plainly marked "SPARE PARTS ONLY". A packing list, indicating the contents of each container, shall be securely fastened, in a moisture-proof envelope, to the outside of the container. The packing list shall also provide the following information:

- (1) Manufacture.
- (2) Contract number.
- (3) Identification, including the manufacturer's drawing number or part number for each spare part in the container.

C1-17. SPECIAL TOOLS. At the time that the engine is delivered to the job site (or storage area), the engine manufacturer shall furnish all "special" tools required to completely assemble, disassemble or maintain the engine. "Special" tools are defined as any special or conventional wrenches with a dimension across the flats greater than one inch, any grossly oversized or special dimension tools of any kind, any special attachments or fixtures, all lifting devices to be used in conjunction with the station crane, or any other similar item. All special tools shall be clearly identified with their intended purpose and shall remain the property of the

Government.

C1-18. LIFTING CONNECTIONS. The engine, as assembled for installation, shall be provided with lifting connections to facilitate handling during loading, unloading and installation. The connections shall be painted yellow for easy identification and shall be so located as to prevent warping or misalignment of the engine or its components.

C1-19. MEASUREMENT AND PAYMENT. No measurement will be made for the manufacture, assembly, factory testing, preparation for storage, and shipment and unloading of the new diesel engine complete with all auxiliaries, accessories and spare parts. Payment for the manufacture, assembly, factory testing, and preparation for storage of the new diesel engine, complete with all auxiliaries, accessories and spare parts will be made at the contract unit price for "Diesel Engine and Auxiliaries." Price and payment shall constitute full compensation for furnishing all plant, labor, materials, equipment, operation and maintenance manuals, spare parts, parts lists, and performing all necessary operations including factory testing and painting.

C1-19.1 Payment for engineering design work for the diesel engines and auxiliaries will be made at the contract lump sum price for "Engineering and Design Service."

C1-19.2 Payment for shipping the diesel engine and unloading at the storage site, complete with all auxiliaries, accessories and spare parts will be made at the contract unit price for "Shipping and Unloading."

SECTION C2 - HORIZONTAL PUMPS

PART 1 - GENERAL

C2-1. SCOPE. Design, model and prototype test, furnish, deliver and unload a minimum of one horizontal axial-flow pump with a nominal capacity of 1000 cfs. Coordinate the suitability for use with the engine, gears and couplings specified in subsequent sections of the contract specifications. Design and furnish pump body and wall sleeve anchorages including threaded bolts and structural steel members for concrete embedment. These requirements shall also apply for up to seven identical horizontal axial-flow pumps.

C2-2. REFERENCES. The publications listed below form a part of this specification to the extent referenced. The publications are referred to in the text by basic designation only.

C2-2.1 Acoustical Society of America (ASA).

ASA S2.19

Mechanical Vibrations - Balance Quality Requirements

(1989) of Rigid Rotors, Part 1: Determination of Permissible Residual
Unbalance

C2-2.2 American Society for Testing and Materials (ASTM).

ASTM A 27-91	Steel Castings, Carbon, for General Applications
ASTM A 36-91	Structural Steel
ASTM A 48-92	Gray Iron Castings
ASTM A 108-90a	Steel Bars, Carbon, Cold Finished, Standard Quality
ASTM A 123-89a	Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products
ASTM A 276-92	Stainless and Heat-Resisting Steel Bars and Shapes
ASTM A 285-90	Pressure Vessel Plates, Carbon Steel, Low- and Intermediate-Tensile Strength
ASTM A 297-89	Steel Casting, Iron-Chromium and Iron-Chromium-Nickel, Heat Resistant, for General Application
ASTM A 312-92	Seamless and Welded Austenitic Stainless Steel Pipes
ASTM A 516-90	Pressure Vessel Plates, Carbon Steel, for Moderate- and Lower-Temperature Service
ASTM A 576-90b	Steel Bars, Carbon, Hot-Wrought, Special Quality
ASTM A 668-91	Steel Forgings, Carbon and Alloy, for General Industrial Use
ASTM B 148-92a	Aluminum-Bronze Sand Castings
ASTM B 584-91a	Copper Alloy Sand Castings for General Applications
ASTM D 2000-90	Rubber Products in Automotive Applications
ASTM E 709-91	Magnetic Particle Examination

C2-2.3 American Society of Mechanical Engineers (ASME).

ASME-16	Boiler and Pressure Vessel Code; Section VIII, Pressure (1992)Vessels, Division 1 - Basic Coverage
ASME-17	Boiler and Pressure Vessel Code; Section IX, Welding (1992) and Brazing Qualifications ASME B4.1 (1967; R 1987) Preferred Limits and Fits for Cylindrical Parts
ASME B16.5	Flanges and Flanged Fittings (1988)
ASME B46.1	Surface Texture (Surface Roughness, Waviness, and Lay) (1985)
ASME B106.1M	Design of Transmission Shafting (Second Printing) (1985)

C2-2.4 American Welding Society (AWS).

AWS D1.1	Structural Welding Code - Steel (1992)
----------	--

C2-2.5 American Water Works Association (AWWA).

AWWA C200	Steel Water Pipe, 6 In. and Larger (1986)
AWWA C203	Coal-Tar Protective Coatings and Linings for Steel Water (1991) Pipelines - Enamel and Tape - Hot-Applied
AWWA C207	Steel Pipe Flanges for Waterworks Service - Sizes 4 In. (1986) Through 144 In.
AWWA C208	Dimensions for Fabricated Steel Water Pipe Fittings (1983; R 1989)

C2-2.6 Hydraulic Institute (HI).

HI-01	Standards for Centrifugal, Rotary & Reciprocating Pumps (1983)
-------	--

C2-2.7 Instrument Society of America (ISA).

ISA RP2.1	Manometer Tables (1985)
-----------	-------------------------

C2-2.8 Steel Structures Painting Council (SSPC).

SSPC Paint 25	Red Iron Oxide, Zinc Oxide, Raw Linseed Oil and Alkyd (1991) Primer (without Lead and Chromate Pigments)
---------------	--

SSPC SP 3	Power Tool Cleaning (1989)
SSPC SP 5	White Metal Blast Cleaning (1991)
SSPC SP 7	Brush-Off Blast Cleaning (1991)

C2-3 SUBMITTALS. Government approval is required for all submittals with a "GA" designation; submittals having an "FIO" designation are for information only. The following shall be submitted in accordance with Section H "Submittal Procedures":

C2-3.1 SD-01, Data.

C2-3.1.1 Lists of Materials; (FIO). Furnish two copies of purchase orders, mill orders, shop orders for materials, and work orders, including orders placed or extended by each supplier. Contractor shall at time of submittal of drawings furnish list designating materials to be used for each item.

C2-3.1.2 Materials; (GA). Furnish, within 60 days of notice of award, names of manufacturers of machinery and other equipment which Contractor contemplates incorporating in the work, together with performance capacities and other relevant information pertaining to the equipment.

C2-3.1.3 Parts List; (FIO). Furnish 10 copies of manufacturer's complete parts list showing all parts and spare parts and bulletins for pump. Clearly show all details and parts, and adequately describe parts or have proper identification marks.

C2-3.1.4 Total Head; (GA). Submit computations of total head and losses.

C2-3.1.5 Shipping Bills; (FIO). Copies of certified shipping bills, in duplicate, shall be mailed promptly to Contracting Officer.

C2-3.1.6 Torsional Analysis; (GA). Submit detailed analysis report.

C2-3.2 SD-04, Drawings.

C2-3.2.1 Drawings; (GA). Within 30 days of notice of award of contract, drawing shall be submitted as listed below. Drawings shall be of sufficient size to be easily read. Drawings notes and dimensions shall be in English. Drawings requiring changes as a result of model test should be submitted within 45 days after approval of model test.

a. Outline drawings of pump showing pertinent dimensions and weight of each component of the pump.

b. Drawing showing details and dimensions of pump mounting design or layout including any embedded items.

c. Cross-sectional drawings of pump showing each component. Major or complicated sections of pump shall be shown in detail. Indicate on each drawing an itemized list of components showing type, grade, and class of material used and make and model number of standard component used.

d. Detail and assembly drawings required for manufacturing showing dimensions, tolerances, and clearances of shafts, bearings, couplings, and packing gland, and diameter and tip clearance of impeller.

e. Drawings covering erection and installation, which Contractor intends to furnish to the erecting engineer.

C2-3.3 SD-06. Instructions.

C2-3.3.1 Installation and Erection Instructions Manual; (GA). No later than 30 days prior to the time of pump delivery, three copies of typed or printed, and bound, manuals shall be furnished describing procedures to be followed by erecting engineer for erecting, assembling, installing, and dry-and wet-testing pump. To the extent necessary or desirable the manuals shall coordinate and consolidate description of pump with similar descriptions specified for gear reducer and diesel engine. Description shall be complete, orderly, step-by-step explanation of operations required, and shall also include such things as alignment procedures, bolt torque values, permissible impeller/impeller casing clearances; permissible impeller casing out-of-roundness; permissible shaft misalignment; recommended instrument setups; recommended gages and instruments; shaft clearances; and similar details.

Description shall be complemented and supplemented by drawings, sketches, photos, and similar materials to whatever extent necessary or desirable, and the overall result shall be a description that may be comprehended by an engineer or mechanic without extensive experience in erecting or installing pumps of this type.

C2-3.3.2 Changes In Installation and Erections Manual; (GA). The Contracting Officer will make changes or modifications as deemed necessary or desirable in the manual, and return one copy to the Contractor. Differences of opinion shall be reconciled in a manner mutually agreeable to the Contractor and Government, and five copies of the corrected manual shall be furnished the Government. The erecting engineer shall follow these instructions when erecting or installing the pumps. Deviation shall be permissible only when agreed to in advance by the Contractor and Government.

C2-3.4 SD-08. Statements.

C2-3.4.1 Test Setup and Procedures; (GA). The Contractor shall, prior to proceeding with the construction of the model, but not later than 90 days after the date of notice to proceed, submit to the Contracting Officer for approval a description of the proposed model and test procedure. Included therein shall be dimensioned drawings and cross-sectional views of the model pump showing the location of all instruments and the point of their connection to the model.

C2-3.4.2 Castings and Casting Repairs; (GA). The Contractor shall submit criteria for acceptance of castings and casting repairs, including welding procedure for each material used, to the Contracting Officer for approval within 90 days of date of notice to proceed.

C2-3.5 SD-14, Samples.

C2-3.5.1 Materials; (GA). Samples of materials shall be submitted as directed. Equipment, materials, and articles installed or used without the approval of the Contracting Officer shall be at risk of subsequent rejection.

C2-3.6 SD-19, Operation and Maintenance Manuals.

C2-3.6.1 Operating and Maintenance Instructions; (FIO). Ten 10 copies of manuals containing complete information on operation, lubrication, adjustment, routine and special maintenance, disassembly, repair, reassembly, list of special tools required, and trouble diagnostics of pump and auxiliary units shall be furnished. Operation and maintenance manual and parts lists shall be bound separately, shall be approximately 8-1/2 inches by 11 inches, printed on good quality paper and bound in three ring loose leaf binder. Drawings incorporated in the manual or parts lists, may be reduced to page size provided they are clear and legible, or may be folded into the manual to page size. Photographs or catalog cuts of components may be included for identification. The manuals shall have one complete set of photo reproducible drawings for the pumps and its components. There shall also be one 24 inch by 36 inch longitudinal cross section of the pump detailing the assembly of all parts.

C2-4. QUALIFICATIONS. Welding operators, welders, and tack welders shall be qualified and, as necessary, requalified for the particular type of work. Qualification shall be in accordance with one of the following codes: Part III, Section 5 of AWS D1.1; or Section IX of ASME-17. Contractor shall certify by name to Contracting Officer the welders and welding operators so qualified, including date of qualification, code, and procedures under which each qualified. Prior qualification may be accepted provided the welder has performed satisfactory work under the code for which he/she qualified within the preceding three months. Contractor shall require welder or welding operator to repeat qualifying tests when, in the opinion of the Contracting Officer, work indicates reasonable doubt as to welder's proficiency. In such cases, welder shall be recertified as required above. The welder shall be considered disqualified until successful completion of retest. All expenses in connection with qualification and requalification shall be borne by the Contractor.

C2-5. REGULATORY REQUIREMENTS. The Contractor shall comply with the following requirements:

- a. Engineer Manual, EM 385-1-1, "Safety and Health Requirements Manual".
- b. Engineer Manual, EM 110-2-3105, "Mechanical and Electrical Design of Pumping Stations" (1962).
- c. Federal Acquisition Regulation, FAR 52.246-2, "Inspection of Supplies - Fixed Price".

C2-6. SYSTEM DESCRIPTION. The pump shall be a constant duty cycle, horizontal shaft, single stage, axial-flow propeller type pump with approximately 132 inch diameter impeller casing and with a nominal capacity of 1000 CFS. The pump shall be designed to provide the performance required by paragraph C2-6.3 "Capacities" and shall be designed to fit between and coupled to the concrete intake and discharge tunnels shown on the contract drawings. The pump shall have the following sections: suction piece, suction elbow, impeller casing, diffuser vane and discharge expansion piece. Thrust loads shall be carried by a horizontal, solid shaft to a thrust bearing mounted inside the pump body. Pump designs based on previously modeled and manufactured pumps are preferred.

C2-6.1 Design Requirements.

- a. The pump is for the purpose of pumping storm water from collection canals into an outfall canal. Water pumped will not exceed 92 degrees F, will be relatively turbid, and may contain sand, silt, and vegetative trash capable of passing trashracks. Trash-racks will have 3 ½-inch clear openings. The pump shall be designed to operate in the dry without harm to the pump and without time or speed restrictions.
- b. The pump shall be a component of a complete system designed to be operated by a horizontal crankshaft diesel engine, as described in Section C1 "Diesel Engines," through a vertical offset horizontal parallel shaft, helical gear speed reducer described in Section C3 "Speed Reducers for Stormwater Pumps." The pump manufacturer shall coordinate the completeness and compatibility of the whole pumping unit including but not limited to; all connections from the pump to the engine, couplings, gears, guards, drive shafts, instrumentation, and controls.
- c. The pump shall be designed to geometrically fit as shown on the contract drawings between the discharge and intake tunnels with no major modifications, alterations, or additions to the pumping station or suction bays to accommodate it. However, requests for changes in setting of pump, supports, and accessories, which would involve only minor modifications, will be considered.

d. The pump manufacturer shall calculate pool to pool pump performance. Pool to pool performance shall take into account the head losses associated with the concrete intake and discharge tubes shown on the contract drawings. Entrance and exit head losses shall be included as well as velocity head losses. Head losses associated with trash racks need not be considered for modeling purposes.

e. Pump priming will be accomplished with the assistance of vacuum equipment supplied by others. As such, the pump shall be made air tight from a negative pressure. Vacuum piping connections for priming shall be located on top of the pump elbow section.

f. Pump anchorages and wall sleeve shall be designed for embedment in concrete.

C2-6.2 Performance Requirements.

a. Maximum level of vibration of assembled pumping unit, consisting of pump, gear reducer, and engine, when tested in the dry as specified in Section C5 "FIELD SERVICES", shall not be greater than the value of lower limit of the "good" range of "General Machinery Vibration Severity Chart". Measurements shall be made at 90%, 95%, 100% and 105% of pump rated speed. The General Machinery Vibration Severity Chart may be obtained from IRD Mechanalysis Inc., 6150 Huntly Rd., Columbus, Ohio 43229.

b. Pump shall be capable of operation without instability over the entire range of heads specified in paragraph C2-6.3. Instability is defined, for this specification, as when one or more of the following conditions occur: pump has two or more flow rates at the same total head; head-capacity curve has a dip (region on curve where change in flow rate produces an abnormally low head); when any point in usable range of head-capacity curve cannot be repeated within 5 percent; when a test point deviates from normal curve by 5 percent.

C2-6.3 Capacities. The pumps furnished shall have the minimum characteristics tabulated in the table that follows. Pumps which deliver more flow, than the minimums listed in the table, at rated head and speed will be rated higher in the Bid Evaluation.

Condition	Minimum quantity (CFS)	Pool-to-pool head (ft.)	Min. pump pool-to-pool efficiency (%)	Water level in suction basin El. (ft. NGVD)	Maximum pump speed (%)
1	915	15	72	-12.00	100
2	1010	13	77	-12.00	100
3	1080	11	74	-10.00	100

4	1150	9	75	-10.00	100
5	1250	5.5	64	-3.5	100
6	960	16.5	72	-8.5	105
7	860	18.0	66	-8.5	105

Table Notes:

a. Elevations are based on National Geodetic Vertical Datum (NGVD) in feet. "CFS" is the abbreviation for Cubic feet per second; "ft." is the abbreviation for feet.

b. Condition 3 is defined as the primary design point.

c. Pool to pool heads shown in the table are defined as the vertical distance in feet between the water surface elevation in the suction basin and the water surface elevation in the discharge basin at the pumping station and do not include any pump intake and discharge tube losses, pump losses, or velocity head losses. All intake and discharge tube losses, sudden contraction and expansion losses as well as frictional losses and velocity head losses are chargeable to the pump and shall be considered pump losses.

d. Condition Nos. 1 thru 5 specified above are for the pump operating at normal (100%) speed which shall not exceed 100 RPM. Horsepower load at conditions 6 inclusive of reduction gear losses, should not exceed the maximum continuous rating of the engine drive. Conditions Nos. 6 and 7 are with the pump operating at a maximum speed of +105% of normal speed. Condition 6 is a condition resulting from a current hurricane, and Condition 7 is a rare condition resulting from a major hurricane on a "critical" path with high tides. Increase in speed shall be allowed if recommended by the pump, gear and engine manufacturers. The horsepower load at Condition 7, inclusive of reduction gear losses shall not exceed the maximum published intermittent load rating of the engine. The pump shaft centerline shall be at elevation 3.00 feet NGVD. The suction pool elevations at the various conditions are shown in the table. Conditions 1 thru 4 represent normal tidal fluctuation and condition 5 represents severe rainstorm flooding the intake bay. Reduced speed performance is not required.

e. The design and speed of the prototype pump shall be such that the pump shall operate in the "good" range of the "General Machinery Vibration Severity Chart" at all conditions specified above. Vibration measurements shall be made in horizontal directions 90 degrees apart and in the vertical direction. Location for the measurements shall be as shown on the contract drawings. In addition, the model test of the pump shall demonstrate operation free of cavitation at all conditions. Test shall be conducted in accordance with paragraph C2-14.2.5.

f. The pump machinery supplier shall guarantee that the pump will meet the performance delineated above with the discharge tube arrangement depicted on the contract plans.

C2-7 DELIVERY, STORAGE AND HANDLING. Shipping and handling bills or memorandums of all shipments of finished pieces or members to designated site shall be furnished, giving designation mark and weight of each piece, number of pieces, total weight, and if shipped by rail in carload lots, car initial and number.

C2-7.1 Processing for Storage.

C2-7.1.1 General. All machined contact or running surfaces, bearings, journals and other such parts of the pump shall be prepared for 24 months of outdoors storage. Unless this processing is as described below, the Contractor shall furnish to the Contracting Officer for approval, 60 days prior to shipment, a complete description of processing method to be used, including complete instructions for maintaining protection. After application of preservatives, pump parts, accessories, auxiliaries, and spare parts shall be sealed in bags with a supply of desiccant. "Pump parts" means pump parts, shafting, bearings, seals, accessories, auxiliaries, and spare parts that would be subject to damaging effects of corrosion, such as rust or oxidation. All pump parts shall be place in crates. "Crate," means boxing suitable for export shipping by ocean carrier and as described below:

- a. Crates shall have a screwed cover or hatch for access. Screws shall be stainless steel.
- b. Crates shall be sealed, moisture tight without ventilation openings.
- c. Openings shall be provided with removable covers so that wire ropes or slings can be attached to hoisting or skidding devices to facilitate loading, unloading, and handling. Covers shall be fastened with stainless steel screws.

C2-7.1.2 Shaft Storage. Shafts shall be prepared for shipment and storage to prevent damage such as bending, deforming machined surfaces, and corrosion. Detailed handling instructions for shipment, unpacking, assembly, and disassembly shall be provided.

C2-7.1.3 Pump Casing. Pump casings shall have exposed flange ends sealed with 1 inch thick marine grade plywood bolted to the flange ends using the flange's bolt holes. Machined surfaces shall be properly protected from damage and corrosion for a minimum of 12 months of exterior exposure. Painted surfaces shall be protected from damage from handling during shipping and storage by means of suitable blocking devises or by crating. If crates are used, they shall be provided with removal covers fasten with stainless steel screws to allow for periodic inspections.

C2-8. PROJECT/SITE CONDITIONS.

C2-8.1 Datum. Elevations shown or referred to in specifications, are Cairo datum.

C2-8.2 Pool-to-Pool Head. Pool-to-pool head is the difference in feet between the water surface elevation in the sump bay and water surface elevation in discharge channel. Pump manufacturer shall determine total head. Total head includes losses from the water surface on suction side of pump to discharge water surface, plus velocity head.

C2-9. MAINTENANCE.

C2-9.1 Special Tools. Three sets of "special tools" required to completely assemble, disassemble, or maintain the pumps shall be furnished. "Special tools" refer to grossly oversized or specially dimensioned tools, special attachment or fixtures, or any similar items. If required, a device shall be provided for temporarily supporting the pump shaft and impeller during assembly, disassembly, and reassembly of pump. Lifting devices other than slings required for use in conjunction with a crane for assembling and disassembling the pump shall be furnished including devices for handling pump components such as the shaft, bearings, bearing houses and impeller. Portable steel cabinets shall be provided large enough to accommodate "special tools" furnished under this paragraph and as required by Sections "C1-Diesel Engines" and "C3- Speed Reducers for Stormwater Pumps." Special tool cabinets shall be mounted on four rubber-tired casters. Drawers shall be provided to accommodate small tools. The front of the cabinet shall be fitted with a hinged door designed to swing horizontally. Doors shall be furnished with necessary stops, catches, and hasps for completely securing cabinet with a padlock. Padlocks shall be furnished complete with three keys. "Special tools," because of their size and weight, do not permit storage in tool cabinet shall be packaged in sturdy wooden crates with covers that are fastened with screws.

C2-10. ERECTING ENGINEER. Refer to Section C5 - "SERVICES OF AN ERECTING ENGINEER".

PART 2 PRODUCTS

C2-11. MATERIALS AND METALWORK FABRICATION. Materials shall conform to requirements of paragraph C2-5 "Regulatory Requirements", subparagraph b., FAR 52.246-2, and to additional specified requirements. Classification and grade of material incorporated in work shall be in accordance with designated specifications.

C2-11.1 Designated Materials. Designated materials shall conform to the following specifications, grades, and classifications.

Material	Grade	Class	Specification
Aluminum-Bronze	Alloy No. C95500	Castings	ASTM B 148
Cast Iron		30A, 30B	ASTM A 48
Cast Steel	65-35 Annealed		ASTM A 27
Cold Tar Protective Coating-Hot Applied			AWWA C203
Cold Roll Steel Bars	Min. Tensile 65KSI		ASTM A 108
Copper Alloy Casting	Alloy No. C93700		ASTM B 584
Corrosion-Resistance	CA15M		ASTM A 487/ A487M
Alloy Casting *	CA6NM CA15M	Class A / C<0.03%	ASTM A 487/A 487M
Dimension for Steel Water Pipe Fittings			AWWA C208
Hot Rolled Stainless	G10200 & G11410		ASTM A 576
Ring Flanges		B	AWWA C207
Rubber Products in Automotive Appl.			ASTM D 2000
Seamless and Welded Aust. Stainless Steel Pipe			ASTM A 312
Stainless Bars and Shapes	S30400 & S41000		ASTM A 276
Steel Forgings		D	ASTM A 668
Steel Pipe, 6 Inches and Larger			AWWA C200
Steel Plates, Pressure Vessel	60 or 70		ASTM A 516
Steel Plates,	B		ASTM A 285

Structural Quality			
Structural Steel			ASTM A 36
Surface Texture (Surface Roughness, Waviness, and Lay)			ASTM B46.1

* Note: If CA6NM is used the contractor shall submit procedure for fabrication and welding for approval by the Contracting Officer.

C2-11.2 Castings.

C2-11.2.1 Cast or Stamp Mark Number. Cast mark number shall be provided on each casting. Heat number shall be cast or stamped on each casting. Warped, distorted, or oversized castings that will interfere with proper fit with other parts of machinery or structures will be rejected. Cracked castings of non-weldable materials (cast iron, etc.) will be rejected. Repairs to castings shall not be made prior to approval by the Contracting Officer. The structure of the metal in castings shall be homogeneous and free from excessive non-metallic inclusions.

C2-11.2.2 Visual Examination. Casting shall be visually examined for defects. Visual defects shall then be further examined by Magnetic Particle Tests. Magnetic particle tests and inspection shall conform to Appendix 6 of ASME-16 and ASTM E 709. Steel castings shall not be used with defects disclosed by magnetic particle test which exceed the degree permitted by Appendix 7 of ASME-16.

C2-11.2.3 Casting Repairs. Castings, except those of cast iron shall have all unsound material or defects removed by chipping, machining, air-arc gouging or grinding, and shall be repaired by welding. Welding repairs shall conform to welding procedures developed and approved for the type of material involved. Stress relief annealing shall be accomplished prior to final machining.

C2-11.2.4 Acceptance Criteria. Criteria for acceptance of castings and casting repairs, including the approved welding procedure for each material used, shall be developed by the Contractor. Standards that are not definitive or that delegate discretionary authority for acceptability of castings or casting repairs to manufacturer's representatives or other individuals are not acceptable. Castings not meeting approved criteria shall be either rejected or repaired as dictated by approved standards. Repairs shall be accomplished in accordance with approved procedure and repaired areas shall be reinspected to insure completed repairs are satisfactory.

C2-11.3 Bolted Connections.

C2-11.3.1 Bolts, Nuts, and Washers. Bolts, nuts, and washers shall conform to requirements of paragraph C2-11.1 "Designated Materials," and paragraph C2-12.11 "Bolts, Nuts and Washers" for types required. Beveled washers shall be used where bearing faces have a slope of more than 1:20 with respect to a plane normal to bolt axis. Plain washer shall conform to the requirements of ANSI B18.22.1 heavy series and lock washers shall conform to the requirements of ANSI B18.21.1 heavy series. All bolts heads and nuts shall be hexagon.

C2-11.3.2 Drill or Subdrill and Ream Holes. Unless otherwise approved holes for bolts shall drilled or subdrill and reamed at the manufacturer's shop. Holes shall be accurately located, smooth, cylindrical and perpendicular to the member. Holes for unfinished bolts shall be no larger than 1/8 inch in diameter than the bolt. Holes for machined bolts shall be not more than 0.020 inches larger than the nominal diameter of the bolt.

C2-11.3.3 Match-ream or Drill Holes. Holes for fitted bolts shall be match-ream or drilled in the shop. Holes shall be smooth, cylindrical, and perpendicular to the member with all burrs removed. Bolt threads shall be entirely outside of holes. Body diameter of bolt shall have tolerances as recommended by ASME B4.1 for class of fit specified. Reamed holes with fitted bolts shall be selectively assembled for an LC-1 fit.

C2-11.3.4 Holes for High-strength Bolts. Holes for high-strength bolts shall be accurately spaced, cylindrical, and perpendicular to the member. Holes in material that is less than the bolt diameter shall be drilled and then reamed to full size. Poor matching of holes will be cause for rejection. Drifting done during assembly shall not distort metal or enlarge holes. For slight mismatching, reaming to a larger diameter for next standard size bolt will be allowed.

C2-11.3.5 Materials Not Specifically Described. Materials not specifically described shall conform to latest ASTM specification or to other listed commercial specifications covering class or kinds of materials to be used.

C2-11.4 Metalwork.

C2-11.4.1 Flame Cutting of Material. Flame cutting of material other than steel shall be subject to approval of the Contracting Officer. Shearing shall be accurately done, and all portions of work neatly finished. Steel may be cut by mechanically guided or hand- guided torches, provided an accurate profile with a smooth surface free from cracks and notches is secured. Surfaces and edges to be welded shall be prepared in accordance with Section 3 of AWS D1.1. Chipping and/or grinding will not be required except where specified and as necessary to remove slag and sharp edges of mechanically guided or hand-guided cuts not exposed to view. Visible or exposed hand-guided cuts shall be chipped, ground, or machined to metal free of voids, discontinuities, and foreign materials.

C2-11.4.2 Stress-Relieving Procedure. After all fabrication welding is completed, and prior to any machining, pump weldments shall be stress-relieved by heat treatment. The contractor shall submit proposed stress-relieving procedure for approval by the Contracting Officer.

C2-11.5 Machine Work.

C2-11.5.1 General. Tolerances for machine-finished surfaces designated by non-decimal dimensions shall be within 1/64 inch. Sufficient machining stock shall be allowed on placing pads to insure true surfaces of solid material. Finished contact or bearing surfaces shall be true and exact to secure full contact. Journal surfaces shall be polished and all surfaces shall be finished with sufficient smoothness and accuracy to insure proper operation when assembled. All like parts shall be interchangeable. All drilled holes for bolts shall be accurately located.

C2-11.5.2 Class of Fit Required. All fits between the various parts described shall be as described in the table below. No alternates to these fits will be allowed without specific approval of the Contracting Officer. Tolerances, allowances, and gages for metal fits between plain, non-threaded cylindrical parts not shown below shall conform to ANSI B4.1, for class of fit required.

Description	Type of fit	Total interference or clearance
Shaft to impeller	Interference Locational Fit	ANSI B4.1 Class LN2
Shaft sleeves (at packing gland)	Interference Locational Fit	ANSI B4.1 Class LN2
Shaft coupling (will be pressed on in field)	Interference Locational Fit	ANSI B4.1 Class LN2
Shaft to bearing, inner race	As recommended for "normal to heavy loads"	Mfg. Recommendation
Shaft to bearing, outer race	As recommended for "normal to heavy loads"	Mfg. Recommendation
Key to keyway, fitted sideways (by others upon erection)	Interference Locational Fit	ANSI B4.1 Class LN1
Key to keyway, top and bottom	Clearance Locational Fit	ANSI B4.1 Class LC1

C2-11.5.3 Surface Finishes. Where surface finishes are indicated, or on Contractor's drawings, or as specified herein, symbols used or finishes specified shall be in accordance with ANSI B46.1. Values of roughness height specified are the arithmetical average deviation expressed in microinches. Roughness specified is the maximum value and any lesser degree will be satisfactory unless otherwise called for on drawings. Compliance with specified surface shall be determined by sense of feel and by visual inspection of work compared to Roughness Comparison Specimens, in accordance with provisions of ANSI B46.1. Values of roughness width and waviness height are not specified, but they shall be consistent with general type of finish produced and specified by roughness height. Finishes shall be 250 rms or better on flange faces, 125 rms on general machine work and 32 rms on bearing journals at anti-friction bearings. Flaws such as scratches, ridges, holes, peaks, cracks or checks which will make the part unsuitable will be cause for rejection.

C2-11.5.4 Unfinished Surfaces. Work shall be laid out to insure matching of adjoining unfinished surfaces. Unfinished surfaces shall be true to lines and dimensions shown on the contract and/or Contractor's drawings and shall be chipped or ground free of all projections and rough spots. Where there is a large discrepancy between adjoining unfinished surfaces, the surfaces shall be ground or machined to proper alignment. Depressions or holes not affecting strength or usefulness of parts shall be filled in a manner approved by the Contracting Officer.

C2-11.5.5 Alignment of Wetted Surfaces. Accurate alignment shall be maintained between wetted surfaces being joined with flanges. Where plates of the water passage change thickness, transition shall occur on the outer surface, leaving inner surface properly aligned. When welding has been completed and welds have been cleaned, but prior to stress relieving, joining of plates shall be carefully checked in the presence of Government inspector for misalignment of adjoining parts. Localized misalignment between inside of wetted surfaces of an adjoining flange connecting sections of pump or tunnels shall not exceed 1/4 inch. Misalignments greater than 1/4 inch shall be corrected by grinding away offending metal, providing the maximum depth to which metal is to be removed does not exceed 1/4 inch and does not introduce excessive stress in the part. Where required correction is greater than 1/4 inch that section of pump shall be rejected for use. Proposed procedure for all corrective work, other than minor grinding, shall be approved by Contracting Officer prior to start of corrective work. Corrective work shall be finished by grinding corrected surface to a smooth taper. Length of the taper along each flow line element shall be 10 times the depth of the offset error at flow line. Wetted surface irregularities that might have existed in an approved model shall not be reason for accepting comparable surface irregularities in prototype pump.

C2-11.5.6 Dowel Holes. Dowel holes shall be bored true to gages, smooth and straight, and at right angles to axis of the member. Boring shall be done after members are securely fastened in position.

C2-11.5.7 Shafting. Shafting of non-uniform diameter shall be made of hot-rolled steel, shall have fillets where changes in section occur, and shall be ground and polished. Plain shafting may be made of cold-finished steel unless specified otherwise.

C2-11.6 Welding.

C2-11.6.1 Welding of Steel. Unless otherwise authorized or specified, welding of steel shall be by electric arc-welding process, using a method that excludes atmosphere from molten metal. Welding of steel, unless specified otherwise, shall conform to applicable provisions of AWS D1.1. All welding operators and machines shall be qualified as required by paragraph C2-4, "QUALIFICATIONS." The Contractor shall certify that welding operators are so qualified. All expenses in connection with qualification and requalification tests for welders and welding machines shall be borne by the Contractor.

C2-11.6.2 Temporary Welds. Temporary welds required for fabrication and erection shall be made under controlled conditions prescribed herein for permanent work. Each temporary weld shall be removed after serving its purpose and ground flush with adjacent surfaces.

C2-11.6.3 Inspection. Welding shall be subject to inspection by the Contracting Officer or his/her representative. The Contracting Officer may require coupons to be cut from any location in any joint for testing. All section of welds found defective shall be chipped or cut out to base metal and properly rewelded. When coupons are cut, the member's cut shall be repaired in a neat and workmanlike manner. Cost of providing the coupons, repairing and testing shall be borne by the manufacturer if found defected. Cost associated with testing parts which are not defected will be borne by the Government.

C2-11.6.4 Welding Procedure. The welding procedure for each structure to be welded shall be in accordance with the best modern welding practice, and shall be such as to minimize residual stresses and distortion of the finished members.

C2-11.6.5 Stress Relieving. Stress relieving shall be by heat treatment. The method used shall be approved by the Contracting Officer. All machining shall be done after stress relieving. In the event the complete bottom half of the suction elbow cannot be positioned for machining, then a section of the suction end may be welded after machining, then the weld stress relieved. Adequate provisions shall be taken to prevent distortion of the machined part.

C2-11.7 Shop Assembly. Unless otherwise specified, each finished pump, shall be assembled in the shop to determine correctness of fabrication and matching of component parts. Tolerances shall not exceed those specified or shown on Contractor's drawings and each assembled unit shall be closely checked to ensure that all necessary clearances and alignments have been provided and that binding does not occur in any moving part. Assembly in shop shall be in the same position as final installation in the field unless otherwise specified. The assembly shall consist of pump casings pieces and sections and shall include mounting the shaft and

impeller in the pump casing with both inboard and outboard bearings and seals. Assembly and disassembly shall be performed in the presence of a Government representative, unless waived in writing by Contracting Officer. Errors encountered shall be immediately remedied. Before disassembly for shipment, each piece of a machine or structure shall be match marked, drilled and doweled, and serial numbered to facilitate erection in the field. The location of match marks shall be shown by circling with a ring of white paint after the shop coat of paint has been applied, or as otherwise directed. Match marks shall be documented on pump assembly drawings and provided with each pump.

C2-12. HORIZONTAL PUMPS.

C2-12.1 Speed. Rotative speed of pump shall be no greater than 100 RPM. The pump manufacturer shall verify that rotative speed of pump at which the NPSH is produced is not more than the required speed required to meet the design requirements of paragraph C2-6.3 "Capacities", as determined by cavitation tests specified in paragraph C2-14.2 "Factory Tests."

C2-12.2 Reverse Flow. Pump manufacturer shall show by computation that the pump is capable of withstanding the full force exerted on it when subjected to reverse flow with activation of the reverse flow backstop. The computations shall use the most severe condition from paragraph C2-6.3 for head and tail water and shall take into account stresses caused from changes in momentum of pumped water and machinery components as well as static heads. Under these conditions stress shall not exceed 2/3 of the yield strength of the materials.

C2-12.3 Efficiency. Pool-to-pool efficiency at head-capacity conditions specified in paragraph C2-6.3 "Capacities" shall not be less than as shown in Table 1 when calculated as follows:

$$\text{Efficiency} = [(Q \times H)/(3960 \times \text{BHP})] \times 100$$

Where: Q = Discharge, gallons per minute
 H = Pool-to-pool total head, feet
 BHP = Pump brake horsepower

C2-12.4 Design Stresses. Working stresses for structural steel, other than that used for pump parts, shall conform to the requirements of the A.I.S.C. Except for the pump shaft, rotating parts of the pump and other machinery components subject to high stresses or shock shall be so designed that the maximum stress due to the most severe operating condition does not exceed two-thirds of the yield point. Where other parts of the pump assembly are subject to operating stresses, the unit stress in ferrous materials used shall not exceed the values in the following table. For the pump shaft the combined torsional and bending stresses at any point shall not exceed 11 percent of the minimum yield point.

Table 4

Material	Maximum unit stress in pounds per square inch	
	Stress in tension	Stress in compression
Cast Iron	2,000	10,000
Cast Steel	10,000	10,000
Alloy Cast Steel, Alloy Steel, Rolled Shapes and Plates	20 percent of the Ultimate Strength or 33 Percent of the Yield Point	20 percent of the Ultimate Strength or 33 Percent of the Yield Point
Plate Steel, Where Utilized	12,000	12,000
Pump Shaft	Stress in Torsion: 11 percent of the yield point	Stress in Bending: 11 percent of the yield point

C2-12.5 Suction Piece. The suction piece shall be fabricated steel with a minimum shell thickness of 3/4 inch and shall be furnished as shown on the drawings. It shall be of one-piece construction with one end flanged to mate with the suction elbow and the other end prepared for grouting into the concrete intake tube. Its flange thickness, tolerance and pressure rating shall be the same as for the pump impeller and diffuser casings.

C2-12.6 Suction Elbow. The suction elbow shall be fabricated from steel plate having a minimum wall thickness of 3/4 inch. The elbow shall be ribbed where necessary for strength and rigidity and shall be designed for a minimum of 20 inches mercury vacuum. The outboard bearing housing shall be rigidly supported from the elbow. Direct support of the housing on the concrete structure will not be allowed. The exact design of the elbow shall be determined by the pump manufacturer. The suction elbow shall be split horizontally on the shaft centerline. The horizontal split flange shall be faced and drilled, and the back of the flange spot faced. Great care shall be taken in the setting up of this piece for machining so that it is not distorted or sprung by the devices used to hold it. The suction end of the elbow shall be flanged to suit the suction piece. The pump end of this piece shall be flanged to suit the impeller casing flange. Both flanges shall have a minimum thickness of 1-1/2 inches after machining. All welds on the pipes, ribs, etc. shall be continuous, i.e., tack welds will not be allowed. Field welds will not be allowed. A 20 inch diameter manhole and 1-1/2 inch flanged air inlet connection shall be built into the suction elbow where shown on the drawings.

C2-12.7 Impeller Casing. The impeller casing shall be of fabricated steel plate and shall have flanged ends. The shell thickness shall be not less than 1 inch after machining. Welds shall be heat-treated stress-relieved before final machining. The casing shall be designed to withstand a minimum of 20 inches of mercury vacuum. The impeller casing shall be

horizontally split and flanged on the shaft centerline and on both ends in order to mate with the elbow and diffuser sections. Concentric and split flanges shall be provided with a registered fit or a minimum of four equally spaced dowels for alinement. Dowels shall be suitable for permanent alinement. Machine finish impeller-swept area in impeller casing shall have a surface finish of at least 125 rms and shall be concentric with the impeller axis. Tolerance for concentricity of impeller with the impeller axis shall not be greater than 20 percent of the operating clearance between impeller and impeller casing.

C2-12.8 Diffuser Vane Section. The diffuser vane section shall be fabricated from steel plate with vanes welded to the inner casing. all welds shall be stressed relieved. The diffuser section shall have a minimum wall thickness of 3/4 inch. The vanes shall be of 1-1/2 inch minimum thickness. The diffuser casing shall be horizontally split and flanged on the shaft centerline with support points provided as indicated on the drawings. The casing shall have flanges on both ends to mate with the impeller casing and the discharge piece. Concentric and split flanges shall be provided with a registered fit or a minimum of four equally spaced dowels for alinement. The lower half of the diffuser section shall be carefully designed to carry the pump inboard bearings within a watertight inner cone. The diffuser section shall be designed for a minimum of 20 inches of mercury vacuum.

C2-12.9 Discharge Piece. The discharge piece shall be fabricated steel with a minimum shell thickness of 3/4 inch and shall be furnished as shown on the drawings. It shall be of one-piece construction with one end flanged to mate with the diffuser vane section and the other end prepared for grouting into the concrete discharge tunnel. The discharge piece shall incorporate an annular convoluted steel expansion ring. The convoluted section shall be steel with a minimum thickness of 3/4 inch and shall be designed to yield due to foundation movement without the section becoming dislodged from the discharge tunnel. Its flange thickness, tolerance and pressure rating shall be the same as for the pump impeller and diffuser casings.

C2-12.10 Flanges. Pump flanges, including horizontal split flanges, shall have a minimum thickness of 1-1/2 inches after machining and shall be faced and drilled. The back face shall be spot faced or ring faced to receive flange bolts and/or nuts. Flanges shall be machined and bolt holes drilled concentric with pump centerline, having tolerance of plus or minus one fourth of the clearance between bolt and bolt hole. Flange thickness after machining shall not vary by more than 10 percent from the maximum flange thickness. Where necessary, flange stiffeners shall be provided. To the maximum extent possible, flanges shall be designed to be through bolted. Flanges which require the use of studs or are not through bolted such that both the nut and bolt are readily accessible shall require written approval from the Contracting Officer. Welded flanges shall be welded with one or more continuous beads on both sides of the flange at the connecting intersection to the pump section. Final design of welds is the responsibility of the manufacturer. Flanges shall have a 250 rms finish or better on the mating surfaces. A minimum of eight jacking bolts shall be provided for separating the horizontal flange.

C2-12.10.1 Flanged Joints. All surfaces of the finished flanges shall be true and straight to within 0.005 inches when restrained. All mating surfaces shall be machined so that when joined without sheet gaskets will form a vacuum tight joint using only "Permatex" or an approved equivalent product. After initial assembly and final alignment at the factory all flange surfaces shall be doweled at a minimum of eight equally spaced locations. The dowels shall be tapered and fitted into tapered holes and shall be designed to aid in reassembling.

C2-12.11 Bolts, Nuts and Washers. Bolts, nuts, screws and other fasteners shall be Type 316 stainless steel.

C2-12.12 Impeller. The pump impeller shall be cast steel with an outside diameter of not less than 10'-6" and not greater than 11'-6". The impeller vanes shall be carefully cast integrally with the hub in one piece to produce smooth vanes without distortion or warping. The nose cone of the impeller shall be a separately cast steel component arranged for bolting to the impeller hub. A minimum 30 inch access opening at the top of the impeller hub shall be provided for inspection of the impeller casing. The impeller shall have its outside diameter machine finished so as to produce a close running fit between the impeller and casing. The impeller shall be bored and key-seated for a press fit to the shaft. The design of the impeller shall be such that mild heating of the casting in order to facilitate placement and removal from the shaft can be used without harming the impeller. The impeller shall have appropriate holes in the hub to for removal from the shaft. The manufacturer shall verify by means of templates or pitchometers that the impeller is geometrically similar to the model impeller. Results of the comparative testing shall be certified and provided to the government for approval.

C2-12.12.1 Inspection of Casting. After removal from mold, and prior to finishing of surface imperfections, castings shall be inspected for cracks using the magnetic particle method in the presents of the Contracting Officer or his representative. Minor surface imperfections shall be filled or ground down as necessary to preserve correct contour and outline of impeller and to restore surface imperfections to the same degree of finish as surrounding surfaces. Surface pits, depressions, projections, or overlaps showing greater than 1/16 inch variation from the general contour for that section shall be corrected. Method and procedure for accomplishing repair shall be as set forth in standards furnished under paragraph C2-11.2 "Castings". Castings that exhibit surface imperfections as defined above which covers an area of more than 10 percent of blade surface will be rejected.

C2-12.12.2 Dynamic Balance. The finished impeller shall be dynamically balanced to within 4000 oz-in of unbalance. Dynamically balance shall be by the two-plane balancing technique. The impeller shall be balanced at 100% and 110% of maximum operating speed. Amount of allowable unbalance shall be quality grade G 6.3 in accordance with ASA S2.19. Weights needed to obtain required level of balance shall be securely welded to the inside cavity of the impeller hub. In no case will portions of the impeller be removed or weights be added to the outside of the hub, vanes, or water passages. Balancing procedure shall be submitted to the Contracting Officer for approval at least four weeks prior to date of balancing. Each finished

impeller shall be weighted and weight stamped on the hub. Weight shall be accurate to 0.5 percent of the total weight of impeller. Weighing and balancing shall be witnessed by the Contracting Officer or his representative.

C2-12.13 Pump Shaft. The shaft design shall be in accordance with ASME B106.1M. The shaft shall be designed with a minimum factor of safety of 5 based on ultimate tensile strength of shaft material and rated horsepower of the engine, and not more than 2/3 of the yield strength of the material at maximum horsepower of the engine. The pump shaft shall be in one piece supported by the outboard bearing and the inboard bearing immediately in back of the impeller. It shall be finished and polished all over and shall be of forged steel ASTM A-668 Class D. All machine work shall be accurate, with fits properly maintained. The shaft shall be a minimum of 16 inches in diameter, with slightly reduced diameters allowed at the impeller and bearing fits. Shaft run out at any point when supported on its bearings shall be less than 0.002 inches, and shaft out of round shall be less than 0.0005 inches. A threaded hole, 2-1/2 inch diameter 10 threads per inch, R.H., and 6 inches deep shall be provided in the end of the shaft for installing the impeller.

C2-12.14 Shaft Sleeves. Stainless steel sleeves, with a minimum surface hardness of 450 Brinnell, shall be provided on the shaft for the inboard and outboard packing boxes. The packing box sleeves shall be of the length required by the manufacturer. These sleeves shall be press fitted or shrink fitted to the shaft and then machined. The out of round of the finished sleeve shall be less than 0.0005 inches.

C2-12.15 Pump and Gear Reducer Shafts Coupling. Pump and gear reducer floating shaft and couplings shall be in accordance with Section "C3- Speed Reducers for Storm Water Pumps."

C2-12.16 Pump Bearings.

C2-12.16.1 Inboard Bearing. The pump inboard bearings shall be mounted within the inner cone of the diffuser section which shall be entirely sealed from the flow area. The bearing shall be mounted downstream of the impeller so that the impeller is between the inboard and the outboard bearings. A bulkhead provided with a packing box for the pump shaft shall be installed on the impeller side of this cavity to exclude all water from the inner cone and bearings. The inboard bearing bulkhead and packing box housing shall be horizontally split. The other end of the cavity shall be sealed by a water tight bolted access cover. The housing and access cover shall be large enough to accommodate the removal of the interior bearing and all bearing parts. The pump inboard bearing assembly within the cavity shall be of the anti-friction type designed for oil lubrication and shall incorporate a thrust bearing used in combination with a radial load bearing. The radial bearing shall be a spherical roller bearing used in conjunction with a spherical roller thrust bearing. The thrust bearing shall be designed to carry the full thrust of the impeller calculated by assuming a 20 foot differential head across the full area of a circle the same outside diameter as impeller. The radial bearing shall be designed to carry the calculated

design dead load multiplied by 1.3. The pump anti-friction bearings shall be designed for a minimum B-10 life of 100,000 hours. The housing shall incorporate a spring arrangement for eliminating thrust bearing clearance when the bearing is unloaded as during priming. The front and rear covers of the inboard bearing housing shall have male and female fits as will assist in preventing distortion of the housing.

C2-12.16.2 Inner Cone. The inner cone shall be provided with a vent pipe and drain pipe to the exterior of the pump. The vent and drain pipes shall be a minimum of 2 inches nominal diameter. The vent shall terminate with a screened breather above the diffuser section. The drain pipe shall terminate with a 2 inch flange below the diffuser section. Other piping for bearing oil level determination, drain and fill, bearing temperature sensing and lines to the packing gland shall also be provided.

C2-12.16.3 Outboard Bearing. The outboard bearing shall be anti-friction type, self-aligning, spherical roller designed for oil lubrication and shall have a minimum B-10 life of 100,000 hours based on the dead load times a service factor of 1.3. The bearing shall be mounted in a four bolt removal cap cast steel pillow block. The pillow block shall be supported on the suction elbow.

C2-12.16.4 Bearing Lubrication. Oil piping shall be included so that bearing oil level can be checked by site glass, drained and refilled from outside the pump.

C2-12.16.5 Bearing Heat Sensors. Each pump bearing shall be provided with an independent and separate temperature indicator with visual and audible alarms mounted on the diesel engine control panel. Temperature indicators shall be liquid crystal with a minimum 3/4 inch numerical readout in degrees Fahrenheit. Provisions shall be made at the bearings and inside the bearing housings for mounting the temperature sensors. The temperature sensor units shall be an "Alnor" Type N-14 clock pyrotroller or equal. The sensing elements shall be an "Alnor" thermocouples complete for this installation and compatible with the specified indicators. All components of the temperature sensors shall be furnished. Support leads and protect from water and mechanical damage. Terminate leads outside of pump casing in an approved waterproof junction box and cap until final connections are made in the field. Lead protection shall consist of pipes fastened to pump with brackets using bolts and nuts to permit their removal, and shall be constructed with enough unions to be completely disassembled. Leads passing through pump water passage in pump shall either be contained in a guide vane or be protected by schedule-80 pipe.

C2-12.17 Packing Boxes. Grease lubricated stuffing box shall be used at the inboard bearing and a water lubricated stuffing box used where the pump shaft exits the pump housing. The stuffing boxes shall be of suitable design and shall be submitted by the pump manufacturer for approval. These stuffing boxes shall incorporate a bronze gland, bronze lantern ring, and bronze neck ring. The stuffing boxes shall provide for not less than five rings of 1 inch square braided packing. The grease lubricated stuffing box shall be designed to use Lubriplate No. 630-

2, NLGI No. 2 lithium grease or equal for lubrication. The water lubricated packing shall be supplied with potable water for lubrication and cooling.

C2-12.18 Lifting Lugs. Furnish major pump components with lifting lugs or eye bolts to facilitate handling. Design and arrange lugs or bolts to allow safe handling of pump components singly or collectively as required during shipping, installation, and maintenance.

C2-13 PAINTING.

C2-13.1 General. Painting shall be done in a professional manner and in accordance with the paint manufacturer's best recommendations. Five copies of the paint manufacturer's application recommendations shall be furnished the government 30 days prior to coating. Coatings shall be applied by spray equipment at the factory with only touch up painting permitted in the field. Whenever possible the complete coating system shall be applied to the disassembled components of the pump to ensure complete coverage and maximum protection against corrosion. All ferrous metal surfaces shall be painted except stainless steel, galvanized, machined mating and contact surfaces, and pump impeller and shaft. Rubber, plastic and nonferrous metals shall not be painted. Non painted surfaces adjacent to painted surfaces shall be neatly taped off to avoid painting. Steel surfaces that are to be embedded in concrete shall be left unpainted except for the first 6" of embedment. Paint coating system shall comply with either paragraphs C2-13.2 or C2-13.3 depending on the surface exposure.

C2-13.2 Paint System No. 1. Paint system no. 1 shall be applied to all parts as delineated above that are not wetted by pumped water. The first coat shall be applied at a rate of not more than 600 square feet per gallon. Subsequent coatings shall be applied at a rate not to exceed 450 square feet per gallon. Total dry film thickness shall not be less than 9 mils as proportioned below.

PAINT SYSTEM NO. 1

Surface preparation	1st Coat	2nd Coat	3rd Coat
Power tool or brush-off blast cleaning as per SSPSP 3 or SSPC SP 7	SSPC Paint 25 (3 mils minimum)	FS TT-P-38 (Aluminum, 3 mils minimum)	FS TT-P-38 (Aluminum, 3 mils minimum)

C2-13.3 Paint System No. 2. Paint system no. 2 shall be applied to all parts as delineated above that are wetted by pumped water. The first coat shall be applied at a rate of not more than 600 square feet per gallon. Subsequent coatings shall be applied at a rate not to exceed 450

square feet per gallon. Total dry film thickness shall not be less than 20 mils as proportioned below.

PAINT SYSTEM NO. 2

Surface preparation	1st Coat	2nd Coat	3rd Coat	4th Coat
Blast cleaning approaching white metal as per SSPC SP 5	Primer if recommended by paint mfg.	Cold-applied coal tar epoxy	Cold-applied coal tar epoxy	Cold-applied coal tar epoxy
		----- MS MIL-C-18480 ----- Total 20 mils minimum		

C2-13.4 Metallic Coatings.

C2-13.4.1 Zinc Coatings. Zinc coatings shall be applied in a manner, thickness, and quality conforming to ASTM A 123.

C2-13.4.2 Methods to Regalvanize. When zinc coating is destroyed by cutting, welding, or other causes, affected areas shall be regalvanized by the following methods. Coatings 2-ounces or heavier shall be regalvanized with suitable low-melting zinc-base alloy similar to recommendations of American Hot-Dip Galvanizers Association to thickness and quality specified for original zinc coating. Coating less than 2 ounces shall be regalvanized by repair compound conforming to MS DOD-P-21035.

C2-14. TESTS, INSPECTIONS AND VERIFICATION.

C2-14.1 Torsional Vibration and Dynamic Analysis. Assembled pumping unit, consisting of engine, speed reducer and pump shall be free from critical speeds or harmful torsional vibrations at all speeds encountered within the operating range of performance characteristics given in paragraph C2-6.2.

C2-14.1.1 Torsional Analysis. Before pump, gear drive, and engine are released for manufacture, engine supplier shall analyze the system for harmful torsional natural frequencies using mass elastic information provided by pump and gear drive manufacturers. A natural frequency that occurs within 25 percent above or below any of the operating speeds required for pump operating conditions is considered to be unacceptable.

C2-14.1.2 Lateral Frequency Analysis. Before the pump, gear drive, and engine furnished under Sections "C1 - Diesel Engines" and "C3 - Speed Reducers for Stormwater

Pumps" respectively, are released for manufacture, the pump, engine, gear drive, shall be analyzed by the pump manufacturer for harmful natural frequencies in the lateral directions. A natural frequency that occurs within 25 percent above or below any operating speeds required for pump operating conditions is considered to be harmful and not acceptable. The dynamic analysis model shall be constructed using a commercially available program such as Ansys, Cosmos/M, or equivalent that utilizes finite element methods. The analysis shall also include all pump parts such as pipes, shafts, bearings, mass concentrations, and other such features as necessary to accurately model the furnished machinery. The model shall incorporate Reed critical frequency and mass elastic diagram information provided by the gear drive manufacturer. If the gear drive manufacturer cannot demonstrate to the satisfaction of Contracting Officer based on impact tests of similar units that the Reed critical frequency value is accurate, a dynamic analysis using finite element methods as described herein shall be conducted by gear drive manufacturer to determine gear drive Reed critical frequency for use by pump manufacturer. A complete dynamic analysis report including the following information shall be submitted:

- a. Computer program used.
- b. Schematic diagram of the model depicting nodes and elements.
- c. Input data consisting of node coordinates, element types, material properties, element characteristics, element connectivities, and specified displacements.
- d. Gear mass elastic and Reed critical information or dynamic analysis, if required.
- e. Analysis results including all significant natural frequencies.
- f. Interpretation of results.

An impact-test on the gear drive before shipment shall be made to determine the actual Reed critical frequency of the drive. Results of impact tests shall be submitted. Pump manufacturer shall address any discrepancy between calculated and actual gear drive Reed critical frequency values as to whether or not design changes are required to prevent harmful natural frequencies in engine/pump/gear drive. If any design changes are required to meet the requirements of this paragraph they shall be made at no cost to Government.

C2-14.2 Factory Test.

C2-14.2.1 General. The performances and cavitation limits of the prototype pump shall be determined by a series of tests made on a scale model of the pump and water passages. The model test shall be completed within 180 days after date of notice to proceed. The tests results shall require government approval prior to the start of prototype production. Any production started prior to an approved successful model test shall be done at the pump manufacturer's risk.

The final performance model tests shall be conducted in the presence of a Contracting Officer's Representative. The Contracting Officer's Representative shall be given at least 14 days notice prior to final performance tests if the test are performed within United States and 45 days noticed if performed outside of the U.S. Final performance test is defined as the test that is used to generate the data required by the specifications.

C2-14.2.2 Test Setup. The model pump shall be homologous to the proposed prototype pump shown on the contract drawings and as specified herein, and with the shaft mounted in the horizontal position. The intake bay and pump's suction elbow shall be equipped with windows strategically located for viewing those areas where separation is likely to occur. The impeller inlet diameter and the datum for this test specification shall be as indicated on the contract drawings. The model pump shall have a minimum impeller diameter not less than 12 inches. The formed suction intake and discharge shown on the contract drawings shall be included in the model test and shall be geometrically the same as that used for the prototype.

C2-14.2.3 Instrumentation and Procedures. Each instrument shall be described in detail, giving all data applicable, such as the manufacturer's name, type, model number, the certified accuracy, coefficient, ratios, specific gravity of manometer fluid to be used, and smallest scale division. When necessary for clarity, a sketch of the instrument or instrument arrangement shall be included. Also included therein shall be a fully detailed narrative description of each proposed method of instrumentation and of the procedures to be used.

a. Head Measurements. Head measurements shall be made using either a direct-reading water column, a mercury-air or mercury-water manometer, or a pressure transducer. Vacuums shall be measured with either a mercury-air or mercury-water manometer or a pressure transducer. Fluctuations shall be dampened sufficiently to permit the column gages and transducers to be read to either the closest one-hundredth (0.01) of 1 foot of water or one-tenth (0.1) of 1 inch of mercury. When pressure transducers are used, their accuracy shall be checked with a manometer. Model test heads shall be the same as prototype heads.

b. Capacity. Model pump capacity shall be determined by a calibrated venturi or magnetic flowmeter. The venturi or nozzle taps shall be connected to column gages or a differential pressure transducer equipped with dampening devices that will permit the differential head to be determined to either the closest one-hundredth (0.01) of 1 foot of water or one-tenth (0.1) of 1 inch of mercury. Both magnetic and venturi flowmeters shall have been calibrated within 6 months of the model test and shall be accurate to within 0.5% of actual flow.

c. Rotational Speed of Pump. The rotational speed of the model pump shall be measured in accordance with HI-01, except that revolution counters shall not be used. Non-contacting hand-held electronic tachometers are acceptable. Device used shall permit speed to be determined to 1 RPM.

d. Power Input. The power input to the pump shall be measured in accordance with "Power Measurements" in HI-01, except that calibrated electric drives shall not be used. A torque-measuring device measuring the torque of the input shaft of the pump is acceptable, provided it is accurate to 1 percent and has been calibrated within the last 6 months. The method used shall permit horsepower to be determined to 1 horsepower.

e. Cavitation Tests. The instruments to be used for these tests shall be selected by the Manufacturer and shall be of the type suited for cavitation testing. However, in no case shall the instruments used yield results less accurate than those obtained with the performance test.

C2-14.2.4 Pump Test. The model shall be sufficiently extensive and complete to demonstrate that the proposed pump complies with the specified performance. Compliance with the requirements of the specifications will be determined from the curves required by the contract specifications. Test procedures, except as herein specified, shall be in accordance with applicable provisions of Hydraulic Institute Standard HI-01. Temperature of water used for testing shall be approximately the same for all tests run and shall be recorded during test runs.

a. Performance of The Prototype Pump. The performance of the prototype pump shall be determined by a series of test points sufficient in number to develop a constant-speed curve over the range of total heads corresponding to the pool-to-pool heads in paragraph C2-6.3 "Capacities". A series of constant speed tests shall be conducted to prove the pump performance characteristics. The tests shall be run at model speeds equivalent to the prototype pump normal (100%) speed and also at 105% and 90% of normal speed. For these tests the model impeller shall be subject to a series of lifts, by varying suction absolute pressure, equivalent to a suction pool elevation of -13.5, -11.5, -9.5, -7.5, -5.5 and -2.0, feet NGVD respectively for the actual pump. The total head for the model test shall be the same as specified for the prototype. Each constant speed tests shall cover the full operating range of the pump as specified (at the equivalent test points), and in addition shall cover the higher and lower heads that are expected near shutoff head and near zero head. There shall be a minimum of fifteen (15) test points for each speed series between maximum and minimum test points. The maximum and minimum and other test points shall be to the satisfaction of the contracting officer. If the plot of the data indicates a possibility of instability or dip in the head-versus-capacity curve, a sufficient number of additional points on either side of instability shall be made to clearly define the head-capacity characteristics. For compliance with the guarantees, the efficiency of the prototype pump shall be considered to be the efficiency of the model. No other computation or upward adjustment of model efficiency to prototype conditions will be permitted.

b. Tests Results. The results of the tests shall be plotted to show total pool to pool head, brake horsepower, and percent efficiency as ordinates; all plotted against the pump discharge in gallons per minute for the model pump and cubic feet per second for the prototype pump as the abscissa. The curves showing prototype performance shall be plotted to a scale that

will permit reading head directly to 0.2 foot, capacity to 10 cubic feet per second, efficiency to 1 percent, and power input to 10 horsepower.

C2-14.2.5 Cavitation and Critical Sigma Tests. Cavitation tests shall be conducted to prove that at the various pool-to-pool heads of conditions 1 thru 7 the pump is free of cavitation and consequence loss of performance or objectional vibration at the high suction lift and shall include the determination of the critical cavitation coefficient, sigma. The cavitation tests shall be conducted to include the full operating range of the pump as specified and shall have a minimum of ten points, not necessarily the specified conditions, between maximum and minimum test points. Pool-to-pool head shall be used in determining all values of sigma. The maximum and minimum and other test points shall be to the satisfaction of the Contracting Officer. Method of producing equivalent submergence of the impeller shall be as approved by the Contracting Officer. Critical sigma shall be determined on a constant capacity or constant head and constant speed basis. Suction conditions shall be varied to produce cavitation. Critical sigma shall be the maximum value of sigma at which any one or all of the plotted curves, head or capacity, horsepower and efficiency, show a sudden drop from the overall trend of more than three percent. A sufficient number of points to accurately locate the departure point shall be obtained. Each test point shall be calculated and plotted before proceeding to the next point. The value of sigma obtained shall be less than the corresponding plant sigma. The test results shall be plotted to show pool-to-pool head, brake horsepower and efficiency as ordinates; all plotted against sigma as the abscissa. The relation of plant sigma to the respective critical sigma shall be shown on the curve. "Lift" of the model for the purpose of Sigma testing will be considered the same as the Prototype "lift" when the absolute pressure at the top of the model impeller is identical to the absolute pressure at the top of the impeller of the prototype at the maximum lift. For all other test runs, "lift" shall be to the centerline of the propeller. Model data results shall be adjusted to account for differences between model water temperature and prototype water temperature of 92 degrees Fahrenheit

C2-14.2.7 Reserved.

C2-14.2.6 Blade Templates Demonstration. The Contractor shall demonstrate to the Government witness that the blade templates fit the tested pump. The templates shall be sufficiently complete to permit construction of the impeller from the templates. The demonstration shall be done immediately after the performance/cavitation testing is completed. The Contractor shall retain all templates for the accepted pump model and for the prototype, and shall furnish them to the Government upon request of the Contracting Officer, to permit the Government to verify that the prototype pump is in complete geometric similarity with the model. In lieu of providing templates, the Contractor shall furnish dimensioned drawings of the impeller that contain all dimensions needed to manufacture the impeller. The Contractor shall retain the model pump impeller used for the test until final acceptance of the prototype pump. The model impeller shall be stamped with identification marks. The Contractor shall retain all templates for the components of the tested model or prototype pump, or both, and shall furnish them to the Government upon request of the Contracting Officer along with the necessary

facilities and instruments needed to permit the Government to verify that the prototype pumps are in complete geometric similarity with the model pump or the tested pump.

C2-14.2.7 Witness Test. When the Contractor is satisfied that the model performs in accordance with the requirements of the specifications and the guaranteed values, the Contractor shall notify the Contracting Officer that the witness tests are ready to be run on the model and shall furnish two copies of the curves required in paragraph C2-14.2.4.b "Tests Results." Two weeks will be required to review this data before the Contracting Officer will be available to visit the Contractor's laboratory for witnessing the test. Should the results of the witness test reveal that the model does not perform in accordance with the requirements of the specification and the guaranteed values, the Contractor shall make such changes to the model as are required to make it acceptable before again notifying the Contracting Officer that the witness tests are ready to be run. Immediately upon completion of each witness test, copies of all data taken during the test shall be delivered to the Contracting Officer witnessing the test. Computations of test results and plotted preliminary curves shall be furnished to the witness.

C2-14.2.8 Test Report. The Contractor shall, within 30 days of receipt of approval of the witness test, furnish to the Contracting Officer seven bound copies of a report covering the model performance and cavitation tests. Each test report shall include, as a minimum, the following:

- a. A statement of the purpose of the test. The name of the project, the contract number, and specified pumping conditions. Where the guaranteed values differ from the specified values, they shall also be given.
- b. A resume of preliminary studies, if such studies were made.
- c. A description of the model pump and motor including serial numbers, if available. The information required under "b" above may be included here.
- d. Copies of calibration of instruments used.
- e. A description of the test procedure used, including dates, test personnel, any retest events, and witness test data.
- f. Sample computations (complete).
- g. A discussion of the test results.
- h. Conclusions.
- I. Photographic evidence in the form of either 24 color photographs of test equipment, the test setup and representative test segments, or a VHS videotape, at least 30 minutes in length, covering the same information as the photographs. All photographic evidence

shall be labeled with the Contract number, location, date/time, and test activity. The videotape shall be voice annotated with the same information.

- j. Copies of instrument calibration.
- k. Copies of all recorded test data.
- l. Curves as required in paragraph C2-14.2.4.b "Tests Results."
- m. Curves showing the performance of the prototype pump.
- n. Drawings, including cross sections of the water passages that should be incorporated in the construction contract.
- o. Drawings of the test setup, showing all pertinent dimensions and elevations and a detailed dimensioned cross section of the model pump.

C2-15. ANCHORS AND SUPPORT ITEMS. All anchor bolts for the pump and those accessories of the pump furnished with the pump including any special supports for the pump shall be designed, sized and supplied by the pump machinery supplier as part of this section.

C2-16. RESERVED.

C2-17. RESERVED.

C2-18. NAMEPLATE. The pump shall be identified by means of a separate name-plate permanently affixed in a conspicuous location. The plate shall bear the manufacturer's name, model designation, serial number if applicable, and other pertinent information such as horsepower, speed, capacity, type, direction of rotation, etc. The plate shall be made of corrosion-resisting metal with raised or depressed lettering and contrasting background.

C2-19. INSTRUCTION PLATES. The pump shall be equipped with suitably located instruction plates, including any warnings and cautions, describing any special and important procedures to be followed in starting, operating, and servicing the equipment. Plates shall be made of corrosion-resisting metal with raised or depressed lettering and contrasting background.

C2-20. GUARDS AND COVERS. Safety guards and/or covers shall be provided wherever necessary to protect the operators from accidental contact with moving parts. Guards and covers shall be of sheet steel, expanded metal, or another acceptable material and removable for disassembly of the pump.

C2-21. SPARE PARTS. The Contractor shall furnish the following spare parts:

- a. Two complete sets of bearing seals used on two pumps.
- b. Sufficient length of packing to allow repacking of all glands.

PART 3 EXECUTION

C2-22. **INSTALLATION.** The installation of the equipment furnished under this section and related drive machinery furnished under other sections of this specification shall be in accordance with the approved Installation and Erection Instructions Manual required by paragraph C2-3 "SUBMITTALS." The erection engineer, familiar with the equipment to be installed, shall supervise the handling, installation, start-up and testing of the equipment as required by Section "C5-FIELD SERVICES."

C2-23. **FIELD TESTS.** Field test shall be in accordance with the requirements of Section "C5 - FIELD SERVICES."

C2-25 **MEASUREMENT AND PAYMENT.** No measurement will be made for work specified in this section. Payment for the fabrication of the pump will be made at the contract unit price for "Pump". Price and payment shall constitute full compensation for furnishing all plant, labor, and equipment to complete the work as specified herein and as shown on the drawings.

C2-25.1. Modeling testing, fabrication, collection and reduction of data and other work associated with model testing shall be paid for at the contract lump sum price for "Model Testing." Payment for all work related to designing the pumps, engineering required for matching and coupling drive components and controls, and dynamic and torsional analysis shall be made at the contract lump sum price for "Engineering and Design Service."

C2-25.2. Payment for special tools, patterns, setups and jigs and/or for modifying standard tools used solely for the production of the pumps shall be paid for at the contract lump sum price for "Tools and Jigs". Price and payment shall constitute full compensation for furnishing all plant, labor, and equipment for special tools, patterns, setups and jigs and/or modifying standard tools and shall be invoiced on the first (1st) delivery order.

SECTION C3 - SPEED REDUCERS FOR STORM WATER PUMPS

PART 1 - GENERAL

C3-1. **SCOPE.** The work consists of designing and furnishing a minimum of one helical

gear, double reduction speed reducer with coupling and shaft required for connection with the engine and pump specified in Sections C1 and C2 respectively. These requirements shall also apply for up to seven identical speed reducers if required.

C3-2. REFERENCES. The publications listed below form a part of this specification to the extent referenced. The publications are referred to in the text by basic designation only.

C3-2.1 American Gear Manufacturers Association (AGMA).

AGMA 6010-E Standard for Spur, Helical, Herringbone, and Bevel (1991)
Enclosed Drives.

AGMA 6025-C Sound for Enclosed Helical, Herringbone, and Spiral (1990) Bevel
Gear Drives.

C3-2.2 American Society of Mechanical Engineers (ASME).

ASME B31.1 Power Piping. (1992)

C3-2.3 Anti-friction Bearing Manufacturers Association (AFBMA).

AFBMA 9 Load Ratings and Fatigue Life for Ball Bearings. (1990)

AFBMA 11 Load Ratings and Fatigue Life for Roller Bearings. (1990)

C3-2.4 National Electrical Manufacturers Association (NEMA).

NEMA 250 Enclosures for Electrical Equipment (1000 Volts Maximum).
(1991)

C3-2.5 National Fire Protection Association (NFPA).

NFPA 70 National Electrical Code. (1993)

C3-2.6 National Fluid Power Association (NFLPA).

NFLPA T3.10.8.8 R1 Hydraulic Filter Fine Element Multi-Pass Test (1990) Hydraulic
Fluid Power - Filters - Multi-Pass Method for Evaluating Filtration
Performance

C3-3. GENERAL REQUIREMENTS.

C3-3.1 Materials and Equipment. Materials and equipment shall be the standard products of manufacturers regularly engaged in the production of gear reducers and couplings for pump drives and shall essentially duplicate products which have been in prior satisfactory use for at least 2 years prior to bid opening. All products shall be new. The reduction gear and couplings will be used to transmit power from the diesel engine to the pump as indicated on the contract drawings and specified herein. The gear reducers and couplings shall be adequately designed and conservatively rated to provide a reliable, efficient, smooth and quiet running drive under all operating conditions. The gear reducers shall be furnished complete with all auxiliaries ready for operation after installation under another contract.

C3-3.2 Spare Parts. The gear reducer/coupling manufacturer shall provide, at the time of delivery, one set of standard recommended spare parts for each unit and coupling. The spare parts shall include those items customarily furnished plus any other special items which the manufacturers deems necessary for the gear reducer and couplings provided. All spare parts shall be duplicates of the original parts furnished and interchangeable therewith. All spare parts shall be enclosed in separate, sealed moisture proof bags with desiccant bags, and packed in containers plainly marked "SPARE PARTS ONLY". A packing list, indicating the contents of each container, shall be securely fastened, in a moisture- proof envelope, to the outside of the container. The packing list shall also provide the following information:

- (1) Manufacture.
- (2) Contract number.
- (3) Identification, including the manufacturer's drawing number or part number for each spare part in the container.

As a minimum the manufacturers of the gear reducers and couplings shall provide the following spare parts:

ITEM	DESCRIPTION	QTY
1	Set of filter elements	7
2	Set of each type of hose used.	7
3	Lubrication pumps	7
4	Coupling seals set	7
5	Bearing seals set	7
6	Gear reducer gasket set	7

7	Engine coupling heat resistant elastomer member set	7
---	---	---

C3-3.3 Delivery and Storage. Material and equipment shall be protected from weather, humidity, temperature variation, dirt, dust, and other contaminants during delivery and storage. The gear reducer and accessories shall be protectively processed for not less than 24 months storage indoors at the destination.

C3-4. SYSTEM DESCRIPTION.

C3-4.1 Design Conditions. The reduction gear unit shall be capable of continuously transmitting not less than the maximum horsepower required by the pump at maximum load, Condition No. 6 of paragraph C2-6.3 "Capacities", multiplied by a minimum service factor of 2.25. The gear reducer shall be capable of operating with ambient temperatures in the range of 32 degrees F to 125 degrees F. Speed reducers with AGMA application factors higher than the minimum will be rated higher in the award evaluation.

C3-4.2 Critical Speeds. Dynamic analysis of the pump, reducer, and engine assembly shall be performed by the pump manufacturer. The reducer manufacturer shall coordinate with the pump manufacturer in performing the dynamic analysis. The reducer manufacturer shall make any design modifications to the reducer or connecting couplings which are necessary to avoid resonances in the system. A torsional natural frequency within 25 percent or lateral natural frequency within 25 percent of normal operating speed of any shaft or gear mesh frequency is unacceptable.

C3-4.3 Arrangement. The speed reducer input and output shaft shall be connected to the engine and pump with flexible steel, self aligning gear type couplings with exposed coupling bolts. The Contractor shall ensure compatibility and fit of the reducer high-speed and low-speed shafts with that of the pump and engine. The speed reducer mounting shall be designed to permit removal of the reducer and reinstallation without requiring realignment of the reducer and shafting or altering pump and/or engine. Before assembly, each gear and shaft assembly shall be statically and dynamically balanced. Reducer vertical shaft centerline distance and arrangement shall be as shown on the contract drawings. There shall be no horizontal offset between the low-speed and high-speed shaft.

C3-5. SUBMITTALS. Government approval is required for all submittals with a "GA" designation; submittals having an "FIO" designation are for information only. The following shall be submitted in accordance with Section H "Submittal Procedures":

C3-5.1 SD-01, Data. Provide complete computations, design loads, and catalog data, as follows:

- a. System Description; GA.
- b. Bearings; GA.
- c. Gears; GA.
- d. Shafts; GA.
- e. Couplings ; GA.
- f. Backstop; GA.
- g. Housing; GA.
- h. Lubrication System; GA.
- i. Instrumentation; GA.
- j. Speed Reducer and Related Lubricating and Auxiliary Equipment; GA.

C3-5.2 SD-04, Drawings. Within 30 days of notice of award of contract, drawing shall be submitted as listed below. Drawings shall be of sufficient size for easy reading and consisting of a complete list of equipment and materials, including manufacturer's descriptive and technical literature; performance charts and curves; catalog cuts; and installation instructions. Drawings shall show proposed layout and anchorage of equipment and appurtenances, and equipment relationship to other parts of work including clearances for maintenance and operation. Drawings notes and dimensions shall be in English. Drawings shall include the following:

- a. Reducer Drawings; GA.
- b. Lubrication System; GA.
- c. Instrumentation; GA.

C3-5.3 SD-09, Reports. A field test report documenting all data for load and speed measurement, lubrication oil temperature and flow, cooling water temperature and flow, gear contact patterns, adjustment of component settings, and otherwise showing compliance with specified performance criteria, submittals shall include:

- a. Shop Testing; GA.
- b. Field Testing; GA.

C3-5.4 SD-10 Reducer Quality Control Report. Submittals shall include:

- a. Material Chemical Certification; GA
- b. Heat Treatment Certification; GA
- c. Gear Accuracy Reports (lead and profile charts to confirm with gearing calculations and NDT certificates); GA

C3-5.5 SD-19, Operation and Maintenance Manuals. The Operation and Maintenance Manual shall provide detailed startup and operating procedures, lubrication instructions, installation and alignment procedures, routine maintenance requirements and procedures, complete detailed procedures for disassembly and assembly of the reducer, parts list for all parts detailed, assembly drawings of the reducer showing all parts, suppliers for all parts, settings and adjustment for protective devices, and a list of all tools, handling devices, and spare parts furnished. Submittals shall include:

- a. Operation and Maintenance Manual; GA.

PART 2 PRODUCTS

C3-6. GENERAL. The reducer assembly shall be rated in accordance with AGMA 6010-E as applicable. The unit rating shall be equal to or exceed the maximum input power times an application factor. The service factor shall be 2.25 for reducers driven by diesel engines. The speed reducers shall be designed and manufactured by a firm that is regularly engaged in the manufacture of speed reducers of the type utilized for these installations. The reduction gear unit shall be single or double reduction, vertical off-set, parallel horizontal shafts with an anti-reverse backstop and, lube oil pumps. Cooling will be by external keel coolers supplied by others. The gear manufacturer shall provide external connections for coupling to the keel coolers. The manufacturer shall also supply cooling requirements. The units shall be factory assembled and furnished complete in every respect with couplings, supports, and lubrication system. Total gear losses shall not exceed three percent (3%) of the input horsepower. The nameplate shall bear the manufacturer's name, model designation, serial number, unit rating, service factor, reduction ratio, and other applicable information. The gear reducer shall conform to the requirements of AGMA 6010-E. The reducer shall display the certified manufacturer's AGMA insignia as evidence of conformance to AGMA standards.

C3-7. BEARINGS. Bearings shall be the anti-friction type, certified by the manufacturer for the application and shall be rated for an L-10 life of 100,000 hours at the rated operating load of the reducer. Ball bearing load ratings shall conform to AFBMA 9. Roller bearing load ratings shall conform to AFBMA 11. Bearings shall be self-contained within the gear case housing and

shall be oil lubricated from the gear unit's pressure lubrication system.

C3-8. GEARS. Gearing shall be of helical design, precision built from alloy steel and shall be gas nitrided or carburized, through hardened and precision machine ground. Gears shall be AGMA Quality No. 12 or higher. The pinion or gear of each helical set shall be crowned to eliminate end loading. Gears shall use standard diametral pitches. In addition to rating the gears according to AGMA 6010-E, gear stresses shall not exceed 80 percent of yield strength for engine peak torque prior to stall. Each gear shall be statistically and dynamically balanced. The maximum pitch line velocity shall not exceed 4,000 feet per minute at 105 percent of pump design speed.

C3-9. SHAFTS. Each shaft shall be heat treated alloy steel with precision ground surfaces for bearings and gears. Input shaft size and configuration shall be compatible with the engine. Output shaft size and configuration shall be compatible with the pump. Welded shafts are not acceptable. Individual shafts shall be statically and dynamically balanced along the axial and radial axes to an amplitude of less than .001 inch at design speed. Suitable oil seals shall be provided where shafting passes through the housing to insure against oil leakage and dirt and water infiltration.

C3-10. COUPLINGS. The speed reducer shall be connected to the engine and pump by flexible steel, self aligning gear type couplings. The couplings shall have a service factor of 2.25 based on maximum rated load. In addition, at peak engine torque prior to stall, stresses shall not exceed 80 percent of yield strength. Engine end- couplings shall feature piloting bushings of bronze and shall transmit torque by means of compression of heat resistant elastomer members which shall effectively absorb shock and engine vibrations. The angle and offset misalignments between coupled shafts shall be less than one half of that allowed by the coupling manufacturer. The couplings shall be dynamically balanced to AGMA balance classification 7 or better. Coupling to shaft fit shall be as shown in the table of fits in paragraph C2-11.5.2 "Class of Fit Required".

C3-11. BACKSTOPS. A backstop shall be provided on the high speed shaft of the reducer to prevent reverse rotation of the pump. The backstop shall be sized for 150% of maximum pump drive torque. A service factor of 2.25 shall be applied to the manufacturer's published ratings. In addition the backstop shall be suitable for continuous operation at engine idle speed. The backstop shall be of a type with cylindrical rollers on inclined cam planes. The backstop shall be mounted with the outer race moving and the inner race fixed. The backstop shall operate at a temperature of less than 160 degrees F under all operating conditions with an ambient temperature of 32 to 125 degrees F. The backstop shall be provided with a circulating oil lubrication system and shall have sufficient flow rate to provide the required cooling. The lubrication system may be part of the gear reducer lubrication system. The recommended gearbox lubricant shall be selected for compatibility with the backstop mechanism.

C3-12. HOUSING.

C3-12.1 General. The housing shall be fabricated from welded steel plates and shapes, stress relieved prior to machining, and reinforced to carry all applied loads and to maintain gear alignment. The housing shall fully enclosed all gearing and bearings and split along the centerline of the shafts. The slit centerline shall be joined by machined flanges. The housing shall be rigidly bolted to the reducer baseplate. It shall have a minimum of four jack bolts to facilitate alignment. The housing bottom shall be machined. The interior of the reducer shall be painted with an oil compatible coating. The exterior shall be painted with the manufacturer's standard coating system. Color shall be light gray. The housing shall have an oil fill connection and a drain connection with a magnetic plug. Lifting lugs shall be provided for lifting the entire reducer assembly and any subassembly or component which cannot be lifted using web slings. The housing shall be water tight up to the invert of the gear output shaft for the pump.

C3-12.2 Seals. Shafts shall have a lip seals to prevent leakage of oil and exclude dirt and water. Lip seals shall utilize hardened steel wear sleeves to preclude shaft repair or replacement if the seal wears the shaft. The seals shall be water tight up to the lowest shaft invert.

C3-12.3 Inspection Covers. The housing shall have inspection holes with cover plates located above the maximum oil level to permit viewing of gear teeth allowing evaluation of the contact patterns of each gear mesh and to allow inspection of internal features of the lubrication system.

C3-13. LUBRICATION SYSTEM.

C3-13.1 General. The speed reducer shall be provided with an oil lubrication system that will provide continuous lubrication to the gears, bearings, and oil lubricated type backstop. The system shall consist of an oil circulating pump, oil-to-water keel coolers (supplied by others), piping, filters, and controls. Each reducer shall be provided with its own system. The lubrication system shall be self - contained and provided with pressure and temperature gauges and with alarms for low oil pressure and high temperature. The oil circulating pump shall be driven directly from the speed reducer shaft. The maximum oil sump temperature at rated speed and load shall not exceed 160 degrees F at an ambient temperature of 125 degrees F. The reducer shall be capable of operating with an ambient temperature in a range of 32 to 125 degree F.

C3-13.2 Oil Pump. The oil pump shall be positive displacement type gear type. The pump shall have a relief valve which discharges to the sump. The pump shall be reversible so it continues to function during a runaway condition. The pump shall be capable of supplying sufficient oil through the keel coolers to cool the speed reducers.

C3-13.3 Oil and Breather Filters. The lubricating system shall have two oil filters on the pump outlet side. One filter shall be for removing particles and the other for water removal. The filter for particles shall have a Beta rating of B6 greater than 75 at 60 psi differential tested in

accordance with NFLPA T3.10.8.8 R1. The reducer manufacturer may propose an alternate Beta rating by submitting proof that B6 greater than 75 is unsuitable for the lubricant to be used. Each filter shall incorporate a glycerin filled differential pressure gauge to indicate the pressure drop across the filter. The filter shall have an internal magnetic element. The water removal filter shall maintain a water content in the oil of no greater than 200 ppm. All filter assemblies shall be sized so the pressure drop across the clean filter is no greater than 4 psi. The particle filter shall be sized to avoid bypass at a startup oil temperature of 70 degrees F. Filters shall have a bypass setting of 45 to 60 psi. Element collapse rating shall not be less than 150 psi. The breather filter shall have a Beta rating of B6 greater than 75 and a desiccant chamber to remove water.

C3-13.4 Remote Radiator. The speed reducers shall be cooled by air cooled engine radiators. A pump of sufficient pump capacity in terms of flow rate and pressure and control valves shall be supplied by the speed reducer manufacturer for circulating the speed reducer oil thru the remote radiator. The radiator will be located approximately 70 feet from the speed reducers with ten 90 degree elbows on the supply line and ten 90 degree elbows on the return line. Supply and return line is limited in size to 6 inch, schedule 40 pipe. Minimum air temperature that the line will be exposed is 32 degrees.

a) **RADIATOR**: A horizontal, remotely located, fan cooled, heat exchanger capable of removing all waste heat generated by the engine shall be provided.

(1) Radiator shall be designed or selected using 100o F ambient temperature at sea level and a coolant composed of 50% water and 50% ethylene glycol. Duty cycle shall be continuous

(2) The radiator shall be designed or selected to maintain the temperature of water/glycol coolant leaving the engine jacket at 165o F to 170o F and the temperature of the lube oil leaving the engine at 185o F. These temperatures and any other cooling requirements shall be maintained at the continuous rating horsepower load of the engine and at 110% of this load. The radiator shall be adequately designed and conservatively rated.

(3) Tubes shall be seamless admiralty brass, not less than 5/8" O.D., and shall have copper or aluminum fins. The core shall have a screen guard.

(4) The vertical discharge fan or fans shall be driven by T.E.F.C., ball bearing 460 volt, 3 phase, 60 Hertz electric motors conforming to NEMA Standards. The number of fans required per radiator, horsepower and speed requirements shall be determined by the radiator manufacturer, multi-v-belt or geared drives with guards shall connect motors to fans. Motors shall be equipped with 120 volt single phase space heaters with built in controls. Space heater terminals shall be brought out to cast iron gasketed motor junction box.

(5) The entire heat exchanger construction shall be in accordance with the ASME Unfired Pressure Vessel Code but need not bear the ASME stamp. All structural members and

steel appurtenances shall be hot dipped galvanized. The radiator shall be designed and adequately braced to withstand a wind velocity of 150 mph.

(6) The radiator shall be furnished complete with all accessories including a galvanized expansion tank if required. The size of all expansion tanks shall be approved by the Engineer.

(7) The radiator shall be factory tested with all of the manufacturer's standard tests.

(8) Those surfaces which cannot be galvanized, excluding aluminum fins, shall be thoroughly cleaned with solvents and made free of grease, weld, scale, etc., and prime coated with two shop coat of Tnemec #90-92 zinc coating.

C3-13.5 Reserve.

C3-13.6 Piping and Tubing. Oil lines up to 2 inches O.D. shall be seamless steel tubing with 37 degree flare or flareless fittings. Where pipe sizes of 2 inches and over are required, steel pipe with welded fittings shall be used. Water piping shall be copper or copper alloy with brazed or 95-5 soldered joints. All piping, tubing, and fittings shall conform to ASME B31.1. Vibration isolating tubing and piping supports shall be used. Oil tubing or ports shall be kept within the gear case where feasible. Dissimilar metals shall be electrically isolated to prevent corrosion.

C3-13.7 Lubricating Oil. Lubricating oil shall be mineral oil or synthetic hydrocarbon as recommended in AGMA 6010-E for a temperature range of 32 to 160 degrees F. The lubricant shall be suitable for the entire temperature range without change of lubricant. Lubricant additives shall be used as recommended by the reducer manufacturer. Lubricant shall also be suitable for use with the backstop. Catalog data of the proposed lubricant shall be submitted for approval.

C3-14. INSTRUMENTATION. Instrumentation for the reducer shall be supplied and installed as a complete working package, coordinated with the pump and engine supplier. All electrical work shall conform to NFPA 70. Electrical enclosures shall be NEMA 250, Type 4. An electrical termination cabinet shall be provided. Available power is 120 V, 1 ph. The speed reducer shall have the following devices as a minimum:

a. High oil temperature switch located in the oil sump and connected to audible and visual alarms. The switch shall be set to activate the alarm for temperatures over 180 degrees F. At temperatures of 200 degrees F and higher the engine shall automatically shutdown. Lower settings may be used if recommended by the reducer manufacturer.

b. An oil pressure gauge shall be located to indicate the oil pump pressure. The gauge shall be clearly visible from the engine room floor. The gauge shall be a 4.5 inch face diameter with a range from 0 to 150 psi and shall be glycerin filled with a snubber and isolation

valve.

c. Industrial dial type thermometers shall be located to detect oil sump temperature, oil temperature after leaving the heat exchanger and backstop oil temperature. Thermometers shall have a 4-1/2 inch face and scale range of 0 to 250 degrees F. In addition the sump temperature of the lubricating oil shall be indicated remotely by an "Alnor" type N 14/19 "Pyrotroller" mounted with the temperature indicating instrument specified for the pump bearings. The sensing element shall be an "Alnor" type 3480 stainless steel stem thermocouple and NPT fitting, all compatible with the specified indicator.

d. An oil level sight gauge with a built in reflector shall be provided. The gauge shall be located so that it can be easily read when the reducer is installed.

e. An oil flow switch shall be provided which shall activate an audible and visual alarm to indicate that oil flow is less than 80 percent of design and shall shut down the engine if flow drops below 60 percent of design.

f. A vibration alarm shall be provided with visual and audible alarms when the vibration level exceeds 0.5 inches/sec or at a baseline recommended by the manufacturer.

PART 3 EXECUTION

C3-15. TESTS, INSPECTIONS AND VERIFICATION.

C3-15.1 Shop Testing. In addition to or as part of the Contractor's normal shop testing procedure, the reducer shall be tested at rated speed, no load to check for potential problems which shall be eliminated prior to field testing. Gear contact patterns, sound level, lubrication and cooling, and all other operational characteristics shall be checked. The sound pressure level of the speed reducer shall not exceed 90 dBA measured at a distance of 1 m (3 feet) from the equipment. Sound shall be measured in accordance with AGMA 6025-C. The Contractor shall provide any preventative measures to control background noise. The Contractor shall notify the Contracting Officer 2 weeks prior to performing the shop test.

C3-15.2 Installation. The installation of the equipment furnished under this section and related drive machinery furnished under other sections of these specifications shall be in accordance with the approved "Installation and Erection Instructions Manual" described in paragraph C2-3 "SUBMITTALS." The Erection Engineer, familiar with the equipment to be installed, shall supervise the handling, installation, start-up and testing of the equipment as required by Section "C5 - FIELD SERVICES."

C3-15.3 Field Testing. Field tests shall be in accordance with the requirements of Section "C5 - FIELD SERVICES"

C3-16 MEASUREMENT AND PAYMENT. No measurement will be made for work specified in this section. Payment for the fabrication, and testing of the speed reducer and coupling will be made at the contract unit price for "Speed Reducer." Price and payment shall constitute full compensation for furnishing all plant, labor, and equipment to complete the work as specified herein and as shown on the drawings.

C3-16.1 Payment for engineering design work for the speed reducer will be made at the contract lump sum price for "Engineering and Design."

C3-16.2 Payment for shipping the speed reducer and unloading at the storage site, complete with all accessories and spare parts will be made at the contract unit price for "Shipping and Unloading."

SECTION C4 - CONTROLS

PART 1 - GENERAL

C4-1. SCOPE. The work provided for herein consists of furnishing all plant, labor, equipment and material, and performing all operations required to design, manufacture, assemble, factory test, prepare for shipment and storage, deliver, and provide instructions and supervision for erection by others under a separate contract and field test, a minimum of one control/instrument panel for the diesel engine, pump, speed reducer, and vacuum breaker specified in Sections C1, C2, C3, and elsewhere in this contract. Coordinate the suitability and compatibility of the control/instrument panel for use with the engines, speed reducer, pumps, and vacuum breaker valves specified in the associated contract specifications. These requirements shall also apply for up to seven identical control/instrument panels.

C4-2 QUALITY CONTROL

C4-2.1 General. The Contractor shall establish and maintain quality control for all manufacturing, fabrication, factory tests, preparation for shipment, erection instructions and supervision, and field testing to assure compliance with contract requirements and to maintain records of his quality control for all fabrication, erection, and testing operations, including but not limited to the following:

- (1) Shop fabrication and assembly
- (2) Preparation for shipment and storage.

(3) Factory tests before shipping.

(4) Inspection at the work site for damage to and defects in material and equipment.

C4-2.2 Reporting. Two copies of the records of inspection, erection and tests, as well as the corrective action taken, shall be furnished to the Government as directed by the Contracting Officer.

C4-3. APPLICABLE PUBLICATIONS.

C4-3.1 National Electrical Manufacturers Association (NEMA).

C4-3.2 NFPA 70 (1996) National Electrical Code.

C4-4 SUBMITTALS. Government approval is required for all submittals with a "GA" designation; submittals having an "FIO" designation are for information purposes only. The following shall be submitted in accordance with Section H "SUBMITTAL PROCEDURES".

C4-4.1 SD-01, Data.

C4-4.1.1 List of Materials; (FIO). Furnish two copies of purchase orders and work orders. Contractor shall, at time of submittal of drawing, furnish a list designating material, and components to be used for the panels.

C4-4.1.2. Materials; (GA). Furnish, within 60 days of notice of award, names of manufacturers of components and other equipment which the Contractor contemplates incorporating in the work, together with other relevant information pertaining to the components and equipment.

C4-4.1.3 Parts List;(GA). Furnish 10 copies of manufacturer's complete parts list showing all parts, components, and equipment along with spare parts for control/ instrument panel. Clearly show all details and components and describe or properly identify each individual component, part, or equipment item.

PART 2 - PRODUCTS

C4-5. CONTROL AND INSTRUMENT PANEL. The engine with accessories, the engine control and instrument panel, speed reducer and the pump shall be supplied together as a complete unit by the pump supplier in order to ensure complete compatibility of the individual components. Each complete unit shall be totally enclosed, free-standing, dead front, floor mounted, provided with a NEMA 12 enclosed, cabinet type control and instrument panelboard which shall be mounted adjacent to the engine in an accessible and readable location within ten

(10) feet of the engine. The instrument and control panelboard shall have an overall dimension of 90 inches high by 20 inches deep and width as necessary, contain not less than the following instruments and controls, the arrangement of which shall be approved by the Contracting Officer. The control and instrument panel shall include all required starters, contacts, relays, etc for the complete control and monitoring of the engine, vacuum pump, pump, speed reducer, siphon breaker valve, vacuum breaker valve, and all auxiliaries. The Contractor shall include any additional equipment or alarms necessary to safeguard the furnished equipment or required for proper and safe operation. The Contractor shall coordinate and ensure compatibility with procedures specified in Section C1. The Contractor shall supply a detailed start-up and operating procedure for the equipment supplied. Electrical supply will be 120 volt, 60 Hertz.

1) Engine running time meter calibrated in hours, minimum indication 9, 999 hours and shall be "non-resettable"

2) Tachometer.

3) Hood light switch.

4) Pressure gauge, fuel, across filter.

5) Pressure gauge, fuel, downstream of filter.

6) Differential Pressure gauge, lubricating oil, across filter.

7) Pressure gauge, lube oil, downstream of filter.

8) Pressure gauge, Gear drive lubricating oil.

9) Pressure gauge, starting air.

10) Pressure gauge, jacket water.

11) Compound pressure vacuum gauge, 30 lbs. pressure 30-inch vacuum. Air intake manifold pressure. Engine manufacturer shall specify exact gauge required.

12) Temperature indicator, pump inboard and outboard bearings.

13) Temperature indicator, jacket water in.

14) Temperature indicator, jacket water out.

15) Temperature indicator, lubricating oil in.

- 16) Temperature indicator, lubricating oil out.
- 17) Temperature indicator, gear drive lubricating oil.
- 18) Fuel flowmeter indicator (Gal/Hr).
- 19) Engine speed control including starting and stopping.
- 20) Mode switch (Test-Off-Auto)

21) An illuminated window type visual and audible annunciator, with first out indication to indicate low fuel pressure, low lube oil pressure, low reduction gear lube oil pressure, low cooling water pressure to gear reducer heat exchanger, low water pressure to stuffing boxes, engine over speed trip, high jacket water temperature, high lube oil temperature, high pump inboard and outboard oil bearing temperature, high speed reducer lube oil temperature, low engine jacket cooling water pressure, high crankcase pressure (see paragraph C1-6.2), excessive vibration (see paragraph C3-14), low reducer oil flow (below 80% of design flow) and low starting air pressure.

20) Pyrometer exhaust temperature indicator with selector switch for each cylinder exhaust and "Off" position.

21) Lube Oil Keep Warm On/Off Switch and Indicator Lights

22) Engine Start/Stop Push-buttons.

23) Siphon Breaker Open (Green Illuminated Push-button)

24) Siphon Breaker Closed (Red Illuminated Push-button)

25) Pump Lubricator Switch (Manual-Off-Auto).

26) Jacket Water Keep Warm System On/Off Switch and Indicating Lights.

27) Pre-Lube Pump Indicating Lights.

28) One control power master disconnect switch to disconnect all incoming "hot" circuits. This master switch shall have its own enclosure, shall be mounted on the inside of the panel door with handle extended through panel door, and shall be of the rotary-type with pistol grip handle G.E. Type SB-1, or approved equal, with pilot light.

29) "Start-Stop" Push-buttons to control the vacuum pump, flush mounted in the cabinet door, with red indicating pilot light.

30) Set of fuse blocks and necessary fuses for adequate protection of all control circuits as required by the National Electric Code.

31) Emergency Stop push-button.

32) Switches for the Alarm System: Test, Reset, and Acknowledge Switches.

33) All other necessary "Start-Stop" Push-buttons, indicating lights, contacts, and auxiliary relays to perform the manual and automatic functions listed under the Start-Up and Automatic Engine Stopping procedures.

34) All terminals for connection to devices outside the cabinet shall be wired to a terminal strip in the cabinet with terminals and wires identified, and shall be internally wired according to the cabinet wiring diagram provided with the cabinet.

35) Push-buttons to test all pilot lights.

36) Alarm Horn.

37) Alarm horn silencer.

38) General alarm contact to actuate alarm and light for pump unit on monitoring, console in central office.

39) Other interlocks as required for safety and proper operation, start-up and shut-down of engine and pump shall be supplied.

PART 3 - EXECUTION

C4-4.6. INSTRUMENT AND CONTROL PANEL CONSTRUCTION. The instrument board shall be constructed on an angle iron frame with the top, back and side panels of not less than No. 12 gage bonderized steel, with panels removable and held in place by stainless steel screws. All equipment within the panel shall be readily accessible by removal of one or more panels. The back panel shall be provided with a bronze insert screened louver in line with the alarm speaker. A hooded light fixture shall be provided on the top face of the board. It shall protrude about 12 inches from the face of the board and house two fluorescent lamps of sufficient wattage to light the entire front of the board. The bottom leg of the base angle shall be drilled all around for cap screws for fastening to the floor or engine base structure, through shock-absorbing mounts. All wiring for the instrument board shall conform to the latest issue of the National Electrical Code and shall be a minimum No. 14 A.W.G. Groups of exposed wires shall be run straight horizontally or vertically on the back of the board with short radius right angle bends,

properly cleated, and shall terminate at terminal blocks near the bottom of the board. All terminal blocks shall provide a minimum of four (4) spare terminals. Wiring and tubing between control panel and engine shall be included. Provision shall be made for easy field connection to external devices on pump and other equipment. The temperature indicators may be combined into one or more multiple position selector switch type. All instruments and controls shall be properly and neatly labeled with engraved laminated plastic nameplates with black letters on white background. The instrument boards shall be finished both sides with a light grey machinery enamel.

C4-4.7. **START-UP SEQUENCE.** The pumping unit shall be manually put into service by one person from the instrument panel as follows:

1) Energize panel by turning "Master Switch" on. Green light shall indicate the panel is on.

2) Start diesel engine through momentary contact "Engine Start" switch. The "Engine Start" switch shall be electrically interlocked so that the air start solenoid valve will not open until the following actions have been accomplished:

a. The pre-lube pump has been energized and normal lube oil pressure has been attained.

b. A pressure or flow switch in the city water supply line senses water flow to the horizontal pump's stuffing box.

3) After sufficient low speed warm-up, engine shall be brought up to normal operating speed. The pre-lube pump shall be automatically shut-down once the engine has started.

4) Visual and audible alarms shall indicate any malfunction.

C4-4.8 Automatic Engine Stopping.

C4-4.8.1 Delayed Stop. Approved means shall be provided to automatically reduce engine speed to the idle setting and then, after a 10-minute delay for temperature stabilization, to stop the engine.

C4-4.8.2 Immediate Stop. Approved means shall be provided to immediately and automatically stop the engine when any of the following conditions exist:

(1) Reducer lubricating oil pressure decreases below the minimum recommended by the reducer manufacturer.

(2) Reducer lubricating oil flow decreases below 60% of design flow.

- (3) Reducer Lubricating oil temperature exceeds 200 degrees F.
- (4) Engine lubricating oil pressure decreases below the minimum recommended by the engine manufacturer.
- (5) Engine jacket water temperature exceeds the safe operating temperature.
- (6) Engine crankcase pressure exceeds a safe limit.
- (7) Engine speed exceeds the safe speed recommended by the engine manufacturer. The over speed trip shall require manual resetting. a second over speed trip shall be provided to back up the normal over speed trip in the event it fails to stop the engine.

C4-8. MEASUREMENT AND PAYMENT. No measurement will be made for the assembly, factory testing, and preparation for storage of the new control and instrument panel complete with all auxiliaries, accessories and spare parts. Payment for the manufacture, assembly, factory testing, and preparation for storage of the control and instrument panel will be made at the contract unit price for "Controls". Price and payment shall constitute full compensation for furnishing all plant, labor, materials, equipment, operation and maintenance manuals, parts list, and performing all necessary operations, including factory testing.

C4-8.1 Payment for engineering design work for the control and instrument panels complete with all auxiliaries and accessories shall be included in the contract lump sum price for "Engineering and Design Service."

C4-8.2 Payment for shipping the controls and unloading at the storage site, complete with all auxiliaries, accessories and spare parts will be made at the contract unit price for "Shipping and Unloading."

APPENDIX D
PHYSICAL MODEL

HYDRAULIC MODEL STUDY OF FIRST AVENUE AND COUSINS CANAL
INTERSECTION, THE COUSINS PUMPING STATION
AND THE COUSINS DISCHARGE CANAL

By

Dean K. White

Johannes Larsen

Sponsored by

COASTAL ENGINEERING AND ENVIRONMENTAL CONSULTANTS, INC.



ALDEN RESEARCH LABORATORY, INC.

Solving Flow Problems Since 1894

168-98/M876F

September 1998

HYDRAULIC MODEL STUDY OF FIRST AVENUE AND COUSINS CANAL
INTERSECTION, THE COUSINS PUMPING STATION
AND THE COUSINS DISCHARGE CANAL

By

Dean K. White

Johannes Larsen

Sponsored by

COASTAL ENGINEERING AND ENVIRONMENTAL CONSULTANTS, INC.

September 1998

ALDEN RESEARCH LABORATORY, INC.

30 Shrewsbury Street

Holden, MA 01520

	<u>PAGE</u>
ABSTRACT	i
INTRODUCTION	1
DESCRIPTION OF PROTOTYPE	2
MODEL SIMILITUDE AND SCALING CONSIDERATIONS	3
MODEL DESCRIPTION AND INSTRUMENTATION	7
TEST PROCEDURE	9
TEST PROGRAM	11
TEST RESULTS	11
CONCLUSIONS AND RECOMMENDATIONS	19
FIGURES	

ABSTRACT

The West Jefferson Levee District, working with the U.S. Army Corps of Engineers in the design of the East Harvey Canal Hurricane Protection Project, will upgrade the Cousins Pumping Station and the drainage and discharge canals. The capacity of the pump station expansion will depend on the capacity of the improvements to the First Avenue Canal. The canal base width will either be 68 ft to carry a maximum flow of 2,000 cfs or 108 ft to carry a maximum flow of 3,000 cfs. The Cousins Canal also serviced by the Cousins Pump Station will not be improved and will have a maximum capacity of 2,000 cfs. The discharge basin and the discharge canal will be expanded to carry the additional flows. Widening of the discharge canal will require increasing the length of the Destrehan Avenue Bridge one span. Coastal Engineering and Environmental Consultants, Inc., under contract to the West Jefferson Levee District to design the proposed expansion, requested the Alden Research Laboratory, Inc. (ARL) to construct a section of both the Cousins Canal and The First Avenue Canal, the existing and proposed pump stations, and the Cousins Discharge Canal immediately downstream of the discharge basin to study flow conditions and losses entering and exiting the pump station.

Modifications were made to the intake walls to minimize flow separation and loss from the drainage canals to the pump station. Velocity measurements made at the entrance to the suction tubes of the 1,000 cfs pumps indicated satisfactory flow distribution. Energy losses in the suction basin were minimized. The discharge basin operated free of major flow disturbances and head losses were acceptable.

INTERSECTION, THE COUSINS PUMPING STATION AND THE COUSINS DISCHARGE CANAL

INTRODUCTION

The West Jefferson Levee District is working with the U.S. Army Corps of Engineers in the design of the East Harvey Canal Hurricane Protection Project. As part of this project, the Cousins Pumping Station will be upgraded, and the inflow and discharge canal transitions improved. The present station consists of two stations; the older, constructed in 1973, containing four pumps with a total capacity of 1,100 cfs and the newer, constructed in 1987, containing two pumps with a total capacity of 2,000 cfs. The proposed pumping station will be constructed similar to the 1987 station and will contain either one or two 1,000 cfs pumps. The capacity of the proposed station will depend on the capacity of the proposed improvements to the First Avenue Canal. The canal base width was tested at 68 ft to carry a 2,000 cfs flow and at 108 ft to carry a 3,000 cfs flow. The existing Cousins Canal will not be improved and will carry up to 2,000 cfs. The discharge basin and discharge canal will also be improved to carry the increased flows. As part of the discharge basin improvement, an additional span is proposed for the Destrehan Avenue Bridge.

The Alden Research Laboratory, Inc. (ARL) was contracted by Coastal Engineering and Environmental Consultants, Inc. to construct and test a 1:25 scale model of the suction and discharge basins to include sections of the canals leading to and from the basins and the existing and proposed pumping stations. Two designs of the First Avenue Canal and the associated increase in pumping capacity were evaluated.

Flow conditions in both the suction basin and the discharge basin were evaluated and velocity distributions were measured at the entrance to the proposed pumping station. Energy losses were measured from the drainage canals to the suction basin and from the discharge basin to the discharge canal. Minor modifications were made to improve flow conditions and minimize losses.

The proposed pump station will use 1,000 cfs pumps similar to the existing 1,000 cfs pumps. The intake and discharge of the proposed pump station are similar to the newer existing station with the exception of the space between pumps in the proposed two pump design. The two pump design will have a wall dividing the intake bay containing the trash racks. Unlike the existing station, the proposed station intake bay will be only as wide as the rectangular entrance to the pump intake tubes.

The discharge basin will be widened on the north side to accommodate the proposed pumps and the Cousins discharge canal modified at Lapalco Boulevard to provide increased flood protection. The Destrahan Avenue Bridge will have an additional span added at the north end. The bottom of the discharge basin and the canal will be flat at elevation -9.0 ft NGVD and deepen to elevation -11 ft NGVD at the pump discharges. The canal sides will be at a 1 on 3 slope. The discharge basin water level will vary from elevation +5 to -1 ft NGVD. The discharge basin excavation will be made to accommodate the two proposed pumps even if only one pump is initially installed. The present Destrahan Avenue Bridge is supported on two pile bents positioned in the canal. Each bent is 51 ft long and utilizes seven 16 in square concrete piles. The superstructure of the bridge is above elevation +5 ft NGVD.

MODEL SIMILITUDE AND SCALING CONSIDERATIONS

To properly simulate the kinematics and dynamics of the flow phenomena to be investigated, an undistorted geometric model was required. Since the model had free surface flow, inertial and gravitational forces were dominant. A necessary condition of similitude is for the model Froude number to be equal to the prototype value. In addition, consideration must also be given to the model Reynolds number, such that viscous forces would not significantly affect the model results.

The Froude number represents the ratio of fluid inertial to gravitational forces, and is given by

Substituting Equation (1) into Equation (2) and defining the length ratio as Equation (4) results in the velocity scale ratio given in Equation (5).

$$y_p/y_m = L_r \quad (4)$$

where L_r is the length scale ratio,

$$V_r = (L_r)^{0.5} \quad (5)$$

The flow ratio, Q_r , may be written as

$$Q_r = A_r V_r \quad (6)$$

where

Q = flow, ft³

A = area, ft²

Substituting Equation (5) into Equation (6), and noting that A can be dimensionally expressed as L², yields

$$Q_r = L_r^{5/2} \quad (7)$$

model scale ratio of 1:25 resulted in a Reynolds number of 47,000, well into the turbulent flow range for the First Avenue Canal at design flow. The numerical scale ratios for various parameters of the 1:25 scale model are shown in Table 1.

TABLE 1
NUMERICAL SCALE RATIOS
1:25 MODEL

<u>Parameter</u>	<u>Scale Ratio</u>
Length, L	1/25
Velocity, V	1/5.0
Flow Rate, Q	1/3125
Time, T	1/5.0

MODEL DESCRIPTION AND INSTRUMENTATION

The model was constructed to a scale of 1:25, and located in an ARL building with the necessary flow capacity. The First Avenue Canal was modeled upstream from the suction basin a distance of 500 ft using plastic coated plywood to represent the canal surface. The Cousins Canal was modeled for a distance of 400 ft upstream of the suction basin using a cement and sand mortar finish applied to a crushed stone base. The canal geometry was controlled with templates positioned using control baselines and set to elevation with a laser leveling system. The suction basin elevation was determined by the elevation of the pump stations and the canal bottoms, see Figures 1, 2, and 3.

The intake and discharge of each pump station was constructed from the same plastic coated plywood and only features of the pump station that effected flow conditions in the suction and discharge basins were modeled. At the intake of each pump station, the model was constructed to represent the prototype from the upstream end of the structure to the point where the flow entered the vertical

Flow Measurement

Water supplied to the canals and drawn through and discharged from each of the pumps was pumped through orifice meters constructed according to ASME standards. These meters are accurate to approximately 2 percent of the indicated flow.

Water Surface Measurements

The piezometers were connected to stilling wells and read using a point gauge. Water surface elevations were measured to 0.05 ft prototype.

Point Velocity Measurements

Point velocity measurements were made with a propeller type current meter capable of reading to as low as 0.5 fps prototype.

TEST PROCEDURE

For each test condition, flow was introduced into the canals and the pumps were adjusted to the proper discharge. The drainage canal flows were then adjusted to provide the proper inflow and the suction basin water level gradually adjusted to the proper level. The discharge canal water level was adjusted with the tailgate. After setting a test condition in the model, a point gauge and stilling wells were used to measure the water surface elevations in the canal system at 12 locations, using the piezometric pressure taps installed in the bottom of the model, see Figure 4.

Raw data was entered into a spreadsheet program and plotted as a graph of canal water surface gradeline and energy gradeline versus location. Energy gradeline is defined as:

TEST PROGRAM

The First Avenue canal, with the 108 ft wide bottom width and the proposed pump station with two 1,000 cfs pumps, was installed and tested initially. The discharge basin was configured to accommodate the proposed two 1,000 cfs pumps and remained in that configuration, except for a small section of wall added where the additional pump could be installed, for the testing of the proposed single 1,000 cfs pump. Finally, the First Avenue Canal bottom width was modified to 68 ft and the suction basin changed to accommodate the proposed single 1,000 cfs pump.

TEST RESULTS

Suction Basin

First Avenue Canal with 108 ft Base and Proposed 2,000 cfs Pump Station

The suction basin flow conditions were evaluated under six combinations of canal flow at canal water surface elevation -6.7 ft NGVD, see Table 2. Operating under Initial Condition 1, at the full capacity of 5,100 cfs, there was significant separation and back flow in front of the proposed Pump 2 initiated by the geometry of the excavation through the side slope of the First Avenue Canal, see Figure 5. There was also a large area of back flow in front of Pump 1 of the newer existing station as can be seen in Figure 5. At both of the effected pumps, the back flow forced the flow to enter the suction conduit through only a fraction of the conduit entrance width. The model operating under Initial Conditions 2 and 3 continued to exhibit similar flow problems particularly when two pumps were operating in the proposed or newer existing stations, see Figures 6 and 7. Initial Conditions 4 and 5 also produced separation at the proposed Pump 2 because the flow separated off the dividing wall between the proposed Pumps 1 and 2 under these conditions, see Figures 8 and 9. The proposed pumps were not operated under Initial Condition 6 and only older existing Pumps 2 and 3 and the

Condition 1 (same as Initial Condition 1), conditions in the suction basin leading to the pump intakes were improved, see Figure 13, and the separation at Pump 2 of the proposed pump station has been eliminated by the redesign of the north intake wall. The separation at the newer existing pump station in front of Pump 1 has been reduced by the modification to the wall between the two existing pump stations. Velocity traverses taken at each of the intakes to both the proposed and existing 1,000 cfs pumps are shown on Figures 14 and 15, respectively. The flow entering the proposed pumps is relatively well distributed at the entrance to the suction tubes of each of the pumps with an average velocity entering the intakes of 2.82 fps. The figures provide the normalized velocity and point values can be multiplied by the average velocity to determine the absolute velocity. The velocity distribution at the newer existing Pump 1 is low at the left side of the opening due to the remaining separation, see Figure 15, while the flow at Pump 2 is well distributed. The average velocity entering the suction tubes of the newer existing pumps is 2.57 fps.

TABLE 3
FINAL TEST CONDITIONS 108' CANAL

Test	<u>1st Ave</u> <u>Flow</u> <u>cfs</u>	<u>Cousins</u> <u>Flow</u> <u>cfs</u>	<u>Pumps Operating</u>							
			<u>Old Exist</u>				<u>New Exist</u>		<u>Proposed</u>	
			<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>1</u>	<u>2</u>	<u>1</u>	<u>2</u>
1	3,000	2,100	x	x	x	x	x	x	x	x
2	0	2,000							x	x
3	0	2,000					x	x		
4	3,000	0					x	x		x
5	3,000	0					x	x	x	

With no flow from the First Avenue Canal and 2,000 cfs from the Cousins Canal, the entire flow was drawn through the two proposed pumps, Test Condition 2. There was a region of separation along the south wall of the proposed station, see Figure 16, that reduced flow into the south side of the Pump 1 suction tube, see Figure 17. Flow into the proposed Pump 2 was not effected by the separation, see Figure 17. When the 2,000 cfs from the Cousins Canal was pumped using the newer

First Avenue Canal With 68 ft Base and Proposed 1,000 cfs Pump Station

The 68 ft base First Avenue Canal was installed in the 108 ft canal using the same canal centerline and bottom elevation. The modifications developed during the study of the wider canal and shown as report Figures 11 and 12, were installed during the construction of the 68 ft base width canal, see Figures 25 and 26. The single proposed pump utilized Pump 1 of the two pump station. The maximum capacity of the pumping station was 4,100 cfs and the suction basin was operated at water surface elevation -6.7 ft NGVD.

The suction basin flow conditions were evaluated under four test conditions by recording flow patterns and measuring suction tube entrance velocity distributions, see Table 4. The station was initially evaluated at the full capacity of 4,100 cfs, Test 1. Flow entered the proposed pump station free of separation, see Figure 27, and the velocity distribution at the entrance to the suction tube, shown in Figure 28, is acceptable and similar to the distribution obtained with the 108 ft canal. The flow patterns in the suction basin at the newer existing station, as well as the velocity distribution at the entrances to the suction tubes, see Figure 29, are very similar to the conditions recorded with the wider canal and higher flow. As before, the back flow in front of Pump 1 of the newer existing station causes a poor flow distribution.

TABLE 4
FINAL TEST CONDITIONS 68 FOOT CANAL

Test	<u>1st Ave</u> <u>Flow</u> cfs	<u>Cousins</u> <u>Flow</u> cfs	<u>Pumps Operating</u>						
			<u>Old Exist</u>				<u>New Exist</u>		<u>Proposed</u> <u>1</u>
			<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>1</u>	<u>2</u>	
1	2,500	1,600	x	x	x	x	x	x	x
2	1,600	0		x	x				x
3	0	2,500		x	x			x	x
4	0	2,500		x	x		x		x

Flow at the north pile bent was parallel to the canal banking and passed between the piles. The piles are on the canal bank and the shallow depth and the small quantity of flow do not make it necessary to align the pile bent with the direction of flow.

The discharge basin was operated with the two proposed pumps off at the three basin levels tested at full flow, see Figures 38, 39, and 40. The flow from the newer existing station moved rapidly along the south side of the discharge basin entering smoothly into the canal while the smaller quantity of water from the older existing station moved slowly through the discharge basin and into the canal. An area of no flow was present downstream of the proposed pumps. Flow was well aligned with the three pile bents supporting the Destrehan Avenue Bridge.

The two existing 1,000 cfs pumps were not operated and the two proposed 1,000 cfs pumps, as well as the older existing station, were operated at a total discharge of 3,100 cfs and flow conditions observed at the three discharge basin water elevations, see Figures 41, 42, and 43. The flow from the two proposed pumps moved rapidly down the north side of the discharge basin with only minor separation at the entrance to the discharge canal. The flow from the older existing station moved more slowly parallel to the flow from the two proposed pumps expanding to the south canal wall at the end of the discharge basin. Flow was not parallel to any of the three pile bents of the Destrahan Avenue Bridge and an area of back flow was present downstream of the newer existing station. The flow turned once into the discharge canal and moved parallel to the canal centerline.

The velocity traverse and the water surface and energy profiles were measured at a discharge of 5,100 cfs and a discharge basin water level of -1 ft NGVD, see Figures 44 and 45, respectively. The velocity traverse indicates an area of low velocity toward the center of the discharge basin. The flow from the newer existing station and the proposed station is higher per foot of canal width than the flow from the older existing station causing the variation in velocity across the width of the basin. The energy loss from the discharge basin to the canal over a distance of approximately 400 ft, with the basin at elevation -1 ft and a pump station flow of 5,100 cfs, was 0.16 ft.

CONCLUSIONS AND RECOMMENDATIONS

1. As initially designed, the intake of the proposed two 1,000 cfs pump expansion of the Cousins Pump Station on the 108 ft wide First Avenue Canal produced unacceptably large areas of separation and back flow at the entrance to the suction tubes of the proposed pumps. In addition, there was a large area of separation at one of the existing 1,000 cfs pumps.
2. The addition of a curved vertical wall at the north side of the proposed two pump expansion eliminated the separation and back flow at the proposed pumps. The wall between the two existing stations was modified and the separation at the existing pump was substantially reduced in size.
3. Velocity traverses at the intake of the suction tubes of the proposed pumps indicated a satisfactory distribution. The presence of the back flow at the newer existing station resulted in a non-uniform velocity distribution at the entrance to the pump suction tube downstream of the separation. The suction tubes for the two proposed and two existing 1,000 cfs pumps decrease in area by a factor of three from the suction tube entrance to the pump impeller. This reduction in area will improve the uniformity of the flow field at the impeller.
4. The loss in energy between the two drainage canals and the suction basin was 0.05 ft and 0.17 ft for the First Avenue Canal and the Cousins Canal, respectively, when the total station flow was 5,100 cfs and the suction basin was at elevation -6.7 ft NGVD.
5. The drainage canals and the pumping station were modified to represent the 68 ft base width First Avenue Canal and a pump station expansion of one 1,000 cfs pump. The resulting total station capacity would be 4,100 cfs. The modifications developed during the two pump expansion were installed in the one pump expansion and functioned satisfactorily.

FIGURES




FIGURE 1 CPS CANALS MODEL LAYOUT





FIGURE 4 PRESSURE TAP LOCATIONS



PUMPING

OLDER EXISTING STATION
 PUMP 1 0 PUMP 2 0
 PUMP 3 350 CFS PUMP 4 0

NEWER EXISTING STATION
 PUMP 1 1000 CFS PUMP 2 1000 CFS


PROPOSED STATION
 PUMP 1 1000 CFS PUMP 2 0

IN FLOW

FIRST AVE CANAL 2000 CFS
 COUSINS CANAL 1350 CFS

FIGURE 6 FLOW PATTERNS AT 3350 CFS





PUMPING
 OLDER EXISTING STATION
 PUMP 1 0 PUMP 2 350 CFS
 PUMP 3 350 CFS PUMP 4 0

NEWER EXISTING STATION
 PUMP 1 0 PUMP 2 0

PROPOSED STATION
 PUMP 1 0 CFS PUMP 2 1000 CFS

IN FLOW
 FIRST AVE CANAL 1000 CFS
 COUSINS CANAL 700 CFS

FIGURE 8 FLOW PATTERNS AT 1700 CFS






FIGURE 10 FLOW PATTERNS AT 1700 CFS





FIGURE 12 RECOMENDED CURVED WALL BETWEEN EXISTING STATIONS



PUMP INTAKE # 1



PUMP OPERATION

EXISTING STATION

TWO PUMPS AT 1,000 cfs
THREE PUMPS AT 350 cfs
ONE PUMP AT 50 cfs


PROPOSED STATION

TWO PUMPS AT 1,000 cfs

CANAL CONDITIONS

FIRST AVENUE CANAL 3,000 cfs
COUSINS CANAL 2,100 cfs
SUCTION BASIN EL. -6.7 ft


PUMP INTAKE # 2



SHOWING PUMP INTAKES #1 AND #2
LOOKING DOWNSTREAM

NORMALIZED VELOCITY USING
AVERAGE VELOCITY OF 2.82 FPS

FIGURE 14 PROPOSED PUMP STATION NORMALIZED INLET VELOCITY
DISTRIBUTION TOTAL STATION FLOW 5100 CFS 108 FT CANAL



PUMPING

OLDER EXISTING STATION			
PUMP 1	0	PUMP 2	0
PUMP 3	0	PUMP 4	0
NEWER EXISTING STATION			
PUMP 1	0	PUMP 2	0
PROPOSED STATION			
PUMP 1	1000 CFS	PUMP 2	1000 CFS

IN FLOW
 FIRST AVE CANAL 0
 COUSINS CANAL 2000 CFS

FIGURE 16 FLOW PATTERNS AT CONDITION 2







FIGURE 18 FLOW PATTERNS AT CONDITION 3





PUMP OPERATION


EXISTING STATION
 TWO PUMPS AT 1,000 cfs
 THREE PUMPS AT 0 cfs
 ONE PUMP AT 0 cfs

PROPOSED STATION
 PUMP # 2 AT 1,000 cfs
 PUMP # 1 AT 0 cfs

CANAL CONDITIONS
 FIRST AVENUE CANAL 3,000 cfs
 COUSINS CANAL 0 cfs
 SUCTION BASIN EL. -6.7 ft

NORMALIZED VELOCITY USING
 AVERAGE VELOCITY OF 2.82 FPS

FIGURE 20 PROPOSED PUMP STATION NORMALIZED INLET VELOCITY
 DISTRIBUTION TOTAL STATION FLOW 3000 CFS 108 FT CANAL



PUMP OPERATION

EXISTING STATION
 TWO PUMPS AT 1,000 cfs
 THREE PUMPS AT 0 cfs
 ONE PUMP AT 0 cfs

PROPOSED STATION
 PUMP # 1 AT 1,000 cfs
 PUMP # 2 AT 0 cfs

CANAL CONDITIONS
 FIRST AVENUE CANAL 3,000 cfs
 COUSINS CANAL 0 cfs
 SUCTION BASIN EL. -6.7 ft

NORMALIZED VELOCITY USING
 AVERAGE VELOCITY OF 2.82 FPS

FIGURE 22 PROPOSED PUMP STATION NORMALIZED INLET VELOCITY
 DISTRIBUTION TOTAL STATION FLOW 3000 CFS 108 FT CANAL




FIGURE 24 COUSINS GRADELINE 5,100 CFS





FIGURE 26 RECOMMENDED CURVED WALL ENTERING NEW PUMP STATION 68 FT CANAL

PUMP INTAKE # 1



PUMP OPERATION

EXISTING STATION
TWO PUMPS AT 1,000 cfs
THREE PUMPS AT 350 cfs
ONE PUMP AT 50 cfs

PROPOSED STATION
PUMP # 1 AT 1,000 cfs

CANAL CONDITIONS
FIRST AVENUE CANAL 2,500 cfs
COUSINS CANAL 1,600 cfs
SUCTION BASIN EL. -6.7 ft

NORMALIZED VELOCITY USING
AVERAGE VELOCITY OF 2.82 FPS
LOOKING DOWNSTREAM

FIGURE 28 PROPOSED PUMP STATION NORMALIZED INLET VELOCITY
DISTRIBUTION TOTAL STATION FLOW 4100 CFS 68 FT CANAL





FIGURE 30 FLOW PATTERNS TEST2





PUMPING

OLDER EXISTING STATION
 PUMP 0 PUMP 2 350 CFS
 PUMP 3 350 CFS PUMP 4 0


NEWER EXISTING STATION
 PUMP 1 0 PUMP 2 1000 CFS

PROPOSED STATION
 PUMP 1 1000 CFS

IN FLOW
 FIRST AVE CANAL 2500 CFS
 COUSINS CANAL 0

FIGURE 32 FLOW PATTERNS TEST3





PUMP OPERATION

EXISTING STATION
 ONE PUMP AT 1,000 cfs
 TWO PUMPS AT 250 cfs

PROPOSED STATION
 PUMP # 1 AT 1,000 cfs

CANAL CONDITIONS
 FIRST AVENUE CANAL 2,500 cfs
 COUSINS CANAL 0 cfs
 SUCTION BASIN EL. -6.7 ft

NORMALIZED VELOCITY USING
 AVERAGE VELOCITY OF 2.82 FPS
 LOOKING DOWNSTREAM

FIGURE 34 PROPOSED PUMP STATION NORMALIZED INLET VELOCITY
 DISTRIBUTION TOTAL STATION FLOW 2500 CFS 68 FT CANAL

TOTAL FLOW 5100 CFS

PUMPING

OLDER EXISTING STATION

PUMP 1 50 PUMP 2 350 CFS

PUMP 3 350 CFS PUMP 4 350 CFS

NEWER EXISTING STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

PROPOSED STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

WATER ELEVATION + 2 FT

SLOW MOVING FLOW 




FIGURE 36 DOWNSTREAM FLOW PATTERNS AT 5100 CFS

TOTAL FLOW 3100 CFS

PUMPING

OLDER EXISTING STATION

PUMP 1 50 PUMP 2 350 CFS
PUMP 3 350 CFS PUMP 4 350 CFS

NEWER EXISTING STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

PROPOSED STATION

PUMP 1 0 PUMP 2 0

WATER ELEVATION - 1 FT

SLOW MOVING FLOW - - - - ->




FIGURE 38 DOWNSTREAM FLOW PATTERNS AT 3100 CFS

TOTAL FLOW 3100 CFS

PUMPING

OLDER EXISTING STATION

PUMP 1 50 PUMP 2 350 CFS

PUMP 3 350 CFS PUMP 4 350 CFS

NEWER EXISTING STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

PROPOSED STATION

PUMP 1 0 PUMP 2 0

WATER ELEVATION + 5 FT

SLOW MOVING FLOW - - - - ->




FIGURE 40 DOWNSTREAM FLOW PATTERNS AT 3100 CFS

TOTAL FLOW 3100 CFS

PUMPING

OLDER EXISTING STATION

PUMP 1 50 PUMP 2 350 CFS

PUMP 3 350 CFS PUMP 4 350 CFS

NEWER EXISTING STATION

PUMP 1 0 PUMP 2 0

PROPOSED STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

WATER ELEVATION + 2 FT

SLOW MOVING FLOW - - - - ->





FIGURE 42 DOWNSTREAM FLOW PATTERNS AT 3100 CFS



PUMP OPERATION

EXISTING STATION

TWO PUMPS AT 1,000 cfs
 THREE PUMPS AT 350 cfs
 ONE PUMP AT 50 cfs

PROPOSED STATION

TWO PUMPS AT 1,000 cfs

CANAL CONDITIONS

TOTAL FLOW 5,100 cfs
 WSEL = -1.0 ft

VELOCITY TRAVERSE IS 37 ft UPSTREAM FROM
 CENTER LINE OF BRIDGE, AT DEPTHS OF 1.5 ft
 AND 6.5 ft. (LOOKING DOWNSTREAM)

FIGURE 44 DOWNSTREAM VELOCITY DISTRIBUTION TOTAL CANAL FLOW 5100 CFS, 2 NEW PUMPS






FIGURE 46 DOWNSTREAM BASIN 1 PROPOSED PUMP

TOTAL FLOW 4100 CFS

PUMPING

OLDER EXISTING STATION

PUMP 1 50 PUMP 2 350 CFS

PUMP 3 350 CFS PUMP 4 350 CFS

NEWER EXISTING STATION

PUMP 1 1000 CFS PUMP 2 1000 CFS

PROPOSED STATION

PUMP 1 1000 CFS

WATER ELEVATION + 2 FT

SLOW MOVING FLOW ----->




FIGURE 48 DOWNSTREAM FLOW PATTERNS AT 4100 CFS

APPENDIX E
DESIGN CALCULATIONS

DESIGN CALCULATIONS

I-WALL

CANTILEVER

COUSINS PUMP STA.
COMPLEX

BURK-KLEINPETER, INC.
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA. BATON ROUGE, LA. TUSCALOOSA, AL

Job No.
9388

Designed By
JJN

Date
4/2/98

Checked By

Page
of

I - WALL

MAX MOMENT IN SHEET PILE = 41.6 K-FT
FROM EUSTIS REPORT DATED FEB. 1998

$$S_{REQ'D} = \frac{M_{MAX}}{0.65 f_y} = \frac{41,600 \text{ lb-ft} \times 12}{0.65 (50,000)}$$


$$S_{REQ'D} = 15.36 \text{ in}^3/\text{FT.}$$

USE CASTEL C295 SHEETPILE

WITH $S = 15.53$

I WALLS & TIE BACK WALL
DUE TO COE ON 4/15

I-WALLS & TIE-BACK WALL
 Due to COE 4/15




DESIGN SUMMARY					
FLOOD SIDE WATER ELEVATION	PROTECTED SIDE WATER ELEVATION	FACTOR OF SAFETY	MAX. MOMENT FT-KIPS	WALL BOTTOM ELEVATION	SCALED DEFLECTION LB-IN ³ AT EL. 11.5
9.5	-1.0	1.5	25.1	-26.0	7.8×10^{10}
11.5	-1.0	1.0	41.6	-27.0	3.2×10^{10}

- NOTE : 1) DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PIPE MOMENT OF INERTIA IN INCHES TO 4th POWER TO OBTAIN DEFLECTION IN INCHES.
- 2) BASED ON HARR'S ANALYSIS, SHEETPILE TIPS AT EL. -27.0 PROVIDE A FACTOR OF SAFETY OF 5 OR MORE AGAINST PIPING.
- 3) SOIL PARAMETERS ARE TAKEN FROM FIGURE 8 OF 7 OCTOBER 1997 REPORT EXCEPT ABOVE EL. -10.0 WHERE PARAMETERS ARE TAKEN FROM FIGURE 6.
- 4) SEE APPENDIX FOR COMPUTER ANALYSES OF GOVERNING SHEETPILE DESIGN GIVEN ABOVE.

I-WALL DESIGN
 NORTH BANK OF DISCHARGE CANAL
 EAST OF DESTREHAN AVENUE BRIDGE

WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA



DESIGN SUMMARY					
FLOOD SIDE WATER ELEVATION	PROTECTED SIDE WATER ELEVATION	FACTOR OF SAFETY	MAX. MOMENT FT-KIPS	WALL BOTTOM ELEVATION	SCALED DEFLECTION LB-IN ³ AT EL. 11.5
9.5	-1.0	1.5	21.3	-25.5	7.4×10^{10}
11.5	-1.0	1.0	36.1	-28.0	2.9×10^{10}

NOTE : 1) DIVIDE SCALED DEFLECTION BY MODULUS OF ELASTICITY IN PSI TIMES PILE MOMENT OF INERTIA IN INCHES TO 4th POWER TO OBTAIN DEFLECTION IN INCHES.

2) BASED ON HARR'S ANALYSIS, SHEETPILE TIPS PENETRATING TO EL. -28.0 PROVIDE A FACTOR OF SAFETY OF 5 OR MORE AGAINST PIPING.

3) SOIL PARAMETERS ARE TAKEN FROM FIGURE 6 OF 7 OCTOBER 1997 REPORT.

4) SEE APPENDIX FOR COMPUTER ANALYSES OF GOVERNING SHEETPILE DESIGN GIVEN ABOVE.

I-WALL DESIGN
 COUSINS PUMP STATION
 DISCHARGE TO DESTREHAN AVENUE BRIDGE

WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA

Burk-Kleinpeter, Inc.Engineers, Architects, Planners, Environmental Scientists
4176 Canal Street, New Orleans, LA 70119

COUSINS PUMPING STATION COMPLEX

Job No.
9388Design By:
R. CHOPINDate:
4/11/98

Checked By:

Page 1
of 4

DESIGN REQUIREMENTS BASED ON
US ARMY CORPS OF ENGINEERS
EM 1110-2-2104 30 JUNE 1993
"STRENGTH DESIGN FOR REINFORCED-CONCRETE
HYDRAULIC STRUCTURES"

GENERAL REQUIREMENTS:

CONCRETE DESIGN WITH THE STRENGTH DESIGN METHOD IN
ACCORDANCE WITH THE CURRENT ACI 318, EXCEPT AS
HEREINAFTER SPECIFIED.

REINFORCEMENT GRADE 60 (ASTM A 615 (BILLET STEEL))

ANCHORAGE, DEVELOPMENT, AND SPLICES CONFORM TO ACI 318

NOTE: DESIGNER MUST INDICATE THE LENGTH OF EMBEDMENT
REQUIRED FOR BAR DEVELOPMENT, SPICE LENGTHS, AND
SPECIAL REQUIREMENTS SUCH AS STAGGERING OF SPLICES,
ETC. ON THE CONTRACT DRAWINGS.

HOOKS + BENDS IN ACCORDANCE TO ACI 318

BAR SPACING

MINIMUM - CLEAR DISTANCE BETWEEN BARS $1\frac{1}{2}$ TIMES
THE NOMINAL DIA. OF THE BAR NOR LESS
THAN $1\frac{1}{2}$ TIMES THE MAXIMUM SIZE OF
COARSE AGGREGATE.

No. 14 6 INCHES CENTER TO CENTER

No. 18 8 INCHES CENTER TO CENTER

PARALLEL REINFORCEMENT - PLACED IN 2 OR MORE LAYERS
CLEAR DIST. BETWEEN LAYERS
SHOULD NOT BE LESS THAN 6".
IN MASSIVE STRUCTURES LAYERS
SHOULD BE PLACED 12" CENTER
TO CENTER WHEREVER POSSIBLE.

MAXIMUM - 18" CENTER TO CENTER FOR BOTH PRIMARY
AND SECONDARY REINFORCEMENT

MINIMUM COVER:

UNFORMED SURFACES IN CONTACT WITH FOUNDATION 4"

FORMED OR SCREEDED SURFACES SUBJECT TO CAVITATION OR ABRASION, SUCH AS BAFFLE BLOCKS AND STILLING BASIN SLABS 6"

FORMED AND SCREEDED SURFACES SUCH AS STILLING BASIN WALLS, CHUTE SPILLWAY SLABS, AND CHANNEL LINING SLABS ON GRADE:

$t \geq 24"$ THICK 4"

$12" < t < 24"$ 3"

$t \leq 12"$ ACI 318

NOTE: IN NO CASE SHALL THE COVER BE LESS THAN:

1.5 x MAXIMUM SIZE OF AGGREGATE
OR
2.5 x MAXIMUM DIA. OF BAR

SPLICING: (ACI 318)
BARS LARGER THAN No. 11 SHALL NOT BE LAP-SPLICED.

TEMPERATURE +) SHRINKAGE REINFORCEMENT:

$A_{s_TEMP} = 0.0028 \times$ GROSS CROSS-SECTIONAL AREA
HALF IN EACH FACE, WITH A MAXIMUM
AREA EQUIVALENT TO No. 9 BARS AT
12 INCHES IN EACH FACE.

IN THIN SECTIONS WILL BE NO LESS THAN
No. 4 BARS AT 12" IN EACH FACE.

CONCRETE DESIGN:

NOTE: FOR CONCRETE DESIGN USE THE FOLLOWING LOAD COMBINATIONS

$$U = 1.7 (D+L) \quad (\text{NO HYDRAULIC LOADING})$$

$$U_h = 1.7 H_f (D+L) \quad (\text{HYDRAULIC LOADING})$$

$$U_h = 0.75 [1.7 H_f (D+L)] \quad (\text{WIND LOADING ALSO})$$

WHERE:

$H_f = 1.3$ FOR HYDRAULIC STRUCTURES, EXCEPT MEMBERS IN DIRECT TENSION

$H_f = 1.65$ FOR MEMBERS IN DIRECT TENSION.

FOR SHEAR DESIGN OF HYDRAULIC STRUCTURES USE:

$$\phi V_s \geq 1.3 (V_u - \phi V_c)$$

WHERE: V_u = FACTORED SHEAR FORCE AT THE SECTION
 ϕV_c = SHEAR STRENGTH PROVIDED BY CONCRETE
 ϕV_s = DESIGN CAPACITY OF THE SHEAR REINFORCEMENT

MAXIMUM TENSION REINFORCEMENT:

$$\text{RECOMMENDED LIMIT} = 0.25 \rho_b$$

$$\text{MAXIMUM PERMITTED UPPER LIMIT} = 0.375 \rho_b$$

USE OF COMPRESSION REINFORCEMENT SHALL BE IN ACCORDANCE WITH ACI 318.

CONTROL OF DEFLECTIONS AND CRACKING:

DEFLECTIONS DUE TO SERVICE LOADS NEED NOT BE INVESTIGATED IF THE LIMITS ON THE DESIGN STRENGTH RATIO OF REINFORCEMENT SPECIFIED ABOVE ARE NOT EXCEEDED.

MINIMUM THICKNESS OF WALLS:

WALL HT. $> 10'$ SHALL BE A MINIMUM OF 12" THICK WITH REINFORCEMENT IN BOTH FACES.

Burk-Kleinpeter, Inc.

Engineers, Architects, Planners, Environmental Scientists
4176 Canal Street, New Orleans, LA 70119

COUSINS PUMPING STATION CAMPEN

Job No.

9388

Design By:

R. CHOPIN

Date:

4/11/98

Checked By:

Page

4

of

4

USE: $f'_c = 4,000 \text{ psi}$

$$E_y = 60,000 \text{ psi}$$

$$S_{\text{MAX}} = 0.25 \times S_b$$

$$S_{\text{MIN}} = \frac{200}{E_y} \text{ OR } \frac{1}{3} \text{ INCREASE OVER REQUIRED BY DESIGN ACI 10.5}$$

COUSINS PUMPING STATION
COMPLEX

I-WALL DESIGN

BURK-KLEINPETER, INC.

ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

Job No.

9388

Designed By:

R. CHOPIN

Date:

4/11/98

Checked By:

Page /

of 6

TOP OF I-WALL ELEVATION = 11.50

BOTTOM OF CONCRETE CAP ELEVATION = 0.00

Ht. OF CONCRETE CAP = 11.5'

FOR THE DESIGN OF THE CONCRETE CAP ON THE I-WALL THE
FOLLOWING LOAD CASES WILL BE CONSIDERED:

- I - STATIC WATER PRESSURE TO SWL, NO WIND, NO DYNAMIC
WAVE FORCE (100% FORCES USED)
- II - STATIC WATER PRESSURE WITH WATER LEVEL 2 FEET
ABOVE SWL (TOP OF THE WALL), NO WIND, NO DYNAMIC
WAVE FORCE (75% FORCES USED)
- III - WIND LOAD, NO WATER (75% FORCES USED)
- IV - WIND LOAD FROM FLOOD SIDE WITH WATER SURFACE AT SWL
(75% FORCES USED)

CONSERVATIVELY SUM MOMENTS ABOUT THE BOTTOM OF THE CAP.

ALSO, CHECK AT BOTTOM OF 12" THICK WALL SECTION

TOP OF WALL 1'-0" THICK

BOTTOM OF WALL 1'-8" THICK → CAP ON TOP OF CASTEL C295
SHEET PILING

I-WALL DESIGN

Job No.
9388

Designed By:
R. CHADW


Date:
4/11/98

Checked By:

Page 2
of 6

CASE I: (LOADING PER 1' STRIP OF WALL)
(100% FORCES)

Point A = 12" wall joint



AT POINT A:

SERVICE LOADS:

$$V = 1.003^k$$

$$M = 1.003^k \times 1.89' = \underline{1.896 \text{ FT}\cdot\text{K}}$$

FACTORED LOADS:

$$V_u = (1.7)(1.3)(1.003^k) = \underline{2.22^k}$$

$$M_u = (1.7)(1.3)(1.896 \text{ FT}\cdot\text{K}) = \underline{4.19 \text{ FT}\cdot\text{K}}$$

AT POINT B:

FACTORED LOADS:

$$V_u = (1.7)(1.3)(2.817^k) = \underline{6.23^k}$$

$$M_u = (1.7)(1.3)(2.817^k \times 3.16') = \underline{19.68 \text{ FT}\cdot\text{K}}$$

COUSINS PUMPING STATION
COMPLEX

BURK-KLEINPETER, INC.
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

I-WALL DESIGN

Job No.

9388

Designed By:

R. CHAPIN

Date:


4/11/78

Checked By:

Page 3

of 6

CASE II: (LOADING PER 1' STRIP OF WALL)
(75% FORCES)



AT POINT A:

FACTORED LOADS:

$$V_u = (0.75)(1.7)(1.3)(1.836^k) = \underline{3.04^k}$$

$$M_u = (0.75)(1.7)(1.3)(1.836^k \times 2.56') = \underline{7.79 \text{ FT}\cdot\text{K}}$$

AT POINT B:

FACTORED LOADS:

$$V_u = (0.75)(1.7)(1.3)(4.129^k) = \underline{6.84^k}$$

$$M_u = (0.75)(1.7)(1.3)(4.129^k \times 3.83') = \underline{26.21 \text{ FT}\cdot\text{K}}$$

CASE III:

NOTE:

BY INSPECTION THIS CASE WILL
NOT GOVERN DESIGN

COUSINS PUMPING STATION
COMPLEX

BURK-KLEINPETER, INC.
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

I-WALL DESIGN

Job No.
9388


Designed By:
R. CHAPIN

Date:
4/11/98

Checked By:

Page 4
of 6

CASE IV: (LOADING PER 1' STRIP OF WALL)
(75% FORCES)



NOTE: FOR LOADS DUE TO WATER SEE CASE I LOADING

AT POINT A:

$$\text{FACTORED LOADS: } V_u = (0.75)(2.22^k + (1.7)(1.3)(0.1^k)) = \underline{1.83^k}$$

$$M_u = (0.75)(4.19 \text{ F.K} + (1.7)(1.3)(0.1^k \times 6.67')) = \underline{4.25 \text{ F.K}}$$

AT POINT B:

$$\text{FACTORED LOADS: } V_u = (0.75)(6.23^k + (1.7)(1.3)(0.1^k)) = \underline{4.84^k}$$

$$M_u = (0.75)(19.68 \text{ F.K} + (1.7)(1.3)(0.1^k \times 10.5')) = \underline{16.50 \text{ F.K}}$$

COUSINS PUMPING STATION
COMPLEX

BURK-KLEINPETER, INC.
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

I-WALL DESIGN

Job No.
9888

Designed By:
R. CHAPIN

Date:
4/11/98

Checked By:

Page 5
of 6

CASE II LOADING GOVERNS DESIGN

DESIGN LOADS

At Point A: $V_u = 3.0 \text{ k}$
 $M_u = 7.79 \text{ Ft.k}$

At Point B: $V_u = 6.84 \text{ k}$
 $M_u = 26.21 \text{ Ft.k}$

Minimum COVER At Points A & B = 3" CLEAR

$$d_A = 12" - (3" + \frac{1}{2}(\frac{5}{8}")) = 8.6875" \quad \text{Assume \#5 BARS}$$

$$d_B = 20" - (3" + \frac{1}{2}(\frac{9}{4}")) = 16.625" \quad \text{Assume \#6 BARS}$$

FLEXURE DESIGN: $f'_c = 4,000 \text{ PSI}$ $f_y = 60,000 \text{ PSI}$

$$\rho_b = 0.0285$$

$$\rho_{max} = 0.25 \times 0.0285 = 0.0071$$

$$\rho_{min} = 0.0033$$

$$R_n = \frac{M_u}{\phi b d^2} \quad \rho = \frac{0.85 f'_c}{f_y} \left(1 - \sqrt{1 - \frac{4R_n}{1.7 f'_c}} \right)$$

SECTION A

$$R_n = \frac{(7.79 \text{ Ft.k})(12") (1,000 \text{ */k})}{(0.9)(12")(8.6875")^2} = 114.7$$

$$\rho = 0.0019 < \rho_{min} = 0.0033 \quad \text{ACI 10.5.2.} \quad 1.33 \times 0.0019 = 0.0026$$

$$A_{s \text{ req'd.}} = (0.0026)(12")(8.6875") = 0.271 \text{ in}^2/\text{ft OF WALL}$$

REQ'D. No. 5 BARS @ 13 1/2" O.C.

SECTION B

$$R_n = \frac{(26.21 \text{ Ft.k})(12") (1,000 \text{ */k})}{(0.9)(12")(16.625")^2} = 105.4$$

$$\rho = 0.0018 < \rho_{min} = 0.0033 \quad 1.33 \times 0.0018 = 0.0024$$

$$A_{s \text{ req'd.}} = (0.0024)(12")(16.625") = 0.479 \text{ in}^2/\text{ft OF WALL}$$

REQ'D. No. 6 BARS @ 11" O.C.

MATCH #5 + #6 BARS

USE #5 @ 11" TOP E.F.
#6 @ 11" BOTTOM E.F.

I-WALL DESIGN

Job No.
9388

Designed By:
R. CHOPIN

Date:
4/11/98

Checked By:

Page 6
of 6

SHEAR DESIGN :

SECTION A $V_u = 3.04^k$

$$\phi V_c = \phi 2 \sqrt{f'_c} b d = (0.85)(2) \sqrt{4,000} (12) (8.6875) = 11,208^{\#}$$

$$\phi V_c = 11.2^k > 3.04^k \quad \underline{\text{O.K.}}$$

SECTION B $V_u = 6.84^k$

BY INSPECTION $\phi V_c > V_u \quad \underline{\text{O.K.}}$

TEMPERATURE & SHRINKAGE REINFORCEMENT :

TOP 12" THICK WALL $A_{s_{TEMP}} = 0.0028 \times 12" \times 92" = 3.09 \text{ in}^2$

BOTTOM 1'-8" THICK WALL $A_{s_{TEMP}} = 0.0028 \times 20" \times 46" = 2.58 \text{ in}^2$

$$A_{s_{E.F. \text{ TOP}}} = \frac{3.09 \text{ in}^2}{2} = \underline{\underline{1.55 \text{ in}^2}}$$

$$A_{s_{E.F. \text{ BOTTOM}}} = \frac{2.58 \text{ in}^2}{2} = \underline{\underline{1.29 \text{ in}^2}}$$

VERTICAL STEEL #5 @ 11" TOP E.F.
#6 @ 11" BOT. E.F.

$f'_c = 4,000 \text{ PSI}$
 $f_y = 60,000 \text{ PSI}$

HORIZONTAL STEEL #4 @ 12" TOP E.F.
#5 @ 9" BOT. E.F.

WALL: 1'-0" TOP
1'-8" BOTTOM

COUSINS PUMPING
STATION COMPLEX

BURK-KLEINPETER, INC.
ENGINEERS, ARCHITECTS, PLANNERS, ENVIRONMENTAL SCIENTISTS
NEW ORLEANS, LA BATON ROUGE, LA TUSCALOOSA, AL

Job No.
9388

Designed By:
JUN

Date:
4/7/98

Checked By:

Page
of

CANTILEVER SHEET PILE WALL

MAX MOMENT = 102.3 K-FT FROM EUSTIS REPORT

$$S_{REQ'D} = \frac{102,300 \text{ * FT (12)}}{0.65 (50,000)}$$

$$S_{REQ'D} = 37.8 \text{ in}^3$$

DUE TO THE FACT THAT THIS WALL IS CANTILEVERED WITH SOIL ON ONE SIDE TO EL. 2.0 AND OPEN CANNEL ON THE OTHER TO EL. -9.0, WE WILL USE HOT-FORMED SHEET PILE RATHER THAN COLD ROLLED SHEETING DUE TO THE TIGHTER INTERLOCK.

USE ARBED AZ 26

$$W / S = 48.4 \text{ in}^3$$

OR CZ 141

$$W / S = 39.1 \text{ in}^3$$

AZ 26 HAS A WIDTH OF 16.81" → SHEET PILE WALL WILL BE CAPPED W/ CONCRETE. TO GET 6" CLEAR ON EACH SIDE OF CONCRETE, CAP SIZE WILL BE 2'-6" WIDE BY 2'-0" DEEP.

SHEET PILE WILL TAKE ALL LOADS - TEMP. + SHRINKAGE STEEL REQUIRED IN CAP

$$A_s = 0.002 (24)(30) = 1.44 \text{ in}^2$$

TEMP. SHRINK


USE 4 - #6 BARS

$$A_s = 1.77 \text{ in}^2$$

Job No. 9388	Designed By: JJN	Date: 4/7/98	Checked By:	Page of
-----------------	---------------------	-----------------	-------------	------------

PROTECTED SIDE

FLOOD SIDE



TYPICAL CANTILEVER SHEET PILE WALL
 SCALE: 1" = 1'-0"

DESIGN CALCULATIONS

CULVERT

CUT OFF WALL

	A	B	C	D	E	F	G	H	I	J	K	
1	COUSINS PUMP STATION DISCHARGE CULVERT										CEEC	
2	S-1	7.5 FOOT HULL			(UNDER THE LAPALCO BRIDGE)						C.E.E.C.	W J MOUTON
3	CLEAR CHANNEL OPENING:			107.00	FEET	WIDTH	WING WL.	WING WL.		REVISED:	17 NOV. 97	
4	CRITERIA:	LENGTH	W/CHAN	HULL	BAY 1-2	BAYS 2-12	BAY 12-13	HULL	HEIGHT	HT OF UNIT	17 MR 98	
5	CL DIMENSIONS	108.33	123.50	DEPTH	(1 BAY)	(10 BAYS)	(1 BAY)	DEPTH	AB. SILL		26 AU 98	
6	O.T.O. WALLS	108.83	124.00	7.50	7.58	10.83	7.58	7.50	20.50	28.00		
7	O.T.O. BASE	111.00	126.67	7.50	123.50			BUOY/FT:	AT.063 KCF	850.21		
8	HULL BOTTOM:		SILL	7.50			53.67	SILL/2		BUOY/FT.		
9	PANEL AND WEIGHT TAKE - OFF: HULL ONLY							10'-10" Bays		T R A N S V E R S E		
10	I T E M	LENGTH	WIDTH	THICKNESS	CU. FT.	NUMBER	UNIT WT.	WEIGHT	DRAFT	MOM ARM	MOMENT	
11	(Hull is separated from Wing Walls for Calculation Purposes)							KCF	K I P S	FEET	FEET	FT. KIPS
12	BOTTOM	111.00	126.67	8.00	9,373.36	1	0.122	1,144	1.35			
13	TOP: SILL	111.00	110.67	8.00	8,189.36	1	0.122	999	1.18			
14	PANELS (Vertical)	Width	Height	Thickness	Cubic Feet	Number	Unit Wt.	Weight				
15	1,2,12,13 /A to L	9.83	7.208	6.00	35.44	40	0.122	173	0.20			
16	3 to 11: A to L	9.83	7.208	5.00	29.53	90	0.122	324	0.38			
17	(Horizontal to page))											
18	A & L: 1-2, 12-13	6.58	7.208	6.00	23.73	4	0.122	22	0.03			
19	A & L: 2 THRU 12	6.58	7.208	6.00	23.73	20	0.122	58	0.07			
20												
21	B THRU K: 2 to 12:	9.83	7.208	6.00	35.44	90	0.122	389	0.46			
22	B Thru K: 1-2, 12-13	9.83	7.208	5.00	29.53	18	0.122	65	0.08			
23	Check <input type="checkbox"/> Panels:	(10 x 13) + (11 x 12) =			262.00	262				C.G.	WT/2 X	
24	Column Joints	1.67	7.21	22.00	22.07	143	0.122	385	0.45	FROM CL	C.G. ARM	
25							SUM:	3,559		-31.00	-55,162	
26											FT. KIPS	
27	20.5 FT WING WALL:		W I N G W A L L S:				cy:	1,080		4.19 FEET		
28	PANELS:	Width	Height	Thickness	Cubic Feet	Number	Unit Wt.	Weight	cu yds			
29	1-2, 11-12: A to L	9.83	20.00	6.00	98.33	40.00	0.122	479.87				
30	A and L: 1-2 12-13	6.58	20.00	6.00	65.83	4.00	0.122	32.13				
31	B thru K: 1-2, 12-13	6.58	20.00	5.00	54.86	18.00	0.122	120.47				
32			SUM OF WING WALL PANELS:				62.00				C.G.	WT/2 X
33	TOP OF WING WALL	108.83	8.08	6.00	439.87	2.00	0.122	107.33		FROM CL	C.G. ARM	
34	WING WALL JTS	1.67	20.00	22.00	61.23	44.00	0.122	328.70	1.26	-57.96	-30,964	
35		VOLUME CY:		Concrete:	Cubic Yds			1,068.50	DRAFT	NEW C.G.	SUM MOM	
36	HULL	3,748.70		cy ww:	324				5.44	-37.22	-86,126	
37	WING WALLS	1,335.90		cy hull	1,080			4,627.30	CL BUOY:	31.00		
38	SUM	5,084.60		sum cy	1,405					-6.22		
39								E C C E N T R I C I T Y:				
								HOGGING MOMENT: NO BALLAST:			-14,402	

	A	B	C	D	E	F	G	H	I	J	K
40	S-2	HOGGING MOMENT AND SOIL BEARING VALUES								WJM	26 AU 98
41					UNIT	WEIGHT	WT / 2	DRAFT	MOM ARM	MOMENT	
42					HULL	3,558.81	1,779.40	4.19	-31.00	-55,162	
43					WING WALL	1,068.50	534.25	1.26	-57.96	-30,964	
44					SUMS:	4,627	2,313.65	5.44	-37.22	-86,126	
45					BUOY:	4,627	2,313.65		31.00	71,723	
46					LAUNCHED HOGGING MOMENT : IN FT. KIPS:						-14,402
47					(Section Modulus, on Page 3): $Ft^3 =$						6,340
48		MOMENT DUE TO EXPOSED WING WALLS			LOW TIDE				FLOATING:	f top:	-0.19
49		WEIGHT	534	1.00	534	-57.96	-30,964				Ksi
50		BUOYANCY:	1,136	0.39	443	57.96	25,687			LAUNCHED:	
51						SUM M	-5,277	FT.KIPS	f top:	-0.07	
52		NO BALLAST WATER									Ksi
53		HOGGING MOMENT =			-14,402	LAUNCHED		FREEBOARD:	1.56	FEET	
54		FT. KIPS:				INSTALLED				RECHECK: SOIL BEARING	
55						DRAFT:	5.23 x .063 =	K/SQ.FT =			
56						1,207	cy x27 at .063 =	2,053		Kips	
57		WT IN AIR:			4,627	KIPS			WEIGHT	4,627	KIPS/AIR
58		CUBIC YDS CONCRETE: HULL ONLY:			1,080	CY. YDS			DISP-WT	2,574	KIPS
59		CU. YDS IN WW -9 TO -1.00 FT:			127	CY YDS			AREA	14,060	
60		SUM C.Y.			1,207	CY YDS					
61		SUBMERGED WEIGHT OF 1026 CY:			1,923	KIPS	AT				
62		WEIGHT OF EXPOSED WING WALLS:			450	KIPS	-1.00	LOW TIDE			
63		TOTAL LOAD ON SOIL			2,373	KIPS					
64		BOTTOM	HULL AREA:		14,060	SQ. FEET					
65			LOAD ON SOIL:		0.169	KSF		ADDITIONAL CHECK ON SOIL BEARING:			LBS:
66					169	PSF		WT/SF OF DISPLACEMENT:	5.25 x 63	342.88	
67								Equivalent thickness of SLWT Concrete: Feet:	330/122	2.81	
68								Submerged weight of 1 Cu Ft. SLWT: (Pounds)	122-63	59.00	
69								SUBMERGED WT OF 2.71 FT OF SLWT CONCRETE:		165.82	
70								AT - 1.00 LOW TIDE:		PSF	
71								PLUS ADD WEIGHT OF WING WALLS ABOVE - 1.00 LEVEL			
72					(20.5-8)/20.5 X	1,068	x63/122 =	336.44	/AREA =KSF	0.024	
73		SUMMARY							SOIL BEARING IN PSF:	189.75	
74		SOIL BEARING VARIES FROM			163	TO	184	PSF			
75											

	A	B	C	D	E	F	G	H	I	J	K
76	TRANSVERSE MOMENT OF INERTIA AND SECTION MODULUS OF HULL SECTION										26 AU 98
77	S-3 SECTION	LENGTH	WIDTH	THICK	NUMBER	AREA	CG.	A x CG	I	A d^2	Sum I
78		FEET	FEET	INCHES		SQ. FT.	BASE		bd^3/12		
79	BOTTOM	126.67	111.00	8.00	1.00	888.00	0.33	296.00	2.74	8,736.8	8,740
80	SILL	124.67	109.00	8.00	1.00	872.00	7.17	6,249.35	2.69	11,916.2	11,919
81											
82	WALLS - 6 IN	1.00	7.21	6.00	2.00	7.21	3.67	26.43	31.21	0.0	31
83	WALLS - 5 INCH	1.00	7.21	5.00	9.00	27.03	3.67	99.11	117.05	1.0	118
84					SUM AREA:	1,794	SUM	6,670.90		Sum I	20,808
85							Y' =	3.72		S top	6,340
86										S bottom	5,597
87									8 In Slab: S = 128 in^3		
88	TENSION STRESS IN HULL AT LAUNCHING:				AT SILL:		Σ Stresses	M Hogging:	w Hyd.	- M	-Mx12 / S
89	HOGGING MOMENT:			-14402	/ St =	-2.27	-0.19	-189	1.29	-5.00	-468.93
90				FT KIPS		KIPS/SF	KSI	PSI	20.5ft Hd	.033wL^2	Psi
91	STRESS HULL TO + 650 PSI										
92	AT LAUNCHING				MAXIMUM TENSION IN SILL:			-189	+	0	-189
93	INSTALLED:				MAXIMUM TENSION IN SILL:						-469
94	COMPRESSION STRESS IN HULL AT BOTTOM:								23 ft Hd	.025wL^2	
95	HOGGING MOMENT:			-14402	/ Sb =	2.57	0.21	214	1.44		134.77
96				FT KIPS		KIPS/SF	KSI	PSI			Psi
97											
98					BOTTOM:			214	+	135	349
99											PSI
100	PRE STRESSING IN HULL BOTTOM :										
101	1/2" Ø 270 K STRAND AT 12 INCHES ON CENTERS AT BOTTOM POURS 1 AND 2:								PRESTRESS =		0.52
102											KSI
103	PRESTRESSING IN SILL:										
104	1/2" Ø 270 K STRAND AT 6 IN. LW IN TOPPING								PRESTRESS =		0.52
105	AND AT 12 IN. SW IN TOPPING OVER PRESTRESSED PLANKS								PRESTRESS =		0.26
106									PSI		KSI
107	MINIMUM COMPRESSION IN SILL DURING LAUNCHING & FLOATING:										
108									520.83	PSI P/S	
109	MINIMUM COMPRESSION				HOGGING	AT SILL:			-468.93	PSI TENSION	
110	TO IN HULL WHEN INSTALLED:				MOMENT	f top	P/s	Residual		PSI COMPRESSION	
111					(INSTALLED)	-5,277	-0.069	0.521	0.451	451	PRE-STRESS
112									PSI		
113											
114											
115											

	L	M	N	O	P	Q	R	S	T	U	V	W	
1	S-4	COUEENS PUMP STATION DISCHARGE CULVERT										26 AU 98	CNEC
2	7.50' HULL+20.5' WW	LOAD CASE I				LOAD CASE II				LOAD CASE III			
3	LOAD CASE :	LAUNCHING	Σ Moment CL Hull		-1.0 ELEV	LOW TIDE		+11.5 ELEV FLOOD		TIDE			
4	WATER ON SILL	0.00			8.00	8.00		20.50	20.50				
5	WATER TABLE	0.00			0.00	0.00		0.00	0.00				
6	HULL WEIGHT/2	1,779.40			1,779.40	0.00		1,779.40	1,779.40				
7	VOLUME CY/2	1,874.35			1,874.35	120.56		1,874.35	1,874.35				
8	CONC VOLUME/2	540.20			540.20	540.20		540.20	540.20				
9	WW WEIGHT 1 SIDE	534.25			534.25	534.25		534.25	534.25				
10	VOLUME W W CY/2	667.95			667.95	37.11		667.95	667.95				
11	CONCRETE WW CY/FT	162.19			162.19	7.91		162.19	162.19				
12	HULL MOM ARM	-31.00			-31.00	-31.00		-31.00	-31.00				
13	WW MOMENT ARM	-57.96			-57.96	-57.96		-57.96	-57.96				
14	SUM MOMENTS CL	WEIGHTS	MOM ARM	MOMENTS	WEIGHTS	MOM ARM	MOMENTS	WEIGHTS	MOM ARM	MOMENTS			
15	HULL	1,779.40	-31.00	-55,162	1,779	-31.00	-55,162	1,779	-31.00	-55,162			
16	WING WALL	534.25	-57.96	-30,964	534	-57.96	-30,964	534	-57.96	-30,964			
17	HULL BALLAST	0.00		0	2,269	-31.00	-70,351	2,269	-31.00	-70,351			
18	W W BALLAST + Hd	0.00		0	336	-57.96	-19,458	860	-57.96	-49,861			
19	SUM HOGG SUM V:	-2,314	HOG M:	-86,126	-4,919	HOG M:	-175,935	-5,443				-206,338	
20													
21	HULL BUOYANCY/2	2,314	31.00	71,723	3,188	31.00	98,836	3,188	31.00	98,836			
22	WW BUOY AT + HD	0.00		0	443	57.96	25,687	1,136	57.96	65,824			
23	SUM: SAGG SUM V:	0.00	SAG. M:	71,723	3,631	SAG. M:	124,524	4,324	SAG M.:	164,660			
24	REMAINING SOIL BEAR	0.00			1,287	31.00	39,906	1,119	31	34,700			
25	TOTALS	0.00	HOG M:	-14,402		SAG. M:	164,430					199,361	
26	DRAFT: FEET:	5.44											
27	SUMS: V =		HOG M:	-14,402	1,287	TENSION	-11,505	1,119	TENSION	-6,978			
28	SOIL BEARING		P/A SOIL:		0.191	Ft. Kips		0.166	Ft. Kips				
29	SECTION MODULUS		St FT^3:	6,340		St FT^3	5,597		St FT^3	5,597			
30	TENSION AT SILL		TENSION:	-0.189 KSI		TENSION	-0.171 KSI		TENSION	-0.104			
31			SILL			SILL			SILL				
32	SOIL BEARING Σ V:				1,287	Σ V		1,119	Σ V				
33													
34													
35													
36													
37													
38													
39	FINAL SOIL BEARING:	0.00	Floating		191	Soil Bearing Psf		166	Soil Bearing Psf				

	L	M	N	O	P	Q	R	S	T	U	V	W	
40	S - 5	FLOATAION FACTOR OF SAFETY										CREC	
41	Sff =	$Ws + Wc + S / (U - Wg)$										WJM	
42		SE F BASED ON HYDRAULIC PRESSURES										26 AU 98	
43													
44	Ws	Weight of Structure, Complete					4,627	Kips	Flood Tide			4,627	Kips
45		(+ Wt. of Conc. & Soil Above Hull Extension)					475	Kips				475	Kips
46	Wc	Ballast Water		(Low Tide)	Elev-1.00	5,210	Kips	El.+ 11.5			6,259	Kips	
47	S	Surcharge Loads					0					0	
48	U	Uplift Forces acting on Base of Structure					12,753	Kips	(27.5'Hd)			23,381	Kips
49	Wg	Weight of Water above Top surface					5,997	Kips	(20.5'Hd)			15,368	Kips
50		(Totally controlled by Gravity Flow)											
51													
52		Floataion Factor of Safety Sff =					S F f:	1.53			S F f:	1.42	
53													
54		SE F BASED ON BUOYANCY											
55													
56	Ws	Weight of Structure, Complete					4,627	Kips	Flood Tide			4,627	Kips
57		(+ Wt. of Conc. & Soil Above Hull Extension)					475	Kips				475	Kips
58	Wc	Ballast Water		(Low Tide)	Elev-1.00	5,210	Kips	El.+ 11.5			6,259	Kips	
59	S	Surcharge Loads					0					0	
60	U	Uplift Forces HULL + WW BUOYANCY:					7,263	Kips	(27.5'Hd)			8,648	Kips
61	Wg	Weight of Water above Top surface					0	Kips	(20.5'Hd)			0	Kips
62		(Controlled by Gravity Flow)											
63													
64		Floataion Factor of Safety Sff =					S F f:	1.42	> 1.30		S F f:	1.31	> 1.30
65													
66													
67													
68													
69													
70													
71													
72													
73													
74													
75													

	X	Y	Z	AA	AB	AC	AD	AE	AF
1	LAPALCO CULVERT: PILE SUPPORTED ALTERNATE:							C.E.E.C.	S-6
2	PRELIMINARY ANALYSIS:								WJM
3	LENGTH OF CULVERT PARALLEL TO CHANNEL:					108.33	FEET		21 JULY 98
4	WIDTH OF LAPALCO BRIDGE OVERHEAD:					68.00	FEET		4 AUG 98
5	DIFFERENCE:					40.33	FEET		26 AU 98
6	CLEARANCE BELOW EACH SIDE:					20.16	FEET		
7									
8	PILE CAISSON LOCATION FROM CENTERLINE:					40.50	FEET		
9	CLEARANCE BELOW EACH SIDE:					6.50	FEET		
10									
11	CULVERT LOADING ON SOIL:								
12	MAX P/A: SOIL BEARING:					-0.20	KSF		
13	CONTRIBUTORY WIDTH OF ONE PILE/SPACING:					10.83	FEET		
14	UNIT LOAD BETWEEN CAISSONS:					2.17	K/ FT		
15									
16	CENTERLINE SPAN BETWEEN CAISSONS:					81.00	FEET		
17	POSITIVE MOMENT AT CENTER OF SPAN: WL ² /8:					1,776.94	FT. KIPS		
18	NEGATIVE MOMENT OF 13.67 FT. CANTILEVERS:					-192.52	FT. KIPS		
19	MAXIMUM MOMENT AT CL SPAN					1,584.42	FT. KIPS	(PER 10.833 FOOT BAY)	
20									
21	PROPERTIES OF ONE-CELL WIDE SECTION					7.50	FT. DEPTH		
22	UNIT	THICKNESS	WIDTH/HT.	AREA	M OF INERTIA	Ad ²	Σ M+Ad ²		
23	TOP	8.00	130.00	1,040.00	5,547	1,748,240	1,753,787		
24	BOTTOM	8.00	130.00	1,040.00	5,547	1,748,240	1,753,787		
25	WALL	6.00	74.00	444.00	202,612	0	202,612		
26								Σ I:	3,710,185
27								Sect. Mod:	82,449 In ³
28									
29	STRESS IN HULL AT CENTERLINE:								
30	f = Mx12/S	1,584.42	x	12.00	/	82,449	=	0.231	
31	(STRESS HULL TO 500 PSI: 1/2" Ø 270 K SR STRANDS AT 6 INCHES ON CENTERS)								KSI
32									
33	LOAD ON 24 INCH DIAMETER CAISSONS IN 30 INCH SLEEVES:								
34									
35	2.17					x	108.33/2 =	117.36	Kips
36								58.68	Tons
37	USE: 24 INCH Ø CAISSONS, CONCRETE FILLED X 30 FT. LENGTH 80 FEET								
38	2.4 REQUIRED:								
39	DESIGN LOAD: 60 TONS								
	(NO DEWATERING REQUIRED)								

	X	Y	Z	AA	AB	AC	AD	AE	AF	
40				LAPALCO CULVERT; PILE SUPPORTED ALTERNATE:						S-7
41				DEWATERING SCENARIO WATER BALLAST						WJM
42				WITH WATER BALLAST:						4 AUG 98
43				LOAD ON SOIL WITH HULL FULLY BALLASTED:		184.00		PSF	26 AU 98	
44				UPLIFT HEAD:	11.50	UPLIFT:	-724.50	PSF	AT 63 PCF	
45						SUM UPLIFT:	-540.50	PSF		
46				AREA AFFECTED BY DEWATERING/UPLIFT:		11,456.80		SQ. FEET		
47				SUM OF UPLIFT FORCE:		-6,192.40		KIPS		
48				DIVIDED BY 24 PILES:		-258.02		KIPS		
49						-129.01		TONS		
50										
51				PILE REQUIREMENT: 24 - 36 INCH DIAMETER PILES X				115.00		
52										
53				UPLIFT UNIT FORCE ON 10 FT. SEGMENT:		-540.50				
54					C. WIDTH	10.83		MOMENT:		
55				UNIT LOAD: UPLIFT:		-5.86		KIPS/FT.	MOMENTS:	
56				EQUIVALENT SPAN:		81.00		FEET	-4,802.17	
57				CANTILEVER:		13.67		FEET	1,846.07	
58								Σ MOMENT:	-2,956.10	
59				1-CELL	SECTION MODULUS			AE-27 :	82,448.56	
60					MAX STRESS:				-0.430 KSI	
61					SHEAR:				-237.14	
62					SHEARING STRESS IN WEB::				-0.44 KSI 6 IN	
63									-0.33 KSI 8 IN.	
64				SUMMARY:	HULL DEPTH: 7.50 FEET					
65				1	PROVIDE 24 - 36" Ø PILES x 115 FEET IN 42 INCH SLEEVES					
66				2	PRESTRESS HULL AND WEBS TO 750 PSI					
67				3	INCREASE VERTICAL WALL PANELS LW TO 8 INCH THICKNESS					
68										
69										
70										
71										
72										
73										
74										
75										

	X	Y	Z	AA	AB	AC	AD	AE	AF
76									S-8
77									WJM
78									4 AUG 98
79									26 AU 98
80									
81						184.00	PSF		
82						461.74	PSF		
83						645.74			
84									
85									
86									
87									
88									
89									
90									
91									
92									
93									
94									
95									
96									
97									
98									
99									
100									
101									
102									
103									
104									
105									
106									
107									
108									
109									
110									
111									
112									
113									
114									
115									

10.5 MG PUMP STATION DISCHARGE CULVERT

CALCULATE HORIZONTAL FORCE DUE TO 6.0 FPS FLOW-FRICTION:

C.E.E.C
W J M
14 JULY 98

COEFFICIENT OF DRAG: TROWELED CONCRETE SURFACE:

REYNOLDS No. $Re = 111 \times 6 \times 1.935 / (.01 / 479) = 6.17e+7$
 Cd Steel: 0.036 (Fundamentals of Fluid Mechanics, Streeter, 4th Edition)
 Cd Concrete: Cd Steel x 1.20 = 0.043

A R E A:		A R E A :	
BOTTOM: 111.00	X	126.67	14,060
SIDES: 2 x 111.00	X	18.00	3,996

Σ AREA : 18,056 Sq. Feet

DRAG: $Cd \times p/2 \times A \times V^2$
 0.043 $\times 1.935/2 \times 18,056 \times 6^2 = 27,169$ POUNDS

R E S I S T A N C E:

BOTTOM FRICTION:

178 PSF Bearing Pressure x Cf 0.5 = PSF: 89.00

$111 \times 126.67 \times 89.00^{**}$ psf Cohesion: 1,251,373 POUNDS **** Geotechnical Recommendation**

SIDE FRICTION: LAND SIDE:

$111 \times 16 \times 125$ PSF 222,000

SIDE FRICTION: CANAL SIDE:

$111 \times 7 \times 60$ PSF: 4,620

PASSIVE PRESSURE, ONE SIDE:

$126.67 \times 7 \times 332^{**}$ PSF Average: 294,381

SUM OF RESISTANCE: 1,772,374

FACTOR OF SAFETY AGAINST HORIZONTAL MOVEMENT: **F.S.:**

$1,772,374 / 27,169 = 65.24$

RESISTANCE / H. FORCE




Fig. 5.17 The drag law for smooth plates.

is valid for a range

$$5 \times 10^5 < R_t < 10^7$$

Experiment shows that the drag is slightly higher than is predicted by Eq. (5.6.16).

$$C_D = 0.074 R_t^{-1/2} \quad (5.6.17)$$

The boundary layer is actually laminar along the upstream part of the plate. Prandtl has subtracted the laminar portion, producing the equation

$$C_D = 0.074 R_t^{-1/2} - \frac{1700}{R_t} \quad 5 \times 10^5 < R_t < 10^7 \quad (5.6.18)$$

In Fig. 5.17 a log-log plot of C_D vs. R_t shows the trend of the drag coefficients.

Use of the logarithmic velocity distribution for pipes produces

$$C_D = \frac{0.455}{(\log_{10} R_t)^{2.58}} \quad 10^6 < R_t < 10^9 \quad (5.6.19)$$

in which the constant term has been selected for best agreement with experimental results.

Example 5.6 A smooth, flat plate 10 ft wide and 100 ft long is towed through still water at 68°F with a speed of 20 ft/sec. Determine the drag on one side of the plate and the drag on the first 10 ft of the plate.

† L. Prandtl, Über den Reibungswiderstand strömender Luft, *Results Aerodynamic Test Inst., Göttingen*, III Lieferung, 1927.

For the whole plate

$$R_t = \frac{100 \times 20 \times 1.935}{0.01/479} = 1.85 \times 10^6$$

From Eq. (5.6.19)

$$C_D = \frac{0.455}{[\log_{10}(1.85 \times 10^6)]^{2.58}} = \frac{0.455}{(8.2675)^{2.58}} = 0.00196$$

The drag on one side is

$$\text{Drag} = C_D b l \frac{\rho U^2}{2} = 0.00196 \times 10 \times 100 \times \frac{1.935}{2} \times (20)^2 = 760 \text{ lb}$$

in which b is the plate width. If the critical Reynolds number occurs at 5 the length l_c to the transition is

$$\frac{l_c \times 20 \times 1.935}{0.01/479} = 5 \times 10^5 \quad l_c = 0.27 \text{ ft}$$

For the first 10 ft of the plate, $R_t = 1.85 \times 10^5$, $C_D = 0.00274$, and


$$\text{Drag} = 0.00274 \times 10 \times 10 \times \frac{1.935}{2} \times (20)^2 = 106 \text{ lb}$$

Calculation of the turbulent boundary layer over rough plates proceeds in similar fashion, starting with the rough-pipe tests using sand roughness. At the upstream end of the flat plate, the flow may be laminar; then the turbulent boundary layer where the boundary layer is still thin the ratio of roughness height to boundary-layer thickness ϵ/δ is significant; the region of fully developed roughness occurs, and the drag is proportional to the square of the velocity. For long plates, this region is followed by a transition region where ϵ/δ becomes increasingly smaller, and even the plate becomes hydraulically smooth, i.e., the loss would not be reduced by reducing the roughness. Prandtl and Schlichting[†] have carried through these calculations, which are too complicated for reproduction here.

Separation.

Along a flat plate the boundary layer continues to grow in the downstream direction, regardless of the length of the plate, when the pressure gradient remains a cone. With the pressure decreasing in the downstream direction in a conical reducing section, the boundary layer tends to reduce thickness.

† L. Prandtl and H. Schlichting, Das Widerstandsgesetz rauher Platten, *Recherch. Hafen*, p. 1, 1934. See also *NACA Tech. Mem.* 1218, part II.



Tie Rods
 Tension
 = 3.75(12)
 = 45 k
 2" dia
 GR. 40
 Allowable =
 2.5(24)(2)
 = 50 k ok

Water Beam
 2-12 Channel
 @ 20.7 #/l'
 M = 3.75(12)²/10
 = 54 k
 Stress =
 54(12) / 24(2) = 13.5
 Section =
 = 21.5 > 13.5 ok

$$Z_{top} = -12.86(7) + 6.05(53) + 6.84(10) = -51.44 + 321.26 + 68.4 = 338.22$$

$$Z_{bot} = -12.86(7) + 6.05(53) + 6.84(10) = -51.44 + 321.26 + 68.4 = 338.22$$

P.C. @ 20' 0"
 M @ -12' 0" = 3.75(12) - 4(3.02) = 45 - 12.08 = 32.92
 M @ -14' 0" = 48.12

Pressure

Piles ≈ 40' Standard
 $S_r = 24 \times 3 / 100$ USE PLZ-23 $S = 30.2 \times 3 / 100$
 x 40' = 0

DESIGN CALCULATIONS

CLOSURE WALL

$$\text{MAX MOMENT} = 836 \text{ k}$$

$$\text{SCALED DEFLECTION} = 5.44 \times 10^{12}$$

TRY w/ 66" PILE:

$$\text{DEFLECTION} : \Delta = (\text{SCALED DEFLECTION}) / EI$$

$$E = 4,45,200 \text{ psi}$$

$$I = 93,454 \text{ in}^4 / \text{FT WALL}$$

$$\Delta = (5.44 \times 10^{12}) / (4415200)(93454)$$

$$\Delta = 13.18'' \quad \text{N.G.}$$

TRY 72" PILE

$$I = 683,000 \text{ in}^4 / 6.0 = \frac{113,833}{147,166} \text{ in}^4 / \text{FT WALL}$$

$$\Delta = (5.44 \times 10^{12}) / (4415200) \left(\frac{113,833}{147,166} \right)$$

$$\Delta = 8.37'' \quad 10.82'' \quad \text{N.G.}$$

TRY 78" PILE

$$I = 940,700 / 6.5 = 144,723 \text{ in}^4 / \text{FT WALL}$$

$$\Delta = 5.44 \times 10^{12} / 4415200 (144723)$$

$$\Delta = 8.51''$$

TRY 84" PILE

$$I = 1,265,300 / 7.0 = 180,757 \text{ in}^4 / \text{FT WALL}$$

$$\Delta = 5.44 \times 10^{12} / 4415200 (180757)$$

$$\Delta = 6.82'' \quad \underline{\underline{OK}}$$

ALLOWABLE STRESS DESIGN: TRY $\phi 184''$

$$\text{MAX MOMENT} = 836 \text{ k}$$

$$- \text{DIVIDE OVER 2 ROWS OF PILES} = 418 \text{ k}$$

$$\text{ALLOWABLES: } f_a + f_b + f_{pc} \leq 0.9 \times 4.5 f_c' \\ \leq 2430 \text{ psi } \quad C$$

$$f_a - f_b + f_{pc} \geq 0 \quad T$$

AXIAL LOAD DUE TO CAP:

$$\text{wt per ft wall} = (15)(4)(.150) = 9 \text{ k/FT WALL}$$

$$\text{over 2 piles} = 4.5 \text{ k/FT WALL} \cdot \text{PILE}$$

$$\text{FOR 7': } P = (4.5 \text{ k/ft})(7') = 31.5 \text{ k}$$

$$f_a = \frac{P}{A} = \frac{31.5}{1693 \text{ in}^2} = 0.0186 \text{ ksi}$$

$$f_b = \frac{M}{S} = \frac{(418)(12)(7)}{30,130} = 1.165 \text{ ksi}$$

$$f_{pc} = \frac{F_{pc}}{A_c} \quad \text{- solve for } F_{pc} \text{ req'd}$$

$$C: 0.019 + 1.17 + f_{pc} \leq 2.43$$

$$1.189 + f_{pc} \leq 2.43$$

$$f_{pc} \leq 1.241 \text{ ksi}$$

$$T: 0.019 - 1.17 + f_{pc} \geq 0$$

$$-1.151 + f_{pc} \geq 0$$

$$f_{pc} \geq 1.15 \text{ ksi}$$

$$1.15 \leq F_{pc} \leq 1.24$$

$$1.15 \leq \frac{F_{pc}}{1693} \leq 1.24$$

$$1947 \text{ k} \leq F_{pc} \leq 2099 \text{ k}$$

$$F_{pc} = \frac{F_{pc}}{A} \quad A = 1693 \text{ in}^2$$

- using prestressing cable consisting of 2 - $\frac{1}{2}$ " ϕ 270 ksi 7-wire strands
of initial tension of 57820 lbs and effective tension of
49,150 lbs :

- each cable gives $F_{pc} = 49^k$


$$\text{- need } \frac{1947}{49} \leq \# \text{ cables} \leq \frac{2099}{49}$$

$$39.7 \leq \# \text{ cables} \leq 42.84$$

- use 41 cables


- use 84" ϕ Piles

13-782 500 SHEET, FILLER, 5 SQUARE
42-381 50 SHEETS, 1/2" EAS, 5 SQUARE
42-382 100 SHEETS, 1/2" EAS, 5 SQUARE
42-383 200 SHEETS, 1/2" EAS, 5 SQUARE
42-384 400 SHEETS, 1/2" EAS, 5 SQUARE
42-385 800 SHEETS, 1/2" EAS, 5 SQUARE
42-386 100 RECYCLED WHITE, 5 SQUARE
42-388 200 RECYCLED WHITE, 5 SQUARE
Made in U.S.A.



P/S

P/S



EL. ~~9.5~~

Δ SWL = $\frac{7.5}{7.5}$

EL. ~~9.5~~
5.5

4'-0"

- 500 SHEETS, FILLER 3 SQUARE
- 100 SHEETS, FILLER 2 SQUARE
- 100 SHEETS, FILLER 1 SQUARE
- 100 SHEETS, FILLER 1/2 SQUARE
- 200 SHEETS, FILLER 1/4 SQUARE
- 100 SHEETS, FILLER 1/8 SQUARE
- 200 SHEETS, FILLER 1/16 SQUARE
- 100 SHEETS, FILLER 1/32 SQUARE
- 200 SHEETS, FILLER 1/64 SQUARE



66" Ø CYLINDER
PILE, FILL
W/ SAND

24" CONCRETE
SHEETPILE

EL. -11.0
METE



TIP EL. -85.0



EUSTIS ENGINEERING COMPANY, INC.

GEOTECHNICAL ENGINEERS
CONSTRUCTION QUALITY CONTROL AND MATERIALS TESTING
3111 26th Street • Metairie, Louisiana 70002 • 504 834-0157

FACSIMILE TRANSMISSION

Date: 8/17/98

NAME	COMPANY/ ORGANIZATION	FAX NUMBER
Ms April Hurry	DEI	

From: Tom Stremelan

Fax Number: (504) 834-0354

Total Number of Pages Transmitted (Excluding Cover Sheet): 2

Comments: Preliminary Reevaluation of
cantilevered Diversion Wall

AT

MEMO

TO: DESIGN ENGINEERING

ATTENTION: MS APRIL HURRY

FROM: TOM STREMLAU

EUSTIS ENGINEERING

SUBJECT: CANTILEVERED DIVERSION WALL


WEST JEFFERSON LEVEE DISTRICT

COUSINS PUMP STATION TO FIRST AVE CANAL

HARVEY, LA.

I HAVE REEVALUATED THE DIVERSION WALL ASSUMING NO ADHESION TO THE WALL WHICH IS THE BASIC CURRENT DIRECTION BY THE CORPS OF ENG. THE PRELIMINARY RESULTS ARE ENCLOSED. REQUIRED PENETRATION FOR THE CUTOFF SHEETPILES IS ALSO GIVEN ON THE ENCLUSURE.

Elevation in Feet (NGVD)



Flood Side Water Elevation	Protected Side Water Elevation	Safety Factor	Maximum Moment ft Kips	Wall Bottom Elevation	Scaled Deflection 16 in ³ at El. 12
9.5	-1.0	1.5	836	-10.9	5.44×10^{12}
11.5	-1.0	1.0	772	-18.5	3.7×10^{12}

- Note: 1) Divide scaled deflection by modulus of elasticity in PSI times concrete pipe wall moment of inertia to obtain deflection in inches.
 2) Boring B soil parameters were used for these analyses except all the sand from elevation -6.5 to -26.5 was assumed to have an angle of internal friction of 30°.
 3) The steel sheetpiles will provide seepage cutoff. They should extend to elevation -27.5 to provide a factor of safety of 4 against piping using the Harr Method.
 4) Adhesion has been assumed to be zero.

Cantilevered Discharge Canal Wall
 West Jefferson Levee District
 Cousine Pumping Station to First Ave Canal
 Harvey, La.


11/15/59
 DIETZEN ENGINEERING
 1370 1/2 ST. CHARLES
 NEW ORLEANS, LA.

RECEIVED

MAR 23 1998

GULF COAST PRE-STRESS, INC.

DRAWER D - PASS CHRISTIAN, MS. 39571 - Phone (601)452-9486 - FAX (601)452-9495



FAX COVER SHEET

TO: DESIGN ENGINEERING FAX # _____

ATTENTION: APRIL HADDY

FROM: DON TIEGEL

DATE: 3-23-98

TOTAL PAGES (INCLUDING COVER SHEET) 4

COMMENTS: _____

Hard copy _____ will _____ will not be mailed.

FILE _____
DISTRIBUTION _____

If you do not receive all pages, please contact us at 601-452-9486. Thank you.




ENGINEERING DESIGN DATA

The structural design of a Raymond Cylinder Pile is governed by the external loads acting on the pile and the desired factor of safety.

Generally Cylinder Piles are used for marine structures or dry-land trestles. The piles therefore extend above ground — sometimes to considerable heights and are designed to resist a combination of axial loads and bending moments.

These engineering data provide the basic principles and procedures for a satisfactory structural design. It should be noted that the actual pile bearing capacity generally depends upon the subsoil conditions.



CYLINDER PILE DESIGN PROPERTIES

SIZE			A _c	I	S	r	CIRCUM-FERENCE	POINT AREA	WEIGHT PER FOOT ①	STRESS ON CONCRETE DUE TO EFFECTIVE STRESS PER CABLE ②	
O.D. #	I.D.	w								in. ²	in. ⁴
in.	in.	in.								lb/in. ²	lb/in. ²
36	27	4½	445	58,360	3,130	11.3	9.43	7.07	479	116	1105
36	28	5	487	60,000	3,330	11.1	9.43	7.07	524	106	1009
42	32	5	581	101,300	4,820	13.2	11.00	9.61	625	89	840
48	38	5	875	158,200	6,590	15.3	12.57	12.57	726	76	720
54	44	5	770	233,400	8,840	17.4	14.14	15.90	829	67	630
54	42	6	905	264,600	9,800	17.1	14.14	15.90	973	57	543
60	49	5½	942	353,200	11,770	19.4	15.71	19.63	1014	54	522
66	54	6	1131	514,000	15,580	21.3	17.28	23.76	1217	45	435
72	60	6	1244	683,000	18,970	23.4	18.85	28.27	1339	41	395
78	65	6½	1460	940,700	24,120	25.4	20.42	33.18	1572	35	337
84	70	7	1693	1,265,300	30,130	27.3	21.99	38.48	1823	31	290
90	76	7	1825	1,582,900	35,180	29.5	23.56	44.18	1964	28	269

* STANDARD SIZES

NOTES:

① The tabulated weights, intended for design purposes, are based on a unit weight of concrete of 155 lbs/ft³ and the nominal wall thicknesses. For handling purposes, allowance should be made for manufacturing tolerance in extra wall thickness with corresponding increase in weight per foot.

② Number of prestressing cables ranges from 8 to 16 for 36" piles, 12 to 24

for 54" piles, and 16 to 32 for 66" piles.




③ Each prestressing cable consists of twelve 0.192" -diameter stress-relieved wires with initial stress of 175,000 psi (60,801 lbs) and effective stress of 148,750 psi (51,681 lbs).

④ Each prestressing cable consists of two ¼" -diameter 270 ksi 7-wire strands with initial tension of 57,820 lbs and effective tension of 49,150 lbs.

**INTERACTION DIAGRAMS FOR RAYMOND PRESTRESSED CONCRETE CYLINDER PILES
STRESS DESIGN**

The interaction diagrams are based on the following design criteria:

1. For permanent loading:
compression:
 $f_a + f_b + f_{pc} \leq 0.9 \times 0.45 f'_c$
tension:
 $f_a - f_b + f_{pc} \geq 0$
*Reflects a 10% reduction for marine structures
2. For temporary loading:
compression:
 $f_a + f_b + f_{pc} \leq 0.9 \times 0.60 f'_c$
tension:
 $f_a - f_b + f_{pc} \leq 0.9 \times 6\sqrt{f'_c}$
*Reflects a 10% reduction for marine structures
3. Eccentricity factor of ten per cent for axial load.
 $M_e = 0.10 D \times P$
4. $f'_c = 7000$ psi
5. Prestressing cables = two 1/2" diameter 270k 7-wire strands each. (Note diagrams slightly conservative but applicable for 12-wire cables).
6. Prestressing force = force resulting from effective tension of 49,150 lbs per cable.



NOTE: Permanent load is load of relatively prolonged duration. Temporary load is permanent load plus loads of short or intermittent duration such as wind, wave, and ship impact.

GENERAL DESIGN NOTES

1. Most cylinder piles are designed for combined axial load and bending.

2. For routine loadings, the pile can generally be designed using stress design (see interaction diagrams page 25). However under extreme loading conditions such as those resulting from a 100-year probability storm (wind, wave and current) or seismic action, strength design analysis must be used to determine the adequacy of the structural strength under such forces. For checking ultimate bending capacities, the following table gives the ultimate bending strengths for various size cylinder piles. Interaction diagrams of ultimate axial load vs ultimate bending moment can be developed using any recognized method of analysis.

CALCULATED ULTIMATE BENDING STRENGTHS

PILE SIZE		NUMBER OF CABLES (a)	ULTIMATE BENDING STRENGTH (b)
O.D. in.	WALL in.		
36	5	16	1400
54	5	24	3400
66	6	32	5500

- (a) Each cable consists of two 1/2" diameter 7-wire strands.
- (b) For lesser number of cables adjust ultimate bending strength proportionally

3. The interaction diagrams (page 25) show that the combined axial and bending load capacity of the pile is generally reduced as the number of prestressing cables is increased.
4. If the strength design method requires a greater number of cables than that required by the stress design method for a given size pile, that size pile with the greater number of cables can be used by stressing each cable to less than the normal tension of 49,150 lbs. so that the total prestressing force is equal to that which would be produced by the lesser number of cables (required by the stress method) stressed to the normal tension. In this way the required minimum safety factor for ultimate loads can be achieved without exceeding the maximum allowable stress.
5. The allowable stress resulting from the external loads is:
 $F_c + F_b = 0.9 \times 0.45 f'_c - f_{pe}$
 *Reflects 10% reduction for marine structures
6. For slenderness ratios l/N greater than 30 and up to 120, apply a reduction factor R to the allowable stress resulting from the external loads.
 $R = 1.24 - 0.008 l/N$


The effective pile length is related to the unsupported length (between points of fixity or hinges) depending upon head and end conditions.

For slenderness ratios exceeding 120, the pile should be investigated for elastic stability using a recognized method of analysis.

7. For cases where $\frac{l_e}{l_u + l_b} \leq 0.1$

the reduction factor R is applied to F_c only:

$$F_c = R (0.9 \times 0.45 f'_c - f_{pe} - f_b)$$



NOTATION

- A_c = area of concrete (including prestressing steel)
- D = outside diameter of pile
- F_a = allowable stress due to axial external load
- F_b = allowable stress due to bending moment
- F_{pe} = total force resulting from effective prestress
- f_a = $\frac{P}{A_c}$ = actual stress due to axial external load
- f_b = $\frac{M}{S}$ = actual stress due to bending moment
- f_{pe} = $\frac{F_{pe}}{A_c}$ = effective prestress
- f'_c = specified 28-day compressive strength of concrete
- I = moment of inertia
- L = unsupported pile length
- l_e = effective pile length
- M = total bending moment
- M_a = bending moment due to eccentric axial load
- P = axial external load
- R = reduction factor
- r = radius of gyration
- S = section modulus

DESIGN EXAMPLE

Consider a trestle bent consisting of two vertical Cylinder Piles rigidly connected a pile cap (see sketch)

Given:
 The vertical and horizontal forces acting on the bent produce the following axial load and bending moment on each pile:

$P = 200$ tons
 $M = 700$ kip-feet

Solution:

An examination of the interaction diagrams (page 25) indicates that a 12-cabl. 54" O.D. x 5" wall pile would satisfy the combined loading requirements.

Pile properties: (page 24)

$A_c = 770$ in.²
 $S = 8640$ in.³
 $r = 17.4$ in.
 $l_w = 12 \times 63.8 = 766$ psi
 $f'_c = 7000$ psi

CASE I: Assume $l_e = 0.5L = 40$ ft

$$\frac{l_e}{r} = \frac{40 \times 12}{17.4} = 27.6$$

No reduction required: $l/N \leq 30$

Allowable compression stress due to external loading without reduction:

$$F_c + F_b = 0.9 \times 0.45 f'_c - f_{pe} = 2835 - 766 = 2069 \text{ psi}$$

Actual compression stress due to external loading:

$$f_c + f_b = \frac{P}{A_c} + \frac{M}{S} = \frac{200 \times 2000}{770} + \frac{700 \times 12,000}{8640} = 519 + 972 = 1491 \text{ psi} \leq 2069 \text{ psi OK}$$

Case II: Assume $l_e = 0.7L = 56$ ft

$$\frac{l_e}{r} = \frac{56 \times 12}{17.4} = 38.6$$

Reduction required: $\frac{l_e}{r} > 30$

Reduction factor:

$$R = 1.24 - 0.008 l/N = 1.24 - 0.008 \times 38.6 = 0.93$$

Allowable compression stress due to external loading with reduction:

$$F_c + F_b = R (0.9 \times 0.45 f'_c - f_{pe}) = 0.93 (2835 - 766) = 1924 \text{ psi}$$

Actual compression stress due to external loading:

$$f_c + f_b = 1491 \text{ psi} \leq 1924 \text{ psi OK}$$

- check $w/w = 400 \neq 187$

$$M = (8)(.4)(130)^2 = 845'k$$

$$S_{req'd} = 845(12) / (1.8) = 512 \text{ in}^3$$

- use W30 x 173

13-82 50 SHEETS FILER 5 SQUARE
 42-81 60 SHEETS 5/8" X 5/8" 5 SQUARE
 42-82 100 SHEETS 5/8" X 5/8" 5 SQUARE
 42-83 100 SHEETS 5/8" X 5/8" 5 SQUARE
 42-84 100 SHEETS 5/8" X 5/8" 5 SQUARE
 42-85 200 SHEETS CYCLED WHITE 5 SQUARE
 42-86 200 SHEETS CYCLED WHITE 5 SQUARE
 Made in U.S.A.



PUMP STATION CALCULATIONS
EXISTING FOUNDATION

SUCTION BASIN COMPRESSIVE LOADS:

PILE CAPACITY: (FROM EUSTIS PRELIM. REPORT)

MUDLINE ~~Pile Tip~~ @ -20.5 NGVD

60' TREATED ASTM D 25
QUALITY TIMBER PILE
7" TIP, 13" BUTT →

26 TONS IN COMPRESSION
16 TONS IN TENSION

EL. WATER SURFACE = -6.7 NGVD

EL. INVERT = -20.0 NGVD

HEIGHT OF WATER = 13.3'

$$wt(water) = (13.3')(0.0624 \text{ ksf}') = 0.83 \text{ ksf}$$

$$wt(slab) = (2')(0.150 \text{ ksf}') = \underline{0.30 \text{ ksf}}$$

$$3(0.150) = \frac{.45}{1.28}$$

$$wt = 1.13 \text{ ksf}$$

$$AREA/PILE = \frac{26 \times 2}{1.13} = 46.02 \text{ sf/pile}$$

$$\frac{26 \times 2}{1.28} = 40.625$$

$$\sqrt{46} = 6.78 - \text{ use } \underline{6' \text{ GRID}}$$

$$\sqrt{40.625} = 6.37 \text{ OK}$$

TENSION:

GROUND WATER @ 0.0 , BASIN DRY

$$UPLIFT = (20')(0.0624) = 1.25 \text{ ksf } \uparrow$$

$$SLAB = (2')(0.15 - 0.0624) = \underline{0.18 \text{ ksf } \downarrow}$$

1.07 ksf tension


$$AREA/PILE = \frac{16 \times 2}{1.07} = 29.9 \text{ sf/pile}$$

$$\sqrt{29.9} = 5.47' - \text{ use } \underline{5' \text{ GRID}}$$

CONTROLS

15' x 10' 500 SHEETS, 10' x 11' 5' SQUARE
 42' x 31' 500 SHEETS, 11' x 17' 5' SQUARE
 42' x 36' 500 SHEETS, 11' x 19' 5' SQUARE
 42' x 48' 500 SHEETS, 13' x 19' 5' SQUARE
 42' x 60' 500 SHEETS, 13' x 23' 5' SQUARE
 48' x 60' 500 SHEETS, 13' x 27' 5' SQUARE
 48' x 72' 500 SHEETS, 15' x 27' 5' SQUARE
 60' x 72' 500 SHEETS, 15' x 31' 5' SQUARE
 60' x 84' 500 SHEETS, 15' x 35' 5' SQUARE
 60' x 96' 500 SHEETS, 15' x 39' 5' SQUARE
 72' x 96' 500 SHEETS, 17' x 39' 5' SQUARE
 72' x 108' 500 SHEETS, 17' x 43' 5' SQUARE
 84' x 108' 500 SHEETS, 17' x 47' 5' SQUARE
 84' x 120' 500 SHEETS, 17' x 51' 5' SQUARE
 96' x 120' 500 SHEETS, 19' x 51' 5' SQUARE
 96' x 132' 500 SHEETS, 19' x 55' 5' SQUARE
 108' x 132' 500 SHEETS, 19' x 59' 5' SQUARE
 108' x 144' 500 SHEETS, 19' x 63' 5' SQUARE
 120' x 144' 500 SHEETS, 19' x 67' 5' SQUARE
 120' x 156' 500 SHEETS, 19' x 71' 5' SQUARE
 132' x 156' 500 SHEETS, 21' x 71' 5' SQUARE
 132' x 168' 500 SHEETS, 21' x 75' 5' SQUARE
 144' x 168' 500 SHEETS, 21' x 79' 5' SQUARE
 144' x 180' 500 SHEETS, 21' x 83' 5' SQUARE
 156' x 180' 500 SHEETS, 21' x 87' 5' SQUARE
 156' x 192' 500 SHEETS, 21' x 91' 5' SQUARE
 168' x 192' 500 SHEETS, 21' x 95' 5' SQUARE
 168' x 204' 500 SHEETS, 21' x 99' 5' SQUARE
 180' x 204' 500 SHEETS, 23' x 99' 5' SQUARE
 180' x 216' 500 SHEETS, 23' x 103' 5' SQUARE
 192' x 216' 500 SHEETS, 23' x 107' 5' SQUARE
 192' x 228' 500 SHEETS, 23' x 111' 5' SQUARE
 204' x 228' 500 SHEETS, 23' x 115' 5' SQUARE
 204' x 240' 500 SHEETS, 23' x 119' 5' SQUARE
 216' x 240' 500 SHEETS, 23' x 123' 5' SQUARE
 216' x 252' 500 SHEETS, 23' x 127' 5' SQUARE
 228' x 252' 500 SHEETS, 25' x 127' 5' SQUARE
 228' x 264' 500 SHEETS, 25' x 131' 5' SQUARE
 240' x 264' 500 SHEETS, 25' x 135' 5' SQUARE
 240' x 276' 500 SHEETS, 25' x 139' 5' SQUARE
 252' x 276' 500 SHEETS, 25' x 143' 5' SQUARE
 252' x 288' 500 SHEETS, 25' x 147' 5' SQUARE
 264' x 288' 500 SHEETS, 25' x 151' 5' SQUARE
 264' x 300' 500 SHEETS, 25' x 155' 5' SQUARE
 276' x 300' 500 SHEETS, 27' x 155' 5' SQUARE
 276' x 312' 500 SHEETS, 27' x 159' 5' SQUARE
 288' x 312' 500 SHEETS, 27' x 163' 5' SQUARE
 288' x 324' 500 SHEETS, 27' x 167' 5' SQUARE
 300' x 324' 500 SHEETS, 27' x 171' 5' SQUARE
 300' x 336' 500 SHEETS, 27' x 175' 5' SQUARE
 312' x 336' 500 SHEETS, 27' x 179' 5' SQUARE
 312' x 348' 500 SHEETS, 27' x 183' 5' SQUARE
 324' x 348' 500 SHEETS, 27' x 187' 5' SQUARE
 324' x 360' 500 SHEETS, 27' x 191' 5' SQUARE
 336' x 360' 500 SHEETS, 29' x 191' 5' SQUARE
 336' x 372' 500 SHEETS, 29' x 195' 5' SQUARE
 348' x 372' 500 SHEETS, 29' x 199' 5' SQUARE
 348' x 384' 500 SHEETS, 29' x 203' 5' SQUARE
 360' x 384' 500 SHEETS, 29' x 207' 5' SQUARE
 360' x 396' 500 SHEETS, 29' x 211' 5' SQUARE
 372' x 396' 500 SHEETS, 29' x 215' 5' SQUARE
 372' x 408' 500 SHEETS, 29' x 219' 5' SQUARE
 384' x 408' 500 SHEETS, 29' x 223' 5' SQUARE
 384' x 420' 500 SHEETS, 29' x 227' 5' SQUARE
 396' x 420' 500 SHEETS, 31' x 227' 5' SQUARE
 396' x 432' 500 SHEETS, 31' x 231' 5' SQUARE
 408' x 432' 500 SHEETS, 31' x 235' 5' SQUARE
 408' x 444' 500 SHEETS, 31' x 239' 5' SQUARE
 420' x 444' 500 SHEETS, 31' x 243' 5' SQUARE
 420' x 456' 500 SHEETS, 31' x 247' 5' SQUARE
 432' x 456' 500 SHEETS, 31' x 251' 5' SQUARE
 432' x 468' 500 SHEETS, 31' x 255' 5' SQUARE
 444' x 468' 500 SHEETS, 31' x 259' 5' SQUARE
 444' x 480' 500 SHEETS, 31' x 263' 5' SQUARE
 456' x 480' 500 SHEETS, 31' x 267' 5' SQUARE
 456' x 492' 500 SHEETS, 31' x 271' 5' SQUARE
 468' x 492' 500 SHEETS, 33' x 271' 5' SQUARE
 468' x 504' 500 SHEETS, 33' x 275' 5' SQUARE
 480' x 504' 500 SHEETS, 33' x 279' 5' SQUARE
 480' x 516' 500 SHEETS, 33' x 283' 5' SQUARE
 492' x 516' 500 SHEETS, 33' x 287' 5' SQUARE
 492' x 528' 500 SHEETS, 33' x 291' 5' SQUARE
 504' x 528' 500 SHEETS, 33' x 295' 5' SQUARE
 504' x 540' 500 SHEETS, 33' x 299' 5' SQUARE
 516' x 540' 500 SHEETS, 33' x 303' 5' SQUARE
 516' x 552' 500 SHEETS, 33' x 307' 5' SQUARE
 528' x 552' 500 SHEETS, 33' x 311' 5' SQUARE
 528' x 564' 500 SHEETS, 33' x 315' 5' SQUARE
 540' x 564' 500 SHEETS, 33' x 319' 5' SQUARE
 540' x 576' 500 SHEETS, 33' x 323' 5' SQUARE
 552' x 576' 500 SHEETS, 35' x 323' 5' SQUARE
 552' x 588' 500 SHEETS, 35' x 327' 5' SQUARE
 564' x 588' 500 SHEETS, 35' x 331' 5' SQUARE
 564' x 600' 500 SHEETS, 35' x 335' 5' SQUARE
 576' x 600' 500 SHEETS, 35' x 339' 5' SQUARE
 576' x 612' 500 SHEETS, 35' x 343' 5' SQUARE
 588' x 612' 500 SHEETS, 35' x 347' 5' SQUARE
 588' x 624' 500 SHEETS, 35' x 351' 5' SQUARE
 600' x 624' 500 SHEETS, 35' x 355' 5' SQUARE
 600' x 636' 500 SHEETS, 35' x 359' 5' SQUARE
 612' x 636' 500 SHEETS, 35' x 363' 5' SQUARE
 612' x 648' 500 SHEETS, 35' x 367' 5' SQUARE
 624' x 648' 500 SHEETS, 35' x 371' 5' SQUARE
 624' x 660' 500 SHEETS, 35' x 375' 5' SQUARE
 636' x 660' 500 SHEETS, 37' x 375' 5' SQUARE
 636' x 672' 500 SHEETS, 37' x 379' 5' SQUARE
 648' x 672' 500 SHEETS, 37' x 383' 5' SQUARE
 648' x 684' 500 SHEETS, 37' x 387' 5' SQUARE
 660' x 684' 500 SHEETS, 37' x 391' 5' SQUARE
 660' x 696' 500 SHEETS, 37' x 395' 5' SQUARE
 672' x 696' 500 SHEETS, 37' x 399' 5' SQUARE
 672' x 708' 500 SHEETS, 37' x 403' 5' SQUARE
 684' x 708' 500 SHEETS, 37' x 407' 5' SQUARE
 684' x 720' 500 SHEETS, 37' x 411' 5' SQUARE
 696' x 720' 500 SHEETS, 39' x 411' 5' SQUARE
 696' x 732' 500 SHEETS, 39' x 415' 5' SQUARE
 708' x 732' 500 SHEETS, 39' x 419' 5' SQUARE
 708' x 744' 500 SHEETS, 39' x 423' 5' SQUARE
 720' x 744' 500 SHEETS, 39' x 427' 5' SQUARE
 720' x 756' 500 SHEETS, 39' x 431' 5' SQUARE
 732' x 756' 500 SHEETS, 39' x 435' 5' SQUARE
 732' x 768' 500 SHEETS, 39' x 439' 5' SQUARE
 744' x 768' 500 SHEETS, 39' x 443' 5' SQUARE
 744' x 780' 500 SHEETS, 39' x 447' 5' SQUARE
 756' x 780' 500 SHEETS, 41' x 447' 5' SQUARE
 756' x 792' 500 SHEETS, 41' x 451' 5' SQUARE
 768' x 792' 500 SHEETS, 41' x 455' 5' SQUARE
 768' x 804' 500 SHEETS, 41' x 459' 5' SQUARE
 780' x 804' 500 SHEETS, 41' x 463' 5' SQUARE
 780' x 816' 500 SHEETS, 41' x 467' 5' SQUARE
 792' x 816' 500 SHEETS, 41' x 471' 5' SQUARE
 792' x 828' 500 SHEETS, 41' x 475' 5' SQUARE
 804' x 828' 500 SHEETS, 41' x 479' 5' SQUARE
 804' x 840' 500 SHEETS, 41' x 483' 5' SQUARE
 816' x 840' 500 SHEETS, 41' x 487' 5' SQUARE
 816' x 852' 500 SHEETS, 41' x 491' 5' SQUARE
 828' x 852' 500 SHEETS, 41' x 495' 5' SQUARE
 828' x 864' 500 SHEETS, 41' x 499' 5' SQUARE
 840' x 864' 500 SHEETS, 41' x 503' 5' SQUARE
 840' x 876' 500 SHEETS, 41' x 507' 5' SQUARE
 852' x 876' 500 SHEETS, 43' x 507' 5' SQUARE
 852' x 888' 500 SHEETS, 43' x 511' 5' SQUARE
 864' x 888' 500 SHEETS, 43' x 515' 5' SQUARE
 864' x 896' 500 SHEETS, 43' x 519' 5' SQUARE
 876' x 896' 500 SHEETS, 43' x 523' 5' SQUARE
 876' x 908' 500 SHEETS, 43' x 527' 5' SQUARE
 888' x 908' 500 SHEETS, 43' x 531' 5' SQUARE
 888' x 920' 500 SHEETS, 43' x 535' 5' SQUARE
 900' x 920' 500 SHEETS, 43' x 539' 5' SQUARE
 900' x 932' 500 SHEETS, 43' x 543' 5' SQUARE
 912' x 932' 500 SHEETS, 43' x 547' 5' SQUARE
 912' x 944' 500 SHEETS, 43' x 551' 5' SQUARE
 924' x 944' 500 SHEETS, 45' x 551' 5' SQUARE
 924' x 956' 500 SHEETS, 45' x 555' 5' SQUARE
 936' x 956' 500 SHEETS, 45' x 559' 5' SQUARE
 936' x 968' 500 SHEETS, 45' x 563' 5' SQUARE
 948' x 968' 500 SHEETS, 45' x 567' 5' SQUARE
 948' x 980' 500 SHEETS, 45' x 571' 5' SQUARE
 960' x 980' 500 SHEETS, 45' x 575' 5' SQUARE
 960' x 992' 500 SHEETS, 45' x 579' 5' SQUARE
 972' x 992' 500 SHEETS, 45' x 583' 5' SQUARE
 972' x 1004' 500 SHEETS, 45' x 587' 5' SQUARE
 984' x 1004' 500 SHEETS, 45' x 591' 5' SQUARE
 984' x 1016' 500 SHEETS, 45' x 595' 5' SQUARE
 996' x 1016' 500 SHEETS, 45' x 599' 5' SQUARE
 996' x 1028' 500 SHEETS, 45' x 603' 5' SQUARE
 1008' x 1028' 500 SHEETS, 45' x 607' 5' SQUARE
 1008' x 1040' 500 SHEETS, 45' x 611' 5' SQUARE
 1020' x 1040' 500 SHEETS, 47' x 611' 5' SQUARE
 1020' x 1052' 500 SHEETS, 47' x 615' 5' SQUARE
 1032' x 1052' 500 SHEETS, 47' x 619' 5' SQUARE
 1032' x 1064' 500 SHEETS, 47' x 623' 5' SQUARE
 1044' x 1064' 500 SHEETS, 47' x 627' 5' SQUARE
 1044' x 1076' 500 SHEETS, 47' x 631' 5' SQUARE
 1056' x 1076' 500 SHEETS, 47' x 635' 5' SQUARE
 1056' x 1088' 500 SHEETS, 47' x 639' 5' SQUARE
 1068' x 1088' 500 SHEETS, 47' x 643' 5' SQUARE
 1068' x 1100' 500 SHEETS, 47' x 647' 5' SQUARE
 1080' x 1100' 500 SHEETS, 49' x 647' 5' SQUARE
 1080' x 1112' 500 SHEETS, 49' x 651' 5' SQUARE
 1092' x 1112' 500 SHEETS, 49' x 655' 5' SQUARE
 1092' x 1124' 500 SHEETS, 49' x 659' 5' SQUARE
 1104' x 1124' 500 SHEETS, 49' x 663' 5' SQUARE
 1104' x 1136' 500 SHEETS, 49' x 667' 5' SQUARE
 1116' x 1136' 500 SHEETS, 49' x 671' 5' SQUARE
 1116' x 1148' 500 SHEETS, 49' x 675' 5' SQUARE
 1128' x 1148' 500 SHEETS, 49' x 679' 5' SQUARE
 1128' x 1160' 500 SHEETS, 49' x 683' 5' SQUARE
 1140' x 1160' 500 SHEETS, 51' x 683' 5' SQUARE
 1140' x 1172' 500 SHEETS, 51' x 687' 5' SQUARE
 1152' x 1172' 500 SHEETS, 51' x 691' 5' SQUARE
 1152' x 1184' 500 SHEETS, 51' x 695' 5' SQUARE
 1164' x 1184' 500 SHEETS, 51' x 699' 5' SQUARE
 1164' x 1196' 500 SHEETS, 51' x 703' 5' SQUARE
 1176' x 1196' 500 SHEETS, 51' x 707' 5' SQUARE
 1176' x 1208' 500 SHEETS, 51' x 711' 5' SQUARE
 1188' x 1208' 500 SHEETS, 51' x 715' 5' SQUARE
 1188' x 1220' 500 SHEETS, 51' x 719' 5' SQUARE
 1200' x 1220' 500 SHEETS, 53' x 719' 5' SQUARE
 1200' x 1232' 500 SHEETS, 53' x 723' 5' SQUARE
 1212' x 1232' 500 SHEETS, 53' x 727' 5' SQUARE
 1212' x 1244' 500 SHEETS, 53' x 731' 5' SQUARE
 1224' x 1244' 500 SHEETS, 53' x 735' 5' SQUARE
 1224' x 1256' 500 SHEETS, 53' x 739' 5' SQUARE
 1236' x 1256' 500 SHEETS, 53' x 743' 5' SQUARE
 1236' x 1268' 500 SHEETS, 53' x 747' 5' SQUARE
 1248' x 1268' 500 SHEETS, 53' x 751' 5' SQUARE
 1248' x 1280' 500 SHEETS, 53' x 755' 5' SQUARE
 1260' x 1280' 500 SHEETS, 55' x 755' 5' SQUARE
 1260' x 1292' 500 SHEETS, 55' x 759' 5' SQUARE
 1272' x 1292' 500 SHEETS, 55' x 763' 5' SQUARE
 1272' x 1304' 500 SHEETS, 55' x 767' 5' SQUARE
 1284' x 1304' 500 SHEETS, 55' x 771' 5' SQUARE
 1284' x 1316' 500 SHEETS, 55' x 775' 5' SQUARE
 1296' x 1316' 500 SHEETS, 55' x 779' 5' SQUARE
 1296' x 1328' 500 SHEETS, 55' x 783' 5' SQUARE
 1308' x 1328' 500 SHEETS, 55' x 787' 5' SQUARE
 1308' x 1340' 500 SHEETS, 55' x 791' 5' SQUARE
 1320' x 1340' 500 SHEETS, 57' x 791' 5' SQUARE
 1320' x 1352' 500 SHEETS, 57' x 795' 5' SQUARE
 1332' x 1352' 500 SHEETS, 57' x 799' 5' SQUARE
 1332' x 1364' 500 SHEETS, 57' x 803' 5' SQUARE
 1344' x 1364' 500 SHEETS, 57' x 807' 5' SQUARE
 1344' x 1376' 500 SHEETS, 57' x 811' 5' SQUARE
 1356' x 1376' 500 SHEETS, 57' x 815' 5' SQUARE
 1356' x 1388' 500 SHEETS, 57' x 819' 5' SQUARE
 1368' x 1388' 500 SHEETS, 57' x 823' 5' SQUARE
 1368' x 1400' 500 SHEETS, 57' x 827' 5' SQUARE
 1380' x 1400' 500 SHEETS, 59' x 827' 5' SQUARE
 1380' x 1412' 500 SHEETS, 59' x 831' 5' SQUARE
 1392' x 1412' 500 SHEETS, 59' x 835' 5' SQUARE
 1392' x 1424' 500 SHEETS, 59' x 839' 5' SQUARE
 1404' x 1424' 500 SHEETS, 59' x 843' 5' SQUARE
 1404' x 1436' 500 SHEETS, 59' x 847' 5' SQUARE
 1416' x 1436' 500 SHEETS, 59' x 851' 5' SQUARE
 1416' x 1448' 500 SHEETS, 59' x 855' 5' SQUARE
 1428' x 1448' 500 SHEETS, 59' x 859' 5' SQUARE
 1428' x 1460' 500 SHEETS, 59' x 863' 5' SQUARE
 1440' x 1460' 500 SHEETS, 61' x 863' 5' SQUARE
 1440' x 1472' 500 SHEETS, 61' x 867' 5' SQUARE
 1452' x 1472' 500 SHEETS, 61' x 871' 5' SQUARE
 1452' x 1484' 500 SHEETS, 61' x 875' 5' SQUARE
 1464' x 1484' 500 SHEETS, 61' x 879' 5' SQUARE
 1464' x 1496' 500 SHEETS, 61' x 883' 5' SQUARE
 1476' x 1496' 500 SHEETS, 61' x 887' 5' SQUARE
 1476' x 1508' 500 SHEETS, 61' x 891' 5' SQUARE
 1488' x 1508' 500 SHEETS, 61' x 895' 5' SQUARE
 1488' x 1520' 500 SHEETS, 61' x 899' 5' SQUARE
 1500' x 1520' 500 SHEETS, 61' x 903' 5' SQUARE
 1500' x 1532' 500 SHEETS, 61' x 907' 5' SQUARE
 1512' x 1532' 500 SHEETS, 63' x 907' 5' SQUARE
 1512' x 1544' 500 SHEETS, 63' x 911' 5' SQUARE
 1524' x 1544' 500 SHEETS, 63' x 915' 5' SQUARE
 1524' x 1556' 500 SHEETS, 63' x 919' 5' SQUARE
 1536' x 1556' 500 SHEETS, 63' x 923' 5' SQUARE
 1536' x 1568' 500 SHEETS, 63' x 927' 5' SQUARE
 1548' x 1568' 500 SHEETS, 63' x 931' 5' SQUARE
 1548' x 1580' 500 SHEETS, 63' x 935' 5' SQUARE
 1560' x 1580' 500 SHEETS, 65' x 935' 5' SQUARE
 1560' x 1592' 500 SHEETS, 65' x 939' 5' SQUARE
 1572' x 1592' 500 SHEETS, 65' x 943' 5' SQUARE
 1572' x 1604' 500 SHEETS, 65' x 947' 5' SQUARE
 1584' x 1604' 500 SHEETS, 65' x 951' 5' SQUARE
 1584' x 1616' 500 SHEETS, 65' x 955' 5' SQUARE
 1596' x 1616' 500 SHEETS, 65' x 959' 5' SQUARE
 1596' x 1628' 500 SHEETS, 65' x 963' 5' SQUARE
 1608' x 1628' 500 SHEETS, 65' x 967' 5' SQUARE
 1608' x 1640' 500 SHEETS, 65' x 971' 5' SQUARE
 1620' x 1640' 500 SHEETS, 67' x 971' 5' SQUARE
 1620' x 1652' 500 SHEETS, 67' x 975' 5' SQUARE
 1632' x 1652' 500 SHEETS, 67' x 979' 5' SQUARE
 1632' x 1664' 500 SHEETS, 67' x 983' 5' SQUARE
 1644' x 1664' 500 SHEETS, 67' x 987' 5' SQUARE
 1644' x 1676' 500 SHEETS, 67' x 991' 5' SQUARE
 1656' x 1676' 500 SHEETS, 67' x 995' 5' SQUARE
 1656' x 1688' 500 SHEETS, 67' x 999' 5' SQUARE
 1668' x 1688' 500 SHEETS, 67' x 1003' 5' SQUARE
 1668' x 1700' 500 SHEETS, 67' x 1007' 5' SQUARE
 1680' x 1700' 500 SHEETS, 69' x 1007' 5' SQUARE
 1680' x 1712' 500 SHEETS, 69' x 1011' 5' SQUARE
 1692' x 1712' 500 SHEETS, 69' x 1015' 5' SQUARE
 1692' x 1724' 500 SHEETS, 69' x 1019' 5' SQUARE
 1704' x 1724' 500 SHEETS, 69' x 1023' 5' SQUARE
 1704' x 1736' 500 SHEETS, 69' x 1027' 5' SQUARE
 1716' x 1736' 500 SHEETS, 69' x 1031' 5' SQUARE
 1716' x 1748' 500 SHEETS, 69' x 1035' 5' SQUARE
 1728' x 1748' 500 SHEETS, 69' x 1039' 5' SQUARE
 1728' x 1760' 500 SHEETS, 69' x 1043' 5' SQUARE
 1740' x 1760' 500 SHEETS, 71' x 1043' 5' SQUARE
 1740' x 1772' 500 SHEETS, 71'

SLAB: (DESIGN SLAB FOR TIMBER PILES)



43 402
43 403
43 404
43 405
43 406
43 407
43 408
43 409
43 410
43 411
43 412
43 413
43 414
43 415
43 416
43 417
43 418
43 419
43 420
43 421
43 422
43 423
43 424
43 425
43 426
43 427
43 428
43 429
43 430
43 431
43 432
43 433
43 434
43 435
43 436
43 437
43 438
43 439
43 440
43 441
43 442
43 443
43 444
43 445
43 446
43 447
43 448
43 449
43 450
43 451
43 452
43 453
43 454
43 455
43 456
43 457
43 458
43 459
43 460
43 461
43 462
43 463
43 464
43 465
43 466
43 467
43 468
43 469
43 470
43 471
43 472
43 473
43 474
43 475
43 476
43 477
43 478
43 479
43 480
43 481
43 482
43 483
43 484
43 485
43 486
43 487
43 488
43 489
43 490
43 491
43 492
43 493
43 494
43 495
43 496
43 497
43 498
43 499
43 500
43 501
43 502
43 503
43 504
43 505
43 506
43 507
43 508
43 509
43 510
43 511
43 512
43 513
43 514
43 515
43 516
43 517
43 518
43 519
43 520
43 521
43 522
43 523
43 524
43 525
43 526
43 527
43 528
43 529
43 530
43 531
43 532
43 533
43 534
43 535
43 536
43 537
43 538
43 539
43 540
43 541
43 542
43 543
43 544
43 545
43 546
43 547
43 548
43 549
43 550
43 551
43 552
43 553
43 554
43 555
43 556
43 557
43 558
43 559
43 560
43 561
43 562
43 563
43 564
43 565
43 566
43 567
43 568
43 569
43 570
43 571
43 572
43 573
43 574
43 575
43 576
43 577
43 578
43 579
43 580
43 581
43 582
43 583
43 584
43 585
43 586
43 587
43 588
43 589
43 590
43 591
43 592
43 593
43 594
43 595
43 596
43 597
43 598
43 599
43 600
43 601
43 602
43 603
43 604
43 605
43 606
43 607
43 608
43 609
43 610
43 611
43 612
43 613
43 614
43 615
43 616
43 617
43 618
43 619
43 620
43 621
43 622
43 623
43 624
43 625
43 626
43 627
43 628
43 629
43 630
43 631
43 632
43 633
43 634
43 635
43 636
43 637
43 638
43 639
43 640
43 641
43 642
43 643
43 644
43 645
43 646
43 647
43 648
43 649
43 650
43 651
43 652
43 653
43 654
43 655
43 656
43 657
43 658
43 659
43 660
43 661
43 662
43 663
43 664
43 665
43 666
43 667
43 668
43 669
43 670
43 671
43 672
43 673
43 674
43 675
43 676
43 677
43 678
43 679
43 680
43 681
43 682
43 683
43 684
43 685
43 686
43 687
43 688
43 689
43 690
43 691
43 692
43 693
43 694
43 695
43 696
43 697
43 698
43 699
43 700
43 701
43 702
43 703
43 704
43 705
43 706
43 707
43 708
43 709
43 710
43 711
43 712
43 713
43 714
43 715
43 716
43 717
43 718
43 719
43 720
43 721
43 722
43 723
43 724
43 725
43 726
43 727
43 728
43 729
43 730
43 731
43 732
43 733
43 734
43 735
43 736
43 737
43 738
43 739
43 740
43 741
43 742
43 743
43 744
43 745
43 746
43 747
43 748
43 749
43 750
43 751
43 752
43 753
43 754
43 755
43 756
43 757
43 758
43 759
43 760
43 761
43 762
43 763
43 764
43 765
43 766
43 767
43 768
43 769
43 770
43 771
43 772
43 773
43 774
43 775
43 776
43 777
43 778
43 779
43 780
43 781
43 782
43 783
43 784
43 785
43 786
43 787
43 788
43 789
43 790
43 791
43 792
43 793
43 794
43 795
43 796
43 797
43 798
43 799
43 800
43 801
43 802
43 803
43 804
43 805
43 806
43 807
43 808
43 809
43 810
43 811
43 812
43 813
43 814
43 815
43 816
43 817
43 818
43 819
43 820
43 821
43 822
43 823
43 824
43 825
43 826
43 827
43 828
43 829
43 830
43 831
43 832
43 833
43 834
43 835
43 836
43 837
43 838
43 839
43 840
43 841
43 842
43 843
43 844
43 845
43 846
43 847
43 848
43 849
43 850
43 851
43 852
43 853
43 854
43 855
43 856
43 857
43 858
43 859
43 860
43 861
43 862
43 863
43 864
43 865
43 866
43 867
43 868
43 869
43 870
43 871
43 872
43 873
43 874
43 875
43 876
43 877
43 878
43 879
43 880
43 881
43 882
43 883
43 884
43 885
43 886
43 887
43 888
43 889
43 890
43 891
43 892
43 893
43 894
43 895
43 896
43 897
43 898
43 899
43 900
43 901
43 902
43 903
43 904
43 905
43 906
43 907
43 908
43 909
43 910
43 911
43 912
43 913
43 914
43 915
43 916
43 917
43 918
43 919
43 920
43 921
43 922
43 923
43 924
43 925
43 926
43 927
43 928
43 929
43 930
43 931
43 932
43 933
43 934
43 935
43 936
43 937
43 938
43 939
43 940
43 941
43 942
43 943
43 944
43 945
43 946
43 947
43 948
43 949
43 950
43 951
43 952
43 953
43 954
43 955
43 956
43 957
43 958
43 959
43 960
43 961
43 962
43 963
43 964
43 965
43 966
43 967
43 968
43 969
43 970
43 971
43 972
43 973
43 974
43 975
43 976
43 977
43 978
43 979
43 980
43 981
43 982
43 983
43 984
43 985
43 986
43 987
43 988
43 989
43 990
43 991
43 992
43 993
43 994
43 995
43 996
43 997
43 998
43 999
43 1000




-USE FLAT SLAB:

$$w_u = 1.13(1.2) = 1.36 \text{ ksf}$$

$$M_o = \frac{w_u l_n^2}{8} = \frac{(1.38)(5)(5)^2}{8} = 21.56 \text{ 'k}$$

$$\text{Max Neg } M = 0.65 M_o = 0.65(21.56) = 14.01 \text{ 'k}$$

- try 24" slab: $d = 21"$ (-M)
 $d = 15"$ (+M)



$$A_s(+M) = \frac{M}{f_y z}, \quad z = 0.9d$$

$$= \frac{(21.56)(12)}{60(.9)(15)} = 0.32 \text{ in}^2$$

$$= \frac{(21.56)(12)}{48(.9)(15)} = 0.399$$

$$A_s(-M) = \frac{(14.01)(12)}{60(.9)(21)} = 0.15 \text{ in}^2$$

$$= \frac{(14.01)(12)}{48(.9)(21)} = 0.185$$

Bottom MAT: -

Top MAT: -


GUIDE WALL (CONT.)

(for 1' STRIP:)

#	LOAD (K)	MOMENT ARM	MOMENT
1	$(18')(2')(15 \text{ kcf}) = 5.4^k$	7.5'	-40.5
2	$(18')(2')(12 \text{ kcf}) = 4.32^k$	9.5'	-41.04
3	$(8.75')(9')(15 \text{ kcf}) = 3.94^k$	5.25'	-20.68
4	$(2)(K_L \times H)(A) =$ $\frac{1}{2}(.333)(.12)(18)^2 = 6.47^k$	6'	38.82
			<hr/>
			63.40

$M = \Sigma V \times e \quad \Sigma V = 13.66^k$

$e = 63.40 / 13.66 = 4.64 \text{ left of "A"} \quad (\text{w/in center } \frac{1}{3} \text{ - } 0.6)$



see 7a

C.G. of PILE GROUP: $\frac{(1.25) + (6.25) + (8.75)}{3} = 5.42' \text{ from "A"}$

$e = 5.42 - 4.64 = 0.78'$

for 5' STRIP: $\Sigma V = 13.66 \times 5 = 68.3^k$

$M_{(PILE \text{ GROUP})} = \Sigma V \times e$
 $= 13.66(5')(0.78')$
 $= 53.27^k$

10 SHEETS TOTAL - 1 SQUARE
 40 SHEETS TOTAL - 2 SQUARE
 100 SHEETS TOTAL - 5 SQUARE
 40 SHEETS TOTAL - 2 SQUARE
 200 SHEETS TOTAL - 10 SQUARE
 40 SHEETS TOTAL - 2 SQUARE
 200 SHEETS TOTAL - 10 SQUARE
 MADE IN U.S.A.



Σd^2 SECTION MODULUS :

$$\Sigma d^2: (1)(3.33)^2 + (1)(.83)^2 + (1)(4.17)^2 = 29.17 \text{ FT}^2 \cdot \text{PILE}$$

SECTION MODULUS:

$$\textcircled{1} 29.17/3.33 = 8.76 \text{ FT PILE}$$

$$\textcircled{2} 29.17/.83 = 35.14 \text{ FT PILE}$$

$$\textcircled{3} 29.17/4.17 = 7.00 \text{ FT PILE}$$

see 7a

PILE REACTIONS :

$$\textcircled{1} \frac{68.3}{3} - \frac{53.27}{8.76} = 16.7^k (c) < 26^T \underline{\text{OK}}$$

$$\textcircled{2} \frac{68.3}{3} - \frac{53.27}{35.14} = 21.25^k (c) < 26^T \underline{\text{OK}}$$

$$\textcircled{3} \frac{68.3}{3} + \frac{53.27}{7.00} = 30.38^k (c) < 26^T \underline{\text{OK}}$$


M@ BASE OF WALL:

$$P_u = 6.47^k (1.7) = 10.99^k$$


$$M_u = 10.99(6') = 65.94^k$$

$$A_s = \frac{65.94(12)}{60(21^2)} = 0.628 \text{ in}^2/\text{ft} \quad - \text{use } 6@6' \cdot 88 \text{ in}^2/\text{ft}$$

500 SHEETS PER 5 SQUARE
 400 SHEETS PER 4 SQUARE
 300 SHEETS PER 3 SQUARE
 200 SHEETS PER 2 SQUARE
 100 SHEETS PER 1 SQUARE
 UNRECYCLED PAPER
 100% RECYCLED PAPER
 100% RECYCLED PAPER
 100% RECYCLED PAPER
 100% RECYCLED PAPER
 MADE IN U.S.A.



SUCTION BASIN GUIDE WALL :



$\Sigma M = 63.40 \text{ k}^2$
 $\Sigma V = 13.66 \text{ k}$

$e = 63.40 / 13.66 = 4.64 \text{ ft of "A"}$

w. this center's - OK

(from calcs. dated 6-11-97
 p. 6)

C.G. of Pile group: $\frac{(1.25) + (6) + (9.0)}{3} = 5.42 \text{ ' from "A"}$

$e = 5.42 - 4.64 = 0.78$

for 5' strip: $\Sigma V = 13.66 \times 5 = 68.3 \text{ k}$

$M_{\text{pile group}} = \Sigma V \cdot e$
 $= 68.3 (0.78)$
 $= 53.27 \text{ k}^2$

$\Sigma d^2 = (4.17)^2 + (1.58)^2 + (3.58)^2 = 30.54 \text{ FT}^2 \cdot \text{pile}$

Section Modulus:

$S_1 = 30.54 / 4.17 = 7.32 \text{ FT} \cdot \text{pile}$
 $S_2 = 30.54 / 1.58 = 52.66$
 $S_3 = 30.54 / 3.58 = 8.53$

Pile Reactions: $\textcircled{1} \frac{68.3}{3} + \frac{53.27}{7.32} = 30.0 \text{ k (c)} < 26^7 \cdot 52 \text{ k } \underline{\text{OK}}$
 $\textcircled{2} \frac{68.3}{3} - \frac{53.27}{52.66} = 21.8 \text{ k (c)} \underline{\text{OK}}$
 $\textcircled{3} \frac{68.3}{3} - \frac{53.27}{8.53} = 16.5 \text{ k (c)} \underline{\text{OK}}$

500 SHEETS, FULLER 5 SQUARE
 42,381 50 SHEETS, FULLER 5 SQUARE
 42,382 100 SHEETS, FULLER 5 SQUARE
 42,383 200 SHEETS, FULLER 5 SQUARE
 42,384 300 SHEETS, FULLER 5 SQUARE
 42,385 400 SHEETS, FULLER 5 SQUARE
 42,386 500 SHEETS, FULLER 5 SQUARE
 42,387 600 SHEETS, FULLER 5 SQUARE
 42,388 700 SHEETS, FULLER 5 SQUARE
 42,389 800 SHEETS, FULLER 5 SQUARE
 42,390 900 SHEETS, FULLER 5 SQUARE
 42,391 1000 SHEETS, FULLER 5 SQUARE
 Made in U.S.A.



DRAWINGS REQ'D: (FROM DEI)

SECTION THROUGH SUCTION BASIN

PUMPING STATION PROFILE (THROUGH & DISCHARGE TUBE)

GENERAL FLOOR PLAN (BLDG)

SECTION (SHOWING METAL BLDG.) (N/S)

SECTION (SHOWING METAL BLDG.) (E/W)

PLAN (DISCHARGE)

SECTION - DISCHARGE BASIN

PILE LAYOUT

FLOODWALL

15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, 120, 125, 130, 135, 140, 145, 150, 155, 160, 165, 170, 175, 180, 185, 190, 195, 200, 205, 210, 215, 220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290, 295, 300, 305, 310, 315, 320, 325, 330, 335, 340, 345, 350, 355, 360, 365, 370, 375, 380, 385, 390, 395, 400, 405, 410, 415, 420, 425, 430, 435, 440, 445, 450, 455, 460, 465, 470, 475, 480, 485, 490, 495, 500, 505, 510, 515, 520, 525, 530, 535, 540, 545, 550, 555, 560, 565, 570, 575, 580, 585, 590, 595, 600, 605, 610, 615, 620, 625, 630, 635, 640, 645, 650, 655, 660, 665, 670, 675, 680, 685, 690, 695, 700, 705, 710, 715, 720, 725, 730, 735, 740, 745, 750, 755, 760, 765, 770, 775, 780, 785, 790, 795, 800, 805, 810, 815, 820, 825, 830, 835, 840, 845, 850, 855, 860, 865, 870, 875, 880, 885, 890, 895, 900, 905, 910, 915, 920, 925, 930, 935, 940, 945, 950, 955, 960, 965, 970, 975, 980, 985, 990, 995, 1000



FRONTAL PROTECTION CALCULATIONS
EXISTING PUMP STATION

T-WALL LOADING CASES:

Case I: Static water pressure to SWL, no wind, impervious sheet pile cut-off (100% forces)

Case II: Static water pressure to SWL, no wind, pervious sheet pile cut-off (100% forces)

Case III: Static water pressure to SWL + 2', no wind, impervious sheet pile (75% forces)

Case IV: Static water pressure to SWL + 2', no wind, pervious sheet pile (75% forces)

Case V: Water at low water level, no wind, (100% forces)

Case VI: Water at low water level, wind from flood side (75%)

13 782 500 SHEETS, FILLER, SOLVATE
42 381 900 SHEETS, FILLER, SOLVATE
42 382 100 SHEETS, FILLER, SOLVATE
42 383 200 SHEETS, FILLER, SOLVATE
42 384 100 SHEETS, FILLER, SOLVATE
42 385 200 SHEETS, FILLER, SOLVATE
42 386 100 RECYCLED WHITE 5 SQUARE
42 387 200 RECYCLED WHITE 5 SQUARE
Made in U.S.A.



DEAD LOADS: (per linear foot)

stem: $(22.5)(2)(.150 \text{ %CF}) = 6.75 \text{ %LF}$

base: $(15)(2.5)(.150) = 5.63$

WATER OVER BASE:

@ SWL: $(11')(20.5')(0.064) = 14.43$

@ SWL + 2': $(11')(22.5)(0.064) = 15.84$

@ low water: $(11')(11')(0.064) = 7.74$

SOIL ON P/S


$(6')(2')(0.120) = 1.44 \text{ %LF}$

500 SHEETS, FILER, 5 SQUARE
50 SHEETS, EYE, 5 SQUARE
100 SHEETS, EYE, 5 SQUARE
100 SHEETS, EYE, 5 SQUARE
100 SHEETS, EYE, 5 SQUARE
100 SHEETS, EYE, 5 SQUARE
200 RECYCLED WHITE, 5 SQUARE
MADE IN U.S.A.



WATER LOADS:

SWL = 9.5



@ SWL:

$$p = (23)(.064) = 1.47 \text{ K/FT.FT}$$

@ SWL + 2':



$$p = (25)(.064) = 1.60 \text{ K/FT.FT}$$

@ Low Water:

$$p = (13.5)(.064) = 0.864 \text{ K/FT.FT}$$

SWL + 2'

LOW WATER:



13 782 500 SHEETS, FILER, 5 SQUARE
 42 381 50 SHEETS, 1/2" EASE, 5 SQUARE
 42 382 100 SHEETS, 1/2" EASE, 5 SQUARE
 42 383 100 SHEETS, 1/2" EASE, 5 SQUARE
 42 384 100 SHEETS, 1/2" EASE, 5 SQUARE
 42 385 100 RECYCLED WHITE, 5 SQUARE
 42 386 200 RECYCLED WHITE, 5 SQUARE
 Made in U.S.A.



WIND LOADS: ON PROTECTED SIDE:

$$(50 \text{ psf})(11.5) = 575 \text{ plf}$$

ANCHOR FORCE:

$$7.1 \text{ k/ft of wall @ } -13.0'$$


(ANCHOR FORCE IS -X,
LOAD IS +X)

$$7.1 \times 80 = 568 \text{ k } +x \quad \leftarrow \text{ ADD TO ALL LOAD GROUPS}$$

$$\text{Lever arm} = -0.5'$$

$$M = 7.1(1.5) = 3.55 + 80' = 284 \text{ k } \leftarrow -M_y$$

13 782
42 382
42 389
42 392
42 395
42 398
42 401
42 404
42 407
42 410
42 413
42 416
42 419
42 422
42 425
42 428
42 431
42 434
42 437
42 440
42 443
42 446
42 449
42 452
42 455
42 458
42 461
42 464
42 467
42 470
42 473
42 476
42 479
42 482
42 485
42 488
42 491
42 494
42 497
42 500
42 503
42 506
42 509
42 512
42 515
42 518
42 521
42 524
42 527
42 530
42 533
42 536
42 539
42 542
42 545
42 548
42 551
42 554
42 557
42 560
42 563
42 566
42 569
42 572
42 575
42 578
42 581
42 584
42 587
42 590
42 593
42 596
42 599
42 602
42 605
42 608
42 611
42 614
42 617
42 620
42 623
42 626
42 629
42 632
42 635
42 638
42 641
42 644
42 647
42 650
42 653
42 656
42 659
42 662
42 665
42 668
42 671
42 674
42 677
42 680
42 683
42 686
42 689
42 692
42 695
42 698
42 701
42 704
42 707
42 710
42 713
42 716
42 719
42 722
42 725
42 728
42 731
42 734
42 737
42 740
42 743
42 746
42 749
42 752
42 755
42 758
42 761
42 764
42 767
42 770
42 773
42 776
42 779
42 782
42 785
42 788
42 791
42 794
42 797
42 800
42 803
42 806
42 809
42 812
42 815
42 818
42 821
42 824
42 827
42 830
42 833
42 836
42 839
42 842
42 845
42 848
42 851
42 854
42 857
42 860
42 863
42 866
42 869
42 872
42 875
42 878
42 881
42 884
42 887
42 890
42 893
42 896
42 899
42 902
42 905
42 908
42 911
42 914
42 917
42 920
42 923
42 926
42 929
42 932
42 935
42 938
42 941
42 944
42 947
42 950
42 953
42 956
42 959
42 962
42 965
42 968
42 971
42 974
42 977
42 980
42 983
42 986
42 989
42 992
42 995
42 998
42 1001
42 1004
42 1007
42 1010
42 1013
42 1016
42 1019
42 1022
42 1025
42 1028
42 1031
42 1034
42 1037
42 1040
42 1043
42 1046
42 1049
42 1052
42 1055
42 1058
42 1061
42 1064
42 1067
42 1070
42 1073
42 1076
42 1079
42 1082
42 1085
42 1088
42 1091
42 1094
42 1097
42 1100
42 1103
42 1106
42 1109
42 1112
42 1115
42 1118
42 1121
42 1124
42 1127
42 1130
42 1133
42 1136
42 1139
42 1142
42 1145
42 1148
42 1151
42 1154
42 1157
42 1160
42 1163
42 1166
42 1169
42 1172
42 1175
42 1178
42 1181
42 1184
42 1187
42 1190
42 1193
42 1196
42 1199
42 1202
42 1205
42 1208
42 1211
42 1214
42 1217
42 1220
42 1223
42 1226
42 1229
42 1232
42 1235
42 1238
42 1241
42 1244
42 1247
42 1250
42 1253
42 1256
42 1259
42 1262
42 1265
42 1268
42 1271
42 1274
42 1277
42 1280
42 1283
42 1286
42 1289
42 1292
42 1295
42 1298
42 1301
42 1304
42 1307
42 1310
42 1313
42 1316
42 1319
42 1322
42 1325
42 1328
42 1331
42 1334
42 1337
42 1340
42 1343
42 1346
42 1349
42 1352
42 1355
42 1358
42 1361
42 1364
42 1367
42 1370
42 1373
42 1376
42 1379
42 1382
42 1385
42 1388
42 1391
42 1394
42 1397
42 1400
42 1403
42 1406
42 1409
42 1412
42 1415
42 1418
42 1421
42 1424
42 1427
42 1430
42 1433
42 1436
42 1439
42 1442
42 1445
42 1448
42 1451
42 1454
42 1457
42 1460
42 1463
42 1466
42 1469
42 1472
42 1475
42 1478
42 1481
42 1484
42 1487
42 1490
42 1493
42 1496
42 1499
42 1502
42 1505
42 1508
42 1511
42 1514
42 1517
42 1520
42 1523
42 1526
42 1529
42 1532
42 1535
42 1538
42 1541
42 1544
42 1547
42 1550
42 1553
42 1556
42 1559
42 1562
42 1565
42 1568
42 1571
42 1574
42 1577
42 1580
42 1583
42 1586
42 1589
42 1592
42 1595
42 1598
42 1601
42 1604
42 1607
42 1610
42 1613
42 1616
42 1619
42 1622
42 1625
42 1628
42 1631
42 1634
42 1637
42 1640
42 1643
42 1646
42 1649
42 1652
42 1655
42 1658
42 1661
42 1664
42 1667
42 1670
42 1673
42 1676
42 1679
42 1682
42 1685
42 1688
42 1691
42 1694
42 1697
42 1700
42 1703
42 1706
42 1709
42 1712
42 1715
42 1718
42 1721
42 1724
42 1727
42 1730
42 1733
42 1736
42 1739
42 1742
42 1745
42 1748
42 1751
42 1754
42 1757
42 1760
42 1763
42 1766
42 1769
42 1772
42 1775
42 1778
42 1781
42 1784
42 1787
42 1790
42 1793
42 1796
42 1799
42 1802
42 1805
42 1808
42 1811
42 1814
42 1817
42 1820
42 1823
42 1826
42 1829
42 1832
42 1835
42 1838
42 1841
42 1844
42 1847
42 1850
42 1853
42 1856
42 1859
42 1862
42 1865
42 1868
42 1871
42 1874
42 1877
42 1880
42 1883
42 1886
42 1889
42 1892
42 1895
42 1898
42 1901
42 1904
42 1907
42 1910
42 1913
42 1916
42 1919
42 1922
42 1925
42 1928
42 1931
42 1934
42 1937
42 1940
42 1943
42 1946
42 1949
42 1952
42 1955
42 1958
42 1961
42 1964
42 1967
42 1970
42 1973
42 1976
42 1979
42 1982
42 1985
42 1988
42 1991
42 1994
42 1997
42 2000




LOAD COMBINATIONS

LOADING CASE	DESCRIPTION	FORCES		MOMENTS
		F _x	F _z	M _y
I	DL, SWL, IMP. S/P	DL	28.25	-10.88
	100% FORCES	SWL	16.91	-129.70
		IMP		-8.09
				-38.43
	TOTAL	16.91	20.16	-179.01
	FOR 80'	1352.80	1612.80	-14,320.8
	+ ANCHOR FORCE	1920.8		-14036.8
II	DL, SWL, PER. S/P	DL	28.25	-10.88
	100% FORCES	SWL	16.91	-129.70
		PER		-11.03
				-27.58
	TOTAL	16.91	17.22	-108.16
	FOR 80'	1352.8	1377.6	-13,452.8
	+ ANCHOR FORCE	1920.8		-13,736.8
III	DL, SWL+2', IMP. S/P	DL	29.66	-8.06
	75% FORCES	SWL+2'	20.0	-166.60
		IMP		-8.80
				-41.80
		TOTAL	20.0	20.86
	75%	15.0	15.64	-162.34
	FOR 80'	1200.0	1251.6	-12,987.6
	+ 75% ANCHOR FORCE	1626.0		-13,200.6
IV	DL, SWL+2', PER. S/P	DL	29.66	-8.06
	75% FORCES	SWL+2'	20.00	-166.60
		PER		-12.00
				-30.00
		TOTAL	20.0	17.66
	75% TOTAL	15.0	13.24	-153.49
	FOR 80'	1200.0	1059.6	-12,279.6
	+ 75% ANCHOR FORCE	1626.0		-12,492.6
VA	DL, LOW WATER, IMP S/P	DL	21.56	-24.26
	100% FORCES	LOW WATER	5.83	-26.24
		IMP		-4.75
				-22.56
	TOTAL	5.83	16.81	-73.06
	FOR 80'	466.4	1344.8	-5844.8
	+ ANCHOR FORCE	1034.4		-5560.8
VB	DL, LOW WATER, PER S/P	DL	21.56	-24.26
	100% FORCES	LOW WATER	5.83	-26.24
		PER		-6.48
				-16.20
	TOTAL	5.83	15.08	-66.7
	FOR 80'	466.4	1206.4	-5336.0
	+ ANCHOR FORCE	1034.4		-5620
VI	DL, LOW WATER, IMP S/P, WIND	DL	21.56	-24.26
	75% FORCES	LOW WATER	5.83	-26.24
		IMP		-4.75
		WIND	0.58	-11.17
		TOTAL	6.41	16.81
	75%	4.81	12.61	-63.17
	FOR 80'	384.6	1008.6	-5053.8

+ 75% ANCHOR FORCE
F_x = 810.0
M_y = -5266.8

500 SHEETS PER 4 SQUARE
500 SHEETS PER 4 SQUARE
100 SHEETS PER 4 SQUARE
100 SHEETS PER 4 SQUARE
200 SHEETS PER 4 SQUARE
200 SHEETS PER 4 SQUARE
42,389 200 RECYCLED WHITE 5 SQUARE
42,389 200 RECYCLED WHITE 5 SQUARE
MADE IN U.S.A.





STRATA NO.	SOIL TYPE	UNIT WEIGHT PCF	UNFACTORED		SAFETY FACTOR C = 1.3			
			FRICTION ANGLE DEGREES	COHESION - PSF		FRICTION ANGLE DEGREES	COHESION - PSF	
				AVERAGE	BOTTOM		AVERAGE	BOTTOM
①	SAND	120	30	0	0	24	0	0
②	CLAY	94	0	220	220	0	169	169
③	CLAY CLAYEY SILT	107	0	310	400	0	238	308
④	CLAY	102	0	400	400	0	308	308
⑤	CLAY	97.5	0	400	400	0	308	308
⑥	CLAY	97.5	0	485	570	0	373	438
⑦	CLAY	97.5	0	655	740	0	504	569

T - WALL ANALYSIS					
SUMMATION OF FORCES (USING FACTORED SHEAR STRENGTHS)					
FAILURE SURFACE		ΣR RESISTANCE LBS/FT	ΣD DRIVING LBS/FT	ΣR - ΣD	EQUIVALENT PRESSURE PSF
(A) ①		3734	10455	-6721	-
(B) ②		10586	24499	-13913	-7192
(C) ③		39230	53798	-14568	-655
(D) ④		57127	65184	-8057	6511


- NOTE : 1) TO SATISFY MOMENT EQUILIBRIUM, SUMMING MOMENTS ABOUT BASE OF FOOTING AT EL. -13.0, REQUIRES SHEET PENETRATION TO EL. -46.0.
 2) MAXIMUM MOMENT OCCURS AT EL. -23.0 AND IS 34.9 FT. KIPS/FT OF WALL.
 3) CALCULATED ANCHOR FORCE, F_A , IS 7.1 KIPS/FT OF WALL AT EL. -13.0.

STABILITY OF PUMP STATION			
FAILURE SURFACE	SUMMATION OF FORCES		FACTOR OF SAFETY
	RESISTING	DRIVING	
(E) ⑤	25801	19615	1.32
(F) ⑥	43575	22636	1.93

* USING UNFACTORED SOIL PARAMETERS

- 4) THE ANCHOR LOAD AND INDICATED T-WALL PRESSURE MUST BE SUPPORTED BY DRIVEN BATTER PILES. AXIAL CAPACITY OF THESE BATTER PILES MUST IGNORE CAPACITY CONTRIBUTION ABOVE EL. -46.0.
 5) USING THE HARR METHOD OF SEEPAGE ANALYSIS, FACTOR OF SAFETY AGAINST PIPING FAILURE IS 4.5 OR MORE IF THE T-WALL CUTOFF SHEETPILE IS DRIVEN TO EL. -46.0.

6) SOIL PARAMETERS ARE TAKEN FROM FIGURE 6 OF EUSTIS ENGINEERING REPORT DATED 7 OCTOBER 1997 FOR SUBJECT PROJECT.



SLOPE STABILITY ANALYSIS AND PROPOSED T-WALL ANALYSES EXISTING NORTH PUMP STATION
 WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA

**WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA**

**MODULUS OF HORIZONTAL SUBGRADE REACTION
 COUSINS PUMP STATION TO DESTREHAN AVENUE BRIDGE**

PRELIMINARY

ELEVATION IN FEET	$K_h \times B$
0 to -6	114
-6 to -10	103
-10 to -23	97
-23 to -36	136
-36 to -45	176
-45 to -62	251
-62 to -69	11,790
-69 to -75	418
-75 to -86	24,150

- Where:
- K_h = Modulus of horizontal subgrade reaction (lbs/in.³)
 - B = Diameter of pile (inches)
 - C = Reduction factor for cyclic loading
 - C = 0.5 for cyclic loading
 - C = 1.0 for initial loading
 - D = Reduction factor for effect of group action

D	PILE SPACING IN DIRECTION OF LOADING
1.0	8B
0.85	7B
0.7	6B
0.55	5B
0.40	4B
0.25	3B

**WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA**

**ALLOWABLE PILE LOAD CAPACITIES
 NEW T-WALL FOUNDATION AT EXISTING NORTH PUMP STATION**

PILE DESCRIPTION	PILE TIP EMBEDMENT BELOW FOOTING TOP AT EL -11 IN FEET	ESTIMATED ALLOWABLE SINGLE PILE LOAD CAPACITY IN TONS FACTOR OF SAFETY = 2	
		COMPRESSION	TENSION
12-In. Square Precast, Prestressed Concrete Pile	65.5	36*	18
	72.5	50*	27
14-In. Square Precast, Prestressed Concrete Pile	65.5	44*	21
	72.5	61*	31
16-In. Square Precast, Prestressed Concrete Pile	65.5	53*	24
	72.5	73*	36

* Pile tips assumed to be bearing in sand

Note:

1. Capacity contribution above el -46 has been ignored.
2. Used soil parameters on Figure 6 of Eustis Engineering's report dated 7 October 1997 for the subject project.

AXIAL AND HORIZONTAL RESISTANCE OF BATTER PILES

ESTIMATED FROM ALLOWABLE VERTICAL LOAD CAPACITY

L = VERTICAL COMPONENT OF BATTER PILE EMBEDMENT LENGTH.

V = ESTIMATED ALLOWABLE SINGLE PILE LOAD CAPACITY OF A PILE DRIVEN VERTICALLY WITH EMBEDMENT LENGTH, L.

B = BATTER OF PILE EXPRESSED AS A RATIO OF VERTICAL DISTANCE TO ONE FOOT HORIZONTAL DISTANCE.

H = HORIZONTAL RESISTANCE OF BATTER PILE ESTIMATED AS FOLLOWS:

$$H = \frac{V}{B}$$

A = ALLOWABLE AXIAL PILE LOAD CAPACITY OF A SINGLE BATTER PILE ESTIMATED AS FOLLOWS:



$$A = \sqrt{V^2 \left(1 + \frac{1}{B^2}\right)} = \sqrt{(100)^2 \left(1 + \frac{1}{2^2}\right)} = \sqrt{100^2 \left(1 + \frac{1}{4}\right)} = \sqrt{125^2} = 125$$

Handwritten calculations:
 $125^2 = 15625$
 $15625 \times 1.25 = 19531.25$
 $\sqrt{19531.25} = 139.79$
 $136.4^2 = 18528.16$
 $1125^2 = 1265625$
 $1125^2 \times 1.25 = 1582031.25$
 $\sqrt{1582031.25} = 1258.18$


NOTE: THE AXIAL LOAD RESISTANCE OF A VERTICAL PILE, V, IS DEPENDENT ON THE TYPE OF LOADING--TENSION OR COMPRESSION. CAUTION SHOULD BE EXERCISED TO INSURE THAT THE CORRECT VERTICAL CAPACITY IS USED.

$$A_T = \sqrt{(62)^2 \left(1 + \frac{1}{2^2}\right)} = \sqrt{62^2 \times 1.25} = \sqrt{4754} = 68.96$$

Handwritten: $69.3^2 = 4796.49$



VECTOR DIAGRAM FOR TENSION PILE



VECTOR DIAGRAM FOR COMPRESSION PILE

SOIL CONSTANT

- PILE CAPACITY ABOVE EL. -46 HAS BEEN IGNORED.
SEE EUSTIS REPORT FOR DETAILS.

- CALCULATE ES USING WEIGHTED AVERAGE BELOW
EL. -46:

$$K_h * B = [(251)(16') + (11790)(7') + 418(6') + 24150(11)](1/40')$$

$$= 8867.6$$

C = 1.0

D = .44 (14" PILES)

ES = 8867.6(.44) = 3902 ksc (14" PILES)

D = .46 (16" PILES)

ES = 8867.6(.46) = 4079 ksc (16" PILES)

C = 73 * 2 = 146 } 16" PILES
T = 36 * 2 = 72

C = 61 * 2 = 122 } 14" PILES
T = 31 * 2 = 62

C = 1.0

D = 0.31 (14" PILES)

5' SPACING

AB = 5', B = 14'

A = 5(12) / 14
= 4.29

SPACING	D
4B	0.4
5B	0.55
4.29B	0.44

ES = 8867.6(.31)
= 2748.9 psc
= 2.75 ksc

C = 61 * 2 = 122 (72.5' *)
T = 31 * 2 = 62 (14" PILES)

4' SPACING

AB = 4', B = 14'

A = 4(12) / 14
= 3.43

spacing	D
4B	0.4
3B	0.25
3.43B	0.31

13 SHEETS, MILLER 2 SQUARE
14 SHEETS, MILLER 2 SQUARE
15 SHEETS, MILLER 2 SQUARE
16 SHEETS, MILLER 2 SQUARE
17 SHEETS, MILLER 2 SQUARE
18 SHEETS, MILLER 2 SQUARE
19 SHEETS, MILLER 2 SQUARE
20 SHEETS, MILLER 2 SQUARE
21 SHEETS, MILLER 2 SQUARE
22 SHEETS, MILLER 2 SQUARE
23 SHEETS, MILLER 2 SQUARE
24 SHEETS, MILLER 2 SQUARE
25 SHEETS, MILLER 2 SQUARE
26 SHEETS, MILLER 2 SQUARE
27 SHEETS, MILLER 2 SQUARE
28 SHEETS, MILLER 2 SQUARE
29 SHEETS, MILLER 2 SQUARE
30 SHEETS, MILLER 2 SQUARE
31 SHEETS, MILLER 2 SQUARE
32 SHEETS, MILLER 2 SQUARE
33 SHEETS, MILLER 2 SQUARE
34 SHEETS, MILLER 2 SQUARE
35 SHEETS, MILLER 2 SQUARE
36 SHEETS, MILLER 2 SQUARE
37 SHEETS, MILLER 2 SQUARE
38 SHEETS, MILLER 2 SQUARE
39 SHEETS, MILLER 2 SQUARE
40 SHEETS, MILLER 2 SQUARE
41 SHEETS, MILLER 2 SQUARE
42 SHEETS, MILLER 2 SQUARE
43 SHEETS, MILLER 2 SQUARE
44 SHEETS, MILLER 2 SQUARE
45 SHEETS, MILLER 2 SQUARE
46 SHEETS, MILLER 2 SQUARE
47 SHEETS, MILLER 2 SQUARE
48 SHEETS, MILLER 2 SQUARE
49 SHEETS, MILLER 2 SQUARE
50 SHEETS, MILLER 2 SQUARE
51 SHEETS, MILLER 2 SQUARE
52 SHEETS, MILLER 2 SQUARE
53 SHEETS, MILLER 2 SQUARE
54 SHEETS, MILLER 2 SQUARE
55 SHEETS, MILLER 2 SQUARE
56 SHEETS, MILLER 2 SQUARE
57 SHEETS, MILLER 2 SQUARE
58 SHEETS, MILLER 2 SQUARE
59 SHEETS, MILLER 2 SQUARE
60 SHEETS, MILLER 2 SQUARE
61 SHEETS, MILLER 2 SQUARE
62 SHEETS, MILLER 2 SQUARE
63 SHEETS, MILLER 2 SQUARE
64 SHEETS, MILLER 2 SQUARE
65 SHEETS, MILLER 2 SQUARE
66 SHEETS, MILLER 2 SQUARE
67 SHEETS, MILLER 2 SQUARE
68 SHEETS, MILLER 2 SQUARE
69 SHEETS, MILLER 2 SQUARE
70 SHEETS, MILLER 2 SQUARE
71 SHEETS, MILLER 2 SQUARE
72 SHEETS, MILLER 2 SQUARE
73 SHEETS, MILLER 2 SQUARE
74 SHEETS, MILLER 2 SQUARE
75 SHEETS, MILLER 2 SQUARE
76 SHEETS, MILLER 2 SQUARE
77 SHEETS, MILLER 2 SQUARE
78 SHEETS, MILLER 2 SQUARE
79 SHEETS, MILLER 2 SQUARE
80 SHEETS, MILLER 2 SQUARE
81 SHEETS, MILLER 2 SQUARE
82 SHEETS, MILLER 2 SQUARE
83 SHEETS, MILLER 2 SQUARE
84 SHEETS, MILLER 2 SQUARE
85 SHEETS, MILLER 2 SQUARE
86 SHEETS, MILLER 2 SQUARE
87 SHEETS, MILLER 2 SQUARE
88 SHEETS, MILLER 2 SQUARE
89 SHEETS, MILLER 2 SQUARE
90 SHEETS, MILLER 2 SQUARE
91 SHEETS, MILLER 2 SQUARE
92 SHEETS, MILLER 2 SQUARE
93 SHEETS, MILLER 2 SQUARE
94 SHEETS, MILLER 2 SQUARE
95 SHEETS, MILLER 2 SQUARE
96 SHEETS, MILLER 2 SQUARE
97 SHEETS, MILLER 2 SQUARE
98 SHEETS, MILLER 2 SQUARE
99 SHEETS, MILLER 2 SQUARE
100 SHEETS, MILLER 2 SQUARE




PILE LAYOUT:

BATTER 2
ANGLE 0

BATTER 2
ANGLE 180

P/S

F/S



#	F/S	Y
1		-38
2		-34
3		-30
4		-26
5		-22
6		-18
7		-14
8		-10
9		-6
10		-2
11		+2
12		+6
13		+10
14		+14
15		+18
16		+22
17		+26
18		+30
19		+34
20	+6	+38
21	+2	+34
22		+30
23		+26
24		+22
25		+18
26		+14
27		+10
28		+6
29		+2
30	+2	+2
31	-6	-2
32		-6
33		-10
34		-14
35		-18
36		-22
37		-26
38		-30
39		-34
40		-38
41		-42
42		-46
43		-50
44		-54
45		-58
46		-62
47		-66
48		-70
49		-74
50		-78
51		-82
52		-86
53		-90
54		-94
55		-98
56		-102
57		-106
58		-110
59		-114
60		-118
61		-122
62		-126
63		-130
64		-134
65		-138

500 SHEETS FULL SIZE SQUARE
 50 SHEETS HALF SIZE SQUARE
 100 SHEETS QUARTER SIZE SQUARE
 100 SHEETS EIGHTH SIZE SQUARE
 100 SHEETS SIXTEENTH SIZE SQUARE
 100 SHEETS THIRTYSECOND SIZE SQUARE
 200 RECYCLED SHEET PAPER
 Made in U.S.A.



H x
 0
 +22
 +26
 +30
 +34
 +38
 -6

32.9"

32.5"

20 10

~~30~~
~~21~~

1010 COUSINS PUMP STATION FRONTAL PROTECTION TWALL
1020 PROP 4030 3201 3201 196 2 0 ALL
1030 SOIL ES 2.75 LEN 73 0 ALL
1040 PIN ALL
1050 DLS S 98 47 600.2 223.1 132.6 1510 1166.8 H 14 ALL
1060 ASC S 196 457 0.816 0.856 2 0 ALL
1070 BATTER 2 ALL
1080 ANGLE 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
1085 ANGLE 0 16 17 18 19 20
1090 ANGLE 0 21 22 23 24 25 26 27 28 29 30
1100 ANGLE 180 31 32 33 34 35 36 37 38 39 40
1105 ANGLE 180 41 42 43 44 45 46 47 48 49 50 51 52
1110 PILE 1 6 -38 0
1111 PILE 2 6 -34 0
1112 PILE 3 6 -30 0
1113 PILE 4 6 -26 0
1114 PILE 5 6 -22 0
1120 PILE 6 6 -18 0
1121 PILE 7 6 -14 0
1122 PILE 8 6 -10 0
1123 PILE 9 6 -6 0
1124 PILE 10 6 -2 0
1130 PILE 11 6 2 0
1131 PILE 12 6 6 0
1132 PILE 13 6 10 0
1133 PILE 14 6 14 0
1134 PILE 15 6 18 0
1140 PILE 16 6 22 0
1141 PILE 17 6 26 0
1142 PILE 18 6 30 0
1143 PILE 19 6 34 0
1144 PILE 20 6 38 0
1150 PILE 21 2 -36 0
1151 PILE 22 2 -28 0
1152 PILE 23 2 -20 0
1153 PILE 24 2 -12 0
1154 PILE 25 2 -4 0
1160 PILE 26 2 4 0
1161 PILE 27 2 12 0
1162 PILE 28 2 20 0
1163 PILE 29 2 28 0
1164 PILE 30 2 36 0
1170 PILE 31 -6 -36.75 0
1171 PILE 32 -6 -33.25 0
1172 PILE 33 -6 -29.75 0
1173 PILE 34 -6 -26.25 0
1174 PILE 35 -6 -22.75 0
1180 PILE 36 -6 -19.25 0
1181 PILE 37 -6 -15.75 0
1182 PILE 38 -6 -12.25 0
1183 PILE 39 -6 -8.75 0
1184 PILE 40 -6 -5.25 0
1190 PILE 41 -6 -1.75 0
1191 PILE 42 -6 1.75 0
1192 PILE 43 -6 5.25 0
1193 PILE 44 -6 8.75 0
1194 PILE 45 -6 12.25 0
1200 PILE 46 -6 15.75 0
1201 PILE 47 -6 19.25 0
1202 PILE 48 -6 22.75 0

1203 PILE 49 -6 26.25 0
1204 PILE 50 -6 29.75 0
1205 PILE 51 -6 33.25 0
1206 PILE 52 -6 36.75 0
1210 LOAD 1 1920.8 0 1612.8 0 -14036.8 0
1220 LOAD 2 1920.8 0 1377.6 0 -13736.8 0
1230 LOAD 3 1626.0 0 1251.6 0 -13200.6 0
1240 LOAD 4 1626.0 0 1059.6 0 -12492.6 0
1250 LOAD 5 1034.4 0 1344.8 0 -5560.8 0
1260 LOAD 6 1034.4 0 1206.4 0 -5620.0 0
1270 LOAD 7 810.6 0 1008.6 0 -5266.8 0
1280 FOUT 1 2 3 4 5 6 7 CPSOUT1
1290 PFO ALL
1300 FPL CPSOUT2

 * CORPS PROGRAM # X0080 * CPGA - CASE PILE GROUP ANALYSIS PROGRAM
 * VERSION NUMBER # 86/09/02-A * RUN DATE 01-19-98 RUN TIME 15:43:00

COUSINS PUMP STATION FRONTAL PROTECTION TWALL

THERE ARE 52 PILES AND
 7 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = { $\begin{matrix} X & Y & Z \\ \hline -6.00 & -38.00 & .00 \\ 6.00 & 38.00 & .00 \end{matrix}$ }

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40300E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -

ALL

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2		FT	FT
	.27500E+01	L	.73000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -

ALL

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X	Y	Z	BATTER	ANGLE	LENGTH	FIXITY
	FT	FT	FT			FT	
1	6.00	-38.00	.00	2.00	.00	73.00	P
2	6.00	-34.00	.00	2.00	.00	73.00	PP
3	6.00	-30.00	.00	2.00	.00	73.00	PP
4	6.00	-26.00	.00	2.00	.00	73.00	PP
5	6.00	-22.00	.00	2.00	.00	73.00	PP
6	6.00	-18.00	.00	2.00	.00	73.00	P

7	6.00	-14.00	.00	2.00	.00	73.00	P
8	6.00	-10.00	.00	2.00	.00	73.00	P
9	6.00	-6.00	.00	2.00	.00	73.00	P
10	6.00	-2.00	.00	2.00	.00	73.00	P
11	6.00	2.00	.00	2.00	.00	73.00	P
12	6.00	6.00	.00	2.00	.00	73.00	P
13	6.00	10.00	.00	2.00	.00	73.00	P
14	6.00	14.00	.00	2.00	.00	73.00	P
15	6.00	18.00	.00	2.00	.00	73.00	P
16	6.00	22.00	.00	2.00	.00	73.00	P
17	6.00	26.00	.00	2.00	.00	73.00	P
18	6.00	30.00	.00	2.00	.00	73.00	P
19	6.00	34.00	.00	2.00	.00	73.00	P
20	6.00	38.00	.00	2.00	.00	73.00	P
21	2.00	-36.00	.00	2.00	.00	73.00	P
22	2.00	-28.00	.00	2.00	.00	73.00	P
23	2.00	-20.00	.00	2.00	.00	73.00	P
24	2.00	-12.00	.00	2.00	.00	73.00	P
25	2.00	-4.00	.00	2.00	.00	73.00	P
26	2.00	4.00	.00	2.00	.00	73.00	P
27	2.00	12.00	.00	2.00	.00	73.00	P
28	2.00	20.00	.00	2.00	.00	73.00	P
29	2.00	28.00	.00	2.00	.00	73.00	P
30	2.00	36.00	.00	2.00	.00	73.00	P
31	-6.00	-36.75	.00	2.00	180.00	73.00	P
32	-6.00	-33.25	.00	2.00	180.00	73.00	P
33	-6.00	-29.75	.00	2.00	180.00	73.00	P
34	-6.00	-26.25	.00	2.00	180.00	73.00	P
35	-6.00	-22.75	.00	2.00	180.00	73.00	P
36	-6.00	-19.25	.00	2.00	180.00	73.00	P
37	-6.00	-15.75	.00	2.00	180.00	73.00	P
38	-6.00	-12.25	.00	2.00	180.00	73.00	P
39	-6.00	-8.75	.00	2.00	180.00	73.00	P
40	-6.00	-5.25	.00	2.00	180.00	73.00	P
41	-6.00	-1.75	.00	2.00	180.00	73.00	P
42	-6.00	1.75	.00	2.00	180.00	73.00	P
43	-6.00	5.25	.00	2.00	180.00	73.00	P
44	-6.00	8.75	.00	2.00	180.00	73.00	P
45	-6.00	12.25	.00	2.00	180.00	73.00	P
46	-6.00	15.75	.00	2.00	180.00	73.00	P
47	-6.00	19.25	.00	2.00	180.00	73.00	P
48	-6.00	22.75	.00	2.00	180.00	73.00	P
49	-6.00	26.25	.00	2.00	180.00	73.00	P
50	-6.00	29.75	.00	2.00	180.00	73.00	P
51	-6.00	33.25	.00	2.00	180.00	73.00	P
52	-6.00	36.75	.00	2.00	180.00	73.00	P

3796.00

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	1920.8	.0	1612.8	.0	-14036.8	.0
2	1920.8	.0	1377.6	.0	-13736.8	.0
3	1626.0	.0	1251.6	.0	-13200.6	.0

4	1626.0	.0	1059.6	.0	-12492.6	.0
5	1034.4	.0	1344.8	.0	-5560.8	.0
6	1034.4	.0	1206.4	.0	-5620.0	.0
7	810.6	.0	1008.6	.0	-5266.8	.0

ORIGINAL PILE GROUP STIFFNESS MATRIX

.22520E+05	.65888E-03	.54812E+04	.21875E+00	-.22363E+07	.10938E+00
.65888E-03	.47058E+04	-.13178E-02	.00000E+00	-.94878E-01	.86877E+04
.54812E+04	-.13178E-02	.75962E+05	-.18750E+00	-.14024E+06	.31250E-01
.18750E+00	.00000E+00	-.18750E+00	.56307E+10	-.80000E+01	-.50048E+09
-.22363E+07	-.94878E-01	-.14024E+06	-.28000E+02	.32647E+09	.10000E+02
-.31250E-01	.86877E+04	-.62500E-01	-.50048E+09	.14000E+02	.16895E+10

LOAD CASE 1. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 2. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 3. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 4. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 5. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 6. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.
 LOAD CASE 7. NUMBER OF FAILURES = 0. NUMBER OF PILES IN TENSION = 22.

PILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.9741E-01	-.6404E-08	.1449E-01	-.2509E-11	.1576E-03	.3221E-12
2	.1030E+00	-.7176E-08	.1108E-01	-.2784E-11	.2052E-03	-.1737E-12
3	.6787E-01	-.6580E-08	.1155E-01	-.1780E-11	-.1537E-04	.1316E-11
4	.7788E-01	-.6961E-08	.8473E-02	-.2156E-11	.7793E-04	.5054E-12
5	.7198E-01	-.4877E-09	.1305E-01	-.1643E-11	.2943E-03	-.1108E-11
6	.7247E-01	-.1068E-08	.1120E-01	-.1728E-11	.2946E-03	-.1193E-11
7	.4605E-01	-.1050E-08	.1019E-01	-.1025E-11	.1262E-03	-.1157E-12

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES
 * INDICATES PILE FAILURE
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3*EMIN) FOR CONCRETE PILES
 B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
2	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
3	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
4	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
5	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
6	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
7	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
8	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
9	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
10	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
11	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
12	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
13	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
14	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
15	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
16	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
17	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
18	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
19	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
20	7.8	.0	83.6	.0	-164.4	.0	.85	.49	1.64	.88
21	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
22	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
23	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
24	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
25	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
26	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
27	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
28	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
29	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
30	7.55	.0	95.88	.0	-157.9	.0	.98	.55	1.69	.96
31	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
32	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
33	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
34	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
35	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
36	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
37	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
38	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
39	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
40	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
41	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
42	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
43	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
44	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
45	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
46	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
47	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
48	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
49	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
50	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
51	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21
52	-8.9	.0	-36.9	.0	189.3	.0	.78	.88	1.08	.21

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
2	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
3	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
4	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
5	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
6	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
7	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
8	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
9	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
10	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
11	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
12	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
13	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
14	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
15	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
16	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
17	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
18	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
19	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
20	8.5	.0	77.1	.0	-179.8	.0	.79	.48	1.64	.82
21	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
22	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
23	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
24	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
25	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
26	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
27	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
28	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
29	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
30	8.1	.0	93.0	.0	-171.4	.0	.95	.56	1.71	.92
31	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
32	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
33	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
34	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
35	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
36	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
37	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
38	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
39	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
40	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
41	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
42	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
43	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
44	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
45	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
46	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
47	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
48	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
49	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
50	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
51	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17
52	-9.4	.0	-41.3	.0	198.8	.0	.88	.96	1.08	.17

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
2	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
3	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
4	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
5	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
6	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
7	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
8	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
9	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
10	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
11	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
12	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
13	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
14	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
15	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
16	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
17	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
18	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
19	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
20	5.0	.0	75.2	.0	-105.6	.0	.77	.34	1.47	.97
21	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
22	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
23	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
24	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
25	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
26	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
27	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
28	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
29	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
30	5.0	.0	74.0	.0	-106.2	.0	.75	.33	1.47	.96
31	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
32	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
33	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
34	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
35	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
36	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
37	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
38	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
39	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
40	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
41	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
42	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
43	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
44	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
45	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
46	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
47	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
48	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
49	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
50	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
51	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35
52	5.0	.0	-37.9	.0	125.4	.0	.81	.75	.94	.35

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
2	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
3	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
4	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
5	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
6	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
7	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
8	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
9	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
10	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
11	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
12	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
13	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
14	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
15	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
16	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
17	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
18	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
19	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
20	6.2	.0	67.4	.0	-131.1	.0	.69	.34	1.49	.87
21	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
22	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
23	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
24	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
25	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
26	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
27	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
28	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
29	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
30	6.0	.0	73.5	.0	-127.9	.0	.75	.37	1.51	.91
31	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
32	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
33	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
34	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
35	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
36	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
37	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
38	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
39	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
40	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
41	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
42	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
43	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
44	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
45	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
46	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
47	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
48	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
49	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
50	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
51	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29
52	-6.9	.0	-40.1	.0	145.7	.0	.85	.82	.97	.29

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
2	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
3	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
4	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
5	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
6	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
7	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
8	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
9	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
10	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
11	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
12	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
13	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
14	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
15	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
16	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
17	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
18	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
19	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
20	6.2	.0	44.9	.0	-130.4	.0	.46	.25	1.37	.76
21	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
22	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
23	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
24	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
25	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
26	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
27	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
28	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
29	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
30	5.6	.0	67.7	.0	-118.3	.0	.69	.32	1.46	.90
31	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
32	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
33	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
34	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
35	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
36	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
37	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
38	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
39	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
40	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
41	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
42	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
43	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
44	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
45	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
46	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
47	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
48	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
49	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
50	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
51	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47
52	-7.2	.0	-2.8	.0	152.8	.0	.06	.39	1.18	.47

LOAD CASE - 6

PILE F1 F2 F3 M1 M2 M3 ALF CBF ASC AST

	K	K	K	IN-K	IN-K	IN-K			KSI	KSI
1	6.3	.0	42.3	.0	-132.9	.0	.43	.27	1.36	.74
2	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
3	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
4	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
5	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
6	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
7	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
8	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
9	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
10	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
11	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
12	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
13	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
14	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
15	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
16	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
17	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
18	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
19	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
20	6.3	.00	42.3	.00	-132.9	.00	.43	.27	1.36	.74
21	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
22	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
23	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
24	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
25	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
26	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
27	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
28	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
29	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
30	5.7	.00	65.1	.00	-120.8	.00	.66	.31	1.45	.88
31	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
32	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
33	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
34	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
35	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
36	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
37	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
38	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
39	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
40	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
41	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
42	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
43	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
44	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
45	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
46	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
47	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
48	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
49	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
50	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
51	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45
52	-7.2	.00	-6.2	.00	152.1	.00	.13	.43	1.16	.45

LOAD CASE - 7

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
------	---------	---------	---------	------------	------------	------------	-----	-----	------------	------------

1	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
2	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
3	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
4	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
5	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
6	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
7	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
8	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
9	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
10	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
11	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
12	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
13	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
14	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
15	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
16	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
17	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
18	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
19	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
20	3.7	.0	38.9	.0	-78.1	.0	.40	.19	1.23	.84
21	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
22	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
23	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
24	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
25	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
26	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
27	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
28	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
29	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
30	3.4	.0	48.7	.0	-72.9	.0	.50	.13	1.26	.90
31	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
32	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
33	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
34	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
35	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
36	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
37	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
38	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
39	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
40	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
41	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
42	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
43	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
44	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
45	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
46	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
47	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
48	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
49	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
50	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
51	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58
52	-4.5	.0	-6.0	.0	95.5	.0	.13	.29	1.03	.58

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	44.3	.0	71.3	.0	.0	.0
2	44.3	.0	71.3	.0	.0	.0
3	44.3	.0	71.3	.0	.0	.0
4	44.3	.0	71.3	.0	.0	.0
5	44.3	.0	71.3	.0	.0	.0
6	44.3	.0	71.3	.0	.0	.0
7	44.3	.0	71.3	.0	.0	.0
8	44.3	.0	71.3	.0	.0	.0
9	44.3	.0	71.3	.0	.0	.0
10	44.3	.0	71.3	.0	.0	.0
11	44.3	.0	71.3	.0	.0	.0
12	44.3	.0	71.3	.0	.0	.0
13	44.3	.0	71.3	.0	.0	.0
14	44.3	.0	71.3	.0	.0	.0
15	44.3	.0	71.3	.0	.0	.0
16	44.3	.0	71.3	.0	.0	.0
17	44.3	.0	71.3	.0	.0	.0
18	44.3	.0	71.3	.0	.0	.0
19	44.3	.0	71.3	.0	.0	.0
20	44.3	.0	71.3	.0	.0	.0
21	49.5	.0	82.4	.0	.0	.0
22	49.5	.0	82.4	.0	.0	.0
23	49.5	.0	82.4	.0	.0	.0
24	49.5	.0	82.4	.0	.0	.0
25	49.5	.0	82.4	.0	.0	.0
26	49.5	.0	82.4	.0	.0	.0
27	49.5	.0	82.4	.0	.0	.0
28	49.5	.0	82.4	.0	.0	.0
29	49.5	.0	82.4	.0	.0	.0
30	49.5	.0	82.4	.0	.0	.0
31	24.5	.0	-29.0	.0	.0	.0
32	24.5	.0	-29.0	.0	.0	.0
33	24.5	.0	-29.0	.0	.0	.0
34	24.5	.0	-29.0	.0	.0	.0
35	24.5	.0	-29.0	.0	.0	.0
36	24.5	.0	-29.0	.0	.0	.0
37	24.5	.0	-29.0	.0	.0	.0
38	24.5	.0	-29.0	.0	.0	.0
39	24.5	.0	-29.0	.0	.0	.0
40	24.5	.0	-29.0	.0	.0	.0
41	24.5	.0	-29.0	.0	.0	.0
42	24.5	.0	-29.0	.0	.0	.0
43	24.5	.0	-29.0	.0	.0	.0
44	24.5	.0	-29.0	.0	.0	.0
45	24.5	.0	-29.0	.0	.0	.0
46	24.5	.0	-29.0	.0	.0	.0
47	24.5	.0	-29.0	.0	.0	.0
48	24.5	.0	-29.0	.0	.0	.0
49	24.5	.0	-29.0	.0	.0	.0
50	24.5	.0	-29.0	.0	.0	.0
51	24.5	.0	-29.0	.0	.0	.0
52	24.5	.0	-29.0	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	42.1	.0	65.2	.0	.0	.0
2	42.1	.00	65.2	.00	.00	.00
3	42.1	.00	65.2	.00	.00	.00
4	42.1	.00	65.2	.00	.00	.00
5	42.1	.00	65.2	.00	.00	.00
6	42.1	.00	65.2	.00	.00	.00
7	42.1	.00	65.2	.00	.00	.00
8	42.1	.00	65.2	.00	.00	.00
9	42.1	.00	65.2	.00	.00	.00
10	42.1	.00	65.2	.00	.00	.00
11	42.1	.00	65.2	.00	.00	.00
12	42.1	.00	65.2	.00	.00	.00
13	42.1	.00	65.2	.00	.00	.00
14	42.1	.00	65.2	.00	.00	.00
15	42.1	.00	65.2	.00	.00	.00
16	42.1	.00	65.2	.00	.00	.00
17	42.1	.00	65.2	.00	.00	.00
18	42.1	.00	65.2	.00	.00	.00
19	42.1	.00	65.2	.00	.00	.00
20	42.1	.00	65.2	.00	.00	.00
21	48.8	.00	79.6	.00	.00	.00
22	48.8	.00	79.6	.00	.00	.00
23	48.8	.00	79.6	.00	.00	.00
24	48.8	.00	79.6	.00	.00	.00
25	48.8	.00	79.6	.00	.00	.00
26	48.8	.00	79.6	.00	.00	.00
27	48.8	.00	79.6	.00	.00	.00
28	48.8	.00	79.6	.00	.00	.00
29	48.8	.00	79.6	.00	.00	.00
30	48.8	.00	79.6	.00	.00	.00
31	26.9	.00	-32.8	.00	.00	.00
32	26.9	.00	-32.8	.00	.00	.00
33	26.9	.00	-32.8	.00	.00	.00
34	26.9	.00	-32.8	.00	.00	.00
35	26.9	.00	-32.8	.00	.00	.00
36	26.9	.00	-32.8	.00	.00	.00
37	26.9	.00	-32.8	.00	.00	.00
38	26.9	.00	-32.8	.00	.00	.00
39	26.9	.00	-32.8	.00	.00	.00
40	26.9	.00	-32.8	.00	.00	.00
41	26.9	.00	-32.8	.00	.00	.00
42	26.9	.00	-32.8	.00	.00	.00
43	26.9	.00	-32.8	.00	.00	.00
44	26.9	.00	-32.8	.00	.00	.00
45	26.9	.00	-32.8	.00	.00	.00
46	26.9	.00	-32.8	.00	.00	.00
47	26.9	.00	-32.8	.00	.00	.00
48	26.9	.00	-32.8	.00	.00	.00
49	26.9	.00	-32.8	.00	.00	.00
50	26.9	.00	-32.8	.00	.00	.00
51	26.9	.00	-32.8	.00	.00	.00
52	26.9	.00	-32.8	.00	.00	.00

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	38.1	.0	65.0	.0	.0	.0
2	38.1	.00	65.00	.00	.00	.00
3	38.1	.00	65.00	.00	.00	.00
4	38.1	.00	65.00	.00	.00	.00
5	38.1	.00	65.00	.00	.00	.00
6	38.1	.00	65.00	.00	.00	.00
7	38.1	.00	65.00	.00	.00	.00
8	38.1	.00	65.00	.00	.00	.00
9	38.1	.00	65.00	.00	.00	.00
10	38.1	.00	65.00	.00	.00	.00
11	38.1	.00	65.00	.00	.00	.00
12	38.1	.00	65.00	.00	.00	.00
13	38.1	.00	65.00	.00	.00	.00
14	38.1	.00	65.00	.00	.00	.00
15	38.1	.00	65.00	.00	.00	.00
16	38.1	.00	65.00	.00	.00	.00
17	38.1	.00	65.00	.00	.00	.00
18	38.1	.00	65.00	.00	.00	.00
19	38.1	.00	65.00	.00	.00	.00
20	38.1	.00	65.00	.00	.00	.00
21	37.6	.00	63.9	.00	.00	.00
22	37.6	.00	63.9	.00	.00	.00
23	37.6	.00	63.9	.00	.00	.00
24	37.6	.00	63.9	.00	.00	.00
25	37.6	.00	63.9	.00	.00	.00
26	37.6	.00	63.9	.00	.00	.00
27	37.6	.00	63.9	.00	.00	.00
28	37.6	.00	63.9	.00	.00	.00
29	37.6	.00	63.9	.00	.00	.00
30	37.6	.00	63.9	.00	.00	.00
31	22.2	.00	-31.2	.00	.00	.00
32	22.2	.00	-31.2	.00	.00	.00
33	22.2	.00	-31.2	.00	.00	.00
34	22.2	.00	-31.2	.00	.00	.00
35	22.2	.00	-31.2	.00	.00	.00
36	22.2	.00	-31.2	.00	.00	.00
37	22.2	.00	-31.2	.00	.00	.00
38	22.2	.00	-31.2	.00	.00	.00
39	22.2	.00	-31.2	.00	.00	.00
40	22.2	.00	-31.2	.00	.00	.00
41	22.2	.00	-31.2	.00	.00	.00
42	22.2	.00	-31.2	.00	.00	.00
43	22.2	.00	-31.2	.00	.00	.00
44	22.2	.00	-31.2	.00	.00	.00
45	22.2	.00	-31.2	.00	.00	.00
46	22.2	.00	-31.2	.00	.00	.00
47	22.2	.00	-31.2	.00	.00	.00
48	22.2	.00	-31.2	.00	.00	.00
49	22.2	.00	-31.2	.00	.00	.00
50	22.2	.00	-31.2	.00	.00	.00
51	22.2	.00	-31.2	.00	.00	.00
52	22.2	.00	-31.2	.00	.00	.00

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	35.7	.0	57.5	.0	.0	.0
2	35.7	.00	57.5	.00	.00	.00
3	35.7	.00	57.5	.00	.00	.00
4	35.7	.00	57.5	.00	.00	.00
5	35.7	.00	57.5	.00	.00	.00
6	35.7	.00	57.5	.00	.00	.00
7	35.7	.00	57.5	.00	.00	.00
8	35.7	.00	57.5	.00	.00	.00
9	35.7	.00	57.5	.00	.00	.00
10	35.7	.00	57.5	.00	.00	.00
11	35.7	.00	57.5	.00	.00	.00
12	35.7	.00	57.5	.00	.00	.00
13	35.7	.00	57.5	.00	.00	.00
14	35.7	.00	57.5	.00	.00	.00
15	35.7	.00	57.5	.00	.00	.00
16	35.7	.00	57.5	.00	.00	.00
17	35.7	.00	57.5	.00	.00	.00
18	35.7	.00	57.5	.00	.00	.00
19	35.7	.00	57.5	.00	.00	.00
20	35.7	.00	57.5	.00	.00	.00
21	38.3	.00	63.0	.00	.00	.00
22	38.3	.00	63.0	.00	.00	.00
23	38.3	.00	63.0	.00	.00	.00
24	38.3	.00	63.0	.00	.00	.00
25	38.3	.00	63.0	.00	.00	.00
26	38.3	.00	63.0	.00	.00	.00
27	38.3	.00	63.0	.00	.00	.00
28	38.3	.00	63.0	.00	.00	.00
29	38.3	.00	63.0	.00	.00	.00
30	38.3	.00	63.0	.00	.00	.00
31	24.1	.00	-32.8	.00	.00	.00
32	24.1	.00	-32.8	.00	.00	.00
33	24.1	.00	-32.8	.00	.00	.00
34	24.1	.00	-32.8	.00	.00	.00
35	24.1	.00	-32.8	.00	.00	.00
36	24.1	.00	-32.8	.00	.00	.00
37	24.1	.00	-32.8	.00	.00	.00
38	24.1	.00	-32.8	.00	.00	.00
39	24.1	.00	-32.8	.00	.00	.00
40	24.1	.00	-32.8	.00	.00	.00
41	24.1	.00	-32.8	.00	.00	.00
42	24.1	.00	-32.8	.00	.00	.00
43	24.1	.00	-32.8	.00	.00	.00
44	24.1	.00	-32.8	.00	.00	.00
45	24.1	.00	-32.8	.00	.00	.00
46	24.1	.00	-32.8	.00	.00	.00
47	24.1	.00	-32.8	.00	.00	.00
48	24.1	.00	-32.8	.00	.00	.00
49	24.1	.00	-32.8	.00	.00	.00
50	24.1	.00	-32.8	.00	.00	.00
51	24.1	.00	-32.8	.00	.00	.00
52	24.1	.00	-32.8	.00	.00	.00

LOAD CASE - 5

PILE PX PY PZ MX MY MZ

	K	K	K	IN-K	IN-K	IN-K
1	25.6	.0	37.4	.0	.0	.0
2	25.6	.00	37.4	.00	.00	.00
3	25.6	.00	37.4	.00	.00	.00
4	25.6	.00	37.4	.00	.00	.00
5	25.6	.00	37.4	.00	.00	.00
6	25.6	.00	37.4	.00	.00	.00
7	25.6	.00	37.4	.00	.00	.00
8	25.6	.00	37.4	.00	.00	.00
9	25.6	.00	37.4	.00	.00	.00
10	25.6	.00	37.4	.00	.00	.00
11	25.6	.00	37.4	.00	.00	.00
12	25.6	.00	37.4	.00	.00	.00
13	25.6	.00	37.4	.00	.00	.00
14	25.6	.00	37.4	.00	.00	.00
15	25.6	.00	37.4	.00	.00	.00
16	25.6	.00	37.4	.00	.00	.00
17	25.6	.00	37.4	.00	.00	.00
18	25.6	.00	37.4	.00	.00	.00
19	25.6	.00	37.4	.00	.00	.00
20	25.6	.00	37.4	.00	.00	.00
21	35.3	.00	58.1	.00	.00	.00
22	35.3	.00	58.1	.00	.00	.00
23	35.3	.00	58.1	.00	.00	.00
24	35.3	.00	58.1	.00	.00	.00
25	35.3	.00	58.1	.00	.00	.00
26	35.3	.00	58.1	.00	.00	.00
27	35.3	.00	58.1	.00	.00	.00
28	35.3	.00	58.1	.00	.00	.00
29	35.3	.00	58.1	.00	.00	.00
30	35.3	.00	58.1	.00	.00	.00
31	7.7	.00	.7	.00	.00	.00
32	7.7	.00	.7	.00	.00	.00
33	7.7	.00	.7	.00	.00	.00
34	7.7	.00	.7	.00	.00	.00
35	7.7	.00	.7	.00	.00	.00
36	7.7	.00	.7	.00	.00	.00
37	7.7	.00	.7	.00	.00	.00
38	7.7	.00	.7	.00	.00	.00
39	7.7	.00	.7	.00	.00	.00
40	7.7	.00	.7	.00	.00	.00
41	7.7	.00	.7	.00	.00	.00
42	7.7	.00	.7	.00	.00	.00
43	7.7	.00	.7	.00	.00	.00
44	7.7	.00	.7	.00	.00	.00
45	7.7	.00	.7	.00	.00	.00
46	7.7	.00	.7	.00	.00	.00
47	7.7	.00	.7	.00	.00	.00
48	7.7	.00	.7	.00	.00	.00
49	7.7	.00	.7	.00	.00	.00
50	7.7	.00	.7	.00	.00	.00
51	7.7	.00	.7	.00	.00	.00
52	7.7	.0	.7	.0	.0	.0

LOAD CASE - 6

PILE PX K PY K PZ K MX IN-K MY IN-K MZ IN-K

1	24.5	.0	3	.0	.0	.0
2	24.5	.00	3	.00	.00	.00
3	24.5	.00	3	.00	.00	.00
4	24.5	.00	3	.00	.00	.00
5	24.5	.00	3	.00	.00	.00
6	24.5	.00	3	.00	.00	.00
7	24.5	.00	3	.00	.00	.00
8	24.5	.00	3	.00	.00	.00
9	24.5	.00	3	.00	.00	.00
10	24.5	.00	3	.00	.00	.00
11	24.5	.00	3	.00	.00	.00
12	24.5	.00	3	.00	.00	.00
13	24.5	.00	3	.00	.00	.00
14	24.5	.00	3	.00	.00	.00
15	24.5	.00	3	.00	.00	.00
16	24.5	.00	3	.00	.00	.00
17	24.5	.00	3	.00	.00	.00
18	24.5	.00	3	.00	.00	.00
19	24.5	.00	3	.00	.00	.00
20	24.5	.00	3	.00	.00	.00
21	34.2	.00	7	.00	.00	.00
22	34.2	.00	7	.00	.00	.00
23	34.2	.00	7	.00	.00	.00
24	34.2	.00	7	.00	.00	.00
25	34.2	.00	7	.00	.00	.00
26	34.2	.00	7	.00	.00	.00
27	34.2	.00	7	.00	.00	.00
28	34.2	.00	7	.00	.00	.00
29	34.2	.00	7	.00	.00	.00
30	34.2	.00	7	.00	.00	.00
31	9.2	.00	3	.00	.00	.00
32	9.2	.00	3	.00	.00	.00
33	9.2	.00	3	.00	.00	.00
34	9.2	.00	3	.00	.00	.00
35	9.2	.00	3	.00	.00	.00
36	9.2	.00	3	.00	.00	.00
37	9.2	.00	3	.00	.00	.00
38	9.2	.00	3	.00	.00	.00
39	9.2	.00	3	.00	.00	.00
40	9.2	.00	3	.00	.00	.00
41	9.2	.00	3	.00	.00	.00
42	9.2	.00	3	.00	.00	.00
43	9.2	.00	3	.00	.00	.00
44	9.2	.00	3	.00	.00	.00
45	9.2	.00	3	.00	.00	.00
46	9.2	.00	3	.00	.00	.00
47	9.2	.00	3	.00	.00	.00
48	9.2	.00	3	.00	.00	.00
49	9.2	.00	3	.00	.00	.00
50	9.2	.00	3	.00	.00	.00
51	9.2	.00	3	.00	.00	.00
52	9.2	.00	3	.00	.00	.00

LOAD CASE - 7
 PILE PX PY PZ MX MY MZ
 K K K K IN-K IN-K IN-K

1	20.7	.00	333.2	.00	.00	.00
2	20.7	.00	333.2	.00	.00	.00
3	20.7	.00	333.2	.00	.00	.00
4	20.7	.00	333.2	.00	.00	.00
5	20.7	.00	333.2	.00	.00	.00
6	20.7	.00	333.2	.00	.00	.00
7	20.7	.00	333.2	.00	.00	.00
8	20.7	.00	333.2	.00	.00	.00
9	20.7	.00	333.2	.00	.00	.00
10	20.7	.00	333.2	.00	.00	.00
11	20.7	.00	333.2	.00	.00	.00
12	20.7	.00	333.2	.00	.00	.00
13	20.7	.00	333.2	.00	.00	.00
14	20.7	.00	333.2	.00	.00	.00
15	20.7	.00	333.2	.00	.00	.00
16	20.7	.00	333.2	.00	.00	.00
17	20.7	.00	333.2	.00	.00	.00
18	20.7	.00	333.2	.00	.00	.00
19	20.7	.00	333.2	.00	.00	.00
20	20.7	.00	333.2	.00	.00	.00
21	24.8	.00	42.0	.00	.00	.00
22	24.8	.00	42.0	.00	.00	.00
23	24.8	.00	42.0	.00	.00	.00
24	24.8	.00	42.0	.00	.00	.00
25	24.8	.00	42.0	.00	.00	.00
26	24.8	.00	42.0	.00	.00	.00
27	24.8	.00	42.0	.00	.00	.00
28	24.8	.00	42.0	.00	.00	.00
29	24.8	.00	42.0	.00	.00	.00
30	24.8	.00	42.0	.00	.00	.00
31	6.7	.00	-3.4	.00	.00	.00
32	6.7	.00	-3.4	.00	.00	.00
33	6.7	.00	-3.4	.00	.00	.00
34	6.7	.00	-3.4	.00	.00	.00
35	6.7	.00	-3.4	.00	.00	.00
36	6.7	.00	-3.4	.00	.00	.00
37	6.7	.00	-3.4	.00	.00	.00
38	6.7	.00	-3.4	.00	.00	.00
39	6.7	.00	-3.4	.00	.00	.00
40	6.7	.00	-3.4	.00	.00	.00
41	6.7	.00	-3.4	.00	.00	.00
42	6.7	.00	-3.4	.00	.00	.00
43	6.7	.00	-3.4	.00	.00	.00
44	6.7	.00	-3.4	.00	.00	.00
45	6.7	.00	-3.4	.00	.00	.00
46	6.7	.00	-3.4	.00	.00	.00
47	6.7	.00	-3.4	.00	.00	.00
48	6.7	.00	-3.4	.00	.00	.00
49	6.7	.00	-3.4	.00	.00	.00
50	6.7	.00	-3.4	.00	.00	.00
51	6.7	.00	-3.4	.00	.00	.00
52	6.7	.00	-3.4	.00	.00	.00

VERTICAL PUMP STATION - DISCHARGE BASIN

PILE CAPACITY - (FROM EUSTIS PRELIM. REPORT)

PILE CUTOFF @ -13 N.G.V.D.

F.S. = 2.0

TREATED ASTM D25 TIMBER PILE	Length	Compression (TONS)	Tension (TONS)
7" Tip, 12" Butt	50'	14	9
	55'	17	11
	60'	20	13

EL. Water Surface = +2 N.G.V.D. (TOP OF DISCHARGE BASIN RET WALL)
 EL. INVERT = -11 N.G.V.D.

HEIGHT OF WATER = 13.0'

$$\begin{aligned} \text{wt(water)} &= (13.0)(1.0624) = 0.81 \text{ ksf} \\ \text{wt(slab)} &= (2.0)(1.150) = 0.30 \text{ ksf} \\ &= 1.11 \text{ ksf} \end{aligned}$$

for 60' piles: F.S. = 2.0

$$\text{AREA/PILE} = \frac{20 \times 2}{1.11} = 36.04 \text{ sf/pile}$$

$$\sqrt{36.04} = 6.00 - 6' \text{ GRID}$$

for 60' piles, F.S. = 3.0: Comp Cap = $20(2/3) = 13.33 \text{ TONS}$

$$\text{AREA/PILE} = \frac{13.33 \times 2}{1.11} = 24.02 \text{ sf/pile}$$

$$\sqrt{24.02} = 4.9 - 4'9" \text{ GRID}$$

17 787 50% WELLS FILLER 5 SQUARE
 42 381 40% WELLS FILLER 5 SQUARE
 42 382 10% WELLS FILLER 5 SQUARE
 42 383 10% WELLS FILLER 5 SQUARE
 42 384 10% WELLS FILLER 5 SQUARE
 42 385 10% WELLS FILLER 5 SQUARE
 42 386 10% WELLS FILLER 5 SQUARE
 42 387 10% WELLS FILLER 5 SQUARE
 42 388 10% WELLS FILLER 5 SQUARE
 42 389 10% WELLS FILLER 5 SQUARE
 42 390 10% WELLS FILLER 5 SQUARE
 42 391 10% WELLS FILLER 5 SQUARE
 42 392 10% WELLS FILLER 5 SQUARE
 42 393 10% WELLS FILLER 5 SQUARE
 42 394 10% WELLS FILLER 5 SQUARE
 42 395 10% WELLS FILLER 5 SQUARE
 42 396 10% WELLS FILLER 5 SQUARE
 42 397 10% WELLS FILLER 5 SQUARE
 42 398 10% WELLS FILLER 5 SQUARE
 42 399 10% WELLS FILLER 5 SQUARE
 42 400 10% WELLS FILLER 5 SQUARE
 Made in U.S.A.



TENSION :

GROUND WATER @ O.D, BASIN DRY

$$\begin{aligned} \text{UPLIFT} &= (11')(0.0624) = 0.6864 \text{ ksf } \uparrow \\ \text{SLAB} &= (2')(0.15 \cdot 0.0624) = 0.1752 \text{ ksf } \downarrow \end{aligned}$$

0.5112 ksf tension

$$\text{AREA/PILE} = \frac{13 \times 2}{.5112} = 50.86 \text{ sf/pile} \quad (\text{F.S.} = 2)$$

6' GRID CONTROLS

$$\text{F.S.} = 3, \text{ Capacity} = 13 \times \frac{2}{3} = 8.67 \text{ TONS}$$

$$\text{AREA/PILE} = \frac{8.67 \times 2}{.5112} = 33.92$$

4'9" GRID CONTROLS

SLAB: (DESIGN FOR 6' GRID)


-USE FLAT SLAB:

$$w_u = 1.11(1.2) = 1.33 \text{ ksf}$$

$$M_o = \frac{w l_2 l_n^2}{8} = \frac{1.33(6)(6)^2}{8} = 35.91 \text{ k}$$

$$M_{max Neg M} = 0.65 M_o = .65(35.91) = 23.34 \text{ k}$$

try 24" SLAB: $d = 21" (-M)$
 $d = 15" (+M)$




$$\begin{aligned} A_s(+M) &= \frac{M}{f_y z}, \quad z = 0.9d \\ &= \frac{(35.91)(12)}{48(.9)(15)} = 0.665 \text{ in}^2 \end{aligned}$$

$$A_s(-M) = \frac{(23.34)(12)}{48(.9)(21)} = 0.309 \text{ in}^2$$

40' SCH 40
 42' SCH 40
 44' SCH 40
 46' SCH 40
 48' SCH 40
 50' SCH 40
 52' SCH 40
 54' SCH 40
 56' SCH 40
 58' SCH 40
 60' SCH 40
 62' SCH 40
 64' SCH 40
 66' SCH 40
 68' SCH 40
 70' SCH 40
 72' SCH 40
 74' SCH 40
 76' SCH 40
 78' SCH 40
 80' SCH 40
 82' SCH 40
 84' SCH 40
 86' SCH 40
 88' SCH 40
 90' SCH 40
 92' SCH 40
 94' SCH 40
 96' SCH 40
 98' SCH 40
 100' SCH 40
 102' SCH 40
 104' SCH 40
 106' SCH 40
 108' SCH 40
 110' SCH 40
 112' SCH 40
 114' SCH 40
 116' SCH 40
 118' SCH 40
 120' SCH 40
 122' SCH 40
 124' SCH 40
 126' SCH 40
 128' SCH 40
 130' SCH 40
 132' SCH 40
 134' SCH 40
 136' SCH 40
 138' SCH 40
 140' SCH 40
 142' SCH 40
 144' SCH 40
 146' SCH 40
 148' SCH 40
 150' SCH 40
 152' SCH 40
 154' SCH 40
 156' SCH 40
 158' SCH 40
 160' SCH 40
 162' SCH 40
 164' SCH 40
 166' SCH 40
 168' SCH 40
 170' SCH 40
 172' SCH 40
 174' SCH 40
 176' SCH 40
 178' SCH 40
 180' SCH 40
 182' SCH 40
 184' SCH 40
 186' SCH 40
 188' SCH 40
 190' SCH 40
 192' SCH 40
 194' SCH 40
 196' SCH 40
 198' SCH 40
 200' SCH 40
 202' SCH 40
 204' SCH 40
 206' SCH 40
 208' SCH 40
 210' SCH 40
 212' SCH 40
 214' SCH 40
 216' SCH 40
 218' SCH 40
 220' SCH 40
 222' SCH 40
 224' SCH 40
 226' SCH 40
 228' SCH 40
 230' SCH 40
 232' SCH 40
 234' SCH 40
 236' SCH 40
 238' SCH 40
 240' SCH 40
 242' SCH 40
 244' SCH 40
 246' SCH 40
 248' SCH 40
 250' SCH 40
 252' SCH 40
 254' SCH 40
 256' SCH 40
 258' SCH 40
 260' SCH 40
 262' SCH 40
 264' SCH 40
 266' SCH 40
 268' SCH 40
 270' SCH 40
 272' SCH 40
 274' SCH 40
 276' SCH 40
 278' SCH 40
 280' SCH 40
 282' SCH 40
 284' SCH 40
 286' SCH 40
 288' SCH 40
 290' SCH 40
 292' SCH 40
 294' SCH 40
 296' SCH 40
 298' SCH 40
 300' SCH 40
 302' SCH 40
 304' SCH 40
 306' SCH 40
 308' SCH 40
 310' SCH 40
 312' SCH 40
 314' SCH 40
 316' SCH 40
 318' SCH 40
 320' SCH 40
 322' SCH 40
 324' SCH 40
 326' SCH 40
 328' SCH 40
 330' SCH 40
 332' SCH 40
 334' SCH 40
 336' SCH 40
 338' SCH 40
 340' SCH 40
 342' SCH 40
 344' SCH 40
 346' SCH 40
 348' SCH 40
 350' SCH 40
 352' SCH 40
 354' SCH 40
 356' SCH 40
 358' SCH 40
 360' SCH 40
 362' SCH 40
 364' SCH 40
 366' SCH 40
 368' SCH 40
 370' SCH 40
 372' SCH 40
 374' SCH 40
 376' SCH 40
 378' SCH 40
 380' SCH 40
 382' SCH 40
 384' SCH 40
 386' SCH 40
 388' SCH 40
 390' SCH 40
 392' SCH 40
 394' SCH 40
 396' SCH 40
 398' SCH 40
 400' SCH 40
 402' SCH 40
 404' SCH 40
 406' SCH 40
 408' SCH 40
 410' SCH 40
 412' SCH 40
 414' SCH 40
 416' SCH 40
 418' SCH 40
 420' SCH 40
 422' SCH 40
 424' SCH 40
 426' SCH 40
 428' SCH 40
 430' SCH 40
 432' SCH 40
 434' SCH 40
 436' SCH 40
 438' SCH 40
 440' SCH 40
 442' SCH 40
 444' SCH 40
 446' SCH 40
 448' SCH 40
 450' SCH 40
 452' SCH 40
 454' SCH 40
 456' SCH 40
 458' SCH 40
 460' SCH 40
 462' SCH 40
 464' SCH 40
 466' SCH 40
 468' SCH 40
 470' SCH 40
 472' SCH 40
 474' SCH 40
 476' SCH 40
 478' SCH 40
 480' SCH 40
 482' SCH 40
 484' SCH 40
 486' SCH 40
 488' SCH 40
 490' SCH 40
 492' SCH 40
 494' SCH 40
 496' SCH 40
 498' SCH 40
 500' SCH 40
 502' SCH 40
 504' SCH 40
 506' SCH 40
 508' SCH 40
 510' SCH 40
 512' SCH 40
 514' SCH 40
 516' SCH 40
 518' SCH 40
 520' SCH 40
 522' SCH 40
 524' SCH 40
 526' SCH 40
 528' SCH 40
 530' SCH 40
 532' SCH 40
 534' SCH 40
 536' SCH 40
 538' SCH 40
 540' SCH 40
 542' SCH 40
 544' SCH 40
 546' SCH 40
 548' SCH 40
 550' SCH 40
 552' SCH 40
 554' SCH 40
 556' SCH 40
 558' SCH 40
 560' SCH 40
 562' SCH 40
 564' SCH 40
 566' SCH 40
 568' SCH 40
 570' SCH 40
 572' SCH 40
 574' SCH 40
 576' SCH 40
 578' SCH 40
 580' SCH 40
 582' SCH 40
 584' SCH 40
 586' SCH 40
 588' SCH 40
 590' SCH 40
 592' SCH 40
 594' SCH 40
 596' SCH 40
 598' SCH 40
 600' SCH 40
 602' SCH 40
 604' SCH 40
 606' SCH 40
 608' SCH 40
 610' SCH 40
 612' SCH 40
 614' SCH 40
 616' SCH 40
 618' SCH 40
 620' SCH 40
 622' SCH 40
 624' SCH 40
 626' SCH 40
 628' SCH 40
 630' SCH 40
 632' SCH 40
 634' SCH 40
 636' SCH 40
 638' SCH 40
 640' SCH 40
 642' SCH 40
 644' SCH 40
 646' SCH 40
 648' SCH 40
 650' SCH 40
 652' SCH 40
 654' SCH 40
 656' SCH 40
 658' SCH 40
 660' SCH 40
 662' SCH 40
 664' SCH 40
 666' SCH 40
 668' SCH 40
 670' SCH 40
 672' SCH 40
 674' SCH 40
 676' SCH 40
 678' SCH 40
 680' SCH 40
 682' SCH 40
 684' SCH 40
 686' SCH 40
 688' SCH 40
 690' SCH 40
 692' SCH 40
 694' SCH 40
 696' SCH 40
 698' SCH 40
 700' SCH 40
 702' SCH 40
 704' SCH 40
 706' SCH 40
 708' SCH 40
 710' SCH 40
 712' SCH 40
 714' SCH 40
 716' SCH 40
 718' SCH 40
 720' SCH 40
 722' SCH 40
 724' SCH 40
 726' SCH 40
 728' SCH 40
 730' SCH 40
 732' SCH 40
 734' SCH 40
 736' SCH 40
 738' SCH 40
 740' SCH 40
 742' SCH 40
 744' SCH 40
 746' SCH 40
 748' SCH 40
 750' SCH 40
 752' SCH 40
 754' SCH 40
 756' SCH 40
 758' SCH 40
 760' SCH 40
 762' SCH 40
 764' SCH 40
 766' SCH 40
 768' SCH 40
 770' SCH 40
 772' SCH 40
 774' SCH 40
 776' SCH 40
 778' SCH 40
 780' SCH 40
 782' SCH 40
 784' SCH 40
 786' SCH 40
 788' SCH 40
 790' SCH 40
 792' SCH 40
 794' SCH 40
 796' SCH 40
 798' SCH 40
 800' SCH 40
 802' SCH 40
 804' SCH 40
 806' SCH 40
 808' SCH 40
 810' SCH 40
 812' SCH 40
 814' SCH 40
 816' SCH 40
 818' SCH 40
 820' SCH 40
 822' SCH 40
 824' SCH 40
 826' SCH 40
 828' SCH 40
 830' SCH 40
 832' SCH 40
 834' SCH 40
 836' SCH 40
 838' SCH 40
 840' SCH 40
 842' SCH 40
 844' SCH 40
 846' SCH 40
 848' SCH 40
 850' SCH 40
 852' SCH 40
 854' SCH 40
 856' SCH 40
 858' SCH 40
 860' SCH 40
 862' SCH 40
 864' SCH 40
 866' SCH 40
 868' SCH 40
 870' SCH 40
 872' SCH 40
 874' SCH 40
 876' SCH 40
 878' SCH 40
 880' SCH 40
 882' SCH 40
 884' SCH 40
 886' SCH 40
 888' SCH 40
 890' SCH 40
 892' SCH 40
 894' SCH 40
 896' SCH 40
 898' SCH 40
 900' SCH 40
 902' SCH 40
 904' SCH 40
 906' SCH 40
 908' SCH 40
 910' SCH 40
 912' SCH 40
 914' SCH 40
 916' SCH 40
 918' SCH 40
 920' SCH 40
 922' SCH 40
 924' SCH 40
 926' SCH 40
 928' SCH 40
 930' SCH 40
 932' SCH 40
 934' SCH 40
 936' SCH 40
 938' SCH 40
 940' SCH 40
 942' SCH 40
 944' SCH 40
 946' SCH 40
 948' SCH 40
 950' SCH 40
 952' SCH 40
 954' SCH 40
 956' SCH 40
 958' SCH 40
 960' SCH 40
 962' SCH 40
 964' SCH 40
 966' SCH 40
 968' SCH 40
 970' SCH 40
 972' SCH 40
 974' SCH 40
 976' SCH 40
 978' SCH 40
 980' SCH 40
 982' SCH 40
 984' SCH 40
 986' SCH 40
 988' SCH 40
 990' SCH 40
 992' SCH 40
 994' SCH 40
 996' SCH 40
 998' SCH 40
 1000' SCH 40
 1002' SCH 40
 1004' SCH 40
 1006' SCH 40
 1008' SCH 40
 1010' SCH 40
 1012' SCH 40
 1014' SCH 40
 1016' SCH 40
 1018' SCH 40
 1020' SCH 40
 1022' SCH 40
 1024' SCH 40
 1026' SCH 40
 1028' SCH 40
 1030' SCH 40
 1032' SCH 40
 1034' SCH 40
 1036' SCH 40
 1038' SCH 40
 1040' SCH 40
 1042' SCH 40
 1044' SCH 40
 1046' SCH 40
 1048' SCH 40
 1050' SCH 40
 1052' SCH 40
 1054' SCH 40
 1056' SCH 40
 1058' SCH 40
 1060' SCH 40
 1062' SCH 40
 1064' SCH 40
 1066' SCH 40
 1068' SCH 40
 1070' SCH 40
 1072' SCH 40
 1074' SCH 40
 1076' SCH 40
 1078' SCH 40
 1080' SCH 40
 1082' SCH 40
 1084' SCH 40
 1086' SCH 40
 1088' SCH 40
 1090' SCH 40
 1092' SCH 40
 1094' SCH 40
 1096' SCH 40
 1098' SCH 40
 1100' SCH 40
 1102' SCH 40
 1104' SCH 40
 1106' SCH 40
 1108' SCH 40
 1110' SCH 40
 1112' SCH 40
 1114' SCH 40
 1116' SCH 40
 1118' SCH 40
 1120' SCH 40
 1122' SCH 40
 1124' SCH 40
 1126' SCH 40
 1128' SCH 40
 1130' SCH 40
 1132' SCH 40
 1134' SCH 40
 1136' SCH 40
 1138' SCH 40
 1140' SCH 40
 1142' SCH 40
 1144' SCH 40
 1146' SCH 40
 1148' SCH 40
 1150' SCH 40
 1152' SCH 40
 1154' SCH 40
 1156' SCH 40
 1158' SCH 40
 1160' SCH 40
 1162' SCH 40
 1164' SCH 40
 1166' SCH 40
 1168' SCH 40
 1170' SCH 40
 1172' SCH 40
 1174' SCH 40
 1176' SCH 40
 1178' SCH 40
 1180' SCH 40
 1182' SCH 40
 1184' SCH 40
 1186' SCH 40
 1188' SCH 40
 1190' SCH 40
 1192' SCH 40
 1194' SCH 40
 1196' SCH 40
 1198' SCH 40
 1200' SCH 40
 1202' SCH 40
 1204' SCH 40
 1206' SCH 40
 1208' SCH 40
 1210' SCH 40
 1212' SCH 40
 1214' SCH 40
 1216' SCH 40
 1218' SCH 40
 1220' SCH 40
 1222' SCH 40
 1224' SCH 40
 1226' SCH 40
 1228' SCH 40
 1230' SCH 40
 1232' SCH 40
 1234' SCH 40
 1236' SCH 40
 1238' SCH 40
 1240' SCH 40
 1242' SCH 40
 1244' SCH 40
 1246' SCH 40
 1248' SCH 40
 1250' SCH 40
 1252' SCH 40
 1254' SCH 40
 1256' SCH 40
 1258' SCH 40
 1260' SCH 40
 1262' SCH 40
 1264' SCH 40
 1266' SCH 40
 1268' SCH 40
 1270' SCH 40
 1272' SCH 40
 1274' SCH 40
 1276' SCH 40
 1278' SCH 40
 1280' SCH 40
 1282' SCH 40
 1284' SCH 40
 1286' SCH 40
 1288' SCH 40
 1290' SCH 40
 1292' SCH 40
 1294' SCH 40
 1296' SCH 40
 1298' SCH 40
 1300' SCH 40
 1302' SCH 40
 1304' SCH 40
 1306' SCH 40
 1308' SCH 40
 1310' SCH 40
 1312' SCH 40
 1314' SCH 40
 1316' SCH 40
 1318' SCH 40
 1320' SCH 40
 1322' SCH 40
 1324' SCH 40
 1326' SCH 40
 1328' SCH 40
 1330' SCH 40
 1332' SCH 40
 1334' SCH 40
 1336' SCH 40
 1338' SCH 40
 1340' SCH 40
 1342' SCH 40
 1344' SCH 40
 1346' SCH 40
 1348' SCH 40
 1350' SCH 40
 1352' SCH 40
 1354' SCH 40
 1356' SCH 40
 1358' SCH 40
 1360' SCH 40
 1362' SCH 40
 1364' SCH 40
 1366' SCH 40
 1368' SCH 40
 1370' SCH 40
 1372' SCH 40
 1374' SCH 40
 1376' SCH 40
 1378' SCH 40
 1380' SCH 40
 1382' SCH 40
 1384' SCH 40
 1386' SCH 40
 1388' SCH 40
 1390' SCH 40
 1392' SCH 40
 1394' SCH 40
 1396' SCH 40
 1398' SCH 40
 1400' SCH 40
 1402' SCH 40
 1404' SCH 40
 1406' SCH 40
 1408' SCH 40
 1410' SCH 40
 1412' SCH 40
 1414' SCH 40
 1416' SCH 40
 1418' SCH 40
 1420' SCH 40
 1422' SCH 40
 1424' SCH 40
 1426' SCH 40
 1428' SCH 40
 1430' SCH 40
 1432' SCH 40
 1434' SCH 40
 1436' SCH 40
 1438' SCH 40
 1440' SCH 40
 1442' SCH 40
 1444' SCH 40
 1446' SCH 40
 1448' SCH 40
 1450' SCH 40
 1452' SCH 40
 1454' SCH 40
 1456' SCH 40
 1458' SCH 40
 1460' SCH 40
 1462' SCH 40
 1464' SCH 40
 1466' SCH 40
 1468' SCH 40
 1470' SCH 40
 1472' SCH 40
 1474' SCH 40
 1476' SCH 40
 1478' SCH 40
 1480' SCH 40
 1482' SCH 40
 1484' SCH 40
 1486' SCH 40
 1488' SCH 40
 1490' SCH 40
 1492' SCH 40
 1494' SCH 40
 1496' SCH 40
 1498' SCH 40
 1500' SCH 40
 1502' SCH 40
 1504' SCH 40
 1506' SCH 40
 1508' SCH 40
 1510' SCH 40
 1512' SCH 40
 1514' SCH 40
 1516' SCH 40
 1518' SCH 40
 1520' SCH 40
 1522' SCH 40
 1524' SCH 40
 1526' SCH 40
 1528' SCH 40
 1530' SCH 40
 1532' SCH 40
 1534' SCH 40
 1536' SCH 40
 1538' SCH 40
 1540' SCH 40
 1542' SCH 40
 1544' SCH 40
 1546' SCH 40
 1548' SCH 40
 1550' SCH 40
 1552' SCH 40
 1554' SCH 40
 1556' SCH 40
 1558' SCH 40
 1560' SCH 40
 1562' SCH 40
 1564' SCH 40
 1566' SCH 40
 1568' SCH 40
 1570' SCH 40
 1572' SCH 40
 1574' SCH 40
 1576' SCH 40
 1578' SCH 40
 1580' SCH 40
 1582' SCH 40
 1584' SCH 40
 1586' SCH 40
 1588' SCH 40
 1590' SCH 40
 1592' SCH 40
 1594' SCH 40
 1596' SCH 40
 1598' SCH 40
 1600' SCH 40
 1602' SCH 40
 1604' SCH 40
 1606' SCH 40
 1608' SCH 40
 1610' SCH 40
 1612' SCH 40
 1614' SCH 40
 1616' SCH 40
 1618' SCH 40
 1620' SCH 40
 1622' SCH 40
 1624' SCH 40
 1626' SCH 40
 1628' SCH 40
 1630' SCH 40
 1632' SCH 40
 1634' SCH 40
 1636' SCH 40
 1638' SCH 40
 1640' SCH 40
 1642' SCH 40
 1644' SCH 40
 1646' SCH 40
 1648' SCH 40
 1650' SCH 40
 1652' SCH 40
 1654' SCH 40
 1656' SCH 40
 1658' SCH 40

12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 68, 72, 76, 80, 84, 88, 92, 96, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 148, 152, 156, 160, 164, 168, 172, 176, 180, 184, 188, 192, 196, 200, 204, 208, 212, 216, 220, 224, 228, 232, 236, 240, 244, 248, 252, 256, 260, 264, 268, 272, 276, 280, 284, 288, 292, 296, 300, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 344, 348, 352, 356, 360, 364, 368, 372, 376, 380, 384, 388, 392, 396, 400, 404, 408, 412, 416, 420, 424, 428, 432, 436, 440, 444, 448, 452, 456, 460, 464, 468, 472, 476, 480, 484, 488, 492, 496, 500, 504, 508, 512, 516, 520, 524, 528, 532, 536, 540, 544, 548, 552, 556, 560, 564, 568, 572, 576, 580, 584, 588, 592, 596, 600, 604, 608, 612, 616, 620, 624, 628, 632, 636, 640, 644, 648, 652, 656, 660, 664, 668, 672, 676, 680, 684, 688, 692, 696, 700, 704, 708, 712, 716, 720, 724, 728, 732, 736, 740, 744, 748, 752, 756, 760, 764, 768, 772, 776, 780, 784, 788, 792, 796, 800, 804, 808, 812, 816, 820, 824, 828, 832, 836, 840, 844, 848, 852, 856, 860, 864, 868, 872, 876, 880, 884, 888, 892, 896, 900, 904, 908, 912, 916, 920, 924, 928, 932, 936, 940, 944, 948, 952, 956, 960, 964, 968, 972, 976, 980, 984, 988, 992, 996, 1000



$$A_{p,w} = (74)(\frac{1}{2}) = 111.0 \text{ in}^2$$

$$P = 44.1 + 9.7 = 53.8 \text{ k}$$

$$f_t = 53.8 / 111.0 = 0.48 \text{ ksi } \text{ok}$$

$$M = 7.4 \text{ k} (4') = 29.6 \text{ k-ft}$$

$$S = \frac{1}{6} b h^2 = \frac{1}{6} (74)(\frac{1}{2})^2 = 3.08 \text{ in}^3 \text{ N.G.}$$

$$f_b = 29.6(12) / 3.08 = 115.32 \text{ ksi } \text{N.G.}$$

$$S_{req'd} = \frac{M}{f_b} = 29.6(12) / 20 = 17.76 \text{ in}^3$$

$$S = \frac{1}{6} b h^2 = 17.76 = \frac{1}{6} (74)(h^2)$$

$$1.44 = h^2$$


$$1.2 = h$$

- use 1/2" R

$$S = \frac{1}{6} (74)(1.5)^2 = 27.75 \text{ in}^3$$

$$f_b = 29.6(12) / 27.75 = 12.8 \text{ ksi } \text{ok}$$

SUPPORT BEAM:



$$w = 14.68 / 3.17 = 4.63 \text{ k/ft}$$

$$M_{DL} = \frac{1}{8} (0.075) (10.5)^2 = 1.03 \text{ k} \quad (\text{Assumed } 75 \text{ #/ft})$$

$$M_1 = R_1 \left(a + \frac{R_1}{2w} \right)$$

$$= 8.39 \left(2.91 + \frac{8.39}{2(4.63)} \right)$$

$$= 32.02 \text{ k} + 1.03 = 33.05 \text{ k}$$

$$R_1 = \frac{wb}{2} (2c + b)$$

$$= \frac{(4.63)(3.17)}{2(10.5)} (2(4.47) + 3.17)$$

$$= 0.699(12)$$

$$= 8.39$$

$$M_2 = P \frac{L}{4} = 0.7(10.5)/4 = 1.84 \text{ k}$$

$$S_{REQ'D} = 33.05(12)/20 = 19.83 \text{ in}^3$$

$$W12 \times 40 \quad S_1 = 51.9 \quad S_2 = 11.0$$



$$f_{b1} = 33.05(12)/51.9 = 7.64 \text{ ksi}$$

$$f_{b2} = 1.84(12)/11 = 2.01 \text{ ksi}$$

$$\frac{7.64}{20} + \frac{2.01}{20} = 0.48 < 1.0 \text{ ok}$$

Check $\frac{1}{2}$ " R FOR T-WALL/DISCHARGE PIPE CONNECTION:

- use $\frac{7}{8}$ " R



$$M = \frac{1}{6}(0.0624)(5)^2$$

$$= 0.195 \text{ k} = 2.06 \text{ ft-k}$$

A36 steel $F_y = 20 \text{ ksi}$

$$\text{Req'd } S = \frac{(2.06)(12)}{20}$$

$$= 1.236 \text{ in}^3$$

$$S = \frac{1}{6}bh^2$$

$$h^2 = \frac{6S}{b}$$

$$\text{Req'd } h = \sqrt{\frac{6S}{b}}$$

$$= \sqrt{\frac{6(1.236)}{12}}$$

$$= 0.786$$

$\frac{1}{2}$ " R N.G. - use $\frac{7}{8}$ " R

DESIGN CALCULATIONS
DESTRAHAN BRIDGE EXTENSION

- LENGTHEN BRIDGE BY 1 - 60' SPAN:
- USE 5 TYPE III GIRDERS
- ASSUME 7" SLAB TO CHECK GIRDERS, VERIFY LATER.

DEAD LOAD: (GIRDER) : $\frac{(559.5)}{144} (.150) = 0.58 \text{ k/ft}$

DEAD LOAD : (SUPERIMPOSED)

INTERIOR GIRDER:

SLAB: $(\frac{7}{12})(6.5')(0.150) = 0.569$

HAUNCH: $(\frac{1.5}{12})(1.33)(0.150) = 0.025$

0.594

0.057

11%

+ 1/5 RAILINGS = $\frac{1}{5}(0.3 + 0.05) = 0.19$

0.653 k/ft

+ 0.19

0.843

EXTERIOR GIRDER:

SLAB: $(\frac{7}{12})(6.5 + 2.5)(0.150) = 0.505$

HAUNCH: $(\frac{1.5}{12})(3.417)(0.150) = 0.064$

0.567

10%

0.057

0.624 k/ft

+ 0.19

0.814

LIVE LOAD: (HS 20-44)

INTERIOR GIRDER:

WHEEL FACTOR: $S/5.5$, $S = 6.5$

L.A. WHEELS

$= 6.5/5.5 = 1.18 \text{ wheels/girder}$
 $= 0.59 \text{ lanes/girder}$

11, 11 1/2, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 44, 48, 54, 60, 66, 72, 84, 96, 108, 120, 132, 144, 156, 168, 180, 192, 210, 228, 240, 252, 264, 276, 288, 300, 312, 324, 336, 348, 360, 372, 384, 396, 408, 420, 432, 444, 456, 468, 480, 492, 504, 516, 528, 540, 552, 564, 576, 588, 600, 612, 624, 636, 648, 660, 672, 684, 696, 708, 720, 732, 744, 756, 768, 780, 792, 804, 816, 828, 840, 852, 864, 876, 888, 900, 912, 924, 936, 948, 960, 972, 984, 996, 1008, 1020, 1032, 1044, 1056, 1068, 1080, 1092, 1104, 1116, 1128, 1140, 1152, 1164, 1176, 1188, 1200, 1212, 1224, 1236, 1248, 1260, 1272, 1284, 1296, 1308, 1320, 1332, 1344, 1356, 1368, 1380, 1392, 1404, 1416, 1428, 1440, 1452, 1464, 1476, 1488, 1500, 1512, 1524, 1536, 1548, 1560, 1572, 1584, 1596, 1608, 1620, 1632, 1644, 1656, 1668, 1680, 1692, 1704, 1716, 1728, 1740, 1752, 1764, 1776, 1788, 1800, 1812, 1824, 1836, 1848, 1860, 1872, 1884, 1896, 1908, 1920, 1932, 1944, 1956, 1968, 1980, 1992, 2004, 2016, 2028, 2040, 2052, 2064, 2076, 2088, 2100, 2112, 2124, 2136, 2148, 2160, 2172, 2184, 2196, 2208, 2220, 2232, 2244, 2256, 2268, 2280, 2292, 2304, 2316, 2328, 2340, 2352, 2364, 2376, 2388, 2400, 2412, 2424, 2436, 2448, 2460, 2472, 2484, 2496, 2508, 2520, 2532, 2544, 2556, 2568, 2580, 2592, 2604, 2616, 2628, 2640, 2652, 2664, 2676, 2688, 2700, 2712, 2724, 2736, 2748, 2760, 2772, 2784, 2796, 2808, 2820, 2832, 2844, 2856, 2868, 2880, 2892, 2904, 2916, 2928, 2940, 2952, 2964, 2976, 2988, 3000, 3012, 3024, 3036, 3048, 3060, 3072, 3084, 3096, 3108, 3120, 3132, 3144, 3156, 3168, 3180, 3192, 3204, 3216, 3228, 3240, 3252, 3264, 3276, 3288, 3300, 3312, 3324, 3336, 3348, 3360, 3372, 3384, 3396, 3408, 3420, 3432, 3444, 3456, 3468, 3480, 3492, 3504, 3516, 3528, 3540, 3552, 3564, 3576, 3588, 3600, 3612, 3624, 3636, 3648, 3660, 3672, 3684, 3696, 3708, 3720, 3732, 3744, 3756, 3768, 3780, 3792, 3804, 3816, 3828, 3840, 3852, 3864, 3876, 3888, 3900, 3912, 3924, 3936, 3948, 3960, 3972, 3984, 3996, 4008, 4020, 4032, 4044, 4056, 4068, 4080, 4092, 4104, 4116, 4128, 4140, 4152, 4164, 4176, 4188, 4200, 4212, 4224, 4236, 4248, 4260, 4272, 4284, 4296, 4308, 4320, 4332, 4344, 4356, 4368, 4380, 4392, 4404, 4416, 4428, 4440, 4452, 4464, 4476, 4488, 4500, 4512, 4524, 4536, 4548, 4560, 4572, 4584, 4596, 4608, 4620, 4632, 4644, 4656, 4668, 4680, 4692, 4704, 4716, 4728, 4740, 4752, 4764, 4776, 4788, 4800, 4812, 4824, 4836, 4848, 4860, 4872, 4884, 4896, 4908, 4920, 4932, 4944, 4956, 4968, 4980, 4992, 5004, 5016, 5028, 5040, 5052, 5064, 5076, 5088, 5100, 5112, 5124, 5136, 5148, 5160, 5172, 5184, 5196, 5208, 5220, 5232, 5244, 5256, 5268, 5280, 5292, 5304, 5316, 5328, 5340, 5352, 5364, 5376, 5388, 5400, 5412, 5424, 5436, 5448, 5460, 5472, 5484, 5496, 5508, 5520, 5532, 5544, 5556, 5568, 5580, 5592, 5604, 5616, 5628, 5640, 5652, 5664, 5676, 5688, 5700, 5712, 5724, 5736, 5748, 5760, 5772, 5784, 5796, 5808, 5820, 5832, 5844, 5856, 5868, 5880, 5892, 5904, 5916, 5928, 5940, 5952, 5964, 5976, 5988, 6000, 6012, 6024, 6036, 6048, 6060, 6072, 6084, 6096, 6108, 6120, 6132, 6144, 6156, 6168, 6180, 6192, 6204, 6216, 6228, 6240, 6252, 6264, 6276, 6288, 6300, 6312, 6324, 6336, 6348, 6360, 6372, 6384, 6396, 6408, 6420, 6432, 6444, 6456, 6468, 6480, 6492, 6504, 6516, 6528, 6540, 6552, 6564, 6576, 6588, 6600, 6612, 6624, 6636, 6648, 6660, 6672, 6684, 6696, 6708, 6720, 6732, 6744, 6756, 6768, 6780, 6792, 6804, 6816, 6828, 6840, 6852, 6864, 6876, 6888, 6900, 6912, 6924, 6936, 6948, 6960, 6972, 6984, 6996, 7008, 7020, 7032, 7044, 7056, 7068, 7080, 7092, 7104, 7116, 7128, 7140, 7152, 7164, 7176, 7188, 7200, 7212, 7224, 7236, 7248, 7260, 7272, 7284, 7296, 7308, 7320, 7332, 7344, 7356, 7368, 7380, 7392, 7404, 7416, 7428, 7440, 7452, 7464, 7476, 7488, 7500, 7512, 7524, 7536, 7548, 7560, 7572, 7584, 7596, 7608, 7620, 7632, 7644, 7656, 7668, 7680, 7692, 7704, 7716, 7728, 7740, 7752, 7764, 7776, 7788, 7800, 7812, 7824, 7836, 7848, 7860, 7872, 7884, 7896, 7908, 7920, 7932, 7944, 7956, 7968, 7980, 7992, 8004, 8016, 8028, 8040, 8052, 8064, 8076, 8088, 8100, 8112, 8124, 8136, 8148, 8160, 8172, 8184, 8196, 8208, 8220, 8232, 8244, 8256, 8268, 8280, 8292, 8304, 8316, 8328, 8340, 8352, 8364, 8376, 8388, 8400, 8412, 8424, 8436, 8448, 8460, 8472, 8484, 8496, 8508, 8520, 8532, 8544, 8556, 8568, 8580, 8592, 8604, 8616, 8628, 8640, 8652, 8664, 8676, 8688, 8700, 8712, 8724, 8736, 8748, 8760, 8772, 8784, 8796, 8808, 8820, 8832, 8844, 8856, 8868, 8880, 8892, 8904, 8916, 8928, 8940, 8952, 8964, 8976, 8988, 9000, 9012, 9024, 9036, 9048, 9060, 9072, 9084, 9096, 9108, 9120, 9132, 9144, 9156, 9168, 9180, 9192, 9204, 9216, 9228, 9240, 9252, 9264, 9276, 9288, 9300, 9312, 9324, 9336, 9348, 9360, 9372, 9384, 9396, 9408, 9420, 9432, 9444, 9456, 9468, 9480, 9492, 9504, 9516, 9528, 9540, 9552, 9564, 9576, 9588, 9600, 9612, 9624, 9636, 9648, 9660, 9672, 9684, 9696, 9708, 9720, 9732, 9744, 9756, 9768, 9780, 9792, 9804, 9816, 9828, 9840, 9852, 9864, 9876, 9888, 9900, 9912, 9924, 9936, 9948, 9960, 9972, 9984, 9996, 10008, 10020, 10032, 10044, 10056, 10068, 10080, 10092, 10104, 10116, 10128, 10140, 10152, 10164, 10176, 10188, 10200, 10212, 10224, 10236, 10248, 10260, 10272, 10284, 10296, 10308, 10320, 10332, 10344, 10356, 10368, 10380, 10392, 10404, 10416, 10428, 10440, 10452, 10464, 10476, 10488, 10500, 10512, 10524, 10536, 10548, 10560, 10572, 10584, 10596, 10608, 10620, 10632, 10644, 10656, 10668, 10680, 10692, 10704, 10716, 10728, 10740, 10752, 10764, 10776, 10788, 10800, 10812, 10824, 10836, 10848, 10860, 10872, 10884, 10896, 10908, 10920, 10932, 10944, 10956, 10968, 10980, 10992, 11004, 11016, 11028, 11040, 11052, 11064, 11076, 11088, 11100, 11112, 11124, 11136, 11148, 11160, 11172, 11184, 11196, 11208, 11220, 11232, 11244, 11256, 11268, 11280, 11292, 11304, 11316, 11328, 11340, 11352, 11364, 11376, 11388, 11400, 11412, 11424, 11436, 11448, 11460, 11472, 11484, 11496, 11508, 11520, 11532, 11544, 11556, 11568, 11580, 11592, 11604, 11616, 11628, 11640, 11652, 11664, 11676, 11688, 11700, 11712, 11724, 11736, 11748, 11760, 11772, 11784, 11796, 11808, 11820, 11832, 11844, 11856, 11868, 11880, 11892, 11904, 11916, 11928, 11940, 11952, 11964, 11976, 11988, 12000, 12012, 12024, 12036, 12048, 12060, 12072, 12084, 12096, 12108, 12120, 12132, 12144, 12156, 12168, 12180, 12192, 12204, 12216, 12228, 12240, 12252, 12264, 12276, 12288, 12300, 12312, 12324, 12336, 12348, 12360, 12372, 12384, 12396, 12408, 12420, 12432, 12444, 12456, 12468, 12480, 12492, 12504, 12516, 12528, 12540, 12552, 12564, 12576, 12588, 12600, 12612, 12624, 12636, 12648, 12660, 12672, 12684, 12696, 12708, 12720, 12732, 12744, 12756, 12768, 12780, 12792, 12804, 12816, 12828, 12840, 12852, 12864, 12876, 12888, 12900, 12912, 12924, 12936, 12948, 12960, 12972, 12984, 12996, 13008, 13020, 13032, 13044, 13056, 13068, 13080, 13092, 13104, 13116, 13128, 13140, 13152, 13164, 13176, 13188, 13200, 13212, 13224, 13236, 13248, 13260, 13272, 13284, 13296, 13308, 13320, 13332, 13344, 13356, 13368, 13380, 13392, 13404, 13416, 13428, 13440, 13452, 13464, 13476, 13488, 13500, 13512, 13524, 13536, 13548, 13560, 13572, 13584, 13596, 13608, 13620, 13632, 13644, 13656, 13668, 13680, 13692, 13704, 13716, 13728, 13740, 13752, 13764, 13776, 13788, 13800, 13812, 13824, 13836, 13848, 13860, 13872, 13884, 13896, 13908, 13920, 13932, 13944, 13956, 13968, 13980, 13992, 14004, 14016, 14028, 14040, 14052, 14064, 14076, 14088, 14100, 14112, 14124, 14136, 14148, 14160, 14172, 14184, 14196, 14208, 14220, 14232, 14244, 14256, 14268, 14280, 14292, 14304, 14316, 14328, 14340, 14352, 14364, 14376, 14388, 14400, 14412, 14424, 14436, 14448, 14460, 14472, 14484, 14496, 14508, 14520, 14532, 14544, 14556, 14568, 14580, 14592, 14604, 14616, 14628, 14640, 14652, 14664, 14676, 14688, 14700, 14712, 14724, 14736, 14748, 14760, 14772, 14784, 14796, 14808, 14820, 14832, 14844, 14856, 14868, 14880, 14892, 14904, 14916, 14928, 14940, 14952, 14964, 14976, 14988, 15000, 15012, 15024, 15036, 15048, 15060, 15072, 15084, 15096, 15108, 15120, 15132, 15144, 15156, 15168, 15180, 15192, 15204, 15216, 15228, 15240, 15252, 15264, 15276, 15288, 15300, 15312, 15324, 15336, 15348, 15360, 15372, 15384, 15396, 15408, 15420, 15432, 15444, 15456, 15468, 15480, 15492, 15504, 15516, 15528, 15540, 15552, 15564, 15576, 15588, 15600, 15612, 15624, 15636, 15648, 15660, 15672, 15684, 15696, 15708, 15720, 15732, 15744, 15756, 15768, 15780, 15792, 15804, 15816, 15828, 15840, 15852, 15864, 15876, 15888, 15900, 15912, 15924, 15936, 15948, 15960, 15972, 15984, 15996, 16008, 16020, 16032, 16044, 16056, 16068, 16080, 16092, 16104, 16116, 16128, 16140, 16152, 16164, 16176, 16188, 16200, 16212, 16224, 16236, 16248, 16260, 16272, 16284, 16296, 16308, 16320, 16332, 16344, 16356, 16368, 16380, 16392, 16404, 16416, 16428, 16440, 16452, 16464, 16476, 16488, 16500, 16512, 16524, 16536, 16548, 16560, 16572, 16584, 16596, 16608, 16620, 16632, 16644, 16656, 16668, 16680, 16692, 16704, 16716, 16728, 16740, 16752, 16764, 16776, 16788, 16800, 16812, 16824, 16836, 16848, 16860, 16872, 16884, 16896, 16908, 16920, 16932, 16944, 16956, 16968, 16980, 16992, 17004, 17016, 17028, 17040, 17052, 17064, 17076, 17088, 17100, 17112, 17124, 17136, 17148, 17160, 17172, 17184, 17196, 17208, 17220, 17232, 17244, 17256, 17268, 17280, 17292, 17304, 17316, 17328, 17340, 17352, 17364, 17376, 17388, 17400, 17412, 17424, 17436, 17448, 17460, 17472, 17484, 17496, 17508, 17520, 17532, 17544, 17556, 17568, 17580, 17592, 17604, 17616, 17628, 17640, 17652, 17664, 17676, 17688, 17700, 17712, 17724, 17736, 17748, 17760, 17772, 17784, 17796, 17808, 17820, 17832, 17844, 17856, 17868, 17880, 17892, 17904, 17916, 17928, 17940, 17952, 17964, 17976, 17988, 18000, 18012, 18024, 18036, 18048, 18060, 18072, 18084, 18096, 18108, 18120, 18132, 18144, 18156, 18168, 18180, 18192, 18204, 18216, 18228, 18240, 18252, 18264, 18276, 18288, 18300, 18312, 18324, 18336, 18348, 18360, 18372, 18384, 18396, 18408, 18420, 18432, 18444, 18456, 18468, 18480, 18492, 18504, 18516, 18528, 18540, 18552, 18564, 18576, 18588, 18600, 18612, 18624, 18636, 18648, 18660, 18672, 18684, 18696, 18708, 18720, 18732, 18744, 18756, 18768, 18780, 18792, 18804, 18816, 18828, 18840, 18852, 18864, 18876, 18888, 18900, 18912, 18924, 18936, 18948, 18960, 18972, 18984, 18996, 19008, 19020, 19032, 19044, 19056, 19068, 19080, 19092, 19104, 19116, 19128, 19140, 19152, 19164, 19176, 19188, 19200, 19212, 19224, 19236, 19248, 19260, 19272, 19284, 19296, 19308, 19320, 19332, 19344, 19356, 19368, 19380, 19392, 19404, 19416, 19428, 19440, 19452, 19464, 19476, 19488, 19500, 19512, 19524, 19536, 19548, 19560, 19572, 19584, 19596, 19608, 19620, 19632, 19644, 19656, 19668, 19680, 19692, 19704, 19716, 19728, 19740, 19752, 19764, 19776, 19788, 19800, 19812, 19824, 19836, 19848, 19860, 19872, 198

MOMENTS & SHEARS:

DEAD LOAD: (SUPERIMPOSED)

INTERIOR GIRDER:

$$M_{DL} = \frac{1}{8} (.843) (60)^2 = 379.35 \text{ }^k$$

$$V_{DL} = \frac{1}{2} (.843) (60) = 25.29 \text{ }^k$$

EXTERIOR GIRDER:

$$M_{DL} = \frac{1}{8} (.814) (60)^2 = 366.3 \text{ }^k$$

$$V_{DL} = \frac{1}{2} (.814) (60) = 24.42 \text{ }^k$$

SELF WT: $M_{DL} = \frac{1}{8} (.58) (60)^2 = 261 \text{ }^k$

$$V_{DL} = \frac{1}{2} (.58) (60) = 17.4 \text{ }^k$$

LIVE LOAD:

MAX MOMENT & SHEAR, 60' SPAN, ONE LANE

$$M_{MAX} = 806.5 \text{ }^k$$

$$V_{MAX} = 60.8 \text{ }^k$$

INTERIOR GIRDER:

$$M_{LL} = (806.5) (.59) = 475.84 \text{ }^k$$

$$V_{LL} = (60.8) (.59) = 35.87 \text{ }^k$$

EXTERIOR GIRDER:

TRAFFIC:

$$M_{LL} = (806.5) (.423) = 341.15 \text{ }^k$$

$$V_{LL} = (60.8) (.423) = 25.72 \text{ }^k$$

WALKWAY:

$$M_{LL} = \frac{1}{8} (.09) (60)^2 = 40.5 \text{ }^k$$

$$V_{LL} = \frac{1}{2} (.09) (60) = 2.7 \text{ }^k$$


MADE IN U.S.A.
 42-989 20000 KELL WHITE 502000
 42-988 20000 KELL WHITE 502000
 42-987 20000 KELL WHITE 502000
 42-986 20000 KELL WHITE 502000
 42-985 20000 KELL WHITE 502000
 42-984 20000 KELL WHITE 502000
 42-983 20000 KELL WHITE 502000
 42-982 20000 KELL WHITE 502000
 42-981 20000 KELL WHITE 502000
 42-980 20000 KELL WHITE 502000



EXTERIOR GIRDER:

LANE FACTOR:

(ASSUME SLAB ACTS AS SIMPLE SPAN BETWEEN GIRDERS)



$$\text{wheel factor} = \frac{5.5}{6.5} = 0.846 \text{ wheels/girder}$$

$$= 0.423 \text{ lanes/girder}$$

SIDEWALK LL:

(ALLOWABLE STRESS IN GIRDER MAY BE INCREASED BY 25% FOR COMBINATION OF DL, SIDEWALK LL, TRAFFIC LL, + IMPACT, PROVIDING THE BEAM IS OF NO LESS CARRYING CAPACITY THAN WOULD BE REQ'D IF THERE WERE NO SIDEWALKS.)

$$(1.5')(0.060 \frac{1}{SF}) =$$

$$0.09 \frac{1}{FT}$$

IMPACT:

$$I = \frac{50}{L+125}$$

$$I = \frac{50}{60+125} = 0.270$$

11,780 50% RECYCLED FILLER, 5.5 SQUARE
 47,781 40% RECYCLED FILLER, 5.5 SQUARE
 47,782 100% RECYCLED FILLER, 5.5 SQUARE
 47,783 100% RECYCLED FILLER, 5.5 SQUARE
 47,784 100% RECYCLED FILLER, 5.5 SQUARE
 47,785 20% RECYCLED WHITE, 5.5 SQUARE
 47,786 20% RECYCLED WHITE, 5.5 SQUARE
 MADE IN U.S.A.



IMPACT :

INTERIOR :

$$M_I = 0.2(475.84) = 128.48^k$$

$$V_I = 0.27(35.87) = 9.68^k$$

EXTERIOR :

TRAFFIC :

$$M_I = 0.27(341.15) = 92.11^k$$

$$V_I = 0.27(25.72) = 6.94^k$$

WALKWAY :

$$M_I = 0.27(40.5) = 10.94^k$$

$$V_I = 0.27(2.7) = 0.73^k$$

TOTALS :

INTERIOR

$$M_{DL+LL+I} = 261^k + 379.35 + 475.84 + 128.48 = 1244.67^k$$

$$V_{DL+LL+I} = 17.4^k + 25.29 + 35.87 + 9.68 = 88.24^k$$

EXTERIOR (TRAFFIC ONLY)

$$M_{DL+LL+I} = 261^k + 366.3 + 341.15 + 92.11 = 1060.56^k$$

$$V_{DL+LL+I} = 17.4^k + 24.42 + 25.72 + 6.94 = 74.48^k$$

EXTERIOR (TRAFFIC + WALKWAY, 25% OVERSTRESS)

$$M_{DL+LL+I} = 0.8(261^k + 366.3 + 341.15 + 40.5 + 92.11 + 10.94) = 879.3^k$$


$$V_{DL+LL+I} = 0.8(17.4^k + 24.42 + 25.72 + 2.7 + 6.94 + 0.73) = 62.33^k$$

∴ INTERIOR GIRDER CONTROLS

13 787 140 214 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000



MEMBER OF THE
 NATIONAL
 ASSOCIATION
 OF
 BRIDGE
 ENGINEERS
 AND
 STRUCTURAL
 ENGINEERS
 INCORPORATED
 1800
 AVENUE OF THE
 STARS
 SUITE 500
 FALLS CHURCH, VA 22034
 (703) 440-2000
 WWW.NASBE.ORG



$f_c = 6000 \text{ psi}$
 #7-270ksi low-relaxation strands

	A	y	Ay	Ay^2	I_o
①	154	3.5	539	1886.5	628.83
②	56.25	9.5	534.375	5076.5625	175.78
③	217	23.5	5099.5	119838.25	17378.08
④	20.25	36.5	739.125	26978.0625	22.78
⑤	112	29.5	3304	97486	457.33
	<u>559.5 in²</u>		<u>10216.0</u>	<u>251265.375</u>	<u>18662.80</u>

$$\bar{y} = 10216.0 / 559.5 = 18.26''$$

$$I = 18662.80 + 251265.375 - (18.26)(10216.0) = 83,984 \text{ in}^4$$

c.g. of strands:

$$E: \frac{10(2.5) + 8(4.5) + 2(40.5)}{20} = 7.1$$

$$e = 18.26 - 7.1 = 11.16$$

$$END: \frac{10(2.5) + 6(4.5) + 2(36.5) + 2(40.5)}{20} = 10.3$$

$$e = 18.26 - 10.3 = 7.96$$

SIDE:

$$I = 83,324 \text{ in}^4$$

$$S_{TOP} = \frac{83,324}{(45 - 18.26)} = 3118.3 \text{ in}^3$$

$$S_{BOT} = \frac{83,324}{18.26} = 4566.5 \text{ in}^3$$

44-782 400 SHEETS PER UNIT 5.00 X 10.00
 44-301 50 SHEETS PER UNIT 5.00 X 10.00
 44-302 60 SHEETS PER UNIT 5.00 X 10.00
 44-303 70 SHEETS PER UNIT 5.00 X 10.00
 44-304 80 SHEETS PER UNIT 5.00 X 10.00
 44-305 90 SHEETS PER UNIT 5.00 X 10.00
 44-306 100 SHEETS PER UNIT 5.00 X 10.00
 44-307 110 SHEETS PER UNIT 5.00 X 10.00
 44-308 120 SHEETS PER UNIT 5.00 X 10.00
 44-309 130 SHEETS PER UNIT 5.00 X 10.00
 44-310 140 SHEETS PER UNIT 5.00 X 10.00
 44-311 150 SHEETS PER UNIT 5.00 X 10.00
 44-312 160 SHEETS PER UNIT 5.00 X 10.00
 44-313 170 SHEETS PER UNIT 5.00 X 10.00
 44-314 180 SHEETS PER UNIT 5.00 X 10.00
 44-315 190 SHEETS PER UNIT 5.00 X 10.00
 44-316 200 SHEETS PER UNIT 5.00 X 10.00
 Made in U.S.A.



Allowable Stresses:

Concrete:

$f'_c = 6000 \text{ psi}$

$f_{ci} = 0.75(6000) = 4500 \text{ psi}$

INITIAL:

TENSION: $3\sqrt{f_{ci}} = 200 \text{ psi} = 3\sqrt{4500} = 201 \text{ psi}$ - use 200 psi

COMPRESSION: $0.60 f_{ci} = 0.6(4500) = 2700 \text{ psi}$

FINAL:

TENSION: 0 psi

COMPRESSION: PRESTRESS + DL = $0.4 f'_c = 2400 \text{ psi}$

LL + 1/2 (PRESTRESS) = $0.4 f'_c = 2400 \text{ psi}$

ALL LOAD COMBINATIONS = $0.4 f'_c = 2400 \text{ psi}$

PRESTRESSING STEEL

LOW-RELAXATION STRANDS

INITIAL STRESS: $(.75) f'_s = 0.75(270) = 202.5 \text{ ksi}$

FORCE: $20(1531)(202.5) = 620.05 \text{ K}$

FINAL STRESS: $202.5 - 45 = 157.5 \text{ ksi}$

FORCE: $20(1531)(157.5) = 482.26 \text{ K}$

17 702
40 311
40 312
40 313
40 314
40 315
40 316
40 317
40 318
40 319
40 320
40 321
40 322
40 323
40 324
40 325
40 326
40 327
40 328
40 329
40 330
40 331
40 332
40 333
40 334
40 335
40 336
40 337
40 338
40 339
40 340
40 341
40 342
40 343
40 344
40 345
40 346
40 347
40 348
40 349
40 350
40 351
40 352
40 353
40 354
40 355
40 356
40 357
40 358
40 359
40 360
40 361
40 362
40 363
40 364
40 365
40 366
40 367
40 368
40 369
40 370
40 371
40 372
40 373
40 374
40 375
40 376
40 377
40 378
40 379
40 380
40 381
40 382
40 383
40 384
40 385
40 386
40 387
40 388
40 389
40 390
40 391
40 392
40 393
40 394
40 395
40 396
40 397
40 398
40 399
40 400
40 401
40 402
40 403
40 404
40 405
40 406
40 407
40 408
40 409
40 410
40 411
40 412
40 413
40 414
40 415
40 416
40 417
40 418
40 419
40 420
40 421
40 422
40 423
40 424
40 425
40 426
40 427
40 428
40 429
40 430
40 431
40 432
40 433
40 434
40 435
40 436
40 437
40 438
40 439
40 440
40 441
40 442
40 443
40 444
40 445
40 446
40 447
40 448
40 449
40 450
40 451
40 452
40 453
40 454
40 455
40 456
40 457
40 458
40 459
40 460
40 461
40 462
40 463
40 464
40 465
40 466
40 467
40 468
40 469
40 470
40 471
40 472
40 473
40 474
40 475
40 476
40 477
40 478
40 479
40 480
40 481
40 482
40 483
40 484
40 485
40 486
40 487
40 488
40 489
40 490
40 491
40 492
40 493
40 494
40 495
40 496
40 497
40 498
40 499
40 500
40 501
40 502
40 503
40 504
40 505
40 506
40 507
40 508
40 509
40 510
40 511
40 512
40 513
40 514
40 515
40 516
40 517
40 518
40 519
40 520
40 521
40 522
40 523
40 524
40 525
40 526
40 527
40 528
40 529
40 530
40 531
40 532
40 533
40 534
40 535
40 536
40 537
40 538
40 539
40 540
40 541
40 542
40 543
40 544
40 545
40 546
40 547
40 548
40 549
40 550
40 551
40 552
40 553
40 554
40 555
40 556
40 557
40 558
40 559
40 560
40 561
40 562
40 563
40 564
40 565
40 566
40 567
40 568
40 569
40 570
40 571
40 572
40 573
40 574
40 575
40 576
40 577
40 578
40 579
40 580
40 581
40 582
40 583
40 584
40 585
40 586
40 587
40 588
40 589
40 590
40 591
40 592
40 593
40 594
40 595
40 596
40 597
40 598
40 599
40 600
40 601
40 602
40 603
40 604
40 605
40 606
40 607
40 608
40 609
40 610
40 611
40 612
40 613
40 614
40 615
40 616
40 617
40 618
40 619
40 620
40 621
40 622
40 623
40 624
40 625
40 626
40 627
40 628
40 629
40 630
40 631
40 632
40 633
40 634
40 635
40 636
40 637
40 638
40 639
40 640
40 641
40 642
40 643
40 644
40 645
40 646
40 647
40 648
40 649
40 650
40 651
40 652
40 653
40 654
40 655
40 656
40 657
40 658
40 659
40 660
40 661
40 662
40 663
40 664
40 665
40 666
40 667
40 668
40 669
40 670
40 671
40 672
40 673
40 674
40 675
40 676
40 677
40 678
40 679
40 680
40 681
40 682
40 683
40 684
40 685
40 686
40 687
40 688
40 689
40 690
40 691
40 692
40 693
40 694
40 695
40 696
40 697
40 698
40 699
40 700
40 701
40 702
40 703
40 704
40 705
40 706
40 707
40 708
40 709
40 710
40 711
40 712
40 713
40 714
40 715
40 716
40 717
40 718
40 719
40 720
40 721
40 722
40 723
40 724
40 725
40 726
40 727
40 728
40 729
40 730
40 731
40 732
40 733
40 734
40 735
40 736
40 737
40 738
40 739
40 740
40 741
40 742
40 743
40 744
40 745
40 746
40 747
40 748
40 749
40 750
40 751
40 752
40 753
40 754
40 755
40 756
40 757
40 758
40 759
40 760
40 761
40 762
40 763
40 764
40 765
40 766
40 767
40 768
40 769
40 770
40 771
40 772
40 773
40 774
40 775
40 776
40 777
40 778
40 779
40 780
40 781
40 782
40 783
40 784
40 785
40 786
40 787
40 788
40 789
40 790
40 791
40 792
40 793
40 794
40 795
40 796
40 797
40 798
40 799
40 800
40 801
40 802
40 803
40 804
40 805
40 806
40 807
40 808
40 809
40 810
40 811
40 812
40 813
40 814
40 815
40 816
40 817
40 818
40 819
40 820
40 821
40 822
40 823
40 824
40 825
40 826
40 827
40 828
40 829
40 830
40 831
40 832
40 833
40 834
40 835
40 836
40 837
40 838
40 839
40 840
40 841
40 842
40 843
40 844
40 845
40 846
40 847
40 848
40 849
40 850
40 851
40 852
40 853
40 854
40 855
40 856
40 857
40 858
40 859
40 860
40 861
40 862
40 863
40 864
40 865
40 866
40 867
40 868
40 869
40 870
40 871
40 872
40 873
40 874
40 875
40 876
40 877
40 878
40 879
40 880
40 881
40 882
40 883
40 884
40 885
40 886
40 887
40 888
40 889
40 890
40 891
40 892
40 893
40 894
40 895
40 896
40 897
40 898
40 899
40 900
40 901
40 902
40 903
40 904
40 905
40 906
40 907
40 908
40 909
40 910
40 911
40 912
40 913
40 914
40 915
40 916
40 917
40 918
40 919
40 920
40 921
40 922
40 923
40 924
40 925
40 926
40 927
40 928
40 929
40 930
40 931
40 932
40 933
40 934
40 935
40 936
40 937
40 938
40 939
40 940
40 941
40 942
40 943
40 944
40 945
40 946
40 947
40 948
40 949
40 950
40 951
40 952
40 953
40 954
40 955
40 956
40 957
40 958
40 959
40 960
40 961
40 962
40 963
40 964
40 965
40 966
40 967
40 968
40 969
40 970
40 971
40 972
40 973
40 974
40 975
40 976
40 977
40 978
40 979
40 980
40 981
40 982
40 983
40 984
40 985
40 986
40 987
40 988
40 989
40 990
40 991
40 992
40 993
40 994
40 995
40 996
40 997
40 998
40 999
40 1000



INITIAL STRESSES:

END:

$$\text{TOP: } \frac{-620.05}{559.5} + \frac{620.05 * 7.96}{3118.3} = 0.47 > 0.2 \text{ N.G.} \\ < 0.5 \text{ OK}$$

- ADD BONDED REINFORCEMENT,

$$\text{ALLOWABLE INCREASES TO } 7.5\sqrt{f_{ci}} \\ = 7.5\sqrt{4500} \\ = 503 \text{ psi}$$

$$\text{BTM: } \frac{-620.05}{559.5} - \frac{620.05 * 7.96}{4566.5} = -2.19 < -2.7 \text{ OK}$$

@ ϕ :

$$\text{TOP: } \frac{-620.05}{559.5} + \frac{620.05 * 11.16}{3118.3} - \frac{261.0 * 12}{3118.3} = 0.11 < 0.5 \text{ OK}$$

$$\text{BTM: } \frac{-620.05}{559.5} - \frac{620.05 * 11.16}{4566.5} + \frac{261.0 * 12}{4566.5} = -1.93 < -2.7 \text{ OK}$$

FINAL STRESSES: (PRESTRESS + DL)

$$M_{DL} = 261 + 379.35 = 640.35$$

$$\text{TOP: } \frac{-482.26}{559.5} + \frac{482.26 * 11.16}{3118.3} - \frac{640.35 * 12}{3118.3} = -1.60 < -2.4 \text{ OK}$$


$$\text{BTM: } \frac{-482.26}{559.5} - \frac{482.26 * 11.16}{4566.5} + \frac{640.35 * 12}{4566.5} = -0.36 < -2.4 \text{ OK}$$

$$LL + \frac{1}{2}(\text{PRESTRESS} + DL) \quad M(LL + \frac{1}{2}) = 604.32$$

- FOR LL, COMPOSITE SECTION MODULUS SHOULD BE USED.

FOR THE FULL LINE, SEE PAGE
 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 915, 916, 917, 918, 919, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 930, 931, 932, 933, 934, 935, 936, 937, 938, 939, 940, 941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 964, 965, 966, 967, 968, 969, 970, 971, 972, 973, 974, 975, 976, 977, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000.

National Brand



	A	y	Ay	Ay ²	I _o
⊖	559.5	18.26	10216.47	186552.74	83384
⊕	546	48.5	26481	1284528.5	2229.5
	<u>1105.5</u>		<u>36697.47</u>	<u>1470881.24</u>	<u>85613.5</u>

$$\bar{y} = 36697.47 / 1105.5 = 33.19$$

$$I = 85613.5 + 1470881.24 - 33.19(36697.47) = 338506 \text{ in}^4$$

$$S_{SLAB} = 338506 / (52 - 33.19) = 17996 \text{ in}^3$$

$$S_{TOPRIBBER} = 338506 / (45 - 33.19) = 28663 \text{ in}^3$$

$$S_{BTM} = 338506 / 33.19 = 10199 \text{ in}^3$$

$$e(c) = 33.19 - 7.1 = 26.09$$

FINAL STRESSES (CONT.)

LL + 1/2 (PRESTRESS + DL)

$$\text{TOP: } \frac{1}{2} \left(\frac{-482.26}{559.5} + \frac{482.26 * 26.09}{28663} - \frac{(640.35 * 12)}{28663} \right) + \frac{604.32 * 12}{28663} = -0.60 < -2.4 \text{ OK}$$

$$\text{BTM: } \frac{1}{2} \left(\frac{-482.26}{559.5} - \frac{482.26 * 26.09}{10199} + \frac{640.35 * 12}{10199} \right) + \frac{604.32 * 12}{10199} = 0.04$$

- say ok for preliminary

DL + LL + I :

$$\text{TOP: } \frac{-482.26}{559.5} + \frac{482.26 * 26.09}{28663} - \frac{(640.35 + 604.32 * 12)}{28663} = -0.94 < -3.6 \text{ OK}$$

$$\text{BTM: } \frac{-482.26}{559.5} - \frac{482.26 * 26.09}{10199} + \frac{(640.35 + 604.32 * 12)}{10199} = -0.63 < -3.6 \text{ OK}$$

NATIONAL BRAND
 PORTLAND CEMENT
 MADE IN U.S.A.



MOMENTS ABOUT A: (+)


$$R(x) = (5 \frac{1}{2}ft)(\frac{19}{12}) + (2.7 \frac{1}{2}ft)(\frac{19}{12}) + (1.25 \frac{1}{2}ft)(\frac{35.25}{12}) - (1.6 \frac{1}{2}ft)(2.55) - (0.11)(3.82)$$

$$R(x) = 11.41$$

$$R = 5 + 2.7 + 1.25 = 8.95 \frac{1}{2}ft$$

$$x = 11.41 / 8.92 = 1.28' = 15.35''$$

-should fall into middle $\frac{1}{3}$ of width. OK



-ASSUME 5 PILES

$$\text{LOAD/PILE: } 255 + 121.6 + 35 = 411.6 = 82.32' / \text{PILE}$$

-use a cone pile tip elev - no existing bridge = -81.73 NGVD

-pile \approx 81'

$$16'' \text{ APFC - capacity} = \frac{100}{200} \text{ TONS} = \frac{175}{200} > 82.32 \text{ OK}$$

13.802 240 SHELLS FILLED 5 SOUJARI
 42.382 100 SHELLS FILLED 5 SOUJARI
 42.382 200 SHELLS FILLED 5 SOUJARI
 42.382 300 SHELLS FILLED 5 SOUJARI
 42.382 400 SHELLS FILLED 5 SOUJARI
 42.382 500 SHELLS FILLED 5 SOUJARI
 42.382 600 SHELLS FILLED 5 SOUJARI
 42.382 700 SHELLS FILLED 5 SOUJARI
 42.382 800 SHELLS FILLED 5 SOUJARI
 42.382 900 SHELLS FILLED 5 SOUJARI
 42.382 1000 SHELLS FILLED 5 SOUJARI
 Made in U.S.A.




MODIFY EXISTING ABUTMENT TO BECOME INTERIOR BEIST

-ADD 2 PILES TO BRING TOTAL TO 7

$$DL - 2-60' SPANS \cdot 2(225) = 450^k$$

LL -



$$\begin{aligned} \text{PIER REACTION} &= (32) + (32)\left(\frac{46'}{60'}\right) + (8)\left(\frac{46'}{60'}\right) \\ &= 62.67^k \quad \text{PER LANE} \end{aligned}$$

$$\text{TOTAL} = 2(62.67) = 125.34^k$$

$$\text{LOAD/PILE} = \frac{(450 + 125.34)}{7} = 82.19^k/\text{PILE}$$

- NECESSITY OF ADDING PILES TO BE DETERMINED BY SOILS REPORT.

$$\begin{aligned} \text{Capacity of existing piles} &= 87 \text{ TONS} \\ &= 174^k \end{aligned}$$

$$\text{if use only 5 piles: } \frac{(450 + 125.34)}{5}$$

$$= 115.1^k < 174$$

BRIDGE ELEVATIONS:

SURVET TOP OF SCAB (HIGH SIDE) = 7.65
 (LOW SIDE) = 7.09

BRIDGE DWGS TOPO SCAB (HIGH SIDE) = 7.52
 (LOW SIDE) = 6.96

DIFFERENCES: $7.65 - 7.52 = 0.13'$
 $7.09 - 6.96 = 0.13'$

∴ ADD 0.13' to ELEVS. ON PLANS.

	PLANS	+ .13
ABUTMENT PEDESTALS:		
A	2.98	3.11
B	2.85	2.98
C	2.72	2.85
D	2.59	2.72
E	2.46	2.59

13 787 50 SHEET IS FULLER 5 SQUARE
 42 381 100 SHEET IS FULLER 5 SQUARE
 42 382 100 SHEET IS FULLER 5 SQUARE
 42 383 100 SHEET IS FULLER 5 SQUARE
 42 384 100 SHEET IS FULLER 5 SQUARE
 42 385 100 SHEET IS FULLER 5 SQUARE
 42 386 100 SHEET IS FULLER 5 SQUARE
 42 387 100 SHEET IS FULLER 5 SQUARE
 42 388 100 SHEET IS FULLER 5 SQUARE
 42 389 100 SHEET IS FULLER 5 SQUARE
 42 390 100 SHEET IS FULLER 5 SQUARE
 42 391 100 SHEET IS FULLER 5 SQUARE
 42 392 100 SHEET IS FULLER 5 SQUARE
 42 393 100 SHEET IS FULLER 5 SQUARE
 42 394 100 SHEET IS FULLER 5 SQUARE
 42 395 100 SHEET IS FULLER 5 SQUARE
 42 396 100 SHEET IS FULLER 5 SQUARE
 42 397 100 SHEET IS FULLER 5 SQUARE
 42 398 100 SHEET IS FULLER 5 SQUARE
 42 399 100 SHEET IS FULLER 5 SQUARE
 42 400 100 SHEET IS FULLER 5 SQUARE
 Made in U.S.A.



DESTRAHAN AVE. BRIDGE

DEAD LOADS:

60' SPANS:

SLAB: $(\frac{7}{12})(31.5')(1.150 \frac{k}{ft^2}) = 2.76 \frac{k}{ft}$


HAUNCHES: $[(\frac{1.5}{12})(3.417)(2) + (\frac{1.5}{12})(1.333)(3)](1.150) = 0.20 \frac{k}{ft}$

BARRIERS: $[(\frac{10}{12})(1.5) + (\frac{6}{12})(1) + \frac{1}{2}(\frac{7}{12})(1)](2)(1.15) = 0.6 \frac{k}{ft}$

$(2)(1.0')(1.0')(1.15) = 0.3 \frac{k}{ft}$

$(2)(1.25)(1.0)(\frac{11}{12})(8)(1.15)(\frac{1}{60}) = 0.05 \frac{k}{ft}$

GIRDERS: $(5)(3.88)(1.15) = 2.91 \frac{k}{ft}$



$$A = (1.23)(.583) + (.83)(.583) + (.583)(2.583) + (.375)(.375) + (.625)(.625) = 3.88 ft^2$$

6.82 $\frac{k}{ft}$

+ 10% misc (diaphragms, handrails, end caps, ...)

0.68

TOTAL (SUPERSTRUCTURE) = 7.5 $\frac{k}{ft}$

END REACTION = $(7.5)(60)(2) = \underline{225^k}$

80' SPAN:

- DL/FOOT SAME AS 60' SPAN

END REACTION = $(7.5)(80)/2 = 300^k$

NATIONAL BRAND
 STEEL
 PRODUCTS
 DIVISION
 AMERICAN
 IRON
 AND
 STEEL
 COMPANY
 PITTSBURGH
 PA. 15101
 1-800-393-6343



SUBSTRUCTURE:

INTERIOR BENT CAPS:

$$(2.5')(3.5')(33')(1.15) = 43.31^k$$

PEDESTALS:

use avg of C & C'

$$(5)(3.167)(3')(2.71-2.09)(1.15) = 4.42^k$$

$$\underline{\underline{47.73^k}}$$

ABUTMENTS:

$$[(25)(3.5) + (2.03)(0.958)](45)(1.15) = 72.19^k$$

$$(2)(8.417)(\frac{1}{2})(2.833)(.958)(1.15) = 3.43^k$$

$$(29')(1.67')(1.958)(1.15) = 6.96^k$$

PEDESTALS:

$$4.42^k$$

$$\underline{\underline{87.0^k}}$$

LIVE LOADS:



(use HS 20-44) (per lane)

60' end spur = 60.8^k

28' roadway gives 2 lanes

LL Reaction = 2(60.8) = 121.6^k @ abutment

PIER REACTION @ Bent: 60's span - 80's span




14 702
42 311
42 312
42 313
42 314
42 315
42 316
42 317
42 318
42 319
42 320
42 321
42 322
42 323
42 324
42 325
42 326
42 327
42 328
42 329
42 330
42 331
42 332
42 333
42 334
42 335
42 336
42 337
42 338
42 339
42 340
42 341
42 342
42 343
42 344
42 345
42 346
42 347
42 348
42 349
42 350
42 351
42 352
42 353
42 354
42 355
42 356
42 357
42 358
42 359
42 360
42 361
42 362
42 363
42 364
42 365
42 366
42 367
42 368
42 369
42 370
42 371
42 372
42 373
42 374
42 375
42 376
42 377
42 378
42 379
42 380
42 381
42 382
42 383
42 384
42 385
42 386
42 387
42 388
42 389
42 390
42 391
42 392
42 393
42 394
42 395
42 396
42 397
42 398
42 399
42 400
42 401
42 402
42 403
42 404
42 405
42 406
42 407
42 408
42 409
42 410
42 411
42 412
42 413
42 414
42 415
42 416
42 417
42 418
42 419
42 420
42 421
42 422
42 423
42 424
42 425
42 426
42 427
42 428
42 429
42 430
42 431
42 432
42 433
42 434
42 435
42 436
42 437
42 438
42 439
42 440
42 441
42 442
42 443
42 444
42 445
42 446
42 447
42 448
42 449
42 450
42 451
42 452
42 453
42 454
42 455
42 456
42 457
42 458
42 459
42 460
42 461
42 462
42 463
42 464
42 465
42 466
42 467
42 468
42 469
42 470
42 471
42 472
42 473
42 474
42 475
42 476
42 477
42 478
42 479
42 480
42 481
42 482
42 483
42 484
42 485
42 486
42 487
42 488
42 489
42 490
42 491
42 492
42 493
42 494
42 495
42 496
42 497
42 498
42 499
42 500
42 501
42 502
42 503
42 504
42 505
42 506
42 507
42 508
42 509
42 510
42 511
42 512
42 513
42 514
42 515
42 516
42 517
42 518
42 519
42 520
42 521
42 522
42 523
42 524
42 525
42 526
42 527
42 528
42 529
42 530
42 531
42 532
42 533
42 534
42 535
42 536
42 537
42 538
42 539
42 540
42 541
42 542
42 543
42 544
42 545
42 546
42 547
42 548
42 549
42 550
42 551
42 552
42 553
42 554
42 555
42 556
42 557
42 558
42 559
42 560
42 561
42 562
42 563
42 564
42 565
42 566
42 567
42 568
42 569
42 570
42 571
42 572
42 573
42 574
42 575
42 576
42 577
42 578
42 579
42 580
42 581
42 582
42 583
42 584
42 585
42 586
42 587
42 588
42 589
42 590
42 591
42 592
42 593
42 594
42 595
42 596
42 597
42 598
42 599
42 600
42 601
42 602
42 603
42 604
42 605
42 606
42 607
42 608
42 609
42 610
42 611
42 612
42 613
42 614
42 615
42 616
42 617
42 618
42 619
42 620
42 621
42 622
42 623
42 624
42 625
42 626
42 627
42 628
42 629
42 630
42 631
42 632
42 633
42 634
42 635
42 636
42 637
42 638
42 639
42 640
42 641
42 642
42 643
42 644
42 645
42 646
42 647
42 648
42 649
42 650
42 651
42 652
42 653
42 654
42 655
42 656
42 657
42 658
42 659
42 660
42 661
42 662
42 663
42 664
42 665
42 666
42 667
42 668
42 669
42 670
42 671
42 672
42 673
42 674
42 675
42 676
42 677
42 678
42 679
42 680
42 681
42 682
42 683
42 684
42 685
42 686
42 687
42 688
42 689
42 690
42 691
42 692
42 693
42 694
42 695
42 696
42 697
42 698
42 699
42 700
42 701
42 702
42 703
42 704
42 705
42 706
42 707
42 708
42 709
42 710
42 711
42 712
42 713
42 714
42 715
42 716
42 717
42 718
42 719
42 720
42 721
42 722
42 723
42 724
42 725
42 726
42 727
42 728
42 729
42 730
42 731
42 732
42 733
42 734
42 735
42 736
42 737
42 738
42 739
42 740
42 741
42 742
42 743
42 744
42 745
42 746
42 747
42 748
42 749
42 750
42 751
42 752
42 753
42 754
42 755
42 756
42 757
42 758
42 759
42 760
42 761
42 762
42 763
42 764
42 765
42 766
42 767
42 768
42 769
42 770
42 771
42 772
42 773
42 774
42 775
42 776
42 777
42 778
42 779
42 780
42 781
42 782
42 783
42 784
42 785
42 786
42 787
42 788
42 789
42 790
42 791
42 792
42 793
42 794
42 795
42 796
42 797
42 798
42 799
42 800
42 801
42 802
42 803
42 804
42 805
42 806
42 807
42 808
42 809
42 810
42 811
42 812
42 813
42 814
42 815
42 816
42 817
42 818
42 819
42 820
42 821
42 822
42 823
42 824
42 825
42 826
42 827
42 828
42 829
42 830
42 831
42 832
42 833
42 834
42 835
42 836
42 837
42 838
42 839
42 840
42 841
42 842
42 843
42 844
42 845
42 846
42 847
42 848
42 849
42 850
42 851
42 852
42 853
42 854
42 855
42 856
42 857
42 858
42 859
42 860
42 861
42 862
42 863
42 864
42 865
42 866
42 867
42 868
42 869
42 870
42 871
42 872
42 873
42 874
42 875
42 876
42 877
42 878
42 879
42 880
42 881
42 882
42 883
42 884
42 885
42 886
42 887
42 888
42 889
42 890
42 891
42 892
42 893
42 894
42 895
42 896
42 897
42 898
42 899
42 900
42 901
42 902
42 903
42 904
42 905
42 906
42 907
42 908
42 909
42 910
42 911
42 912
42 913
42 914
42 915
42 916
42 917
42 918
42 919
42 920
42 921
42 922
42 923
42 924
42 925
42 926
42 927
42 928
42 929
42 930
42 931
42 932
42 933
42 934
42 935
42 936
42 937
42 938
42 939
42 940
42 941
42 942
42 943
42 944
42 945
42 946
42 947
42 948
42 949
42 950
42 951
42 952
42 953
42 954
42 955
42 956
42 957
42 958
42 959
42 960
42 961
42 962
42 963
42 964
42 965
42 966
42 967
42 968
42 969
42 970
42 971
42 972
42 973
42 974
42 975
42 976
42 977
42 978
42 979
42 980
42 981
42 982
42 983
42 984
42 985
42 986
42 987
42 988
42 989
42 990
42 991
42 992
42 993
42 994
42 995
42 996
42 997
42 998
42 999
43 000




PIER REACTION: (cont.)

Lane Loading:




$$R_B = (.64)(30+60) + 26 = 70.8^k$$


truck loading:



$$R_B = 32 + 32\left(\frac{10}{60}\right) + 8\left(\frac{32}{60}\right) = 60.2^k$$



$$R_B = 32 + 32\left(\frac{10}{60}\right) + 8\left(\frac{32}{60}\right) = 63.6^k$$



$$R_B = 32 + 8\left(\frac{46}{60}\right) + 32\left(\frac{64}{60}\right) = 64.5^k$$

LL PIER REACTION FOR 2 LANES = 129.0^k

APPROACH SLABS:

20' APPROACH SLABS:

$$\left(\frac{10''}{12}\right)(28')(1.15) = 3.5^k/ft$$

$$DL \text{ Reaction} = (20)(3.5)\left(\frac{1}{2}\right) = 35^k$$

EXISTING PILE LOADS:

ABUTMENTS: $225^k + 35^k + 87^k + 121.6^k = \frac{468.6^k}{5 \text{ PILES}} = 93.72^k/\text{PILE}$

BENTS: $300^k + 225 + 47.73 + 129.0 = \frac{701.73^k}{7 \text{ PILES}} = 100.25^k/\text{PILE}$

- ALL PILES ARE 16" ϕ
- MAX DESIGN LOAD = 54T = 102K

NATIONAL BRAND
 PILES ARE MADE OF
 STEEL AND ARE
 AVAILABLE IN
 VARIOUS SIZES
 AND WEIGHTS
 FOR ALL TYPES
 OF FOUNDATION
 WORK.
 CONTACT YOUR
 LOCAL DISTRIBUTOR
 FOR MORE INFORMATION.
 NATIONAL BRAND
 PILES ARE MADE
 IN THE U.S.A.



DESTRAHAN AVE BRIDGE :

EL. TOP OF BENTS & ABUTS. = 2.09 (ALL SAME)

MIN. PEDESTAL ELEV. = 2.44'

BEARING PAD = 3/4" (60' GIRDERS)
= 1" (80' GIRDERS) ←

GIRDER HEIGHT = 3'-9"

HAUNCH = 1 1/2"

SLAB = 7"

HEIGHT OF WALKWAY

+ HANDRAIL = 10" + 1/3" + 1/5"
= 19 1/5"

= 4'5"

AS BUILT ELEV OF SLAB = $2.44 + \frac{1}{2} + 3.75 + \frac{8.5}{12}$
= 6.98 (MIN. ELEV.)

SURVEY ELEV OF SLAB = 2.09' (MIN. ELEV.)

DIFFERENCE = $2.09 - 6.98 = -4.89$

EQ. SURVEY ELEV OF BTM GIRDER = $2.44 + \frac{1}{2} + 0.11$
= 2.63

EQ. SURVEY ELEV BTM BENT CAP = $2.63 - \frac{1}{2} - 2.5 - 0.35$ ← PEDESTAL HT
= -0.30


FRANK L. COOPER, INC. ENGINEERS
4100 W. CENTRAL EXP. HWY. SUITE 100
DENVER, CO 80244
TEL: (303) 733-1111
FAX: (303) 733-1112




DESIGN CALCULATIONS

FLOOD GATE

BEAM DESIGN:



SWL+2'



Reactions: (1/2)(320)(5) = A (2+)

$$0 = -3B - \left(\frac{1}{2} \times 320\right) \frac{(5)^2}{3} + \frac{320(4.5)^2}{2} + (320-52)(3)(4.5)$$

$$3B = -1.33 + 324 + 1744$$

$$B = 755.56$$

$$A = 800 - 755.56 = 44.44$$


CANTILEVER MOMENTS

$$M_A = \frac{1}{2}(32)(1.5)^2/3 = 1.33'$$

$$M_B = (224)(1.5)/2 + \frac{1}{2}(320 - 224)(1.5)^2/3$$

$$= 168 + 72$$


$$= 240'$$



M



SWL



$$M_B = (5)(288) - 3A(5)$$

$$= 1440 - 15A$$

$$= 800(5)$$

$$1440 - 15A = 800(5)$$

SWL+2' CONTROLS

SKIN R:

$$M_{max} = .324 \text{ k} \quad (\text{p. 2})$$

$$S_{REQ'D} = \frac{.324(12)}{20} = 0.1944 \text{ in}^3$$

$$\text{try } 5/16 \text{ R: } S = 6(12)(5/16)^2 = 0.195 \text{ in}^3 \quad \text{OK}$$


$$\text{try } 3/8 \text{ R: } S = 6(12)(3/8)^2 = 0.281 \text{ in}^3 \quad \leftarrow \text{use } 3/8 \text{ R}$$

$$f_b = \frac{.324(12)}{.281} = 13.84 \text{ ksi} < 20 \text{ OK}$$

13 282
42 383
42 389
42 390
42 391
42 392
42 393
42 394
42 395
42 396
42 397
42 398
42 399
42 400
42 401
42 402
42 403
42 404
42 405
42 406
42 407
42 408
42 409
42 410
42 411
42 412
42 413
42 414
42 415
42 416
42 417
42 418
42 419
42 420
42 421
42 422
42 423
42 424
42 425
42 426
42 427
42 428
42 429
42 430
42 431
42 432
42 433
42 434
42 435
42 436
42 437
42 438
42 439
42 440
42 441
42 442
42 443
42 444
42 445
42 446
42 447
42 448
42 449
42 450
42 451
42 452
42 453
42 454
42 455
42 456
42 457
42 458
42 459
42 460
42 461
42 462
42 463
42 464
42 465
42 466
42 467
42 468
42 469
42 470
42 471
42 472
42 473
42 474
42 475
42 476
42 477
42 478
42 479
42 480
42 481
42 482
42 483
42 484
42 485
42 486
42 487
42 488
42 489
42 490
42 491
42 492
42 493
42 494
42 495
42 496
42 497
42 498
42 499
42 500



try E' simple beam



$$M_{max} = .1283 W L^2 + \frac{w x^2}{2} (L-x)$$

$$x = .5774 L = .5774(3) = 1.732'$$

$$M_{max} = .1283(1/2)(224-32)(3)(3) + \frac{32(1.732^2)}{2}(3-1.732)$$

$$= 110.88 + 35.14 = 146.02 \text{ k} < 324 \text{ k}$$

- DESIGN PILES, FOOTING, WHEN SOILS REPORT IS IN


JN 3003

DESTRAHAN AVE
FLOODGATE

AAH

4-9-98


BRIDGE
DESIGN
PROJECT
NO. 1000
DATE
10/10/97



RECEIVED

FEB 4 1968

D. H. H.



STRATA NO.	SOIL TYPE	UNIT WEIGHT PCF	UNFACTORED		SAFETY FACTOR OF 1.3			
			FRICTION ANGLE DEGREES	COHESION - PSF		FRICTION ANGLE DEGREES	COHESION - PSF	
				AVERAGE	BOTTOM		AVERAGE	BOTTOM
1	FILL CLAY, SAND & SHELL	120	25	0	0	20	0	0
2	CLAY	95	0	280	280	0	200	200
3	CLAY	60	0	215	220	0	181	169
4	CLAY	60	0	220	220	0	169	169

SUMMATION OF FORCES USING FACTORED SLOPE STRENGTHS:				
FAILURE SURFACE	SR RESISTANCE LBS/FT	SD DRIVING LBS/FT	SR - SD	CHANGE IN NET FORCE, LB
①	628	1841	-1013	-
②	3122	3098	24	1037
③	10285	6455	3830	2806

Post-It File Note	7171	Date	2/5/68
To	DET.	From	L. Spangler
On	April Hurry	By	Earl Eng
Where		Phone	834 0157
File #		File #	

NOTE - 1) ANALYSIS INDICATES NO UNBALANCED FORCE BENEATH THE FLOODGATE FOOTING TO MAINTAIN STABILITY WITH RESPECT TO A FACTOR OF SAFETY OF 1.3.
 2) SHEETPILE CUT OFF MUST PENETRATE TO EL. 19.0 OR BELOW TO HAVE A FACTOR OF SAFETY OF 2 OR GREATER AGAINST PIPING.
 3) SOIL PARAMETERS ARE TAKEN FROM FIGURE 6 OF 7 OCTOBER 1967 REPORT.
 4) THIS DRAWING IS A REVISION OF FIGURE 39 OF THE REFERENCED REPORT REFLECTING A RAISED STORM WATER LEVEL.



FLOODGATE STABILITY ANALYSIS
 DESTREHAN AVENUE
 WEST JEFFERSON LEVEE DISTRICT
 COUSINS PUMP STATION TO FIRST AVENUE CANAL
 HARVEY, LOUISIANA

SUBSTRUCTURE:

GATE MONOLITH FORCES:

WT OF ROLLER GATE:

BEAM	W33x118	:	118x47	=	5546 #
SKIN	3/8" x 60' x 47'	=			3596 #
					<u>9142</u>
					1371
					<u>10,513 #</u>
					- use 11 #

TRAFFIC LOADS:

- REMAIN THE SAME

WATER LOADS:

water @ 2' + 2' : $(64)(7+2.5) = 608 \text{ PSF } (0.75) = 456 \text{ PSF}$

water @ 5' : $(64)(5+2.5) = 480 \text{ PSF}$

WIND LOADS: 50 PSF FOR HURRICANE WIND:

AREA = $(54)(7) = 378 \text{ SF}$

FORCE = $378(50) = 18900 \#$

11.00' 200# CYCLO WHITE 5 SQUARE
 12.00' 200# CYCLO WHITE 5 SQUARE
 13.00' 200# CYCLO WHITE 5 SQUARE
 14.00' 200# CYCLO WHITE 5 SQUARE
 15.00' 200# CYCLO WHITE 5 SQUARE
 16.00' 200# CYCLO WHITE 5 SQUARE
 17.00' 200# CYCLO WHITE 5 SQUARE
 18.00' 200# CYCLO WHITE 5 SQUARE
 19.00' 200# CYCLO WHITE 5 SQUARE
 20.00' 200# CYCLO WHITE 5 SQUARE
 21.00' 200# CYCLO WHITE 5 SQUARE
 22.00' 200# CYCLO WHITE 5 SQUARE
 23.00' 200# CYCLO WHITE 5 SQUARE
 24.00' 200# CYCLO WHITE 5 SQUARE
 25.00' 200# CYCLO WHITE 5 SQUARE
 26.00' 200# CYCLO WHITE 5 SQUARE
 27.00' 200# CYCLO WHITE 5 SQUARE
 28.00' 200# CYCLO WHITE 5 SQUARE
 29.00' 200# CYCLO WHITE 5 SQUARE
 30.00' 200# CYCLO WHITE 5 SQUARE
 31.00' 200# CYCLO WHITE 5 SQUARE
 32.00' 200# CYCLO WHITE 5 SQUARE
 33.00' 200# CYCLO WHITE 5 SQUARE
 34.00' 200# CYCLO WHITE 5 SQUARE
 35.00' 200# CYCLO WHITE 5 SQUARE
 36.00' 200# CYCLO WHITE 5 SQUARE
 37.00' 200# CYCLO WHITE 5 SQUARE
 38.00' 200# CYCLO WHITE 5 SQUARE
 39.00' 200# CYCLO WHITE 5 SQUARE
 40.00' 200# CYCLO WHITE 5 SQUARE
 41.00' 200# CYCLO WHITE 5 SQUARE
 42.00' 200# CYCLO WHITE 5 SQUARE
 43.00' 200# CYCLO WHITE 5 SQUARE
 44.00' 200# CYCLO WHITE 5 SQUARE
 45.00' 200# CYCLO WHITE 5 SQUARE
 46.00' 200# CYCLO WHITE 5 SQUARE
 47.00' 200# CYCLO WHITE 5 SQUARE
 48.00' 200# CYCLO WHITE 5 SQUARE
 49.00' 200# CYCLO WHITE 5 SQUARE
 50.00' 200# CYCLO WHITE 5 SQUARE
 51.00' 200# CYCLO WHITE 5 SQUARE
 52.00' 200# CYCLO WHITE 5 SQUARE
 53.00' 200# CYCLO WHITE 5 SQUARE
 54.00' 200# CYCLO WHITE 5 SQUARE
 55.00' 200# CYCLO WHITE 5 SQUARE
 56.00' 200# CYCLO WHITE 5 SQUARE
 57.00' 200# CYCLO WHITE 5 SQUARE
 58.00' 200# CYCLO WHITE 5 SQUARE
 59.00' 200# CYCLO WHITE 5 SQUARE
 60.00' 200# CYCLO WHITE 5 SQUARE
 61.00' 200# CYCLO WHITE 5 SQUARE
 62.00' 200# CYCLO WHITE 5 SQUARE
 63.00' 200# CYCLO WHITE 5 SQUARE
 64.00' 200# CYCLO WHITE 5 SQUARE
 65.00' 200# CYCLO WHITE 5 SQUARE
 66.00' 200# CYCLO WHITE 5 SQUARE
 67.00' 200# CYCLO WHITE 5 SQUARE
 68.00' 200# CYCLO WHITE 5 SQUARE
 69.00' 200# CYCLO WHITE 5 SQUARE
 70.00' 200# CYCLO WHITE 5 SQUARE
 71.00' 200# CYCLO WHITE 5 SQUARE
 72.00' 200# CYCLO WHITE 5 SQUARE
 73.00' 200# CYCLO WHITE 5 SQUARE
 74.00' 200# CYCLO WHITE 5 SQUARE
 75.00' 200# CYCLO WHITE 5 SQUARE
 76.00' 200# CYCLO WHITE 5 SQUARE
 77.00' 200# CYCLO WHITE 5 SQUARE
 78.00' 200# CYCLO WHITE 5 SQUARE
 79.00' 200# CYCLO WHITE 5 SQUARE
 80.00' 200# CYCLO WHITE 5 SQUARE
 81.00' 200# CYCLO WHITE 5 SQUARE
 82.00' 200# CYCLO WHITE 5 SQUARE
 83.00' 200# CYCLO WHITE 5 SQUARE
 84.00' 200# CYCLO WHITE 5 SQUARE
 85.00' 200# CYCLO WHITE 5 SQUARE
 86.00' 200# CYCLO WHITE 5 SQUARE
 87.00' 200# CYCLO WHITE 5 SQUARE
 88.00' 200# CYCLO WHITE 5 SQUARE
 89.00' 200# CYCLO WHITE 5 SQUARE
 90.00' 200# CYCLO WHITE 5 SQUARE
 91.00' 200# CYCLO WHITE 5 SQUARE
 92.00' 200# CYCLO WHITE 5 SQUARE
 93.00' 200# CYCLO WHITE 5 SQUARE
 94.00' 200# CYCLO WHITE 5 SQUARE
 95.00' 200# CYCLO WHITE 5 SQUARE
 96.00' 200# CYCLO WHITE 5 SQUARE
 97.00' 200# CYCLO WHITE 5 SQUARE
 98.00' 200# CYCLO WHITE 5 SQUARE
 99.00' 200# CYCLO WHITE 5 SQUARE
 100.00' 200# CYCLO WHITE 5 SQUARE





11.25" 220 SHEET WHITE 5 SQUARE
 11.25" 400 SHEET WHITE 5 SQUARE
 11.25" 600 SHEET WHITE 5 SQUARE
 11.25" 800 SHEET WHITE 5 SQUARE
 11.25" 1000 SHEET WHITE 5 SQUARE
 11.25" 1200 SHEET WHITE 5 SQUARE
 11.25" 1400 SHEET WHITE 5 SQUARE
 11.25" 1600 SHEET WHITE 5 SQUARE
 11.25" 1800 SHEET WHITE 5 SQUARE
 11.25" 2000 SHEET WHITE 5 SQUARE
 Made in U.S.A.

GATE MONOLITH FORCE TABULATIONS

ITEM	COMPUTATIONS	FORCES IN KIPS			LEVER ARM, FT			MOMENTS IN FT-K		
		F _x	F _y	F _z	X	Y	Z	M _{A-x}	M _{A-y}	M _{A-z}
I	DEAD LOADS									
① COLUMNS (2 EA)	(3.5')(2.75')(7')(150)(2)			20.21	1.625				-32.84	
	(3.5')(1.75')(7')(150)(2)			12.86	1.375				-17.68	
	(1')(0.25')(3.5')(7')(150)(2)			0.92	0.42				-0.39	
② FOOTING	(8.5')(2.5')(54.0')(150)			172.12						
③ GATE OPEN but 1/3' from end	1/3 (11) :			3.69	-1.75'	-19.0'			-69.73	6.42
I a	Σ LOADING, GATE OPEN			209.78					-69.73	-44.49
④ GATE CLOSED				11.0	-1.75				19.25	
I b	Σ LOADING, GATE CLOSED			217.11					-31.66	
II	WATER @ 11.5 (SWL + 2')									
HYDROSTATIC PRESSURE (a)	(11')(1.61)(9.5')(54')	156.47					3.17		-496.0	
WATER WT BUOYANCY	(11')(7')(54')(1.64)			24.19	-3.75				+90.71	
IMPRESSIONS (a)	(1.61)(4.25)(54)			-140.0	-2.155				-297.50	
REFLECTIONS (b)	(1.61)(1')(8.5')(54)			-140.0	-1.417				-198.38	

JN 3003

LOADING TURN ON FOR
FLOODGATE

A4H

2-5-98

4

GATE MONOLITH FORCE TABULATIONS

ITEM	COMPUTATIONS	FORCES IN KIPS			LEVER ARM, FT			MOMENTS IN FT.K		
		F _x	F _y	F _z	x	y	z	M _{x-z}	M _{y-y}	M _{z-z}
I (a)	WATER PRESSURE	156.17		-115.21					-702.79	
I (b)	WATER PRESSURE	156.17		-115.21					-603.67	
III	WATER WEIGHT									
	WATER WEIGHT	97.2					2.5		-243.0	
	WATER WEIGHT			17.28	-3.75				164.8	
	BUOYANCY									
	BUOYANCY			-110.16	-3.25				-234.09	
	BUOYANCY			-110.16	-1.117				-156.10	
III (a)	WATER PRESSURE			-11.22					-412.29	
III (b)	WATER PRESSURE			-11.22					-334.3	
IV (a)	WATER WEIGHT	-18.9					3.5		+66.15	
IV (b)	WATER WEIGHT	18.9					3.5		-66.15	
V (a)	WATER PRESSURE			86.4	11.25	-1.0		-86.4	-367.2	
V (b)	WATER PRESSURE			86.4	11.25	-1.0		-86.4	+367.2	

2113003

FLOODGATE

AAH

2-5-98

4/5

LOAD COMBINATIONS

LOADING CASE	DESCRIPTION	FORCES		MOMENTS	
		F _x	F _y	M _y	M _x
VII	GATE OPEN, NO WIND, TRUCKS ON F/S (100% FORCES)				
			209.78	-44.49	-69.73
		I(a) I(a)	86.4	-367.2	-86.4
		TOTAL	296.18	-411.39	-156.13
VIII	GATE OPEN, NO WIND, TRUCKS ON F/S (100% FORCES)				
			209.78	-44.49	-69.73
		I(a) I(b)	86.4	-367.2	-86.4
		TOTAL	296.18	-411.39	-156.13

→ 2.3 SLAB PER SIDE
 1.5' SLAB PER SIDE


ADD 2 PILES
 - opposite

2000 LBS EQ. ON F/S
 45'

+1.5' 2.3' F
 2.0
 1.5
 1.0
 0.5
 0.0
 -0.5
 -1.0
 -1.5
 -2.0
 -2.5
 -3.0
 -3.5
 -4.0
 -4.5
 -5.0
 -5.5
 -6.0
 -6.5
 -7.0
 -7.5
 -8.0
 -8.5
 -9.0
 -9.5
 -10.0

2.5
 1.5
 1.0
 0.5

1.5



1010 DEST. HAN AVENUE FLOODGATE
 1020 PROP 4030 3201 3201 196 2 0 ALL
 1030 SOIL ES 0.866 LEN 68 0 ALL
 1040 PIN ALL
 1050 DLS S 78 48 600.2 223.1 132.6 1510.0 1166.8 H 14 ALL
 1060 ASC S 196 457 0.816 0.856 2 0 ALL
 1070 BATTER 2 1 2 7 8 9 12 13 14
 1080 ANGLE 0 1 2 3 4 5 6 7 14
 1090 ANGLE 180 8 9 10 11 12 13
 1100 PILE 1 -2.75 -24.5 0
 1110 PILE 2 -2.75 -17.5 0
 1120 PILE 3 -2.75 -10.5 0
 1130 PILE 4 -2.75 -3.5 0
 1140 PILE 5 -2.75 3.5 0
 1150 PILE 6 -2.75 10.5 0
 1160 PILE 7 -2.75 17.5 0
 1170 PILE 8 2.75 -22.5 0
 1180 PILE 9 2.75 -13.5 0
 1190 PILE 10 2.75 -4.5 0
 1192 PILE 11 2.75 4.5 0
 1194 PILE 12 2.75 13.5 0
 1196 PILE 13 2.75 22.5 0
 1198 PILE 14 -2.75 24.5 0
 1200 LOAD 1 97.2 0 124.23 0 -443.95 0
 1210 LOAD 2 97.2 0 124.23 0 -365.96 0
 1220 LOAD 3 117.35 0 75.98 0 -550.84 0
 1230 LOAD 4 117.35 0 75.98 0 -476.5 0
 1240 LOAD 5 -14.18 0 162.83 0 25.87 0
 1250 LOAD 6 14.18 0 162.83 0 -73.36 0
 1260 LOAD 7 0 0 296.18 -156.13 -411.39 0
 1270 LOAD 8 0 0 296.18 -156.13 322.71 0
 1280 FOUT 1 2 3 4 5 6 7 FGATEOUT
 1290 PFO ALL
 1300 FPL N

***** .*****
 * CORPS PROGRAM # X0080 * CPGA - CASE PILE GROUP ANALYSIS PROGRAM
 * VERSION NUMBER # 86/09/02-A * RUN DATE 07-13-98 RUN TIME 16:16:24

DESTRAHAN AVENUE FLOODGATE

THERE ARE 14 PILES AND
 8 LOAD CASES IN THIS RUN.

ALL PILE COORDINATES ARE CONTAINED WITHIN A BOX

WITH DIAGONAL COORDINATES = { $\begin{matrix} X & Y & Z \\ \hline -2.75 & -24.50 & .00 \\ 2.75 & 24.50 & .00 \end{matrix}$ }

PILE PROPERTIES AS INPUT

E	I1	I2	A	C33	B66
KSI	IN**4	IN**4	IN**2		
.40300E+04	.32010E+04	.32010E+04	.19600E+03	.20000E+01	.00000E+00

THESE PILE PROPERTIES APPLY TO THE FOLLOWING PILES -

ALL

SOIL DESCRIPTIONS AS INPUT

ES	ESOIL	LENGTH	L	LU
	K/IN**2	L	FT	FT
	.86600E+00		.68000E+02	.00000E+00

THIS SOIL DESCRIPTION APPLIES TO THE FOLLOWING PILES -

ALL

PILE GEOMETRY AS INPUT AND/OR GENERATED

NUM	X	Y	Z	BATTER	ANGLE	LENGTH	FIXITY
	FT	FT	FT			FT	
1	-2.75	-24.50	.00	2.00	.00	68.00	P
2	-2.75	-17.50	.00	2.00	.00	68.00	P
3	-2.75	-10.50	.00	V	.00	68.00	P
4	-2.75	-3.50	.00	V	.00	68.00	P
5	-2.75	3.50	.00	V	.00	68.00	P
6	-2.75	10.50	.00	V	.00	68.00	P

7	-2.75	17.50	.00	2.00	.00	68.00	P
8	2.75	-22.50	.00	2.00	180.00	68.00	PP
9	2.75	-13.50	.00	2.00	180.00	68.00	PPP
10	2.75	-4.50	.00	V	180.00	68.00	PPPP
11	2.75	4.50	.00	V	180.00	68.00	PPPP
12	2.75	13.50	.00	2.00	180.00	68.00	PPP
13	2.75	22.50	.00	2.00	180.00	68.00	PPP
14	-2.75	24.50	.00	2.00	.00	68.00	P
						952.00	

APPLIED LOADS

LOAD CASE	PX K	PY K	PZ K	MX FT-K	MY FT-K	MZ FT-K
1	97.2	.0	124.2	.0	-444.0	.0
2	97.2	.0	124.2	.0	-366.0	.0
3	117.3	.0	76.0	.0	-550.8	.0
4	117.3	.0	76.0	.0	-476.5	.0
5	-14.2	.0	162.8	.0	25.9	.0
6	14.2	.0	162.8	.0	-73.4	.0
7	.0	.0	296.2	-156.1	-411.4	.0
8	.0	.0	296.2	-156.1	322.7	.0

ORIGINAL PILE GROUP STIFFNESS MATRIX

.35693E+04	.13274E-03	.00000E+00	.00000E+00	.20042E+06	.78125E-02
.13274E-03	.53260E+03	-.26548E-03	.00000E+00	.87607E-02	-.25108E+04
.00000E+00	-.26548E-03	.24067E+05	.12500E+00	.12777E+06	.00000E+00
.00000E+00	.00000E+00	.12500E+00	.79454E+09	-.30000E+01	-.47664E+08
.20042E+06	.87607E-02	.12777E+06	-.20000E+01	.26209E+08	.50000E+00
.78125E-02	-.25108E+04	.00000E+00	-.47664E+08	-.15000E+01	.19399E+09

LOAD CASE	1.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	8.
LOAD CASE	2.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	8.
LOAD CASE	3.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	8.
LOAD CASE	4.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	8.
LOAD CASE	5.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	6.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.
LOAD CASE	7.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	4.
LOAD CASE	8.	NUMBER OF FAILURES =	0.	NUMBER OF PILES IN TENSION =	0.

FILE CAP DISPLACEMENTS

LOAD CASE	DX IN	DY IN	DZ IN	RX RAD	RY RAD	RZ RAD
1	.7225E-01	-.1739E-09	.9418E-02	-.5131E-11	-.8017E-03	-.1037E-10
2	.6857E-01	-.5048E-09	.9070E-02	-.4784E-11	-.7361E-03	-.9635E-11
3	.8638E-01	-.1818E-08	.8216E-02	-.5625E-11	-.9528E-03	-.1225E-10
4	.8287E-01	-.2133E-08	.7884E-02	-.5295E-11	-.8903E-03	-.1155E-10
5	-.4925E-02	.4277E-08	.6676E-02	-.9775E-12	.1696E-04	.1447E-12
6	.1397E-01	.3279E-08	.7711E-02	-.2029E-11	-.1780E-03	-.2395E-11
7	.2560E-01	-.2764E-05	.1473E-01	-.2393E-05	-.4559E-03	-.5881E-06
8	-.9046E-02	-.2767E-05	.1145E-01	-.2393E-05	.1611E-03	-.5881E-06

PILE FORCES IN LOCAL GEOMETRY

M1 & M2 NOT AT PILE HEAD FOR PINNED PILES
 * INDICATES PILE FAILURE
 # INDICATES CBF BASED ON MOMENTS DUE TO (F3*EMIN) FOR CONCRETE PILES
 B INDICATES BUCKLING CONTROLS

LOAD CASE - 1

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	2.7	.0	33.1	.0	-77.7	.0	.42	.21	1.19	.81
2	2.7	.0	33.1	.0	-77.7	.0	.42	.21	1.19	.81
3	2.7	.0	-33.0	.0	-77.8	.0	.69	.58	.86	.48
4	2.7	.0	-33.0	.0	-77.8	.0	.69	.58	.86	.48
5	2.7	.0	-33.0	.0	-77.8	.0	.69	.58	.86	.48
6	2.7	.0	-33.0	.0	-77.8	.0	.69	.58	.86	.48
7	2.7	.0	33.1	.0	-77.7	.0	.42	.21	1.19	.81
8	-3.1	.0	-.4	.0	86.8	.0	.01	.21	1.04	.62
9	-3.1	.0	-.4	.0	86.8	.0	.01	.21	1.04	.62
10	-2.7	.0	69.4	.0	77.8	.0	.89	.29	1.38	1.00
11	-2.7	.0	69.4	.0	77.8	.0	.89	.29	1.38	1.00
12	-3.1	.0	-.4	.0	86.8	.0	.01	.21	1.04	.62
13	-3.1	.0	-.4	.0	86.8	.0	.01	.21	1.04	.62
14	2.7	.0	33.1	.0	-77.7	.0	.42	.21	1.19	.81

LOAD CASE - 2

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	2.6	.0	33.0	.0	-73.3	.0	.42	.21	1.18	.82
2	2.6	.0	33.0	.0	-73.3	.0	.42	.21	1.18	.82
3	2.6	.0	-29.5	.0	-73.8	.0	.61	.53	.87	.50
4	2.6	.0	-29.5	.0	-73.8	.0	.61	.53	.87	.50
5	2.6	.0	-29.5	.0	-73.8	.0	.61	.53	.87	.50
6	2.6	.0	-29.5	.0	-73.8	.0	.61	.53	.87	.50

7	.6	.0	33.0	.0	-73.3	.0	.42	.21	1.18	.82
8	-2.9	.0	-1.6	.0	82.1	.0	.03	.21	1.03	.63
9	-2.9	.0	-1.6	.0	82.1	.0	.03	.21	1.03	.63
10	-2.6	.0	64.6	.0	73.8	.0	.83	.25	1.35	.98
11	-2.6	.0	64.6	.0	73.8	.0	.83	.25	1.35	.98
12	-2.9	.0	-1.6	.0	82.1	.0	.03	.21	1.03	.63
13	-2.9	.0	-1.6	.0	82.1	.0	.03	.21	1.03	.63
14	2.6	.0	33.0	.0	-73.3	.0	.42	.21	1.18	.82

#

LOAD CASE - 3

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	3.3	.0	34.6	.0	-94.3	.0	.44	.24	1.24	.79
2	3.3	.0	34.6	.0	-94.3	.0	.44	.24	1.24	.79
3	3.3	.0	-45.0	.0	-93.0	.0	.94	.76	.83	.38
4	3.3	.0	-45.0	.0	-93.0	.0	.94	.76	.83	.38
5	3.3	.0	-45.0	.0	-93.0	.0	.94	.76	.83	.38
6	3.3	.0	-45.0	.0	-93.0	.0	.94	.76	.83	.38
7	3.3	.0	34.6	.0	-94.3	.0	.44	.24	1.24	.79
8	-3.6	.0	-6.1	.0	102.2	.0	.13	.31	1.05	.56
9	-3.6	.0	-6.1	.0	102.2	.0	.13	.31	1.05	.56
10	-3.3	.0	76.8	.0	93.0	.0	.98	.35	1.45	1.00
11	-3.3	.0	76.8	.0	93.0	.0	.98	.35	1.45	1.00
12	-3.6	.0	-6.1	.0	102.2	.0	.13	.31	1.05	.56
13	-3.6	.0	-6.1	.0	102.2	.0	.13	.31	1.05	.56
14	3.3	.0	34.6	.0	-94.3	.0	.44	.24	1.24	.79

#

LOAD CASE - 4

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	3.2	.0	34.5	.0	-90.1	.0	.44	.23	1.23	.79
2	3.2	.0	34.5	.0	-90.1	.0	.44	.23	1.23	.79
3	3.2	.0	-41.6	.0	-89.2	.0	.87	.71	.84	.41
4	3.2	.0	-41.6	.0	-89.2	.0	.87	.71	.84	.41
5	3.2	.0	-41.6	.0	-89.2	.0	.87	.71	.84	.41
6	3.2	.0	-41.6	.0	-89.2	.0	.87	.71	.84	.41
7	3.2	.0	34.5	.0	-90.1	.0	.44	.23	1.23	.79
8	-3.5	.0	-7.2	.0	97.7	.0	.15	.31	1.03	.57
9	-3.5	.0	-7.2	.0	97.7	.0	.15	.31	1.03	.57
10	-3.2	.0	72.1	.0	89.2	.0	.92	.31	1.42	.99
11	-3.2	.0	72.1	.0	89.2	.0	.92	.31	1.42	.99
12	-3.5	.0	-7.2	.0	97.7	.0	.15	.31	1.03	.57
13	-3.5	.0	-7.2	.0	97.7	.0	.15	.31	1.03	.57
14	3.2	.0	34.5	.0	-90.1	.0	.44	.23	1.23	.79

#

LOAD CASE - 5

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
1	-.3	.0	8.3	.0	8.2	.0	.11	.21	.92	.84
2	-.3	.0	8.3	.0	8.2	.0	.11	.21	.92	.84
3	-.2	.0	14.0	.0	5.3	.0	.18	.20	.94	.88

#

4	.2	.0	14.0	.0	5.3	.0	.18	.20	.94	.88	#
5	-.2	.0	14.0	.0	5.3	.0	.18	.20	.94	.88	#
6	-.2	.0	14.0	.0	5.3	.0	.18	.20	.94	.88	#
7	-.3	.0	8.3	.0	8.2	.0	.11	.21	.92	.84	#
8	.1	.0	14.9	.0	-1.8	.0	.19	.20	.94	.89	#
9	.1	.0	14.9	.0	-1.8	.0	.19	.20	.94	.89	#
10	.2	.0	11.8	.0	-5.3	.0	.15	.20	.93	.86	#
11	.2	.0	11.8	.0	-5.3	.0	.15	.20	.93	.86	#
12	.1	.0	14.9	.0	-1.8	.0	.19	.20	.94	.89	#
13	.1	.0	14.9	.0	-1.8	.0	.19	.20	.94	.89	#
14	-.3	.0	8.3	.0	8.2	.0	.11	.21	.92	.84	#

LOAD CASE - 6

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.4	.0	15.3	.0	-12.6	.0	.20	.19	.96	.87	#
2	.4	.0	15.3	.0	-12.6	.0	.20	.19	.96	.87	#
3	.5	.0	3.6	.0	-15.0	.0	.05	.24	.91	.80	
4	.5	.0	3.6	.0	-15.0	.0	.05	.24	.91	.80	
5	.5	.0	3.6	.0	-15.0	.0	.05	.24	.91	.80	
6	.5	.0	3.6	.0	-15.0	.0	.05	.24	.91	.80	
7	.4	.0	15.3	.0	-12.6	.0	.20	.19	.96	.87	#
8	-.7	.0	11.4	.0	20.0	.0	.15	.21	.96	.83	
9	-.7	.0	11.4	.0	20.0	.0	.15	.21	.96	.83	
10	-.5	.0	26.3	.0	15.0	.0	.34	.17	1.02	.92	#
11	-.5	.0	26.3	.0	15.0	.0	.34	.17	1.02	.92	#
12	-.7	.0	11.4	.0	20.0	.0	.15	.21	.96	.83	
13	-.7	.0	11.4	.0	20.0	.0	.15	.21	.96	.83	
14	.4	.0	15.3	.0	-12.6	.0	.20	.19	.96	.87	#

LOAD CASE - 7

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI	
1	.9	.0	22.7	.0	-24.3	.0	.29	.18	1.02	.88	#
2	.9	.0	22.4	.0	-24.4	.0	.29	.18	1.02	.88	#
3	1.0	.0	.0	.0	-27.5	.0	.00	.06	.92	.76	
4	1.0	.0	-.4	.0	-27.5	.0	.01	.07	.91	.75	
5	1.0	.0	-.8	.0	-27.6	.0	.02	.07	.91	.75	
6	1.0	.0	-1.2	.0	-27.6	.0	.03	.08	.91	.75	
7	.9	.0	20.9	.0	-25.2	.0	.27	.18	1.02	.87	#
8	-1.4	.0	30.6	.0	39.1	.0	.39	.16	1.10	.89	#
9	-1.4	.0	30.1	.0	39.1	.0	.39	.16	1.10	.88	#
10	-1.0	.0	57.9	.0	27.5	.0	.74	.20	1.21	1.05	#
11	-1.0	.0	57.4	.0	27.6	.0	.74	.19	1.21	1.05	#
12	-1.4	.0	28.6	.0	38.9	.0	.37	.17	1.09	.88	#
13	-1.4	.0	28.1	.0	38.8	.0	.36	.17	1.08	.87	#
14	.9	.0	20.5	.0	-25.3	.0	.26	.18	1.02	.87	#

LOAD CASE - 8

PILE	F1 K	F2 K	F3 K	M1 IN-K	M2 IN-K	M3 IN-K	ALF	CBF	ASC KSI	AST KSI
------	---------	---------	---------	------------	------------	------------	-----	-----	------------	------------

1	.6	.0	22.3	.0	17.3	.0	.29	.18	1.01	.89	#
2	-.6	.0	22.0	.0	17.1	.0	.28	.18	1.01	.89	#
3	.3	.0	33.0	.0	9.8	.0	.42	.16	1.05	.96	#
4	.3	.0	32.7	.0	9.8	.0	.42	.16	1.04	.96	#
5	.3	.0	32.3	.0	9.7	.0	.41	.16	1.04	.96	#
6	.3	.0	31.9	.0	9.7	.0	.41	.16	1.04	.96	#
7	.6	.0	20.4	.0	16.4	.0	.26	.18	1.00	.88	#
8	.2	.0	19.7	.0	-5.6	.0	.25	.19	.97	.90	#
9	.2	.0	19.2	.0	-5.7	.0	.25	.19	.97	.90	#
10	.3	.0	12.1	.0	-9.8	.0	.16	.20	.94	.86	#
11	.3	.0	11.6	.0	-9.7	.0	.15	.20	.94	.85	#
12	.2	.0	17.7	.0	-5.9	.0	.23	.19	.96	.89	#
13	.2	.0	17.2	.0	-5.9	.0	.22	.19	.96	.89	#
14	-.6	.0	20.1	.0	16.3	.0	.26	.18	.99	.88	#

PILE FORCES IN GLOBAL GEOMETRY

LOAD CASE - 1

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	17.2	.0	28.3	.0	.0	.0
2	17.2	.0	28.3	.0	.0	.0
3	2.7	.0	-33.0	.0	.0	.0
4	2.7	.0	-33.0	.0	.0	.0
5	2.7	.0	-33.0	.0	.0	.0
6	2.7	.0	-33.0	.0	.0	.0
7	17.2	.0	28.3	.0	.0	.0
8	2.9	.0	1.0	.0	.0	.0
9	2.9	.0	1.0	.0	.0	.0
10	2.7	.0	69.4	.0	.0	.0
11	2.7	.0	69.4	.0	.0	.0
12	2.9	.0	1.0	.0	.0	.0
13	2.9	.0	1.0	.0	.0	.0
14	17.2	.0	28.3	.0	.0	.0

LOAD CASE - 2

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	17.1	.0	28.4	.0	.0	.0
2	17.1	.0	28.4	.0	.0	.0
3	2.6	.0	-29.5	.0	.0	.0
4	2.6	.0	-29.5	.0	.0	.0
5	2.6	.0	-29.5	.0	.0	.0
6	2.6	.0	-29.5	.0	.0	.0
7	17.1	.0	28.4	.0	.0	.0
8	3.3	.0	-.1	.0	.0	.0
9	3.3	.0	-.1	.0	.0	.0
10	2.6	.0	64.6	.0	.0	.0
11	2.6	.0	64.6	.0	.0	.0
12	3.3	.0	-.1	.0	.0	.0

13	3.3	.0	- .1	.0	.0	.0
14	17.1	.0	28.4	.0	.0	.0

LOAD CASE - 3

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	18.4	.0	29.4	.0	.0	.0
2	18.4	.0	29.4	.0	.0	.0
3	3.3	.0	-45.0	.0	.0	.0
4	3.3	.0	-45.0	.0	.0	.0
5	3.3	.0	-45.0	.0	.0	.0
6	3.3	.0	-45.0	.0	.0	.0
7	18.4	.0	29.4	.0	.0	.0
8	6.0	.0	-3.9	.0	.0	.0
9	6.0	.0	-3.9	.0	.0	.0
10	3.3	.0	76.8	.0	.0	.0
11	3.3	.0	76.8	.0	.0	.0
12	6.0	.0	-3.9	.0	.0	.0
13	6.0	.0	-3.9	.0	.0	.0
14	18.4	.0	29.4	.0	.0	.0

LOAD CASE - 4

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	18.3	.0	29.5	.0	.0	.0
2	18.3	.0	29.5	.0	.0	.0
3	3.2	.0	-41.6	.0	.0	.0
4	3.2	.0	-41.6	.0	.0	.0
5	3.2	.0	-41.6	.0	.0	.0
6	3.2	.0	-41.6	.0	.0	.0
7	18.3	.0	29.5	.0	.0	.0
8	6.3	.0	-4.9	.0	.0	.0
9	6.3	.0	-4.9	.0	.0	.0
10	3.2	.0	72.1	.0	.0	.0
11	3.2	.0	72.1	.0	.0	.0
12	6.3	.0	-4.9	.0	.0	.0
13	6.3	.0	-4.9	.0	.0	.0
14	18.3	.0	29.5	.0	.0	.0

LOAD CASE - 5

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	3.4	.0	7.5	.0	.0	.0
2	3.4	.0	7.5	.0	.0	.0
3	- .2	.0	14.0	.0	.0	.0
4	- .2	.0	14.0	.0	.0	.0
5	- .2	.0	14.0	.0	.0	.0
6	- .2	.0	14.0	.0	.0	.0
7	3.4	.0	7.5	.0	.0	.0
8	-6.7	.0	13.3	.0	.0	.0
9	-6.7	.0	13.3	.0	.0	.0

10	-.2	.0	11.8	.0	.0	.0
11	-.2	.0	11.8	.0	.0	.0
12	-6.7	.0	13.3	.0	.0	.0
13	-6.7	.0	13.3	.0	.0	.0
14	3.4	.0	7.5	.0	.0	.0

LOAD CASE - 6

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	7.2	.0	13.5	.0	.0	.0
2	7.2	.0	13.5	.0	.0	.0
3	.5	.0	3.6	.0	.0	.0
4	.5	.0	3.6	.0	.0	.0
5	.5	.0	3.6	.0	.0	.0
6	.5	.0	3.6	.0	.0	.0
7	7.2	.0	13.5	.0	.0	.0
8	-4.5	.0	10.5	.0	.0	.0
9	-4.5	.0	10.5	.0	.0	.0
10	.5	.0	26.3	.0	.0	.0
11	.5	.0	26.3	.0	.0	.0
12	-4.5	.0	10.5	.0	.0	.0
13	-4.5	.0	10.5	.0	.0	.0
14	7.2	.0	13.5	.0	.0	.0

LOAD CASE - 7

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	10.9	.0	19.9	.0	.0	.0
2	10.8	.0	19.6	.0	.0	.0
3	1.0	.0	.0	.0	.0	.0
4	1.0	.0	-.4	.0	.0	.0
5	1.0	.0	-.8	.0	.0	.0
6	1.0	.0	-1.2	.0	.0	.0
7	10.1	.0	18.3	.0	.0	.0
8	-12.5	.0	28.0	.0	.0	.0
9	-12.2	.0	27.6	.0	.0	.0
10	1.0	.0	57.9	.0	.0	.0
11	1.0	.0	57.4	.0	.0	.0
12	-11.6	.0	26.2	.0	.0	.0
13	-11.4	.0	25.8	.0	.0	.0
14	10.0	.0	18.0	.0	.0	.0

LOAD CASE - 8

PILE	PX K	PY K	PZ K	MX IN-K	MY IN-K	MZ IN-K
1	9.4	.0	20.2	.0	.0	.0
2	9.3	.0	19.9	.0	.0	.0
3	-.3	.0	33.0	.0	.0	.0
4	-.3	.0	32.7	.0	.0	.0
5	-.3	.0	32.3	.0	.0	.0
6	-.3	.0	31.9	.0	.0	.0

7
8
9
10
11
12
13
14

-19.8
-18.8
-18.8
-18.3
-18.3
-17.9
8.5

.0
.0
.0
.0
.0
.0
.0

18.5
17.5
17.1
12.1
11.6
15.7
15.3
18.3

.0
.0
.0
.0
.0
.0
.0

.0
.0
.0
.0
.0
.0
.0

.0
.0
.0
.0
.0
.0
.0

MAX LOAD = ~~40.4~~^{76.8} C
~~-14.0~~^{-45.0} T

LOAD CASE 7 3



LOAD CASE 3

ALLOWABLES : 39^T = 78^K C OK ✓
24^T = 48^K T OK ✓

500 SHEET 10, 14, 17, 18 SQUARE
60 SHEETS 11, 12, 13, 15, 16 SQUARE
70 SHEETS 19, 20, 21, 22, 23, 24 SQUARE
80 SHEETS 25, 26, 27, 28, 29, 30 SQUARE
90 SHEETS 31, 32, 33, 34, 35, 36 SQUARE
100 SHEETS 37, 38, 39, 40, 41, 42 SQUARE
110 SHEETS 43, 44, 45, 46, 47, 48 SQUARE
120 SHEETS 49, 50, 51, 52, 53, 54 SQUARE
130 SHEETS 55, 56, 57, 58, 59, 60 SQUARE
140 SHEETS 61, 62, 63, 64, 65, 66 SQUARE
150 SHEETS 67, 68, 69, 70, 71, 72 SQUARE
160 SHEETS 73, 74, 75, 76, 77, 78 SQUARE
170 SHEETS 79, 80, 81, 82, 83, 84 SQUARE
180 SHEETS 85, 86, 87, 88, 89, 90 SQUARE
190 SHEETS 91, 92, 93, 94, 95, 96 SQUARE
200 SHEETS 97, 98, 99, 100, 101, 102 SQUARE
210 SHEETS 103, 104, 105, 106, 107, 108 SQUARE
220 SHEETS 109, 110, 111, 112, 113, 114 SQUARE
230 SHEETS 115, 116, 117, 118, 119, 120 SQUARE
240 SHEETS 121, 122, 123, 124, 125, 126 SQUARE
250 SHEETS 127, 128, 129, 130, 131, 132 SQUARE
260 SHEETS 133, 134, 135, 136, 137, 138 SQUARE
270 SHEETS 139, 140, 141, 142, 143, 144 SQUARE
280 SHEETS 145, 146, 147, 148, 149, 150 SQUARE
290 SHEETS 151, 152, 153, 154, 155, 156 SQUARE
300 SHEETS 157, 158, 159, 160, 161, 162 SQUARE
310 SHEETS 163, 164, 165, 166, 167, 168 SQUARE
320 SHEETS 169, 170, 171, 172, 173, 174 SQUARE
330 SHEETS 175, 176, 177, 178, 179, 180 SQUARE
340 SHEETS 181, 182, 183, 184, 185, 186 SQUARE
350 SHEETS 187, 188, 189, 190, 191, 192 SQUARE
360 SHEETS 193, 194, 195, 196, 197, 198 SQUARE
370 SHEETS 199, 200, 201, 202, 203, 204 SQUARE
380 SHEETS 205, 206, 207, 208, 209, 210 SQUARE
390 SHEETS 211, 212, 213, 214, 215, 216 SQUARE
400 SHEETS 217, 218, 219, 220, 221, 222 SQUARE
410 SHEETS 223, 224, 225, 226, 227, 228 SQUARE
420 SHEETS 229, 230, 231, 232, 233, 234 SQUARE
430 SHEETS 235, 236, 237, 238, 239, 240 SQUARE
440 SHEETS 241, 242, 243, 244, 245, 246 SQUARE
450 SHEETS 247, 248, 249, 250, 251, 252 SQUARE
460 SHEETS 253, 254, 255, 256, 257, 258 SQUARE
470 SHEETS 259, 260, 261, 262, 263, 264 SQUARE
480 SHEETS 265, 266, 267, 268, 269, 270 SQUARE
490 SHEETS 271, 272, 273, 274, 275, 276 SQUARE
500 SHEETS 277, 278, 279, 280, 281, 282 SQUARE
510 SHEETS 283, 284, 285, 286, 287, 288 SQUARE
520 SHEETS 289, 290, 291, 292, 293, 294 SQUARE
530 SHEETS 295, 296, 297, 298, 299, 300 SQUARE
540 SHEETS 301, 302, 303, 304, 305, 306 SQUARE
550 SHEETS 307, 308, 309, 310, 311, 312 SQUARE
560 SHEETS 313, 314, 315, 316, 317, 318 SQUARE
570 SHEETS 319, 320, 321, 322, 323, 324 SQUARE
580 SHEETS 325, 326, 327, 328, 329, 330 SQUARE
590 SHEETS 331, 332, 333, 334, 335, 336 SQUARE
600 SHEETS 337, 338, 339, 340, 341, 342 SQUARE
610 SHEETS 343, 344, 345, 346, 347, 348 SQUARE
620 SHEETS 349, 350, 351, 352, 353, 354 SQUARE
630 SHEETS 355, 356, 357, 358, 359, 360 SQUARE
640 SHEETS 361, 362, 363, 364, 365, 366 SQUARE
650 SHEETS 367, 368, 369, 370, 371, 372 SQUARE
660 SHEETS 373, 374, 375, 376, 377, 378 SQUARE
670 SHEETS 379, 380, 381, 382, 383, 384 SQUARE
680 SHEETS 385, 386, 387, 388, 389, 390 SQUARE
690 SHEETS 391, 392, 393, 394, 395, 396 SQUARE
700 SHEETS 397, 398, 399, 400, 401, 402 SQUARE
710 SHEETS 403, 404, 405, 406, 407, 408 SQUARE
720 SHEETS 409, 410, 411, 412, 413, 414 SQUARE
730 SHEETS 415, 416, 417, 418, 419, 420 SQUARE
740 SHEETS 421, 422, 423, 424, 425, 426 SQUARE
750 SHEETS 427, 428, 429, 430, 431, 432 SQUARE
760 SHEETS 433, 434, 435, 436, 437, 438 SQUARE
770 SHEETS 439, 440, 441, 442, 443, 444 SQUARE
780 SHEETS 445, 446, 447, 448, 449, 450 SQUARE
790 SHEETS 451, 452, 453, 454, 455, 456 SQUARE
800 SHEETS 457, 458, 459, 460, 461, 462 SQUARE
810 SHEETS 463, 464, 465, 466, 467, 468 SQUARE
820 SHEETS 469, 470, 471, 472, 473, 474 SQUARE
830 SHEETS 475, 476, 477, 478, 479, 480 SQUARE
840 SHEETS 481, 482, 483, 484, 485, 486 SQUARE
850 SHEETS 487, 488, 489, 490, 491, 492 SQUARE
860 SHEETS 493, 494, 495, 496, 497, 498 SQUARE
870 SHEETS 499, 500, 501, 502, 503, 504 SQUARE
880 SHEETS 505, 506, 507, 508, 509, 510 SQUARE
890 SHEETS 511, 512, 513, 514, 515, 516 SQUARE
900 SHEETS 517, 518, 519, 520, 521, 522 SQUARE
910 SHEETS 523, 524, 525, 526, 527, 528 SQUARE
920 SHEETS 529, 530, 531, 532, 533, 534 SQUARE
930 SHEETS 535, 536, 537, 538, 539, 540 SQUARE
940 SHEETS 541, 542, 543, 544, 545, 546 SQUARE
950 SHEETS 547, 548, 549, 550, 551, 552 SQUARE
960 SHEETS 553, 554, 555, 556, 557, 558 SQUARE
970 SHEETS 559, 560, 561, 562, 563, 564 SQUARE
980 SHEETS 565, 566, 567, 568, 569, 570 SQUARE
990 SHEETS 571, 572, 573, 574, 575, 576 SQUARE
1000 SHEETS 577, 578, 579, 580, 581, 582 SQUARE
1010 SHEETS 583, 584, 585, 586, 587, 588 SQUARE
1020 SHEETS 589, 590, 591, 592, 593, 594 SQUARE
1030 SHEETS 595, 596, 597, 598, 599, 600 SQUARE
1040 SHEETS 601, 602, 603, 604, 605, 606 SQUARE
1050 SHEETS 607, 608, 609, 610, 611, 612 SQUARE
1060 SHEETS 613, 614, 615, 616, 617, 618 SQUARE
1070 SHEETS 619, 620, 621, 622, 623, 624 SQUARE
1080 SHEETS 625, 626, 627, 628, 629, 630 SQUARE
1090 SHEETS 631, 632, 633, 634, 635, 636 SQUARE
1100 SHEETS 637, 638, 639, 640, 641, 642 SQUARE
1110 SHEETS 643, 644, 645, 646, 647, 648 SQUARE
1120 SHEETS 649, 650, 651, 652, 653, 654 SQUARE
1130 SHEETS 655, 656, 657, 658, 659, 660 SQUARE
1140 SHEETS 661, 662, 663, 664, 665, 666 SQUARE
1150 SHEETS 667, 668, 669, 670, 671, 672 SQUARE
1160 SHEETS 673, 674, 675, 676, 677, 678 SQUARE
1170 SHEETS 679, 680, 681, 682, 683, 684 SQUARE
1180 SHEETS 685, 686, 687, 688, 689, 690 SQUARE
1190 SHEETS 691, 692, 693, 694, 695, 696 SQUARE
1200 SHEETS 697, 698, 699, 700, 701, 702 SQUARE
1210 SHEETS 703, 704, 705, 706, 707, 708 SQUARE
1220 SHEETS 709, 710, 711, 712, 713, 714 SQUARE
1230 SHEETS 715, 716, 717, 718, 719, 720 SQUARE
1240 SHEETS 721, 722, 723, 724, 725, 726 SQUARE
1250 SHEETS 727, 728, 729, 730, 731, 732 SQUARE
1260 SHEETS 733, 734, 735, 736, 737, 738 SQUARE
1270 SHEETS 739, 740, 741, 742, 743, 744 SQUARE
1280 SHEETS 745, 746, 747, 748, 749, 750 SQUARE
1290 SHEETS 751, 752, 753, 754, 755, 756 SQUARE
1300 SHEETS 757, 758, 759, 760, 761, 762 SQUARE
1310 SHEETS 763, 764, 765, 766, 767, 768 SQUARE
1320 SHEETS 769, 770, 771, 772, 773, 774 SQUARE
1330 SHEETS 775, 776, 777, 778, 779, 780 SQUARE
1340 SHEETS 781, 782, 783, 784, 785, 786 SQUARE
1350 SHEETS 787, 788, 789, 790, 791, 792 SQUARE
1360 SHEETS 793, 794, 795, 796, 797, 798 SQUARE
1370 SHEETS 799, 800, 801, 802, 803, 804 SQUARE
1380 SHEETS 805, 806, 807, 808, 809, 810 SQUARE
1390 SHEETS 811, 812, 813, 814, 815, 816 SQUARE
1400 SHEETS 817, 818, 819, 820, 821, 822 SQUARE
1410 SHEETS 823, 824, 825, 826, 827, 828 SQUARE
1420 SHEETS 829, 830, 831, 832, 833, 834 SQUARE
1430 SHEETS 835, 836, 837, 838, 839, 840 SQUARE
1440 SHEETS 841, 842, 843, 844, 845, 846 SQUARE
1450 SHEETS 847, 848, 849, 850, 851, 852 SQUARE
1460 SHEETS 853, 854, 855, 856, 857, 858 SQUARE
1470 SHEETS 859, 860, 861, 862, 863, 864 SQUARE
1480 SHEETS 865, 866, 867, 868, 869, 870 SQUARE
1490 SHEETS 871, 872, 873, 874, 875, 876 SQUARE
1500 SHEETS 877, 878, 879, 880, 881, 882 SQUARE
1510 SHEETS 883, 884, 885, 886, 887, 888 SQUARE
1520 SHEETS 889, 890, 891, 892, 893, 894 SQUARE
1530 SHEETS 895, 896, 897, 898, 899, 900 SQUARE
1540 SHEETS 901, 902, 903, 904, 905, 906 SQUARE
1550 SHEETS 907, 908, 909, 910, 911, 912 SQUARE
1560 SHEETS 913, 914, 915, 916, 917, 918 SQUARE
1570 SHEETS 919, 920, 921, 922, 923, 924 SQUARE
1580 SHEETS 925, 926, 927, 928, 929, 930 SQUARE
1590 SHEETS 931, 932, 933, 934, 935, 936 SQUARE
1600 SHEETS 937, 938, 939, 940, 941, 942 SQUARE
1610 SHEETS 943, 944, 945, 946, 947, 948 SQUARE
1620 SHEETS 949, 950, 951, 952, 953, 954 SQUARE
1630 SHEETS 955, 956, 957, 958, 959, 960 SQUARE
1640 SHEETS 961, 962, 963, 964, 965, 966 SQUARE
1650 SHEETS 967, 968, 969, 970, 971, 972 SQUARE
1660 SHEETS 973, 974, 975, 976, 977, 978 SQUARE
1670 SHEETS 979, 980, 981, 982, 983, 984 SQUARE
1680 SHEETS 985, 986, 987, 988, 989, 990 SQUARE
1690 SHEETS 991, 992, 993, 994, 995, 996 SQUARE
1700 SHEETS 997, 998, 999, 1000, 1001, 1002 SQUARE
1710 SHEETS 1003, 1004, 1005, 1006, 1007, 1008 SQUARE
1720 SHEETS 1009, 1010, 1011, 1012, 1013, 1014 SQUARE
1730 SHEETS 1015, 1016, 1017, 1018, 1019, 1020 SQUARE
1740 SHEETS 1021, 1022, 1023, 1024, 1025, 1026 SQUARE
1750 SHEETS 1027, 1028, 1029, 1030, 1031, 1032 SQUARE
1760 SHEETS 1033, 1034, 1035, 1036, 1037, 1038 SQUARE
1770 SHEETS 1039, 1040, 1041, 1042, 1043, 1044 SQUARE
1780 SHEETS 1045, 1046, 1047, 1048, 1049, 1050 SQUARE
1790 SHEETS 1051, 1052, 1053, 1054, 1055, 1056 SQUARE
1800 SHEETS 1057, 1058, 1059, 1060, 1061, 1062 SQUARE
1810 SHEETS 1063, 1064, 1065, 1066, 1067, 1068 SQUARE
1820 SHEETS 1069, 1070, 1071, 1072, 1073, 1074 SQUARE
1830 SHEETS 1075, 1076, 1077, 1078, 1079, 1080 SQUARE
1840 SHEETS 1081, 1082, 1083, 1084, 1085, 1086 SQUARE
1850 SHEETS 1087, 1088, 1089, 1090, 1091, 1092 SQUARE
1860 SHEETS 1093, 1094, 1095, 1096, 1097, 1098 SQUARE
1870 SHEETS 1099, 1100, 1101, 1102, 1103, 1104 SQUARE
1880 SHEETS 1105, 1106, 1107, 1108, 1109, 1110 SQUARE
1890 SHEETS 1111, 1112, 1113, 1114, 1115, 1116 SQUARE
1900 SHEETS 1117, 1118, 1119, 1120, 1121, 1122 SQUARE
1910 SHEETS 1123, 1124, 1125, 1126, 1127, 1128 SQUARE
1920 SHEETS 1129, 1130, 1131, 1132, 1133, 1134 SQUARE
1930 SHEETS 1135, 1136, 1137, 1138, 1139, 1140 SQUARE
1940 SHEETS 1141, 1142, 1143, 1144, 1145, 1146 SQUARE
1950 SHEETS 1147, 1148, 1149, 1150, 1151, 1152 SQUARE
1960 SHEETS 1153, 1154, 1155, 1156, 1157, 1158 SQUARE
1970 SHEETS 1159, 1160, 1161, 1162, 1163, 1164 SQUARE
1980 SHEETS 1165, 1166, 1167, 1168, 1169, 1170 SQUARE
1990 SHEETS 1171, 1172, 1173, 1174, 1175, 1176 SQUARE
2000 SHEETS 1177, 1178, 1179, 1180, 1181, 1182 SQUARE
2010 SHEETS 1183, 1184, 1185, 1186, 1187, 1188 SQUARE
2020 SHEETS 1189, 1190, 1191, 1192, 1193, 1194 SQUARE
2030 SHEETS 1195, 1196, 1197, 1198, 1199, 1200 SQUARE
2040 SHEETS 1201, 1202, 1203, 1204, 1205, 1206 SQUARE
2050 SHEETS 1207, 1208, 1209, 1210, 1211, 1212 SQUARE
2060 SHEETS 1213, 1214, 1215, 1216, 1217, 1218 SQUARE
2070 SHEETS 1219, 1220, 1221, 1222, 1223, 1224 SQUARE
2080 SHEETS 1225, 1226, 1227, 1228, 1229, 1230 SQUARE
2090 SHEETS 1231, 1232, 1233, 1234, 1235, 1236 SQUARE
2100 SHEETS 1237, 1238, 1239, 1240, 1241, 1242 SQUARE
2110 SHEETS 1243, 1244, 1245, 1246, 1247, 1248 SQUARE
2120 SHEETS 1249, 1250, 1251, 1252, 1253, 1254 SQUARE
2130 SHEETS 1255, 1256, 1257, 1258, 1259, 1260 SQUARE
2140 SHEETS 1261, 1262, 1263, 1264, 1265, 1266 SQUARE
2150 SHEETS 1267, 1268, 1269, 1270, 1271, 1272 SQUARE
2160 SHEETS 1273, 1274, 1275, 1276, 1277, 1278 SQUARE
2170 SHEETS 1279, 1280, 1281, 1282, 1283, 1284 SQUARE
2180 SHEETS 1285, 1286, 1287, 1288, 1289, 1290 SQUARE
2190 SHEETS 1291, 1292, 1293, 1294, 1295, 1296 SQUARE
2200 SHEETS 1297, 1298, 1299, 1300, 1301, 1302 SQUARE
2210 SHEETS 1303, 1304, 1305, 1306, 1307, 1308 SQUARE
2220 SHEETS 1309, 1310, 1311, 1312, 1313, 1314 SQUARE
2230 SHEETS 1315, 1316, 1317, 1318, 1319, 1320 SQUARE
2240 SHEETS 1321, 1322, 1323, 1324, 1325, 1326 SQUARE
2250 SHEETS 1327, 1328, 1329, 1330, 1331, 1332 SQUARE
2260 SHEETS 1333, 1334, 1335, 1336, 1337, 1338 SQUARE
2270 SHEETS 1339, 1340, 1341, 1342, 1343, 1344 SQUARE
2280 SHEETS 1345, 1346, 1347, 1348, 1349, 1350 SQUARE
2290 SHEETS 1351, 1352, 1353, 1354, 1355, 1356 SQUARE
2300 SHEETS 1357, 1358, 1359, 1360, 1361, 1362 SQUARE
2310 SHEETS 1363, 1364, 1365, 1366, 1367, 1368 SQUARE
2320 SHEETS 1369, 1370, 1371, 1372, 1373, 1374 SQUARE
2330 SHEETS 1375, 1376, 1377, 1378, 1379, 1380 SQUARE
2340 SHEETS 1381, 1382, 1383, 1384, 1385, 1386 SQUARE
2350 SHEETS 1387, 1388, 1389, 1390, 1391, 1392 SQUARE
2360 SHEETS 1393, 1394, 1395, 1396, 1397, 1398 SQUARE
2370 SHEETS 1399, 1400, 1401, 1402, 1403, 1404 SQUARE
2380 SHEETS 1405, 1406, 1407, 1408, 1409, 1410 SQUARE
2390 SHEETS 1411, 1412, 1413, 1414, 1415, 1416 SQUARE
2400 SHEETS 1417, 1418, 1419, 1420, 1421, 1422 SQUARE
2410 SHEETS 1423, 1424, 1425, 1426, 1427, 1428 SQUARE
2420 SHEETS 1429, 1430, 1431, 1432, 1433, 1434 SQUARE
2430 SHEETS 1435, 1436, 1437, 1438, 1439, 1440 SQUARE
2440 SHEETS 1441, 1442, 1443, 1444, 1445, 1446 SQUARE
2450 SHEETS 1447, 1448, 1449, 1450, 1451, 1452 SQUARE
2460 SHEETS 1453, 1454, 1455, 1456, 1457, 1458 SQUARE
2470 SHEETS 1459, 1460, 1461, 1462, 1463, 1464 SQUARE
2480 SHEETS 1465, 1466, 1467, 1468, 1469, 1470 SQUARE
2490 SHEETS 1471, 1472, 1473, 1474, 1475, 1476 SQUARE
2500 SHEETS 1477, 1478, 1479, 1480, 1481, 1482 SQUARE
2510 SHEETS 1483, 1484, 1485, 1486, 1487, 1488 SQUARE
2520 SHEETS 1489, 1490, 1491, 1492, 1493, 1494 SQUARE
2530 SHEETS 1495, 1496, 1497, 1498, 1499, 1500 SQUARE
2540 SHEETS 1501, 1502, 1503, 1504, 1505, 1506 SQUARE
2550 SHEETS 1507, 1508, 1509, 1510, 1511, 1512 SQUARE
2560 SHEETS 1513, 1514, 1515, 1516, 1517, 1518 SQUARE
2570 SHEETS 1519, 1520, 1521, 1522, 1523, 1524 SQUARE
2580 SHEETS 1525, 1526, 1527, 1528, 1529, 1530 SQUARE
2590 SHEETS 1531, 1532, 1533, 1534, 1535, 1536 SQUARE
2600 SHEETS 1537, 1538, 1539, 1540, 1541, 1542 SQUARE
2610 SHEETS 1543, 1544, 1545, 1546, 1547, 1548 SQUARE
2620 SHEETS 1549, 1550, 1551, 1552, 1553, 1554 SQUARE
2630 SHEETS 1555, 1556, 1557, 1558, 1559, 1560 SQUARE
2640 SHEETS 1561, 1562, 1563, 1564, 1565, 1566 SQUARE
2650 SHEETS 1567, 1568, 1569, 1570, 1571, 1572 SQUARE
2660 SHEETS 1573, 1574, 1575, 1576, 1577, 1578 SQUARE
2670 SHEETS 1579, 1580, 1581, 1582, 1583, 1584 SQUARE
2680 SHEETS 1585, 1586, 1587, 1588, 1589, 1590 SQUARE
2690 SHEETS 1591, 1592, 1593, 1594, 1595, 1596 SQUARE
2700 SHEETS 1597, 1598, 1599, 1600, 1601, 1602 SQUARE
2710 SHEETS 1603, 1604, 1605, 1606, 1607, 1608 SQUARE
2720 SHEETS 1609, 1610, 1611, 1612, 1613, 1614 SQUARE
2730 SHEETS 1615, 1616, 1617, 1618, 1619, 1620 SQUARE
2740 SHEETS 1621, 1622, 1623, 1624, 1625, 1626 SQUARE
2750 SHEETS 1627, 1628, 1629, 1630, 1631, 1632 SQUARE
2760 SHEETS 1633, 1634, 1635, 1636, 1637, 1638 SQUARE
2770 SHEETS 1639, 1640, 1641, 1642, 1643, 1644 SQUARE
2780 SHEETS 1645, 1646, 1647, 1648, 1649, 1650 SQUARE
2790 SHEETS 1651, 1652, 1653, 1654, 1655, 1656 SQUARE
2800 SHEETS 1657, 1658, 1659, 1660, 1661, 1662 SQUARE
2810 SHEETS 1663, 1664, 1665, 1666, 1667, 1668 SQUARE
2820 SHEETS 1669, 1670, 1671, 1672, 1673, 1674 SQUARE
2830 SHEETS 1675, 1676, 1677, 1678, 1679, 1680 SQUARE
2840 SHEETS 1681, 1682, 1683, 1684, 1685, 1686 SQUARE
2850 SHEETS 1687, 1688, 1689, 1690, 1691, 1692 SQUARE
2860 SHEETS 1693, 1694, 1695, 1696, 1697, 1698 SQUARE
2870 SHEETS 1699, 1700, 1701, 1702, 1703, 1704 SQUARE
2880 SHEETS 1705, 1706, 1707, 1708, 1709, 1710 SQUARE
2890 SHEETS 1711, 1712, 1713, 1714, 1715, 1716 SQUARE
2900 SHEETS 1717, 1718, 1719, 1720, 1721, 1722 SQUARE
2910 SHEETS 1723, 1724, 1725, 1726, 1727, 1728 SQUARE
2920 SHEETS 1729, 1730, 1731, 1732, 1733, 1734 SQUARE
2930 SHEETS 1735, 1736, 1737, 1738, 1739, 1740 SQUARE
2940 SHEETS 1741, 1742, 1743, 1744, 1745, 1746 SQUARE
2950 SHEETS 1747, 1748, 1749, 1750, 1751, 1752 SQUARE
2960 SHEETS 1753, 1754, 1755, 1756, 1757, 1758 SQUARE
2970 SHEETS 1759, 1760, 1761, 1762, 1763, 1764 SQUARE
2980 SHEETS 1765, 1766, 1767, 1768, 1769, 1770 SQUARE
2990 SHEETS 1771, 1772, 1773, 1774, 1775, 1776 SQUARE
3000 SHEETS 1777, 1778, 1779, 1780, 1781, 1782 SQUARE
3010 SHEETS 1783, 1784, 1785, 1786, 1787, 1788 SQUARE
3020 SHEETS 1789, 1790, 1791, 1792, 1793

CONCRETE DESIGN:

PEDESTALS:



- for reactions, see p. 2

Reaction @ PEDESTAL:

$$A : \frac{1}{2}(0.045)(43.5) = 0.98^k (0.75) = 0.74^k$$

$$B : \frac{1}{2}(7.55)(43.5) = 16.4^k (0.75) = 12.3^k$$


sub 2, use 75% for us

MOMENT @ BASE OF PEDESTAL:

$$M = (12.3^k)(1.5') + (0.74^k)(4.5')$$

$$= 21.78^k$$

FACTORED MOMENT = $1.7 \times 1.3 \times 21.78 = 48.1^k$



Assume Moment is resisted by 3'-6" x 2'-9" area.

$$M_u = \phi [A_s f_y (d - \frac{a}{2})]$$

$$A_{s req'd} = \frac{M}{\phi f_y (d - \frac{a}{2})}$$

$$= \frac{48.1(12)}{0.9(66)(33-6-1)} = 0.41 in^2$$

FOR MORE INFORMATION CONTACT US AT 1-800-875-5351
 MEMBER OF THE NATIONAL ASSOCIATION OF
 ARCHITECTS AND ENGINEERS
 400 NORTH ZEEB ROAD
 ANN ARBOR, MI 48106-1500
 WWW.NAABUILDING.COM



CHECK SHEAR:

$$V_u = 1.7 * 1.3 (.74 + 12.3)$$

$$= 28.8^k$$

$$V_n = \frac{V_u}{\phi}$$

$$= 28.8 / .85$$

$$= 33.9^k$$

$$V_c = 2\sqrt{3000}$$

$$= 109 \text{ psi}$$

$$V_c = (109)[(42)(29.5) + 42(21 - 3.5)] / 1000$$

$$= 215^k > 33.9^k$$

- use minimum stirrups


16 INCH
18 INCH
20 INCH
24 INCH
30 INCH
36 INCH
42 INCH
48 INCH
54 INCH
60 INCH
66 INCH
72 INCH
78 INCH
84 INCH
90 INCH
96 INCH
102 INCH
108 INCH
114 INCH
120 INCH
126 INCH
132 INCH
138 INCH
144 INCH
150 INCH
156 INCH
162 INCH
168 INCH
174 INCH
180 INCH
186 INCH
192 INCH
198 INCH
204 INCH
210 INCH
216 INCH
222 INCH
228 INCH
234 INCH
240 INCH
246 INCH
252 INCH
258 INCH
264 INCH
270 INCH
276 INCH
282 INCH
288 INCH
294 INCH
300 INCH
306 INCH
312 INCH
318 INCH
324 INCH
330 INCH
336 INCH
342 INCH
348 INCH
354 INCH
360 INCH
366 INCH
372 INCH
378 INCH
384 INCH
390 INCH
396 INCH
402 INCH
408 INCH
414 INCH
420 INCH
426 INCH
432 INCH
438 INCH
444 INCH
450 INCH
456 INCH
462 INCH
468 INCH
474 INCH
480 INCH
486 INCH
492 INCH
498 INCH
504 INCH
510 INCH
516 INCH
522 INCH
528 INCH
534 INCH
540 INCH
546 INCH
552 INCH
558 INCH
564 INCH
570 INCH
576 INCH
582 INCH
588 INCH
594 INCH
600 INCH
606 INCH
612 INCH
618 INCH
624 INCH
630 INCH
636 INCH
642 INCH
648 INCH
654 INCH
660 INCH
666 INCH
672 INCH
678 INCH
684 INCH
690 INCH
696 INCH
702 INCH
708 INCH
714 INCH
720 INCH
726 INCH
732 INCH
738 INCH
744 INCH
750 INCH
756 INCH
762 INCH
768 INCH
774 INCH
780 INCH
786 INCH
792 INCH
798 INCH
804 INCH
810 INCH
816 INCH
822 INCH
828 INCH
834 INCH
840 INCH
846 INCH
852 INCH
858 INCH
864 INCH
870 INCH
876 INCH
882 INCH
888 INCH
894 INCH
900 INCH
906 INCH
912 INCH
918 INCH
924 INCH
930 INCH
936 INCH
942 INCH
948 INCH
954 INCH
960 INCH
966 INCH
972 INCH
978 INCH
984 INCH
990 INCH
996 INCH
1000 INCH

National Brand

FOUNDATION DESIGN:

P/S


P/S



-CHECK CASES 1 & 7

-CASE 1: GATE CLOSED, SWLj
IMPERVIOUS SIP

-CASE 7: GATE OPEN, TRUCK
ON P/S




13.980 500 SHEETS FULLER 5 SQUARE
 42.981 500 SHEETS FULLER 5 SQUARE
 42.982 500 SHEETS FULLER 5 SQUARE
 42.983 500 SHEETS FULLER 5 SQUARE
 42.984 500 SHEETS FULLER 5 SQUARE
 42.985 500 SHEETS FULLER 5 SQUARE
 42.986 500 SHEETS FULLER 5 SQUARE
 42.987 500 SHEETS FULLER 5 SQUARE
 42.988 500 SHEETS FULLER 5 SQUARE
 42.989 500 SHEETS FULLER 5 SQUARE
 42.990 500 SHEETS FULLER 5 SQUARE
 42.991 500 SHEETS FULLER 5 SQUARE
 42.992 500 SHEETS FULLER 5 SQUARE
 42.993 500 SHEETS FULLER 5 SQUARE
 42.994 500 SHEETS FULLER 5 SQUARE
 42.995 500 SHEETS FULLER 5 SQUARE
 42.996 500 SHEETS FULLER 5 SQUARE
 42.997 500 SHEETS FULLER 5 SQUARE
 42.998 500 SHEETS FULLER 5 SQUARE
 42.999 500 SHEETS FULLER 5 SQUARE
 43.000 500 SHEETS FULLER 5 SQUARE
 Made in U.S.A.



CASE 1 : GATE CLOSED, SWL, IMP. SP

11.76" 4000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 5000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 6000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 7000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 8000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 9000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 10000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 11000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 12000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 13000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 14000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 15000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 16000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 17000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 18000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 19000 BTU/LB. FILLER 5.5 SQUARE
 42.90" 20000 BTU/LB. FILLER 5.5 SQUARE
 MADE IN U.S.A.



wt of gate = 26k (p. 7)

wt of water = 10.37k (p. 11)

Moment of Column = GATE * L.A. + WATER * L.A. - PILE * L.A. + (WT. CONC. - EDDY) L.A.

= (26k)(1.75') + (10.37k)(3.875') - (12.4k)(5)(3.0') + (375 - 352)(2375')

= 100.3 k'

FACTORED M = 1.7 * 1.3 * 100.3 = 221.7 k'

M = 221.7/54 = 4.1 k'/ft

CASE 7: GATE OPEN, TRUCK ON P.

TRUCK = 86.4 @ 4.05'

PILE = 19.8

M = 19.8(5)(-2.375) = 231.56 k'

FACTORED M = $1.7 \times 1.3 \times 231.56$
 $= 511.71^k$

$M_u = 511.7 / 11.0 = 46.5^k/ft$

$A_{stemp} = 0.0018(A_g)$
 $= .0018(12)(26)$
 $= 0.562 \text{ in}^2/ft$

$d = 30" - 3" - \frac{1}{2}" - \frac{1}{2}" = 26"$

$\rho_{min} = \frac{200}{46000} = 0.0042$

$a = \frac{12 \times 60}{85 \times 3 \times 12}$
 $= 2.35$

$A_{smin} = 0.0042(12)(26)$
 $= 1.31 \text{ in}^2/ft$

$M_u = (1.31)(46)(26 - 2.35) = 117.1^k > 46.5^k$


Alt min: $M_u / (\phi f'_c b d^2) = \frac{46.5 \times 12}{0.9(3.0)(12)(26)^2} = 0.0255$ $\rho = 0.0255 (\frac{3}{48})$
 $= 0.0016$

Alt min: $1.33 \times 0.0016 = 0.0021$

LONGITUDINAL DIRECTION:

$A_{ST} = 0.0021(12)(26)$
 $= 0.66$ - use #8 @ 12"
 $A_{ST, PROV} = 0.79$

TRUCK LOADS:



Reinforcing perpendicular to traffic direction
 (AASHTO 3.24.3)

Moment/foot = $\frac{S+2}{32} \times P_{20}$

$S = 11'$
 $P_{20} = 16^k$

$I = 30\%$

L.L. Moment = $\frac{13}{32} \times 16 = 6.5^k$

$M(L+I) = 1.3(6.5) = 8.45^k$

$M_{DL} = .8(\text{bw}^2)$
 $= (6)(.375)(11)^2 \cdot 8 = 4.5^k$

$w = (2.5')(1.15 \text{ ccf}) = 0.375^k/ft$

13 260
 12 300
 12 362
 12 389
 12 399
 12 400
 12 401
 12 402
 12 403
 12 404
 12 405
 12 406
 12 407
 12 408
 12 409
 12 410
 12 411
 12 412
 12 413
 12 414
 12 415
 12 416
 12 417
 12 418
 12 419
 12 420
 12 421
 12 422
 12 423
 12 424
 12 425
 12 426
 12 427
 12 428
 12 429
 12 430
 12 431
 12 432
 12 433
 12 434
 12 435
 12 436
 12 437
 12 438
 12 439
 12 440
 12 441
 12 442
 12 443
 12 444
 12 445
 12 446
 12 447
 12 448
 12 449
 12 450
 12 451
 12 452
 12 453
 12 454
 12 455
 12 456
 12 457
 12 458
 12 459
 12 460
 12 461
 12 462
 12 463
 12 464
 12 465
 12 466
 12 467
 12 468
 12 469
 12 470
 12 471
 12 472
 12 473
 12 474
 12 475
 12 476
 12 477
 12 478
 12 479
 12 480
 12 481
 12 482
 12 483
 12 484
 12 485
 12 486
 12 487
 12 488
 12 489
 12 490
 12 491
 12 492
 12 493
 12 494
 12 495
 12 496
 12 497
 12 498
 12 499
 12 500
 12 501
 12 502
 12 503
 12 504
 12 505
 12 506
 12 507
 12 508
 12 509
 12 510
 12 511
 12 512
 12 513
 12 514
 12 515
 12 516
 12 517
 12 518
 12 519
 12 520
 12 521
 12 522
 12 523
 12 524
 12 525
 12 526
 12 527
 12 528
 12 529
 12 530
 12 531
 12 532
 12 533
 12 534
 12 535
 12 536
 12 537
 12 538
 12 539
 12 540
 12 541
 12 542
 12 543
 12 544
 12 545
 12 546
 12 547
 12 548
 12 549
 12 550
 12 551
 12 552
 12 553
 12 554
 12 555
 12 556
 12 557
 12 558
 12 559
 12 560
 12 561
 12 562
 12 563
 12 564
 12 565
 12 566
 12 567
 12 568
 12 569
 12 570
 12 571
 12 572
 12 573
 12 574
 12 575
 12 576
 12 577
 12 578
 12 579
 12 580
 12 581
 12 582
 12 583
 12 584
 12 585
 12 586
 12 587
 12 588
 12 589
 12 590
 12 591
 12 592
 12 593
 12 594
 12 595
 12 596
 12 597
 12 598
 12 599
 12 600
 12 601
 12 602
 12 603
 12 604
 12 605
 12 606
 12 607
 12 608
 12 609
 12 610
 12 611
 12 612
 12 613
 12 614
 12 615
 12 616
 12 617
 12 618
 12 619
 12 620
 12 621
 12 622
 12 623
 12 624
 12 625
 12 626
 12 627
 12 628
 12 629
 12 630
 12 631
 12 632
 12 633
 12 634
 12 635
 12 636
 12 637
 12 638
 12 639
 12 640
 12 641
 12 642
 12 643
 12 644
 12 645
 12 646
 12 647
 12 648
 12 649
 12 650
 12 651
 12 652
 12 653
 12 654
 12 655
 12 656
 12 657
 12 658
 12 659
 12 660
 12 661
 12 662
 12 663
 12 664
 12 665
 12 666
 12 667
 12 668
 12 669
 12 670
 12 671
 12 672
 12 673
 12 674
 12 675
 12 676
 12 677
 12 678
 12 679
 12 680
 12 681
 12 682
 12 683
 12 684
 12 685
 12 686
 12 687
 12 688
 12 689
 12 690
 12 691
 12 692
 12 693
 12 694
 12 695
 12 696
 12 697
 12 698
 12 699
 12 700
 12 701
 12 702
 12 703
 12 704
 12 705
 12 706
 12 707
 12 708
 12 709
 12 710
 12 711
 12 712
 12 713
 12 714
 12 715
 12 716
 12 717
 12 718
 12 719
 12 720
 12 721
 12 722
 12 723
 12 724
 12 725
 12 726
 12 727
 12 728
 12 729
 12 730
 12 731
 12 732
 12 733
 12 734
 12 735
 12 736
 12 737
 12 738
 12 739
 12 740
 12 741
 12 742
 12 743
 12 744
 12 745
 12 746
 12 747
 12 748
 12 749
 12 750
 12 751
 12 752
 12 753
 12 754
 12 755
 12 756
 12 757
 12 758
 12 759
 12 760
 12 761
 12 762
 12 763
 12 764
 12 765
 12 766
 12 767
 12 768
 12 769
 12 770
 12 771
 12 772
 12 773
 12 774
 12 775
 12 776
 12 777
 12 778
 12 779
 12 780
 12 781
 12 782
 12 783
 12 784
 12 785
 12 786
 12 787
 12 788
 12 789
 12 790
 12 791
 12 792
 12 793
 12 794
 12 795
 12 796
 12 797
 12 798
 12 799
 12 800
 12 801
 12 802
 12 803
 12 804
 12 805
 12 806
 12 807
 12 808
 12 809
 12 810
 12 811
 12 812
 12 813
 12 814
 12 815
 12 816
 12 817
 12 818
 12 819
 12 820
 12 821
 12 822
 12 823
 12 824
 12 825
 12 826
 12 827
 12 828
 12 829
 12 830
 12 831
 12 832
 12 833
 12 834
 12 835
 12 836
 12 837
 12 838
 12 839
 12 840
 12 841
 12 842
 12 843
 12 844
 12 845
 12 846
 12 847
 12 848
 12 849
 12 850
 12 851
 12 852
 12 853
 12 854
 12 855
 12 856
 12 857
 12 858
 12 859
 12 860
 12 861
 12 862
 12 863
 12 864
 12 865
 12 866
 12 867
 12 868
 12 869
 12 870
 12 871
 12 872
 12 873
 12 874
 12 875
 12 876
 12 877
 12 878
 12 879
 12 880
 12 881
 12 882
 12 883
 12 884
 12 885
 12 886
 12 887
 12 888
 12 889
 12 890
 12 891
 12 892
 12 893
 12 894
 12 895
 12 896
 12 897
 12 898
 12 899
 12 900
 12 901
 12 902
 12 903
 12 904
 12 905
 12 906
 12 907
 12 908
 12 909
 12 910
 12 911
 12 912
 12 913
 12 914
 12 915
 12 916
 12 917
 12 918
 12 919
 12 920
 12 921
 12 922
 12 923
 12 924
 12 925
 12 926
 12 927
 12 928
 12 929
 12 930
 12 931
 12 932
 12 933
 12 934
 12 935
 12 936
 12 937
 12 938
 12 939
 12 940
 12 941
 12 942
 12 943
 12 944
 12 945
 12 946
 12 947
 12 948
 12 949
 12 950
 12 951
 12 952
 12 953
 12 954
 12 955
 12 956
 12 957
 12 958
 12 959
 12 960
 12 961
 12 962
 12 963
 12 964
 12 965
 12 966
 12 967
 12 968
 12 969
 12 970
 12 971
 12 972
 12 973
 12 974
 12 975
 12 976
 12 977
 12 978
 12 979
 12 980
 12 981
 12 982
 12 983
 12 984
 12 985
 12 986
 12 987
 12 988
 12 989
 12 990
 12 991
 12 992
 12 993
 12 994
 12 995
 12 996
 12 997
 12 998
 12 999
 13 000
 13 001
 13 002
 13 003
 13 004
 13 005
 13 006
 13 007
 13 008
 13 009
 13 010
 13 011
 13 012
 13 013
 13 014
 13 015
 13 016
 13 017
 13 018
 13 019
 13 020
 13 021
 13 022
 13 023
 13 024
 13 025
 13 026
 13 027
 13 028
 13 029
 13 030
 13 031
 13 032
 13 033
 13 034
 13 035
 13 036
 13 037
 13 038
 13 039
 13 040
 13 041
 13 042
 13 043
 13 044
 13 045
 13 046
 13 047
 13 048
 13 049
 13 050
 13 051
 13 052
 13 053
 13 054
 13 055
 13 056
 13 057
 13 058
 13 059
 13 060
 13 061
 13 062
 13 063
 13 064
 13 065
 13 066
 13 067
 13 068
 13 069
 13 070
 13 071
 13 072
 13 073
 13 074
 13 075
 13 076
 13 077
 13 078
 13 079
 13 080
 13 081
 13 082
 13 083
 13 084
 13 085
 13 086
 13 087
 13 088
 13 089
 13 090
 13 091
 13 092
 13 093
 13 094
 13 095
 13 096
 13 097
 13 098
 13 099
 13 100
 13 101
 13 102
 13 103
 13 104
 13 105
 13 106
 13 107
 13 108
 13 109
 13 110
 13 111
 13 112
 13 113
 13 114
 13 115
 13 116
 13 117
 13 118
 13 119
 13 120
 13 121
 13 122
 13 123
 13 124
 13 125
 13 126
 13 127
 13 128
 13 129
 13 130
 13 131
 13 132
 13 133
 13 134
 13 135
 13 136
 13 137
 13 138
 13 139
 13 140
 13 141
 13 142
 13 143
 13 144
 13 145
 13 146
 13 147
 13 148
 13 149
 13 150
 13 151
 13 152
 13 153
 13 154
 13 155
 13 156
 13 157
 13 158
 13 159
 13 160
 13 161
 13 162
 13 163
 13 164
 13 165
 13 166
 13 167
 13 168
 13 169
 13 170
 13 171
 13 172
 13 173
 13 174
 13 175
 13 176
 13 177
 13 178
 13 179
 13 180
 13 181
 13 182
 13 183
 13 184
 13 185
 13 186
 13 187
 13 188
 13 189
 13 190
 13 191
 13 192
 13 193
 13 194
 13 195
 13 196
 13 197
 13 198
 13 199
 13 200
 13 201
 13 202
 13 203
 13 204
 13 205
 13 206
 13 207
 13 208
 13 209
 13 210
 13 211
 13 212
 13 213
 13 214
 13 215
 13 216
 13 217
 13 218
 13 219
 13 220
 13 221
 13 222
 13 223
 13 224
 13 225
 13 226
 13 227
 13 228
 13 229
 13 230
 13 231
 13 232
 13 233
 13 234
 13 235
 13 236
 13 237
 13 238
 13 239
 13 240
 13 241
 13 242
 13 243
 13 244
 13 245
 13 246
 13 247
 13 248
 13 249
 13 250
 13 251
 13 252
 13 253
 13 254
 13 255
 13 256
 13 257
 13 258
 13 259
 13 260
 13 261
 13 262
 13 263
 13 264
 13 265
 13 266
 13 267
 13 268
 13 269
 13 270
 13 271
 13 272
 13 273
 13 274
 13 275
 13 276
 13 277
 13 278
 13 279
 13 280
 13 281
 13 282
 13 283
 13 284
 13 285
 13 286
 13 287
 13 288
 13 289
 13 290
 13 291
 13 292
 13 293
 13 294
 13 295
 13 296
 13 297
 13 298
 13 299
 13 300
 13 301
 13 302
 13 303
 13 304
 13 305
 13 306
 13 307
 13 308
 13 309
 13 310
 13 311
 13 312
 13 313
 13 314
 13 315
 13 316
 13 317
 13 318
 13 319
 13 320
 13 321
 13 322
 13 323
 13 324
 13 325
 13 326
 13 327
 13 328
 13 329
 13 330
 13 331
 13 332
 13 333
 13 334
 13 335
 13 336
 13 337
 13 338
 13 339
 13 340
 13 341
 13 342
 13 343
 13 344
 13 345
 13 346
 13 347
 13 348
 13 349

$$M_{TOT} = 1.3[4.5] + (1.7)(8.45) \\ = 24.5 \quad (\text{AASTHO})$$

$$M_{TOT} = 1.3(1.7)(4.5 + 8.75) \\ = 29.28 \quad (\text{COE}) \leftarrow$$

$$d = 30' - 3' - \frac{1}{2}'' - \frac{1}{2}'' = 26'$$

$$\frac{M_u}{\phi f_c' b d^2} = \frac{29.28 * 12}{.9(3)(12)(26)^2} = 0.016$$

$$\rho = 0.016 \left(\frac{3}{4}\right) = 0.001$$

$$\rho_{min} = \frac{200}{48000} = 0.0042$$

$$\text{alt } \rho_{min} = 1.33 * 0.001 = 0.0013 \quad \leftarrow$$

$$A_{s \text{ req'd}} = 0.0013(12)(26) = 0.41 \text{ in}^2/\text{ft}$$

$$\text{use } \#7 @ 12'' \quad A_{s \text{ prov}} = 0.60 \text{ in}^2/\text{ft}$$

14 707 500 SHEETS, BUILT 5.5.00H
 42 811 50 SHEETS, EAST 5.5.00H
 42 865 50 SHEETS, WEST 5.5.00H
 42 872 50 SHEETS, EAST 5.5.00H
 42 873 50 SHEETS, WEST 5.5.00H
 42 874 50 SHEETS, WEST 5.5.00H
 42 875 50 SHEETS, WEST 5.5.00H
 42 876 50 SHEETS, WEST 5.5.00H
 42 877 50 SHEETS, WEST 5.5.00H
 42 878 50 SHEETS, WEST 5.5.00H
 42 879 50 SHEETS, WEST 5.5.00H
 42 880 50 SHEETS, WEST 5.5.00H
 42 881 50 SHEETS, WEST 5.5.00H
 42 882 50 SHEETS, WEST 5.5.00H
 42 883 50 SHEETS, WEST 5.5.00H
 42 884 50 SHEETS, WEST 5.5.00H
 42 885 50 SHEETS, WEST 5.5.00H
 42 886 50 SHEETS, WEST 5.5.00H
 42 887 50 SHEETS, WEST 5.5.00H
 42 888 50 SHEETS, WEST 5.5.00H
 42 889 50 SHEETS, WEST 5.5.00H
 42 890 50 SHEETS, WEST 5.5.00H
 42 891 50 SHEETS, WEST 5.5.00H
 42 892 50 SHEETS, WEST 5.5.00H
 42 893 50 SHEETS, WEST 5.5.00H
 42 894 50 SHEETS, WEST 5.5.00H
 42 895 50 SHEETS, WEST 5.5.00H
 42 896 50 SHEETS, WEST 5.5.00H
 42 897 50 SHEETS, WEST 5.5.00H
 42 898 50 SHEETS, WEST 5.5.00H
 42 899 50 SHEETS, WEST 5.5.00H
 42 900 50 SHEETS, WEST 5.5.00H
 42 901 50 SHEETS, WEST 5.5.00H
 42 902 50 SHEETS, WEST 5.5.00H
 42 903 50 SHEETS, WEST 5.5.00H
 42 904 50 SHEETS, WEST 5.5.00H
 42 905 50 SHEETS, WEST 5.5.00H
 42 906 50 SHEETS, WEST 5.5.00H
 42 907 50 SHEETS, WEST 5.5.00H
 42 908 50 SHEETS, WEST 5.5.00H
 42 909 50 SHEETS, WEST 5.5.00H
 42 910 50 SHEETS, WEST 5.5.00H
 42 911 50 SHEETS, WEST 5.5.00H
 42 912 50 SHEETS, WEST 5.5.00H
 42 913 50 SHEETS, WEST 5.5.00H
 42 914 50 SHEETS, WEST 5.5.00H
 42 915 50 SHEETS, WEST 5.5.00H
 42 916 50 SHEETS, WEST 5.5.00H
 42 917 50 SHEETS, WEST 5.5.00H
 42 918 50 SHEETS, WEST 5.5.00H
 42 919 50 SHEETS, WEST 5.5.00H
 42 920 50 SHEETS, WEST 5.5.00H
 42 921 50 SHEETS, WEST 5.5.00H
 42 922 50 SHEETS, WEST 5.5.00H
 42 923 50 SHEETS, WEST 5.5.00H
 42 924 50 SHEETS, WEST 5.5.00H
 42 925 50 SHEETS, WEST 5.5.00H
 42 926 50 SHEETS, WEST 5.5.00H
 42 927 50 SHEETS, WEST 5.5.00H
 42 928 50 SHEETS, WEST 5.5.00H
 42 929 50 SHEETS, WEST 5.5.00H
 42 930 50 SHEETS, WEST 5.5.00H
 42 931 50 SHEETS, WEST 5.5.00H
 42 932 50 SHEETS, WEST 5.5.00H
 42 933 50 SHEETS, WEST 5.5.00H
 42 934 50 SHEETS, WEST 5.5.00H
 42 935 50 SHEETS, WEST 5.5.00H
 42 936 50 SHEETS, WEST 5.5.00H
 42 937 50 SHEETS, WEST 5.5.00H
 42 938 50 SHEETS, WEST 5.5.00H
 42 939 50 SHEETS, WEST 5.5.00H
 42 940 50 SHEETS, WEST 5.5.00H
 42 941 50 SHEETS, WEST 5.5.00H
 42 942 50 SHEETS, WEST 5.5.00H
 42 943 50 SHEETS, WEST 5.5.00H
 42 944 50 SHEETS, WEST 5.5.00H
 42 945 50 SHEETS, WEST 5.5.00H
 42 946 50 SHEETS, WEST 5.5.00H
 42 947 50 SHEETS, WEST 5.5.00H
 42 948 50 SHEETS, WEST 5.5.00H
 42 949 50 SHEETS, WEST 5.5.00H
 42 950 50 SHEETS, WEST 5.5.00H
 42 951 50 SHEETS, WEST 5.5.00H
 42 952 50 SHEETS, WEST 5.5.00H
 42 953 50 SHEETS, WEST 5.5.00H
 42 954 50 SHEETS, WEST 5.5.00H
 42 955 50 SHEETS, WEST 5.5.00H
 42 956 50 SHEETS, WEST 5.5.00H
 42 957 50 SHEETS, WEST 5.5.00H
 42 958 50 SHEETS, WEST 5.5.00H
 42 959 50 SHEETS, WEST 5.5.00H
 42 960 50 SHEETS, WEST 5.5.00H
 42 961 50 SHEETS, WEST 5.5.00H
 42 962 50 SHEETS, WEST 5.5.00H
 42 963 50 SHEETS, WEST 5.5.00H
 42 964 50 SHEETS, WEST 5.5.00H
 42 965 50 SHEETS, WEST 5.5.00H
 42 966 50 SHEETS, WEST 5.5.00H
 42 967 50 SHEETS, WEST 5.5.00H
 42 968 50 SHEETS, WEST 5.5.00H
 42 969 50 SHEETS, WEST 5.5.00H
 42 970 50 SHEETS, WEST 5.5.00H
 42 971 50 SHEETS, WEST 5.5.00H
 42 972 50 SHEETS, WEST 5.5.00H
 42 973 50 SHEETS, WEST 5.5.00H
 42 974 50 SHEETS, WEST 5.5.00H
 42 975 50 SHEETS, WEST 5.5.00H
 42 976 50 SHEETS, WEST 5.5.00H
 42 977 50 SHEETS, WEST 5.5.00H
 42 978 50 SHEETS, WEST 5.5.00H
 42 979 50 SHEETS, WEST 5.5.00H
 42 980 50 SHEETS, WEST 5.5.00H
 42 981 50 SHEETS, WEST 5.5.00H
 42 982 50 SHEETS, WEST 5.5.00H
 42 983 50 SHEETS, WEST 5.5.00H
 42 984 50 SHEETS, WEST 5.5.00H
 42 985 50 SHEETS, WEST 5.5.00H
 42 986 50 SHEETS, WEST 5.5.00H
 42 987 50 SHEETS, WEST 5.5.00H
 42 988 50 SHEETS, WEST 5.5.00H
 42 989 50 SHEETS, WEST 5.5.00H
 42 990 50 SHEETS, WEST 5.5.00H
 42 991 50 SHEETS, WEST 5.5.00H
 42 992 50 SHEETS, WEST 5.5.00H
 42 993 50 SHEETS, WEST 5.5.00H
 42 994 50 SHEETS, WEST 5.5.00H
 42 995 50 SHEETS, WEST 5.5.00H
 42 996 50 SHEETS, WEST 5.5.00H
 42 997 50 SHEETS, WEST 5.5.00H
 42 998 50 SHEETS, WEST 5.5.00H
 42 999 50 SHEETS, WEST 5.5.00H
 43 000 50 SHEETS, WEST 5.5.00H

14 707 500 SHEETS, BUILT 5.5.00H

National Brand


$$M = \left(\frac{1}{8}\right)(3.0)(14)^2$$

$$= 73.5 \text{ k}$$

Factored M = $1.7 \times 1.3 \times 73.5$

$$= 162.4 \text{ k}$$

$$= 198.8 \text{ k}$$

Top of Slab = $4.5 - \frac{17}{8} = 4.34$

Bottom of Slab = 2.8

Depth = $2 - 4 \frac{1}{8}''$

d = $28.125 - 4 = 24.125''$

$$p_{min} = \frac{200}{48000} = 0.0042$$

$$A_{smin} = 0.0042(72'')(24.125'')$$

$$= 7.30 \text{ in}^2$$

# 6 - 17	$A_s = 17(.44) = 7.48$
# 7 - 13	$A_s = 13(.52) = 6.76$
# 8 - 10	$A_s = 10(.79) = 7.9$ ←

use 10 @ TOP & BOTTOM

Shear:

$$V = \frac{1}{2} wL$$

$$= \frac{1}{2} (3)(14)$$

$$= 21 \text{ k}$$

$$V_u = 1.7 + 1.3 \times 21$$

$$= 46.4 \text{ k}$$

$$V_n = \frac{46.4}{1.25} = 37.12 \text{ k}$$

$$V_c = 2\sqrt{3000} (72)(24.125)/1000 = 190.3 \text{ k}$$

$$V_c > 2 V_n$$

$$190.3 > 2(37.12)$$

$$> 74.24$$

✓ - NO STIRRUPS
NEEDED

13/82 5000 LBS PER 5 SQUARE
12/81 4000 LBS PER 5 SQUARE
11/80 3000 LBS PER 5 SQUARE
10/79 2000 LBS PER 5 SQUARE
9/78 1000 LBS PER 5 SQUARE
8/77 500 LBS PER 5 SQUARE
7/76 250 LBS PER 5 SQUARE
6/75 125 LBS PER 5 SQUARE
5/74 62.5 LBS PER 5 SQUARE
4/73 31.25 LBS PER 5 SQUARE
3/72 15.625 LBS PER 5 SQUARE
2/71 7.8125 LBS PER 5 SQUARE
1/70 3.90625 LBS PER 5 SQUARE
Made in U.S.A.



JN 3003

COUSINS PUMP STATION


AAH

8-12-97

(2 Pumps)


87' x 84' 11 1/2"
85'

DISCHARGE SIDE



SUCTION SIDE

13 787 200 SHEETS FULL SIZE SQUARE
 42 382 100 SHEETS 1/2" EASE SQUARE
 42 383 200 SHEETS 1/2" EASE SQUARE
 42 384 100 SHEETS 1/4" EASE SQUARE
 42 385 200 SHEETS 1/4" EASE SQUARE
 42 386 200 RECYCLED WHITE SQUARE
 MADE IN U.S.A.



SLAB: From B1 TO B3:

$$h = 24''$$

$$L = 18'-8\frac{1}{2}'' = 18.71'$$

$$DL = (2)(.150 \text{ rcf}) = 0.3 \text{ ksf}$$

MACHINERY LOADS:

DIESEL ENGINE

DIESEL TANK

EMERGENCY GENERATOR

VACUUM PUMP

BKI

$$LL = 100 \text{ psf} = 0.1 \text{ ksf}$$

* FLOOR MUST BE DESIGNED TO SUPPORT
HEAVIEST PIECE OF MACHINERY PLACED
ANYWHERE: use 300 #/SF - VERIFY W/BKI

$$\text{FACTORED LOAD} = 1.7 \times 1.3 \text{ (HYDRAULIC FACTOR)} (DL + MACH + LL)$$

$$= 1.7 \times 1.3 (0.3 + 0.3 + 0.1)$$

$$= 1.55 \text{ ksf}$$

$$M_+ = \frac{1}{4} wL^2 = \frac{1}{4} (1.55) (18.71)^2$$

$$= 38.76 \text{ k' / FOOT WIDTH}$$

(FROM: REINFORCED CONCRETE
FUNDAMENTALS BY
FERGUSON/BREEN/IRSA
P 350)

$$M_- = -\frac{1}{4} wL^2 \text{ (@ center support)}$$

$$= -\frac{1}{4} (1.55) (18.71)^2$$

$$= -60.29 \text{ k'}$$

$$f_c' = 3000 \text{ psi}$$

$$f_y = 48000 \text{ psi (Gr 60 - hydraulic structures)}$$

$$d = 24'' - 4'' \text{ clr} - \frac{1}{2}'' = 19.5''$$

13-782 100 SHEETS PAPER 5 SQUARE
42-281 100 SHEETS PAPER 5 SQUARE
42-282 100 SHEETS PAPER 5 SQUARE
42-283 100 SHEETS PAPER 5 SQUARE
42-284 100 SHEETS PAPER 5 SQUARE
42-285 100 SHEETS PAPER 5 SQUARE
42-286 100 SHEETS PAPER 5 SQUARE
42-287 100 SHEETS PAPER 5 SQUARE
42-288 100 SHEETS PAPER 5 SQUARE
42-289 100 SHEETS PAPER 5 SQUARE
42-290 100 SHEETS PAPER 5 SQUARE
42-291 100 SHEETS PAPER 5 SQUARE
42-292 100 SHEETS PAPER 5 SQUARE
42-293 100 SHEETS PAPER 5 SQUARE
42-294 100 SHEETS PAPER 5 SQUARE
42-295 100 SHEETS PAPER 5 SQUARE
42-296 100 SHEETS PAPER 5 SQUARE
42-297 100 SHEETS PAPER 5 SQUARE
42-298 100 SHEETS PAPER 5 SQUARE
42-299 100 SHEETS PAPER 5 SQUARE
42-300 100 SHEETS PAPER 5 SQUARE
Made in U.S.A.



Positive Moment:

$$\frac{M_u}{\phi_c b d^2} = \frac{38.74 \times 12}{.9 \times 3 \times 12 \times 19.5^2}$$

$$= 0.038$$

$$p = 0.038 \frac{f_c}{f_y}$$

$$= 0.038 \left(\frac{3}{4}\right)$$

$$= 0.0024$$

$$p_{min} = \frac{200}{f_y} = \frac{200}{48000} = 0.0042$$

$$\text{alt } p_{min} = 1.33p = 1.33(0.0024) = 0.0032 \leftarrow$$

$$A_s = 0.0032(12)(19.5)$$

$$= 0.75 \text{ in}^2/\text{ft}$$

$$\#6 @ 6" \rightarrow A_s = 2(.44) = .88 > .75 \text{ OK}$$

Negative Moment:

$$\frac{M_u}{\phi_c b d^2} = \frac{60.29(12)}{.9(3)(12)(20.5)^2}$$

$$= 0.053$$

$$d = 20.5"$$

$$p = 0.053 \frac{f_c}{f_y} = 0.053 \left(\frac{3}{4}\right)$$

$$= 0.0033$$

$$p_{min} = 0.0042 \leftarrow$$

$$\text{alt } p_{min} = 1.33(0.0033) = 0.0044$$

$$A_{sT} = 0.0044(12)(20.5)$$

$$= 1.03 \text{ in}^2/\text{ft}$$

$$\#7 @ 6" = 2(.60) = 1.20 \text{ in}^2/\text{ft over under beam}$$


(82)

13-782 500 SHEETS, FILLER 3 SQUARE
 42-381 50 SHEETS, FILLER 3 SQUARE
 42-382 100 SHEETS, FILLER 3 SQUARE
 42-383 200 SHEETS, FILLER 3 SQUARE
 42-384 100 SHEETS, FILLER 3 SQUARE
 42-385 100 RECYCLED WHITE 3 SQUARE
 42-386 200 RECYCLED WHITE 3 SQUARE
 Manufactured in U.S.A.



BEAM B1:

DEAD LOAD:



$$\text{BEAM: } (12.67)(3.5)(.150) = 4.75 \text{ k/ft}$$

$$\text{SLAB: } (2')\left(\frac{16.708}{2}\right)(.15) = 2.51 \text{ k/ft}$$

$$\text{SUPERIMPOSED DL: } (300 \text{ psf})\left(\frac{16.708}{2}\right) = 2.51 \text{ k/ft}$$

$$\text{LL} = 100 \text{ psf} = 0.1\left(\frac{16.708}{2}\right) = 0.84 \text{ k/ft}$$

$$\text{span length: } 43.5' - 4' = 39.5'$$

$$d = 152'' - 3'' \text{ dia} - 3'' = 146''$$

$$\text{FACTORED LOAD} = 1.7 \times 1.3 \times (4.75 + 2.51 + 2.51 + .84) \\ = 23.45$$

$$M_u = \frac{1}{8} w L^2 \\ = \frac{1}{8} (23.45) (39.5)^2 \\ = 4573 \text{ k}$$

$$\frac{M_u}{\phi L' b d^2} = \frac{4573 \times 12}{.9(3)(30)(146)^2} \\ = 0.032$$

$$\rho = 0.032 \left(\frac{3}{48}\right) \\ = 0.002$$

$$\rho_{\min} = 200/48000 = 0.0042$$

$$\text{alt } \rho_{\min} = 1.33(.002) = 0.0027 \leftarrow$$

$$A_s = 0.0027(30)(146) \\ = 11.83 \text{ in}^2$$

- 8-#11 (to match existing)


$$A_s = 8(1.56) = 12.48 > 11.83 \text{ ok}$$

400 SHEETS FULLER 8 SQUARE
300 SHEETS FULLER 8 SQUARE
100 SHEETS FULLER 8 SQUARE
100 SHEETS FULLER 8 SQUARE
200 SHEETS FULLER 8 SQUARE
200 SHEETS FULLER 8 SQUARE
200 RECYCLED WHITE 8 SQUARE
200 RECYCLED WHITE 8 SQUARE

12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82, 84, 86, 88, 90, 92, 94, 96, 98, 100



BEAM B2:



d = 83-3" = 3', 77"

span length = 39.5'

BEAM:	$(6.917)(2')(1.15) =$	2.08
SLAB:	$(2')(16.702')(1.15) =$	5.01
SUPERIMPOSED DL:	$(.3)(16.702) =$	5.01
LL:	$(.11)(16.702) =$	1.67
		<hr/>
		13.77

FACTORED LOAD = $1.7 * 1.3 * 13.77$
 $= 30.43 \text{ k/ft}$

$M_u = \frac{1}{8} w L^2$
 $= \frac{1}{8} (30.43) (39.5)^2$
 $= 5935 \text{ k}$

$M_u / \phi f_c b d^2 = \frac{5935(12)}{.9(3)(24)(77)^2}$
 $= .0185$

$\rho = 0.185 \left(\frac{3}{48}\right)$
 $= 0.012$

$\rho_{min} = 200 / 48000 = 0.0042$

$A_s = 0.012(77)(24)$
 $= 22.2 \text{ in}^2$ N.G.

TRY 2'-11" x 2'-6" beam:

d = 77+12 = 89"

DL BEAM: $(7.917)(2.5)(1.15) = 2.97 \text{ k/ft}$

TOTAL = $2.97 + 5.01 + 5.01 + 1.67 = 14.66 \text{ k/ft}$

FACTORED LOAD = $1.7 + 1.3 + 14.66 = 32.40 \text{ k/ft}$

$M = \frac{1}{8} w L^2 = \frac{1}{8} (32.4) (39.5)^2$
 $= 6319 \text{ k}$

13782 50 SHEETS FILER 5 SQUARE
 42-241 50 SHEETS EYE LAMP 5 SQUARE
 42-242 100 SHEETS EYE LAMP 5 SQUARE
 42-243 100 SHEETS EYE LAMP 5 SQUARE
 42-244 100 RECYCLED WHITE 5 SQUARE
 42-245 200 RECYCLED WHITE 5 SQUARE
 Made in U.S.A.



try original beam as T section:

$$b_f = \text{Span}/4 = 39.5/4 = 9.875 \times 12 = 118.5'' \leftarrow$$
$$8b_f = 8 \times 24 = 192''$$

beam spacing = 18'

$$\rightarrow \text{use } z = d \cdot \frac{1}{2} = 0.9d$$

$$z = 0.9(77) = 69.3''$$

$$d \cdot \frac{1}{2} = 69.3''$$

$$77'' \cdot \frac{1}{2} = 69.3''$$

$$\frac{1}{2} = 7.7''$$

$$a = 15.4'' < 24 \quad \therefore b = 118.5''$$

$$M_u / \phi_s b d^2 = 5985 \times 12 / 1.9(3)(118.5)(77)^2$$
$$= 0.038$$

$$\rho = 0.038 \left(\frac{3}{48} \right)$$
$$= 0.0024$$

$$\rho_{\min} = 0.0042$$

$$\rho_{\text{alt min}} = 1.33(0.0024) = 0.0032 \leftarrow$$

$$A_s = 0.0032 b_w d$$
$$= 0.0032(24)(77)$$
$$= 5.92 \text{ in}^2$$

13-782 500 SHEETS, FILLER, 3 SQUARE
42-981 50 SHEETS, FILLER, 3 SQUARE
42-981 100 SHEETS, FILLER, 3 SQUARE
42-981 200 SHEETS, FILLER, 3 SQUARE
42-982 100 SHEETS, FILLER, 3 SQUARE
42-982 200 SHEETS, FILLER, 3 SQUARE
42-982 100 RECYCLED WHITE, 3 SQUARE
42-982 200 RECYCLED WHITE, 3 SQUARE
Made in U.S.A.




BEAM BS:

$$6'-11" \times 2'$$

$$10-\#10 \text{ bars}$$

$$d = 83-6" = 77"$$

$$W_{\text{beam}} = (6.917)(2)(.15) = 2.1 \text{ k/ft}$$



$$R = 39.5'$$

$$W_{\text{slab}1} = (2') \left(\frac{16.708}{2} \right) (.15) = 2.51 \text{ k/ft}$$

$$\begin{aligned} W_{\text{slab}2} &= W_{\text{slab}1} + \left(\frac{15.917}{2} \right) (2') (.15) \\ &= 2.51 + 2.39 \\ &= 4.9 \text{ k/ft} \end{aligned}$$

$$\text{superimposed } DL_1 = (.3) \left(\frac{16.708}{2} \right) = 2.51$$

$$\begin{aligned} DL_2 &= \text{sup. } DL_1 + (.3) \left(\frac{15.917}{2} \right) \\ &= 2.51 + 2.39 \\ &= 4.9 \end{aligned}$$

$$LL_1 = (.1) \left(\frac{16.708}{2} \right) = 0.84$$

$$\begin{aligned} LL_2 &= (.1) \left(\frac{15.917}{2} \right) + LL_1 \\ &= 0.80 + 0.84 \\ &= 1.64 \end{aligned}$$

FACTORED LOADS:

$$\begin{aligned} W_1 &= 1.7 * 1.3 (2.51 + 2.51 + .84) \\ &= 12.95 \text{ k/ft} \end{aligned}$$

$$\begin{aligned} W_2 &= W_1 + 1.7 * 1.3 (2.39 + 2.39 + .80) \\ &= W_1 + 12.33 \\ &= 25.28 \text{ k/ft} \end{aligned}$$

$$\begin{aligned} W_{\text{beam}} &= 1.7 * 1.3 * 2.1 \\ &= 4.64 \text{ k} \end{aligned}$$

$$A_s = (.0081)(24)(177) \\ = 14.97 \text{ in}^2$$

$$10 \cdot \# 10 \quad - \quad A_s = 10(1.27) = 12.7 \quad \text{N.G.}$$

$$8 \cdot \# 11 \quad - \quad A_s = 8(1.56) = 12.48 \quad \text{N.G.}$$

$$10 \cdot \# 11 \quad - \quad A_s = 10(1.56) = 15.6 \quad \underline{\underline{\text{OK}}}$$

BEAM B4:

$$L = 15'-11'' \\ h = 8'.058'' \\ b = 24''$$

$$7 \cdot \# 11 \text{ bars} \quad 7 \times 1.56 = 10.92$$

$$d = 90.625 - 6 = 90.625''$$

$$w_{\text{beam}} = (8.05)(2)(.15) = 2.4 \text{ k/ft}$$

$$w_{\text{slab}} = (2')(\frac{12.583}{2}) (.15) = 1.89 \text{ k/ft}$$

$$w_{\text{superimposed}} = (.3)(\frac{12.583}{2}) = 1.89 \text{ k/ft}$$

$$w_{\text{LL}} = (.1)(\frac{12.583}{2}) = 0.63 \text{ k/ft}$$

$$w_{\text{TOTAL}} = 6.81 \text{ k/ft}$$

$$\text{FACTORED LOAD} = 1.7 \times 1.3 \times 6.81 \\ = 15.05$$

$$M = \frac{1}{8} (15.05)(15.917)^2 \\ = 476.62 \text{ k}$$

$$M_u / \phi_s b d^2 = \frac{476.62(12)}{.9(3)(24)(90.625)^2} \\ = 0.011$$

$$\rho = 0.011 (\frac{3}{49}) = 0.00069$$

$$\rho_{\text{min}} = 0.0042$$

$$A_s = 0.0042(24)(90.625) \\ = 9.135 \text{ in}^2 < 10.92 \quad \underline{\underline{\text{OK}}}$$

500 SHEETS FULLER 2 SQUARE
 400 SHEETS FULLER 3 SQUARE
 300 SHEETS FULLER 4 SQUARE
 200 SHEETS FULLER 5 SQUARE
 100 SHEETS FULLER 6 SQUARE
 50 SHEETS FULLER 7 SQUARE
 25 SHEETS FULLER 8 SQUARE
 12 SHEETS FULLER 9 SQUARE
 6 SHEETS FULLER 10 SQUARE
 3 SHEETS FULLER 11 SQUARE
 1 SHEET FULLER 12 SQUARE



BEAM B5:

$$l = 13'-7''$$

$$h = 5'-6\frac{5}{8}''$$

$$b_w = 24''$$

5 # 9 bars

$$5 \times 100 = 5.0 \text{ in}^2$$

$$d = 66.625 - 4'' = 62.625''$$

$$w_{\text{beam}} = (5.55)(2)(.15) = 1.66 \text{ k/ft}$$

$$w_{\text{slab}} = (2')(\frac{1}{2}) (15.92 + 10.34)(.15) = 3.94 \text{ k/ft}$$

$$w_{\text{side DL}} = (1)(15.92 + 10.34)(.30) = 3.94 \text{ k/ft}$$

$$w_{\text{LL}} = (.1)(\frac{1}{2}) (15.92 + 10.34) = 1.31 \text{ k/ft}$$

$$\text{FACTORED LOAD} = 1.7 \times 1.3 (1.66 + 3.94 + 3.94 + 1.31)$$

$$= 23.98 \text{ k/ft}$$

$$M = \frac{1}{8} w L^2$$

$$= \frac{1}{8} (23.98) (13.58)^2$$

$$= 552.8 \text{ k}$$

$$M_u / \phi_s b d^2 = 552.8 (12) / .7 (3) (24) (62.625)^2$$

$$= 0.024$$

$$\rho = 0.024 (3/48) = 0.0016$$

$$\rho_{\text{min (alt)}} = 1.33 (.0016)$$

$$= 0.0021$$

$$A_s = 0.0021 (24) (62.625)$$

$$= 3.16 \text{ in}^2 < 5.0 \quad \underline{\underline{OK}}$$

50 SHEETS, FILLER, 8 SQUARE
 90 SHEETS, FILLER, 8 SQUARE
 100 SHEETS, FILLER, 8 SQUARE
 110 SHEETS, FILLER, 8 SQUARE
 120 SHEETS, FILLER, 8 SQUARE
 130 SHEETS, FILLER, 8 SQUARE
 140 SHEETS, FILLER, 8 SQUARE
 150 SHEETS, FILLER, 8 SQUARE
 160 SHEETS, FILLER, 8 SQUARE
 170 SHEETS, FILLER, 8 SQUARE
 180 SHEETS, FILLER, 8 SQUARE
 190 SHEETS, FILLER, 8 SQUARE
 200 SHEETS, FILLER, 8 SQUARE
 210 SHEETS, FILLER, 8 SQUARE
 220 SHEETS, FILLER, 8 SQUARE
 230 SHEETS, FILLER, 8 SQUARE
 240 SHEETS, FILLER, 8 SQUARE
 250 SHEETS, FILLER, 8 SQUARE
 260 SHEETS, FILLER, 8 SQUARE
 270 SHEETS, FILLER, 8 SQUARE
 280 SHEETS, FILLER, 8 SQUARE
 290 SHEETS, FILLER, 8 SQUARE
 300 SHEETS, FILLER, 8 SQUARE
 Made in U.S.A.



BEAM BU:

$$l = 10' - 4\frac{1}{8}''$$

7 - #11 bars

$$7 \times 1.56 = 10.92$$

$$h = 3' - 6''$$

$$b_w = 24''$$

$$d = 42 - 4 = 38''$$

$$w_{Beam} = (3.5)(2)(.15) = 1.05 \text{ k/ft}$$

$$w_{slab} = (1')(2')(15.58)(.15) = 1.17 \text{ k/ft}$$

$$w_{sup. DL} = (.3)(15.58/2) = 2.34 \text{ k/ft}$$

$$w_{LL} = (.1)(15.58/2) = 0.78 \text{ k/ft}$$

$$\text{FACTORED LOAD} = 1.7 \times 1.3 + (1.05 + 1.17 + 2.34 + 0.78) \\ = 11.80 \text{ k}$$

$$M = \frac{1}{2} w l^2$$

$$= .125 (11.80) (10.34)^2$$

$$= 157.70 \text{ k}$$

$$M_y / \phi b_w d^2 : (157.7)(12) / .9(24)(38)^2$$

$$= 0.020$$

$$\rho = 0.020 \left(\frac{3}{48}\right) = 0.00125$$

$$p_{min} = 0.0042$$

$$\text{alt } p_{min} = 1.33 (0.00125) = 0.0017$$

$$A_s = 0.0017 (24) (38)$$

$$= 1.55$$

$$A_s = 0.0042 (24) (38)$$

$$= 3.83$$

ok

13-782 500 SHEETS, FILLER 8 SQUARE
 42-381 100 SHEETS, FIVE-LAYER 8 SQUARE
 42-382 100 SHEETS, FIVE-LAYER 8 SQUARE
 42-383 200 SHEETS, FIVE-LAYER 8 SQUARE
 42-384 100 RECYCLED WHITE 8 SQUARE
 42-385 200 RECYCLED WHITE 8 SQUARE
 Made in U.S.A.



BEAM B7:

$$l = 21.3''$$

9. #10 bars

$$9 \times 1.27 = 11.43 \text{ in}^2$$

$$h = 8' - 1\frac{3}{16}''$$

$$b_w = 24''$$

$$d = 97.81 - 6 = 91.81''$$

$$w_{\text{beam}} = (8.15)(2)(.15) = 2.44$$

$$w_{\text{slab}} = (1')(\frac{1}{2})(15.58)(.15) = 1.17$$

$$(2')(9.42')(.15) = 2.83$$

$$w_{\text{sup. sl.}} = (.30) [\frac{1}{2} (15.58) + 9.42] = 5.16$$

$$w_{\text{cl.}} = (.1) (\frac{15.58}{5} + 9.42) = 1.72$$

$$\text{FACTORED LOAD} = 1.7 + 1.3 * (2.44 + 1.17 + 2.83 + 5.16 + 1.72)$$

$$= 29.44$$

$$M = \frac{1}{8} w L^2$$

$$= \frac{1}{8} (29.44) (21.25)^2$$

$$= 1661.75 \text{ k}$$

$$M_u / \phi f_c' b d^2 = (1661.75)(12) / (.9)(3)(24)(91.81)^2$$

$$= 0.036$$

$$p = 0.036 (3/48) = 0.00225$$

$$p_{\text{min}} = 0.0042$$

$$\text{alt } p_{\text{min}} = 1.33 (0.00225)$$

$$= 0.0030$$

$$A_s = 0.0030 (24) (91.81)$$

$$= 6.61$$

OK

15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190 195 200 205 210 215 220 225 230 235 240 245 250 255 260 265 270 275 280 285 290 295 300 305 310 315 320 325 330 335 340 345 350 355 360 365 370 375 380 385 390 395 400 405 410 415 420 425 430 435 440 445 450 455 460 465 470 475 480 485 490 495 500 505 510 515 520 525 530 535 540 545 550 555 560 565 570 575 580 585 590 595 600 605 610 615 620 625 630 635 640 645 650 655 660 665 670 675 680 685 690 695 700 705 710 715 720 725 730 735 740 745 750 755 760 765 770 775 780 785 790 795 800 805 810 815 820 825 830 835 840 845 850 855 860 865 870 875 880 885 890 895 900 905 910 915 920 925 930 935 940 945 950 955 960 965 970 975 980 985 990 995 1000

