

HOT SPOTS

An "Airport surface hot spot" is a location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.

A "hot spot" is a runway safety related problem area on an airport that presents increased risk during surface operations. Typically it is a complex or confusing taxiway/taxiway or taxiway/runway intersection. The area of increased risk has either a history of or potential for runway incursions or surface incidents, due to a variety of causes, such as but not limited to: airport layout, traffic flow, airport marking, signage and lighting, situational awareness, and training. Hot spots are depicted on airport diagrams as open circles or polygons designated as "HS 1", "HS 2", etc. and tabulated in the list below with a brief description of each hot spot. Hot spots will remain charted on airport diagrams until such time the increased risk has been reduced or eliminated.

CITY/AIRPORT	HOT SPOT	DESCRIPTION
ALASKA		
ANCHORAGE TED STEVENS ANCHORAGE INTL (ANC) (PANC)	HS 1	Acft taxiing via Twy E to Twy G and Twy K to Rwy 33 sometimes miss the turn from Twy G on to Twy K and continue on Twy G across Rwy 07L-25R by mistake, especially with rstd visibility.
KODIAK KODIAK (ADQ)(PADQ)	HS 1	Twy F is narrow, do not stop acft on or near the twy blocking access to the main ramp.