N
500 0 FEET 500 1000 1500
CONTOUR INTERVAL-10 FEET
EXPLANATION
DRILL HOLE LOCATION
8.0 COAL SEAM ISOPACH LINE (ISOPACH INTERVAL 0.5 FEET)
MINIMUM MINEABLE COAL QUALITY LINE (6,000 BTU)
COAL SEAM BURN LINE
COAL SEAM SPLIT LINE (BARBS POINT TOWARD SPLIT AREA WHERE ROCK PARTING IS GREATER THAN 1 FOOT THICK)
COAL SEAM PINCH-OUT LINE (ARROWS POINT TOWARD AREA WHERE COAL SEAM IS LESS THAN 2 FEET THICK)
COAL MINED OUT AS OF DECEMBER 16, 1977.
COAL LEASE BOUNDARY
INDEX MAP
AREA I
AREA II
AREA III
AREA IV N
EXHIBIT 5-22a
BHP-MINERALS INTERNATIONAL
NAVAJO MINE
FRUITLAND, NEW MEXICO
AREA IV
SEAM Ga
THICKNESS MAP
SAN JUAN COUNTY, NEW MEXICO
DRAWN BY L. DAN SCALE 1" = 500' SUBMITTED
APPROVED BY DATE
DRAWING NO. LOCATION NO.
REVISIONS
APPROVALS