N
500 0 FEET 500 1000 2000
CONTOUR INTERVAL = 10 FEET
DATUM NO. 4613
LEGEND
DRILL HOLE LOCATION
5280 TOP OF COAL SEAM STRUCTURE CONTOURS (CONTOUR INTERVAL 10 FEET)
50 OVERBURDEN ISOPACH LINES (ISOPACH INTERVAL 10 FEET)
MINIMUM MINEABLE COAL QUALITY LINE 8,000BTU
COAL SEAM BURN LINE
COAL SEAM SPLIT LINE (BARBS POINT TOWARD SPLIT AREA WHERE ROCK PARTING IS GREATER THAN 1 FOOT THICK)
COAL SEAM PINCH-OUT LINE (ARROWS POINT TOWARD AREA WHERE COAL SEAM IS LESS THAN 2 FEET THICK)
COAL MINED OUT AS OF DECEMBER 16, 1977.
COAL LEASE BOUNDARY
UNMINEABLE
BURN
OVERBURDEN TO TOP OF SEAM
TOP OF SEAM CONTOUR
INDEX-MAP
AREA I
AREA II
AREA III
AREA IV
EXHIBIT 5-2
BHP MINERALS INTERNATIONAL
FARMINGTON, NEW MEXICO
SEAM 6B
AREA
TOP OF SEAM STRUCTURE
AND ISO-OVERBURDEN MAP
DRAWN BY L. DAN
SCALE 1"=500'
EXHIBIT
APPROVED BY
DATE
DRAWING NO.