EXPLANATION

- DRILL HOLE LOCATION
- COAL SEAM ISOPACH LINES (ISOPACH INTERVAL = 0.5 FEET)
- MINIMUM MINEABLE COAL QUALITY LINE (6,000 BTU)
- COAL SEAM BURN LINE
- COAL SEAM SPLIT LINE (BARBS POINT TOWARD SPLIT AREA WHERE ROCK PARTING IS GREATER THAN 1 FOOT THICK)
- COAL SEAM PINCH-OUT LINE (ARROWS POINT TOWARD AREA WHERE COAL SEAM IS LESS THAN 2 FEET THICK)
- COAL MINED OUT AS OF DECEMBER 16, 1977
- COAL LEASE BOUNDARY

I, HEREBY CERTIFY THIS MAP TO BE A TRUE AND CORRECT MAP OF THE COAL SEAM OF THE MINE OF EHP MINERALS INTERNATIONAL INC.

INDEX MAP



EXHIBIT 5-37a

EHP MINERALS INTERNATIONAL INC.

MINE 8 PILE

SEAM - RIDER ABOVE SEAM 8b
COAL THICKNESS
AREA I

DRAWN BY	L. DUDA	SCALE 1" = 200'	CONTRT.
APPROVED BY	J. S.V.	DATE	
DRAWING NO.		LOCATION NO.	

REV.	DATE	REVISIONS	APPROVALS			
			DRAWN	CHECKED	ENGINEER	MANAGER
1	1-77	"A" PILE REVISED TO MINE 8 PILE AND "B" PILE REVISED TO MINE 8 PILE	Bo	JDM	TJC	
2	3-77	ADDED COAL SEAM BURN LINE				