

Developing and Managing a Comprehensive Reservoir Analysis Model

November 1988

TP-123

| Я | REPORT DOC | CUMENTATIC | N PAGE | | Form Approved OMB No. 0704-0188 | |
|---|---|--|---|--|--|--|
| The public reporting burc existing data sources, ga burden estimate or any c Services and Communic subject to any penalty for PLEASE DO NOT RETU | len for this collection o thering and maintainin ther aspect of this coll- ations Directorate (070 failing to comply with RN YOUR FORM TO | f information is estimate g the data needed, and ection of information, in 4-0188). Respondents a collection of informati THE ABOVE ORGANIZ | d to average 1 hour p completing and revie cluding suggestions fo should be aware that on if it does not displa ZATION. | er response, in wing the collect or reducing this notwithstanding y a currently va | cluding the time for reviewing instructions, searching ion of information. Send comments regarding this burden, to the Department of Defense, Executive g any other provision of law, no person shall be lid OMB control number. | |
| 1. REPORT DATE (DD-M | ИМ-ҮҮҮҮ) | 2. REPORT TYPE | | 3. DATE | S COVERED (From - To) | |
| November 1988 | E | Technical Paper | | | | |
| Developing and Ma | naging a Compre | hensive Reservoir | · Analysis | Ja. CONTRAC | I NOMBER | |
| Model | ininging a compre | | 1 11101 9 515 | 5b. GRANT N | UMBER | |
| | | | - | 5c. PROGRAM | I ELEMENT NUMBER | |
| 6. AUTHOR(S) | | | | 5d. PROJECT | NUMBER | |
| Richard J. Hayes, H | Bill S. Eichert, Ma | rilyn B. Hurst | | | | |
| | | | | 5e. TASK NUI | MBER | |
| | | | | 5F. WORK UN | IIT NUMBER | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Corps of Engineers Institute for Water Resources Hydrologic Engineering Center (HEC) 609 Second Street Davis, CA 95616-4687 | | | | 8. PERF TP-123 | ORMING ORGANIZATION REPORT NUMBER | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPO | NSOR/ MONITOR'S ACRONYM(S) | |
| | | | | 11. SPO | NSOR/ MONITOR'S REPORT NUMBER(S) | |
| | | | | | | |
| Approved for publi | c release; distribu | ttion is unlimited. | | | | |
| 13. SUPPLEMENTARY Presented at Ameri | NOTES can Water Resour | rce Association, M | lilwaukee, Wisco | onsin, Nover | nber 1988. | |
| 14. ABSTRACT The Corps of Engineers operates over 300 reservoir projects which serve a variety of purposes including flood control, hydropower, water supply, water quality, recreation and navigation. Corps projects are operated in a wide range of physical environments with numerous operational constraints. The Corps' Hydrologic Engineering Center (HEC) has developed a generalized simulation model capable of analyzing complex river-reservoir systems. The development of the model "HEC-5, Simulation of Flood Control and Conservation | | | | | | |
| Systems" (Eichert, 1974, 1975) has been paced by the changing mission of the Corps as well as the evolution of computer system. | | | | | | |
| HEC-5 development and management, including code development, testing, documentation, training and field application experience, will be discussed. | | | | | | |
| | | | | | | |
| | | | | | | |
| 15. SUBJECT TERMS computer model, re | 15. SUBJECT TERMS computer model, reservoir system modeling, program management | | | | | |
| 16. SECURITY CLASSI | FICATION OF: | | 17. LIMITATION | 18. NUME | ER 19a. NAME OF RESPONSIBLE PERSON | |
| a. REPORT | b. ABSTRACT | c. THIS PAGE | OF | OF | 6 | |
| U | U | U | UU | PAGE 22 | 19b. TELEPHONE NUMBER | |
| | | I | I | I | Standard Form 298 (Rev. 8/98) | |

Prescribed by ANSI Std. Z39-18

Developing and Managing a Comprehensive Reservoir Analysis Model

November 1988

US Army Corps of Engineers Institute for Water Resources Hydrologic Engineering Center 609 Second Street Davis, CA 95616

(530) 756-1104 (530) 756-8250 FAX www.hec.usace.army.mil

TP-123

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution with the Corps of Engineers.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

Developing and Managing a Comprehensive Reservoir Analysis Model¹

Richard J. Hayes², Bill S. Eichert³ and Marilyn B. Hurst⁴

ABSTRACT

The Corps of Engineers operates over 300 reservoir projects which serve a variety of purposes including flood control, hydropower, water supply, water quality, recreation, and navigation. Corps projects are operated in a wide range of physical environments with numerous operational constraints.

The Corps' Hydrologic Engineering Center (HEC) has developed a generalized simulation model capable of analyzing complex river-reservoir systems. The development of the model, "HEC-5, Simulation of Flood Control and Conservation Systems" (Eichert, 1974, 1975) has been paced by the changing mission of the Corps as well as the evolution of computer systems.

HEC-5 development and management, including code development, testing, documentation, training, and field application experience, will be discussed.

INTRODUCTION

Computer program "HEC-5, Simulation of Flood Control and Conservation Systems", has evolved during the last 16 years (1972-1988) from a flood control only, single event reservoir simulation model to a generalized hydrologic and economic reservoir simulation model with capabilities for flood control, water supply, and hydropower analysis for multi-flood or period of record analysis. HEC-5 has developed in ways which the program's author, Bill S. Eichert, could

¹Presented at American Water Resource Association, Milwaukee, Wisconsin, 8 November 1988

²Hydraulic Engineer, Hydrologic Engineering Center (HEC), 609 Second Street, Davis, CA 95616, Member AWRA

³Director, HEC

⁴Computer Programmer, HEC, Member AWRA

not have anticipated, reflecting both the changing requirements of the Corps of Engineers and the evolution of computer systems.

The first release of HEC-5, May 1973, gave the Corps of Engineers a mainframe based, reservoir simulation model which automated the traditional manual reservoir routing and release decision making computations. This version provided the ability to simulate up to three flood control reservoirs operating for downstream damage centers or reservoirs, with consideration of local flows and hydrologic routing, for a single flood event.

The most recent release, the October 1988 version, provides the Corps with the ability to simulate reservoir system operation for flood control, water supply, and hydropower objectives on both mainframe and personal computers for any configuration of up to twenty reservoirs and thirty-five control points. Current Corps HEC-5 applications include real-time water control as well as planning oriented simulations.

PROGRAM DEVELOPMENT

The original code, written in FORTRAN IV, was developed on 64-bit CDC 7600 computers. The current version has been updated to FORTRAN 77 and development is occurring on a 24-bit Harris mini-computer and 32-bit PCs. Program size has increased from approximately 20,000 lines of code for HEC-5 in 1979 to more than 143,000 lines of code in the six programs that comprise the family of file creation, data checking, and simulation modules that represent the complete 1988 HEC-5 package of programs (see Figure 1).

The code style of the early releases of HEC-5 was typified by a small number of rather lengthy complex subroutines tied together with large catch-all COMMON blocks. In 1978, storage requirements for the program had grown large enough that a subdivision of the code into two separate programs, a simulation module (HEC5A) and an output/economic analysis post-processor (HEC5B), was required.

2

LI

HEC-5 FAMILY OF PROGRAMS (APRIL 1988)

| Name | Program Purpose | Number of Subroutines | Lines of Code |
|--------------|-----------------------------|--------------------------|---------------|
| HEC5A | Simulation (Batch) | 169 | 86,000 |
| HEC5B | Output & Economics (Batch) | 30 | 10,000 |
| CKHEC5 | Input Checking (Batch) | 28 | 9,600 |
| IN5 | Input Creation (IA) | 23 | 10,800 |
| MOD5 | Input Modification (IA) | 47 | 25,000 |
| MENU5 | Program, I/O Selection (IA) | 10 | 1,600 |
| Total | | 307 | 143,000 |

PROGRAM MODERNIZATION

In 1982, the HEC initiated an analysis of the structure and function of the HEC-5 subroutines and COMMON block structure. The goal of this analysis and subsequent code modernization was to minimize program support efforts, reduce malfunctions, and make future HEC-5 code improvements more manageable. This resulted in segmentation of the HEC5A's 12 major routines into 102 routines with most inter-routine communication accomplished with argument strings.

In addition to creating logic modules which were easier to understand and modify, numerous comments were added to the code with explanations of logic, variable definitions, and notes related to possible future improvements. This type of internal documentation has proven to be a significant aid to both the original program author as well as other HEC staff in making improvements and correcting malfunctions.

The majority of the segmentation work was performed under contract. An in-house run through of the subroutine segmentation process was performed by Ms. Marilyn Hurst, a programmer assigned full time to the HEC-5 program, to better estimate the time required and the process necessary for the remaining segmentation. The task of designing the COMMON blocks and argument strings as well as completing the segmentation process was then contracted to the staff of the Hydraulics Lab of the University of California at Davis (UCD). Their experience with FORTRAN programming for a variety of micro-computers used for data collection and analysis proved quite useful when the HEC began the process of adapting HEC-5 to personal computers.

In a further effort to streamline the program logic, several new subroutines were created to centralize logic, such as that related to the program's determination of reservoir releases. This was necessary because during the first 10 years of development of HEC-5 the logic for the prioritization and selection of many of the seventeen possible reservoir releases had been scattered throughout the code. In addition several essential routines were rewritten to clarify logic that had become difficult to understand after years of code

improvements by several authors, each with a different style and understanding of the program.

Also improved in the modernization process was the HEC-5 optional "trace output" capability. This program feature provides diagnostic output showing, the normally unseen, internal computations. The trace feature is selectable by subroutine, simulation time period, and data model location (ie, reservoir or control point). The modernization activity enhanced the trace output feature by including variable name labels above the numeric trace output for easier debugging. In addition, the origin of the trace output (subroutine names and statement numbers) is shown for each trace output. We have found the trace output feature to be indispensable in the development and maintenance of a large, complex, program such as HEC-5.

The net result of the HEC-5 modernization effort has been the development of a program which is significantly easier to understand, to maintain and to adapt to a variety of computer systems. Future code enhancements, including the addition of hydraulic routing and graphical interfaces, will no doubt benefit from these efforts.

ADAPTATION TO MICRO COMPUTERS

The process of adapting HEC-5 from the CDC mainframe computers to the personal computer actually began with the installation of HEC-5 on the HEC's Harris 500 mini-computer in 1980. The change from the CDC 64-bit word size to the Harris' 24-bit computer required the selected use of double precision integer variables and resulted in an effort to modify HEC-5's use of mixed mode arithmetic statements to avoid the use of double precision statements. Further PC related code enhancements were developed as a result of adapting HEC-5 for use with the less forgiving compilers of an HP 9000 mini and an Amdahl mainframe computer. These adaptations, coupled with the revised subroutine structure and improved COMMON blocks, provided the basis for the successful adaptation of HEC-5 to micro computers.

5

The HEC contracted with Mr. Carl Franke, an electrical engineer and microcomputer hobbyist, to make the adaptation of HEC-5 to an IBM PC/XT. Mr. Franke had worked on the program while a UCD employee, and had adapted it to the HP and Amdahl computer systems for the Corps. He investigated four PC level FORTRAN compilers and found that the LAHEY FORTRAN 77 (LAHEY, 1987) compiler was the only PC level FORTRAN compiler with a complete enough implementation of FORTRAN 77 to accommodate HEC-5's large number of arguments and continuation lines.

Originally, it was anticipated that the implementation of a large mainframe type program such as HEC-5 to the micro computer environment would be made at the expense of program capabilities and by significant reductions in array sizes. Mr. Franke was able, however, to successfully implement the September 1986 program on an IBM PC/XT while maintaining HEC-5's full capabilities, with only moderate reductions in array sizes through the use of program overlays.

This first HEC-5 PC release utilized a complex nested overlay scheme to fit the program within the 640 Kb MS-DOS memory limit. The October 1988 PC version (HEC, 1988), however, provides full mainframe array sizes and comparable execution times without overlaying by using A.I. Architects OS/286 (A.I. ARCHITECTS, 1988) extension to MS-DOS and extended memory. (See Figure 2)

MAINTENANCE SOFTWARE

As program code is revised and new capabilities are added to a large program such as HEC-5, the need arises for a systematic, trackable, software maintenance system. The primary tool that is being currently utilized for updating and maintaining the HEC-5 package of software is OPCODE's "Historian Plus" (OPCODE, 1985) program, which is available on the HEC Harris 1000 computer. The Historian program provides a systematic procedure for tracking program modifications; thus, as its name implies, it provides a "history" of the programs development. With HEC-5 code modifications developed simultaneously at the HEC by three staff members, in addition to code changes provided by contractors, the usefulness of a systematic approach is obvious.

CURRENT HEC-5 PC PERFORMANCE

ARRAY SIZES

| | Mainframe | 1986 PC | 1988 PC |
|--------------------------|-----------|---------|---------|
| Number of Reservoirs | 20 | 15 | 20 |
| Number of Control Points | 35 | 15 | 35 |
| Number of Time Periods | 2,000 | 200 | 2,000 |
| Number of Power Plants | 12 | σ | 12 |

:9

In order to better understand the many lines of program code that constitute the HEC-5 package of programs, several other utility programs have been developed for use as programming tools. One of the most useful is the HEC developed "FORTRAN Source Inventory and Renumbering (FSIR)" program (HEC,1966). FSIR is utilized primarily to map the location and function of program variables. It creates, for all variables in a FORTRAN source deck, files which contain the FORTRAN statement numbers, subroutine name and a code which indicates the type of FORTRAN statement where the variable was used. In addition, FSIR is used to renumber FORTRAN statement numbers, which becomes necessary when many changes are made to HEC-5. These capabilities have proven to be invaluable tools in modifying and maintaining HEC-5.

PROGRAM TESTING

An important aspect of the management and development of a complex program, such as HEC-5, is the creation and use of test materials for the verification of code changes. In the case of HEC-5, it is not entirely unexpected that revisions to program logic related to water supply simulation could effect hydropower or flood control release determinations. The HEC initially developed a series of ten standard data sets which provided testing for many of the programs options. These standard data sets have also been utilized for installation verification and benchmarking when HEC-5 has been adapted to other computer systems.

As the number of program options increased, it became obvious that further development of test data sets would be of value both for verification and training purposes. Three additional groups of data sets were developed to provide testing for HEC-5's gate regulation, water supply and hydropower simulation capabilities. An additional collection of flood control test data sets are currently under development. Upon completion of this effort approximately one hundred standard data sets will be available for verification and for use as training examples. In addition to the standard test data sets, training course workshop problems and several large field application data sets are utilized periodically for testing.

DOCUMENTATION AND TRAINING

The HEC has always endeavored to provide suitable documentation and training for each of its major programs. Current HEC-5 documentation includes: a Users Manual (HEC, 1982); a separate Input Description (HEC, 1988), which is updated once or twice each year to reflect program developments; and Training Documents for Water Supply (HEC, 1985) and Hydropower (HEC, 1983) applications. In addition, users manuals are available for HEC-5 auxilarly programs; CKHEC5 (HEC, 1987), a data checking program; INFIVE (HEC, 1987), an interactive input preparation program; and INCARD (HEC, 1983), a flow conversion program. In addition to these documents, a Programmers Manual, as well as a revised training document for hydropower and a new document of flood control applications are in preparation.

Training related to computer program HEC-5 is offered in a two week course titled "Reservoir System Analysis" at the HEC in Davis, CA every other year.

FIELD APPLICATIONS

HEC staff members provide HEC-5 field application support to Corps of Engineers offices upon request. Usually HEC assistance is sought by offices for a number of reasons including those without the necessary inhouse HEC-5 expertise or for those studies which require code modifications to extend or add new program capabilities. From a program management point of view, the HEC welcomes the opportunity to involve staff members in practical engineering applications. These are often opportunities to provide informal at-site training, develop new program capabilities, improve program documentation, or develop new training materials.

Corps of Engineers field applications utilizing HEC-5 which have required extensive HEC staff assistance in the past year have included: a period-of-record water supply analysis of the Rio Grande Basin in New Mexico, a navigation/hydropower study for the Han River Basin in South Korea, a flood control study for the Savannah River Basin in Georgia and South Carolina, real-

9

time water control for the Allegheny River in Pennsylvania, and a period-ofrecord analysis for system power in Alabama, Georgia and South Carolina.

An example of a recent HEC-5 application is shown in Figure 3, which is a schematic diagram of an HEC-5 model developed to provide real-time reservoir operation for Corps projects in the Allegheny River Basin near Pittsburgh, PA. The HEC-5 model developed for this application interfaces with other HEC software which provides forecasted flows from observed and forecast precipitation. The simulation interval for this analysis is three hours.

Another example is shown in Figure 4, which is a schematic diagram of an HEC-5 model developed to simulate system hydropower production in ten of the Corps projects within the South Eastern Power Administration (SEPA). This model is being utilized in a planning mode to evaluate proposed changes in reservoir operation to reflect the impact of water supply, recreation, and navigation on system power production. The period of analysis for this study is about sixty years and the simulation interval is weekly.

PROGRAM SUPPORT

Program support in the form of hotline assistance for both engineering and programming assistance is available to the Corps of Engineers and other federal agencies. At-site training courses, application assistance and program modifications are also provided to Corps offices. Mr. Richard Hayes is the Engineer in charge of providing hotline user support and is the principal Engineer providing field application assistance for HEC-5. Non-federal support for HEC-5 users, including program distribution, users assistance, and engineering is available through several engineering firms.

10

ALLEGHNEY BASIN HEC-5 MODEL SCHEMATIC





LITERATURE CITED

A.I. Architects, Inc., 1988. OS/286 Documentation.

Eichert, Bill S., 1974. HEC-5C, A Simulation Model for System Formulation and Evaluation.

Eichert, Bill S., 1975. Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources System.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1966. FORTRAN Source Inventory and Renumbering.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1980. Application of the HEC-5 Hydropower Routines. Training Document No. 12.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1982. HEC-5, Simulation of Flood Control and Conservation Systems, Users Manual.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1983. INCARD, Flow Conversion for HEC-5, Users Manual.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1985. Water Supply Simulation Using HEC-5, Training Document No. 20.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1987. INFIVE, Interactive Input Preparation Program for HEC-5, Users Manual.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1987. CKHEC5, Input Data Checking Program for HEC-5, Users Manual.

Hydrologic Engineering Center, U.S. Army Corps of Engineers, 1988. HEC-5, Simulation of Flood Control And Conservation Systems, Exhibit 8 of Users Manual, Input Description.

Lahey Computer Systems, Inc. 1987. Fortran 77 Language System.

Opcode, Inc, 1987. Historian[™] Plus, Reference Manual.

Technical Paper Series

- TP-1 Use of Interrelated Records to Simulate Streamflow TP-2 Optimization Techniques for Hydrologic Engineering TP-3 Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs TP-4 Functional Evaluation of a Water Resources System TP-5 Streamflow Synthesis for Ungaged Rivers TP-6 Simulation of Daily Streamflow TP-7 Pilot Study for Storage Requirements for Low Flow Augmentation TP-8 Worth of Streamflow Data for Project Design - A Pilot Study TP-9 Economic Evaluation of Reservoir System Accomplishments Hydrologic Simulation in Water-Yield Analysis **TP-10 TP-11** Survey of Programs for Water Surface Profiles **TP-12** Hypothetical Flood Computation for a Stream System **TP-13** Maximum Utilization of Scarce Data in Hydrologic Design **TP-14** Techniques for Evaluating Long-Tem Reservoir Yields **TP-15** Hydrostatistics - Principles of Application **TP-16** A Hydrologic Water Resource System Modeling Techniques Hydrologic Engineering Techniques for Regional **TP-17** Water Resources Planning **TP-18** Estimating Monthly Streamflows Within a Region **TP-19** Suspended Sediment Discharge in Streams **TP-20** Computer Determination of Flow Through Bridges TP-21 An Approach to Reservoir Temperature Analysis **TP-22** A Finite Difference Methods of Analyzing Liquid Flow in Variably Saturated Porous Media **TP-23** Uses of Simulation in River Basin Planning **TP-24** Hydroelectric Power Analysis in Reservoir Systems **TP-25** Status of Water Resource System Analysis **TP-26** System Relationships for Panama Canal Water Supply **TP-27** System Analysis of the Panama Canal Water Supply **TP-28** Digital Simulation of an Existing Water Resources System **TP-29** Computer Application in Continuing Education **TP-30** Drought Severity and Water Supply Dependability TP-31 Development of System Operation Rules for an Existing System by Simulation **TP-32** Alternative Approaches to Water Resources System Simulation **TP-33** System Simulation of Integrated Use of Hydroelectric and Thermal Power Generation **TP-34** Optimizing flood Control Allocation for a Multipurpose Reservoir **TP-35** Computer Models for Rainfall-Runoff and River Hydraulic Analysis **TP-36** Evaluation of Drought Effects at Lake Atitlan **TP-37** Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes **TP-38** Water Quality Evaluation of Aquatic Systems
- TP-39 A Method for Analyzing Effects of Dam Failures in Design Studies
- TP-40 Storm Drainage and Urban Region Flood Control Planning
- TP-41 HEC-5C, A Simulation Model for System Formulation and Evaluation
- TP-42 Optimal Sizing of Urban Flood Control Systems
- TP-43 Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems
- TP-44 Sizing Flood Control Reservoir Systems by System Analysis
- TP-45 Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin
- TP-46 Spatial Data Analysis of Nonstructural Measures
- TP-47 Comprehensive Flood Plain Studies Using Spatial Data Management Techniques
- TP-48 Direct Runoff Hydrograph Parameters Versus Urbanization
- TP-49 Experience of HEC in Disseminating Information on Hydrological Models
- TP-50 Effects of Dam Removal: An Approach to Sedimentation
- TP-51 Design of Flood Control Improvements by Systems Analysis: A Case Study
- TP-52 Potential Use of Digital Computer Ground Water Models
- TP-53 Development of Generalized Free Surface Flow Models Using Finite Element Techniques
- TP-54 Adjustment of Peak Discharge Rates for Urbanization
- TP-55 The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers
- TP-56 Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models
- TP-57 Flood Damage Assessments Using Spatial Data Management Techniques
- TP-58 A Model for Evaluating Runoff-Quality in Metropolitan Master Planning
- TP-59 Testing of Several Runoff Models on an Urban Watershed
- TP-60 Operational Simulation of a Reservoir System with Pumped Storage
- TP-61 Technical Factors in Small Hydropower Planning
- TP-62 Flood Hydrograph and Peak Flow Frequency Analysis
- TP-63 HEC Contribution to Reservoir System Operation
- TP-64 Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study
- TP-65 Feasibility Analysis in Small Hydropower Planning
- TP-66 Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems
- TP-67 Hydrologic Land Use Classification Using LANDSAT
- TP-68 Interactive Nonstructural Flood-Control Planning
- TP-69 Critical Water Surface by Minimum Specific Energy Using the Parabolic Method

| IP-70 | Corps of Engineers Experience with Automatic |
|---------------|--|
| | Calibration of a Precipitation-Runoff Model |
| TP-71 | Determination of Land Use from Satellite Imagery |
| | for Input to Hydrologic Models |
| TP-72 | Application of the Finite Element Method to |
| | Vertically Stratified Hydrodynamic Flow and Water |
| | Quality |
| TED 70 | |
| TP-/3 | Flood Mitigation Planning Using HEC-SAM |
| TP-74 | Hydrographs by Single Linear Reservoir Model |
| TP-75 | HEC Activities in Reservoir Analysis |
| TP-76 | Institutional Support of Water Resource Models |
| TP-77 | Investigation of Soil Conservation Service Urban |
| | Hydrology Techniques |
| TP-78 | Potential for Increasing the Output of Existing |
| 11 /0 | Hudroalactria Dlants |
| TD 7 0 | |
| TP-/9 | Potential Energy and Capacity Gains from Flood |
| | Control Storage Reallocation at Existing U.S. |
| | Hydropower Reservoirs |
| TP-80 | Use of Non-Sequential Techniques in the Analysis |
| | of Power Potential at Storage Projects |
| TP-81 | Data Management Systems of Water Resources |
| | Planning |
| TD 92 | The New HEC 1 Flood Hydrograph Deckage |
| TD 02 | The New HEC-1 Flood Hydrograph Fackage |
| TP-83 | River and Reservoir Systems water Quality |
| | Modeling Capability |
| TP-84 | Generalized Real-Time Flood Control System |
| | Model |
| TP-85 | Operation Policy Analysis: Sam Rayburn |
| | Reservoir |
| TP-86 | Training the Practitioner: The Hydrologic |
| 11 00 | Engineering Center Program |
| TD 97 | Desumantation Needs for Water Pesources Medals |
| TD 00 | Documentation Needs for water Resources Models |
| TP-88 | Reservoir System Regulation for Water Quality |
| | Control |
| TP-89 | A Software System to Aid in Making Real-Time |
| | Water Control Decisions |
| TP-90 | Calibration, Verification and Application of a Two- |
| | Dimensional Flow Model |
| TP-91 | HEC Software Development and Support |
| TP-92 | Hydrologic Engineering Center Planning Models |
| TD 03 | Flood Pouting Through a Flot Complex Flood |
| 11-95 | Plain Using a One Dimensional Usetes de Flam |
| | Plain Using a One-Dimensional Unsteady Flow |
| | Computer Program |
| TP-94 | Dredged-Material Disposal Management Model |
| TP-95 | Infiltration and Soil Moisture Redistribution in |
| | HEC-1 |
| TP-96 | The Hydrologic Engineering Center Experience in |
| | Nonstructural Planning |
| TP-97 | Prediction of the Effects of a Flood Control Project |
| 11)/ | on a Meandering Stream |
| TD 08 | Evolution in Computer Programs Causes Evolution |
| 11-90 | |
| | in Training Needs: The Hydrologic Engineering |
| | Center Experience |
| TP-99 | Reservoir System Analysis for Water Quality |
| TP-100 | Probable Maximum Flood Estimation - Eastern |
| | United States |
| TP-101 | Use of Computer Program HEC-5 for Water Supply |
| | Analysis |
| TP_102 | Role of Calibration in the Application of HEC 6 |
| TD 102 | Engineering and Economic Considerations in |
| 11-103 | Engineering and Economic Considerations in |
| | Formulating |
| TP-104 | Modeling Water Resources Systems for Water |
| | Quality |

Come of Englishers Experience with Automatic

TD 70

- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model for Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computer Water Surface Profiles -Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the Microcomputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of U.S. Army corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning -Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins
- TP-134 Annual Extreme Lake Elevations by Total Probability Theorem
- TP-135 A Muskingum-Cunge Channel Flow Routing Method for Drainage Networks
- TP-136 Prescriptive Reservoir System Analysis Model -Missouri River System Application
- TP-137 A Generalized Simulation Model for Reservoir System Analysis
- TP-138 The HEC NexGen Software Development Project
- TP-139 Issues for Applications Developers
- TP-140 HEC-2 Water Surface Profiles Program
- TP-141 HEC Models for Urban Hydrologic Analysis

- TP-142 Systems Analysis Applications at the Hydrologic Engineering Center
- TP-143 Runoff Prediction Uncertainty for Ungauged Agricultural Watersheds
- TP-144 Review of GIS Applications in Hydrologic Modeling
- TP-145 Application of Rainfall-Runoff Simulation for Flood Forecasting
- TP-146 Application of the HEC Prescriptive Reservoir Model in the Columbia River Systems
- TP-147 HEC River Analysis System (HEC-RAS)
- TP-148 HEC-6: Reservoir Sediment Control Applications
- TP-149 The Hydrologic Modeling System (HEC-HMS): Design and Development Issues
- TP-150 The HEC Hydrologic Modeling System
- TP-151 Bridge Hydraulic Analysis with HEC-RAS
- TP-152 Use of Land Surface Erosion Techniques with Stream Channel Sediment Models

- TP-153 Risk-Based Analysis for Corps Flood Project Studies - A Status Report
- TP-154 Modeling Water-Resource Systems for Water Quality Management
- TP-155 Runoff simulation Using Radar Rainfall Data
- TP-156 Status of HEC Next Generation Software Development
- TP-157 Unsteady Flow Model for Forecasting Missouri and Mississippi Rivers
- TP-158 Corps Water Management System (CWMS)
- TP-159 Some History and Hydrology of the Panama Canal
- TP-160 Application of Risk-Based Analysis to Planning Reservoir and Levee Flood Damage Reduction Systems
- TP-161 Corps Water Management System Capabilities and Implementation Status