
# 

HIGH FLUX ISOTOPE REACTOR

Ш



## GENERAL-PURPOSE SANS - SMALL-ANGLE NEUTRON SCATTERING DIFFRACTOMETER

### SPECIFICATIONS

 $\lambda = 4 - 25 \text{ Å}$ 

Beam

The general-purpose SANS diffractometer is optimized for providing information about structure and interactions in materials in the size range of 0.5–200 nm. It has a cold neutron flux on sample and capabilities comparable to those of the best SANS instruments worldwide, including a wide range of neutron wavelengths  $\lambda = 4-25$  Å, resolution  $\delta\lambda/\lambda = 9-45\%$ , and a 1 m<sup>2</sup> area detector with 5 × 5 mm<sup>2</sup> pixel resolution with a maximum counting capability of up to 25 kHz. The sample-to-detector distance can be varied from 1 to 20 m, and the detector can be offset horizontally by up to 45 cm, allowing a total accessible Q range of from <0.001 to 1 Å<sup>-1</sup>. The 2 m sample environment area accommodates large, special-purpose sample environments such as cryomagnets, furnaces, mechanical load frames, and shear cells.



# APPLICATIONS

- Soft condensed matter: molecular self-assembly and interactions in complex fluids; intermediate order in glassy systems, polymer solutions, gels and blends, colloids, micelles, and microemulsions
- Hard condensed matter: phase separation, grain growth, and orientation in metallurgical alloys, nanocomposites, advanced ceramics, and porous catalytic, adsorbent materials, geophysics and carbon-storage systems
- Magnetic systems: flux lattices in superconductors, ferrofluids, and the relationship between structural and magnetic domains and ordering

### For more information, contact

Instrument Scientist: Ken Littrell, littrellkc@ornl.gov, 865.291.7583 Instrument Scientist: Yuri Melnichenko, melnichenkoy@ornl.gov, 865.576.7746

spectrum	$\Delta\lambda/\lambda = 9-45\%$
Sample- detector distance	1.1–19.4 m
Detector offset	0–45 cm
Source-sam- ple distance	1.8–17.4 m
Max flux on sample	>2 × 10 <sup>7</sup> n/cm <sup>2</sup> /s at $\lambda$ = 4.75 Å, $\Delta\lambda/\lambda$ = 14%
Detector	2D linear position- sensitive detector
Detector resolution/ pixels	192 x 256
Momentum transfer range	Q = 0.0007 -1 Å <sup>-1</sup> $Q_{max}/Q_{min}$ 10-20

Status: Available to users

