


INSTRUMENT

BEAM LINE

9

SPALLATION NEUTRON SOURCE

Fact Sheet



CORELLI – ELASTIC DIFFUSE SCATTERING SPECTROMETER

CORELLI is a statistical chopper spectrometer with energy discrimination. CORELLI is designed and optimized to probe complex disorder in crystalline materials through diffuse scattering of single-crystal samples. The momentum transfer ranges from 0.5 to 12 Å⁻¹, and the energy of incident neutrons ranges from 10 to 200 meV. This



instrument combines the high efficiency of white-beam Laue diffraction with energy discrimination by modulating the beam with a statistical chopper. A cross-correlation method is used to reconstruct the elastic signal from the modulated data. Accurate modeling of the short-range order associated with the diffuse scattering requires measurements over large volumes of three-dimensional reciprocal

space, with sufficient momentum resolution to distinguish the diffuse signal from the strong Bragg peaks.

APPLICATIONS

- Diffuse scattering in material science, including colossal magnetoresistance materials, ferroelectric relaxors, and fast ion conductors
- Diffuse scattering in condensed matter physics, including high-temperature superconductors, geometrically frustrated systems, and quantum critical phenomena
- Diffuse scattering in molecular systems including molecular solids and microporous framework systems

SPECIFICATIONS

Moderator	Ambient H ₂ O decoupled poisoned
Source-to-sample distance	20 m
Sample-to-detector distance	2.5 m
Anular coverage	-23 to +152° horizontally ±28.5° vertically
Energy resolution	1 meV at 10 Å ⁻¹
Momentum resolution	ΔQ/Q~0.005
Incident energy range	10–200 meV
Momentum transfer	0.5–12 Å ⁻¹
Beam size at sample position	~ 1 cm ²

Status: Under construction

FOR MORE INFORMATION, CONTACT

Instrument Scientist: Feng Ye, yefl@ornl.gov, 865.576.0931



May 2012

09-G00161B/gjm