



Port Washington Harbor, WI

Project Features

- ➤ Located on the west shore of Lake Michigan, about 53 miles south of Manitowoc and about 29 miles north of Milwaukee, WI.
- > Deep draft commercial harbor.
- ➤ Depth of 21 feet below LWD in entrance and inner channels and 18 foot depths in inner basins.
- ➤ 100,000 tons of material shipped or received in 2004.
- About 3,000 feet of structures including breakwaters and piers.
- > Over one-half mile of maintained channel.
- ➤ Major stakeholders include U.S. Coast Guard, Lake Carriers Association,

Project Needs

- Approximately 10,000 to 15,000 cubic yards of material must be dredged from the inner basins on a 10 to 15 year cycle.
- ➤ Navigation structures are primarily maintained by Government floating plant.



➤ Light loading associated with inadequate maintenance dredging, increasing vessel transportation costs.

Transportation Importance

- ➤ Locally significant receiving port on the Great Lakes.
- > Commodities include coal and lignite.

Consequences of Not Maintaining the Project

Significant loss of jobs both locally and regionally.

U.S. Army Corps of Engineers Fiscal Year (FY) 2007 and 2008 Port Washington Harbor, WI Project Needs and President's Budget

Work Package	FY07 Need	FY07 Budget	Δ	FY08 Need	FY08 Budget*
Operations					
CDF					
Maintenance Dredging					
Structural Repairs					
Environmental Acitivities					
TOTALS	0	0		0	

^{*} FY08 President's Budget will not be available until February 2007