

				STA	TE	PROJECT	SHEET NUMBER	
VOTI	Ξ:							
Traffic barrier protection is required for all posts larger than 150 x 200 mm when located within the clear zone or if the post is vulnerable to being struck when placed outside the clear zone.								
H1 thru H4 indicate overall post length. Select post lengths to fit field conditions.								
D is the minimum post embedment depth for average soil conditions. See Wood Post Selection Table below.								
Z is the height from ground line to mid-height of sign at the longest post.								
 For the purpose of post selection X and Y are as follows: Single sign, or back to back signs: X and Y are the overall dimensions of the signs. Multiple sign installations: X and Y are the dimensions of a rectangle enclosing all the signs. 								
Dimensions without units are millimeters.								
M8 lock nut — 8 mm oversized washer								
onmetallic d washer outside dia.) M8 bolt								
				 	8 bolt	thru the pos	st	
TYPICAL MOUNTING FOR SIGNS WITHOUT ANGLES								
WO	OD PO	OST S	ELEC	TION	TAB			
ST		JMBER			~	Notch depth		
ľE n)	1 Pro	2 duct of	3 X-Y-7 (4 (m3)	D (m)	and hole diameter		
100	2.2	4.3	6.6	18.7	0.9	-		
150	5.0	10.8	15.3	20.3	1.2	45 mm		
150	6.6	13.3	19.9	26.6	1.2	45 mm		
200	8.4	23.8	35.8	47.6	1.2	65 mm		
250 250	10.8 16.1	33.0 45.1	49.6 67.5	66.1 90.0	<u>1.5</u> 1.5	-		
300	21.7	64.7	97.0	129.4	1.8	-		
the limit for the largest post, use steel post installation.								
			U.S. DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION WESTERN FEDERAL LANDS HIGHWAY DIVISION					
		METRIC DETAIL						
		PERMANENT SIGN						
			INSTALLATION					
WOOD POSTS								
) SCAL	E	DETAIL APPROVED FOR USE/ DETAIL						
	-	REVISED: 2/1998 3/1999 DRAFT: 10/2009					WM633-7	