



Hanford 300 A IFRC

New Results from the Hanford Integrated Field Research Challenge (IFRC)

John M. Zachara and the IFRC Research Team
Pacific Northwest National Laboratory, Richland, WA

<http://ifchanford.pnl.gov>

Hanford IFRC Meeting
February 24, 2009





Pacific Northwest
NATIONAL LABORATORY

PNNL-SA-64863

Presentation Focus and Content

- ▶ A little background
- ▶ Completed saturated zone experimental site
- ▶ Initial results of field and laboratory characterization
- ▶ Evolving experimental plans and rationale
- ▶ Challenges and opportunities


Hanford's 300 A Uranium Plume



2008/DCL/300FF5 U/002 (04/01)



- ▶ Large volumes of process waste from fuel fabrication resulted in extensive U groundwater contamination
- ▶ Highly contaminated waste pond sediments excavated, Cu- and U-containing vadose zone sediments remain
- ▶ MNA selected as an interim remedy for groundwater contamination in 1996
- ▶ Persistent U groundwater contamination remains above regulatory limits
- ▶ Complex seasonal concentration trends associated with river stage changes and WT rise and fall
- ▶ Investigations ongoing to understand hydrogeochemical behavior of VZ-SZ system and select appropriate remedy

Hypothesized Vadose Zone Release Model



Hanford Integrated Field Research Challenge Science Theme

Multiscale mass transfer processes influencing sorbed contaminant migration




- ▶ Mass transfer is controlled by diffusion, and is influenced by the path length, tortuosity, thickness, and surface charge of immobile, water-filled pore space.
- ▶ It controls contaminant release at the particle scale from intragrain domains to porewater, and at the aquifer scale from fine-textured to coarse-textured aquifer facies.
- ▶ Kinetic behavior results, as well as long-term contaminant resupply after remedial activities.

Associated Practical Issues

1. Accurate projection of dissipation times for groundwater plumes
2. Optimal delivery of remediation reactants
3. Effectiveness of remediation




South Process Pond – Pit #2 – From ERSP




Significant ERSP research on 300 A sediments (~10 papers)

- molecular speciation of adsorbed and precipitated species
- adsorption/desorption and dissolution kinetics
- bulk, surface, and microscopic mineralogy
- mass transfer behavior and models
- remaining mysteries

Mass Transfer: Importance, Modeling, and Scaling




Hanford IFRC Site Concept




- ▶ Wells spaced 10 m to allow cross-hole geophysical interrogation for inter-well properties determination.
- ▶ Injection experiments (10^5 gallon) in the 6 m saturated zone under different seasonal gradients using site groundwaters.
- ▶ Passive experiments will exploit natural gradients and WT fluctuations
- ▶ Continual water level monitoring at 12 locations to quantify boundary conditions.

IFRC Site and SPP2



- ▶ 60 m site with 37 wells (extensive borehole documentation and logging, reports on web)
- ▶ Rigorous geophysical and hydrologic field site characterization and measurements (described by “Plan”)
- ▶ Carefully selected laboratory measurements on many sediments retrieved from wells (geostatistical relationships)
- ▶ Focus on upscaling of microscopic reaction information (from ERSP) and identifying physical/geologic features causing kinetic behavior at m+ scales
- ▶ Attempt to characterize and model multi-process effects at multiple scales.

Example Compilation Borehole Summary Log for Well 399-2-9 (C6186)



Hydrologic/Groundwater Characterization

Described in Plan on website

▶ Hydrologic


- Electromagnetic borehole flowmeter (EBF) surveys (vertically, temporally)
- Constant rate injection experiments (enable vertical K profiles)
- Solute tracer injection experiments
- ΔT injection experiments (March 2009)

▶ Geochemical



- Quarterly all well survey
- Monthly 12 well survey (9 ML + 3 FS)
- Seasonal select MLS deployment (early March 2009)
- Comprehensive passive experiment (April-June 2009)
- Downhole monitoring of T and EC

Electromagnetic Borehole Flowmeter (EBF) Testing

- ▶ Both ambient and dynamic tests conducted
- ▶ Net flow corrected to account for effects of ambient flow
- ▶ Incremental contribution of each depth interval to flow used to estimate relative K




2007/DCL/NABIR/002 (05/17)




Selected Examples of EBF Profiles

- ▶ General (although non-uniform) EBF profile structure indicating lower permeability materials over the middle portion of the aquifer
- ▶ Consistent with tracer arrival response in middle zone of northern multi-level well cluster




⊗ - Locations where test conditions resulted in non-representative EBF profiles


Hydraulic Conductivity from Short-Duration Constant Rate Injection Testing



Field Electrode Measurements and Aqueous Sampling





Results of November 2008 Tracer Test for Hydrologic Characterization






Tracer Response in Northern Multi-Level Well Cluster

- ▶ Tracer arrival and elution significantly lagged in middle zone
- ▶ Consistent with EBF results
- ▶ Earliest arrival in lower zone - closely followed by upper zone



- ▶ Upper zone well exhibits stronger tracer response to river stage variability than lower zone – more connected
- ▶ This difference in connectivity likely explains the strong ambient flow observed during EBF testing




Well Cluster 1



Sulfate in IFRC Well Waters




Uranium Isotopes in 300 A Groundwaters



Sediment Characterization Strategy

Based on field-scale surface complexation RTM



and 3-D properties/parameter distributions

- ▶ Transport properties
 K_{sat} , porosity, density


- ▶ Reaction parameters
 $K, k, \text{SOH}, \text{CO}_3^{2-}$

- ▶ U distribution
 $U(\text{VI})_{\text{ads}}, U(\text{VI})_{\text{aq}}$


Sediment Characterization Approach

- ▶ Interpolation between boreholes
 - Down-hole geophysical measurements (uncharacterized boreholes)
 - Porosity, density, EC, MS, K-U-T
 - Cross-hole measurements (intervening space)
 - Radar, ERT
 - Correlations between geophysical measurements and physical/chemical properties (SFA)
- ▶ Direct measurements on select cores/samples
 - Physical
 - PSD [200], SA [50]
 - Chemical
 - U_T , U_{ads} , U_{des} , K_d -SGW1&2, $AAO_{Fe(III)}$ [200]
 - K, k [select, establish correlations with properties]

Downhole Electrical Conductivity Measurements



Schematic of ERT / Monitoring Wells




- ▶ Electrodes spaced at 60 cm (2 ft)
- ▶ Electrode length approx 10 cm (4 in)
- ▶ Electrode material 316 stainless steel
- ▶ Single wire connections to electrodes
- ▶ Wires run on outside of PVC well pipe
- ▶ Thermistors placed between electrodes
- ▶ Wire wrap PVC from 106-98 m elevation
- ▶ Tube capped at bottom
- ▶ Well head ~0.6 m (2 ft) above ground
- ▶ Central connector/DAQ box at top of wellhead
- ▶ Heat dissipation unit (HDU), time- domain reflectometry (TDR) probe and porous cup solution sampler at multiple depths on 5 wells around infiltration site


Calibrating Electrodes in the IFRC Well Field




IFRC ERT Inversion Results





Relationship Between Total and Bicarbonate Extractable U(VI)




Bicarbonate Extractable U(VI) from Three Boreholes





Forced U(VI) Desorption for Kd Measurement from Well 3-31 Sediments




Lability of Adsorbed U(VI) in IFRC Site



Influence of Desorption Cycle on $<2\text{mm}$ K_d for Core 2-26



Extrapolated Groundwater U(VI) Concentration from First Desorption Event



Ex-situ/In-Situ Reaction Parameters [PNNL SFA]




Intact Column Studies

- ▶ RT experiments at 10'/d, 3 cores from different aquifer depths
 - A-desorption, B-tracer, C-adsorption/desorption SGW-1, D-hydrologic properties


- ▶ Deconstruction
 - psd, SA (< 2 mm), < 2 μ m mineralogy
 - Low [U(VI)] isotherm (< 2 mm)
 - Mass transfer parameters by flow cell (< 2 mm)
 - AAO Fe(III) (< 2 mm)

- ▶ Upscaled modeling
 - SC-DR-DP (PFBA)



U(VI) Desorption and Adsorption/Desorption from Intact IFRC Core 3-26/35.8-36.8'



Particle Size of Coatings on Gravel (32 mm)



Tracer Behavior and U(VI) Desorption During Phase B




Field Experimental Plan is in Progress

New characterization data will allow completion



Expected Experimental Campaigns

- ▶ Multi-tracer, cold water injection (March, 2009)
- ▶ Passive during rising and falling water table (May - July, 2009)
- ▶ Desorption U(VI) injection (September, 2009)
- ▶ Adsorption U(VI) injection (March, 2010)
- ▶ Passive during rising and falling water table (May - July, 2010)
- ▶ In-situ microbiologic activity (August, 2010 – February 2011)
- ▶ Isotopic exchange (March, 2011)


Defining Heterogeneities in Hydrologic Properties and Flow



Concept for Passive Groundwater Experiments



Uranium Injection Plumes Simulated with Two Models



Important Progress

- ▶ State of the art well field and monitoring system installed and tested
- ▶ Extensive hydrologic testing completed that has modified the site hydrologic model
- ▶ Significant progress made toward the site 3-D geostatistical model ("Characterization Plan")
 - Laboratory chemical, physical, and electrical measurements
 - Surface, downhole and cross-hole geophysical measurements
 - Inversion modeling and geostatistical analysis
- ▶ Modeling Plan nearly completed
 - Data collection sequences
 - Sequential modeling goals
 - Roles and responsibilities
- ▶ High quality samples obtained for microbiologic characterization that have shown surprising results
- ▶ Established collaborative strategy and experiments with PNNL SFA
- ▶ Ready for the experimental program to begin in March

Challenges and Opportunities

► Challenges

- Experimental planning for maximum scientific and programmatic impact given system hydrologic complexities
- Vertical resolution of solute breakthrough in the IFRC well-field
- Maximizing the contribution of the modeling team
- Meaningful collaborations with EM

► Opportunities

- Original mass transfer hypothesis holds with qualification
- Site is a "gold-mine" for coupled process, "upscaling", and systems-level research
- Site infrastructure will support many experiment types, has sophisticated attributes
- Unique field laboratory for study of contaminant migration and microbiology of the groundwater-river interaction zone


Linkage to Site Remediation and Closure

- ▶ Operational model for infusion of DOE fundamental science into the closure mission
 - In-ground contaminant status and behavior
 - Understanding of processes and complexities of specific sites
 - Evaluation and testing of new models and measurement techniques
 - Knowledge to reduce uncertainty
 - Websites updated every 6 mo. to include new findings and publications


- ▶ 300 A site is representative of Hanford River Corridor locations
 - Applicability of conceptual and numeric models to other locations

- ▶ Scientific context for evaluation of remediation strategies and concepts
 - Critical characterization needs
 - MNA versus active approaches
 - Expectations for long-term remediation efficiency


IFRC Well-Field Cross Section




Hourly, Daily Average, and Monthly Average River Stage at the 300 Area in 1996



IFRC Modeling and Parameterization Workflow



Geo-/Petro- Physics Workflow



Distribution Coefficients for Well Sediments

