INFORMATION BULLETIN



FEDERAL Communications Commission

TV BROADCAST STATION SELF - INSPECTION CHECKLIST

Bulletin EB-18TV June 2008 Edition Updated as of September 1, 2009 This Page Intentionally Left Blank

TV SELF-INSPECTION CHECKLIST

TABLE OF CONTENTS

<u>Introduction</u>		I
Where to get Assistance, Forms & Other	<u>Information</u>	ii
Section I: Administrative and Non-Techn	nical	
A. Authorizations		1
B. Station Logs/Records		1
C. Chief Operators		2
D. Station Identification		2
E. Telephone Access to Station		3
F. Public Inspection File		3
G. Main Studio Presence		7
H. Main Studio Location		7
Section II: Antenna Structures		
A. Antenna Registration		9
B. Antenna Specifics		10
C. Tower Light Observations		10
D. Painting/Lighting		11
E. FAA Notifications		11
F. Station Logs		12
Section III: Emergency Alert System (EAS		
A. Participating vs. Non-Participating		13
B. Handbook		13
C. EAS Decoder/Monitor		14
D. EAS Encoder/Generator		15
E. EAS Tests		15
F. Station Logs		16
Section IV: Technical		
A. Power		17
B. Direct Power Measurement		17
C. Frequency		18
D. Modulation		18
E. Transmitter Metering & Control		18
F. Spurious and Harmonic Emissions	<u>s</u>	19
G. Monitoring Procedures		19
H. Calibration		20

Section V: Attended VS Unatte	ended Operation		
A. Attended vs Unattende	d Operation	 	21
B. Notification		 	21
Section VI: Local Marketing Ag	reements (LMA)		
A. LMA Status		 	23
B. Filing of Contracts		 	23
C. Control of Station		 	24
D. Main Studio		 	24
Section VII: Abbreviations		 	25
Section VIII: Glossary of Broad	cast Terms	 	27

INTRODUCTION


Welcome to the TV Broadcast Station Self-Inspection Checklist.


The Enforcement Bureau (EB) of the FCC is committed to improving licensee compliance with the broadcast regulations. We do this through a combination of educational and enforcement efforts. The enforcement effort usually involves an on-scene station inspection conducted by FCC personnel. Most on-scene inspections are conducted without prior notification to the station licensee.


This checklist has been developed to assist broadcast station management in conducting a self-inspection of their station. It provides an opportunity for the broadcaster to review and correct any deficiencies associated with the operation of a station without an actual on-scene visit by the Commission.

While not all broadcast regulations are covered by this checklist, you will be able to assess your compliance with the most frequently violated broadcast regulations. Each question contains a reference to the relevant rule section(s) to facilitate your review. These references pertain to Title 47 Code of Federal Regulations (C.F.R.) Parts 11, 17 and 73.

The following boxes are provided throughout the checklist to aid the broadcaster in determining the stations compliance:







All of the above responses are not applicable to every question. Only appropriate responses will be provided for each question.

You will note that the above responses do not include a "NO" answer. Any question in which a "NO" answer is applicable would be a violative condition requiring corrective action. Stations encountering such situations should take immediate steps to correct the problem.

WHERE TO GET ASSISTANCE, FORMS and OTHER INFORMATION

On June 3, 1996, the FCC established a national call center in Gettysburg, Pennsylvania. This call center is operated by the FCC Consumer and Governmental Affairs Bureau (CGB). This facility is capable of providing services for the hearing impaired and the center is staffed full-time with bi-lingual (English and Spanish) Specialists. The toll free telephone number for this call center is 1-888-CALLFCC (1-888-225-5322).

If you have any questions about this self inspection checklist or the applicability of any regulation to your operation, you may contact the FCC Call Center. **DO NOT MAIL THIS CHECKLIST TO THE FCC FOR OUR REVIEW!**

Information and materials pertaining to the Emergency Alert System (EAS) may be found through the FCC, Public Safety and Homeland Security Bureau web page at http://www.fcc.gov/pshs/services/eas/index.html.

Requests for any <u>FCC form</u> or bulletin should be directed to the Commission's forms distribution contractor at 1-800-418-FORM (1-800-418-3676). This is a voice mail answering system. You should have the number of the form available when you call.

Some forms, bulletins and other documents, including a copy of this checklist, are also available through the Internet by visiting the FCC Homepage at "http://www.fcc.gov". Please check this Homepage for the latest updates to the checklist. Some forms may also be filed through the use of the Internet.

The FCC, Media Bureau, Video Division maintains a webpage at "http://www.fcc.gov/mb/video". This page provides information relating to television broadcast. Information on EEO requirements for broadcasters are maintained at http://www.fcc.gov/mb/policy/eeo or by calling EEO staff at (202)418-1450.

The FCC maintains a fax on demand service at (202)418-2830. Through this service you may obtain information on the following: Daily Digest News Releases Speeches Fact Sheets Current List of Events Public Notices Auctions

The government printing office (http://www.gpo.gov) maintains current copies of the Code of Federal Regulations (C.F.R.) in both printed and electronic form. A beta online version of Title 47 C.F.R. Parts 11, 17 and 73 can be found at:

Part 11: http://ecfr.gpoaccess.gov/cgi/t/text/text-idx?c=ecfr&sid=dfb774ab024c5b210621bfdd118f08f1&tpl=/ecfrbrowse/Title47/47cfr17_main_02.tpl
Part 73: http://ecfr.gpoaccess.gov/cgi/t/text/text-idx?c=ecfr&sid=dfb774ab024c5b210621bfdd118f08f1&tpl=/ecfrbrowse/Title47/47cfr73_main_02.tpl

SECTION I: ADMINISTRATIVE AND NON-TECHNICAL

Α.	AUTHORIZATIONS: The station license, construction permit, renewal certificate, auxiliary transmitte
	authorization, special temporary authorization (STA), and/or any other instrument of authorization shall be
	readily available and easily accessible at the station's principal control point. Renewal certificates should be
	associated with the corresponding station authorization. [See 73.1230(a), 73.1635, 73.1670, 73.3533, 73.3536
	73.3537 and 73.3539]

1. AUTHORIZATIONS: Are <u>current</u> station authorizations posted or readily available at the principal control point for the station?

B. STATION LOGS/RECORDS:

STATION LOGS include entries pertaining to equipment status, equipment calibration, the Emergency Alert System (EAS) and, when applicable, the recording of tower light outages. STATION RECORDS include, but are not limited to chief operator designations and equipment performance measurements.


The station logs and records are to be kept in an orderly and legible manner, in suitable form and with sufficient detail. Station logs and records are to be retained for a period of two years, unless specified otherwise, and they shall be made available for inspection or duplication at the request of the FCC or its representatives. Required logs and records are to be readily available for inspection. [See <u>73.1225</u>, <u>73.1226</u>, <u>73.1590</u>, <u>73.1800</u>, <u>73.1820</u> and <u>73.1840</u>]

- 2. Cogs/Records: Are required station logs retained for a period of 2 years? [See 73.1840(a)]
- AVAILABILITY: Are station logs/records readily available for inspection and/or duplication at the request of the FCC or its representatives?

 [See 73.1225] and 73.1226]
- 4. Y P SUIPMENT PERFORMANCE MEASUREMENTS: Are the latest Equipment Performance Measurements maintained and readily available? [See 73.1590(a)]
- 5. CLARITY: Are the station logs legible and in such detail that they clearly document any problems that may have occurred at the station? [See <u>73.1800(b)</u>]

C. CHIEF OPERATORS: Each station must designate a chief operator. The designation is to be in writing with a copy posted with the station authorization. Chief operators for TV stations must be station employees working sufficient number of hours to keep the station compliant with FCC Rules. The chief operator is to review the station logs at least once each week to determine if required entries are being made correctly and to <u>SIGN AND DATE</u> the log upon completion of the review. The chief operator is also responsible for inspection and calibration of the transmission system, monitors, metering and control systems in addition to any equipment performance measurements or other tests as specified in the rules or terms of station authorization. [See 73.1870]

NOTE: An electronic signature is acceptable in lieu of a written signature for those making, or reviewing, entries in station logs and records which are maintained on digital media.



- D. STATION IDENTIFICATION: Station identification shall be made at the beginning and ending of each period of operation, and hourly, as close to the hour as feasible, at a natural break in program offerings. The identification shall consist of the station's call letters immediately followed by the community of license. Any reference to additional communities must be made after the community of license. The name of the licensee, or the station frequency, channel number, or both, may be inserted between the call letters and community of license. No other insertion is permissible. ID announcements may be made either visually or aurally. [See 73.1201]
 - 10. **Y P** IDENTIFICATION: Is the station identification made in accordance with <u>73.1201</u>?


E.	TELEPHONE ACCESS TO STATION: Each station must maintain a local or toll free telephone number within
	its community of license. Stations operating from studio locations outside of the community of license must
	make sure residents in the community have access to this number. [See 73.1125]

TELEPHONE ACCESS: Does the station maintain a local or toll-free telephone number in its community of license? [See <u>73.1125(e)</u>]

F. PUBLIC INSPECTION FILE: All stations are to maintain a public inspection file at the main studio of the station. The file shall be available for public inspection at any time during regular business hours. Regular business hours are generally any eight hour period between the hours of 8 a.m. and 6 p.m., Monday through Friday. The licensee may require members of the public to provide personal information as a prerequisite to granting access to the public file. However, such personal information is limited to the name and address of the person(s) seeking access to the file. The licensee may not require identification of the person's organizations or affiliations they may be associated with.

All or part of the file may be maintained in a computer database as long as the computer terminal is made available to members of the public who wish to review it. If a station is concerned about documents being stolen or destroyed, then copies of required documents may be placed into the file in lieu of the originals.

The contents of the file are to be made available within a reasonable time for printing or machine reproduction upon request made in person, provided the requesting party pays the reasonable cost of reproduction. The licensee may require guarantee of payment in advance for any such requests. The licensee shall also mail photocopies of documents from the file upon request made in person, by telephone, by mail or by e-mail, with all postage paid by the station. [See <u>73.3526</u> for commercial station public file rules and <u>73.3527</u> for non-commercial station public file rules]



REPRODUCTION: Can all of the materials contained in the public file be reproduced and provided upon request made either in person, by phone or by mail? [See 73.3526(c) or 73.3527(c)]

AUTHORIZATION: Is a copy of the current FCC authorization to construct or operate the station being maintained in the file?

[See 73.3526(e)(1) or 73.3527(e)(1)]

19.	Y P N/A	RETENTION OF CONTOUR MAPS: Are the station's contour maps retained for as long as they reflect current, accurate information regarding the station? [See <u>73.3526(e)(4)</u> or <u>73.3527(e)(3)</u>]
20.	Y P N/A	OWNERSHIP REPORTS: For station licensees who are not sole proprietorships, or partnerships comprised entirely of natural persons, does the public file contain copies of ownership reports and supplemental ownership reports filed with the Commission, including all exhibits, letters, and other documents associated with these filings? [See 73.3526(e)(5), 73.3527(e)(4) and 73.3615]
21.	Y P N/A	OWNERSHIP INFORMATION: For non-commercial stations, does the ownership information on file with the Commission reflect the current ownership (board members, officers, etc.) of this station? [See $\underline{73.3527(e)(4)}$ and $\underline{73.3615(d,e\&f)}$]
22.	Y P N/A	CONTRACTS: For all stations, does the public file contain either a copy of the contracts listed in the latest ownership reports or an up to date list of such contracts for as long as they are in effect? [See 73.3526(e)(5), 73.3527(e)(4), 73.3613, 73.3615(a)(4)(i) and 73.3615(d)(3)]
23.	YP	RETENTION OF OWNERSHIP REPORTS: Are the ownership reports retained until a new, complete ownership report is filed with the FCC with a copy placed in the public inspection file? [See <u>73.3526(e)(5)</u> or <u>73.3527(e)(4)</u>]
24.	Y P N/A	POLITICAL: Does the licensee have a complete record of all requests for broadcast time made by or on behalf of candidates for public office, together with an appropriate notation showing the disposition made by the licensee of such requests, and the charges made, if any, if the request was granted? [See 73.1943 and either 73.3526(e)(6) or 73.3527(e)(5)]

APPLICATIONS: Does the public file contain copies of all applications, exhibits, letters, initial and final decisions in hearing cases, and other documents pertaining to the station which were filed with the Commission and which are open for public inspection at the

FCC? This includes applications granted pursuant to a waiver.

for the term of the agreement? [See 73.3526(e)(3)]

Note: Applications retained in file until final action taken on the application.


CITIZEN AGREEMENTS: For commercial stations, are copies of any written


agreements with local viewers or listeners (citizen agreements) maintained in the file

CONTOUR MAPS: Is a copy of any service contour map, submitted with any application tendered for filing with the FCC, together with any other information in the application showing service contours and/or main studio and transmitter location in the file? [See

[See 73.3526(e)(2) or 73.3527(e)(2)]

73.3526(e)(4) or 73.3527(e)(3)]





G.

H.

N/A

	YP	N/A	copy of every agreement involving the joint sale of advertising time involving this station? Confidential or proprietary information may be removed.
			[See <u>73.3526(e)(16)</u> and <u>73.3613(d)(2)</u>]
51.	YP	N/A	RETENTION OF JOINT SALES AGREEMENTS: While there is currently no rule indicating a specific retention period, these agreements should be maintained as long as the agreement is in force.
52.	YP	N/A	LOCAL ANNOUNCEMENTS: Was a statement certifying compliance with the local public notice filing announcements placed into the file within 7 days of the last day of broadcast of such announcements? [See 73.3526(e)(13), 73.3527(e)(10) and 73.3580(h)]
53.	YP	N/A	RETENTION OF LOCAL ANNOUNCEMENTS: Was the statement certifying compliance with 73.3580(h) retained until final action is taken on the application to which it refers to? [See <u>73.3526(e)(13)</u> or <u>73.3527(e)(10)</u>]
54.	YP	N/A	MUST CARRY ELECTION: For commercial stations, are the records pertaining to the station's election with respect to either must-carry or retransmission consent available in the public inspection file? [See $\underline{73.3526(e)(15)}$ and $\underline{76.64}$]
55.	YP	N/A	RETENTION OF MUST CARRY: Are the records retained for the three year election period to which the statement applies? [See $\frac{73.3526(e)(15)}{2}$ and $\frac{76.64}{2}$]
the ma and re the sta hour p	ain studio d eceive acce ation availa period betw	uring no ss to the ble for ir een 8:00	CE: Each station must maintain a full time managerial and non-managerial presence at rmal business hours so members of the public can reach responsible station personnel public inspection file. In addition, a main studio presence allows the licensee to make aspection at any time during normal business hours. Normal hours are typically an 8 of a.m. and 6:00 p.m. local time Monday through Friday. This requirement is separate smitter operation rules. [See 73.1125] and 73.1225(a)]
56.	YP		MAIN STUDIO PRESENCE: Does the licensee maintain a human presence of at least 8 hours per week day at the station's main studio?
			[See <u>73.1125</u> and <u>73.1225(a)</u>]
	Full time in ne employe		ntext is the entire time a studio is open to the public, not the full or part time status of
signal	strength co	ontour of	ON: The main studio for each station shall be located within the principal community any broadcast station licensed to that same community or 25 miles from the reference of its community of license, whichever the licensee chooses. [See <u>73.1125</u>]
57.	YP		MAIN STUDIO LOCATION: Is the main studio for this station located within the principal community contour of any station or within 25 miles of the reference center? [See 73.1125]

JOINT SALES AGREEMENTS: For commercial stations, does the public file contain a

THIS PAGE INTENTIONALLY LEFT BLANK


SECTION II: ANTENNA STRUCTURES

A. ANTENNA REGISTRATION: Most antenna structures that are higher than 60.96 meters (200 feet) above ground level or that may interfere with the flight path of a nearby airport must be studied by the Federal Aviation Administration (FAA) and registered with the FCC. <u>Owners</u> are required to register their non-exempt tower structures with the FCC. All proposed and altered antenna structures must be registered prior to construction or alteration. For licensees this means that the tower must be registered before a new construction permit or license modification involving the tower or antenna is granted.


Licensees should be familiar with the painting and lighting specifications shown on their station authorization. In the event that the structure owner is unable to maintain the prescribed painting and lighting, e.g. in cases including but not limited to abandonment, negligence, or bankruptcy, the FCC would require that each tenant licensee on the structure undertake efforts to maintain painting and/or lighting. Additionally, if the licensee has reason to believe that the structure is not in compliance or that the owner is not carrying out its responsibility to maintain the structure, the licensee must immediately notify the owner, notify the site management company (if applicable), notify the FCC, and make a diligent effort to ensure that the antenna structure is brought into compliance.


Once a tower is registered, then the registration number is to be displayed in a conspicuous place so that it is readily visible near the base of the antenna structure. When the tower is located where the number cannot be seen without access to the property on which it is located, then the number should also be placed on the gate or fence leading to the tower where an outside observer can see it. Materials used to display the registration number must be weather-resistant and of sufficient size to be easily seen.


An informational FACT SHEET, PR5000-15, "ANTENNA STRUCTURE REGISTRATION", and the Antenna Structure Registration Form (FCC Form 854), may be obtained by contacting the FCC's Forms Distribution Center at (800)418-3676. This document will provide information on how to register a tower. Users may also visit the FCC's Internet Homepage at http://wireless.fcc.gov/antenna/ for up to date information on filing procedures, electronic filing and database access.




Posting of Number: Has the registration number been posted in an easily viewed location at the tower site? [See FACT SHEET - PR5000-15]










- C. TOWER LIGHT OBSERVATIONS: The lighting on tower structures is to be observed at least once every 24 hours either visually or by observing an automatic indicating device; or alternatively the licensee/tower owner may provide and maintain an automatic alarm system to constantly monitor the lighting on a structure. All automatic or mechanical control devices, indicators, and alarm systems are required to be inspected at intervals NOT TO EXCEED 3 months. [See 17.47]
 - OBSERVATIONS: Is the lighting on the tower(s) observed at least once every 24 hours either visually or by observing an automatic indicating device; or alternatively has the licensee/tower owner provided and maintained an automatic alarm system? [See 17.47]
 - 64. MAINTENANCE CHECKS: Have all automatic and/or mechanical control devices, indicators, and alarm systems associated with the antenna structure lighting been inspected within the last 3 months? [See 17.47]

D. PAINTING/LIGHTING: The station authorization and/or tower registration specifies the painting and lighting requirements for your operation. This is shown as a set of numbers or letters which correspond to paragraphs found on FCC Form 715 (Numbers - For towers with beacons and side lights) or 715A (Letters - For towers with strobed lighting), or the most current <u>FAA Advisory Circular (currently AC 70/7460-1K) on Obstruction Marking and Lighting</u>. If no painting or lighting is required, then the authorization will specify "NONE" or "NONE REQUIRED". Tower registration is only necessary when painting and/or lighting is required.

The licensee must make certain that the number and placement of paint bands and lighting match exactly with that shown on the station authorization and/or tower registration. The licensee/tower owner should also be aware of the requirement to clean or repaint tower structures as often as necessary to maintain good visibility to aircraft. [See Part 17] and TSA]

NOTE: One of the most common problems associated with tower painting is the feedlines that are on the outside legs of a tower. In many cases, the tower is painted correctly, but the solid black colored feedlines defeat the purpose of the painting by covering up the outside legs of the tower. The licensee/tower owner should make certain that the feedlines are also painted in such instances. This does not apply in cases where the tower is authorized for strobe lighting.



- PAINT BANDS: Does the structure have the correct number of bands and are the top and bottom bands painted orange? [See Part 17]
- 67. LIGHTING SPECIFICATIONS: Does the lighting on the tower structure match exactly with the specifications in the station authorization? [See TSA]
- E. FAA NOTIFICATIONS: The tower owner/licensee is to notify the Federal Aviation Administration (FAA) at (Phone: 877-487-6867) within 30 minutes of the observation of an improper functioning or extinguished top steady burning light or ANY flashing obstruction light regardless of its position on the structure. Such improper functioning beacons include non-lighted beacons as well as those that are lighted, but non-flashing. Notification is to also be made immediately to the FAA once the beacon or steady burning top light is returned to service. Notification is not required when side light outages are observed. Tower owners/licensees should insure that the telephone number for the FAA is readily available and known to all personnel who would be responsible for notifying the FAA of such outages. [See 17.48]
 - FAA NOTIFICATION: Are the tower owner/licensee and all station operators aware of the requirement to notify the FAA within 30 minutes of the observation of an outage AND to notify the FAA again once the outage is corrected? [See 17.48]

- **F. STATION LOGS:** For all stations operating from a tower owned by the licensee and which have authorizations that specify tower lighting, the licensee/tower owner is to make entries in the station log concerning <u>ANY</u> observed or otherwise known extinguishment or improper functioning of <u>ANY</u> tower light regardless of its position on the tower. [See <u>17.49</u>, <u>73.1213</u> and <u>73.1820(a)(1)(i)</u>] This log must contain the following:
 - a. The nature of such extinguishment or improper functioning.
 - b. The date and time the extinguishment or improper operation was observed or otherwise noted.
 - c. Date and time of FAA notification, required for outages of any flashing light.
 - d. The date, time and nature of adjustments, repairs or replacements made. This would include any work conducted as part of a system inspection or preventive maintenance program.
 - 69. STATION LOGS: Does the licensee/tower owner maintain a station log containing entries concerning ANY observed or otherwise known extinguishment or improper functioning of ANY tower light? [See 17.49, 73.1213 and 73.1820(a)(1)(i)]

NOTE 1: Licensees should also log the date and time of quarterly inspections of lighting systems as described in §17.47(b).


NOTE 2: Any extinguishment or improper functioning of a required tower light, regardless of its position on the tower, is to be corrected as soon as possible. See §17.49(b) and the terms of the structure registration. A structure is not in compliance with the structure registration if any required light is not functioning properly. However, violations are avoided by prompt and complete logging of the outage and by documenting that the efforts made to correct the condition are being done in a timely manner.


SECTION III: EMERGENCY ALERT SYSTEM (EAS)

On December 9, 1994, the Commission released a Report and Order (10 FCC Rcd 1786) which relocated the Emergency Broadcast System (EBS) rules of Part 73 to the newly established Emergency Alert System (EAS) rules under Part 11. This new rule part reflects the expansion of EAS into other radio services, including cable, along with establishing the move from the analog technology used in EBS to the digital technology used with EAS. On February 26, 2002, the Commission released a report and order (FCC 02-64) authorizing certain changes to the EAS rules, which have been incorporated into this document.

All broadcast stations must have installed operational EAS equipment capable of sending and receiving the digital EAS protocol. If there are any questions pertaining to the new EAS rules then please contact the Commission's EAS office by email at eas@fcc.gov, or by visiting the EAS web site at http://www.fcc.gov/pshs/services/eas/index.html.

- A. PARTICIPATING vs. NON-PARTICIPATING: The difference between a "Participating" and a "Non-Participating" station occurs during national level Emergency Activation Notification (EAN) alerts. Upon receipt of an EAN the participating station will stay on the air providing necessary information while the non-participating station takes its carrier off the air. All stations are considered participating stations, unless they submit a written request to become a non-participating station, AND they receive a written authorization to that effect. Regardless of their participating or non-participating status, ALL stations are to install and maintain EAS equipment and participate in the weekly and monthly tests of the system. Additionally, all stations are required to monitor for state and local EAS activations. Once a state or local level activation has been received, the station management can then decide whether or not to participate further at that level. [See 11.19, 11.54, 11.55 and the EAS plan for your state]
 - PARTICIPATING: Does the management of this station know whether the station is a participating or non-participating EAS station?
- **B. HANDBOOK:** All stations are to maintain an EAS Operating Handbook. The handbook is to be available at <u>ALL</u> EAS control points. Please visit http://www.fcc.gov/pshs/services/eas/handbooks.html for copies of the handbook. [See 11.15]
 - HANDBOOK: Does the station have an EAS Operating Handbook available at <u>EACH</u> normal duty operator position, including all remote control and ATS points utilized during any portion of the broadcast day? [See <u>11.15</u>] http://www.fcc.gov/pshs/services/eas/handbooks.html








NOTE 1: EAS test and activation announcements are to be in the same language as the primary language of the station. [See 11.54(b)(2&7), 11.55(c)(4) and 11.61(a)(1)(v)]

[See 11.52]

NOTE 2: The Commission released a report and order (<u>FCC 02-64</u>) on February 26, 2002, authorizing the use of selective display and logging of state and local EAS activations and the use of additional alert codes. This same order authorized EAS manufacturers and system operators to upgrade existing systems on an optional basis without need for additional equipment authorizations. The order further requires all EAS units produced after August 1, 2003 to have the additional codes and selective display and logging features installed prior to sale. [See 11.33(a)(4) and the R&O]










- LOCATION: For manually operated equipment, is the equipment positioned where responsible broadcast staff can initiate an activation during any portion of the broadcast day? [See 11.51]
- E. EAS TESTS: All TV stations are to conduct required weekly tests (RWT) of the EAS header and End of Message (EOM) codes a minimum of once a week at random days and times, which can include any time of the day or night. In addition, required monthly tests (RMT) are to be conducted once a month as coordinated by the Emergency Communications Committee for each state. The RWT is optional during the week that a monthly (RMT) test is conducted. The RMT conducted in odd numbered months shall occur between 8:30 a.m. local time and local sunset. The RMT conducted in even numbered months shall occur between local sunset and 8:30 a.m. local time. All RMT's shall be retransmitted within 60 minutes of receipt and include the EAS header, 8-25 seconds of two tone attention signal, entire audio message and EOM. [See 11.61]

Note1: Since stations are required to monitor two EAS sources, then each station should receive at least one RWT (or emergency activation) from each of the two sources. An EAS activation for a state or local emergency, as defined in the EAS Handbook, may be substituted for an RWT. The RMT may result in only one test being received during that week.

Note2: If the station is not operating at the time an RMT is scheduled, then the licensee shall log that they were off the air and an RWT should be aired some time during the week after operation of the station resumes.







F. STATION LOGS: All stations are to maintain a station log containing entries pertaining to each test and activation of the Emergency Alert System that is received or initiated by the station. EAS entries must be made in the station log either manually by responsible broadcast station staff, or by an automatic device. Stations may keep EAS data in a special EAS log which can be maintained at any convenient location; however, such log must be considered a part of the official station log. It is also to contain entries which adequately describe the reason why any test activation was not received and any corrective action taken.

[See 11.35(a), 11.51(j), 11.52(e), 11.55(c)(7), 11.61(b) and 73.1820(a)(1)(iii)]

Whenever any EAS equipment becomes defective, the station may operate without the defective equipment, pending its repair or replacement, for a period not in excess of 60 days. The station must make appropriate entries into the station log showing the date and time the equipment was removed and restored to service. [See 11.35(b)]

If the station cannot restore service to the defective equipment within 60 days due to conditions beyond the control of the licensee, then the station must request an extension of this time from the FCC District Director of the area in which the station is located. Such request shall include the steps that were taken to repair or replace the defective equipment, the alternative procedures being used while the defective equipment is out of service and an estimation when the defective equipment will be repaired or replaced. [See 11.35(c)]

STATION LOGS MAINTAINED: Does the licensee maintain a station log containing an entry of each activation (both sent and received) of the Emergency Alert System (EAS)? [See 11.51(j), 11.52(e), 11.55(c)(7), and 73.1820(a)(1)(iii)]

FAILURE TO RECEIVE EAS TEST: Does the station log contain appropriate entries indicating the reasons why required EAS Weekly/Monthly test transmissions were not received? If all tests have been received and logged during the last two year period, then the appropriate response is yes "Y". [See 11.35(a)]

EQUIPMENT OUTAGE: Does the station log contain appropriate entries documenting the date and time any EAS equipment was removed and/or restored to service? If there have been no such outages in the last two years, then the appropriate response is yes "Y". [See 11.35(b)]

NOTE: On February 26, 2002, the Commission released a report and order (<u>FCC 02-64</u>) which allows licensees the option to program their EAS equipment to preselect which EAS messages containing state and local event codes they wish to display and log. Stations will continue to display and log all National level alerts, RWT's, RMT's and any state and local events they elect to receive.

SECTION IV: TECHNICAL REQUIREMENTS

A. POWER: All TV stations are to maintain visual transmitter output power between 80% and 110% of that authorized. The power is to be maintained as near as practicable to the station's authorized power. The aural transmitter output power shall be maintained as necessary to provide an aural carrier ERP up to, but not exceeding, 22 percent of the peak authorized visual ERP. [See <u>73.1560</u> and TSA]

In the event that it becomes technically impossible to operate at authorized power, a station may operate at reduced power for a period of not more than 30 days without specific authority from the FCC. If operation at reduced power will exceed 10 consecutive days, a notification must be sent to the FCC-Media Bureau no later than the 10th day. If normal power is restored prior to the expiration of the 30 day period, the licensee must notify the FCC upon restoration of normal operation.

OPERATING POWER: Is the station operating with power levels within tolerance of the power levels authorized? [See TSA and <u>73.1560</u>]

B. DIRECT POWER MEASUREMENT - CALIBRATION: The operating power of TV stations is normally determined by the direct method. The direct method of power determination for a TV station uses the indications of a calibrated transmission line meter located at the RF output terminals of the transmitter. The meter indicates the peak visual RF output as a percentage of the authorized value. The calibration process includes marking the meter at the upper and lower operating tolerance limits. This meter must be calibrated whenever there is any indication that the calibration is inaccurate or whenever any component of the metering circuit is repaired or replaced.

Other methods may be used to determine operating power if the direct method cannot be used (for example, in the case of a metering failure). The indirect method, appropriate for most VHF transmitters, is determined by applying an appropriate efficiency factor to the input power to the last radio-frequency power amplifier stage of the transmitter. Indications of a peak reading, calibrated transmission line wattmeter have been used for UHF stations. [See <u>73.664</u>]


Licensees must make certain that all duty operators know which method of power determination is being used (and how to calculate the output power if necessary).

POWER CALIBRATION: Has the visual transmitter reflectometer been calibrated and appropriately marked so that the operating power can be readily and accurately determined? [See <u>73.664</u>, <u>73.1560(c)</u>]

baseband components. [See 73.1570, 73.682(c), TSA]

SE	CTION IV: Continue	e d
C.	Certain stations (for exinstrument of authoriza	ual carrier frequency of a TV station may not exceed +/- 1000 Hz from that authorized. cample, those under precise offsets) may have a more stringent tolerance in their tion. The aural carrier frequency may not exceed +/- 1000 Hz from the actual visual .5 MHZ. [See 73.1545] and TSA]
	88. Y P	FREQUENCY: Is the station in compliance with the frequency tolerance specified in 73.1545 and/or TSA?
D.	unless other limits are s defined as +/- 25 kHz of	otal <u>aural</u> modulation may not exceed 100 percent on peaks of frequent reoccurrence, pecified in an authorization. For monophonic transmissions, 100 percent modulation is deviation. For stereophonic operation and/or for operation with multiplex subcarriers, yen in 73 682(c), and are limited to a maximum total deviation of ±/- 75 kHz for all

Visual modulation shall conform to the standards shown in 73.699, Figures 6 and/or 7, and described in 73.682.



- E. TRANSMITTER METERING & CONTROL: All TV stations are to maintain sufficient metering to determine compliance with the visual power limits and modulation (See Note below). In addition, where applicable stations may need monitoring devices to determine compliance with antenna tower lighting. All stations must have personnel which maintain the ability to turn off the transmitter. [See 73.688, 73.691, 73.1350 and 73.1400]
 - CONTROL: Does the equipment at this station allow transmitter control personnel the capability of turning off the transmitter at any time the station is in operation? [See 73.1350(b)(2)]
 - OPERATING PARAMETERS: Does the licensee maintain access to necessary metering as needed to determine compliance with power and modulation? [See <u>73.688</u>, <u>73.691</u>, <u>73.1350(c)(1)</u> and <u>73.1400</u>]

NOTE: Stations are not required to have modulation metering installed, but are required to maintain compliance with the modulation requirements and have access to a means of measuring the modulation.

- **F. SPURIOUS AND HARMONIC EMISSIONS:** Emissions from TV transmitters on frequencies in <u>excess</u> of 3 MHZ above and below the channel edges shall be attenuated at least 60 dB below the visual transmitted power. In certain cases greater attenuation may be required to eliminate interference. Additional emission limits for the spectrum <u>within</u> 3 MHZ, including the lower sideband modulation energy, are found in <u>73.687(a)</u>. [See <u>73.687(a)</u>, <u>73.687(e)</u>]
 - 92. **Y P** EMISSION LIMITS: Does the transmission system comply with the emission limits found in 73.687?
- **G. MONITORING PROCEDURES:** The licensee must establish monitoring procedures and schedules for the station. Monitoring procedures and schedules must enable the licensee to determine compliance with operating power, modulation levels and where applicable with antenna tower lighting. Licensees should be able to provide upon request made by the FCC, the monitoring procedures and schedules they have established for each station. [See 73.691(a) and 73.1350(c)(1)]

In the event that a TV broadcast station is operating with excessive power, or with excessive modulation, then station operation is to be terminated within 3 hours, unless corrective action is taken prior to that time. [See 73.1350(d)]

93. SCHEDULES: Has the licensee established procedures and schedules for monitoring the power and modulation of this station? [See <u>73.691(a)</u> and <u>73.1350(c)</u>]

H. CALIBRATION: The licensee must conduct periodic complete inspections of the transmitting system, all required monitors and automatic logging devices to ensure proper station operation. Monitors and automatic logging devices must be periodically calibrated so as to provide reliable indications of transmitter operating parameters with a known degree of accuracy. The determination as to how frequent the complete inspection and calibrations are to occur is up to the licensee. The licensee should make certain that the date of calibration of each device is entered in the station log along with any other resulting actions associated with the calibration, such as replacement of a meter or other device. The licensee may keep calibration data in a special calibration log, however, such log must be considered a part of the official station log and as such must be made available upon request. [See <u>73.1350(c)</u>, <u>73.1580</u> and <u>73.1820(a)(2)(iii)</u>]

94. CALIBRATION: Has the licensee established procedures and schedules for conducting periodic inspection of the transmitting system and all monitors, and to periodically calibrate these devices? [See <u>73.1350(c)</u> and <u>73.1580</u>]

95. LOGGING: Are the results of such calibration entered into the station log? [See 73.1820(a)(2)(iii)]

SECTION V: ATTENDED VS UNATTENDED OPERATION

A. ATTENDED VS UNATTENDED: Broadcast stations may be operated as either attended or unattended facilities. No prior FCC approval is required to operate a station in the unattended mode. Regardless of which method of station operation is employed, licensees must employ procedures which will ensure compliance with the EAS rules. [See <u>73.1300</u>]

ATTENDED OPERATION: Attended operation consists of ongoing supervision of the transmission facilities by a station employee or other person designated by the licensee either at the transmitter site, a remote control point, or an ATS control point. Such supervision may be by direct observation and control of the transmitting system by a live person at the transmitter site or remote control point, or such supervision can be by automated equipment that is configured to contact a person designated by the licensee. In either case a live person must be on duty at a **FIXED** location during all hours of broadcast operation where they can turn off the transmitter and where they can either monitor the station operating parameters themselves or be contacted by the automated equipment which is monitoring the equipment for them. During attended operation it is expected that the transmitter will be turned off by station personnel within 3 hours of an overpower or overmodulation condition (within 3 minutes for operation with an incorrect mode or directional pattern for that time of day) that can cause interference that cannot be corrected within that period of time. [See <u>73.1350</u> and <u>73.1400(a)</u>]

UNATTENDED OPERATION: Unattended operation consists of using self-monitoring or automatic transmission system (ATS) monitoring equipment to control the transmission system, or alternatively, operation in the absence of constant human supervision with equipment that can operate for prolonged periods of time within assigned tolerances. In the former case, equipment must be configured to automatically take the station off the air within the required 3 hour or 3 minute time periods after an out-of-tolerance condition arises. In the latter case, the licensee is required to make certain that the station is monitored frequently enough to ensure that station operation is corrected or terminated within the designated 3 hour or 3 minute time limits, but constant human supervision is not required. [See 73.1350(c) and 73.1400(b)]

NOTE 1: The unattended transmitter operation rules are separate from the main studio presence requirements. Please do not confuse the two. Stations operating in an unattended transmitter monitoring mode are still required to maintain a human presence at the main studio during normal business hours.

NOTE 2: A Media Bureau Fact Sheet on Unattended Operation may be found on the Internet at http://www.fcc.gov/mb/audio/bickel/noonehome.html.

UNATTENDED: Does the licensee maintain either automated equipment or periodic human monitoring that enables station operation to be corrected or terminated within 3 hours (or 3 minutes) after an out-of-tolerance condition arises?

[See 73.1350(c) and 73.1400(b)]

ATTENDED: Does the licensee maintain a person on duty at a fixed location during all periods that the station is on the air where they can either monitor and control the station themselves or be contacted by automated transmitter monitoring equipment within 3 hours (or 3 minutes) after an out-of-tolerance condition arises?

[See 73.1350(c) and 73.1400(a)]

B. NOTIFICATION: Whenever a transmission system control point is established at a location other than at the main studio or transmitter, then notification of that location must be sent to the FCC, Media Bureau, Washington, D.C. 20554, within 3 days of the initial use of that point. This notification is not required if responsible station personnel can be contacted at the transmitter or studio site during hours of operation. [See 73.1350]

NOTE: Notification of an alternate control point should be a separate notification and not a part of another action or notification you are sending to the Commission. An informal letter is sufficient notification. Please make certain that the letter includes the complete street address of the control point as well as a telephone number. The licensee should also include the hours that this point is normally being used as the control point.

98. NOTIFICATION: Has the licensee notified the Media Bureau in writing of the location of all transmission system control points other than the main studio or transmitter location? [See 73.1350(g)]

99. Y N/A STATION RECORDS: Is a copy of this notification available in the station records?

SECTION VI: LOCAL MARKETING AGREEMENT (LMA)

DEFINITION:

"Time brokerage", also known as "Local Marketing Agreement" or "LMA", is the sale by a licensee of discrete blocks of time to a "broker" that supplies the programming and commercial spot

announcements to fill that time.

LMA STATUS:

100



LMA STATUS: Has this station been engaged in a time brokerage agreement during any portion the current term of the station authorization?


If this station has not been engaged in a time brokerage agreement during any part of the current NOTE: term of the station license or other authorization, then you are not required to answer any further questions contained in this section (Section VI).

В. FILING OF CONTRACTS: All stations involved in an LMA must file a copy of the agreement in the stations public inspection file. In addition, the LMA agreement must be filed with the FCC, Media Bureau, Washington, D.C. 20554, within 30 days of execution if a licensee in the same market is brokering the station and providing more that 15 percent of the time on the brokered station. Confidential or proprietary information may be marked out in the copies placed in the public inspection file and this same information may be marked out in the copies filed with the Commission, however, such information shall be made available for inspection upon request by the FCC. [See 73.3526(e)(14) and 73.3613(d)]


A list of all contracts still in effect, which are required to be filed with the FCC in accordance with 73.3613, are to be filed with the ownership report. This list shall include the date of execution and the expiration of each contract and the list shall document any interest which the licensee may have in any other broadcast station. [See 73.3615(a)(4)]

- FILING: Has the licensee submitted a copy of the LMA to the FCC within 30 days of execution of the agreement?
- LISTS: Has the licensee provided a list of all contracts in effect along with the ownership report?

C. CONTROL OF THE STATION: There is no exact formula by which control of a broadcast station can be determined. However, the FCC has traditionally held that the licensee has ultimate responsibility over essential station matters, such as personnel, programming and finances. Licensees are required to maintain control of their stations regardless of who is brokering the station. [See <u>Title 47 United States Code Chapter 5</u>, <u>Subchapter III</u>, <u>Part I</u>, <u>Section 310(d)</u> and <u>73.3540</u>]



D. MAIN STUDIO: Licensees are required to maintain a meaningful management and staff presence at stations, even when they are engaged in an LMA. The Commission has interpreted this to mean full-time managerial and full-time staff personnel are to be employed and present at the station during normal business hours. [See 73.1125]



VII. ABBREVIATIONS

AM - Amplitude Modulation

ANSI - American National Standards Institute

ATS - Automatic Transmission System

dB - Decibel

EAS - Emergency Alert System

EFM - Educational FM Station

ERP - Effective Radiated Power

F - Transmitter Efficiency Factor

FAA - Federal Aviation Administration

FCC - Federal Communications Commission

FM - Frequency Modulation

KHz - Kilohertz

LMA - Local Marketing Agreement

MHZ - Megahertz

NRSC - National Radio Systems Committee

RF - Radio Frequency

RMT - Required Monthly Test (EAS)

RPU - Remote Pickup Unit

RWT - Required Monthly Test (EAS)

SCA - Subsidiary Communications Authorization

STA - Special Temporary Authority

TPO - Transmitter Power Output

TSA - Terms of the Station Authorization

TV - Television Broadcast

THIS PAGE INTENTIONALLY LEFT BLANK

VIII. GLOSSARY OF BROADCAST TERMS

Amplitude Modulation (AM)	- A type of transmission used in the standard radio broadcast band at 535-1705 kilohertz.
Antenna Proof	- See Proof of Performance Measurements
Bandwidth	- The amount of frequency spectrum a radio signal occupies.
EAS Attention Signal	 An audio signal using the two tone frequencies of 853 and 960 Hz which is transmitted by an EAS station to actuate muted receivers for interstation receipt of emergency cuing announcements and broadcasts.
EAS Operating Handbook	 A booklet which states in summary form the actions to be taken by station personnel upon receipt of emergency action notification, termination, or test messages.
EAS Generator/Encoder	 Equipment capable of generating the EAS attention signal for transmission.
EAS Monitor/Decoder	- Equipment capable of receiving the EAS attention signal and emergency programming transmitted by other EAS stations.
EAS Tests	 Tests conducted weekly/monthly by EAS stations to ensure that their EAS equipment is functioning properly.
Equipment Performance Measurements	 Measurements performed to determine the overall performance characteristics of a broadcast transmission system from point of program origination to sampling of signal as radiated.
Experimental Period	 The time between 12 midnight local time and local sunrise, used by AM broadcast stations for tests, maintenance and experimentation.
Extension Metering	- The meters used to provide indications of a sampled parameter of a broadcast station transmitting system. To be considered an extension meter and not a remote meter, it must be less than 100 feet from the transmitter and installed in the same building as the transmitter.

- Electric field intensity, usually measured in millivolts per Field Strength meter (mV/m) or in decibels above 1 microvolt per meter (dBu). - A method of modulation where the amplitude remains Frequency constant and the frequency of the carrier wave is varied Modulation (FM) according to the modulating wave. The FM broadcast band covers 88-108 Megahertz. Local Marketing - See Time Brokerage Agreement (LMA) NRSC-1 - An audio pre-emphasis standard for AM stations which was implemented June 30, 1990. The pre-emphasis generally is obtained by using special "NRSC-1-equipped" audio processing equipment or a special NRSC-1 audio "filter". NRSC-2 - An emission standard for AM stations aimed at attenuating AM sideband energy beyond 10 kHz of the assigned carrier frequency. This standard was implemented June 30, 1994. **Output Power** - The radio frequency output power of a transmitter's final radio frequency stage as measured at the output terminal while connected to a load. Often referred to as TPO. **Public Inspection** - A publicly accessible file to be maintained by broadcast

Remote Control

File

- Operation by a properly designated person on duty at a control position from which the transmitter is not visible but that position is equipped with suitable controls so that essential functions can be performed.

stations which contains documents pertaining to the

station's licensing, ownership, and operation.

Spurious Emissions

- An emission on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products.

Station Authorization

- Any construction permit, license, special temporary authority, or any other authorization issued by the FCC.

Time Brokerage

- Sale by a licensee of discrete blocks of time to a broker who then supplies the programming to fill that time and sells the commercial spot announcements to support it.

Unattended Operation

- Operation of a station by automatic means without the attention of a qualified operator.