EPA 832-B-95-004

#### COMBINED SEWER OVERFLOWS GUIDANCE FOR SCREENING AND RANKING

Office of Wastewater Management U.S. Environmental Protection Agency 401 M Street, SW Washington, DC 20460

August 1995

#### NOTICE

The statements in this document are intended solely as guidance. This document is not intended, nor can it be relied on, to create any rights enforceable by any party in litigation with the United States. EPA and State officials may decide to follow the guidance provided in this document, or to act at variance with the guidance, based on an analysis of specific site circumstances. This guidance may be revised without public notice to reflect changes in EPA's strategy for implementation of the Clean Water Act and its implementing regulations, or to clarify and update the text.

Mention of trade names or commercial products in this document does not constitute an endorsement or recommendation for use.

## TABLE OF CONTENTS

## Page

1	Introc	luction	
	1.1	Background	
	1.2	History of the CSO Control Policy 1-1	
	1.3	Key Elements of the CSO Control Policy	
	1.4	Guidance to Support Implementation of the CSO Control Policy 1-4	
	1.5	Purpose of Manual and Target Audience	
	1.6	Watershed Approach to Permitting 1-8	
2	The S	Screening Process	
	2.1	Criterion 1	
	2.2	Criterion 2	
3	The Ranking Process		
	3.1	Criterion 1	
	3.2	Criterion 2	
	3.3	Criterion 3	
	3.4	Criterion 4	
	3.5	Criterion 5	
	3.6	Criterion 6	
	3.7	Criterion 7	
APPE	ENDIX	A TESTING OF THE GUIDANCE FOR SCREENING	
		AND RANKING COMBINED SEWER SYSTEMS A-1	
REFE	ERENC	ES	

### LIST OF EXHIBIT AND TABLES

Exhibit 1-1	Roles and Responsibilities
Table A-1.	Sources From Which Needed Information Was Acquired for Screening and Ranking Process Criteria A-2
Table A-2.	Summary of Results Obtained in Applying the Screening and Ranking Process to 13 CSSs

# CHAPTER 1 INTRODUCTION

#### 1.1 Background

Combined sewer systems (CSSs) are wastewater collection systems designed to carry sanitary sewage (consisting of domestic, commercial, and industrial wastewater) and storm water (surface drainage from rainfall or snowmelt) in a single pipe to a treatment facility. CSSs serve about 43 million people in approximately 1,100 communities nationwide. Most of these communities are located in the Northeast and Great Lakes regions. During dry weather, CSSs convey domestic, commercial, and industrial wastewater. In periods of rainfall or snowmelt, total wastewater flows can exceed the capacity of the CSS and/or treatment facilities. When this occurs, the CSS is designed to overflow directly to surface water bodies, such as lakes, rivers, estuaries, or coastal waters. These overflows—called combined sewer overflows (CSOs)—can be a major source of water pollution in communities served by CSSs.

Because CSOs contain untreated domestic, commercial, and industrial wastes, as well as surface runoff, many different types of contaminants can be present. Contaminants may include pathogens, oxygen-demanding pollutants, suspended solids, nutrients, toxics, and floatable matter. Because of these contaminants and the volume of the flows, CSOs can cause a variety of adverse impacts on the physical characteristics of surface water, impair the viability of aquatic habitats, and pose a potential threat to drinking water supplies. CSOs have been shown to be a major contributor to use impairment and aesthetics degradation of many receiving waters and have contributed to shellfish harvesting restrictions, beach closures, and even occasional fish kills.

#### 1.2 History of the CSO Control Policy

Historically, the control of CSOs has proven to be extremely complex. This complexity stems partly from the difficulty in quantifying CSO impacts on receiving water quality and the site-specific variability in the volume, frequency, and characteristics of CSOs. In addition, the financial considerations for communities with CSOs can be significant. The U.S. Environmental