


# Initial Structural Response Measurements and Model Validation for the Sandia 34-Meter VAWT Test Bed

*When printing a copy of any digitized SAND Report, you are required to update the markings to current standards.*

T.D. Ashwill

Prepared by  
Sandia National Laboratories  
Albuquerque, New Mexico 87185 and  
Livermore, California 94550  
for the United States Department of Energy  
under Contract DE-ACO4-76DP00789



Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from  
Office of Scientific and Technical Information  
PO Box 62  
Oak Ridge, TN 37831

Prices available from (615) 576-8401, FTS 626-8401

Available to the public from  
National Technical Information Service  
US Department of Commerce  
5285 Port Royal Rd  
Springfield, VA 22161

NTIS price codes  
Printed copy: A02  
Microfiche copy: A01

Distribution  
Category  
UC-261

SAND88-0633  
Unlimited Release  
Printed February 1990

INITIAL STRUCTURAL RESPONSE MEASUREMENTS AND  
MODEL VALIDATION FOR THE SANDIA 34-METER VAWT TEST BED

Thomas D. Ashwill  
Wind Energy Research Division  
Sandia National Laboratories  
Albuquerque, New Mexico 87185

ABSTRACT

Sandia National Laboratories (SNL) has designed and constructed a 34-meter diameter vertical axis wind turbine (VAWT) Test Bed. The machine will be used to advance research in aerodynamics and structural dynamics, improve fatigue life prediction capabilities, and investigate control algorithms and system concepts. The Test Bed has extensive instrumentation including 70 strain gauges to measure blade and tower response. Immediately after the blades were mounted, blade gravity stresses were measured and a modal test on the stationary rotor performed to determine zero rpm modal frequencies. Assembly and start-up tests are complete, and testing is in the machine characterization phase. Structural resonance surveys will fully characterize the modal frequencies and mode shapes of the rotor, drive train and guy cables. Measured gravity stresses, centrifugal stresses, and modal frequencies are compared to predicted values.

## INTRODUCTION

The 34-m VAWT Test Bed is a variable-speed, research turbine recently designed and constructed by Sandia National Labs. The design of this 500 kW machine incorporates the results of recent VAWT research in aerodynamics and structural dynamics. The turbine will be used to evaluate the advances in these areas and to contribute to developments in other areas such as fatigue life predictive techniques, stochastic wind modeling, variable-speed control algorithms, and system design concepts. The construction of the Test Bed, which is located at the U.S.D.A. Agricultural Research Service facility, 15 miles west of Amarillo, Texas, has been completed, and testing is underway. The blades were mounted on the tower in November, 1987, and the first rotation with blades occurred on February 4, 1988.

Assembly and start-up tests, Phase I of the Test Plan (1), are finalized. Phase I included testing of the power system and controller, verification of the blade strain gauges, testing of the transmission and drive train for vibrations and power losses, set-up and checkout of the brake system and implementation of the data acquisition system. Immediately after the blades were mounted, blade gravity stresses were measured and a modal test performed on the stationary rotor. The modal test measured stationary modal frequencies, which have been compared to predicted frequencies. This allows the predicted fanplot (a plot of modal frequencies versus rotation rate) to be used more accurately as a guide for identifying resonant frequencies during rotation and provides validation of the finite element model used to obtain the predictions.

The turbine testing has progressed into the machine characterization phase - Phase II of the Test Plan. This testing will determine the structural response and aerodynamic performance over the entire operating range. It will include further evaluation of the variable speed controller, understanding its capabilities, and upgrading the control algorithm to reflect knowledge gained during the characterization. Before running for long periods of time at different rotation rates and wind speeds, a resonance survey was conducted by operating for short periods at several rotation rates from 6 through 40 rpm in low, medium, and high wind conditions. This survey characterizes the modal frequencies of the rotor, drive train, and guy cables and allows for the determination of mean stress levels and approximate cyclic stress levels. The evaluation of structural response and turbine performance during these short periods has been followed by operation for longer periods of time to collect enough time series records to create statistically reliable, averaged data (2).

This report describes the major aspects of the measured structural response data obtained up to and including the resonance surveys. (The turbine has rotated from 6 to 40 rpm in winds up to 17 mps). After a general description of the Test Bed structure and the finite element model employed in the structural design, measurements of gravity stresses, centrifugal stresses, and modal frequencies are shown and compared to predicted values.

#### GENERAL DESCRIPTION OF THE TEST BED

The 34-meter Test Bed is rated at 500 kW at 37.5 rpm in a 12.8 mps (28 mph) wind. Figure 1 shows a photograph of the turbine in its completed form. The rotor is 34 meters (110 feet) in diameter and has a height-to-diameter ratio of 1.25. The turbine, which has a total height of 50 meters (165 ft), is supported at the top by three sets of double guy cables each of which is 63.5 mm (2 1/2 in.) in diameter. Each cable pair is tensioned to 826 kN (186,000 lb) and is anchored at ground level to a reinforced concrete tiedown block measuring 4.3x4.3x6.1 m<sup>3</sup> (14x14x20 ft<sup>3</sup>). The tower, or column, is an aluminum cylinder, 3 meters (10 ft) in diameter, constructed of 13 mm (0.5 in.) rolled plates, butt-welded together. Two blade mounts attached to the tower at each end are box-like structures that provide blade attachment surfaces and transition the tower diameter down to bearing shaft diameters.

Each blade is step-tapered with five sections constructed of extruded 6063-T6 aluminum. The top and bottom root sections are straight with a 1.22 meter (48 in.) chord using a NACA 0021 profile. The equatorial section, with a 17.1 meter (675 in.) radius of curvature, has a 0.91 meter (36 in.) chord with an SNLA 0018/50 profile. The intermediate sections, with a 30.0 meter (1180 in.) radius of curvature, have a 1.07 meter (42 in.) chord with an SNLA 0018/50 profile. The SNLA 0018/50 airfoils are part of a series of natural laminar flow airfoils developed at Sandia specifically for use on VAWT's (3). Because all three chords are too large to be fabricated from a single extrusion, each blade section is made of two or three single extrusions bolted together in the spanwise direction. The seven different extrusions that make up the three profiles were successfully extruded to specification during October, 1986 by Consolidated Aluminum, Inc. of Madison, Illinois. The 36-inch and 42-inch chord sections were bent to the proper radius around dies designed specifically for the Test Bed. The extrusion-to-extrusion bolts were retorqued to specification after the blade bending. The extrusion-to-extrusion assembly and blade bending process were performed by Flow Industries of Kent, Washington.




Fig. 1. 34-Meter Test Bed



The blade shape approximates a 37.5 rpm troposkien and contains "kinks", or slope discontinuities, of 6-7 degrees at the blade-to-blade joints as shown in Fig. 2, a schematic of the blade shape geometry. Because of the multi-sectioned, step-tapered characteristics of the Test Bed blades, the normally-used straight/single-curve/straight approximation to a troposkien was not employed. A better approximation resulted by implementing the different radii of curvature along the blade and the slope discontinuities at the blade joints where mass is concentrated. Design calculations (4) show that these implementations reduce the largest mean flatwise stresses approximately fifty percent. This mean stress reduction extends the estimated fatigue life by a factor of two to four.

#### THE FINITE ELEMENT MODEL

The structural design process (5) of the Test Bed incorporated the finite element code NASTRAN to determine the turbine dynamic response. Gravity stresses were also predicted with NASTRAN using a static solution (Rigid Format 24). Predicted modal frequencies were computed with NASTRAN using an eigenvalue solution methodology (FEVD) developed at Sandia (6). In this methodology the stiffness matrix, representing the turbine structure when subjected to centrifugal and gravitational loading, is determined by running a series of geometric nonlinear analyses (Solution 64). The complex eigenvalue analysis (Solution 67) is then used after including rotating coordinate system effects (Coriolis and softening matrices). The mean stresses due to gravitational and centrifugal loading at a particular rpm are output by Solution 64. The complex mode shapes and their respective frequencies of vibration are determined by Solution 67.

A forced response analysis code, called FFEVD (7), determines the vibratory stresses. In FFEVD the stiffness, Coriolis and softening matrices are computed just as in FEVD and input to the complex frequency response analysis (Solution 68) along with the steady (per-rev) wind loads determined by the double streamtube code CARDAA (8). Solution 68 then computes the structural response at each per-rev frequency.

Figure 3 shows the finite element grid for the 34-m Test Bed. It consists of 42 CBEAM elements for each blade, 25 CBEAM elements for the tower, and 2 CBEAM's for each of the four "mini-struts." (The NASTRAN beam element, CBEAM, has properties that include two-dimensional bending, extension, and torsion.) These ministruts model the large blade mounts. The guy cables that restrict motion at the top of the turbine are represented by two orthogonal, horizontal springs, a torsional spring, and a




Fig. 2. Blade Shape Geometry



vertical load acting down through the tower. At the bottom of the rotor, at grid point 1, the restriction of motion by the support stand is represented by two orthogonal, horizontal springs. A torsional spring at grid point 1 represents the torsional stiffness of the drive train. Concentrated masses are added at several grid points along the tower to account for the entire tower mass. The mass of the blade joints is distributed evenly along the relatively short joint elements. As the turbine was constructed, each component was measured and weighed. The concentrated masses and properties of the finite elements were then updated in the model to reflect these "as-built" conditions.




Fig. 3. Finite Element Grid

For blade one, elements 101-108 and 135-142 represent the blade root sections, elements 109-115 and 128-134 the intermediate sections, and elements 116-127 the equatorial section. Blade two is identical in structure to blade one. For comparisons with test results, an additional boundary condition was added to the model at grid point 2 to represent the brakes in the engaged condition. This condition was modelled as two orthogonal, horizontal springs and a torsional spring (torsion about the vertical axis) equal to the appropriate stiffnesses of the support stand.

#### GRAVITY STRESSES

The Test Bed has been instrumented with 70 strain gauges that measure axial, lead-lag, and flatwise response in the blades and torque and bending in the tower (9). Brake strain gauges and damage gauges that measure crack growth of a pre-cracked aluminum coupon also have been installed. When the blades were first instrumented, the flatwise gauges were validated by hanging known weights from each blade section, recording the strains and comparing them to calculations. The entire set of gauges functioned correctly, and the measured strains agreed with predictions to within 2 percent. Following the gauge validation tests, the blade sections were transported to the turbine site and bolted together while at the same time pulling instrumentation cabling through two blade cavities. The blade cavities containing the cabling were filled with structural foam to prevent cable movement. Before the blades were mounted, the gauges were rechecked, recalibrated and rezeroed. Immediately after the blades were mounted, the gauges were monitored to measure gravity strains.

Figure 4 compares the measured flatwise gravity stresses to the predictions. Stresses along the blade from the top to the bottom are plotted left to right on the x-axis. Positive stress corresponds to tension on the outside of the blade. The patterns of stress distribution for the measured and predicted are very similar; the values agree well at the ends of the blades where fatigue is a major concern. Discontinuities in the stress distribution occur at the joints because of the change of blade stiffness at those locations. The analytical values show an offset along the middle portion, however, indicating an underprediction at the tension side and an overprediction at the compression side of up to 10 MPa (1440 psi). This is also the area where the only significant differences between blades one and two occur. These differences may be due to small errors in the blade shape geometry in the model. Gravity stresses are especially sensitive to small angle changes at the blade-to-tower connection. The blade section lengths were carefully measured in

the field, and the blade sections (including the instrumentation cabling, paint and aerodynamic smoothing compound) were weighed several times. A survey of the turbine structure will be performed to attempt to determine the exact "as-mounted" blade attachment angles.




Fig. 4. Flatwise Gravity Stress Distribution

#### MODAL FREQUENCIES

After the blades were mounted on the tower, a modal test was performed on the stationary rotor by Sandia's Modal and Structural Mechanics Division (7544). During this test, frequency response functions were measured using both wind and step relaxation (snap releasing) excitations. Accelerometers were temporarily attached to the blades, tower and cables. These measurements were used to determine the mode shapes, their frequencies of vibration, and modal damping values. Reference 10 describes the details of the Test Bed modal test.

Table I compares the measured modal frequencies with those determined analytically. The mode number and name are listed in the first two columns (Figure 5 shows the shapes of these modes when viewed from three orthogonal directions). Columns three and four of Table I show the modal frequencies for the stationary rotor measured after a snap release and during wind excitation, respectively. Column five lists the predicted values, and column six lists measured frequencies obtained from amplitude spectra plots of strain gauge data taken during the the wind-excited modal analysis. There is excellent agreement between the measured and predicted frequencies for the first eleven modes. At the higher modes the predicted modal frequencies do not agree as well with the measurements. The two- dimensional finite element model appears to have a limit on its ability to predict these higher modes. However, in general, the higher modes have lower deformation and less energy associated with them.

Mode Number	Mode Shape	Modal Analysis		Predicted	Strain Gauge Spectra
		Snap Release	Wind Excitation		
1	1FA-First Flatwise Antisymmetric	1.04	1.06	1.05	> 1.06
2	1FS-First Flatwise Symmetric	1.04	1.06	1.05	
3	1Pr First Propeller (Rotor Twist)	1.35	1.52	1.56	1.50
4	1B-First Blade Edgewise	1.81	1.81	1.72	1.82
5	2FA-Second Flatwise Antisymmetric	2.06	2.06	2.07	> 2.14
6	2FS-Second Flatwise Symmetric	2.16	2.16	2.14	
7	1TI-First Tower In-Plane	2.49	2.50	2.46	2.50
8	1TO-First Tower Out-of-Plane	2.60	2.61	2.58	2.61
9	3FA-Third Flatwise Antisymmetric	3.45	3.50	3.49	> 3.51
10	3FS-Third Flatwise Symmetric	3.45	3.50	3.51	
11	2Pr Second Propeller	3.59	3.59	3.52	3.59
12	2B-Second Blade Edgewise	-	4.06	3.90	4.05
13	2TI-Second Tower In-Plane	-	4.69	4.33	-
14	2TO-Second Tower Out-of-Plane	-	-	4.57	-
15	4FS-Fourth Flatwise Symmetric	-	5.09	5.25	-
16	4FA-Fourth Flatwise Antisymmetric	-	5.30	5.37	-
17	3Pr Third Propeller	-	-	5.71	-

Table I. Stationary Modal Frequencies - Brakes Engaged




Fig. 5. Mode Shapes

The first propeller mode is approximately 1.5 Hz with the brakes engaged and 0.2 Hz with the brakes released. By adding or changing elastomeric pads (known as hockey pucks because of their size and shape), the drive train stiffness can be adjusted and the frequency of the first propeller mode changed. The first three flatwise modes (both antisymmetric and symmetric), the first tower in-plane and out-of-plane modes, and the second propeller mode were all predicted within two percent of the measured frequencies. The first blade edgewise mode is underpredicted by 0.09 Hz (approximately 5 percent) indicating that the blades are actually slightly stiffer in the lead-lag direction than modeled or that the blade-to-tower attachment should be more rigid in that direction. The close agreement between predicted and measured frequencies for the first eleven modes is an indication that the finite element model does an excellent job in representing the Test Bed - a complicated three-dimensional structure.

The measured frequencies resulting from the two methods of excitation - snap releasing and wind excitation - are very close. Only the first propeller mode shows any significant difference in frequency between the two methods. The reason for this difference is not clear. However, the snap release puts more energy into the system and possibly alters the brake boundary condition slightly. As shown in column six, the peak frequencies from the strain amplitude spectra agree closely with those measured by the modal test.

The first two guy cable frequencies, modes  $n=1$  and  $n=2$ , were designed to vibrate at 0.81 Hz and 1.62 Hz, respectively, at a nominal cable tension of 826 kN (186,000 lb), assuming a uniform cross-sectional area the entire cable length. This design puts the first cable mode below 2P (two per-rev) and the second mode between 2P and 4P for the entire operating range. The first four cable frequencies were measured at 0.81, 1.27, 2.05, and 3.02 Hz. The first cable mode occurs at the frequency to which it was designed (0.81 Hz), however, the second measured mode is significantly lower than the second design mode. This is due to an interaction between the cables and heavy cable attachment hardware at the lower cable connection. There is much less motion associated with this mode than the  $n=1$  mode. As the cable fanplot (Fig. 6) indicates, this resonance is the second mode crossing the 2P line. A new guy cable model that includes the ability to model the variation in mass distribution has recently been developed and correctly predicts the four measured cable modes.




Fig. 6. Cable Fanplot

The predicted fanplot for the "as-built" finite element model with the brakes released is shown in Fig. 7. Because the brake boundary condition is eliminated, some of the stationary tower modal frequencies, as expected, are lower than the modal frequencies shown in Table I. The blade modal frequencies are not affected by this boundary condition. Because potential resonances are possible wherever a modal frequency crosses a per-rev line, both this rotor fanplot and the guy cable fanplot have been employed extensively during the resonance surveys to identify and avoid resonances.






Fig. 7. Rotor Fanplot - Brakes Disengaged

The turbine has operated at rotation rates from 6 to 40 rpm in winds up to 17 mps. Time series have been analyzed with the aid of the data acquisition and analysis (DAAS) software (11). This software can plot any segment of a time series, compute the statistical properties of a segment, statistically reduce the data, and perform spectral analyses. A plot of a strain amplitude spectrum for a flatwise gauge at the upper root at 10 rpm is shown in Fig. 8. The first five per-rev peaks and several other peaks that indicate modal frequencies are evident. By plotting these measured modal frequencies at several rotation rates on the predicted fanplot, as shown in Fig. 9, one can track several rotor modes with rpm. The lower frequency modes (below 3 Hz) including the first and second flatwise (1F,2F), the first blade edgewise (1B), the first tower in-plane (1TI), and the second propeller (2Pr), all track along their predicted mode lines very well. The two measured first flatwise modal frequencies are either the antisymmetric and symmetric modes, which normally vibrate at the same frequency, or the two blades vibrating at slightly different frequencies. The first tower out-of-plane (1TO) does not show up in any of the many spectral plots examined thus far. The first blade edgewise mode (1B) was underpredicted by 5% at zero rpm, but above 25 rpm the observed and predicted frequencies coincide. The first blade edgewise crossing of the 3P line shows up as a larger spike in the spectra of lead-lag gauges at 32 rpm. The stresses are not high in this region in low winds, but significantly increase in winds above 13 mps. The first tower in-plane mode (1TI) tracks well except in the region where it crosses the second flatwise modes. An excitation of this tower in-plane mode begins around 39.5 rpm, and the response is still increasing at 40 rpm. This is due to the 3P crossing predicted at 40.5 rpm. The tower-in-plane excitation which includes blade edgewise motion causes significant lead-lag RMS stresses.

#### CENTRIFUGAL STRESSES

Figure 10 is a time series record that includes an upper root, flatwise-bending strain gauge and turbine rotation speed. Since the gauges are zeroed before testing, the mean stresses are due solely to centrifugal effects. As the rpm is increased from 0 to 40 rpm, there is an increase in blade bending stresses due to growing centrifugal loading. By averaging each flatwise strain gauge for 40 seconds at each rpm, centrifugal stresses are determined for comparison to analytical results. The increase of centrifugal stresses with higher rpm continues to offset the bending stresses due to gravity until the mean stresses are minimized at 37.5 rpm (the design troposkien rpm).




Fig. 8. Strain Amplitude Spectrum at 10 RPM




Fig. 9. Rotating Modal Frequencies - Measured vs. Predicted

bu0728881045 07/28/88 BU 10:55  
40(RPM0)avg=24.85598 std=11.13185  
RESONANCE TESTING AT ABOUT 9M/S




Fig. 10. Upper Root Flatwise Stress vs. RPM

Figures 11 and 12 show a comparison of the measured flatwise centrifugal bending stresses at 28 and 40 rpm to those determined analytically. The stresses along the blade from top to bottom are plotted left to right on the x-axis. There is excellent agreement between the measured and predicted values. Comparisons have also been made at 10,15,20,32,and 36 rpm, and similar agreement is observed.




Fig. 11. Centrifugal Stress Distribution at 28 RPM




Fig. 12. Centrifugal Stress Distribution at 40 RPM

#### OPERATING STRESSES

Standard deviations of stress time histories for all recorded channels were computed for segments of data at various rotation rates and wind speeds. This information was used during the resonance surveys for diagnostic purposes (qualitative only) to determine the presence and severity of resonances. It requires hours of time series records at each rpm of interest when using the Method of Bins to obtain quantitative operating stress response and turbine performance as a function of wind speed. Sufficient averaged data are now becoming available for comparisons to predictions.



## SUMMARY

At this early stage of testing, the turbine is responding structurally as expected. Predicted gravity stresses compare very well to measured values over most of the blade. Small adjustments to the model's blade attachment angles, if justified, may result in even better agreement.

The first guy cable mode was measured at its design frequency. Interaction between the heavy cable attachment hardware and the cables causes the second and higher modes to be lower than predicted because of the design assumption of a uniform cable mass distribution. A more exact cable model that includes the proper mass distribution of the attachment hardware has recently been developed. The second cable mode appears to become excited at two per-rev around 37 rpm.

A modal test was performed on the stationary rotor. The measured modal frequencies were compared to analytical predictions with excellent results. Rotating modal frequencies obtained from strain amplitude spectra also agree closely with predicted values.

Measured centrifugal stresses have been compared to analytical predictions at several rotation rates, and again, agreement has been excellent.

The close agreement between measured and predicted modal frequencies and mean stresses indicates that the finite element model accurately represents the 34-m Test Bed structure.

REFERENCES

1. Stephenson, W. A., "Test Plan for the 34 Meter Vertical Axis Wind Turbine Test Bed Located at Bushland, Texas," SAND86-1623, Sandia National Laboratories, Albuquerque, NM, December 1986.
2. Akins, R. A., "Performance Evaluation of Wind Energy Conversion Systems Using the Method of Bins - Current Status," SAND77-1375, Sandia National Laboratories, Albuquerque, NM, March 1978.
3. Klimas, P. C., "Tailored Airfoils for Vertical Axis Wind Turbines," SAND84-1062, Sandia National Laboratories, Albuquerque, NM, November 1984.
4. Ashwill, T. D. and Leonard, T. M., "Developments in Blade Shape Design for a Darrieus Vertical Axis Wind Turbine," SAND86-1085, Sandia National Laboratories, Albuquerque, NM, September 1986.
5. Ashwill, T. D., "Structural Design and Fabrication of the Sandia 34-Meter Vertical Axis Wind Turbine," Proceedings of the 1987 ASME-JSME Solar Energy Conference, Honolulu, HI, March 1987.
6. Carne, T. G., Lobitz, D. W., Nord, A. R., Watson, R. A., "Finite Element Analysis and Modal Testing of a Rotating Wind Turbine," SAND82-0345, Sandia National Laboratories, Albuquerque, NM, October 1982.
7. Lobitz, D. W., and Sullivan, W. N., "Comparison of Finite Element Predictions and Experimental Data for the Forced Response of the DOE 100 kW Vertical Axis Wind Turbine," SAND82-2534. Sandia National Laboratories, Albuquerque, NM, February 1984.
8. Paraschivoiu, I., "Aerodynamic Loads and Performance of the Darrieus Rotor," AIAA Journal of Energy, Volume 6, No. 6, pp 406-412, December 1982.
9. Sutherland, H. J. and Stephenson, W. A., "Rotor Instrumentation Circuits for the Sandia 34-Meter Vertical Axis Wind Turbine," SAND88-1144, Sandia National Laboratories, Albuquerque, NM, July 1988.
10. Carne, T. G., Lauffer, J. P., Gomez, A. J., and Ashwill, T. D., "Model Validation of the Sandia 34-Meter Test Bed Turbine Using Substructured Modal-Testing," Proceedings of the Eighth ASME Wind Energy Symposium, Houston, TX, January 1989.

11. Berg, D., Rumsey, M., Gallo, L., and Burwinkle, D., "Data Acquisition and Analysis System for the Sandia 34-Meter Vertical Axis Wind Turbine, Proceedings of the Seventh ASME Wind Symposium, New Orleans, LA., January 1988.

DISTRIBUTION:

Advanced Alternative Energy  
Solutions  
Attn: Ugur Ortabasi  
5673 W. Las Positas Boulevard  
Suite 205  
P.O. Box 5246  
Pleasanton, CA

Alcoa Technical Center (5)  
Aluminum Company of America  
Attn: D. K. Ai  
J. T. Huang  
J. R. Jombock  
M. Klingensmith  
J. L. Prohaska  
Alcoa Center, PA 15069

Alternative Sources of Energy  
Attn: L. Stoiaken  
Milaca, MN 56353

Amarillo College  
Attn: E. Gilmore  
Amarillo, TX 79100

The American Wind Energy Association  
1730 N. Lynn Street, #610  
Arlington, VA 22209

Roger J. Austin  
Hydro-LIFT Systems  
125 Catron Drive  
Reno, NV 89512

Dr. A. S. Barker  
Trinity Western  
7600 Glover Road  
Langley, BC  
CANADA V3A 4R9

Battelle-Pacific Northwest  
Laboratory  
Attn: L. Wendell  
P.O. Box 999  
Richland, WA 99352

Bechtel Group, Inc.  
Attn: B. Lessley  
P.O. Box 3965  
San Francisco, CA 94119

Dr. George Bergeles  
Dept. of Mechanical Engineering  
National Technical University  
42, Patission Street  
Athens, GREECE

Ir. Jos Beurskens  
Programme Manager for  
Renewable Energies  
Netherlands Energy Research  
Foundation ECN  
Westerduinweg 3  
P.O. Box 1  
1755 ZG Petten (NH)  
The Netherlands

Bonneville Power Administration  
Attn: N. Butler  
P.O. Box 3621  
Portland, OR 97208

Canadian Standards Association  
Attn: T. Watson  
178 Rexdale Blvd.  
Rexdale, Ontario, M9W 1R3  
CANADA

Monique Carpentier  
Energy, Mines and Resources  
Renewable Energy Branch  
460 O'Connor St.  
Ottawa, Ontario  
CANADA K1A 0E4

Professor V. A. L. Chasteau  
School of Engineering  
University of Auckland  
Private Bag  
Auckland, NEW ZEALAND

W. H. Cherry  
4547 Province Line Road  
Princeton, NJ 08540

Colorado State University  
Dept. of Civil Engineering  
Attn: R. N. Meroney  
Fort Collins, CO 80521

Commonwealth Electric Co.  
Attn: D. W. Dunham  
Box 368  
Vineyard Haven, MA 02568

M. M. Curvin  
11169 Loop Road  
Soddy Daisy, TN 37379

Alcir de Faro Orlando  
Pontificia Universidade Catolica-  
PUC/Rj  
Mechanical Engineering Department  
R. Marques de S. Vicente 225  
Rio de Janeiro, BRAZIL

Department of Economic Planning  
and Development  
Barrett Building  
Attn: G. N. Monsson  
Cheyenne, WY 82002

Beatrice de Saint Louvent  
Etablissement d'Etudes et  
de Recherches Meteorologiques  
77 Rue de Serves  
92106 Boulogne-Billancourt Cedex  
FRANCE

Otto de Vries  
National Aerospace Laboratory  
Anthony Fokkerweg 2  
Amsterdam 1017  
THE NETHERLANDS

DOE/ALO/ETWMD  
Attn: G. P. Tennyson  
Albuquerque, NM 87115

DOE/ALO  
Energy Technology Liaison Office  
NGD  
Attn: Capt. J. L. Hanson, USAF  
Albuquerque, NM 87115

DOE Headquarters (5)  
Wind/Oceans Technologies Division  
Attn: L. J. Rogers  
P. R. Goldman  
1000 Independence Avenue  
Washington, DC 20585

J. B. Dragt  
Nederlands Energy Research  
Foundation  
(E.C.N.)  
Physics Department  
Westerduinweg 3 Petten (NH)  
THE NETHERLANDS

Electric Power Research Institute  
Attn: J. R. Birk  
E. A. DeMeo  
3412 Hillview Avenue  
Palo Alto, CA 94304

George Elliot, Manager  
National Wind Turbine Centre  
Department of Trade and Industry  
National Engineering Laboratory  
East Kilbride  
Glasgow G75 0QU  
Scotland

John Ereaux  
RR No. 2  
Woodbridge, Ontario L4L 1A6  
CANADA

Dr. Norman E. Farb  
10705 Providence Drive  
Villa Park, CA 92667

FloWind Corporation  
Attn: L. Schienbein  
1183 Quarry Lane  
Pleasanton, CA 94566

A. D. Garrad  
Garrad Hasson  
10 Northampton Square  
London EC1M 5PA  
UNITED KINGDOM

H. Gerardin  
Mechanical Engineering Department  
Faculty of Sciences & Engineering  
Universite Laval-Quebec, G1K 7P4  
CANADA

Dr. I. J. Graham  
Southern University  
Dept. of Mechanical Engineering  
P.O. Box 9445  
Baton Rouge, LA 70813-9445

R. T. Griffiths  
University College of Swansea  
Dept. of Mechanical Engineering  
Singleton Park  
Swansea, SA2 8PP  
UNITED KINGDOM

Helion, Inc.  
Attn: J. Park, President  
Box 445  
Brownsville, CA 95919

Indal Technologies, Inc.  
Attn: V. Lacey  
3570 Hawkestone Road  
Mississauga, Ontario  
CANADA L5C 2V8

Institut de Recherche d'Hydro-Quebec  
Attn: Bernard Masse  
1800, Montee Ste-Julie  
Varenes, Quebec, JOL 2P.O.  
CANADA

Iowa State University  
Agricultural Engineering  
Attn: L. H. Soderholm  
Room 213  
Ames, IA 50010

K. Jackson  
Dynamic Design  
123 C Street  
Davis, CA 95616

M. Jackson  
McAllester Financial  
1816 Summit  
W. Lafayette, IN 47906

Leif G. Johansen  
Vice President of Operations  
Cannon Energy Corporation  
P.O. Box 1457  
Tehachapi, CA 93561

KW Control Systems, Inc.  
Attn: R. H. Klein  
RD#4, Box 914C  
South Plank Road  
Middletown, NY 10940

Kaiser Aluminum and Chemical  
Sales, Inc.  
Attn: A. A. Hagman  
14200 Cottage Grove Avenue  
Dolton, IL 60419

Kaiser Aluminum and Chemical  
Sales, Inc.  
Attn: D. D. Doerr  
6177 Sunol Blvd.  
P.O. Box 877  
Pleasanton, CA 94566

Kansas State University  
Electrical Engineering Department  
Attn: Dr. G. L. Johnson  
Manhattan, KS 66506

R. E. Kelland  
The College of Trades & Technology  
P.O. Box 1693  
Prince Philip Drive  
St. John's, Newfoundland, A1C 5P7  
CANADA

Kinetics Group, Inc.  
Attn: J. Sladky, Jr.  
P.O. Box 1071  
Mercer Island, WA 98040

L. K. Liljergren  
120 East Penn Street  
San Dimas, CA 91773

L. Liljidahl  
Building 005, Room 304  
Barc-West  
Beltsville, MD 20705

Olle Ljungstrom  
FFA, The Aeronautical Research  
Institute  
Box 11021  
S-16111 Bromma, SWEDEN

Robert Lynette  
R. Lynette & Assoc., Inc.  
15042 NE 40th Street  
Suite 206  
Redmond, WA 98052

David Malcolm  
Lavalin Engineers, Inc.  
Atria North - Phase 2  
2235 Sheppard Avenue East  
Willowdale, Ontario M25 5A6  
CANADA

Massachusetts Institute of  
Technology  
Attn: Professor N. D. Ham  
W. L. Harris, Aero/Astro  
Dept.  
77 Massachusetts Avenue  
Cambridge, MA 02139

Brian McNiff  
Engineering Consulting Services  
55 Brattle Street  
So. Berwick, ME 03908

Michigan State University  
Division of Engineering Research  
Attn: O. Krauss  
East Lansing, MI 48825

Alan H. Miller  
10013 Tepopa Drive  
Oakdale, CA 95361

Napier College of Commerce  
and Technology  
Tutor Librarian,  
Technology Faculty  
Colinton Road  
Edinburgh, EH10 5DT  
ENGLAND

National Rural Electric  
Cooperative Assn.  
Attn: Wilson Prichett, III  
1800 Massachusetts Avenue, NW  
Washington, DC 20036

Natural Power, Inc.  
Attn: Leander Nichols  
New Boston, NH 03070

New Mexico Engineering  
Research Institute (2)  
Attn: G. G. Leigh  
D. Morrison  
Campus P.O. Box 25  
Albuquerque, NM 87131

Ohio State University  
Aeronautical & Astronautical Dept.  
Attn: Professor G. Gregorek  
2300 West Case Road  
Columbus, OH 43220

Oklahoma State University  
Mechanical Engineering Dept.  
Attn: D. K. McLaughlin  
Stillwater, OK 76074

Oregon State University  
Mechanical Engineering Dept.  
Attn: R. E. Wilson  
Corvallis, OR 97331

Debby Oscar  
Massachusetts Institute of  
Technology  
77 Massachusetts Ave.  
Room 1-303  
Cambridge, MA 02139

Pacific Gas & Electric Co.  
Attn: T. Hillesland  
J. J. Iannucci  
W. J. Steele  
3400 Crow Canyon Road  
San Ramon, CA 94583

Ion Paraschivoiu  
Dept. of Mechanical Engineering  
Ecole Polytechnique  
CP 6079  
Succursale A  
Montreal, Quebec  
CANADA H3C 3A7

Jacques Plante  
Shawinigan Consultants, Inc.  
620 Dorchester Blvd. West  
Montreal, Quebec  
CANADA H3B 1N8



Public Service Co. of New Hampshire  
Attn: D. L. C. Frederick  
1000 Elm Street  
Manchester, NH 03105

Public Service Co. of New Mexico  
Attn: M. Lechner  
P.O. Box 2267  
Albuquerque, NM 87103

Dr. R. Ganesh Rajagopalan,  
Asst. Prof.  
Aerospace Engineering Department  
Iowa State University  
404 Town Engineering Bldg.  
Ames, IA 50011

R. Rangi (2)  
Low Speed Aerodynamics Laboratory  
NRC-National Aeronautical  
Establishment  
Montreal Road  
Ottawa, Ontario, K1A 0R6  
CANADA

RANN, Inc.  
Attn: A. J. Eggers, Jr.  
260 Sheridan Ave., Suite 414  
Palo Alto, CA 94306

Mr. Bent Rasmussen  
Overgade 14  
DK-7000 Fredericia  
DENMARK

Markus G. Real, President  
Alpha Real Ag  
Feldeggstrasse 89  
CH 8008 Zurich  
Switzerland

Reynolds Metals Company  
Mill Products Division  
Attn: G. E. Lennox  
6601 West Broad Street  
Richmond, VA 23261

R. G. Richards  
Atlantic Wind Test Site  
P.O. Box 189  
Tignish P.E.I., COB 2B0  
CANADA

Riso National Laboratory  
Attn: Troels Friis Pedersen  
Helge Petersen  
Peter Hauge Madsen  
Postbox 49  
DK-4000 Roskilde  
DENMARK

H. M. Romanowitz, P. E.  
Oak Creek Energy Systems, Inc.  
P.O. Box 469  
Tehachapi, CA 93561

Dr. Ing. Hans Ruscheweyh  
Institut fur Leichbau  
Technische Hochschule Aachen  
Wullnerstrasse 7  
FEDERAL REPUBLIC OF GERMANY

Gwen Schreiner  
Librarian  
National Atomic Museum  
Albuquerque, NM 87185

Arnan Seginer  
Professor of Aerodynamics  
Technion-Israel Institute of  
Technology  
Aeronautical Engineering Dept.  
Haifa  
ISRAEL

Mr. Farrell Smith Seiler, Editor  
Wind Energy News Service  
P.O. Box 4008  
St. Johnsbury, VT 05819

David Sharpe  
Dept. of Aeronautical Engineering  
Queen Mary College  
Mile End Road  
London, E1 4NS  
UNITED KINGDOM

Kent Smith  
Instituto Tecnológico Costa Rica  
Apartado 159 Cartago  
COSTA RICA

Solar Energy Research Institute  
Attn: R. W. Thresher  
1617 Cole Boulevard  
Golden, CO 80401

Bent Sorenson  
Roskilde University Center  
Energy Group, Bldg. 17.2  
IMFUFA  
P.O. Box 260  
DK-400 Roskilde  
DENMARK

Peter South  
ADECON  
6535 Millcreek Dr., Unit 67  
Mississauga, Ontario  
CANADA L5N 2M2

Southern California Edison  
Research & Development Dept.  
Room 497  
Attn: R. L. Scheffler  
P.O. Box 800  
Rosemead, CA 91770

G. Stacey  
The University of Reading  
Department of Engineering  
Whiteknights, Reading, RG6 2AY  
ENGLAND

Stanford University  
Dept. of Aeronautics and  
Astronautics Mechanical Engr.  
Attn: Holt Ashley  
Stanford, CA 94305

Dr. Derek Taylor  
Alternative Energy Group  
Walton Hall  
Open University  
Milton Keynes, MK7 6AA  
UNITED KINGDOM

Texas Tech University  
Mechanical Engineering Dept.  
Attn: J. W. Oler  
P.O. Box 4289  
Lubbock, TX 79409

Walter V. Thompson  
410 Ericwood Court  
Manteca, CA 95336

K. J. Touryan  
P.O. Box 713  
Indian Hills, CO 80454

Tulane University  
Dept. of Mechanical Engineering  
Attn: R. G. Watts  
New Orleans, LA 70018

J. M. Turner Technologies, Inc.  
Attn: Eric N. Hinrichsen  
P.O. Box 1058  
Schenectady, NY 12301-1058

US WindPower  
Attn: W. E. Holley  
G. M. McNerney  
Suite 3050  
400 West Cummings Park  
Woburn, MA 01803

USDA  
Agricultural Research Service  
Southwest Great Plains Research  
Center  
Attn: Dr. R. N. Clark  
Bushland, TX 79012

United Engineers and  
Constructors, Inc.  
Attn: A. J. Karalis  
P.O. Box 8223  
Philadelphia, PA 19101

Universal Data Systems  
Attn: C. W. Dodd  
5000 Bradford Drive  
Huntsville, AL 35805

University of California  
Institute of Geophysics  
and Planetary Physics  
Attn: Dr. P. J. Baum  
Riverside, CA 92521

University of Colorado  
Dept. of Aerospace  
Engineering Sciences  
Attn: J. D. Fock, Jr.  
Boulder, CO 80309

University of Massachusetts  
Mechanical and Aerospace  
Engineering Dept.  
Attn: Dr. D. E. Cromack  
Amherst, MA 01003

University of Oklahoma  
Aero Engineering Department  
Attn: K. Bergey  
Norman, OK 73069

University of Sherbrooke  
Faculty of Applied Science  
Attn: A. Laneville  
P. Vittecoq  
Sherbrooke, Quebec, J1K 2R1  
CANADA

The University of Tennessee  
Dept. of Electrical Engineering  
Attn: T. W. Reddoch  
Knoxville, TN 37916

W. A. Vachon  
W. A. Vachon & Associates  
P.O. Box 149  
Manchester, MA 01944

Dirk Vandenberghe  
State Univ. of Ghent  
St. Pietersnieuwstraat 41  
9000 Ghent  
BELGIUM

Washington & Lee University  
Attn: Dr. R. E. Akins  
P.O. Box 735  
Lexington, VA 24450

Washington State University  
Dept. of Electrical Engineering  
Attn: F. K. Bechtel  
Pullman, WA 99163

West Texas State University  
Government Depository Library  
Number 613  
Canyon, TX 79015

West Texas State University  
Department of Physics  
Attn: V. Nelson  
P.O. Box 248  
Canyon, TX 79016

West Virginia University  
Dept. of Aero Engineering  
Attn: R. Walters  
1062 Kountz Avenue  
Morgantown, WV 26505

D. Westlind  
Central Lincoln People's  
Utility District  
2129 North Coast Highway  
Newport, OR 97365-1795

Wichita State University  
Aero Engineering Department (2)  
Attn: M. Snyder  
W. Wentz  
Wichita, KS 67208

Wind Power Digest  
Attn: Michael Evans  
P.O. Box 700  
Bascom, OH 44809

400 R. C. Maydew  
1520 L. W. Davison  
1522 R. C. Reuter, Jr.  
1522 D. W. Lobitz  
1522 E. D. Reedy  
1523 J. H. Biffle  
1524 C. R. Dohrmann  
1524 D. R. Martinez  
1550 C. W. Peterson  
1552 J. H. Strickland  
1556 G. F. Homicz  
3141 S. A. Landenberger (5)  
3151 W. I. Klein (3)  
3154-1 C. L. Ward (8)  
For DOE/OSTI (Unlimited

3161 P. S. Wilson  
6000 D. L. Hartley  
6200 V. L. Dugan  
6220 D. G. Schueler  
6225 H. M. Dodd (50)  
6225 T. D. Ashwill  
6225 D. E. Berg  
6225 T. C. Bryant  
6225 M. E. Ralph  
6225 D. C. Reda  
6225 M. A. Rumsey  
6225 L. L. Schluter  
6225 W. A. Stephenson  
6225 H. J. Sutherland  
6225 P. S. Veers  
7544 D. O. Smallwood  
7544 T. G. Carne  
7544 J. Lauffer  
8524 J. R. Wackerly