

## ENERGY STAR Qualified Light Fixtures Product List

List Posted on January 03, 2013

Below are currently qualified ENERGY STAR models available for sale in the U.S. and Canada.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
AFX Lighting Inc.	AFX lighting, Inc.	323911/IDSR118SNSCT	Residential	Fluorescent	Wall Sconces	1200.0	18.17	75.2	N/A	0.603	3500.0	82.0	10000.0	7/25/2012		
AFX Lighting Inc.	AFX lighting, Inc.	323913/IDS118SNSCT	Residential	Fluorescent	Wall Sconces	1200.0	18.17	75.2	N/A	0.603	3500.0	82.0	10000.0	7/25/2012		
AFX Lighting Inc.	AFX lighting, Inc.	323915/IDSS118SNSCT	Residential	Fluorescent	Wall Sconces	1200.0	18.17	75.2	N/A	0.603	3500.0	82.0	10000.0	7/25/2012		
AFX Lighting Inc.	AFX lighting, Inc.	357062	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	7/31/2012		
AFX Lighting Inc.	AFX lighting, Inc.	CEV117PC/PNR8	Residential	Fluorescent	Bath Vanity	1239.9	18.62	66.6	N/A	0.513	3000, 3500, 4100	84.2	10000.0	9/11/2012		
AFX Lighting Inc.	AFX lighting, Inc.	CEV125PC/PNR8	Residential	Fluorescent	Bath Vanity	1976.4	30.76	73.73	N/A	0.543	3000, 3500, 4100	83.9	10000.0	9/11/2012		
AFX Lighting Inc.	AFX lighting, Inc.	CEV217PC/PNR8	Residential	Fluorescent	Bath Vanity	2018.0	26.81	65.6	N/A	0.543	3000, 3500, 4100	84.2	10000.0	9/11/2012		
AFX Lighting Inc.	AFX lighting, Inc.	CEV225PC/PNR8	Residential	Fluorescent	Bath Vanity	3223.0	42.49	75.9	N/A	0.612	3000, 3500, 4100	83.9	10000.0	9/11/2012		
AFX Lighting Inc.	American Fluorescent	357062	Residential	Fluorescent	Wall Sconces	900.0	13.8	71.0	N/A	0.6	2700.0	82.0	10000.0	2/10/2012		
AFX Lighting Inc.	American Fluorescent	L606M30S1D-6 WRWT	Both	Solid State	Downlight Solid State retrofit	626.47	13.7	N/A	45.91	0.95	3000.0	80.7	35000.0	6/14/2012	Dimmable	
AFX Lighting Inc.	American Fluorescent	SWC313SCT	Residential	Fluorescent	Chandelier	2700.0	41.4	71.0	N/A	0.6	2700.0	82.0	10000.0	2/17/2012		
AFX Lighting Inc.	American Fluorescent	SWF213SCT	Residential	Fluorescent	Close to Ceiling Mount	1800.0	27.6	71.0	N/A	0.6	2700.0	82.0	10000.0	2/17/2012		
AFX Lighting Inc.	American Fluorescent	SWP113SCT	Residential	Fluorescent	Decorative Pendant	900.0	13.8	71.0	N/A	0.6	2700.0	82.0	10000.0	2/17/2012		
AFX Lighting Inc.	American Fluorescent	SWP313SCT	Residential	Fluorescent	Chandelier	2700.0	41.4	71.0	N/A	0.6	2700.0	82.0	10000.0	2/17/2012		
AFX Lighting Inc.	American Fluorescent Co	SW232SNR8	Residential	Fluorescent	Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3000, 3500, 4100	N/A	10000.0	4/26/2012		
AFX Lighting Inc.	American Fluorescent Co	TW232R8	Residential	Fluorescent	Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3000, 3500, 4100	N/A	10000.0	4/26/2012		
AFX Lighting Inc.	American Fluorescent Co	TW232R8-CA	Residential	Fluorescent	Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3000, 3500, 4100	N/A	10000.0	4/26/2012		
AFX Lighting Inc.	Ascent	CARF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.22	0.9842	3000.0	83.6	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Ascent	CRRF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.15	0.98	3000.0	83.3	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Ascent	MTRF4200LED RB3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	45.43	0.9841	3000.0	82.1	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Ascent	MTRF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	52.13	0.9833	3000.0	83.6	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Ascent	TRRF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.41	0.9825	3000.0	84.4	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Hampton Bay	DWSW20030LB KC (135136)	Residential	Solid State	Outdoor Post-mounted	307.0	8.0	N/A	40.48	0.8655	3000.0	83.1	35000.0	8/13/2012		
AFX Lighting Inc.	Hampton Bay	VERF4200LEDR B3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	45.43	0.9841	3000.0	82.1	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Hampton Bay	VERF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	52.13	0.9833	3000.0	83.6	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Innova/ Hampton bay	INFT9001SN; KERF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	50.8	0.9738	3000.0	84.0	35000.0	6/21/2012	Dimmable	
AFX Lighting Inc.	Innova Lighting	INE6006APC {372133}	Residential	Solid State	Outdoor Post-mounted	1008.9	23.99	N/A	42.06	0.81	N/A	N/A	35000.0	3/19/2012		
AFX Lighting Inc.	Innova Lighting	INE6008AP {631690}	Residential	Solid State	Outdoor Post-mounted	1156.76	24.1	N/A	48.0	0.826	N/A	N/A	35000.0	4/3/2012		
AFX Lighting Inc.	Innova Lighting	INE6009APC {372122}	Residential	Solid State	Porch Light	354.613	7.89	44.945	N/A	0.763	3500.0	N/A	35000.0	5/4/2012		
AFX Lighting Inc.	Patriot	APRF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	46.1	0.9831	3000.0	83.0	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	Patriot	BERF4200LEDS N3K	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	45.92	0.9842	3000.0	83.5	35000.0	8/9/2012	Dimmable	
AFX Lighting Inc.	PORTFOLIO	ALRF4200LEDS N3K (397865)	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	50.22	0.9851	3000.0	84.2	35000.0	8/9/2012	Dimmable	
Allied Moulded Products, Inc.	Allied Moulded	LH-CFL1	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.5	2700.0	82.0	10000.0	4/3/2012		
Allied Moulded Products, Inc.	Allied Moulded	LH-CFL2	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.5	2700.0	82.0	10000.0	4/3/2012		
Altair Lighting	Altair	AL-2148	Residential	Solid State	Porch Light	317.0	8.89	35.7	N/A	0.843	4500.0	82.2	36000.0	3/28/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
American Lighting Inc.	American Lighting Inc.	LD6-E26-30-WH	Residential	Solid State	Downlight Solid State Retrofit	656.07	12.56	N/A	52.99	0.912	3000.0	82.0	35000.0	5/22/2012		
American Lighting Inc.	American Lighting LLC	043L-16	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	255.06	8.595	N/A	29.52	0.94	3000.0	81.0	35000.0	11/21/2011	Dimmable	
American Lighting Inc.	American Lighting LLC	043L-24	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	452.78	12.36	N/A	36.65	0.94	3000.0	81.0	35000.0	11/21/2011	Dimmable	
American Lighting Inc.	American Lighting LLC	043L-32	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	638.25	17.67	N/A	35.97	0.94	3000.0	81.0	35000.0	11/21/2011	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	C3RTLX-X-26-LED-E-XX-120-XX-XX-XXXX	Commercial	Solid State	Accent Light Line-voltage	972.0	24.34	N/A	40.0	0.975	2700.0	81.0	36000.0	3/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	C3R-X-26-LED-E-XX-120-XX-XX-XXXX	Commercial	Solid State	Accent Light Line-voltage	972.0	24.34	N/A	40.0	0.975	2700.0	81.0	36000.0	3/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	C3SR-X-26-LED-E-XX-120-XX-XX-XXXX	Commercial	Solid State	Accent Light Line-voltage	972.0	24.34	N/A	40.0	0.975	2700.0	81.0	36000.0	3/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	C3TV-30-LED-E-XX-XXX-120-XX-XXXX	Commercial	Solid State	Accent Light Line-voltage	1173.0	29.41	N/A	39.9	0.978	2700.0	81.0	36000.0	7/5/2012		
Amerlux Global Lighting Solutions	Amerlux	CNTRV22-12-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Accent Light Line-voltage	435.0	11.87	N/A	36.7	0.971	2700.0	83.0	35000.0	12/14/2011	Dimmable	Includes 3000K, 3500K, 4000K models and all lens variations
Amerlux Global Lighting Solutions	Amerlux	CNTRV23-18-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Accent Light Line-voltage	653.4	16.76	N/A	39.0	0.974	2700.0	83.0	35000.0	11/15/2011	Dimmable	Includes 3000K, 3500K, 4000K models and all lens variations
Amerlux Global Lighting Solutions	Amerlux	CNTRV33-24-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Accent Light Line-voltage	968.6	24.55	N/A	39.5	0.992	2700.0	83.0	35000.0	11/15/2011	Dimmable	Includes 3000K, 3500K, 4000K models and all lens variations
Amerlux Global Lighting Solutions	Amerlux	CNTRV34-32-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Accent Light Line-voltage	1309.0	32.13	N/A	40.7	0.984	2700.0	83.0	35000.0	10/25/2011		Includes 3000K, 3500K, 4000K models and all lens variations
Amerlux Global Lighting Solutions	Amerlux	CNTRV44-40-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Accent Light Line-voltage	1734.0	42.04	N/A	41.2	0.989	2700.0	83.0	35000.0	10/25/2011		Includes 3000K, 3500K, 4000K models and all lens variations
Amerlux Global Lighting Solutions	Amerlux	E2.9RD-12-LED-E-120-XX-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	478.0	11.32	N/A	42.3	0.97	3000.0	83.0	36000.0	5/8/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E2.9RLW-12-LED-E-120-WW-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	478.0	11.32	N/A	42.3	0.97	3000.0	83.0	36000.0	5/8/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E2.9XA-G2-12-LED-120-XX-XX-XXXX / E2.9XA-G2-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	548.0	12.16	N/A	45.1	0.969	3000.0	82.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E2.9XA-G2-TL-12-LED-120-XX-XXXX / E2.9XA-G2-TL-XXX	Commercial	Solid State	Commercial: Downlight Recessed	548.0	12.16	N/A	45.1	0.969	3000.0	82.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E2.9XD-G2-12-LED-120-XX / E2.9XD-G2-XXX-XX-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	552.0	12.15	N/A	45.5	0.971	3000.0	82.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E2.9XD-G2-TL-12-LED-120 / E2.9XD-G2-TL-XXX-XX-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	552.0	12.15	N/A	45.5	0.971	3000.0	82.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E4.75XA-G2-12-LED-120-XX-XXXX / E4.75XA-G2-XXX	Commercial	Solid State	Commercial: Downlight Recessed	545.0	12.45	N/A	43.8	0.986	3000.0	81.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	E4.75XA-G2-TL-12-LED-120-XX-XXXX / E4.75XA-G2-TL-XXX	Commercial	Solid State	Commercial: Downlight Recessed	545.0	12.45	N/A	43.8	0.986	3000.0	81.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-15-LED-E-XX-XXXX-120-XXX-XXXX	Commercial	Solid State	Commercial: Accent Light Line-voltage	765.0	15.47	N/A	49.4	0.989	3000.0	82.0	36000.0	4/12/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Amerlux Global Lighting Solutions	Amerlux	HORNET-R-1-12-LED-E-XX-WT-XXX-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-R-2-12-LED-E-XX-120-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-R-3-12-LED-E-XX-120-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-R-4-12-LED-E-XX-120-XX-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-RTLX-1-12-LED-E-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-RTLX-2-12-LED-E-XX-120-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-RTLX-3-12-LED-E-XX-120-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-RTLX-4-12-LED-E-XX-120-XX-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-SR-1-12-LED-E-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-SR-2-12-LED-E-XX-120-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-SR-3-12-LED-E-XX-120-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
Amerlux Global Lighting Solutions	Amerlux	HORNET-SR-4-12-LED-E-XX-120-XX-XX-XX-XX-WT-XXXX	Commercial	Solid State	Commercial: Downlight Recessed	679.0	11.88	N/A	57.2	0.969	3000.0	83.0	36000.0	4/12/2012	Dimmable	
AmerTac (American Tack and Hardware)	Westek	LPBD16	Residential	Solid State	Under Cabinet Luminaire	333.9	8.29	N/A	40.28	0.812	3000.0	86.0	25000.0	8/28/2012	Dimmable	
Amlite Lighting	Amlite Lighting	FM376/12BN-ES	Residential	Fluorescent	Ceiling Mount	975.86	24.67	39.54	N/A	0.597	2700.0	81.0	10000.0	10/4/2012		
ATG Electronics Corp.	ATG Electronics	HDL-T018W-01900D-H1	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	1100.0	18.0	N/A	62.61	0.9893	3000.0	81.8	40000.0	8/13/2012	Dimmable	
Aurum Electronics Corp.	Aurum	AEC-9336	Residential	Halogen	Security	N/A	146.3	N/A	N/A	1.0	N/A	N/A	2500.0	3/5/2012		
Aurum Electronics Corp.	Aurum	AEC-9336A	Residential	Halogen	Security	N/A	147.4	N/A	N/A	1.0	N/A	N/A	2500.0	3/5/2012		
Aurum Electronics Corp.	Aurum	AEC-939BSD	Residential	Halogen	Security	N/A	200.0	N/A	N/A	1.0	N/A	N/A	2500.0	2/13/2012		
AutoCell Electronics, Inc.	AutoCell Electronics	57W-TOR-27KYN	Residential	Fluorescent	Torchieres	3900.0	57.0	70.24	N/A	0.539	2700.0	82.6	10000.0	5/3/2012		
AutoCell Electronics, Inc.	AutoCell Electronics	57W-TOR-41KYN	Residential	Fluorescent	Torchieres	3900.0	57.0	70.04	N/A	0.537	4100.0	81.7	10000.0	5/3/2012		
Aztec / Kichler	Allen & Roth	38147	Residential	Fluorescent	Ceiling Mount	1878.0	26.4	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	34401	Residential	Fluorescent	Chandelier	4695.0	66.0	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	34423	Residential	Fluorescent	Chandelier	8451.0	118.8	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	34424	Residential	Fluorescent	Chandelier	4695.0	66.0	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	34425	Residential	Fluorescent	Chandelier	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	34426	Residential	Fluorescent	Chandelier	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	37255	Residential	Fluorescent	Bath Vanity	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	PORTFOLIO	38134	Residential	Fluorescent	Ceiling Mount	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	Westwood	34423	Residential	Fluorescent	Chandelier	8451.0	118.8	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	Westwood	34424	Residential	Fluorescent	Chandelier	4695.0	66.0	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Aztec / Kichler	Westwood	34425	Residential	Fluorescent	Chandelier	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Aztec / Kichler	Westwood	34426	Residential	Fluorescent	Chandelier	2817.0	39.6	71.0	N/A	0.6	2700.0	83.0	10000.0	4/9/2012		
Bel Air Lighting, Trans Globe Lighting	Bel Air Lighting	BA0003B1-PL	Residential	Fluorescent	Wall Sconces	900.0	12.79	69.2	N/A	0.6	2700.0	82.0	10000.0	10/22/2012		Retail Product Number 104801
Bel Air Lighting, Trans Globe Lighting	Bel Air Lighting	CB-60002	Residential	Fluorescent	Wall Sconces	900.0	12.79	69.2	N/A	0.6	2700.0	82.0	10000.0	9/21/2012		
Bright Yin Huey	Bright Yin Huey Company Limited	D0099RA	Residential	Solid State	Downlight Recessed	357.8	7.35	N/A	49.081	0.833	3000.0	82.0	35000.0	9/30/2011	Dimmable	
Bright Yin Huey	Bright Yin Huey Company Limited	D0100RA	Residential	Solid State	Downlight Recessed	422.564	8.97	N/A	46.128	0.836	3000.0	82.0	35000.0	9/30/2011	Dimmable	
Bright Yin Huey	Bright Yin Huey Company Limited	D0101RA	Residential	Solid State	Downlight Recessed	657.345	12.99	N/A	50.217	0.777	3000.0	83.0	35000.0	9/30/2011	Dimmable	
Brownlee Lighting	Brownlee Lighting	1005-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1005-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1022-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1022-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1042-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1042-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1080-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1080-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1080-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1086-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1086-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1140-XX-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1140-XX-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1215-XX-XXX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1230-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1230-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1230-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1230-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1230-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1230-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1281-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1281-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1283-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1330-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1330-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1330-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1330-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1330-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1350-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1362-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1362-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1375-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1380-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1380-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1385-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1385-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1390-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1390-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1405-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1405-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1410-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1450-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1450-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1468-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1468-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1470-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1470-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1470-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1470-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1472-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1472-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1472-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1472-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1474-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1474-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1474-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1474-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1476-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1476-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1476-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1476-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1480-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1480-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1480-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1480-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1482-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1482-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1482-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1482-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1484-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1484-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1484-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1484-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1486-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1486-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1486-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1486-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1490-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1490-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1490-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1490-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1492-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1492-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1492-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1492-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1494-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1494-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1494-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1494-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1496-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1496-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1496-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1496-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1500-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1500-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1500-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1500-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1503-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1503-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1503-XX-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1503-XX-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1506-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1506-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1506-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1506-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1509-XX-13Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1509-XX-18Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1509-XX-26Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1510-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1510-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1510-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1510-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1511-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1511-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1511-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1511-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1515-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1515-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1518-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1520-XX-13Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1520-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1520-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1520-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1520-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1520-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1522-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1532-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1532-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-13Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1535-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1535-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1538-13Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1540-13Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1542-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1544-XX-13Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1560-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1560-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1562-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1562-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1565-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1565-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	1567-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	1567-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2020-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2020-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2035-XX-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-19-WH-318Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-19-WH-326Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-19-WH-413Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2045-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-318Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-323G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-326Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-413Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2045-XX-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2047-11-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-14-WH-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-14-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-14-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-19-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2047-XX-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-13G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-13Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-18G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-18Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-213G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-213Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-218G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-218Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-223G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-226G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-226Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-22C-XX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-23G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-26G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-26Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-313G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-313Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-318G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-318Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-323G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-326Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-32C-XX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2050-XX-XX-54C-XX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-223G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-22C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2051-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-313G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-313Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-32C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2051-XX-54C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-13Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-223G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2057-XX-226G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-22C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-32C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2057-XX-54C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-223G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-226G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-22C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-32C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-54C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2058-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-24-XX-426Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-13Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-223G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-226G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-22C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-318G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-318Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-326G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	76.59	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-326Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-32C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-413G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-413Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-423G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-426G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2059-XX-XX-54C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2060-XX-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-223G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-226G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-226Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-22C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-26Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-313G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-313Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-32C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2060-XX-54C-XXX-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2061-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2061-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2062-24-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-24-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-24-XX-423G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-24-XX-426G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062--XX-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-318Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062--XX-XX-323G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-323Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-326G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	76.59	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-326Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-413Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-418Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-423G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-426G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-426Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2062-XX-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-413G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-413Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-418G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-418Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-423G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-426G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2068-XX-XX-426Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-413G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-413Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-418G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-418Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-423G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-426G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2069-XX-XX-426Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2072-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2072-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2074-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2086-XX-13Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2086-XX-213Q-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2125-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2125-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2130-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2135-XX-XX-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2135-XX-XX-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2140-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2144-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2144-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2149-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-418G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-418Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-423G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-426G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2154-XX-XX-426Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-418G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-418Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-423G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-426G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2156-XX-XX-426Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-418G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-418Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-423G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-426G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2158-XX-XX-426Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-318Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-323G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-326G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	76.59	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-326Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2161-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-413Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-418Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-423G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-426G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2161-XX-426Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-226G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-226Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-318G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-318Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-323G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-326G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	76.59	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2168-XX-326Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2168-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-413G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-413Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-418G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-418Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3987.4	60.6	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-423G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	8800.0	97.2	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-426G-XX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	102.12	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2169-XX-XX-426Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	5880.4	84.56	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2172-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2172-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2174-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-13G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-13Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-18G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2200-18Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-213G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-213Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-218G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-218Q-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-23G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2200-26G-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2245-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2245-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2281-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2283-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2283-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2300-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2310-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2310-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-22C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1299.9	19.46	66.8	N/A	0.575	4100.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-318Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2951.3	44.67	66.1	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-326Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	4577.5	65.29	70.11	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-32C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1971.0	29.9	65.9	N/A	0.6	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-413Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	3458.6	52.88	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2320-XX-XX-54C-ES3	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2982.3	44.23	67.4	N/A	0.638	4100.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	2510-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-313Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2609.4	39.72	65.7	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-323G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	6600.0	72.9	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	2510-326G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	76.59	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-24-17L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-24-217L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-36-225L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-36-25L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-48-232L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5010-48-32L-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-13G-XXX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-13Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-18G-XXX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-18Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-213Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-218Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5020-12-226Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-23G-XXX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-26G-XXX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-12-26Q-XXX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-24-17L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-24-217L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-36-225L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-36-25L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-48-232L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5020-48-32L-XXX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-27-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-27-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-39-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-39-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-51-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5027-51-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-25-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-25-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-37-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-37-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-49-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5028-49-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-25-17L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5029-25-217L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-37-125L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-37-225L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-37-25L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-49-132L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-49-232L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5029-49-32L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-25-17L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-25-217L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-37-225L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-37-25L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-49-232L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5038-49-32L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-27-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-27-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-39-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-39-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-51-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5057-51-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5060-24-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5060-36-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5060-48-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5080-24-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5080-39-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5080-51-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5150-26-17L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5150-26-217L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5150-38-225L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5150-38-25L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5150-50-232L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5150-50-32L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-27-17L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-27-217L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-39-225L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-39-25L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-51-232L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5281-51-32L-XX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-26-17L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-26-217L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-38-225L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-38-25L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-50-232L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5283-50-32L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-26-17L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-26-217L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-38-225L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-38-25L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-50-232L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5300-50-32L-XX-XXX-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5450-26-XX-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5450-26-XX-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5450-38-XX-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5450-38-XX-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5450-50-XX-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5450-50-XX-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-24-XX-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-24-XX-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-36-XX-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-36-XX-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-48-XX-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5460-48-XX-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-24-XX-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-24-XX-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-36-XX-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-36-XX-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-48-XX-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5461-48-XX-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-26-XX-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-26-XX-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-38-XX-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-38-XX-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-50-XX-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5542-50-XX-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-24-XX-17L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2018.0	30.76	65.6	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-24-XX-217L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1240.0	18.62	66.6	N/A	0.513	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-36-XX-225L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	3223.0	42.49	75.9	N/A	0.612	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-36-XX-25L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	1976.4	26.81	73.73	N/A	0.543	3000.0	84.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-48-XX-232L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	4573.43	52.4	88.46	N/A	0.587	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5550-50-XX-32L-ES4	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Wall Sconces	2674.33	33.4	80.07	N/A	0.594	3000.0	85.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5652-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5652-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5653-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5653-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5654-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5654-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5662-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5662-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5663-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5663-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5664-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5664-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5672-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5672-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5673-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5673-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5674-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5674-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5852-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5852-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5853-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5853-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5854-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5854-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5862-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	5862-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5863-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5863-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5864-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5864-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5872-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5872-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5873-XX-313G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2700.0	38.46	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5873-XX-318G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	5400.0	54.99	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5874-XX-413G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.28	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	5874-XX-418G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	7200.0	73.32	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7008-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7027-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7028-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7030-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7032-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7033-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7037-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7050-XX-213Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7050-XX-26Q-XX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7060-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7060-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7140-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7140-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7140-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7145-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7150-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7155-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7155-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7155-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7155-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7155-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7156-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7156-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7156-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7156-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7156-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7165-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7165-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7165-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7170-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7172-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7182-13G-XX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-13Q-XX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-18G-XX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-18Q-XX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-213Q-XX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-23G-XX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-23G-XX-XXX-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7182-26Q-XX-XXX-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7183-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7193-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7194-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7290-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7293-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7295-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7300-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7300-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7305-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7305-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7310-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7310-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7315-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7322-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7322-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7322-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7322-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7325-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7325-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-213G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.64	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-218G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	36.66	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-223G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	4400.0	48.6	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-226G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	3600.0	51.06	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7326-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-23G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	2200.0	24.3	71.6	N/A	0.566	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-26G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	25.53	73.4	N/A	0.551	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7326-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7504-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7562-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7562-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7563-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7577-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7577-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-13G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	900.0	12.82	65.6	N/A	0.578	2700.0	83.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-18G-ES3	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Decorative Pendant, Wall Sconces	1800.0	18.33	67.9	N/A	0.548	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7590-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7600-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7602-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7603-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7604-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7605-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7606-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7607-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7608-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7609-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7700-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7700-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7700-X-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7700-X-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7700-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7702-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7702-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7702-X-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7702-X-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7702-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7704-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7704-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7704-X-XX-218Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1993.7	30.3	65.8	N/A	0.579	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7704-X-XX-226Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	2940.2	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Brownlee Lighting	Brownlee Lighting	7704-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7710-X-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7710-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7710-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7710-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7712-X-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7712-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7712-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7712-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7714-X-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7714-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7714-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7714-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7716-X-XX-13Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	880.1	13.28	66.3	N/A	0.515	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7716-X-XX-18Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	957.6	14.37	66.6	N/A	0.524	2700.0	81.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7716-X-XX-213Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1729.3	26.44	65.4	N/A	0.603	2700.0	82.0	10000.0	3/14/2012		
Brownlee Lighting	Brownlee Lighting	7716-X-XX-26Q-ESX	Residential	Fluorescent	Bath Vanity, Ceiling Mount, Close to Ceiling Mount, Wall Sconces	1637.3	23.01	71.2	N/A	0.842	2700.0	80.0	10000.0	3/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buckingham Industrial Corporation	Hampton Bay	16031KIT-BK	Residential	Solid State	Accent Light Line-voltage	263.9	5.734	N/A	46.0	0.7815	3000.0	80.0	25000.0	5/23/2012		
Buckingham Industrial Corporation	Hampton Bay	16031KIT-WH	Residential	Solid State	Accent Light Line-voltage	263.9	5.734	N/A	46.0	0.7815	3000.0	80.0	25000.0	5/23/2012		
Buckingham Industrial Corporation	Hampton Bay	16033KIT-BK	Residential	Solid State	Accent Light Line-voltage	817.6	17.077	N/A	47.8	0.7815	3000.0	80.0	25000.0	5/23/2012		
Buckingham Industrial Corporation	Hampton Bay	16033KIT-WH	Residential	Solid State	Accent Light Line-voltage	817.6	17.077	N/A	47.8	0.7815	3000.0	80.0	25000.0	5/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1001-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1002-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1002-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1002-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-213	Residential	Fluorescent	Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-218	Residential	Fluorescent	Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-223	Residential	Fluorescent	Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1003-XX-226	Residential	Fluorescent	Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1004-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1004-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1004-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1005-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1005-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1036-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1036-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1038-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1038-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1038-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1040-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1040-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1048-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1048-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1048-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1049-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1049-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1049-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1051-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1051-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1067-XX-118	Residential	Fluorescent	Ceiling MountWall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1067-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1067-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G1117-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G1117-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2001-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-213-11	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-213-13	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-218-13	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2004-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2009-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2009-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2010-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2014-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2014-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2014-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2014-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2014-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2017-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2017-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2017-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2017-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2017-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2023-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2028-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2028-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2029-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2029-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2033-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2036-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2050-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2050-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2050-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2050-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2050-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2057-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2058-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2058-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2058-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2058-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2058-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2059-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2059-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2059-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2059-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2059-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2060-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2060-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2060-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2060-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2060-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2061-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2061-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2061-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2061-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2061-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2062-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2062-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2062-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G2062-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2062-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2063-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2063-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2063-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2063-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2063-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2064-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2064-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2064-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G2064-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G2064-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3001-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3001-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3001-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3021-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3021-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3021-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G3024-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3024-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3024-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3025-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G3104-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3104-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3104-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G3104-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3104-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3104-XX-226	Residential	Fluorescent	Bath Vanity;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3105-XX-226	Residential	Fluorescent	Bath Vanity;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G3106-XX-226	Residential	Fluorescent	Bath Vanity;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7001-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7002-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G7003-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7003-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7004-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7004-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7004-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7004-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7004-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7005-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7005-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7005-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7005-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7005-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7006-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7006-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7006-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7006-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7006-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7007-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7007-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7007-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7007-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7007-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7008-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7008-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7009-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7009-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7010-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G7010-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7014-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7015-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7016-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7016-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7016-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7016-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7016-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7017-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7017-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7017-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7017-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7017-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7021-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7031-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Buffalo Lite	Buffalo Lite	G7031-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7031-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Buffalo Lite	Buffalo Lite	G7033-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Canarm Ltd.	Canarm	EFP824117-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFP848132-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFV824217 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFV836125 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFW836225 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFW848232V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount;Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFW848432 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX824X17 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17CG 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17CG 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX824X17W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X17WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1160.0	17.0	73.95	N/A	0.523	3500.0	84.1	10000.0	4/2/2012		
Canarm Ltd.	Canarm	EFX824X17WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2240.0	34.0	73.45	N/A	0.514	3500.0	84.1	10000.0	4/9/2012		
Canarm Ltd.	Canarm	EFX824X32U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX824X32U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX836X25WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX836X25WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32A 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32A-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32AL 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32ALP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32AP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32B 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32B-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32BP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32C 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32C-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CG 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CG 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CGP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CS 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32CSP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32-D 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32E 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32G 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32GP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32O 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32OP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32P 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32PM 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32U 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32UP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32V 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32VP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32W 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32WH 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX848X32WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX848X32WP 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25ATD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25ATD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25BTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25BTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25GTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25GTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX872X25TD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1915.0	25.0	82.25	N/A	0.511	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX872X25TD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	3690.0	50.0	81.91	N/A	0.546	3500.0	83.5	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32ATD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32ATD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32BTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32BTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32GTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32GTD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	EFX896X32TD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	2920.0	32.0	94.78	N/A	0.875	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	EFX896X32TD 1st X: Represents feature W,S,T,D,R,V,U or B or P;2nd X: Means the number of fluorescent bulb: 1,2,3,4.	Residential	Fluorescent	Ceiling Mount,Wall Sconces	4890;9780	64;128	91.94	N/A	0.567	3500.0	84.2	10000.0	4/18/2012		
Canarm Ltd.	Canarm	FC9111RD	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9111SL	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9121SQ	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9131EU	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9131RD	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9132RD	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9141SL	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9141SQ	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9142SL	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9142SQ	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9171EU	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9172EU	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9192RD	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9192SQ	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9202SL	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC9212EU	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-01	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-02	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-03	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-04	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-05	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-06	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-07	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-08	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-09	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC922-10	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-01	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-02	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-03	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-04	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-05	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-06	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-07	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-08	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-09	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC92232-10	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-01	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-02	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-03	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-04	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-05	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-06	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-07	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-08	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	FC932-09	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC932-10	Residential	Fluorescent	Ceiling Mount	1695.0	32.0	76.17	N/A	0.599	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-01	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-02	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-03	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-04	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-05	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-06	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-07	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-08	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-09	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FC93240-10	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED130-ES	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED130-ESFL	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED170-ES	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED170-ESFL	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED210-ES	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLED210-ESFL	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR115-ES	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR115-ESFL	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR140-ES	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR140-ESFL	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR190-ES	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTR190-ESFL	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS125-ES	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS125-ESFL	Residential	Fluorescent	Ceiling Mount	1170.0	22.0	68.29	N/A	0.582	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS145-ES	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS145-ESFL	Residential	Fluorescent	Ceiling Mount	3010.0	54.0	70.7	N/A	0.594	4100.0	84.7	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS195-ES	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	FLTS195-ESFL	Residential	Fluorescent	Ceiling Mount	3385.0	72.0	76.46	N/A	0.605	4100.0	84.3	10000.0	4/6/2012		
Canarm Ltd.	Canarm	ICHANXXXM07713;ICHXXXM07713 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	6300.0	91.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM04413;ICHXXXM04413 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM04423;ICHXXXM04423 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM05513;ICHXXXM05513 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM05523;ICHXXXM05523 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	8000.0	115.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM06613;ICHXXXM06613 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	ICHANXXXM066 23;ICHXXXM066 23 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	9600.0	138.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM077 23;ICHXXXM077 23 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	11200.0	161.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM088 13;ICHXXXM088 13 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	7200.0	104.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM088 23;ICHXXXM088 23 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	12800.0	184.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM099 13;ICHXXXM099 13 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXM099 23;ICHXXXM099 23 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Chandelier	14400.0	207.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXMX 313;ICHXXXMX X313 "XXX"stands for number from 800-999;"M" Means A or B;Second two group of "XX"- 1st X - 0 to 3 and 2nd X - from 0 to 9	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICHANXXXMX 323;ICHXXXMX X323 "XXX"stands for number from 800-999;"M" Means A or B;Second two group of "XX"- 1st X - 0 to 3 and 2nd X - from 0 to 9	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICWYYYYU1113 "YYY"stands for number from 800-999.	Residential	Fluorescent	Ceiling mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICWYYYYU2213 "YYY"stands for number from 800-999.	Residential	Fluorescent	Ceiling mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICWYYYYU3313 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ICWYYYYU4413 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFLYYYAXX113;IFLYYYBXX113 "YYY"stands for number from 800-999;"XX" Means size 50-85.	Residential	Fluorescent	Floor Lamp	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	IFLYYYAXX123; IFLYYYBXX123 "YYY"stands for number from 800-999;"XX" Means size 50-85.	Residential	Fluorescent	Floor Lamp	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFLYYYAXX213; IFLYYYBXX213 "YYY"stands for number from 800-999;"XX" Means size 50-85.	Residential	Fluorescent	Floor Lamp	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFLYYYAXX223; IFLYYYBXX223 "YYY"stands for number from 800-999;"XX" Means size 50-85.	Residential	Fluorescent	Floor Lamp	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFLYYYAXX231 3;IFLYYYBXX2313 "YYY"stands for number from 800-999;"XX" Means size 50-85.	Residential	Fluorescent	Floor Lamp	2500.0	36.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY113 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 07-20.	Residential	Fluorescent	Ceiling mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY123 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 07-20.	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY213 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 11-20.	Residential	Fluorescent	Ceiling mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY223 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 13-20.	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY313 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 13-20	Residential	Fluorescent	Ceiling mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IFMXXMY323 "XXX"stands for number from 800-999;"M" Means A or B or C;"YY" Means size 15-20	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IOLXXU113 "XXX"stands for number from 800-999.	Residential	Fluorescent	Outdoor wall-mounted	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IOLXXU213 "XXX"stands for number from 800-999	Residential	Fluorescent	Outdoor wall-mounted	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IOLXXU313 "XXX"stands for number from 800-999	Residential	Fluorescent	Outdoor wall-mounted	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	IPLXXXM01113 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative pendant	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IPLXXXM01123 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative pendant	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IPLXXXM02213 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative Pendant	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IPLXXXM02223 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative Pendant	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IPLXXXM03313 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative Pendant	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IPLXXXM03323 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Decorative Pendant	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISFXXXM02213 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Close to ceiling count	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISFXXXM02223 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Close to ceiling count	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISFXXXM03313 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Close to ceiling count	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISFXXXM03323 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Close to ceiling count	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISTYYYYU2213 "YYY"stands for number from 800-999.	Residential	Fluorescent	Ceiling mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISTYYYYU3313 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISTYYYYU4413 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISTYYYYU5513 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ISTYYYYU6613 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITLYYYAAXX113; ITLYYYBXX113 "YYY"stands for number from 800-999;"XX" Means size 10-30.	Residential	Fluorescent	Table	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITLYYYAAXX123; ITLYYYBXX123 "YYY"stands for number from 800-999;"XX" Means size 10-30	Residential	Fluorescent	Table	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	ITLYYYAXX213; ITLYYYBXX213 "YYY"stands for number from 800-999;"XX" Means size 10-30.	Residential	Fluorescent	Table	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITLYYYAXX223; ITLYYYBXX223 "YYY"stands for number from 800-999;"XX" Means size 10-30.	Residential	Fluorescent	Table	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITYYYU2213 "YYY"stands for number from 800-999.	Residential	Fluorescent	Ceiling mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITYYYU3313 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITYYYU4413 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITYYYU5513 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	ITYYYU6613 "YYY"stands for number from 800-999	Residential	Fluorescent	Ceiling mount	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM01113 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM01123 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM02213 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM02223 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM03313 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM03323 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM04413 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM04423 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM05513 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXM05523 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	8000.0	115.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Canarm Ltd.	Canarm	IVLXXXM06613 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/15/2012		
Canarm Ltd.	Canarm	IVLXXXM06623 "XXX"stands for number from 800-999;"M" Means A or B.	Residential	Fluorescent	Bath vanity	9600.0	138.0	72.32	N/A	0.568	2700.0	82.1	10000.0	3/15/2012		
Can-Bramar Ltd.	Orr Lighting	S9051E15-xx-xx	Both	Solid State	Downlight Recessed	685.0 lm	13.28 W	N/A	51.47 lm/W	0.92	2700.0	83.0	35000.0	9/19/2012	Dimmable	S9051E15-xx-xx , the preceding xx(xx=MW, AB) represents different finish, the following xx (xx=27,30,40) represents differentCCT 2700K, 3000K, 4000K.
Can-Bramar Ltd.	Orr Lighting	S9051E21-xx-xx	Both	Solid State	Downlight Recessed	1061.7 lm	19.03 W	N/A	57.16 lm/W	0.966	2700.0	85.0	50000.0	9/19/2012	Dimmable	S9051E21-xx-xx , the preceding xx(xx=MW, AB) represents different finish, the following xx (xx=27,30,40) represents differentCCT 2700K, 3000K, 4000K.
Can-Bramar Ltd.	Orr Lighting	S9051N15-xx-xx	Both	Solid State	Downlight Recessed	682.3 lm	13.30 W	N/A	51.27 lm/W	0.917	2700.0	83.0	35000.0	9/19/2012	Dimmable	S9051N15-xx-xx , the preceding xx(xx=MW, AB) represents different finish, the following xx (xx=27,30,40) represents differentCCT 2700K, 3000K, 4000K.
Can-Bramar Ltd.	Orr Lighting	S9051N21-xx-xx	Both	Solid State	Downlight Recessed	1074.7 lm	18.58 W	N/A	58.01 lm/W	0.948	2700.0	83.0	50000.0	9/19/2012	Dimmable	S9051N21-xx-xx , the preceding xx (xx=MW, AB) represents different finish, the following xx (xx=27,30,40) represents differentCCT 2700K, 3000K, 4000K.
Capital Lighting Fixture Co.	Capital	1082BB-130-GU	Residential	Fluorescent	Bath Vanity	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1082BB-133-GU	Residential	Fluorescent	Bath Vanity	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	7/3/2012		
Capital Lighting Fixture Co.	Capital	1082MN-132-GU	Residential	Fluorescent	Bath Vanity	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1083BB-130-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1083BB-133-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	7/3/2012		
Capital Lighting Fixture Co.	Capital	1083MN-132-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1084BB-130-GU	Residential	Fluorescent	Bath Vanity	3600.0	52.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1084BB-133-GU	Residential	Fluorescent	Bath Vanity	3600.0	52.0	71.0	N/A	0.615	2700.0	82.0	10000.0	7/3/2012		
Capital Lighting Fixture Co.	Capital	1084MN-132-GU	Residential	Fluorescent	Bath Vanity	3600.0	52.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1162BB-297-GU	Residential	Fluorescent	Bath Vanity	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1162MN-117-GU	Residential	Fluorescent	Bath Vanity	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1163BB-297-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1163MN-117-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1165BB-297-GU	Residential	Fluorescent	Bath Vanity	4500.0	65.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1165MN-117-GU	Residential	Fluorescent	Bath Vanity	4500.0	65.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	1741-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	1742-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	1743-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Capital Lighting Fixture Co.	Capital	1744-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	1932-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	1941CZ-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2713MN-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2715BB-GU	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Capital Lighting Fixture Co.	Capital	2715MN-GU	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Capital Lighting Fixture Co.	Capital	2719MN-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2720BB-GU	Residential	Fluorescent	Decorative Pendant	3750.0	54.0	74.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	2720MN-GU	Residential	Fluorescent	Decorative Pendant	3750.0	54.0	74.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	2724BB-GU	Residential	Fluorescent	Decorative Pendant	4800.0	69.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	2724MN-GU	Residential	Fluorescent	Decorative Pendant	4800.0	69.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	2728BB-GU	Residential	Fluorescent	Decorative Pendant	6400.0	92.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/16/2012		
Capital Lighting Fixture Co.	Capital	2728MN-GU	Residential	Fluorescent	Decorative Pendant	6400.0	92.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/16/2012		
Capital Lighting Fixture Co.	Capital	2739MBZ-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2743BB-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2745BB-GU	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Capital Lighting Fixture Co.	Capital	2749BB-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	2749CS-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	3150BB-259-GU	Residential	Fluorescent	Decorative Pendant	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/8/2012		
Capital Lighting Fixture Co.	Capital	3150MN-224-GU	Residential	Fluorescent	Decorative Pendant	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/8/2012		
Capital Lighting Fixture Co.	Capital	3150MN-254-GU	Residential	Fluorescent	Decorative Pendant	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	7/3/2012		
Capital Lighting Fixture Co.	Capital	3787BB-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	4353BB-252-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4353MN-298-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4354BB-252-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4354MN-298-GU	Residential	Fluorescent	Chandelier	2700.0	39.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4356BB-252-GU	Residential	Fluorescent	Chandelier	5400.0	78.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4356MN-298-GU	Residential	Fluorescent	Chandelier	5400.0	78.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/15/2012		
Capital Lighting Fixture Co.	Capital	4359BB-252-GU	Residential	Fluorescent	Chandelier	8100.0	117.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	4359MN-298-GU	Residential	Fluorescent	Chandelier	8100.0	117.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	9051RI-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9052RI-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9053RI-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9057RI-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9059RI-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9061NB-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9062NB-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9063NB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9067NB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Capital Lighting Fixture Co.	Capital	9830BK-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9830TS-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9872BB-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9873BB-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9874BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9875BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9951BB-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9952BB-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9953BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9954BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9956BB-GU	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Capital Lighting Fixture Co.	Capital	9961BB-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9961BB-GU	Residential	Fluorescent	Wall Sconces	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/17/2012		
Capital Lighting Fixture Co.	Capital	9961BK-GU	Residential	Fluorescent	Porch Light	900.0	13.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9962BB-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9962BK-GU	Residential	Fluorescent	Porch Light	1250.0	18.0	74.09	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9963BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9963BK-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9966BB-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9966BK-GU	Residential	Fluorescent	Porch Light	1600.0	23.0	72.3	N/A	0.615	2700.0	82.0	10000.0	5/10/2012		Has Photo Sensor
Capital Lighting Fixture Co.	Capital	9968BB-GU	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Capital Lighting Fixture Co.	Capital	9968BK-GU	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.0	N/A	0.615	2700.0	82.0	10000.0	5/22/2012		
Chien Luen Industries, Co. Ltd., Inc.	Harbor Breeze	405016	Residential	Fluorescent	Ceiling Fan Light Kit	1200.0	18.0	72.07	N/A	0.539	2700.0	82.8	10000.0	9/20/2012		
Chien Luen Industries, Co. Ltd., Inc.	Harbor Breeze	405019	Residential	Fluorescent	Ceiling Fan Light Kit	1200.0	18.0	72.07	N/A	0.539	2700.0	82.8	10000.0	9/20/2012		
Conglom, Inc.	Luminus	C-UPR63M	Both	Solid State	Downlight Solid State Retrofit	1200.0	18.0	N/A	70.28	0.9885	3000.0	81.8	35000.0	10/18/2012	Dimmable	
Conglom, Inc.	Luminus	P-PR603	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	1100.0	18.0	N/A	62.61	0.9893	3000.0	81.8	50000.0	8/20/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	All Pro	AP706830WBST 24	Both	Solid State	Downlight Solid State Retrofit	729.0	13.9	N/A	52.3	0.96	3000.0	82.0	35000.0	10/5/2011	Dimmable	
Cooper Lighting a Division of Cooper Industries	All Pro	FSS1530LPCES	Residential	Solid State	Security	1354.0	20.8	65.2	N/A	0.9707	N/A	N/A	35000.0	9/24/2012		
Cooper Lighting a Division of Cooper Industries	All Pro	MS185	Residential	Halogen	Security	N/A	200.0	N/A	N/A	1.0	N/A	N/A	3000.0	6/22/2012		
Cooper Lighting a Division of Cooper Industries	All Pro	MS245R	Residential	Halogen	Security	N/A	200.0	N/A	N/A	1.0	N/A	N/A	3000.0	6/22/2012		
Cooper Lighting a Division of Cooper Industries	All Pro	MSS11315LES	Residential	Solid State	Security	1354.0	20.8	65.2	N/A	0.9707	N/A	N/A	35000.0	9/11/2012		
Cooper Lighting a Division of Cooper Industries	All Pro	MST18920LES	Residential	Solid State	Security	2236.0	30.7	72.8	N/A	0.991	N/A	N/A	35000.0	9/11/2012		Additionally qualified units are MST18920LWES and MST27920LES

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	All Pro	RL706827WBS	Both	Solid State	Downlight Solid State retrofit	731.0	14.4	N/A	50.9	0.944	2700.0	80.0	36000.0	6/4/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	All Pro	RL706830E26WBS	Both	Solid State	Downlight Solid State Retrofit	729.0	13.9	N/A	52.3	0.96	3000.0	82.0	35000.0	10/5/2011	Dimmable	
Cooper Lighting a Division of Cooper Industries	All Pro	RL706830WBS	Both	Solid State	Downlight Solid State Retrofit	729.0	13.9	N/A	52.3	0.96	3000.0	82.0	35000.0	10/5/2011	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1012D830MB	Commercial	Solid State	Under Cabinet Luminaire	338.2	5.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1012D830P	Commercial	Solid State	Under Cabinet Luminaire	338.2	5.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1012D830SN	Commercial	Solid State	Under Cabinet Luminaire	338.2	5.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1018D830MB	Commercial	Solid State	Under Cabinet Luminaire	507.3	7.5	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1018D830P	Commercial	Solid State	Under Cabinet Luminaire	507.3	7.5	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1018D830SN	Commercial	Solid State	Under Cabinet Luminaire	507.3	7.5	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1024D830MB	Commercial	Solid State	Under Cabinet Luminaire	676.4	10.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1024D830P	Commercial	Solid State	Under Cabinet Luminaire	676.4	10.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper	HU1024D830SN	Commercial	Solid State	Under Cabinet Luminaire	676.4	10.0	N/A	67.64	83.0	3000.0	83.0	50000.0	10/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	DLE217	Residential	Fluorescent	Ceiling Mount	2210.0	29.15	65.0	N/A	0.6	3000.0	80.0	10000.0	2/21/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	DLE232	Residential	Fluorescent	Ceiling Mount	4160.0	52.4	65.0	N/A	0.574	3000.0	80.0	10000.0	2/21/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	ECL432RLU	Residential	Fluorescent	Ceiling Mount	8368.0	112.0	65.0	N/A	0.5817	3000.0	80.0	10000.0	3/12/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	MS185D	Residential	Halogen	Security	N/A	200.0	N/A	N/A	N/A	N/A	N/A	N/A	9/26/2011		
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	MS185D/1	Residential	Halogen	Security	N/A	200.0	N/A	N/A	N/A	N/A	N/A	N/A	9/26/2011		
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	MS185DW	Residential	Halogen	Security	N/A	200.0	N/A	N/A	N/A	N/A	N/A	N/A	9/26/2011		
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	MS185DW/1	Residential	Halogen	Security	N/A	200.0	N/A	N/A	N/A	N/A	N/A	N/A	9/26/2011		
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	SL232	Residential	Fluorescent	Other	4279.0	60.02	65.0	N/A	0.588	3000.0	80.0	10000.0	2/9/2012		Luminaire does not ship with lamp; Qualified versions SLNR232R, SLWR232R, SL232RPC, SLNR232RCHR

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	WN217R	Residential	Fluorescent	Ceiling Mount	2235.0	33.0	65.0	N/A	0.544	3000.0	80.0	10000.0	3/12/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Cooper Lighting	WP232RNKL	Residential	Fluorescent	Ceiling Mount	4160.0	52.4	65.0	N/A	0.574	3000.0	80.0	10000.0	2/21/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Halo	EL405827	Both	Solid State	Downlight Recessed	596.0	13.9	N/A	43.0	0.92	2700.0	83.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	EL405830	Both	Solid State	Downlight Recessed	596.0	13.9	N/A	43.0	0.92	3000.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	EL405835	Both	Solid State	Downlight Recessed	596.0	13.9	N/A	43.0	0.92	3500.0	83.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	EL405840	Both	Solid State	Downlight Recessed	596.0	13.9	N/A	43.0	0.92	4000.0	81.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELG405830	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	3000.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELG405835	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	3500.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELG405840	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	4000.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELSG405830	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	3000.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELSG405835	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	3500.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ELSG405840	Both	Solid State	Downlight Recessed	637.0	13.7	N/A	46.5	0.92	4000.0	80.0	50000.0	3/19/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606827	Both	Solid State	Downlight Recessed	575.0	85.0	N/A	67.9	0.992	2700.0	81.0	50000.0	7/13/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606830	Both	Solid State	Downlight Recessed	580.0	8.8	N/A	65.9	0.906	3000.0	82.0	50000.0	7/12/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	Halo	ML5606835	Both	Solid State	Downlight Recessed	580.0	8.8	N/A	65.9	0.906	3500.0	83.0	50000.0	7/12/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606840	Both	Solid State	Downlight Recessed	580.0	8.8	N/A	65.9	0.906	4000.0	86.0	50000.0	7/12/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606927	Both	Solid State	Downlight Recessed	581.0	9.5	N/A	61.2	0.909	2700.0	93.5	50000.0	7/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606930	Both	Solid State	Downlight Recessed	580.0	9.8	N/A	59.2	0.99	3000.0	95.3	50000.0	7/30/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	Halo	ML5606935	Both	Solid State	Downlight Recessed	580.0	9.8	N/A	59.2	0.99	3500.0	94.2	50000.0	7/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5606940	Both	Solid State	Downlight Recessed	580.0	9.8	N/A	59.2	0.99	4000.0	94.0	50000.0	7/30/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	Halo	ML5609827	Both	Solid State	Downlight Recessed	594.0	12.2	N/A	48.7	0.909	2700.0	81.0	50000.0	7/12/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5609830	Both	Solid State	Downlight Recessed	585.0	13.1	N/A	44.7	0.988	3000.0	84.0	50000.0	7/13/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	Halo	ML5609835	Both	Solid State	Downlight Recessed	585.0	13.1	N/A	44.7	0.988	3500.0	83.0	50000.0	7/13/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5609840	Both	Solid State	Downlight Recessed	585.0	13.1	N/A	44.7	0.988	4000.0	84.0	50000.0	7/13/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5609927	Both	Solid State	Downlight Recessed	588.0	12.3	N/A	47.8	0.902	2700.0	92.9	50000.0	7/24/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5609930	Both	Solid State	Downlight Recessed	588.0	12.7	N/A	46.3	0.99	3000.0	95.6	50000.0	7/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	Halo	ML5609935	Both	Solid State	Downlight Recessed	588.0	12.7	N/A	46.3	0.99	3500.0	94.3	50000.0	7/24/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML5609940	Both	Solid State	Downlight Recessed	588.0	12.7	N/A	46.3	0.99	4000.0	94.1	50000.0	7/24/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML706 827	Both	Solid State	Downlight Recessed	665.0	14.0	N/A	47.4	0.95	2700.0	81.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML706 830	Both	Solid State	Downlight Recessed	665.0	14.0	N/A	47.4	0.95	3000.0	81.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML706 835	Both	Solid State	Downlight Recessed	665.0	14.0	N/A	47.4	0.95	3500.0	81.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML706 840	Both	Solid State	Downlight Recessed	665.0	14.0	N/A	47.4	0.95	4000.0	81.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML709 827	Both	Solid State	Downlight Recessed	854.0	14.9	N/A	52.3	0.96	2700.0	82.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML709 830	Both	Solid State	Downlight Recessed	854.0	14.9	N/A	52.3	0.96	3000.0	82.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML709 835	Both	Solid State	Downlight Recessed	854.0	14.9	N/A	52.3	0.96	3500.0	82.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML709 840	Both	Solid State	Downlight Recessed	854.0	14.9	N/A	52.3	0.96	4000.0	82.1	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML712 827	Both	Solid State	Downlight Recessed	1216.0	25.23	N/A	48.2	0.99	2700.0	81.7	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML712 830	Both	Solid State	Downlight Recessed	1216.0	25.23	N/A	48.2	0.99	3000.0	81.7	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML712 835	Both	Solid State	Downlight Recessed	1216.0	25.23	N/A	48.2	0.99	3500.0	81.7	50000.0	2/28/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	ML712 840	Both	Solid State	Downlight Recessed	1216.0	25.23	N/A	48.2	0.99	4000.0	81.7	50000.0	2/28/2012	Dimmable	



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	Halo	PD6H142E	Commercial	Fluorescent	Downlight Recessed	1858.0	43.0	N/A	42.0	0.998	2700.0	80.0	10000.0	3/12/2012		
Cooper Lighting a Division of Cooper Industries	Halo	PD6V142E	Commercial	Fluorescent	Downlight Recessed	1858.0	43.0	N/A	42.0	0.998	2700.0	80.0	10000.0	3/12/2012		
Cooper Lighting a Division of Cooper Industries	Halo	PD8H142E	Commercial	Fluorescent	Downlight Recessed	1858.0	43.0	N/A	42.0	0.998	2700.0	80.0	10000.0	3/12/2012		
Cooper Lighting a Division of Cooper Industries	Halo	PD8V142E	Commercial	Fluorescent	Downlight Recessed	1858.0	43.0	N/A	42.0	0.998	2700.0	80.0	10000.0	3/12/2012		
Cooper Lighting a Division of Cooper Industries	Halo	RL406830SN	Residential	Solid State	Downlight Solid State retrofit	580.16	9.78	N/A	59.35	0.996	3000.0	82.8	50000.0	3/9/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	RL406830WH	Both	Solid State	Downlight Solid State retrofit	637.0	13.7	N/A	46.5	0.9546	3000.0	83.0	50000.0	3/9/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Halo	RL560WH-R	Both	Solid State	Downlight Solid State retrofit	648.0	9.6	N/A	67.5	0.99	3000.0	84.0	50000.0	6/4/2012	Dimmable	Models RL560WH, RL560WH-R, RL560WH-C, RL560SN, RL560SN-R and RL560SN-C also Qualified
Cooper Lighting a Division of Cooper Industries	Iris	P3LED9 FL40 830	Both	Solid State	Downlight Recessed	947.0	19.2	N/A	49.3	0.94	3000.0	81.0	50000.0	5/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Iris	P3LED9 NFL25 830	Both	Solid State	Downlight Recessed	920.0	19.2	N/A	47.9	0.94	3000.0	81.0	50000.0	5/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Iris	P3LED9 NSP10 830	Both	Solid State	Downlight Recessed	969.0	19.2	N/A	50.4	0.94	3000.0	81.0	50000.0	5/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Iris	P3LED9 SP15 830	Both	Solid State	Downlight Recessed	984.0	19.2	N/A	51.2	0.94	3000.0	81.0	50000.0	5/30/2012	Dimmable	
Cooper Lighting a Division of Cooper Industries	Metalux	DT2U632OR	Residential	Fluorescent	Ceiling Mount	4352.0	56.9	65.0	N/A	0.662	3000.0	80.0	10000.0	8/14/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	DT2U632WH	Residential	Fluorescent	Ceiling Mount	4352.0	56.9	65.0	N/A	0.662	3000.0	80.0	10000.0	8/14/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	DT432OR	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	DT432WR	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	ECL432R	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	SNF217R	Residential	Fluorescent	Ceiling Mount	2402.0	35.1	65.0	N/A	1.0	3000.0	80.0	10000.0	4/5/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Metalux	SNF232R	Residential	Fluorescent	Ceiling Mount	4410.0	59.7	65.0	N/A	1.0	3000.0	80.0	10000.0	4/5/2012		Luminaire does not ship with lamp.
Cooper Lighting a Division of Cooper Industries	Metalux	WN432R	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	WP217R	Residential	Fluorescent	Ceiling Mount	1671.8	25.67	65.9	N/A	0.544	3000.0	84.0	10000.0	1/20/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	Metalux	WP217RNKL	Residential	Fluorescent	Ceiling Mount	1671.8	25.67	65.9	N/A	0.544	3000.0	84.0	10000.0	1/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	WSC432R	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	Metalux	WSC432RLP	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	CD6042E	Commercial	Fluorescent	Downlight Recessed	1878.0	40.86	N/A	46.0	0.99	2700.0	80.0	10000.0	10/25/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	CD6S142E	Commercial	Fluorescent	Downlight Recessed	2083.0	43.22	N/A	48.2	0.99	2700.0	80.0	10000.0	10/25/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	DT432ORLP	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	DT432UNRLP	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	DT432WRLP	Residential	Fluorescent	Ceiling Mount	7840.0	112.0	70.0	N/A	0.58	N/A	N/A	10000.0	3/20/2012		
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D010 ERM4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D010 ERM4 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D010 ERN4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D010 ERW4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D120 ERM4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D120 ERM4 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D120 ERN4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD409 D120 ERW4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD413 D010 ERM4 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD413 D010 ERN4 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD413 D010 ERW4 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD418 D010 ERM4 830 H	Both	Solid State	Downlight Recessed	1692.0	33.2	N/A	51.0	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD418 D010 ERM4 830 Li	Both	Solid State	Downlight Recessed	1692.0	33.2	N/A	51.0	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD418 D010 ERW4 830 H	Both	Solid State	Downlight Recessed	1688.0	33.0	N/A	51.2	0.986	3000.0	84.1	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD418 D010 ERW4 830 Li	Both	Solid State	Downlight Recessed	1688.0	33.0	N/A	51.2	0.986	3000.0	84.1	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERM6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERM6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERN6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERN6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERW6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D010 ERW6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERM6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERM6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERN6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERN6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERW6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD610 D120 ERW6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD615 D010 ERM6 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD615 D010 ERN6 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD615 D010 ERW6 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERM6 830 H	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERM6 830 Li	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERN6 830 H	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERN6 830 Li	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERW6 830 H	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LD620 D010 ERW6 830 Li	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ409 D010 ESQ4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ409 D120 ESQ4 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ413 D010 ESQ4 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ418 D010 ESQ4 830 H	Both	Solid State	Downlight Recessed	1688.0	33.0	N/A	51.2	0.986	3000.0	84.1	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ418 D010 ESQ4 830 Li	Both	Solid State	Downlight Recessed	1688.0	33.0	N/A	51.2	0.986	3000.0	84.1	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ610 D010 ESQ6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ610 D010 ESQ6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ610 D120 ESQ6 827 Li	Both	Solid State	Downlight Recessed	871.0	17.3	N/A	50.2	0.969	2700.0	83.1	50000.0	5/24/2012	Dimmable	Additional CCT's: 3000, 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ610 D120 ESQ6 830 H	Both	Solid State	Downlight Recessed	880.0	17.4	N/A	50.7	0.969	3000.0	82.3	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ615 D010 ESQ6 830 Li	Both	Solid State	Downlight Recessed	1173.0	24.0	N/A	48.8	0.994	3000.0	82.5	50000.0	5/24/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ620 D010 ESQ6 830 H	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	PORTFOLIO	LDSQ620 D010 ESQ6 830 Li	Both	Solid State	Downlight Recessed	1636.0	33.2	N/A	49.3	0.986	3000.0	84.5	50000.0	5/22/2012	Dimmable	Additional CCT's: 3500, 4000
Cooper Lighting a Division of Cooper Industries	Utilitec	384285	Residential	Fluorescent	Ceiling Mount	1671.8	25.67	65.9	N/A	0.544	3000.0	84.0	10000.0	1/20/2012		
Cooper Lighting a Division of Cooper Industries	Utilitec	WP217RNKLLU	Residential	Fluorescent	Ceiling Mount	1671.8	25.67	65.9	N/A	0.544	3000.0	84.0	10000.0	1/20/2012		
Cordelia Lighting Inc.	Commercial Electric	CER3E338CLP	Residential	Fluorescent	Downlight Recessed	900.0	13.0	N/A	69.2	0.558	2700.0	82.0	10000.0	6/6/2012		
Cordelia Lighting Inc.	Commercial Electric	CER3LICR3730-x	Both	Solid State	Downlight Recessed	465.0	7.7	N/A	61.0	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER473-X	Both	Solid State	Downlight Recessed	400.0	8.3	N/A	48.2	0.951	3000.0	83.0	36000.0	4/17/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER4741-x	Both	Solid State	Downlight Recessed	561.0	11.3	N/A	49.5	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER4742-x	Both	Solid State	Downlight Recessed	600.0	11.5	N/A	52.3	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cordelia Lighting Inc.	Commercial Electric	CER5741-x	Both	Solid State	Downlight Recessed	623.0	10.6	N/A	58.7	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER5742-x	Both	Solid State	Downlight Recessed	754.0	14.2	N/A	53.3	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER6730WH	Both	Solid State	Downlight Solid State Retrofit	731.0	10.5	N/A	69.0	0.9728	2700.0	80.1	35000.0	7/20/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER6731WH	Both	Solid State	Downlight Solid State Retrofit	1049.0	14.3	N/A	73.0	0.9554	3000.0	82.1	35000.0	7/20/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER673-X	Both	Solid State	Downlight Recessed	650.0	14.5	N/A	44.8	0.953	3000.0	83.0	36000.0	4/17/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER6741-x	Both	Solid State	Downlight Recessed	695.0	11.0	N/A	63.4	0.9	3000.0	83.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CER6742-x	Both	Solid State	Downlight Recessed	761.0	14.4	N/A	53.0	0.9	3000.0	82.0	36000.0	8/6/2012	Dimmable	
Cordelia Lighting Inc.	Commercial Electric	CESL401-06;CESL401-XX (Note: "06" denotes "white"; "XX" means "finish code".)	Residential	Fluorescent	Linear Strip	4570.0	64.0	88.46	N/A	0.587	2700.0	85.2	10000.0	4/20/2012		
Cordelia Lighting Inc.	Commercial Electric	CEW101-X (Note: "X" means "finish code".)	Residential	Fluorescent	Ceiling Mount	1650.0	34.0	65.9	N/A	0.544	3000.0	84.2	10000.0	9/25/2012		
Cordelia Lighting Inc.	Commercial Electric	CEW102-X (Note: "X" means "finish code".)	Residential	Fluorescent	Ceiling Mount	4150.0	64.0	81.3	N/A	0.567	3000.0	85.2	10000.0	9/25/2012		
Cordelia Lighting Inc.	Commercial Electric	CEW103-X (Note: "X" means "finish code".)	Residential	Fluorescent	Ceiling Mount	6615.0	96.0	81.32	N/A	0.565	3000.0	85.2	10000.0	9/25/2012		
Cordelia Lighting Inc.	Commercial Electric	CEW104-X (Note: "X" means "finish code".)	Residential	Fluorescent	Ceiling Mount	8160.0	128.0	81.4	N/A	0.623	3000.0	85.2	10000.0	9/25/2012		
Cordelia Lighting Inc.	Commercial Electric	HBSL-25G	Residential	Fluorescent	Linear Strip	5288.0	64.0	82.6	N/A	0.574	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Commercial Electric	HBSL-35	Residential	Fluorescent	Linear Strip	5288.0	64.0	82.6	N/A	0.574	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia	7101LPP-X	Residential	Fluorescent	Wrapped Lens	N/A	N/A	N/A	N/A	0.56	N/A	N/A	N/A	8/16/2012		
Cordelia Lighting Inc.	Cordelia	ES2461-FR-05	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.62	2700.0	N/A	10000.0	8/16/2012		
Cordelia Lighting Inc.	Cordelia Lighting	2861PLPC-X	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	4208ES-AL-x	Residential	Fluorescent	Chandelier	4500.0	65.0	69.23	N/A	0.558	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	4254ES-AL-x	Residential	Fluorescent	Chandelier	2700.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	52001ES-x	Residential	Fluorescent	Bath Vanity	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	52003ES-x	Residential	Fluorescent	Bath Vanity	2700.0	36.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	52005ES-x	Residential	Fluorescent	Bath Vanity	4500.0	65.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	DC032P	Residential	Fluorescent	Ceiling Mount	3958.33	56.45	70.14	N/A	0.638	4100.0	84.3	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1129P-x	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1208P-x	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1209P-x	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1230P-x	Residential	Fluorescent	Ceiling Mount	3958.33	56.45	70.14	N/A	0.638	4100.0	84.3	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1231-x	Residential	Fluorescent	Ceiling Mount	5940.0	75.0	71.3	N/A	0.986	3000.0	N/A	10000.0	6/6/2012		
Cordelia Lighting Inc.	Cordelia Lighting	HBF1232-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Cordelia Lighting	OBL50-X	Residential	Fluorescent	Linear Strip	7506.0	96.0	78.2	N/A	0.97	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Hampton Bay	DC018P	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1331P-x	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1337P-x	Residential	Fluorescent	Ceiling Mount	2982.3	96.0	67.7	N/A	0.638	4100.0	84.1	10000.0	6/6/2012		
Cordelia Lighting Inc.	Hampton Bay	CO1248HPF	Residential	Fluorescent	Ceiling Mount	7506.0	96.0	78.2	N/A	0.986	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Hampton Bay	HB7040LEDP-X	Residential	Solid State	Porch Light	267.3	10.57	25.3	N/A	0.981	N/A	N/A	36000.0	3/24/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cordelia Lighting Inc.	Hampton Bay	HB7041LEDP-X	Residential	Solid State	Porch Light	267.3	10.57	26.6	N/A	0.981	N/A	N/A	36000.0	3/24/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights
Cordelia Lighting Inc.	Hampton Bay	HB7042LEDP-X	Residential	Solid State	Porch Light	267.3	10.57	33.1	N/A	0.981	N/A	N/A	36000.0	3/24/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights
Cordelia Lighting Inc.	Hampton Bay	HB7043LEDP-X	Residential	Solid State	Porch Light	267.3	10.57	25.3	N/A	0.981	N/A	N/A	36000.0	3/24/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights
Cordelia Lighting Inc.	Hampton Bay	HB7044LEDP-X	Residential	Solid State	Porch Light	267.3	10.57	30.4	N/A	0.981	N/A	N/A	36000.0	3/24/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights
Cordelia Lighting Inc.	Hampton Bay	HB7051P-X	Residential	Solid State	Porch Light	333.0	8.32	40.0	N/A	0.843	3000.0	82.2	36000.0	3/28/2012		Qualified using SSL v1.3 for outdoor wall-mounted porch lights
Cordelia Lighting Inc.	Hampton Bay	HBF1143-06;HB F1143-XX (Note: "06" denotes "white"; "XX" means "finish code".)	Residential	Fluorescent	Ceiling Mount	4350.0	56.0	83.53	N/A	0.611	3500.0	82.3	10000.0	5/18/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1144-06;HB F1144-XX (Note: "06" denotes "white"; "XX" means "finish code".)	Residential	Fluorescent	Ceiling Mount	6630.0	84.0	84.51	N/A	0.564	4100.0	83.3	10000.0	5/22/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1330-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1332-X	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Hampton Bay	HBF1338-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	Hampton Bay	HBP1042P-x	Residential	Fluorescent	Torchieres	3200.0	48.0	72.0	N/A	0.6	2700.0	82.0	10000.0	2/14/2012		
Cordelia Lighting Inc.	World Imports	WI 7202-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	World Imports	WI7203-x	Residential	Fluorescent	Ceiling Mount	7506.0	96.0	78.2	N/A	0.986	3000.0	N/A	10000.0	5/30/2012		
Cordelia Lighting Inc.	World Imports	WI7204-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Cree, Inc.	Commerical Electric	CE-JB4-600L-27K-E26	Residential	Solid State	Downlight Solid State Retrofit	620.0	11.23	N/A	55.2	0.974	2700.0	81.7	35000.0	10/23/2012	Dimmable	
Cree, Inc.	Commerical Electric	CE-JB6-650L-27K-E26	Residential	Solid State	Downlight Solid State Retrofit	651.8	11.51	N/A	56.62	0.972	2700.0	80.2	35000.0	10/4/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-E26	Both	Solid State	Downlight Solid State Retrofit	585.5	9.231	N/A	63.43	0.901	2700.0	93.0	35000.0	4/19/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-E26	Commercial	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-E26-D	Both	Solid State	Downlight Solid State Retrofit	605.9	9.66	N/A	62.72	0.92	2700.0	92.0	35000.0	6/22/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-GU24	Both	Solid State	Downlight Solid State Retrofit	585.5	9.231	N/A	63.43	0.901	2700.0	93.0	35000.0	4/19/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-GU24	Commercial	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR4-575L-GU24-D	Both	Solid State	Downlight Solid State Retrofit	605.9	9.66	N/A	62.72	0.92	2700.0	92.0	35000.0	6/22/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR6-575L	Commercial	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	Cree, Inc	CR6-575L-GU24	Commercial	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	Cree, Inc	CR6-625L	Commercial	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR6-625L-GU24	Commercial	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR6-800L	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	
Cree, Inc.	Cree, Inc	CR6-800L-GU24	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	
Cree, Inc.	CREE, Inc.	CR6-575L	Commercial	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	CREE, Inc.	CR6-575L-GU24	Commercial	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	CREE, Inc.	KR6-13L-27K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	2700.0	92.0	36000.0	6/15/2012	Dimmable	Data representative of the following trims: A KXKR6TDJF & KXKR6TDJW

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	KR6-13L-27K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	2700.0	91.0	36000.0	6/12/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-13L-27K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	2700.0	92.0	36000.0	6/21/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-13L-27K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	2700.0	91.0	36000.0	6/18/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-13L-30K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	3000.0	N/A	36000.0	6/16/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-13L-30K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	3000.0	N/A	36000.0	6/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-13L-30K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	3000.0	N/A	36000.0	6/22/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-13L-30K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	3000.0	N/A	36000.0	6/19/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-13L-35K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	3500.0	N/A	36000.0	6/17/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-13L-35K-12 0V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	3500.0	N/A	36000.0	6/14/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-13L-35K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1040.0	17.59	N/A	59.1	0.99	3500.0	N/A	36000.0	6/23/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-13L-35K-27 7V	Commercial	Solid State	Commercial: Downlight Recessed	1060.0	17.58	N/A	60.3	0.99	3500.0	N/A	36000.0	6/20/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-27K-120 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	2700.0	93.0	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-9L-27K-120 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	2700.0	92.0	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-27K-277 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	2700.0	93.0	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-9L-27K-277 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	2700.0	92.0	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-30K-120 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	3000.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-9L-30K-120 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	3000.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-30K-277 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	3000.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-9L-30K-277 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	3000.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-35K-120 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	3500.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	KR6-9L-35K-120 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	3500.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	KR6-9L-35K-277 V	Commercial	Solid State	Downlight Recessed	667.0	12.32	N/A	54.1	0.982	3500.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDJF & KXKR6TDJW
Cree, Inc.	CREE, Inc.	KR6-9L-35K-277 V	Commercial	Solid State	Downlight Recessed	685.0	12.31	N/A	55.7	0.982	3500.0	N/A	36000.0	9/13/2012	Dimmable	Data representative of the following trims:Â KXKR6TDMF & KXKR6TDMW
Cree, Inc.	CREE, Inc.	LR4E-15	Both	Solid State	Downlight Solid State Retrofit	605.8	10.76	N/A	56.3	0.96	2700.0	93.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR4E-15C	Both	Solid State	Downlight Solid State Retrofit	635.0	11.2	N/A	56.7	0.964	3500.0	92.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR4E-30	Both	Solid State	Downlight Solid State Retrofit	481.3	11.19	N/A	43.0	0.962	2700.0	93.0	35000.0	2/3/2012	Dimmable	
Cree, Inc.	CREE, Inc.	LR4E-30C	Both	Solid State	Downlight Solid State Retrofit	565.9	10.98	N/A	51.5	0.965	3500.0	92.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6	Both	Solid State	Downlight Solid State Retrofit	658.8	10.68	N/A	61.7	0.963	2700.0	93.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6-10L-27K-12 0V-A-DR	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	2700.0	93.0	36000.0	5/17/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-27K-12 0V-A-DR-US	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	2700.0	93.0	36000.0	5/17/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-30K-12 0V-A-DR	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	3000.0	93.0	36000.0	11/21/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-30K-12 0V-A-DR-US	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	3000.0	93.0	36000.0	11/21/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-35K-12 0V-A-DR	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	3500.0	93.0	36000.0	5/17/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-35K-12 0V-A-DR-US	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	3500.0	93.0	36000.0	5/17/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-40K-12 0V-A-DR	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	4000.0	93.0	36000.0	11/21/2012		
Cree, Inc.	CREE, Inc.	LR6-10L-40K-12 0V-A-DR-US	Both	Solid State	Residential: Downlight Solid State Retrofit, Commercial: Downlight Solid State Retrofit	1006.0	10.74	N/A	93.7	0.972	4000.0	93.0	36000.0	11/21/2012		
Cree, Inc.	CREE, Inc.	LR6-277V	Both	Solid State	Downlight Solid State Retrofit	656.5	10.82	N/A	60.7	0.932	2700.0	92.0	35000.0	12/27/2011		
Cree, Inc.	CREE, Inc.	LR6C	Both	Solid State	Downlight Solid State Retrofit	643.6	10.04	N/A	64.1	0.961	3500.0	95.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6C-277V	Both	Solid State	Downlight Solid State Retrofit	659.4	10.66	N/A	61.9	0.932	3500.0	91.0	35000.0	12/27/2011		
Cree, Inc.	CREE, Inc.	LR6C-DR1000	Both	Solid State	Downlight Solid State Retrofit	970.5	12.38	N/A	78.4	0.971	3500.0	94.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6C-DR1000-277V	Both	Solid State	Downlight Solid State Retrofit	967.8	13.75	N/A	70.4	0.957	3500.0	92.0	35000.0	12/27/2011		
Cree, Inc.	CREE, Inc.	LR6C-DR650	Both	Solid State	Downlight Solid State Retrofit	646.1	11.86	N/A	54.5	0.969	3500.0	91.0	35000.0	12/27/2011	Dimmable	



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	LR6C-GU24	Both	Solid State	Downlight Solid State Retrofit	643.6	10.04	N/A	64.1	0.961	3500.0	95.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6-DR1000	Both	Solid State	Downlight Solid State Retrofit	992.1	12.48	N/A	79.5	0.967	2700.0	92.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6-DR1000-277V	Both	Solid State	Downlight Solid State Retrofit	1012.0	12.29	N/A	82.3	0.942	2700.0	93.0	35000.0	12/27/2011		
Cree, Inc.	CREE, Inc.	LR6-DR650	Both	Solid State	Downlight Solid State Retrofit	666.8	10.93	N/A	61.0	0.966	2700.0	92.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	LR6-GU24	Both	Solid State	Downlight Solid State Retrofit	658.8	10.68	N/A	61.7	0.963	2700.0	93.0	35000.0	12/27/2011	Dimmable	
Cree, Inc.	CREE, Inc.	SR6E-12L-A-30K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1225.0	15.91	N/A	77.0	0.99	3000.0	93.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-12L-A-30K / SR6T-45-SSGGR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	680.0	15.9	N/A	42.8	0.99	3000.0	94.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-45-SSGGR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	SR6E-12L-A-35K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1225.0	15.91	N/A	77.0	0.99	3500.0	93.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-12L-A-35K / SR6T-45-SSGGR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	680.0	15.9	N/A	42.8	0.99	3500.0	94.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-45-SSGGR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-12L-A-40K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1225.0	15.91	N/A	77.0	0.99	4000.0	93.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	SR6E-12L-A-40K / SR6T-45-SSGBR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	680.0	15.9	N/A	42.8	0.99	4000.0	94.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-45-SSGBR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGBR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-18L-A-30K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1824.0	23.3	N/A	78.3	0.99	3000.0	95.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGBR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-18L-A-30K / SR6T-45-SSGBR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1028.0	23.27	N/A	44.2	0.99	3000.0	95.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-45-SSGBR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGBR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	CREE, Inc.	SR6E-18L-A-35K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1824.0	23.3	N/A	78.3	0.99	3500.0	95.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-18L-A-35K / SR6T-45-SSGGR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1028.0	23.27	N/A	44.2	0.99	3500.0	95.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-45-SSGGR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-18L-A-40K / SR6T-30-C / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1824.0	23.3	N/A	78.3	0.99	4000.0	95.0	36000.0	7/30/2012	Dimmable	Note - Data represents the following reflector / PSU combination: SR6T-30-C / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGGR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
																Note - Data represents the following reflector / PSU combination: SR6T-45-SSGBR / SR6H-A-120V. The performance of the following reflectors will be between the SR6T-30-C and the SR6T-45-SSGBR: SR6T-XX-W, SR6T-XX-GR, SR6T-XX-BR, SR6T-XX-CG, SR6T-XX-PE, SR6T-XX-WH, SR6T-XX-WM, SR6T-XX-SSGC, SR6T-XX-SSGGR, SR6T-XX-SSGCG, SR6T-XX-SSGPE, SR6T-XX-SSGWH where XX is 30 or 45 degrees. The photometric performance for 120V and 277V is the same
Cree, Inc.	CREE, Inc.	SR6E-18L-A-40K / SR6T-45-SSGBR / SR6H-A-120V	Commercial	Solid State	Downlight Recessed	1028.0	23.27	N/A	44.2	0.99	4000.0	95.0	36000.0	7/30/2012	Dimmable	
Cree, Inc.	e-conolight	ECO20-120V-3K-WH	Both	Solid State	Downlight Solid State Retrofit	691.0	15.7	N/A	44.0	0.945	3000.0	82.0	36000.0	11/12/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L	Residential	Solid State	Downlight Recessed	598.9	8.805	N/A	68.01	0.901	2700.0	93.0	25000.0	1/5/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L	Residential	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-CA	Residential	Solid State	Downlight Recessed	598.9	8.805	N/A	68.01	0.901	2700.0	93.0	25000.0	1/5/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-CA	Residential	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-GU24	Residential	Solid State	Downlight Recessed	598.9	8.805	N/A	68.01	0.901	2700.0	93.0	25000.0	1/5/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-GU24	Residential	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-GU24-CA	Commercial	Solid State	Downlight Recessed	598.9	8.805	N/A	68.01	0.901	2700.0	93.0	35000.0	1/5/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-GU24-CA	Residential	Solid State	Downlight Recessed	598.9	8.805	N/A	68.01	0.901	2700.0	93.0	25000.0	1/5/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO4-575L-GU24-CA	Residential	Solid State	Downlight Solid State Retrofit	589.7	8.428	N/A	69.97	0.92	2700.0	92.0	35000.0	7/25/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L	Residential	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L	Residential	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L	Residential	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-50K	Residential	Solid State	Downlight Solid State Retrofit	625.0	8.77	N/A	71.26	0.918	5000.0	89.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-50K-CA	Residential	Solid State	Downlight Solid State Retrofit	625.0	8.77	N/A	71.26	0.918	5000.0	89.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-50K-GU24	Residential	Solid State	Downlight Solid State Retrofit	625.0	8.77	N/A	71.26	0.918	5000.0	89.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-CA	Residential	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-CA	Residential	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-CA	Residential	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24	Residential	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24	Residential	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24	Residential	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24-CA	Residential	Solid State	Downlight Recessed	582.2	8.417	N/A	69.17	0.828	2700.0	92.7	35000.0	3/28/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24-CA	Residential	Solid State	Downlight Solid State Retrofit	591.2	9.226	N/A	64.08	0.901	2700.0	93.0	35000.0	9/19/2011	Dimmable	
Cree, Inc.	EcoSmart	ECO-575L-GU24-CA	Residential	Solid State	Downlight Solid State Retrofit	623.0	9.59	N/A	64.96	0.926	2700.0	92.4	35000.0	10/4/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-800L	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-800L-CA	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Cree, Inc.	EcoSmart	ECO-800L-GU24	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	
Cree, Inc.	EcoSmart	ECO-800L-GU24-CA	Both	Solid State	Downlight Recessed	877.3	12.438	N/A	70.53	0.909	2700.0	92.8	35000.0	2/1/2012	Dimmable	
Designers Fountain, Inc.	Designers Fountain	ES1161-X	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES1257L-x	Residential	Fluorescent	Ceiling Mount	1800.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES1257M-x	Residential	Fluorescent	Ceiling Mount	1800.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES1257S-X	Residential	Fluorescent	Ceiling Mount	1800.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2301-x	Residential	Fluorescent	Porch Light	1380.0	18.0	80.0	N/A	0.578	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2370-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2371-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2375-x	Residential	Fluorescent	Ceiling Mount	1297.3	19.43	66.8	N/A	0.59	2700.0	84.0	10000.0	6/6/2012		
Designers Fountain, Inc.	Designers Fountain	ES2381-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2391-x	Residential	Fluorescent	Porch Light	1380.0	18.0	80.0	N/A	0.578	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2394-x	Residential	Fluorescent	Close to Ceiling Mount	1380.0	18.0	80.0	N/A	0.578	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES2861-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES30511-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES30521-x	Residential	Fluorescent	Porch Light	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES30531-X	Residential	Fluorescent	Porch Light	1380.0	18.0	80.0	N/A	0.578	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES30534-x	Residential	Fluorescent	Close to Ceiling Mount	900.0	13.0	69.23	N/A	0.5579	2700.0	82.0	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES31921-X	Residential	Solid State	Porch Light	900.0	13.0	69.23	N/A	0.615	N/A	N/A	10000.0	5/16/2012		
Designers Fountain, Inc.	Designers Fountain	ES31931-X	Residential	Solid State	Porch Light	900.0	13.0	69.23	N/A	0.615	N/A	N/A	10000.0	5/16/2012		
Designers Fountain, Inc.	Designers Fountain	ES32021-X	Residential	Solid State	Porch Light	900.0	13.0	69.23	N/A	0.615	N/A	N/A	10000.0	5/16/2012		
Designers Fountain, Inc.	Designers Fountain	ES32031-X	Residential	Solid State	Porch Light	900.0	13.0	69.23	N/A	0.615	N/A	N/A	10000.0	5/16/2012		
Designers Fountain, Inc.	Designers Fountain	ES82223-x	Residential	Fluorescent	Ceiling Mount	7506.0	96.0	78.2	N/A	0.986	3000.0	N/A	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES82323-x	Residential	Fluorescent	Ceiling Mount	7506.0	96.0	78.2	N/A	0.986	3000.0	N/A	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	ES82423-x	Residential	Fluorescent	Ceiling Mount	10008.0	96.0	78.2	N/A	0.51	3000.0	N/A	10000.0	5/30/2012		
Designers Fountain, Inc.	Designers Fountain	LED21321-ABP	Residential	Solid State	Porch Light	236.0	9.0	27.0	N/A	1.0	3000.0	81.0	35000.0	10/14/2011		Data is to SSL V1.3 for outdoor porch category extension (col S). SSL source is inseperable and will not match choices in (col AI). TM-21 proj in column BB instead of Estar min req.
Designers Fountain, Inc.	Designers Fountain	LED21331-ABP	Residential	Solid State	Porch Light	349.0	11.0	32.0	N/A	1.0	3000.0	80.0	35000.0	10/14/2011		Data is to SSL V1.3 for outdoor porch category extension (col S). SSL source is inseperable and will not match choices in (col AI). TM-21 proj in column BB instead of Estar min req.
Designers Fountain, Inc.	Designers Fountain	RTL47301-X	Both	Solid State	Downlight Recessed	400.0	8.3	N/A	48.2	0.951	3000.0	83.0	36000.0	4/17/2012	Dimmable	
Designers Fountain, Inc.	Designers Fountain	RTL67301-X	Both	Solid State	Downlight Recessed	650.0	14.5	N/A	44.8	0.953	3000.0	83.0	36000.0	4/17/2012	Dimmable	
Designers Fountain, Inc.	Designers Fountain	S116M2S-XX (Note: "XX" means "finish code".)	Residential	Fluorescent	Ceiling Mount	4350.0	56.0	83.53	N/A	0.611	3500.0	82.3	10000.0	5/18/2012		
Designers Fountain, Inc.	Designers Fountain	S116M3S-XX (Note: "XX" means "finish code".)	Residential	Fluorescent	Ceiling Mount	6630.0	84.0	84.51	N/A	0.564	4100.0	83.3	10000.0	5/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Designers Fountain, Inc.	Designers Fountain	WA232120MPF	Residential	Fluorescent	Ceiling Mount	5288.0	64.0	82.6	N/A	0.574	3000.0	N/A	10000.0	5/30/2012		
Design Solutions International Inc	Mainstays	13717	Residential	Fluorescent	Torchieres	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/5/2012		
Digital Lighting, Inc.	Q-RAY	MP-400	Both	Solid State	Portable Desk Task Light	250.0	7.0	N/A	38.0	1.0	3000.0	84.0	36000.0	10/12/2012		
Digital Lighting, Inc.	Q-RAY	QDL05-USW-27G24E	Both	Solid State	Downlight Solid State Retrofit	571.0	12.0	N/A	49.0	0.9	2700.0	82.0	36000.0	9/27/2012	Dimmable	
Digital Lighting, Inc.	Q-RAY	QDL05-USW-30G24E	Both	Solid State	Downlight Solid State Retrofit	571.0	12.0	N/A	49.0	0.9	2700.0	82.0	36000.0	9/27/2012	Dimmable	
Digital Lighting, Inc.	Q-RAY	QDL06-USW-27G24E	Both	Solid State	Downlight Solid State Retrofit	571.0	12.0	N/A	49.0	0.9	2700.0	82.0	36000.0	9/27/2012	Dimmable	
Digital Lighting, Inc.	Q-RAY	QDL06-USW-30G24E	Both	Solid State	Downlight Solid State Retrofit	571.0	12.0	N/A	49.0	0.9	2700.0	82.0	36000.0	9/27/2012	Dimmable	
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	PL-PF2A;RL-WA2A	Residential	Fluorescent	Linear Strip	4065.0	64.0	79.61	N/A	0.613	3000.0	85.2	10000.0	7/2/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	RL-V001C1;RL-M001C1;RL-R001C1;RL-S001C1;RL-C001C1;JR-002 C2	Residential	Fluorescent	Ceiling Mount, Residential Portable Desk Task Light	1250.0	22.0	65.84	N/A	0.597	4100.0	83.3	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	RL-V001P2;RL-M001P2;RL-R001P2;RL-R002P2;RL-V002P2;JR-002 P2;RL-S001P2;RL-C001P2 RL-S001P2; RL-C001P2	Residential	Fluorescent	Ceiling Mount, Residential Portable Desk Task Light	1360.0	26.0	65.45	N/A	0.574	4100.0	80.9	10000.0	7/2/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	RL-V002C2;RL-M002C2;RL-R002C2;RL-S002C2;RL-C001C2;JR-003 C2	Residential	Fluorescent	Ceiling Mount, Residential Portable Desk Task Light	3040.0	54.0	67.96	N/A	0.584	4100.0	83.2	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	RL-V003C2;RL-M003C2;RL-R003C2;RL-S003C2;RL-C003C2	Residential	Fluorescent	Ceiling Mount, Residential Portable Desk Task Light	4360.0	72.0	71.05	N/A	0.607	4100.0	83.1	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	RL-WA4A;PL-PF4A	Residential	Fluorescent	Linear Strip	8130.0	128.0	79.61	N/A	0.613	3000.0	85.2	10000.0	7/2/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	ST48D-120	Residential	Fluorescent	Linear Strip	4065.0	64.0	79.61	N/A	0.613	3000.0	85.2	10000.0	7/2/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	ST48S-120	Residential	Fluorescent	Linear Strip	2130.0	32.0	77.24	N/A	0.609	3000.0	85.2	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UC-18B; UC-18BC	Both	Fluorescent	Under Cabinet Luminaire	445.0	11.0	N/A	35.93	0.9838	4100.0	84.7	10000.0	6/13/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UC-22B; UC-22BC	Both	Fluorescent	Under Cabinet Luminaire	555.0	14.0	N/A	41.74	0.9858	4100.0	83.4	10000.0	6/13/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UC-34B; UC-34BC	Both	Fluorescent	Under Cabinet Luminaire	830.0	21.0	N/A	35.87	0.9944	4100.0	81.4	10000.0	6/13/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UC-42S (UEB42); UC-42	Residential	Fluorescent	Under Cabinet Luminaire	1200.0	26.0	N/A	49.68	0.549	4100.0	84.6	10000.0	6/13/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UC-46B; UC-46BC	Both	Fluorescent	Under Cabinet Luminaire	1030.0	28.0	N/A	38.81	0.9948	4100.0	80.2	10000.0	6/13/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UD13-120A;UC-21S (UEB21);UC-21	Residential	Fluorescent	Under Cabinet Luminaire	355.0	13.0	N/A	31.57	0.5624	4100.0	84.6	10000.0	7/3/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UD16-120A;UC-24S (UEB24);UC-24	Residential	Fluorescent	Under Cabinet Luminaire	500.0	16.0	N/A	33.44	0.515	4100.0	84.9	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UD21-120A;UC-33S (UEB33);UC-33	Residential	Fluorescent	Under Cabinet Luminaire	570.0	21.0	N/A	30.83	0.5473	4100.0	84.9	10000.0	7/3/2012		
DJL Electric Device (Shanghai) Co., Ltd.	djllighting	UD8-120A;UC-12S (UEB12);UC-12	Residential	Fluorescent	Under Cabinet Luminaire	270.0	8.0	N/A	36.59	0.5161	4100.0	84.9	10000.0	7/2/2012		
DMF Lighting	dmfLighting	DH6ICAQ/GU24	Residential	Fluorescent	Downlight Recessed	1800.0	27.0	N/A	66.7	0.551	2700.0	82.0	10000.0	5/16/2012		
DMF Lighting	dmfLighting	DM10XXX	Both	Solid State	Downlight Recessed	941.0	14.5	N/A	64.9	0.956	3000.0	93.0	36000.0	5/16/2012		
DMF Lighting	dmfLighting	DM6XXX	Both	Solid State	Downlight Recessed	572.9	10.51	N/A	54.5	0.958	2700.0	91.0	36000.0	5/16/2012		
DMF Lighting	DMF Lighting	DMC10XXX	Both	Solid State	Downlight Recessed	1000.0	17.5	N/A	57.1	0.975	2700.0	82.0	36000.0	2/2/2012	Dimmable	xx can be any combination of numbers and letters, CCT - 2700-4100K
DMF Lighting	DMF Lighting	DMC7XXX	Both	Solid State	Downlight Recessed	700.0	12.5	N/A	56.0	0.947	2700.0	81.0	36000.0	2/2/2012	Dimmable	xx can be any combination of numbers and letters, CCT - 2700-4100K
DMF Lighting	DMF Lighting	DME11-X-XX	Both	Solid State	Downlight Recessed	1000.0	17.5	N/A	57.1	0.975	2700.0	82.0	36000.0	2/2/2012	Dimmable	xx can be any combination of numbers and letters, CCT - 2700-4100K
DMF Lighting	DMF Lighting	DME800-X-XX	Both	Solid State	Downlight Recessed	700.0	12.5	N/A	56.0	0.947	2700.0	81.0	36000.0	2/2/2012	Dimmable	xx can be any combination of numbers and letters, CCT - 2700-4100K
Dolan Designs	Design Classics	JJ 2961ES-X/ALB	Residential	Fluorescent	Ceiling Mount	586.283	12.15	48.266	N/A	0.574	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 2961ES-X/OP	Residential	Fluorescent	Ceiling Mount	616.749	12.36	49.895	N/A	0.579	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 2962ES-X/ALB	Residential	Fluorescent	Ceiling Mount	1279.534	23.92	53.49	N/A	0.57	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 2962ES-X/OP	Residential	Fluorescent	Ceiling Mount	1164.478	23.78	48.963	N/A	0.569	2700.0	81.0	10000.0	8/22/2012		
Dolan Designs	Design Classics	JJ 3045ES-1-X	Residential	Fluorescent	Other	575.187	12.37	46.508	N/A	0.575	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 322ES-1-X	Residential	Fluorescent	Other	443.071	13.08	33.881	N/A	0.577	2700.0	82.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 493ES-1-X/HG	Residential	Fluorescent	Other	544.914	21.26	25.633	N/A	0.54	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 495ES-1-X/HG	Residential	Fluorescent	Other	302.367	13.02	23.217	N/A	0.579	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 497ES-1-X/HG	Residential	Fluorescent	Other	541.638	21.4	25.304	N/A	0.539	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 49856ES-1-X	Residential	Fluorescent	Other	405.536	11.45	35.399	N/A	0.567	2700.0	79.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 501ES-1-X	Residential	Fluorescent	Other	421.5	12.9	32.682	N/A	0.577	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 671ES-X	Residential	Fluorescent	Wall Sconces	928.776	13.39	69.363	N/A	0.585	2700.0	82.0	10000.0	9/10/2012		
Dolan Designs	Design Classics	JJ 672ES-X	Residential	Fluorescent	Wall Sconces	1928.711	27.0	71.433	N/A	0.582	2700.0	82.0	10000.0	9/10/2012		
Dolan Designs	Design Classics	JJ 673ES-X	Residential	Fluorescent	Wall Sconces	3360.526	39.71	84.634	N/A	0.581	2700.0	85.0	10000.0	9/10/2012		
Dolan Designs	Design Classics	JJ761ES-X	Residential	Fluorescent	Ceiling Mount	849.541	22.41	37.914	N/A	0.573	2700.0	79.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ762ES-X	Residential	Fluorescent	Ceiling Mount	1095.795	23.6	46.425	N/A	0.568	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ763ES-X	Residential	Fluorescent	Ceiling Mount	1689.386	39.63	42.628	N/A	0.542	2700.0	79.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ765ES-X	Residential	Fluorescent	Ceiling Mount	1549.934	34.33	45.139	N/A	0.576	2700.0	79.0	10000.0	9/10/2012		
Dolan Designs	Design Classics	JJ 766ES-X	Residential	Fluorescent	Other	2892.588	40.23	71.901	N/A	0.584	2700.0	82.0	10000.0	9/10/2012		
Dolan Designs	Design Classics	JJ 768ES-X	Residential	Fluorescent	Other	1523.794	25.15	60.58	N/A	0.577	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 769ES-X	Residential	Fluorescent	Other	2104.764	36.34	57.924	N/A	0.569	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 770ES-X	Residential	Fluorescent	Other	3459.042	60.53	57.143	N/A	0.577	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 911ES-MF/X	Residential	Fluorescent	Ceiling Mount	575.0	12.44	46.222	N/A	0.577	2700.0	80.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 913ES-MF/X	Residential	Fluorescent	Ceiling Mount	1055.905	23.27	45.382	N/A	0.568	2700.0	79.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 915ES-MF/X	Residential	Fluorescent	Ceiling Mount	1797.564	38.94	46.159	N/A	0.538	2700.0	78.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 9204ES-1-X	Residential	Fluorescent	Other	547.384	12.64	43.303	N/A	0.577	2700.0	81.0	10000.0	8/23/2012		
Dolan Designs	Design Classics	JJ 9711ES-2-X	Residential	Fluorescent	Other	291.751	12.1	24.104	N/A	0.569	2700.0	81.0	10000.0	10/17/2012		
Dolan Designs	Design Classics	JJ 9713ES-2-X	Residential	Fluorescent	Other	572.994	16.29	35.833	N/A	0.549	2700.0	80.0	10000.0	10/17/2012		
Dolan Designs	Design Classics	JJ 9715ES-2-X	Residential	Fluorescent	Other	532.751	16.45	32.392	N/A	0.544	2700.0	81.0	10000.0	10/17/2012		
Dolan Designs	Design Classics	JJ 9716ES-2-X	Residential	Fluorescent	Other	309.456	16.94	18.264	N/A	0.552	2700.0	81.0	10000.0	10/17/2012		
Dolan Designs	Dolan Designs	9201-68	Residential	Fluorescent	Other	319.038	11.9	26.802	N/A	0.58	2700.0	81.0	10000.0	7/27/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Dolan Designs	Dolan Designs	9203-68	Residential	Fluorescent	Other	579.973	16.0	36.238	N/A	0.545	2700.0	82.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9205-68	Residential	Fluorescent	Other	667.237	16.28	40.977	N/A	0.548	2700.0	82.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9206-68	Residential	Fluorescent	Other	516.79	16.03	32.245	N/A	0.546	2700.0	82.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9710-68	Residential	Fluorescent	Other	402.039	15.96	25.195	N/A	0.544	2700.0	83.0	10000.0	7/26/2012		
Dolan Designs	Dolan Designs	9713-68	Residential	Fluorescent	Other	440.627	16.1	27.363	N/A	0.547	2700.0	83.0	10000.0	7/26/2012		
Dolan Designs	Dolan Designs	9715-68	Residential	Fluorescent	Other	375.981	16.16	23.26	N/A	0.546	2700.0	83.0	10000.0	7/26/2012		
Dolan Designs	Dolan Designs	9716-68	Residential	Fluorescent	Other	278.189	16.23	17.143	N/A	0.547	2700.0	83.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9719-68	Residential	Fluorescent	Ceiling Mount	385.229	23.59	16.328	N/A	0.573	2700.0	82.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9790-68	Residential	Fluorescent	Other	280.628	12.98	21.62	N/A	0.582	2700.0	83.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9795-68	Residential	Fluorescent	Other	471.366	16.92	27.859	N/A	0.553	2700.0	83.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9797-68	Residential	Fluorescent	Other	429.182	16.02	26.784	N/A	0.546	2700.0	83.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9798-68	Residential	Fluorescent	Other	620.405	22.44	27.651	N/A	0.564	2700.0	83.0	10000.0	7/27/2012		
Dolan Designs	Dolan Designs	9799-68	Residential	Fluorescent	Other	593.225	20.46	28.981	N/A	0.552	2700.0	82.0	10000.0	7/27/2012		
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	BPM 1691-PL	Residential	Fluorescent	Wall Sconces	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	BPM1691-PL	Residential	Fluorescent	Other	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	BPN 1691P	Residential	Fluorescent	Wall Sconces	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	BPN1691P	Residential	Fluorescent	Other	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	EFG 1011P-3	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish, "SC-1" implies brushed nickel finish and "WH-10" implies white finish.
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	EFG1011P-3	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish, "SC-1" implies brushed nickel finish and "WH-10" implies white finish.
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	GFC 1611P-2	Residential	Fluorescent	Wall Sconces	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
DongGuan JiaSheng Lighting Technology Co Ltd.	Hampton Bay	GFC1611P-2	Residential	Fluorescent	Other	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/31/2012		Actual product may be showed different finish from ENERGY STAR qualified sample:"AB-33-1" implies oil rubbed bronze finish
Dongguan Tida Lighting Co., Ltd.	Tida	61676410000;61683410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	50.8	0.9738	3000.0	84.0	35000.0	6/26/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61678410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	45.43	0.9841	3000.0	82.1	35000.0	8/3/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Dongguan Tida Lighting Co., Ltd.	Tida	61678410001	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	50.22	0.9851	3000.0	84.2	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61678411000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	52.13	0.9833	3000.0	83.6	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61679410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	46.1	0.9831	3000.0	83.0	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61680410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.41	0.9825	3000.0	84.4	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61681411000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	45.92	0.9842	3000.0	83.5	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61682410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.15	0.98	3000.0	83.3	35000.0	8/3/2012	Dimmable	
Dongguan Tida Lighting Co., Ltd.	Tida	61684410000	Both	Solid State	Accent Light Line-voltage	800.0	16.0	N/A	48.22	0.9842	3000.0	83.6	35000.0	8/3/2012	Dimmable	
EcoSense Lighting Co Ltd	EcoSense Lighting	04LC-12-xx-120-120	Residential	Solid State	Cove Mount	255.0	4.0	N/A	54.0	0.9	2700.0	83.0	36000.0	10/22/2012	Dimmable	*xx' suffix 27,30,35and 40 refer to the products CCT 2700K ,3000K,3500K and 4000K respectively
EcoSense Lighting Co Ltd	EcoSense Lighting	04LC-48-xx-120-120	Residential	Solid State	Cove Mount	1033.0	16.0	N/A	61.0	0.9	2700.0	82.0	36000.0	10/24/2012	Dimmable	*xx' suffix 27,30,35 and 40 refer to the products CCT: 2700K,3000K, 3500K and 4000K respectively.
EcoSense Lighting Co Ltd	EcoSense Lighting	05LC-12-xx-120-120	Residential	Solid State	Cove Mount	632.0	12.0	N/A	50.0	0.882	2700.0	82.0	36000.0	10/24/2012	Dimmable	*xx' suffix 27,30,35 and 40 refer to the products CCT: 2700K,3000K,3500K and 4000K respectively
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD425C070 UE-D10/ LRALD4SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD4R25C07 0UE-D10/ LRALD4CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD4R25C07 0UE-D10/ LRALD4CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD4R25C07 0UE-D10/ LRALD4SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD4R25C07 0UE-D10/ LRALD4SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD4R25C07 0UE-D10/ LRALD4SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD625C70U E-D10/ LRALD6SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD6R25C70 UE-D10/ LRALD6SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD825C70U E-D10/ LRALD8SWF15 0-T40 LHALD825C70U E-D10/ LRALD8CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8CWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8SWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8SWF15 0 LHALD8R25C70 UE-D10/ LRALD8CWF15 0	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8SWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8SWF15 0-T35 LHALD8R25C70 UE-D10/ LRALD8CWF15 0-T35	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LHALD8R25C70 UE-D10/ LRALD8SWF15 0-T40	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD6CWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD6SWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD6WWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD8CWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD8SWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD9CWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD9SWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRALD9WWF15 0-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRELD4X	Both	Solid State	Downlight Solid State Retrofit	421.0	10.0	N/A	43.0	0.9	3000.0	83.0	36000.0	8/1/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRELD4X-T40	Both	Solid State	Downlight Solid State Retrofit	421.0	10.0	N/A	43.0	0.9	3000.0	83.0	36000.0	8/1/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
EEMA Industries Dba Liton Lighting	LITON Lighting	LRELD6X	Both	Solid State	Downlight Solid State Retrofit	645.0	15.0	N/A	43.0	0.9	3000.0	86.0	36000.0	9/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	LRELD6X-T40	Both	Solid State	Downlight Solid State Retrofit	645.0	15.0	N/A	43.0	0.9	3000.0	86.0	36000.0	9/10/2012	Dimmable	
EEMA Industries Dba Liton Lighting	LITON Lighting	RALD8WWF150-R25UE-D10	Commercial	Solid State	Downlight Recessed	1345.0	28.0	N/A	48.0	0.996	3000.0	81.0	36000.0	8/10/2012	Dimmable	
Efficient Lighting	Efficient Lighting	EL-200-213-XX	Residential	Fluorescent	Bath Vanity	1800.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/23/2012		
Efficient Lighting	Efficient Lighting	EL-200-218-XX	Residential	Fluorescent	Bath Vanity	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	10/22/2012		
Efficient Lighting	Efficient Lighting	EL-203-313-XX	Residential	Fluorescent	Bath Vanity	2700.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-205G-213-XX	Residential	Fluorescent	Bath Vanity	1800.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/23/2012		
Efficient Lighting	Efficient Lighting	EL-205G-218-XX	Residential	Fluorescent	Bath Vanity	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	10/22/2012		
Efficient Lighting	Efficient Lighting	EL-210-03-313-XX	Residential	Fluorescent	Bath Vanity	2700.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-210-03-318-XX	Residential	Fluorescent	Bath Vanity	3750.0	56.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-220-02-218-XX	Residential	Fluorescent	Bath Vanity	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	10/22/2012		
Efficient Lighting	Efficient Lighting	EL-220-03-313-XX	Residential	Fluorescent	Bath Vanity	2700.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-220-03-318-XX	Residential	Fluorescent	Bath Vanity	3750.0	56.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-230-03-313-XX	Residential	Fluorescent	Bath Vanity	2700.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-230-03-318-XX	Residential	Fluorescent	Bath Vanity	3750.0	56.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-240-02-218-XX	Residential	Fluorescent	Bath Vanity	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	10/22/2012		
Efficient Lighting	Efficient Lighting	EL-240-03-313-XX	Residential	Fluorescent	Bath Vanity	2700.0	42.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-240-03-318-XX	Residential	Fluorescent	Bath Vanity	3750.0	56.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/10/2012		
Efficient Lighting	Efficient Lighting	EL-800-113-XX	Residential	Fluorescent	Ceiling Mount	900.0	14.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-800-118-XX	Residential	Fluorescent	Ceiling Mount	1250.0	19.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-800-123-XX	Residential	Fluorescent	Ceiling Mount	1600.0	24.0	72.32	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-801-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-801-218-XX	Residential	Fluorescent	Ceiling Mount	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-801-223-XX	Residential	Fluorescent	Ceiling Mount	3200.0	48.0	72.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-803-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-805-113-XX	Residential	Fluorescent	Ceiling Mount	900.0	14.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-805-118-XX	Residential	Fluorescent	Ceiling Mount	1250.0	19.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-805-123-XX	Residential	Fluorescent	Ceiling Mount	1600.0	24.0	72.32	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-810-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-810-218-XX	Residential	Fluorescent	Ceiling Mount	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-810-223-XX	Residential	Fluorescent	Ceiling Mount	3200.0	48.0	72.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-815-113-XX	Residential	Fluorescent	Ceiling Mount	900.0	14.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-815-118-XX	Residential	Fluorescent	Ceiling Mount	1250.0	19.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-815-123-XX	Residential	Fluorescent	Ceiling Mount	1600.0	24.0	72.32	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-820-113-XX	Residential	Fluorescent	Ceiling Mount	900.0	14.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-820-118-XX	Residential	Fluorescent	Ceiling Mount	1250.0	19.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-820-123-XX	Residential	Fluorescent	Ceiling Mount	1600.0	24.0	72.32	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-825-113-XX	Residential	Fluorescent	Ceiling Mount	900.0	14.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-825-118-XX	Residential	Fluorescent	Ceiling Mount	1250.0	19.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-825-123-XX	Residential	Fluorescent	Ceiling Mount	1600.0	24.0	72.32	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-830-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-835-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-835-218-XX	Residential	Fluorescent	Ceiling Mount	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-835-223-XX	Residential	Fluorescent	Ceiling Mount	3200.0	48.0	72.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-845-213-XX	Residential	Fluorescent	Ceiling Mount	1800.0	28.0	71.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-845-218-XX	Residential	Fluorescent	Ceiling Mount	2500.0	38.0	74.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		
Efficient Lighting	Efficient Lighting	EL-845-223-XX	Residential	Fluorescent	Ceiling Mount	3200.0	48.0	72.0	N/A	0.6	2700.0	82.0	10000.0	8/14/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
ElectraLED, Inc.	ElectraLED, Inc.	K9TL-XXXD	Both	Solid State	Accent Light Line-Voltage	1660.0	32.71	N/A	50.8	0.98	2700.0	83.0	60000.0	10/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs.Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	K9TL-XXXM	Both	Solid State	Accent Light Line-Voltage	1724.0	32.65	N/A	52.7	0.98	2700.0	83.0	60000.0	10/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs.Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	K9TL-XXXR	Both	Solid State	Accent Light Line-Voltage	1735.0	32.7	N/A	53.1	0.98	2700.0	83.0	60000.0	10/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs.Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	K9TL-XXXS	Both	Solid State	Accent Light Line-Voltage	1729.0	32.65	N/A	53.0	0.98	2700.0	83.0	60000.0	10/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs.Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	TLC-09-xxxD-36x	Both	Solid State	Residential: Accent Light Line-Voltage, Commercial: Accent Light Line-Voltage	1430.0	30.64	N/A	46.7	0.981	2700.0	81.0	60000.0	4/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs. Include Dimming and Non-Dimming Models. Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	TLC-09-xxxM-36x	Both	Solid State	Residential: Accent Light Line-Voltage, Commercial: Accent Light Line-Voltage	1416.0	30.37	N/A	46.6	0.981	2700.0	81.0	60000.0	4/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs. Include Dimming and Non-Dimming Models. Include alternate exterior housing colors.
ElectraLED, Inc.	ElectraLED, Inc.	TLC-09-xxxR-36x	Both	Solid State	Residential: Accent Light Line-Voltage, Commercial: Accent Light Line-Voltage	1483.0	30.59	N/A	48.5	0.981	2700.0	81.0	60000.0	4/24/2012	Dimmable	Include 3000, 3500, 4000, 5000 CCTs. Include Dimming and Non-Dimming Models. Include alternate exterior housing colors.
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH6-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH6-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH6-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH6-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH8-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH8-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH8-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HH8-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ6-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ6-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ6-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ6-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ8-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ8-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ8-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHJ8-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR6-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR6-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR6-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR6-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR8-LED-1200L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1200.0	23.3	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR8-LED-2000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	1809.0	31.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR8-LED-3000L-DIM10-120/277V	Both	Solid State	Downlight Recessed	3000.0	52.9	N/A	56.7	0.946	2700.0	80.0	35000.0	9/25/2012	Dimmable	
Elite Lighting	MAXILUME A DIVISION OF ELITE LIGHTING	HHR8-LED-900L-DIM10-120/277V	Both	Solid State	Downlight Recessed	867.0	16.8	N/A	51.4	0.954	2700.0	81.0	35000.0	9/25/2012	Dimmable	
Engineered Products Company	Engineered Products Co	16530	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.8	N/A	0.5	2700.0	82.0	10000.0	7/16/2012		
Engineered Products Company	Engineered Products Co	16535	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.8	N/A	0.5	2700.0	82.0	10000.0	7/16/2012		
enLux Lighting	enLux	DL1-TC-120V_1_270 0K	Both	Solid State	Downlight Recessed	878.9	13.5	N/A	65.1	0.945	2700.0	82.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-120V_1_300 0K	Both	Solid State	Downlight Recessed	816.3	13.5	N/A	60.5	0.953	3000.0	83.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-120V_1_350 0K	Both	Solid State	Downlight Recessed	936.3	13.7	N/A	68.3	0.944	3500.0	86.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-120V_1_400 0K	Both	Solid State	Downlight Recessed	966.4	13.5	N/A	71.6	0.945	4000.0	86.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-277V_1_270 0K	Both	Solid State	Downlight Recessed	878.9	13.5	N/A	65.1	0.945	2700.0	82.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-277V_1_300 0K	Both	Solid State	Downlight Recessed	816.3	13.5	N/A	60.5	0.953	3000.0	83.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-277V_1_350 0K	Both	Solid State	Downlight Recessed	936.3	13.7	N/A	68.3	0.944	3500.0	86.0	50000.0	5/16/2012	Dimmable	
enLux Lighting	enLux	DL1-TC-277V_1_400 0K	Both	Solid State	Downlight Recessed	966.4	13.5	N/A	71.6	0.945	4000.0	86.0	50000.0	5/16/2012	Dimmable	
Evolution Lighting LLC	Catalina Lighting	17900	Residential	Fluorescent	Residential Portable Desk Task Light	1005.38	13.83	72.7	N/A	0.6	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17901	Residential	Fluorescent	Residential Portable Desk Task Light	1005.38	13.83	72.7	N/A	0.599	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17961	Residential	Fluorescent	Residential Portable Desk Task Light	1718.75	23.76	72.34	N/A	0.588	2700.0	82.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17962	Residential	Fluorescent	Residential Portable Desk Task Light	1005.38	13.83	72.7	N/A	0.599	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17963	Residential	Fluorescent	Residential Portable Desk Task Light	3729.51	51.42	72.53	N/A	0.594	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17978	Residential	Fluorescent	Residential Portable Desk Task Light	1005.38	13.83	72.7	N/A	0.6	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	Catalina Lighting	17982	Residential	Fluorescent	Residential Portable Desk Task Light	3016.14	41.49	72.7	N/A	0.585	2700.0	83.0	10020.0	10/12/2011		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Evolution Lighting LLC	Catalina Lighting	17983	Residential	Fluorescent	Residential Portable Desk Task Light	4021.52	55.32	72.7	N/A	0.597	2700.0	83.0	10020.0	10/12/2011		
Evolution Lighting LLC	ETILITECH	18307	Residential	Solid State	Accent Light Line-voltage	419.0	7.0	N/A	54.0	0.9	3000.0	83.0	36000.0	9/26/2012	Dimmable	
Evolution Lighting LLC	N/A	18289	Residential	Solid State	Downlight Solid State Retrofit	541.0	8.0	N/A	67.0	0.9	3000.0	82.0	36000.0	9/11/2012	Dimmable	
Evolution Lighting LLC	N/A	18290	Residential	Solid State	Downlight Solid State Retrofit	641.0	8.0	N/A	72.0	0.9	3000.0	81.0	36000.0	9/11/2012	Dimmable	
Evolution Lighting LLC	PORTFOLIO	17835	Residential	Solid State	Accent Light Line-voltage	823.0	17.13	N/A	47.94	0.8	3000.0	81.0	25000.0	8/8/2012	Dimmable	
Exceedlite Ltd.	Exceedlite	ELC1001x	Residential	Fluorescent	Ceiling Mount	1382.56	18.66	74.09	N/A	0.558	2700.0	82.0	10020.0	9/30/2011		
Exceedlite Ltd.	Exceedlite	ELC1002x	Residential	Fluorescent	Ceiling Mount	2010.76	27.66	72.7	N/A	0.594	2700.0	83.0	10020.0	9/30/2011		
Exceedlite Ltd.	Exceedlite	ELF4004x	Residential	Fluorescent	Torchieres	3101.31	42.42	73.11	N/A	0.558	2700.0	81.0	10020.0	9/30/2011		
Fairway Products Inc.	Galaxy Lighting	002-30431	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200331	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200332	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200333	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200371	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200572	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200921	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES200931	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES201261	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES208612	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES208616	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES21008	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES210440	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211335	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211441	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211442	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211511	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211551	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211552	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211621	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211690	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211706	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211781	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES211870	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES212430	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES212480	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES212510	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES212870	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES213040	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES213041	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES213130	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES213140	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES213150	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES213151	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES216112	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES216122	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES221511	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES221621	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES221870	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES244021	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES244023	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250101	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250102	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250350	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250480	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250501	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250616	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250636	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES250701	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES300110	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES300120	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301010	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301020	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301021	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301090	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301091	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301130	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301131	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301230	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301290	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301291	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301390	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301392	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301500	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301540	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES301830	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES302620	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES302621	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES303045	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES303218	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES334021	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES351760	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600174	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600175	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600331	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600372	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600388	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600408	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600418	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600428	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600448	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600579	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600611	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600612	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600801	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600905	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600931	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES600993	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES601261	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES601322	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES606201	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES606202	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES606371	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES607370	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES607371	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610148	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610278	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610328	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610346	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610396	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610403	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610406	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610446	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610456	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610478	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES610486	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES611511	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES611870	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES622621	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660019	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660022	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES660032	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660313	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660335	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660441	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660442	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660480	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660550	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660560	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES660781	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700191	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700192	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700193	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700194	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700241	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700242	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700243	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700245	Residential	fluorescent	Bath Vanity	8000.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700281	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700283	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700284	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700285	Residential	fluorescent	Bath Vanity	8000.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700351	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700352	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700353	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700354	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700381	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700382	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700383	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700384	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700401	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES700402	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES710471	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710472	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710481	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710482	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710483	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710571	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710572	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710573	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710574	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710651	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710652	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710653	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710654	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710691	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710692	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710693	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710721	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710722	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710723	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710724	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES710751	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711411	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711412	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711413	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711414	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711696	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711697	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711698	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711961	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711962	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711963	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES711964	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712612	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712712	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712724	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712736	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712748	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712821	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES712822	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES790515	Residential	fluorescent	Porch Light	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790517	Residential	fluorescent	Porch Light	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790601	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790800	Residential	fluorescent	Porch Light	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790801	Residential	fluorescent	Bath Vanity	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790802	Residential	fluorescent	Bath Vanity	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790803	Residential	fluorescent	Bath Vanity	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES790804	Residential	fluorescent	Bath Vanity	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800171	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800174	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800281	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800282	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800332	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	8000.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800371	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800611	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800612	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800613	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800801	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800802	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800901	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800902	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800921	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800930	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES800931	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	9600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES801240	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801241	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801262	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801321	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801322	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801340	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES801341	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES805849	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES806201	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES806202	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES806203	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES810146	Residential	fluorescent	Bath Vanity	14400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811004	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811020	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811023	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811033	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811231	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811232	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811234	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811235	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811331	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES811332	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811335	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811411	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811412	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811441	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811442	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811443	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811480	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811481	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811509	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811550	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811551	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811621	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811706	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	3200.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811850	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811851	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811852	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811853	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811854	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811855	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES811862	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811863	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811864	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811865	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811870	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES811871	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES812335	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES812781	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES813781	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES813916	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES813920	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES813924	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES813930	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES814018	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES814024	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES814030	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES814040	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	9600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES815116	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES815120	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES815124	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES851381	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900381	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900384	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900401	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900404	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900411	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900414	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900421	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900501	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900504	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900571	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES900574	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910141	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910144	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910271	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910274	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910294	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910321	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910341	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910344	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Fairway Products Inc.	Galaxy Lighting	ES910391	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910394	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910401	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910404	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910431	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910434	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910441	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910444	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910454	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910471	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910474	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910481	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910484	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	1600.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES910751	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES911961	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES913021	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	4800.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES913041	Residential	fluorescent	Close to Ceiling Mount, Decorative Pendant	6400.0	N/A	72.0	N/A	0.6	2700.0	82.0	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES921224	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES921236	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES921248	Residential	fluorescent	Bath Vanity	N/A	N/A	65.0	N/A	0.984	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES944812	Residential	fluorescent	Wrapped Lens	N/A	N/A	65.0	N/A	0.993	N/A	N/A	10000.0	9/12/2012		
Fairway Products Inc.	Galaxy Lighting	ES944818	Residential	fluorescent	Wrapped Lens	N/A	N/A	65.0	N/A	0.993	N/A	N/A	10000.0	9/12/2012		
Feit Electric	FEIT ELECTRIC	71933	Residential	Fluorescent	wall sconces	2700.0	39.0	69.23	N/A	0.598	2700.0	82.1	10000.0	4/13/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Feit Electric	FEIT ELECTRIC	LEDR6	Residential	Solid State	Downlight Recessed, Downlight Solid State Retrofit	840.0	16.5	N/A	50.91	0.75	3000.0	82.8	50000.0	8/31/2012	Dimmable	
Generation Brands	Seagull Lighting	49170BLE-710	Residential	Fluorescent	Wall Sconces	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	49170BLE-962	Residential	Fluorescent	Wall Sconces	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	5901BLE-15	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	5902BLE-16	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	59055BLE-15	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	59232BLE-15	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	5931BLE-15	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	79121BLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	79121BLE-15	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	7925BLE-15	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	7926BLE-15	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	83055BLE-12	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	83055BLE-15	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	83057BLE-12	Residential	Fluorescent	Ceiling Mount	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	83057BLE-15	Residential	Fluorescent	Ceiling Mount	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8335BLE-12	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8335BLE-15	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88113BLE-12	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88113BLE-15	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88198BLE-12	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88198BLE-15	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88390BLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	88392BLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89018BLE-12	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89018BLE-15	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89018PBLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Generation Brands	Seagull Lighting	89018PBLE-15	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8909BLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8909PBLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8955BLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	8955PBLE-12	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89805BLE-12	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89805BLE-15	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89806BLE-12	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89806BLE-15	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89807BLE-12	Residential	Fluorescent	Ceiling Mount	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Generation Brands	Seagull Lighting	89807BLE-15	Residential	Fluorescent	Ceiling Mount	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/7/2012		Variable X can be added or dropped from catalog number
Globe Electric Inc.	Globe	10900	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	1090001	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	10923;67772;67621;6762101;67622;6762201;67637;6763701	Residential	Fluorescent	Porch Light	3300.0	55.0	65.55	N/A	0.584	2700.0	82.1	10000.0	6/13/2012		
Globe Electric Inc.	Globe	1099401;6268001;68906;6890601	Residential	Fluorescent	Porch Light	1600.0	23.0	72.79	N/A	0.569	2700.0	80.9	10000.0	5/18/2012		
Globe Electric Inc.	Globe	455299	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	455524	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52038	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5203801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52108	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5210801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52109	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5210901	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52499	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5249901	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52541	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5254101	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Globe Electric Inc.	Globe	52543	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5254301	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5258801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52604	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5260401	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52605	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5260501	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52606	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5260601	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52624	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5262401	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52669	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5266901	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52685	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5268501	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52686	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5268601	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52687	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5268701	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52688	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5268801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52689	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5268901	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52691	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5269101	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52692	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5269201	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Globe Electric Inc.	Globe	52693	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5269301	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52694	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5269401	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52737	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5273701	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52738	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5273801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52770	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5277001	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52771	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5277101	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52772	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5277201	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52773	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5277301	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	52775	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5277501	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56150	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615001	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56151	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615101	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56152	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615201	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56153	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56154	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56155	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Globe Electric Inc.	Globe	5615501	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56156	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615601	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56158	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56159	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5615901	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56160	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5616001	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5616401	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56183	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5618301	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56185	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5618501	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56222	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5622301	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56348	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56383	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56384	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56398	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5639801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56510	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56626	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5662601	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56627	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5662701	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56628	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Globe Electric Inc.	Globe	5662801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56744	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56760	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	5676001	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56770	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	56868; 5686801; 56866; 5686601; 56867; 5686701; 56869; 5686901	Residential	Fluorescent	Portable desk task light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	4/26/2012		
Globe Electric Inc.	Globe	62550	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6255001	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62551	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6255101	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62582	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62584	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62585	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62586	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62587	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6258701	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62588	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62589	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62590	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62591	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62592	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62593	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62594	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62596	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62597	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62598	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62599	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62605	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62607	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62609	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62610	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62611	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62612	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6261201	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62613	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6261301	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Globe Electric Inc.	Globe	62642	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62643	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62644	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62731	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62732	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	62733	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	63134	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6313401	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	63135	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	63180	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6318001	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	63283	Residential	Fluorescent	Wall Sconces	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6328301	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6331701	Residential	Fluorescent	Ceiling Mount	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	68718	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6871801	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	68719	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	68720	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	68819	Residential	Fluorescent	Residential Portable Desk Task Light	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6881901	Residential	Fluorescent	Residential Portable Desk Task Light	1800.0	26.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	68832	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	6883201	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	792565	Residential	Fluorescent	Residential Portable Desk Task Light	900.0	13.0	71.56	N/A	0.548	2700.0	82.1	10000.0	5/21/2012		
Globe Electric Inc.	Globe	90058; 9212001	Residential	Fluorescent	Downlight Recessed, Under Cabinet Luminaire	530.0	13.0	N/A	44.63	0.6283	2700.0	82.1	10000.0	6/13/2012		
Globe Electric Inc.	Globe	9232301	Residential	Fluorescent	Downlight Recessed, Under Cabinet Luminaire	865.0	23.0	N/A	45.17	0.605	2700.0	80.9	10000.0	5/7/2012		
Glocal International Ltd.	Glocal	T5-21W-120V	Residential	Fluorescent	Linear Strip	1249.7	20.53	60.87	N/A	0.965	4100.0	83.0	10000.0	7/9/2012		
Glomar Corporation	Green Living	45-002	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-003	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-004	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-005	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-006	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-007	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-008	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Glomar Corporation	Green Living	45-009	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-011	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-012	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-012	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-013	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-014	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-015	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-031	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-032	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-033	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-034	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-035	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-036	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-037	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-038	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-039	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-041	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-042	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-043	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
Glomar Corporation	Green Living	45-044	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-045	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-046	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-047	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Glomar Corporation	Green Living	45-048	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
Golo Chang Co., Ltd	GOLO	G-24-13	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	G-24-18	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	1150.0	18.0	65.33	N/A	0.541	2700.0	81.9	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	G-24-26	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	1550.0	26.0	69.09	N/A	0.548	2700.0	82.3	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	GU-24-13	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	GU-24-18	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	1150.0	18.0	65.33	N/A	0.541	2700.0	81.9	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	GU-24-26	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	1550.0	26.0	69.09	N/A	0.548	2700.0	82.3	10000.0	8/22/2012		
Golo Chang Co., Ltd	GOLO	GU-24A-13	Residential	Fluorescent	Ceiling Mount, Wall Sconces, Security	900.0	13.0	69.06	N/A	0.557	2700.0	81.4	10000.0	8/22/2012		
Good Earth Lighting, Inc.	allen + roth	LF1000-SSP-24T84-R	Residential	Fluorescent	Ceiling Mount	4315.0	62.0	70.0	N/A	0.5	N/A	N/A	10000.0	8/22/2012		N/A
Good Earth Lighting, Inc.	allen + roth	LF1000-SSP-48T84-R	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	allen + roth	LF1001-BR4-48T84-R	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	allen + roth	LF1002-BR4-24T84-R	Residential	Fluorescent	Ceiling Mount	4315.0	62.0	70.0	N/A	0.5	N/A	N/A	10000.0	8/22/2012		N/A
Good Earth Lighting, Inc.	allen + roth	LF1006-BR2-48T84-R	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Good Earth Lighting, Inc.	EcoLight	G0209CL-BK-I	Residential	Solid State	Under Cabinet Luminaire	138.0	4.0	N/A	37.0	0.7	3000.0	83.0	36000.0	6/28/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0209CL-MOB-I	Residential	Solid State	Under Cabinet Luminaire	138.0	4.0	N/A	37.0	0.7	3000.0	83.0	36000.0	6/28/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0209CL-SWH-I	Residential	Solid State	Under Cabinet Luminaire	138.0	4.0	N/A	37.0	0.7	3000.0	83.0	36000.0	6/28/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0414CL-BK-I	Residential	Solid State	Under Cabinet Luminaire	279.0	6.62	N/A	42.0	0.84	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0414CL-MOB-I	Residential	Solid State	Under Cabinet Luminaire	279.0	6.62	N/A	42.0	0.84	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0414CL-SWH-I	Residential	Solid State	Under Cabinet Luminaire	279.0	6.62	N/A	42.0	0.84	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0830CL-BK-I	Residential	Solid State	Under Cabinet Luminaire	536.0	12.0	N/A	45.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0830CL-MOB-I	Residential	Solid State	Under Cabinet Luminaire	536.0	12.0	N/A	45.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G0830CL-SWH-I	Residential	Solid State	Under Cabinet Luminaire	536.0	12.0	N/A	45.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	G4018-WH-I	Residential	Fluorescent	Other	900.0	14.0	69.0	N/A	0.6	2700.0	82.0	10000.0	4/26/2012		Pull chain on/off switch
Good Earth Lighting, Inc.	EcoLight	GL45112-BN-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GLC1301-NKES-I	Residential	Fluorescent	Other	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	5/11/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC1301-ORBES-I	Residential	Fluorescent	Other	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	5/11/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC1301-WHES-I	Residential	Fluorescent	Other	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	5/11/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC2301-KNES-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC2301-ORBES-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC2301-WHES-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC4018-WH-I	Residential	Fluorescent	Other	900.0	14.0	69.0	N/A	0.6	2700.0	82.0	10000.0	4/26/2012		Pull chain on/off switch
Good Earth Lighting, Inc.	EcoLight	GLC4795-ORB-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GLC9163-BAL-I	Residential	Solid State	Under Cabinet Luminaire	355.0	9.0	N/A	38.0	0.9	3000.0	84.0	36000.0	6/11/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	GLS2401-BN-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GLS2401-TWH-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GLS4511-BN-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GLS4511-WH-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GLS8113-NK-I	Residential	Fluorescent	Porch Light	900.0	12.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	EcoLight	GLS8113-RT-I	Residential	Fluorescent	Porch Light	900.0	12.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	EcoLight	GPT1301-ORBES-I	Residential	Fluorescent	Other	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	5/11/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GPT1301-WHES-I	Residential	Fluorescent	Other	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	5/11/2012		N/A
Good Earth Lighting, Inc.	EcoLight	GPT2401-BN-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GPT2401-TWH-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	EcoLight	GU0209CL-BA-I	Residential	Solid State	Under Cabinet Luminaire	138.0	4.0	N/A	37.0	0.7	3000.0	83.0	36000.0	6/28/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	GU0414CL-BA-I	Residential	Solid State	Under Cabinet Luminaire	279.0	6.62	N/A	42.0	0.84	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	GU0830CL-BA-I	Residential	Solid State	Under Cabinet Luminaire	536.0	12.0	N/A	45.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	EcoLight	GU4018-WH-I	Residential	Fluorescent	Other	900.0	14.0	69.0	N/A	0.6	2700.0	82.0	10000.0	4/26/2012		Pull chain on/off switch
Good Earth Lighting, Inc.	EcoLight	GU9163-BAL-I	Residential	Solid State	Under Cabinet Luminaire	355.0	9.0	N/A	38.0	0.9	3000.0	84.0	36000.0	6/11/2012	Dimmable	
Good Earth Lighting, Inc.	GEL	GL4830-NKCP-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	Good Earth	G1224-T8-WHES	Residential	Fluorescent	Ceiling Mount	2525.0	36.0	71.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		N/A
Good Earth Lighting, Inc.	Good Earth	G1248-T8-WHES	Residential	Fluorescent	Ceiling Mount	4872.0	64.0	83.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G1633-BZ-I	Residential	Fluorescent	Vanity	2700.0	39.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/6/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Good Earth Lighting, Inc.	Good Earth Lighting	G1634-BZ-I	Residential	Fluorescent	Vanity	3600.0	52.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G2401-TWH-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3150-BN13-IBX	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3150-BN23-IBX	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3431-BN-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3431-CH-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3630-PB13-IBX	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3651-BZ-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G3811-DBZ-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4112-BN-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4130-BN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4130-BN-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4130-PB-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4130-WH-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G41311-ORB-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G41315-ORB-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G41319-ORB-I	Residential	Fluorescent	Ceiling Mount	3000.0	44.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G41319-ORB-I	Residential	Fluorescent	Ceiling Mount	3200.0	46.0	70.0	N/A	0.6	3000.0	85.0	10000.0	1/23/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4150-BN-I	Residential	Fluorescent	Ceiling Mount	3000.0	44.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4419-DBL-I	Residential	Fluorescent	Close to Ceiling Mount	3200.0	46.0	71.0	N/A	0.6	3000.0	85.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4614-BN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4614-BZ-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4614-NK-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4614-PB-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4614-WH-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4617-BZ-I	Residential	Fluorescent	Decorative Pendant	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4639-BZ-I	Residential	Fluorescent	Chandelier	2700.0	39.0	70.0	N/A	0.5	2700.0	84.0	10000.0	1/10/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4659-BZ-I	Residential	Fluorescent	Chandelier	4500.0	65.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4697-BZ-I	Residential	Fluorescent	Decorative Pendant	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4711-ORB-I	Residential	Fluorescent	Ceiling Mount	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	8/10/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4813-BN-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4813-WH-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4814-WH-IBX	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4823-ORB-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4923-PPW-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	G4925-PN-I	Residential	Fluorescent	Close to Ceiling Mount	1800.0	26.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G4959-PN-I	Residential	Fluorescent	Chandelier	4500.0	65.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G8013-BZ-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G8013-WH-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Good Earth Lighting, Inc.	Good Earth Lighting	G8313-BZ-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G8313-WH-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	G8923-BZ-I	Residential	Fluorescent	Security	1500.0	22.0	75.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	Good Earth Lighting	G8923-WH-I	Residential	Fluorescent	Security	1500.0	22.0	75.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	Good Earth Lighting	GH4212-BN-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GH4312-BZ-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GL1433-NK-I	Residential	Fluorescent	Vanity	2700.0	39.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/6/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GL1434-NK-I	Residential	Fluorescent	Vanity	3600.0	52.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GLC3352-BN-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GLC4230-BN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4215-BN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4215-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4330-ORB-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4350-ORB-I	Residential	Fluorescent	Ceiling Mount	3000.0	44.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4552-BN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4614-NK-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4614-ORB-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GPT4823-ORBA-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GR1013-CH-I	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GR1313-CH-I	Residential	Fluorescent	Vanity	2700.0	39.0	70.0	N/A	0.6	3000.0	84.0	10000.0	4/6/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GR4212-BN-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GR4312-BZ-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/6/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	GU8013-BZ-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GU8013-WH-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GU8813-BZ-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GU8813-WH-I	Residential	Fluorescent	Security	800.0	12.0	69.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	GU8923-BZ-I	Residential	Fluorescent	Security	1500.0	22.0	75.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	Good Earth Lighting	GU8923-WH-I	Residential	Fluorescent	Security	1500.0	22.0	75.0	N/A	0.6	4100.0	84.0	10000.0	4/26/2012		Integral photosensor
Good Earth Lighting, Inc.	Good Earth Lighting	H3008-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H3008-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H3408-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H3408-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	4/3/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H4015-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4015-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	10/22/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4019-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	3000.0	44.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4019-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	3000.0	44.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/10/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4215-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H4215-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H4219-BN-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Good Earth Lighting, Inc.	Good Earth Lighting	H4219-BZ-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4315-BN-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H4315-BZ-LIN-I	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	73.0	N/A	0.5	3000.0	83.0	10000.0	4/4/2012		
Good Earth Lighting, Inc.	Good Earth Lighting	H4319-BN-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A
Good Earth Lighting, Inc.	Good Earth Lighting	H4319-BZ-LIN-I	Residential	Fluorescent	Close to Ceiling Mount	3000.0	46.0	68.0	N/A	0.5	3000.0	83.0	10000.0	10/17/2012		N/A
Good Earth Lighting, Inc.	Menards	LF1008-BR4-48T84-T	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	Menards	LF1008-SSP-24T82-T	Residential	Fluorescent	Ceiling Mount	2525.0	36.0	71.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		N/A
Good Earth Lighting, Inc.	Menards	LF1008-SSP-48T82-T	Residential	Fluorescent	Ceiling Mount	4872.0	64.0	83.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		
Good Earth Lighting, Inc.	Patriot	GPT2301-ORBES-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	Patriot	GPT2301-WHES-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	Patriot	GPT4715-BN-I	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	G4313-WH-I	Residential	Fluorescent	Other	900.0	13.0	72.0	N/A	0.6	3000.0	85.0	10000.0	10/10/2012		Pull chain on/off switch
Good Earth Lighting, Inc.	PORTFOLIO	GL2301-NKES-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	GL4024W-T8-WHT	Residential	Fluorescent	Ceiling Mount	2525.0	36.0	71.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	GL4224-4T8-BZ	Residential	Fluorescent	Ceiling Mount	4315.0	62.0	70.0	N/A	0.5	N/A	N/A	10000.0	8/22/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	GL4224-4T8-WH	Residential	Fluorescent	Ceiling Mount	4315.0	62.0	70.0	N/A	0.5	N/A	N/A	10000.0	8/22/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	GL4248-4T8-BZ	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	PORTFOLIO	GL4248-4T8-WH	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	PORTFOLIO	GL4424-2T8-WH	Residential	Fluorescent	Ceiling Mount	2525.0	36.0	71.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	GL4548-4T8-BA	Residential	Fluorescent	Ceiling Mount	9380.0	107.0	88.0	N/A	0.6	N/A	N/A	10000.0	8/7/2012		
Good Earth Lighting, Inc.	PORTFOLIO	GLZ2301-WHES-I	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	71.0	N/A	0.6	3000.0	85.0	10000.0	8/29/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	LF1005-NK3-24T84-P	Residential	Fluorescent	Ceiling Mount	4315.0	62.0	70.0	N/A	0.5	N/A	N/A	10000.0	8/22/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	UT1007-BR413CF1-P	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	PORTFOLIO	UT1007-NK3-13CF1-P	Residential	Fluorescent	Ceiling Mount	1500.0	22.0	68.0	N/A	0.5	3000.0	83.0	10000.0	11/9/2012		N/A
Good Earth Lighting, Inc.	Utilitech	G0312DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	212.0	5.13	N/A	42.0	0.75	3000.0	84.0	36000.0	8/7/2012		
Good Earth Lighting, Inc.	Utilitech	G0312LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	217.0	5.08	N/A	43.0	0.74	3000.0	83.0	36000.0	8/1/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	G0518DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	357.0	7.87	N/A	45.0	0.8	3000.0	83.0	36000.0	7/16/2012		
Good Earth Lighting, Inc.	Utilitech	G0518LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	359.0	7.8	N/A	46.0	0.8	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	G0622CL-BK-I	Residential	Solid State	Under Cabinet Luminaire	424.0	9.2	N/A	46.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	G0622CL-MOB-I	Residential	Solid State	Under Cabinet Luminaire	424.0	9.2	N/A	46.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	G0622CL-SWH-I	Residential	Solid State	Under Cabinet Luminaire	424.0	9.2	N/A	46.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	G0724DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	509.0	10.8	N/A	47.0	0.8	3000.0	83.0	36000.0	8/9/2012		
Good Earth Lighting, Inc.	Utilitech	G0724LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	522.0	10.8	N/A	48.0	0.8	3000.0	83.0	36000.0	8/9/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GLC0312DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	212.0	5.13	N/A	42.0	0.75	3000.0	84.0	36000.0	8/7/2012		
Good Earth Lighting, Inc.	Utilitech	GLC0312LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	217.0	5.08	N/A	43.0	0.74	3000.0	83.0	36000.0	8/1/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GLC0518DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	357.0	7.87	N/A	45.0	0.8	3000.0	83.0	36000.0	7/16/2012		
Good Earth Lighting, Inc.	Utilitech	GLC0518LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	359.0	7.8	N/A	46.0	0.8	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GLC0518LD-WH-I	Residential	Solid State	Under Cabinet Luminaire	359.0	7.8	N/A	46.0	0.8	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GLC0724DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	509.0	10.8	N/A	47.0	0.8	3000.0	83.0	36000.0	8/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Good Earth Lighting, Inc.	Utilitech	GLC0724LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	522.0	10.8	N/A	48.0	0.8	3000.0	83.0	36000.0	8/9/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GLC9283C-LED-I	Residential	Solid State	Under Cabinet Luminaire	357.0	7.87	N/A	45.0	0.8	3000.0	83.0	36000.0	7/16/2012		
Good Earth Lighting, Inc.	Utilitech	GLC9284C-LED-I	Residential	Solid State	Under Cabinet Luminaire	509.0	10.8	N/A	47.0	0.8	3000.0	83.0	36000.0	8/9/2012		
Good Earth Lighting, Inc.	Utilitech	GU0312DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	212.0	5.13	N/A	42.0	0.75	3000.0	84.0	36000.0	8/7/2012		
Good Earth Lighting, Inc.	Utilitech	GU0312LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	217.0	5.08	N/A	43.0	0.74	3000.0	83.0	36000.0	8/1/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GU0518DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	357.0	7.87	N/A	45.0	0.8	3000.0	83.0	36000.0	7/16/2012		
Good Earth Lighting, Inc.	Utilitech	GU0518LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	359.0	7.8	N/A	46.0	0.8	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GU0622CL-BA-I	Residential	Solid State	Under Cabinet Luminaire	424.0	9.2	N/A	46.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GU0724DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	509.0	10.8	N/A	47.0	0.8	3000.0	83.0	36000.0	8/9/2012		
Good Earth Lighting, Inc.	Utilitech	GU0724LD-BKSS-I	Residential	Solid State	Under Cabinet Luminaire	522.0	10.8	N/A	48.0	0.8	3000.0	83.0	36000.0	8/9/2012	Dimmable	
Good Earth Lighting, Inc.	Utilitech	GU0930DW-WH-I, G0930DW-WH-I	Residential	Solid State	Under Cabinet Luminaire	675.0	15.3	N/A	44.0	0.8	3000.0	83.0	36000.0	8/9/2012		
Good Earth Lighting, Inc.	Utilitech	GU4482-T8-ORB	Residential	Fluorescent	Ceiling Mount	4872.0	64.0	83.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		
Good Earth Lighting, Inc.	Utilitech	GU9804-T8-BKSS	Residential	Fluorescent	Other	9380.0	112.0	88.0	N/A	0.6	3500.0	N/A	10000.0	6/7/2012		
Good Earth Lighting, Inc.	Utilitech	LF1004-BR1-24T82-U	Residential	Fluorescent	Ceiling Mount	2525.0	36.0	71.0	N/A	0.6	N/A	N/A	10000.0	8/30/2012		N/A
Grainger Industrial Supply	LUMAPRO	13R383	Residential	Solid State	Downlight Solid State Retrofit	432.01	10.26	N/A	42.11	0.857	2700.0	89.0	25000.0	11/11/2011		
Grainger Industrial Supply	LUMAPRO	13R384	Residential	Solid State	Downlight Solid State Retrofit	599.9	10.1	N/A	59.6	0.865	2700.0	84.0	25000.0	9/13/2011		
Grainger Industrial Supply	LUMAPRO	13R385	Residential	Solid State	Downlight Solid State Retrofit	696.5	14.4	N/A	48.5	0.879	2700.0	84.0	25000.0	9/13/2011		
Grainger Industrial Supply	LUMAPRO	13R386	Residential	Solid State	Downlight Solid State Retrofit	790.65	14.02	N/A	56.39	0.871	2700.0	91.0	25000.0	11/11/2011		
Grainger Industrial Supply	LUMAPRO	33L570	Residential	Solid State	Under Cabinet Luminaire	279.0	6.62	N/A	42.0	0.84	3000.0	83.0	36000.0	7/16/2012	Dimmable	
Grainger Industrial Supply	LUMAPRO	33L571	Residential	Solid State	Under Cabinet Luminaire	424.0	9.2	N/A	46.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Grainger Industrial Supply	LUMAPRO	33L572	Residential	Solid State	Under Cabinet Luminaire	536.0	12.0	N/A	45.0	0.9	3000.0	83.0	36000.0	8/30/2012	Dimmable	
Green Creative	Green Creative	01-808-D/827	Both	Solid State	Downlight Recessed	650.0	9.5	N/A	72.25	0.9837	2700.0	84.8	35000.0	8/20/2012	Dimmable	
Green Creative	Green Creative	01-808-D/830	Both	Solid State	Downlight Recessed	700.0	9.5	N/A	72.25	0.9837	3000.0	84.8	35000.0	8/20/2012	Dimmable	
Green Creative	Green Creative	01-811-D/827	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	500.0	7.0	N/A	65.56	0.9746	2700.0	83.2	35000.0	9/20/2012	Dimmable	
Green Creative	Green Creative	01-811-D/830	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	500.0	7.0	N/A	65.56	0.9746	3000.0	83.2	35000.0	9/20/2012	Dimmable	
Greenheck Fan Corporation	Greenheck	Decorative - Grill - CFL	Both	Fluorescent	Other	1800.0	27.0	73.4	N/A	0.6	2700.0	82.0	10000.0	5/23/2012		
Greenlite Lighting Corporation	Greenlite	13W/DL/NBL	Residential	Fluorescent	Residential Portable Desk Task Light	482.289	13.0	39.402	N/A	0.572	2700.0	81.0	10000.0	7/17/2012		
Greenlite Lighting Corporation	Greenlite	13W/DL/NS	Residential	Fluorescent	Residential Portable Desk Task Light	482.289	13.0	39.402	N/A	0.572	2700.0	81.0	10000.0	7/17/2012		
Greenlite Lighting Corporation	Greenlite	13W/DL/SL	Residential	Fluorescent	Residential Portable Desk Task Light	598.51	13.0	52.932	N/A	0.596	2700.0	81.0	10000.0	7/17/2012		
Greenlite Lighting Corporation	Greenlite	13W/DL/VN/XX	Residential	Fluorescent	Residential Portable Desk Task Light	182.997	13.0	16.588	N/A	0.564	2700.0	81.0	10000.0	7/2/2012		
Hardware Concepts Inc., dba LED Outdoor USA	LEDOUTDOORUSA	LED-006S/L	Residential	Solid State	Outdoor Post-mounted	417.589	9.14	N/A	46.093	0.817	N/A	N/A	35000.0	10/8/2012		
Hardware Concepts Inc., dba LED Outdoor USA	LEDOUTDOORUSA	LED-040F	Residential	Solid State	Outdoor Post-mounted	1416.892	43.212	99.96	N/A	0.996	N/A	N/A	35000.0	10/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Hardware Concepts Inc., dba LED Outdoor USA	LEDOUTDOORUSA	LED-060F	Residential	Solid State	Outdoor Post-mounted	2523.512	57.888	99.96	N/A	0.997	N/A	N/A	35000.0	10/11/2012		
Heng Cheng IND. Co., LTD.	Heng Cheng IND. Co., LTD.	HNDL-615P-XX	Both	Solid State	Downlight Solid State retrofit	1092.67	18.17	N/A	60.14	0.9604	3000.0	86.0	35000.0	11/26/2012		
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT3-DIM	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	650.0	9.0	N/A	72.79	0.9662	3000.0	82.4	40000.0	8/29/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT4-DIM	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	650.0	9.0	N/A	70.06	0.9689	3000.0	82.3	40000.0	8/29/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT4-DIM/B	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	800.0	13.0	N/A	63.48	0.9592	3000.0	82.1	40000.0	8/29/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT5/6-DIM-E1	Both	Solid State	Downlight Solid State Retrofit	850.0	13.0	N/A	70.28	0.979	3000.0	82.0	35000.0	8/22/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT5/6-DIM-E2	Both	Solid State	Downlight Solid State Retrofit	1200.0	18.0	N/A	70.28	0.9885	3000.0	81.8	35000.0	8/22/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT5/6-DIM-P1	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	800.0	13.0	N/A	66.84	0.9586	3000.0	82.0	40000.0	8/29/2012	Dimmable	
Hengdian Group Tospo Lighting Co., Ltd.	Tospo	TP120-RT5/6-DIM-P2	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	1100.0	18.0	N/A	62.61	0.9893	3000.0	81.8	50000.0	7/3/2012	Dimmable	
HomeSelects International	Home Selects	6100	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/2/2012		
Hubbardton Forge	Hubbardton	204529E	Residential	Fluorescent	Wall Sconces	900.0	13.0	65.6	N/A	0.578	2700.0	83.0	10000.0	1/10/2012		
Ilsung Moolsan Company Ltd.	Ilsung	AFR56	Both	Solid State	Downlight Solid State Retrofit	920.0	13.0	N/A	70.0	0.9	3000.0	87.0	50000.0	11/16/2012	Dimmable	
INCON Industries	Incon Lighting	11111-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11111-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11111-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11111-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11111-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11111-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11191-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11191-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11191-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11191-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11191-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11191-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11411-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11411-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11411-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11411-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11411-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11411-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11491-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11491-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11491-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
INCON Industries	Incon Lighting	11491-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11491-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11491-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11511-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11511-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11511-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11511-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11511-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11511-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11561-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11561-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11561-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11561-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11561-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11561-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11711-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11711-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11711-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11711-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11711-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11711-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11791-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11791-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11791-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11791-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	11791-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	11791-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13312-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13312-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13312-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13312-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13312-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13312-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13392-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13392-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13392-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13392-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13392-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13392-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
INCON Industries	Incon Lighting	13412-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13412-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13412-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13412-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13412-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13412-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13492-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13492-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13492-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13492-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	13492-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	13492-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	136X1-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	136X1-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	136X1-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	136X1-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	136X1-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	136X1-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16111-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16111-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16111-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16111-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16111-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16111-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16161-13GU-ES-XX	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16161-13QE-ES-XX	Residential	Fluorescent	Ceiling Mount	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16161-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16161-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16161-26GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16161-26QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1550.0	21.35	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16411-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16411-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16411-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16411-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16411-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16411-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16461-213GU-ES-XX	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16461-213QE-ES-XX	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16461-226GU-ES-XX	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
INCON Industries	Incon Lighting	16461-313GU-ES-XX	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	16461-313QE-ES-XX	Residential	Fluorescent	Ceiling Mount	2400.0	32.91	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	16461-52QE-ES-XX	Residential	Fluorescent	Ceiling Mount	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	20017-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	20017-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	20017-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	20017-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	20017-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	20017-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21511-13QE-ES-XX	Residential	Fluorescent	Wall Sconces	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21511-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	21511-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21611-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	21611-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21611-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	21611-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	21611-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21611-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	21762-13GU-ES-XX	Residential	Fluorescent	Wall Sconces	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	230X1-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	230X1-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	230X1-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	230X1-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	230X1-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	230X1-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	236X1-13QE-ES-XX	Residential	Fluorescent	Wall Sconces	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	236X1-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	236X1-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	24017-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	24017-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	24017-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	24017-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	24017-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	24017-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	25011-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	25011-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	25011-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	25011-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	25011-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
INCON Industries	Incon Lighting	25011-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	26811-13QE-ES-XX	Residential	Fluorescent	Wall Sconces	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	26811-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	26811-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	27912-213GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.578	2700.0	83.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	27912-213QE-ES-XX	Residential	Fluorescent	Wall Sconces	1600.0	21.94	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	27912-226GU-ES-XX	Residential	Fluorescent	Wall Sconces	3600.0	52.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	27912-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	27912-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	27912-52QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
INCON Industries	Incon Lighting	28811-13QE-ES-XX	Residential	Fluorescent	Wall Sconces	800.0	10.97	65.6	N/A	0.515	2700.0	81.7	10000.0	4/16/2012		
INCON Industries	Incon Lighting	28811-26GU-ES-XX	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.551	2700.0	82.0	10000.0	5/9/2012		
INCON Industries	Incon Lighting	28811-26QE-ES-XX	Residential	Fluorescent	Wall Sconces	3100.0	42.7	65.3	N/A	0.997	2700.0	80.0	10000.0	4/16/2012		
Inter-Global Inc.	Inter-Global Inc	FA1xx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FB155-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FB156-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FBxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC133-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC135-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC142-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC144-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC159-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC160-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC321-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC322-E2XX-XXX	Residential	Fluorescent	Ceiling Mount	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC322-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FC3xx-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FCxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FD3x1-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FD3x4-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FD3XX-E2XX-XXXX	Residential	Fluorescent	Ceiling Mount	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Inter-Global Inc.	Inter-Global Inc	FD3XX-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE11X-E2XX-XXXX	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE11X-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE1XX-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/5/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE1xx-Exxx-xxxx	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	7/12/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE1xx-Gxxx-xxxx	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE35X-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/5/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE36X-E2XX-XXXX	Residential	Fluorescent	Wall Sconces	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE36X-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE3xx-Exxx-xxxx	Residential	Fluorescent	Ceiling Mount, Other	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	7/12/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FE3xx-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FG10x-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FK391-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount, Wall Sconces	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FK395-Gxxx-xxxx	Residential	Fluorescent	Ceiling Mount, Wall Sconces	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FK39X-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FKxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FM10X-E2XX-XXXX	Residential	Fluorescent	Wall Sconces	1518.0	21.76	69.8	N/A	0.55	2700.0	82.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FM10X-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FM10x-Gxxx-xxxx	Residential	Fluorescent	Wall Sconces	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FM1X1-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FN151-EXX-XXXX	Residential	Fluorescent	Porch Light	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FN151-Gxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FN251-EXX-XXXX	Residential	Fluorescent	Porch Light	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FP10X-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FP10x-Gxx-xxxx	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FP122-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FP123-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Inter-Global Inc.	Inter-Global Inc	FP123-Gxx-xxxx	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FP131-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FPxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FR1X1-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FR1X2-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FR1xx-Gxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FT141-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FT161-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/5/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FTxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FWSBx-Gxxx-xx	Residential	Fluorescent	Wall Sconces	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FWXXX-E2XX-XXXX	Residential	Fluorescent	Wall Sconces	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FWXXX-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FX169-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/5/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FX39X-E2XX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	8/29/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	FXxxx-Gxxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/28/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS2-2X17T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	9/6/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS2-2X17T8/IG13-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS2-2X17T8/IG213-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS3-2X25T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	9/6/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS3-2X25T8/IG130ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS3-2X25T8/IG230ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS4-2X32T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS4-2X32T8/IG130ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.6	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS4-2X32T8/IG214-32ELT8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	HS4-2X32T8/IG230ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	RF2-217T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/15/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	RF3-225T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/15/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Inter-Global Inc.	Inter-Global Inc	RF4-232T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/15/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S2-1X17T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S2-2X17T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S2-2X17T8/IG13-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S3-1X25T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S3-1X25T8/IG25-32ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	9/6/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S3-2X25T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S4-1X32T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.6	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	S4-2X32T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ-217T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	9/6/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ-217T8/IG13-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ-217T8/IG213-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ3-225T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	9/6/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ3-225T8/IG13-20ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ3-225T8/IG230ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ4-232T8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ4-232T8/IG130ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.6	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ4-232T8/IG214-32ELT8	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Inter-Global Inc.	Inter-Global Inc	SQ4-232T8/IG230ELSX	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	6/13/2012		Variable X can be added or dropped from catalog number
Intermatic Incorporated	INTERMATIC	IR6-600WH	Both	Solid State	Downlight Solid State retrofit	626.47	13.7	N/A	45.91	0.95	3000.0	80.7	35000.0	6/20/2012	Dimmable	
Janmar Lighting	Janmar Lighting	2XXLED-PAR20YYY	Residential	Solid State	Downlight Recessed	729.0	15.6	N/A	46.7	0.989	3000.0	85.0	36000.0	5/1/2012		
Janmar Lighting	Janmar Lighting	311LED-PAR20YYY	Residential	Solid State	Downlight Recessed	729.0	15.6	N/A	46.7	0.989	3000.0	85.0	36000.0	5/1/2012		
Janmar Lighting	Janmar Lighting	7XXLED-XX-PAR20XXX	Residential	Solid State	Downlight Recessed	729.0	15.6	N/A	46.7	0.989	3000.0	85.0	36000.0	5/1/2012		
Janmar Lighting	Janmar Lighting	8XXLED-PAR20YYY	Residential	Solid State	Downlight Recessed	729.0	15.6	N/A	46.7	0.989	3000.0	85.0	36000.0	5/1/2012		
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	213LED-PAR30	Both	Solid State	Downlight Solid State Retrofit	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	7/3/2012		
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	215LED-PAR30	Both	Solid State	Downlight Solid State Retrofit	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	7/3/2012		
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	814LED-PAR30	Both	Solid State	Downlight Recessed	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	6/28/2012		
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	815LED-PAR30	Both	Solid State	Downlight Recessed	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	6/28/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	829LED-PAR30	Both	Solid State	Downlight Recessed	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	6/28/2012		
Janmar Lighting	LED PAR 30 RECESSED DOWNLIGHTS	836LED-PAR30	Both	Solid State	Downlight Recessed	1048.0	21.18	N/A	49.48	0.99	2700.0	86.0	50000.0	6/28/2012		
Janmar Lighting	SERIES 738 LED	738E-22LED-LPAR30	Both	Solid State	Accent Light Line-voltage	832.0	22.27	N/A	37.0	1.0	3000.0	86.0	35000.0	1/12/2012		
Janmar Lighting	SERIES 738 LED	738E-22LED-LPAR30-LM	Both	Solid State	Accent Light Line-voltage	832.0	22.27	N/A	37.0	1.0	3000.0	86.0	35000.0	1/12/2012		
Jiangmen Rainbow-Lite Co Ltd.	Patriot Lighting	3483965	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.0	10000.0	11/14/2012		
Jiangmen Rainbow-Lite Co Ltd.	Patriot Lighting	3483966	Residential	Fluorescent	Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.0	10000.0	11/14/2012		
Jiangmen Rainbow-Lite Co Ltd.	Patriot Lighting	3483967	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.0	10000.0	11/14/2012		
Jiangmen Rainbow-Lite Co Ltd.	Patriot Lighting	3483968	Residential	Fluorescent	Decorative Pendant	900.0	13.0	70.97	N/A	0.615	2700.0	82.0	10000.0	11/14/2012		
JUNO LIGHTING, LLC	Aculux	IC43L-827-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	2700.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC43L-830-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3000.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Aculux	IC43L-835-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3500.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC43L-841-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	4100.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC43LSQ-827-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	2700.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC43LSQ-830-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3000.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Aculux	IC43LSQ-835-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3500.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC43LSQ-841-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	4100.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943L-827-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	2700.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943L-830-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3000.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Aculux	IC943L-835-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3500.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943L-841-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	4100.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943LSQ-827-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	2700.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943LSQ-830-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3000.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Aculux	IC943LSQ-835-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	3500.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Aculux	IC943LSQ-841-y-z	Both	Solid State	Downlight Recessed	591.0	12.21	N/A	48.0	1.0	4100.0	85.0	36000.0	8/16/2012	Dimmable	xx' suffix 27, 30, 35, and 40 refer to the products CCT: 2700K, 3000K, 3500K, and 4000K respectively. 'y' suffix S, N, F refer to the products diffusion: S=Spot, N=Narrow Flood, F=Flood. â zâ suffix 1, U, L refer to the available driver: U=Driver option with universal input 120/277V, 1=Driver Option with 120V input only, and L=Driver option with Lutron Universal input.
JUNO LIGHTING, LLC	Indy	LRMw-x27y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRMw-x30y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRMw-x30y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRMw-x35y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRMw-x35y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Indy	LRMw-x41y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRMw-x41y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x27y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x30y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x30y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x35y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x35y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x41y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	LRTw-x41y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x27y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x30y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x30y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Indy	Lw-x35y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x35y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x41y-z	Both	Solid State	Downlight Recessed	912.0	20.71	N/A	44.0	1.0	2700.0	80.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00H-CS, Lx00HW-CS, Lx00H-CQ, Lx00HW-CQ, Lx00H-CL, Lx00HW-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Indy	Lw-x41y-z	Both	Solid State	Downlight Recessed	960.0	20.39	N/A	47.0	1.0	3000.0	81.0	36000.0	5/29/2012	Dimmable	Qualified Trims are Lx00P-CS, Lx00P-CQ, Lx00P-CL, where x = 4, 6, or 8 depending on aperture size.
JUNO LIGHTING, LLC	Juno	IC1LEDG3-27K-1	Commercial	Solid State	Downlight Recessed	524.0	11.91	N/A	44.0	1.0	2700.0	81.6	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-27K-U	Commercial	Solid State	Downlight Recessed	532.0	10.61	N/A	50.0	1.0	2700.0	81.7	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-35K-1	Commercial	Solid State	Downlight Recessed	582.0	11.79	N/A	49.0	1.0	3500.0	83.6	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-35K-U	Commercial	Solid State	Downlight Recessed	582.0	10.53	N/A	55.0	1.0	3500.0	83.7	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-3K-1	Commercial	Solid State	Downlight Recessed	534.0	11.83	N/A	45.0	1.0	3000.0	80.1	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-3K-U	Commercial	Solid State	Downlight Recessed	547.0	10.59	N/A	52.0	1.0	3000.0	80.1	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-41K-1	Commercial	Solid State	Downlight Recessed	603.0	11.9	N/A	51.0	1.0	4100.0	81.9	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LEDG3-41K-U	Commercial	Solid State	Downlight Recessed	605.0	10.57	N/A	57.0	1.0	4100.0	82.0	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1LWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-27K-1	Commercial	Solid State	Downlight Recessed	524.0	11.91	N/A	44.0	1.0	2700.0	81.6	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-27K-U	Commercial	Solid State	Downlight Recessed	532.0	10.61	N/A	50.0	1.0	2700.0	81.7	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-35K-1	Commercial	Solid State	Downlight Recessed	582.0	11.79	N/A	49.0	1.0	3500.0	83.6	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-35K-U	Commercial	Solid State	Downlight Recessed	582.0	10.53	N/A	55.0	1.0	3500.0	83.7	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-3K-1	Commercial	Solid State	Downlight Recessed	534.0	11.83	N/A	45.0	1.0	3000.0	80.1	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-3K-U	Commercial	Solid State	Downlight Recessed	547.0	10.59	N/A	52.0	1.0	3000.0	80.1	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-41K-1	Commercial	Solid State	Downlight Recessed	603.0	11.9	N/A	51.0	1.0	4100.0	81.9	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLEDG3-41K-U	Commercial	Solid State	Downlight Recessed	605.0	10.57	N/A	57.0	1.0	4100.0	82.0	35000.0	11/10/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC1RLWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-35K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-35K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-3K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-3K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-41K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20LEDG3-41K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC20LWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-35K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-35K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-3K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-3K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-41K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLEDG3-41K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC20RLWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22-GU24-18ESL	Residential	Fluorescent	Downlight Recessed	703.0	15.45	N/A	45.0	0.5	2700.0	82.0	10000.0	11/6/2012		
JUNO LIGHTING, LLC	Juno	IC22LEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-35K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-35K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-3K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-3K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-41K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LEDG3-41K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22LWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-35K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-35K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-3K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-3K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-41K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLEDG3-41K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC22RLWDG3-3K-1	Both	Solid State	Downlight Recessed	602.0	14.0	N/A	43.0	1.0	3000.0	81.0	36000.0	10/22/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-35K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-35K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-3K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-3K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-41K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920LEDG3-41K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-27K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-27K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-3 5K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-3 5K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-3 K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-3 K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-4 1K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC920RLEDG3-4 1K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-27 K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-27 K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-35 K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-35 K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-3K -1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-3K -U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-41 K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922LEDG3-41 K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-2 7K-1	Both	Solid State	Downlight Recessed	596.0	12.02	N/A	49.55	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-2 7K-U	Both	Solid State	Downlight Recessed	584.0	10.32	N/A	56.54	0.977	2700.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-3 5K-1	Both	Solid State	Downlight Recessed	654.0	11.94	N/A	54.81	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-3 5K-U	Both	Solid State	Downlight Recessed	637.0	10.26	N/A	62.05	0.977	3500.0	83.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-3 K-1	Both	Solid State	Downlight Recessed	618.0	12.0	N/A	51.51	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-3 K-U	Both	Solid State	Downlight Recessed	604.0	10.31	N/A	58.55	0.977	3000.0	81.4	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-4 1K-1	Both	Solid State	Downlight Recessed	677.0	11.95	N/A	56.67	0.977	4100.0	81.9	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC922RLEDG3-4 1K-U	Both	Solid State	Downlight Recessed	658.0	10.25	N/A	64.15	0.977	4100.0	81.6	35000.0	10/25/2011	Dimmable	
JUNO LIGHTING, LLC	Juno	IC926LED9G3-2 7K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	2700.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC926LED9G3-27K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	2700.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC926LED9G3-35K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3500.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC926LED9G3-35K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3500.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC926LED9G3-3K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3000.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC926LED9G3-3 K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3000.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC926LED9G3-4 1K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	4100.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC926LED9G3-4 1K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	4100.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-2 7K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	2700.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC928LED9G3-27K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	2700.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-35K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3500.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-35K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3500.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-3K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3000.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	IC928LED9G3-3 K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	3000.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-4 1K-1	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	4100.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	IC928LED9G3-4 1K-U	Both	Solid State	Downlight Recessed	779.0	16.77	N/A	46.0	1.0	4100.0	81.0	36000.0	10/3/2012	Dimmable	The IC928 based housing is qualified with the following trim/reflectors: 602C-WH, 604W-WH, 602G-WH, 604B-WH, 602B-WH, 604B-BL, 602HZ-WH, 604B-ABZ, 602HZ-SC, 604B-SC, 602W-WH, 602WHZ-ABZ, 602WHZ-WH. The IC926 based housing is qualified with the following trim/reflectors: 620C-WH, 614W-WH, 620G-WH, 614B-WH, 620B-WH, 614B-BL, 620HZ-WH, 614B-ABZ, 620HZ-SC, 614B-SC, 620W-WH, 620WHZ-ABZ, 620WHZ-WH
JUNO LIGHTING, LLC	Juno	J6RLEG3-27K-6 -WH	Commercial	Solid State	Downlight Recessed	616.0	10.88	N/A	57.0	1.0	2700.0	82.0	35000.0	3/14/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-27K-9 -WH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-35K-6 -WH	Commercial	Solid State	Downlight Recessed	675.0	10.8	N/A	62.0	1.0	3500.0	84.0	35000.0	3/14/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-35K-9 -WH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-3K-6 -WH	Commercial	Solid State	Downlight Recessed	631.0	10.9	N/A	58.0	1.0	3000.0	81.0	35000.0	3/14/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-3K-9 -WH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-41K-6 -WH	Commercial	Solid State	Downlight Recessed	696.0	10.8	N/A	64.0	1.0	4100.0	83.0	35000.0	3/14/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLEG3-41K-9 -WH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-6-CLW	Commercial	Solid State	Downlight Recessed	610.0	10.88	N/A	56.0	1.0	2700.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-6-HZW	Commercial	Solid State	Downlight Recessed	610.0	10.88	N/A	56.0	1.0	2700.0	83.0	35000.0	3/16/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-6-WHW	Commercial	Solid State	Downlight Recessed	610.0	10.88	N/A	56.0	1.0	2700.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-6-WWH	Commercial	Solid State	Downlight Recessed	610.0	10.88	N/A	56.0	1.0	2700.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-6-WZW	Commercial	Solid State	Downlight Recessed	610.0	10.88	N/A	56.0	1.0	2700.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-9-CLW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-9-HZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-9-WHW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-9-WWH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-27K-9-WZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	2700.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-6-CLW	Commercial	Solid State	Downlight Recessed	621.0	10.78	N/A	58.0	1.0	3500.0	85.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-6-HZW	Commercial	Solid State	Downlight Recessed	621.0	10.78	N/A	58.0	1.0	3500.0	85.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-6-WHW	Commercial	Solid State	Downlight Recessed	621.0	10.78	N/A	58.0	1.0	3500.0	85.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-6-WWH	Commercial	Solid State	Downlight Recessed	621.0	10.78	N/A	58.0	1.0	3500.0	85.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-6-WZW	Commercial	Solid State	Downlight Recessed	621.0	10.78	N/A	58.0	1.0	3500.0	85.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-9-CLW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-9-HZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-9-WHW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-9-WWH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-35K-9-WZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3500.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-6-CLW	Commercial	Solid State	Downlight Recessed	587.0	10.84	N/A	54.0	1.0	3000.0	81.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-6-HZW	Commercial	Solid State	Downlight Recessed	587.0	10.84	N/A	54.0	1.0	3000.0	81.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-6-WHW	Commercial	Solid State	Downlight Recessed	587.0	10.84	N/A	54.0	1.0	3000.0	81.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-6-WWH	Commercial	Solid State	Downlight Recessed	587.0	10.84	N/A	54.0	1.0	3000.0	81.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-6-WZW	Commercial	Solid State	Downlight Recessed	587.0	10.84	N/A	54.0	1.0	3000.0	81.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-9-CLW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-9-HZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-9-WHW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-9-WWH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-3K-9-WZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	3000.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-6-CLW	Commercial	Solid State	Downlight Recessed	632.0	10.78	N/A	59.0	1.0	4100.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-6-HZW	Commercial	Solid State	Downlight Recessed	632.0	10.78	N/A	59.0	1.0	4100.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-6-WHW	Commercial	Solid State	Downlight Recessed	632.0	10.78	N/A	59.0	1.0	4100.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-6-WWH	Commercial	Solid State	Downlight Recessed	632.0	10.78	N/A	59.0	1.0	4100.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-6-WZW	Commercial	Solid State	Downlight Recessed	632.0	10.78	N/A	59.0	1.0	4100.0	83.0	35000.0	3/16/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-9-CLW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-9-HZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-9-WHW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-9-WWH	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	J6RLG3-41K-9-WZW	Both	Solid State	Downlight Solid State Retrofit	820.0	15.18	N/A	54.0	1.0	4100.0	81.0	36000.0	10/10/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	SP253MLL-2D-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-2K-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-35D-xx-yy-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-35K-xx-yy-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-3D-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-3K-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-4D-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP253MLL-4K-xxx-STN	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	SP254MLL-2HC-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	SP254MLL-2K-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	SP254MLL-35K-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3500.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	SP254MLL-3HC-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	SP254MLL-3K-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	SP254MLL-4K-y-STN	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	4000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T209LED-27K-xx-yy	Both	Solid State	Accent Light Line-voltage	1615.0	34.63	N/A	47.0	1.0	2700.0	86.0	36000.0	3/14/2012		
JUNO LIGHTING, LLC	Juno	T209LED-3K-xx-yy	Both	Solid State	Accent Light Line-voltage	1615.0	34.63	N/A	47.0	1.0	2700.0	86.0	36000.0	3/14/2012		
JUNO LIGHTING, LLC	Juno	T209LED-4K-xx-yy	Both	Solid State	Accent Light Line-voltage	1615.0	34.63	N/A	47.0	1.0	2700.0	86.0	36000.0	3/14/2012		
JUNO LIGHTING, LLC	Juno	T251LED-27D-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-27K-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-35D-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-35K-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-3D-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-3K-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T251LED-4D-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	T251LED-4K-xx-yy	Both	Solid State	Accent Light Line-voltage	541.0	15.43	N/A	35.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T252L-3K-HC-y-zz	Both	Solid State	Accent Light Line-voltage	740.0	18.0	N/A	40.0	1.0	3000.0	94.0	36000.0	11/6/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T253LED-27D-xxx-yy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T253LED-35D-xx-yy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T253LED-35K-xx-yy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T253LED-3D-xxx-yy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T253LED-4D-xxx-yy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T254L-27K-HC-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T254L-27K-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T254L-35K-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3500.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	T254L-3K-HC-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T254L-3K-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T254L-4K-y-zz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	4000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	T255LED-27D-xx-yy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	2700.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T255LED-35D-xx-yy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3500.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T255LED-3D-xx-yy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	T255LED-4D-xx-yy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	4000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TC920LEDG3-27K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC920LEDG3-35K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	TC920LEDG3-3 K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC920LEDG3-4 1K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	4100.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC922LEDG3-2 7K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC922LEDG3-3 5K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC922LEDG3-3 K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TC922LEDG3-4 1K-yz	Commercial	Solid State	Downlight Recessed	729.0	16.86	N/A	43.0	1.0	4100.0	82.0	36000.0	10/10/2012	Dimmable	y' suffix refers to the available driver. U = Driver option with universal input 120/277V and L = Driver option with Lutron Universal input. â zâ suffix refers to Chicago Plenum UL Listing. If equipped, z = CP.
JUNO LIGHTING, LLC	Juno	TEK253LED27D xxxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light, NFL for Narrow Flood Light, SP for Spot Light. yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED27K xxxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	2700.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light, NFL for Narrow Flood Light, SP for Spot Light. yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	TEK253LED35Dxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED35Kxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3500.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED3Dxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED3Kxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	3000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED4Dxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK253LED4Kxyy	Both	Solid State	Accent Light Line-voltage	896.0	22.13	N/A	41.0	1.0	4000.0	82.0	36000.0	10/10/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK254L27KHCyzz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	TEK254L27Kyzz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	2700.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	TEK254L35Kyzz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3500.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	TEK254L3KHcyzz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	91.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
JUNO LIGHTING, LLC	Juno	TEK254L3Kyz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	3000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	TEK254L4Kyz	Both	Solid State	Accent Light Line-voltage	923.0	18.57	N/A	50.0	1.0	4000.0	80.0	35000.0	11/14/2012	Dimmable	y' suffix denotes light distribution where S = Spot, N = Narrow Flood, or F = Flood. â zzâ suffix denotes fixture finish where BL = Black, SL = Silver, or WH = White.
JUNO LIGHTING, LLC	Juno	TEK25527Dxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	2700.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK25527Kxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	2700.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK25535Dxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3500.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK25535Kxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3500.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK2553Dxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK2553Kxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	3000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK2554Dxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	4000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	TEK2554Kxyy	Both	Solid State	Accent Light Line-voltage	2113.0	46.13	N/A	46.0	1.0	4000.0	85.0	36000.0	9/18/2012	Dimmable	xx = FL for Flood Light,NFL for Narrow Flood Light, SP for Spot Light.yy = BL for Black Finish, SL for Silver Finish, WH for White Finish.
JUNO LIGHTING, LLC	Juno	ULL12-WH	Residential	Solid State	Under Cabinet Luminaire	216.0	5.16	N/A	42.0	0.8	3000.0	84.0	36000.0	2/6/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	ULL18-WH	Residential	Solid State	Under Cabinet Luminaire	376.0	8.0	N/A	50.0	0.8	3000.0	84.0	36000.0	2/6/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	ULL24-WH	Residential	Solid State	Under Cabinet Luminaire	510.0	11.0	N/A	46.0	0.8	3000.0	84.0	36000.0	2/6/2012	Dimmable	
JUNO LIGHTING, LLC	Juno	V6RL3K-WH	Residential	Solid State	Downlight Solid State Retrofit	643.94	12.29	N/A	52.41	0.964	3000.0	82.0	25000.0	3/30/2012		
JUNO LIGHTING, LLC	Juno	V6RL3K-WH-T24	Residential	Solid State	Downlight Solid State Retrofit	643.94	12.29	N/A	52.41	0.964	3000.0	82.0	25000.0	3/30/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Kadium Lighting	Verlux Lighting	VL-CF-11X5-26-01 X	Residential	Fluorescent	Ceiling Mount	884.73	20.3	43.497	N/A	0.544	2700.0	81.0	10000.0	4/25/2012		
Kadium Lighting	Verlux Lighting	VL-CF-13X5-36-01	Residential	Fluorescent	Ceiling Mount	2540.0	36.0	73.83	N/A	0.547	2700.0	81.8	10000.0	7/3/2012		
Kadium Lighting	Verlux Lighting	VL-ET-41-01 X	Residential	Fluorescent	Torchiere	1550.956	35.53	43.655	N/A	0.547	2700.0	81/80	10000.0	4/26/2012	Dimmable	
Kadium Lighting	Verlux Lighting	VL-OF-01 X	Residential	Fluorescent	Wall Mounted	769.212	16.18	47.123	N/A	0.547	2700.0	81.0	10000.0	4/27/2012		
Kee Tat Lighting Holdings Limited	Kee Tat	DL4-10RB-AA60-B-C-DD	Both	Solid State	Downlight Recessed	531.0	11.0	N/A	45.0	0.9	3000.0	83.0	35000.0	1/22/1900	Dimmable	*AA indicate Color temperature WS=3000K, Beam Angle 75Å° NW=4000K, Beam Angle 75Å° B indicate installation structure N= New Construction R= Remodel C indicate Shape of Trim R= Round Trim S= Square Trim DD indicate Color of Trim WT= White Trim PT= Platinum Trim BN= Brushed Nickel Trim
Kee Tat Lighting Holdings Limited	Kee Tat	DL6-14RB-AA60-B-C-DD	Both	Solid State	Downlight Recessed	845.0	15.0	N/A	53.0	0.9	3000.0	85.0	35000.0	1/22/1900	Dimmable	*AA indicate Color temperature WS=3000K, Beam Angle 75Å° NW=4000K, Beam Angle 75Å° B indicate installation structure N= New Construction R= Remodel C indicate Shape of Trim R= Round Trim S= Square Trim DD indicate Color of Trim WT= White Trim PT= Platinum Trim BN= Brushed Nickel Trim
Kee Tat Lighting Holdings Limited	KT	DL6D;DL6D-4KT-WS90-E-R	Residential	Solid State	Downlight Solid State retrofit	840.06	13.7	N/A	60.94	0.944	3000.0	80.3	25000.0	7/12/2012	Dimmable	
Kee Tat Lighting Holdings Limited	KT	DL6; DL6C-4KT-WS90-E-R	Both	Solid State	Downlight Solid State retrofit	626.47	13.65	N/A	45.91	0.95	3000.0	80.7	35000.0	12/27/2011	Dimmable	
King of Fans	Hampton Bay	72199	Residential	Fluorescent	Ceiling Fan Light Kit	1800.0	26.0	70.82	N/A	0.548	2700.0	82.4	10000.0	2/6/2012		
King One Products, Co.	King One	RC-56123	Residential	Fluorescent	Downlight Recessed	1054.69	20.67	N/A	51.023	0.544	2700.0	81.0	10000.0	10/30/2012		
King One Products, Co.	King One Products, Co.	CLG-80022-213 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-6012-118X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6021-213X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-6022-218X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6036-223X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	CMG-63147-113 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-63201-113 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-63205-113 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-63205-213 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-63205-218 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-63205-223 XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6321-118X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6321-213X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-6321-218X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6324-118X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	CMG-6324-213X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	CMG-6324-218X X	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	K6105	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0013013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0013013 A	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0013018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0013018 A	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0015013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0015018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0016013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0016018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0019013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0019018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESCH0065018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0066013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0066018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0069013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0069018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH00712013	Residential	Fluorescent	Chandelier	10800.0	156.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH00712018	Residential	Fluorescent	Chandelier	15000.0	216.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0072013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0072018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0073013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0073018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0075013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0075018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0076013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0076018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0079013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0079018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH00815013	Residential	Fluorescent	Chandelier	13500.0	195.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH00815018	Residential	Fluorescent	Chandelier	15000.0	216.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0083013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0083018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0085013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0085018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0086013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0086018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0089013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0089018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0093013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0093018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0095013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0095018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0103013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0103018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0104013	Residential	Fluorescent	Chandelier	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0104018	Residential	Fluorescent	Chandelier	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0105013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0105018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0106013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0106018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESCH0109013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0109018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0113013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0113018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0115013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0115018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0116013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0116018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0119013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0119018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0125013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0125018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0126013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0126018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0132013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0132018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0133013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0133013 A	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0133018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0133018 A	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0134013	Residential	Fluorescent	Chandelier	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0134018	Residential	Fluorescent	Chandelier	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0135013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0135018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0136013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0136018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0139013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESCH0139018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0001013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0011013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0021013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0031013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0041013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0051013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0061013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0061018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0061023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0071013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0071018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		













ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESFM0693013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0693018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0693023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0701013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0701018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0701023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0712013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0712018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0712023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0722013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0722018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0722023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0733013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0733018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0733023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0743013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0743018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0743023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0753013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0753018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0753023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0761013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0761018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0761023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0774013	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0774018	Residential	Fluorescent	Ceiling mount	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0774023	Residential	Fluorescent	Ceiling mount	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0781013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0781018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0781023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0792013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0792018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESFM0792023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0011013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0011018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0011023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0021013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0021018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESMP0021023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		













ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESPD0272013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0272018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0272023	Residential	Fluorescent	Chandelier	3200.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0281013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0281018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0281023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0283013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0283018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0283023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0291013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0291018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0291023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0292013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0292018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0292023	Residential	Fluorescent	Chandelier	3200.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0303013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0303018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0303023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0323013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0323018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0323023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0333013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0333018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESPD0333023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0242013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0242018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0242023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0253013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0253018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0253023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0302013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0302018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0302023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0313013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0313018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0313023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0362013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0362018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0362023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESSF0373013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0373018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0373023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0472013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0472018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0472023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0483013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0483018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0483023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0532013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0532018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0532023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0543013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0543018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0543023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0592013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0592018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0592023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0603013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0603018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0603023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0682013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0682018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0682023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0693013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0693018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0693023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0761013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0761018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESSF0761023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0011013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0011018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0012013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0012018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0013013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0013018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0014013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0014018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0015013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		

















ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	KESVL0301013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0301018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0311013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0311018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0322013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0322018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0332013	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0332018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0341013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0341018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0351013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0361013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0371013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0372013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0373013	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0381013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0382013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0383013	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0384013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0385013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0391013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0391018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0392013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0392018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0393013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0393018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0394013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	KESVL0394018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	8/22/2012		
King One Products, Co.	King One Products, Co.	ODG-6401-123X X	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-6402-118X X	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-6403-118X X	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64179-118 XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64179-123 XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64182-118 XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64186-118 XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64187-218 XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	ODG-64189-113 XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
King One Products, Co.	King One Products, Co.	ODG-67133-213 XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	ODG-67135-213 XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	PDG-6601-218X X	Residential	Fluorescent	Decorative Pendant	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-6501-118 XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-65187-21 8XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-65187-22 3XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-6901-113 XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	WMG-6901-213 XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	WMG-6901-313 XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	WMG-6901-413 XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	WMG-69114-21 8XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-69115-21 3XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
King One Products, Co.	King One Products, Co.	WMG-69115-21 8XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
King One Products, Co.	King One Products, Co.	WMG-69115-22 3XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Lamps Plus Corporate	Casa Vieja	SKU T4198	Residential	Fluorescent	Ceiling Fan Light Kit	1602.0	24.0	67.0	N/A	0.5	2700.0	82.0	10000.0	8/31/2011		
Lamps Plus Corporate	Casa Vieja	SKU T4200	Residential	Fluorescent	Ceiling Fan Light Kit	1602.0	24.0	67.0	N/A	0.5	2700.0	82.0	10000.0	8/31/2011		
Lamps Plus Corporate	Casa Vieja	SKU T4201	Residential	Fluorescent	Ceiling Fan Light Kit	1602.0	24.0	67.0	N/A	0.5	2700.0	82.0	10000.0	8/31/2011		
Legrand	Legrand	ALLNLED	Residential	Solid State	Under Cabinet Luminaire	274.0	7.0	N/A	36.0	0.7	3000.0	95.0	40000.0	9/7/2012	Dimmable	
Legrand	Legrand	ALPKLED	Residential	Solid State	Under Cabinet Luminaire	238.0	6.0	N/A	38.0	0.7	3000.0	96.0	40000.0	9/7/2012	Dimmable	
Leviton Mfg Co., Inc.	Leviton	9860	Residential	Fluorescent	Ceiling Mount	600.0	13.27	67.88	N/A	0.557	2700.0	81.4	10000.0	6/27/2012		
Leviton Mfg Co., Inc.	Leviton	9860	Residential	Fluorescent	Ceiling Mount	900.0	13.7	68.7	N/A	0.63	2700.0	82.0	10000.0	7/25/2012		
Leviton Mfg Co., Inc.	Leviton	9862	Residential	Fluorescent	Ceiling Mount	600.0	13.27	67.88	N/A	0.557	2700.0	81.4	10000.0	6/27/2012		
Leviton Mfg Co., Inc.	Leviton	9862	Residential	Fluorescent	Ceiling Mount	900.0	13.7	68.7	N/A	0.63	2700.0	82.0	10000.0	7/25/2012		
Leviton Mfg Co., Inc.	Leviton	9863	Residential	Fluorescent	Ceiling Mount	600.0	13.27	67.88	N/A	0.557	2700.0	81.4	10000.0	6/27/2012		
Leviton Mfg Co., Inc.	Leviton	9863	Residential	Fluorescent	Ceiling Mount	900.0	13.7	68.7	N/A	0.63	2700.0	82.0	10000.0	7/25/2012		
LG Electronics, Inc.	LG	D4AN08xECC0	Both	Solid State	Downlight Recessed	501.0	8.0	N/A	63.0	0.9	3000.0	82.0	50000.0	11/7/2012	Dimmable	*x' suffix 1 and 2 refer to the products CCT: 3000K, 3500K, respectively
LG Electronics, Inc.	LG	D5AN11xECC0	Both	Solid State	Downlight Recessed	693.0	11.0	N/A	62.0	0.9	3000.0	83.0	50000.0	11/7/2012	Dimmable	*x' suffix 1 and 2 refer to the products CCT: 3000K, 3500K, respectively
LG Electronics, Inc.	LG	D6AN13xECC0	Both	Solid State	Downlight Recessed	806.0	12.0	N/A	64.0	0.9	3000.0	82.0	50000.0	11/7/2012	Dimmable	*x' suffix 1 and 2 refer to the products CCT: 3000K, 3500K, respectively
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.âââââ	010101-06XXXX ; "XXXX" means â finishesâ which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	010101-06XXXX YYYYYY; "XXXX" means a finishes which may be any alphanumeric character or symbol or blank; "YYYYYY" means a switch which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	010404-11XXXX ; "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	010404-13XXXX ; "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	020593-10XXXX ; "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	021358-28XXXX ; "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	021359-23XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/21/2012		
LiangHsin Lighting (Shenzhen) Co., Ltd.	LiangHsin Lighting (Shenzhen) Co., Ltd.	021359-39XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/21/2012		
Light Corporation	Lucio	LU	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
Light Engine Ltd.	Optiled	2018050117	Both	Solid State	Downlight Recessed	631.0	12.0	N/A	51.0	0.988	3000.0	82.0	50000.0	11/7/2012	Dimmable	*Additional CCT's 4000K, model no. 2018070117
Light Engine Ltd.	Optiled	2018408021	Both	Solid State	Downlight Solid State Retrofit	1041.0	15.0	N/A	67.0	0.9	4000.0	82.0	35000.0	8/22/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 CW BK	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	5000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 CW BN	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	5000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 CW WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	5000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 NW BK	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	4000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 NW BN	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	4000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 NW WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	4000.0	80.2	35000.0	3/29/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lighting Science Group, Corp	Commerical Electric	CED6 WW BK	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 WW BN	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Commerical Electric	CED6 WW WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 CW 120 BK	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	5000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 CW 120 BN	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	5000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 CW 120 WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	5000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 NW MTL 120 CC BK	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	4000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 NW MTL 120 CC BN	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	4000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 NW MTL 120 CC WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	4000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 W27 MTL 120 CC BK	Residential	Solid State	Downlight Solid State Retrofit	475.0	9.1	N/A	56.77	0.968	2700.0	81.4	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 W27 MTL 120 CC BN	Residential	Solid State	Downlight Solid State Retrofit	475.0	9.1	N/A	56.77	0.968	2700.0	81.4	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 W27 MTL 120 CC WH	Residential	Solid State	Downlight Solid State Retrofit	475.0	9.1	N/A	56.77	0.986	2700.0	81.4	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 WW MTL 120 CC BK	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	3000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 WW MTL 120 CC BN	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	3000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP4 WW MTL 120 CC WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	3000.0	81.9	35000.0	2/24/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 CW BK	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 CW BN	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 CW WH	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 NW BK	Residential	Solid State	Downlight Solid State Retrofit	750.0	13.295	N/A	54.03	0.792	4000.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 NW BN	Residential	Solid State	Downlight Solid State Retrofit	750.0	13.295	N/A	54.03	0.792	4000.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 NW WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	13.295	N/A	54.03	0.792	4000.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 W27 BK	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 W27 BN	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 W27 WH	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 WW BK	Residential	Solid State	Downlight Solid State Retrofit	718.2	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 WW BN	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Lighting Science Group, Corp	Glimpse	GLP6 WW WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.9	35000.0	3/29/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2024-C	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2024-D	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2024-F	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2026-F	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2026-H	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2044-C	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2044-D	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lighting Services Inc.	LumeLEX	LX2044-F	Both	Solid State	Accent Light Line-voltage	1187.0	24.4	N/A	48.6	0.989	2700.0	80.0	36000.0	9/19/2012	Dimmable	
Lightolier	Lightolier	LLABR17120 / LLABR17BK0XX H2XXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.986	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lightolier	Lightolier	LLABR17120 / LLABR17BK1XX H2XXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.993	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17120 / LLABR17WH0X XH2XXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.986	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17120 / LLABR17WH1X XH2XXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.993	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17277 / LLABR17BK0XX H2XXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.901	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17277 / LLABR17BK1XX H2XXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.901	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17277 / LLABR17WH0X XH2XXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.901	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR17277 / LLABR17WH1X XH2XXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.901	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24120 / LLABR24BK0XX H3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.986	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24120 / LLABR24BK1XX H3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.993	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24120 / LLABR24WH0X XH3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.986	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24120 / LLABR24WH1X XH3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.993	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24277 / LLABR24BK0XX H3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.901	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24277 / LLABR24BK1XX H3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.901	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lightolier	LLABR24277 / LLABR24WH0X XH3XXXXXXXXXX	Commercial	Solid State	Downlight Recessed	962.0	18.56	N/A	51.8	0.901	2700.0	86.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lightolier	Lightolier	LLABR24277 / LLABR24WH1X XH3XXXXXXXXX	Commercial	Solid State	Downlight Recessed	1324.0	30.48	N/A	43.4	0.901	2700.0	85.0	36000.0	10/25/2012	Dimmable	Data listed is for 2700K, the worst case scenario fixture. For specific fixture data please visit the Lightolier website.
Lightolier	Lytecaster	1001LED15N27 D1	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9913	2700.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1001LED15N27 D2	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9485	2700.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1001LED15N35 D1	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9913	3500.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1001LED15N35 D2	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9485	3500.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1013CDL27K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL27K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL27K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL30K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL30K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL30K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL35K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL35K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013CDL35K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L27K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L27K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L27K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	2700.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L30K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L30K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L30K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L35K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1013L35K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lightolier	Lytecaster	1013L35K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1050LRN0609D 2 / 1050LRN0927	Commercial	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.93	2700.0	83.0	36000.0	10/15/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1050LRN0609D 2 / 1050LRN0935	Commercial	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.93	3500.0	83.0	36000.0	10/15/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1050LRN09D1 / 1050LRN0927	Both	Solid State	Downlight Recessed	823.0	19.53	N/A	42.2	0.981	2700.0	83.0	36000.0	2/20/2012	Dimmable	
Lightolier	Lytecaster	1050LRN09D1 / 1050LRN0935	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.981	3500.0	83.0	36000.0	2/20/2012	Dimmable	
Lightolier	Lytecaster	1050LSQ0609D 2 / 1050LSQ0927	Commercial	Solid State	Downlight Recessed	994.0	22.48	N/A	44.3	0.93	2700.0	83.0	36000.0	10/15/2012	Dimmable	
Lightolier	Lytecaster	1050LSQ0609D 2 / 1050LSQ0935	Commercial	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.93	3500.0	83.0	36000.0	10/15/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1050LSQ09D1 / 1050LSQ0927	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.981	2700.0	83.0	36000.0	2/20/2012	Dimmable	
Lightolier	Lytecaster	1050LSQ09D1 / 1050LSQ0935	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.981	3500.0	83.0	36000.0	2/20/2012	Dimmable	
Lightolier	Lytecaster	1076WHL27K / 1004ICLED	Both	Solid State	Downlight Recessed	667.0	12.41	N/A	53.7	0.9189	2700.0	86.0	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL27K / 1004ICNLED	Both	Solid State	Downlight Recessed	667.0	12.41	N/A	53.7	0.9189	2700.0	86.0	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL27K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	667.0	12.41	N/A	53.7	0.9189	2700.0	86.0	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL30K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL30K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL30K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3000.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL35K / 1004ICLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL35K / 1004ICNLED	Both	Solid State	Downlight Recessed	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/7/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1076WHL35K / LARFA / 1004IC	Both	Solid State	Downlight Solid State Retrofit	N/A	N/A	N/A	N/A	0.9189	3500.0	N/A	36000.0	11/26/2012	Dimmable	For all luminaire specifications not listed here please visit the Lightolier website.
Lightolier	Lytecaster	1101LED15N27 D1	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9913	2700.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1101LED15N27 D2	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9485	2700.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1101LED15N35 D1	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9913	3500.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	1101LED15N35 D2	Both	Solid State	Downlight Recessed	1695.0	31.41	N/A	54.0	0.9485	3500.0	84.0	54000.0	8/15/2012	Dimmable	
Lightolier	Lytecaster	500L09AICD1 / 500LAA0930 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09AICD1 / 500LAA0930 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09AICD1 / 500LAA0930 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lightolier	Lytecaster	500L09AICD1 / 500LDL0630 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09AICD1 / 500LDL0630 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09AICD1 / 500LDL0630 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500AA0930 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500AA0930 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500AA0930 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500LDL0630 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500LDL0630 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09ND1 / 500LDL0630 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LAA0930 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LAA0930 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LAA0930 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LDL0630 / 504CL	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LDL0630 / 505BK	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	Lytecaster	500L09RD1 / 500LDL0630 / 505LWH	Both	Solid State	Downlight Recessed	703.0	13.09	N/A	54.0	0.98	3000.0	85.0	36000.0	3/12/2012	Dimmable	
Lightolier	LyteSpan	LLAB027-2700K -RF	Both	Solid State	Accent Light Line-voltage	895.0	16.17	N/A	55.4	0.982	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB027-2700K -RNF	Both	Solid State	Accent Light Line-voltage	930.6	16.21	N/A	57.4	0.982	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB027-2700K -RS	Both	Solid State	Accent Light Line-voltage	970.5	16.2	N/A	59.9	0.982	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB030-3000K -RF	Both	Solid State	Accent Light Line-voltage	952.0	16.2	N/A	58.8	0.982	3000.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB030-3000K -RNF	Both	Solid State	Accent Light Line-voltage	978.7	16.2	N/A	60.4	0.982	3000.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB030-3000K -RS	Both	Solid State	Accent Light Line-voltage	1029.0	16.2	N/A	63.5	0.982	3000.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB030-3000K -RSRNF	Both	Solid State	Accent Light Line-voltage	1010.0	16.2	N/A	62.3	0.982	3000.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RF	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.99	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	2700.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RNF	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.99	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RNF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	2700.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RS	Both	Solid State	Accent Light Line-voltage	1751.0	33.87	N/A	51.7	0.99	2700.0	86.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB127-2700K -RS-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	2700.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K -RF	Both	Solid State	Accent Light Line-voltage	1809.0	34.26	N/A	52.8	0.99	3000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K -RF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	3000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K -RNF	Both	Solid State	Accent Light Line-voltage	1889.0	34.24	N/A	55.2	0.99	3000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K -RNF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	3000.0	86.0	54000.0	7/17/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lightolier	LyteSpan	LLAB130-3000K-RS	Both	Solid State	Accent Light Line-voltage	1946.0	34.23	N/A	56.9	0.99	3000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K-RS-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	3000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K-RSRNF	Both	Solid State	Accent Light Line-voltage	1854.0	34.22	N/A	54.2	0.99	3000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB130-3000K-RSRNF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	3000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RF	Both	Solid State	Accent Light Line-voltage	1829.0	33.57	N/A	54.5	0.99	4000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	4000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RNF	Both	Solid State	Accent Light Line-voltage	1803.0	33.57	N/A	53.7	0.99	4000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RNF-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	4000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RS	Both	Solid State	Accent Light Line-voltage	1869.0	33.58	N/A	55.7	0.99	4000.0	85.0	54000.0	12/8/2011	Dimmable	
Lightolier	LyteSpan	LLAB140-4000K-RS-277V	Both	Solid State	Accent Light Line-voltage	1708.0	33.87	N/A	50.4	0.9186	4000.0	86.0	54000.0	7/17/2012	Dimmable	
Lightolier	LyteSpan	LLABS-2700K-RF	Both	Solid State	Accent Light Line-voltage	480.0	9.94	N/A	48.3	0.9262	2700.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLABS-2700K-RNF	Both	Solid State	Accent Light Line-voltage	516.0	9.94	N/A	51.9	0.9262	2700.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLABS-2700K-RS	Both	Solid State	Accent Light Line-voltage	535.0	9.94	N/A	53.8	0.9262	2700.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLABS-3000K-RF	Both	Solid State	Accent Light Line-voltage	551.0	9.94	N/A	55.4	0.9262	3000.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLABS-3000K-RNF	Both	Solid State	Accent Light Line-voltage	574.0	9.94	N/A	57.7	0.9262	3000.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLABS-3000K-RS	Both	Solid State	Accent Light Line-voltage	596.0	9.94	N/A	60.0	0.9262	3000.0	86.0	54000.0	9/20/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RF	Both	Solid State	Accent Light Line-voltage	455.6	9.584	N/A	47.5	0.9186	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RFSOL	Residential	Solid State	Accent Light Line-voltage	436.0	9.9	N/A	44.0	0.883	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RNF	Both	Solid State	Accent Light Line-voltage	459.0	9.581	N/A	47.9	0.9186	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RNFSOL	Both	Solid State	Accent Light Line-voltage	450.0	9.58	N/A	47.0	0.9186	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RS	Both	Solid State	Accent Light Line-voltage	457.0	9.593	N/A	47.6	0.9186	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-2700K-RSSOL	Both	Solid State	Accent Light Line-voltage	442.7	9.583	N/A	46.2	0.9186	2700.0	84.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RF	Both	Solid State	Accent Light Line-voltage	490.0	10.28	N/A	47.7	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RFSOL	Both	Solid State	Accent Light Line-voltage	453.9	10.28	N/A	44.12	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RNF	Both	Solid State	Accent Light Line-voltage	488.2	10.28	N/A	47.5	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RNFSOL	Both	Solid State	Accent Light Line-voltage	480.0	10.28	N/A	46.7	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RS	Both	Solid State	Accent Light Line-voltage	493.0	10.28	N/A	47.9	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	LyteSpan	LLAV00-3000K-RSSOL	Both	Solid State	Accent Light Line-voltage	480.0	10.28	N/A	46.6	0.902	3000.0	82.0	60000.0	3/15/2012	Dimmable	
Lightolier	TCP	LED14DR630K	Residential	Solid State	Downlight Recessed	850.0	14.0	N/A	60.7	0.887	3000.0	84.0	36000.0	11/27/2012	Dimmable	
Lights of America	Ceiling Lighting	4058WGT	Residential	Fluorescent	Ceiling Mount	981.38	13.83	70.96	N/A	0.615	2700.0	82.3	10000.0	4/13/2012		
Lights of America	Lights of America	7212LEDS-BK3	Residential	Solid State	Under Cabinet Luminaire	141.2	2.403	N/A	58.76	0.6	3000.0	81.1	25000.0	9/17/2012		
Lights of America	Lights of America	7212LEDS-WH3	Residential	Solid State	Under Cabinet Luminaire	141.2	2.403	N/A	58.76	0.6	3000.0	81.1	25000.0	9/17/2012		
Lights of America	Lights of America	7613S-CL3	Residential	Solid State	Under Cabinet Luminaire	157.0	3.0	N/A	52.33	0.75	3000.0	82.1	25000.0	9/17/2012		
Lights of America	Lights of America	7613S-CL4	Residential	Solid State	Under Cabinet Luminaire	157.0	3.0	N/A	52.33	0.75	3000.0	82.1	25000.0	9/24/2012		
Lights of America	Lights of America	7618S-CL3	Residential	Solid State	Under Cabinet Luminaire	249.7	4.736	N/A	52.72	0.652	3000.0	82.3	25000.0	9/19/2012		
Lights of America	Lights of America	7618S-CL4	Residential	Solid State	Under Cabinet Luminaire	249.7	4.736	N/A	52.72	0.652	3000.0	82.3	25000.0	9/24/2012		
Lights of America	Lights of America	7624S-CL3	Residential	Solid State	Under Cabinet Luminaire	316.4	6.088	N/A	51.97	0.737	3000.0	82.1	25000.0	9/19/2012		
Lights of America	Lights of America	7624S-CL4	Residential	Solid State	Under Cabinet Luminaire	316.4	6.088	N/A	51.97	0.737	4000.0	82.1	25000.0	9/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lites "R" Us Co., Ltd.	Bel Air Lighting	OU080328-3;OU080330-1;4484-PL;2942B;2952B-C09;2851B;2852B;2853B;2852P;2841B;2842B;2843B;2842P;2821B;2822B	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.82	N/A	0.548	2700.0	82.4	10000.0	6/28/2012		
Lithonia Lighting	Evo	27/10-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/10-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/14-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/14-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/18-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/18-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	27/22-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Evo	27/29-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/10-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/10-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/14-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/14-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/18-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/18-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Evo	30/18-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/22-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	30/29-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/10-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/10-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/14-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/14-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Evo	35/18-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/18-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/18-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/22-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	35/29-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/10-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/10-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Evo	41/14-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/14-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/18-4XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/18-6XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/18-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/22-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Evo	41/29-8XX-YY	Both	Solid State	Downlight Recessed	868.0	20.5	N/A	43.0	1.0	2700.0	84.0	60000.0	9/6/2012	Dimmable	XX = AR for Clear, PR for Pewter, WRT for Wheat, GR for Gold, or WR for White Reflector. YY = LD for matte-diffuse or LS for Clear Specular Reflector Finish. YY = LD for matte-diffuse or LS for Clear Specular.
Lithonia Lighting	Lithonia	UCLD XX YY	Residential	Solid State	Under Cabinet Luminaire	222.0	5.28	N/A	42.1	0.798	3000.0	83.0	36000.0	4/5/2012		Includes 12", 18", and 24" models. XX = Length, YY = Finish
Lithonia Lighting	Lithonia Lighting	10636RE OA	Residential	Fluorescent	Ceiling Mount	N/A	59.0	N/A	N/A	0.6	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	10637RE OA	Residential	Fluorescent	Ceiling Mount	N/A	112.0	N/A	N/A	0.58	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	10640RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	10642RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Lithonia Lighting	10648RE (BZ/BN)	Residential	Fluorescent	Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3500, 4000, 4100	N/A	10000.0	4/20/2012		BZ represents Antique Bronze, BN represents Brush Nickel
Lithonia Lighting	Lithonia Lighting	10813 BN	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	10814 BZA	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	10976(BNP)	Residential	Fluorescent	Ceiling Mount	1600.0	23.76	72.33	N/A	0.568	2700.0	82.1	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	10976(BZ)	Residential	Fluorescent	Ceiling Mount	1600.0	23.76	72.33	N/A	0.568	2700.0	82.1	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	10976(WH)	Residential	Fluorescent	Ceiling Mount	1600.0	23.76	72.33	N/A	0.568	2700.0	82.1	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	11232RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/14/2012		
Lithonia Lighting	Lithonia Lighting	11233 RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	11430RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	11432 RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	11432RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	11602RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/14/2012		
Lithonia Lighting	Lithonia Lighting	11604RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	11642RE BNS	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	11642RE BZ	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	11642RE WH	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	11644 RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	11656RE OA	Residential	Fluorescent	Ceiling Mount	N/A	112.0	N/A	N/A	0.58	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	11694RE	Residential	Fluorescent	Ceiling Mount	N/A	112.0	N/A	N/A	0.58	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	11741RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/14/2012		
Lithonia Lighting	Lithonia Lighting	11742RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/14/2012		
Lithonia Lighting	Lithonia Lighting	11746RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/14/2012		
Lithonia Lighting	Lithonia Lighting	11832 KR	Residential	Fluorescent	Ceiling Mount	1600.0	23.76	72.33	N/A	0.568	2700.0	82.1	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	11981(BNP)	Residential	Fluorescent	Ceiling Mount	900.0	13.83	70.97	N/A	0.615	2700.0	82.3	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	11981(BZ)	Residential	Fluorescent	Ceiling Mount	900.0	13.83	70.97	N/A	0.615	2700.0	82.3	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	11981(WH)	Residential	Fluorescent	Ceiling Mount	900.0	13.83	70.97	N/A	0.615	2700.0	82.3	10000.0	3/29/2012		
Lithonia Lighting	Lithonia Lighting	1233 CW 232	Residential	Fluorescent	Close to Ceiling Mount	N/A	59.0	N/A	N/A	0.6	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	1241DP RE	Residential	Fluorescent	Close to Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3500, 4000, 4100	N/A	10000.0	4/20/2012		
Lithonia Lighting	Lithonia Lighting	1241DP RE	Residential	Fluorescent	Close to Ceiling Mount	4882.323	58.12	84.013	N/A	0.564	3500, 4000, 4100	80.0	10000.0	6/15/2012		
Lithonia Lighting	Lithonia Lighting	1242ZG RE	Residential	Fluorescent	Close to Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	Lithonia Lighting	1245	Residential	Fluorescent	Close to Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3500, 4000, 4100	N/A	10000.0	4/20/2012		
Lithonia Lighting	Lithonia Lighting	1284GRD RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3255RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3324	Residential	Fluorescent	Ceiling Mount	2388.0	31.7	75.3	N/A	0.54	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3348	Residential	Fluorescent	Ceiling Mount	4446.0	53.6	82.9	N/A	0.56	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3776RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3902RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/20/2012		
Lithonia Lighting	Lithonia Lighting	3940RE	Residential	Fluorescent	Ceiling Mount	N/A	59.0	N/A	N/A	0.6	3500.0	N/A	10000.0	9/5/2012		
Lithonia Lighting	Lithonia Lighting	4BLMWLED	Residential	Solid State	Downlight Recessed	422.564	8.97	N/A	46.128	0.836	3000.0	82.0	35000.0	2/2/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	5BLMWLED	Residential	Solid State	Downlight Recessed	657.345	12.99	N/A	50.217	0.777	3000.0	83.0	35000.0	2/2/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	6BLMW LED	Residential	Solid State	Downlight Recessed	683.609	14.26	N/A	47.572	0.756	3000.0	80.0	35000.0	2/15/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	FMCL 13 ACRD	Residential	Fluorescent	Ceiling Mount	900.0	12.93	69.8	N/A	0.589	3000.0	84.0	10000.0	3/19/2012		
Lithonia Lighting	Lithonia Lighting	LB 2 17 120 RE	Residential	Fluorescent	Ceiling Mount	2592.0	33.0	78.5	N/A	0.544	3500.0	N/A	10000.0	5/1/2012		
Lithonia Lighting	Lithonia Lighting	LB 2 32 120 GESB	Residential	Fluorescent	Ceiling Mount	4742.0	56.0	85.0	N/A	0.991	3500.0	N/A	10000.0	4/25/2012		
Lithonia Lighting	Lithonia Lighting	LB 2 32 120 RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/23/2012		
Lithonia Lighting	Lithonia Lighting	LB 4 32 120 1/4 GESB	Residential	Fluorescent	Ceiling Mount	9678.0	112.0	86.4	N/A	0.996	3500.0	N/A	10000.0	5/17/2012		
Lithonia Lighting	Lithonia Lighting	LB 4 32 120 GESB	Residential	Fluorescent	Ceiling Mount	9484.0	103.0	92.0	N/A	0.991	3500.0	N/A	10000.0	4/25/2012		
Lithonia Lighting	Lithonia Lighting	LB 4 32 120 RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/23/2012		
Lithonia Lighting	Lithonia Lighting	LK3BMWLED	Residential	Solid State	Downlight Recessed	357.8	7.35	N/A	49.081	0.833	3000.0	82.0	35000.0	12/2/2011	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Lithonia Lighting	LK3BPMW LED	Residential	Solid State	Downlight Recessed	408.0	8.0	N/A	49.0	0.7	3000.0	80.0	28000.0	6/29/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	LK4BMWLED	Residential	Solid State	Downlight Recessed	422.564	8.97	N/A	46.128	0.836	3000.0	82.0	35000.0	12/2/2011	Dimmable	
Lithonia Lighting	Lithonia Lighting	LK4BPMW LED	Residential	Solid State	Downlight Recessed	497.0	9.0	N/A	50.0	0.7	3000.0	80.0	28000.0	6/29/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	LK4GMW LED	Residential	Solid State	Downlight Recessed	433.0	10.0	N/A	42.0	0.7	3000.0	81.0	35000.0	6/28/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	LK5BMWLED	Residential	Solid State	Downlight Recessed	657.345	12.99	N/A	50.217	0.777	3000.0	83.0	35000.0	12/2/2011	Dimmable	
Lithonia Lighting	Lithonia Lighting	LK5BPMW LED	Residential	Solid State	Downlight Recessed	578.0	11.0	N/A	52.0	0.7	3000.0	80.0	30000.0	6/29/2012	Dimmable	
Lithonia Lighting	Lithonia Lighting	NEW 2 32 120 RE (BN/BZ)	Residential	Fluorescent	Ceiling Mount	3854.5	59.3	65.0	N/A	0.5741	3500, 4000, 4100	N/A	10000.0	4/20/2012		BZ represents Antique Bronze, BN represents Brush Nickel
Lithonia Lighting	Lithonia Lighting	NEW 2 32 120 RE (BN/BZ)	Residential	Fluorescent	Ceiling Mount	4882.323	58.12	84.013	N/A	0.564	3500, 4000, 4100	80.0	10000.0	6/15/2012		BZ represents Antique Bronze, BN represents Brush Nickel
Lithonia Lighting	Lithonia Lighting	OFLLED 12	Residential	Solid State	Inseparable Solid State	1557.0	20.0	N/A	78.0	0.8	N/A	N/A	55000.0	10/16/2012		
Lithonia Lighting	Lithonia Lighting	OLAW25 40K 120 PE DBB	Residential	Solid State	Downlight Surface Mount	2540.0	36.0	N/A	71.0	0.874	4000.0	74.8	50000.0	11/16/2012		
Lithonia Lighting	Lithonia Lighting	Real6 D6MW ESL 35K	Both	Solid State	Downlight Recessed	642.8	11.513	N/A	55.9	0.956	3500.0	80.0	35000.0	1/26/2012		
Lithonia Lighting	Lithonia Lighting	Real6 D6MW ESL 40K	Both	Solid State	Downlight Recessed	642.8	11.513	N/A	55.9	0.956	3500.0	80.0	35000.0	1/26/2012		
Lithonia Lighting	Lithonia Lighting	SB 2 17 120 RE	Residential	Fluorescent	Ceiling Mount	2592.0	33.0	78.5	N/A	0.544	3500.0	N/A	10000.0	4/25/2012		
Lithonia Lighting	Lithonia Lighting	SB 2 32 120 GESB	Residential	Fluorescent	Ceiling Mount	4742.0	56.0	85.0	N/A	0.991	3500.0	N/A	10000.0	4/25/2012		
Lithonia Lighting	Lithonia Lighting	SB 2 32 120 RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/23/2012		
Lithonia Lighting	Lithonia Lighting	SB 4 17 120 RE	Residential	Fluorescent	Ceiling Mount	5184.0	67.0	77.4	N/A	0.544	3500.0	N/A	10000.0	5/1/2012		
Lithonia Lighting	Lithonia Lighting	SB 4 32 120 1/4 GESB	Residential	Fluorescent	Ceiling Mount	9678.0	112.0	86.4	N/A	0.996	3500.0	N/A	10000.0	5/17/2012		
Lithonia Lighting	Lithonia Lighting	SB 4 32 120 RE	Residential	Fluorescent	Ceiling Mount	9910.0	112.0	88.6	N/A	0.58	3500.0	N/A	10000.0	3/23/2012		
Lithonia Lighting	Lithonia Lighting	XWL 2 32 120 RE	Residential	Fluorescent	Ceiling Mount	4959.0	59.0	84.1	N/A	0.6	3500.0	N/A	10000.0	3/15/2012		
Lithonia Lighting	P-series	6BP	Both	Solid State	Downlight Solid State Retrofit	589.0	9.0	N/A	66.0	0.9	3000.0	86.0	36000.0	10/25/2012	Dimmable	
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.60SC 27K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.60SC 30K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.60SC 35K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.60SC 40K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.90SC 27K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.90SC 30K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.90SC 35K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6C D6xxx ESL yyyL 0.90SC 40K	Both	Solid State	Downlight Recessed	1030.0	18.27	N/A	56.0	1.0	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 1000 for 1000 Lumens or 1500 for 1500 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.60SC 27K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.60SC 30K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.60SC 35K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.60SC 40K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.90SC 27K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.90SC 30K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.90SC 35K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Lithonia Lighting	Reality	REAL6 D6xxx ESL yyyL 0.90SC 40K	Both	Solid State	Downlight Solid State Retrofit	560.0	8.29	N/A	68.0	0.9	2700.0	82.0	36000.0	6/26/2012	Dimmable	xxx = A for Clear Diffuse, AZ for Semi-Specular, BLZ for Black Specular, BN for Brushed Nickel, BZA for Antique Bronze, MW for Matte White, ORB for Oil-rubbed bronze, or WT for Wheat Diffuse Trim Finish. Yyy = 600 for 600 Lumens or 1000 for 1000 Lumens
LittleFootprint Lighting, Incorporated	LittleFootprint Lighting	HERONLED01	Commercial	Solid State	Portable Desk Task Light	219.0	4.0	N/A	51.0	0.6	3000.0	82.0	36000.0	8/10/2012		
L-Tech Corporation	L-TECH CORP	LD400ICA (LT400W/403W)	Both	Solid State	Downlight Recessed	572.57	12.56	N/A	47.46	0.976	3000.0	82.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD400ICA (LT401W)	Both	Solid State	Downlight Recessed	688.82	12.47	N/A	57.49	0.975	3000.0	82.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD400ICRA (LT400W/403W)	Both	Solid State	Downlight Recessed	572.57	12.56	N/A	47.46	0.976	3000.0	82.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD400ICRA (LT401W)	Both	Solid State	Downlight Recessed	688.82	12.47	N/A	57.49	0.975	3000.0	82.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD600ICA (LT600W/603W)	Both	Solid State	Downlight Recessed	944.12	17.29	N/A	58.06	0.974	3000.0	83.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD600ICA (LT601W)	Both	Solid State	Downlight Recessed	875.94	17.25	N/A	51.09	0.975	3000.0	83.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD600ICRA (LT600W/603W)	Both	Solid State	Downlight Recessed	944.12	17.29	N/A	58.06	0.974	3000.0	83.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LD600ICRA (LT601W)	Both	Solid State	Downlight Recessed	875.94	17.25	N/A	51.09	0.975	3000.0	83.0	35000.0	6/28/2012		
L-Tech Corporation	L-TECH CORP	LRKT400/403	Both	Solid State	Downlight Recessed	472.37	10.08	N/A	46.11	0.99	3000.0	80.0	35000.0	6/15/2012		
L-Tech Corporation	L-TECH CORP	LRKT401	Both	Solid State	Downlight Recessed	528.45	9.98	N/A	52.26	0.99	3000.0	80.0	35000.0	6/15/2012		
L-Tech Corporation	L-TECH CORP	LRKT600/603	Both	Solid State	Downlight Recessed	676.2	15.11	N/A	44.87	0.955	3000.0	81.0	35000.0	6/15/2012		
L-Tech Corporation	L-TECH CORP	LRKT601	Both	Solid State	Downlight Recessed	687.46	15.07	N/A	45.29	0.956	3000.0	80.0	35000.0	6/15/2012		
Lumateq, Div. Of Taco Metals, Inc.	LUMATEQ	LB40	Residential	Solid State	Outdoor Post-mounted	1416.892	43.212	99.96	N/A	0.996	N/A	N/A	35000.0	10/11/2012		
Lumateq, Div. Of Taco Metals, Inc.	LUMATEQ	LB60	Residential	Solid State	Outdoor Post-mounted	2523.512	57.888	99.96	N/A	0.997	N/A	N/A	35000.0	10/11/2012		
Lumateq, Div. Of Taco Metals, Inc.	LUMATEQ	LL50, LL51	Residential	Solid State	Outdoor Post-mounted	421.402	46.093	99.29	N/A	0.817	N/A	N/A	35000.0	10/11/2012		
LumenOptix LLC	Lumenoptix	LRD-XX-XX-XXX-XX	Residential	Solid State	Downlight Recessed	2318.0	48.86	N/A	47.4	0.994	2700.0	82.0	36000.0	10/5/2012		
Lumivert Incorporated	Lumivert Incorporated	5205	Residential	Fluorescent	Bath Vanity	4500.0	65.0	69.0	N/A	0.578	2700.0	83.0	10000.0	12/20/2011		
Maxlite	MaxLED	ML2L141RR6W30; ML2L141RR6NI30	Both	Solid State	Downlight Solid State retrofit	626.47	13.65	N/A	45.91	0.95	3000.0	80.7	35000.0	12/27/2011	Dimmable	
Maxlite	MaxLED	RR61430	Both	Solid State	Downlight Solid State Retrofit	920.0	13.0	N/A	70.0	0.9	3000.0	87.0	50000.0	11/16/2012	Dimmable	
Maxlite	MaxLite	ML10Gxxxxxx	Residential	Fluorescent	Chandelier	2400.0	32.91	65.6	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxxxx = 393BTBZ, 655BTBZ
Maxlite	MaxLite	ML1G4523xxxx	Residential	Fluorescent	Torchieres	3230.0	44.0	73.4	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = ARBK, ARW, ARBK-157, ARW-157
Maxlite	MaxLite	ML1G7033xxxx	Residential	Fluorescent	Torchieres	3230.0	44.0	73.4	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = ARBK, ARW, ARBK-157, ARW-157
Maxlite	MaxLite	ML2G181xxxx	Residential	Fluorescent	Ceiling Mount	1380.0	18.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = OB, TRBR, TRNI, TRW
Maxlite	MaxLite	ML2G231xxxx	Residential	Fluorescent	Ceiling Mount	1580.0	23.0	68.7	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = GLBK, OBNI
Maxlite	MaxLite	ML2G261xxxx	Residential	Fluorescent	Ceiling Mount	1850.0	26.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = BTBZ, TRNI, TRW
Maxlite	MaxLite	ML2G262xxxx	Residential	Fluorescent	Ceiling Mount	1600.0	21.94	65.6	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = CLSW
Maxlite	MaxLite	ML2G362xxxx	Residential	Fluorescent	Ceiling Mount	2760.0	36.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = ALNI, ALW, CNNI, PRNIPBP, PRWP, CLSW, OB, TRBR, TRNI, TRNIBP, TRW, TRWBP, BTBZ
Maxlite	MaxLite	ML4G181xxxx	Residential	Fluorescent	Other	1380.0	18.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = CLBK, BLBZ, PLBKPL, OLBK, OLW, ELBK, JJBK, GLBK, PLBK

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Maxlite	MaxLite	ML5G261xxxx	Residential	Fluorescent	Table Lamps	1850.0	26.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = CSAB, CASB/ BP, CSNI, CSNI/BP, WI
Maxlite	MaxLite	ML6G522xxxx	Residential	Fluorescent	Floor Lamps	3700.0	52.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = CSAB, CSNI, WI
Maxlite	MaxLite	ML7G261xxxx	Residential	Fluorescent	Table Lamps	1850.0	26.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = CT, DR
Maxlite	MaxLite	ML8G522xxxx	Residential	Fluorescent	Bath Vanity	3700.0	52.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = RBNIBP
Maxlite	MaxLite	ML8G543xxxx	Residential	Fluorescent	Bath Vanity	4140.0	54.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = TUNI
Maxlite	MaxLite	ML8Gxxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	32.91	65.6	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxxxxx = 131BTBZ, 393BTBZ
Maxlite	MaxLite	ML9G181xxxx	Residential	Fluorescent	Wall Sconces	1380.0	18.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = BTBZ
Maxlite	MaxLite	ML9G261xxxx	Residential	Fluorescent	Wall Sconces	1850.0	26.0	71.2	N/A	0.6	2700.0	82.0	10000.0	3/22/2012		xxxx = ALWBP, CC/ BP, TRNIBP, TRW/ BP
Maxlite	MaxLite	MLxG181xxxx	Residential	Fluorescent	Table Lamps	1380.0	18.0	76.67	N/A	0.5	2700.0	82.0	10000.0	3/22/2012		xxxx = LCO, CUPN
Megalight Inc.	MegaLight	DL6-600	Both	Solid State	Downlight Solid State retrofit	626.47	13.7	N/A	45.91	0.95	3000.0	80.7	35000.0	6/14/2012	Dimmable	
Minka Group	Minka Lavery	1420-281-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1420-84-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1421-84-PL	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1422-84-PL	Residential	Fluorescent	Decorative Pendant	3200.0	47.88	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1424-84-PL	Residential	Fluorescent	Close to Ceiling Mount	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1425-84-PL	Residential	Fluorescent	Chandelier	4000.0	59.85	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	1426-84-PL	Residential	Fluorescent	Decorative Pendant	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	341-172-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	341-248-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	341-357-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	341-84-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	342-172-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	342-248-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	342-357-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	342-84-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	368-PL	Residential	Fluorescent	Wall Sconces	2760.0	32.5	84.9	N/A	0.5	2700.0	82.0	10000.0	7/10/2012		
Minka Group	Minka Lavery	370-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	505-84-PL	Residential	Fluorescent	Wall Sconces	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	7/10/2012		
Minka Group	Minka Lavery	5422-84-PL	Residential	Fluorescent	Bath Vanity	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	5423-84-PL	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	5424-84-PL	Residential	Fluorescent	Bath Vanity	3200.0	47.88	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	62-84-PL	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	63-84-PL	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	66-84-PL	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	866-44-PL	Residential	Fluorescent	Ceiling Mount	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	867-44-PL	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	893-84-PL	Residential	Fluorescent	Ceiling Mount	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
Minka Group	Minka Lavery	893-91-PL	Residential	Fluorescent	Ceiling Mount	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	8/23/2012		
MP Lighting	Paulmann	79458	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	79459	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	79460	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	79461	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	835	Residential	Fluorescent	Close to Ceiling Mount	800.0	13.0	67.0	N/A	0.5	2700.0	82.0	10000.0	11/27/2012		
MP Lighting	Paulmann	836	Residential	Fluorescent	Close to Ceiling Mount	800.0	13.0	67.0	N/A	0.5	2700.0	82.0	10000.0	11/27/2012		
MP Lighting	Paulmann	99831	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99832	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99833	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99834	Residential	Fluorescent	Other	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99835	Residential	Fluorescent	Close to Ceiling Mount	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
MP Lighting	Paulmann	99836	Residential	Fluorescent	Close to Ceiling Mount	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99837	Residential	Fluorescent	Close to Ceiling Mount	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99838	Residential	Fluorescent	Close to Ceiling Mount	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99839	Residential	Fluorescent	Wall Sconces	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
MP Lighting	Paulmann	99840	Residential	Fluorescent	Wall Sconces	800.0	12.0	67.0	N/A	0.5	2700.0	82.0	10000.0	9/6/2012		
M-Tech International Corporation	Lumira	LM-4CW-10	Both	Solid State	Downlight Solid State Retrofit	421.0	10.0	N/A	43.0	0.9	3000.0	83.0	36000.0	8/1/2012	Dimmable	
M-Tech International Corporation	Lumira	LM-4HW-10	Both	Solid State	Downlight Solid State Retrofit	421.0	10.0	N/A	43.0	0.9	3000.0	83.0	36000.0	8/1/2012	Dimmable	
M-Tech International Corporation	Lumira	LM-4WW-10	Both	Solid State	Downlight Solid State Retrofit	421.0	10.0	N/A	43.0	0.9	3000.0	83.0	36000.0	8/1/2012	Dimmable	
M-Tech International Corporation	Lumiraâ LED Lighting	LM-6HW-12	Both	Solid State	Downlight Solid State Retrofit	645.0	15.0	N/A	43.0	0.9	3000.0	86.0	36000.0	9/10/2012	Dimmable	
M-Tech International Corporation	Lumiraâ LED Lighting	LM-6WW-12	Both	Solid State	Downlight Solid State Retrofit	645.0	15.0	N/A	43.0	0.9	3000.0	86.0	36000.0	9/10/2012	Dimmable	
Nanghai Bright Electrical Lighting Co., Ltd.	Preferred Industries	131484	Residential	Fluorescent	Ceiling Mount	3960.0	64.0	70.14	N/A	0.619	4100.0	84.3	10000.0	5/23/2012		
Nanghai Bright Electrical Lighting Co., Ltd.	Preferred Industries	131485; 131488	Residential	Fluorescent	Ceiling Mount	1300.0	22.0	66.8	N/A	0.575	4100.0	84.1	10000.0	5/23/2012		
Nanghai Bright Electrical Lighting Co., Ltd.	Preferred Industries	131486	Residential	Fluorescent	Ceiling Mount	4590.0	72.0	73.92	N/A	0.611	4100.0	84.3	10000.0	5/23/2012		
Nanghai Bright Electrical Lighting Co., Ltd.	Preferred Industries	131487	Residential	Fluorescent	Ceiling Mount	2980.0	54.0	67.4	N/A	0.638	4100.0	84.1	10000.0	5/23/2012		
Neo-Neon International Ltd	Neo-Neon	B10881A (2700K)	Both	Solid State	Downlight Recessed	700.0	9.5	N/A	72.25	0.9837	2700.0	84.8	35000.0	8/3/2012	Dimmable	
Neo-Neon International Ltd	Neo-Neon	B10881A (3000K)	Both	Solid State	Downlight Recessed	700.0	9.5	N/A	72.25	0.9837	3000.0	84.8	35000.0	8/3/2012	Dimmable	
Neo-Neon International Ltd	Neo-Neon, American lighting	B0611-(Cree lamp)	Residential	Solid State	Downlight Solid State retrofit	656.07	12.56	N/A	52.99	0.912	3000.0	82.0	35000.0	11/15/2011		
Neo-Neon International Ltd	Neo-Neon, American lighting	B0611-(Nichia lamp)	Residential	Solid State	Downlight Solid State retrofit	605.75	13.36	N/A	45.34	0.913	3000.0	85.0	35000.0	11/15/2011		
Neo-Neon International Ltd	Neo-Neon, American lighting	B0881A-E26, B0881A-GU24	Residential	Solid State	Downlight Solid State retrofit	643.94	12.29	N/A	52.41	0.964	3000.0	83.0	25000.0	2/6/2012		B0881A-GU24: GU24 base
Nicor Inc.	NICOR	DLR4-10-120V-3 K-XX	Both	Solid State	Downlight Solid State Retrofit	533.0	10.95	N/A	48.8	0.955	3000.0	83.0	36000.0	7/13/2012	Dimmable	
Nicor Inc.	NICOR	DLR4-10-120V-4 K-XX	Both	Solid State	Downlight Solid State Retrofit	584.0	11.16	N/A	52.4	0.955	4000.0	85.0	36000.0	7/13/2012	Dimmable	
Nicor Inc.	NICOR	DLR4-10-120V-5 K-XX	Both	Solid State	Downlight Solid State Retrofit	633.0	11.18	N/A	56.7	0.955	5000.0	81.0	36000.0	7/13/2012	Dimmable	
Nicor Inc.	NICOR	NSSLR-1-3-14-5 6-W	Both	Solid State	Downlight Solid State Retrofit	857.0	14.41	N/A	59.5	0.957	3000.0	82.0	35000.0	12/14/2011	Dimmable	
Nicor Inc.	NICOR	NSSLR-1-4-14-5 6-W	Both	Solid State	Downlight Solid State Retrofit	864.0	14.02	N/A	61.5	0.957	4000.0	83.0	35000.0	12/14/2011	Dimmable	
Nicor Inc.	NICOR	NSSLR-1-5-14-5 6-W	Both	Solid State	Downlight Solid State Retrofit	907.0	14.39	N/A	63.1	0.957	5000.0	80.0	35000.0	12/14/2011	Dimmable	
Ningbo Utec Electric Co.,Ltd	LUTEC UME	6144-1-PHO	Residential	Solid State	Inseparable Solid State	1644.0	19.32	N/A	84.65	0.99	N/A	N/A	60000.0	10/24/2012		
Ningbo Utec Electric Co.,Ltd	LUTEC UME	6144S-2-PIR	Residential	Solid State	Inseparable Solid State	1210.0	14.42	N/A	83.9	0.99	N/A	N/A	60000.0	12/30/1899		
Ningbo Utec Electric Co.,Ltd	LUTEC UME	6156-PIR	Residential	Solid State	Inseparable Solid State	1182.0	15.38	N/A	76.9	0.99	N/A	N/A	60000.0	10/24/2012		
Ningbo Utec Electric Co.,Ltd	LUTEC UME	where X maybe any alphanumeric representing vendor, color codes. The model number is not restricted by the number of alphanumerics. More or less alphanumeric characters may be used to make up the vendors model number.	Residential	Solid State	Inseparable Solid State	2349.4	33.0	N/A	71.3	0.99	N/A	N/A	35000.0	10/24/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Nora Lighting	Nora Lighting	NLEDC-46127	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46127xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46130	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46130xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46140	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46140xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46227	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46227xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46230	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46230xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46240	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-46240xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56227W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56227X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56230W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56230X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56240W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-56240X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58127W	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58127X	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58130W	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58130X	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58140W	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58140X	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58227W	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58227X	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58230W	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58230X	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58240W	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-58240X	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66127W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66127X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66130W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66130X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66140W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66140X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66227W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66227X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66230W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Nora Lighting	Nora Lighting	NLEDC-66230X X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66240W W	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-66240X X	Both	Solid State	Downlight Recessed	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68127W W	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68127X X	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68130W W	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68130X X	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68140W W	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68140X X	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68227W W	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68227X X	Both	Solid State	Downlight Recessed	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68230W W	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68230X X	Both	Solid State	Downlight Recessed	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68240W W	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDC-68240X X	Both	Solid State	Downlight Recessed	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46127	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46127xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46130	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46130xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46140	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46140xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46227	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46227xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46230	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46230xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46240	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	1/9/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-46240xx	Both	Solid State	Downlight Solid State Retrofit	576.0	11.0	N/A	51.0	0.9	2700.0	92.0	35000.0	2/3/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56227W W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56227X X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56230W W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56230X X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56240W W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-56240X X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58127W W	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58127X X	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58130W W	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58130X X	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58140W W	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58140X X	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Nora Lighting	Nora Lighting	NLEDR-58227W	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58227X	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58230W	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58230X	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58240W	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-58240X	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66127W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66127X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66130W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66130X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66140W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66140X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66227W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66227X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66230W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66230X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	3000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66240W	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-66240X	Both	Solid State	Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	4000.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68127W	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68127X	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68130W	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68130X	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68140W	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68140X	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68227W	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68227X	Both	Solid State	Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68230W	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68230X	Both	Solid State	Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68240W	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDR-68240X	Both	Solid State	Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-56127X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-56130X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-56140X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-56227X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Nora Lighting	Nora Lighting	NLEDX-56230X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-56240X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58127X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58130X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58140X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58227X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58230X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-58240X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/18/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66127X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66130X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66140X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66227X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66230X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-66240X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	617.0	10.57	N/A	58.4	0.915	2700.0	80.0	36000.0	5/8/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68127X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/24/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68130X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/24/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68140X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/24/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68227X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	903.0	15.6	N/A	57.9	0.982	2700.0	90.0	36000.0	4/24/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68230X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	970.0	14.64	N/A	66.3	0.959	3000.0	93.0	36000.0	4/24/2012	Dimmable	
Nora Lighting	Nora Lighting	NLEDX-68240X X	Both	Solid State	Downlight Recessed, Downlight Solid State Retrofit	959.0	14.25	N/A	67.4	0.985	4000.0	91.0	36000.0	4/24/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Noribachi	Noribachi	L-I-DLS-021-A-WW-MT-XX-Y	Both	Solid State	Downlight Surface Mount	1155.0	26.0	N/A	44.0	0.9	3500.0	82.0	36000.0	9/28/2012		TRIM COLOR(XX): BK=Black; BL=Blue; RD=Red; GR=Green; OR=Orange; YE=Yellow; PU=Purple; OP=Opal; SL=Silver; GD=Gold; PT=Platinum; TI=Titanium. LENS TYPE(Y): F=Frosted; C=Clear; N=No Lens.
OSRAM SYLVANIA	Osram	707020	Both	Solid State	Downlight Solid State Retrofit	555.0	9.0	N/A	62.0	1.0	3000.0	83.0	50000.0	8/31/2012	Dimmable	
OSRAM SYLVANIA	Osram	70704	Both	Solid State	Downlight Solid State Retrofit	631.0	10.22	N/A	62.0	1.0	3000.0	83.0	50000.0	8/31/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70644 LED/625/RT6/830/FL80/WRFL/WTR/HVP	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70645 LED/625/RT6/830/FL80/WRFL/WTR/HVP	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70651 LED/625/RT6/830/FL80/WRFL/WTR/2PK	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70653	Both	Solid State	Downlight Solid State Retrofit	631.0	10.22	N/A	62.0	1.0	3000.0	83.0	50000.0	8/31/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70653 LED/625/RT6/830/FL80/WRFL/WTR/BOX	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70654	Both	Solid State	Downlight Solid State Retrofit	621.0	10.36	N/A	60.0	0.9	2700.0	82.0	50000.0	5/25/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70655 LED/625/RT6/830/FL80/WRFL/WTR/HVP/CND	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70658 LED/550/RT4/830/FL80/WRFL/WTR/HVP	Residential	Solid State	Downlight Solid State Retrofit	512.0	8.0	N/A	61.0	0.8	3000.0	83.0	35000.0	1/12/2012		
OSRAM SYLVANIA	Sylvania	70659 LED/550/RT4/830/FL80/WRFL/WTR/BOX	Residential	Solid State	Downlight Solid State Retrofit	512.0	8.0	N/A	61.0	0.8	3000.0	83.0	35000.0	1/12/2012		
OSRAM SYLVANIA	Sylvania	70664 LED/550/RT4/830/FL80/WRFL/WTR/HVP/OSL	Residential	Solid State	Downlight Solid State Retrofit	512.0	8.0	N/A	61.0	0.8	3000.0	83.0	35000.0	1/12/2012		
OSRAM SYLVANIA	Sylvania	70688 LED/550/RT4/827/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	559.0	9.0	N/A	61.0	1.0	2700.0	81.0	50000.0	4/5/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	70751 LED/625/RT6/830/FL80/WRFL/WTR/2PK	Residential	Solid State	Downlight Solid State Retrofit	645.0	10.51	N/A	61.0	0.7	3000.0	82.0	35000.0	2/16/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/1400/RT6/827/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	1030.0	16.35	N/A	63.0	1.0	2700.0	84.0	50000.0	9/18/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/1400/RT6/830/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	1030.0	16.35	N/A	63.0	1.0	3000.0	84.0	50000.0	9/18/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/1400/RT6/835/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	1030.0	16.35	N/A	63.0	1.0	3500.0	84.0	50000.0	9/18/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/550/RT4/830/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	555.0	9.0	N/A	62.0	1.0	3000.0	83.0	50000.0	8/31/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/600/RT4/830/FL80/WRFL/WTR	Residential	Solid State	Downlight Solid State Retrofit	614.0	9.26	N/A	66.0	1.0	3000.0	82.0	33000.0	11/14/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/625/RT5/827/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	610.0	10.43	N/A	58.0	1.0	2700.0	82.0	55200.0	9/18/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
OSRAM SYLVANIA	Sylvania	LED/625/RT5/830/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	610.0	10.43	N/A	58.0	1.0	3000.0	82.0	55200.0	9/18/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/700/RT6/830/FL80/WRFL/WTR	Residential	Solid State	Downlight Solid State Retrofit	614.0	9.26	N/A	66.0	1.0	3000.0	82.0	33000.0	11/14/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/700/RT6/830/FL80/WRFL/WTR/RP	Residential	Solid State	Downlight Solid State Retrofit	614.0	9.26	N/A	66.0	1.0	3000.0	82.0	33000.0	11/14/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	LED/700/RT6/840/FL80/WRFL/WTR/BOX	Both	Solid State	Downlight Solid State Retrofit	679.0	9.94	N/A	68.0	1.0	4000.0	85.0	55200.0	10/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70646 à LED/900/RT6/830/FL80/WRFL/WTR/HVP	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70647 à LED/900/RT6/830/FL80/WRFL/WTR/BOX	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70656 à LED/900/RT6/827/FL80/WRFL/WTR/BOX	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70703 à LED/900/RT6/G/830/FL80/WRFL/WTR/HVP/CD	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70705 à LED/900/RT6/G/830/FL80/WRFL/WTR/BOX	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70706 à LED/900/RT6/G/827/FL80/WRFL/WTR/BOX	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
OSRAM SYLVANIA	Sylvania	SKU 70707 à LED/900/RT6/G/830/FL80/WRFL/WTR/HVP	Commercial	Solid State	Downlight Solid State Retrofit	844.0	12.89	N/A	65.0	1.0	2700.0	80.0	50000.0	8/24/2012	Dimmable	
Philips Capri	Philips Capri	CRL4K-G1-6-27K-***	Both	Solid State	Downlight Solid State Retrofit	592.0	13.0	N/A	46.0	0.95	2700.0	81.0	54000.0	3/28/2012	Dimmable	*** = SL,BRZ,RCP,SPM,M CA, CBN, or TBZ finishes
Philips Capri	Philips Capri	CRL4K-G1-6-35K	Both	Solid State	Downlight Solid State Retrofit	626.0	12.0	N/A	54.0	0.9	3500.0	85.0	54000.0	3/23/2012	Dimmable	
Philips Capri	Philips Capri	CRL4K-G1-6-35K-***	Both	Solid State	Downlight Solid State Retrofit	626.0	12.0	N/A	54.0	0.9	3500.0	85.0	54000.0	3/23/2012	Dimmable	
Philips Capri	Philips Capri	CRL5K-G1-6-35K-CRL5-***	Both	Solid State	Downlight Solid State Retrofit	594.0	11.0	N/A	52.0	0.9	3500.0	86.0	54000.0	4/25/2012	Dimmable	
Philips Capri	Philips Capri	CRL6K-G2-6-27K-CRL6B-WHT	Both	Solid State	Downlight Solid State Retrofit	594.0	12.7	N/A	47.0	0.9	2700.0	82.0	36000.0	3/28/2012	Dimmable	inseparable
Philips Capri	Philips Capri	CRL6K-G2-6-27K-CRL6R-xxx	Both	Solid State	Downlight Solid State Retrofit	594.0	12.7	N/A	47.0	0.9	2700.0	82.0	36000.0	3/28/2012	Dimmable	inseparable
Philips Capri	Philips Capri	CRL6K-G2-6-35K-CRL6B-WHT	Both	Solid State	Downlight Solid State Retrofit	649.0	11.0	N/A	58.0	0.9	3500.0	86.0	36000.0	3/28/2012	Dimmable	
Philips Capri	Philips Capri	CRL6K-G2-6-35K-CRL6R-xxx	Both	Solid State	Downlight Solid State Retrofit	649.0	11.0	N/A	58.0	0.9	3500.0	86.0	36000.0	3/28/2012	Dimmable	
Philips Capri	Philips Capri	PRL6K-G1-6-27K	Both	Solid State	Downlight Solid State Retrofit	681.4	10.91	N/A	62.4	0.937	2700.0	80.8	50000.0	8/17/2012	Dimmable	All models identical with only exception being the base
Philips Lighting Company	AmbientLED; EnduraLED	9290002078	Residential	Solid State	Downlight Recessed	860.0	14.0	N/A	58.0	0.7	2700.0	85.0	45000.0	11/5/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-54Å Å	Both	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-55Å	Both	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-56	Both	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-57	Commercial	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-58	Commercial	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Alkco	523-000027-59	Commercial	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-00	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-01	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-02	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-03	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-04	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-05	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-06	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-07	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-08	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-09	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-10	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-11	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-12	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-13	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-14	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	2700.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-15	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-16	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-17	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-18	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	350-000006-19	Residential	Solid State	Under Cabinet Luminaire	173.0	3.28	N/A	53.0	0.8	4000.0	80.0	36000.0	5/18/2012		
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000009-14	Both	Solid State	Downlight Surface Mount	779.2	14.03	N/A	55.54	0.981	2700.0	82.0	35000.0	2/9/2012	Dimmable	Includes 3000K, 3500K, 4000K models, qualified only with the Driver Model Number 523-000010-00.
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000009-15	Both	Solid State	Downlight Surface Mount	796.936	14.1	N/A	56.52	0.981	3000.0	82.0	35000.0	2/9/2012	Dimmable	qualified only with the Driver Model Number 523-000010-00.
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000009-16	Both	Solid State	Downlight Surface Mount	807.135	14.12	N/A	57.163	0.981	3500.0	83.0	35000.0	2/9/2012	Dimmable	qualified only with the Driver Model Number 523-000010-00.
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000009-17	Both	Solid State	Downlight Surface Mount	859.766	14.11	N/A	60.933	0.981	4000.0	83.0	35000.0	2/9/2012	Dimmable	qualified only with the Driver Model Number 523-000010-00.
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-60	Both	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-61	Both	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-62	Both	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-63	Commercial	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-64	Commercial	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-65	Commercial	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-66	Both	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-67	Both	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-68	Both	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-69	Commercial	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-70	Commercial	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-71Å	Commercial	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-72	Both	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-73	Both	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-74	Both	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	3000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-75	Commercial	Solid State	Under Cabinet Luminaire	211.4	6.54	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-76	Commercial	Solid State	Under Cabinet Luminaire	403.7	12.49	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000027-77	Commercial	Solid State	Under Cabinet Luminaire	788.07	24.39	N/A	32.31	0.994	4000.0	84.5	35000.0	8/14/2012	Dimmable	Individual Model Numbers may have prefix or suffix to denote minor changes such as luminaire finish and length
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-00	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-01	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-02	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-03	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-04	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-05	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-06	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-07	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-08	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-09	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-10	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-11	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-12	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-13	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-14	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-15	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-16	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-17	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-18	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-19	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-20	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-21	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-22	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-23	Both	Solid state	Under Cabinet Luminaire	340.0	8.22	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-24	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-25	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	2700.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-26	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-27	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-28	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-29	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	3500.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-30	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	
Philips Solid-State Lighting Solutions, Inc.	Philips Color Kinetics	523-000068-31	Both	Solid state	Under Cabinet Luminaire	625.0	15.11	N/A	41.36	0.9855	4000.0	83.3	50000.0	8/6/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Prescolite, Inc.	Prescolite	LB4LEDA30Kk WH	Residential	Solid State	Downlight Solid State Retrofit	557.0	8.79	N/A	63.0	1.0	3000.0	83.0	33000.0	10/22/2012	Dimmable	
Prescolite, Inc.	Prescolite	LB6LEDA30K WH	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Prescolite, Inc.	Prescolite	LB6LEDA35K WH	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Prescolite, Inc.	Prescolite	LB6LEDA40K WH	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Prescolite, Inc.	Prescolite	LB6LEDA50K WH	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4100	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4200	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4300	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4400	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4500	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4600	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4700	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
PRISM Co., Ltd.	Prism	TL-4800	Commercial	Solid State	Portable Desk Task Light	433.0	8.37	N/A	52.0	0.9	3500.0	84.0	36000.0	10/10/2012	Dimmable	
Progress Lighting	Progress	P2620xxxxxx	Residential	Fluorescent	Ceiling Fan Light Kit	900.0	13.8	71.0	N/A	0.55	2700.0	82.0	10000.0	7/20/2012		xxxxxx can be any combination of numbers and letters and is used to denote changes in finish.
Progress Lighting	Progress	P2621xxxxxx	Residential	Fluorescent	Ceiling Fan Light Kit	1800.0	27.6	71.0	N/A	0.55	2700.0	82.0	10000.0	7/20/2012		xxxxxx can be any combination of numbers and letters and is used to denote changes in finish.
Progress Lighting	Progress	P2649xxxxxx	Residential	Fluorescent	Ceiling Fan Light Kit	1800.0	27.6	71.0	N/A	0.55	2700.0	82.0	10000.0	7/20/2012		xxxxxx can be any combination of numbers and letters and is used to denote changes in finish.
Progress Lighting	Progress	P8080-28/30KS TR2	Residential	Solid State	Downlight Solid State Retrofit	557.0	8.79	N/A	63.0	1.0	3000.0	83.0	33000.0	10/25/2012	Dimmable	
Progress Lighting	Progress Lighting	P2602xxxxxx	Residential	Fluorescent	Ceiling Fan Light Kit	1800.0	27.6	71.0	N/A	0.55	2700.0	82.0	10000.0	7/20/2012		xxxxxx can be any combination of numbers and letters and is used to denote changes in finish.
Progress Lighting	Progress Lighting	P2706xxxxxx	Residential	Fluorescent	Bath Vanity	800.0	11.97	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P2707xxxxxx	Residential	Fluorescent	Bath Vanity	1600.0	23.94	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P2708xxxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P2709xxxxxx	Residential	Fluorescent	Bath Vanity	3200.0	47.8	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P2794xxxxxx	Residential	Fluorescent	Bath Vanity	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P2796xxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3051xxxxxx	Residential	Fluorescent	Bath Vanity	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3052xxxxxx	Residential	Fluorescent	Bath Vanity	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3053xxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Progress Lighting	Progress Lighting	P3054xxxxxx	Residential	Fluorescent	Bath Vanity	3200.0	47.88	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3153xxxxxx	Residential	Fluorescent	Bath Vanity	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3154xxxxxx	Residential	Fluorescent	Bath Vanity	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3155xxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3156xxxxxx	Residential	Fluorescent	Bath Vanity	3200.0	47.88	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3187xxxxxx	Residential	Fluorescent	Bath Vanity	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3188xxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3190xxxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3191xxxxxx	Residential	Fluorescent	Bath Vanity	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3192xxxxxx	Residential	Fluorescent	Bath Vanity	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3193xxxxxx	Residential	Fluorescent	Bath Vanity	3200.0	47.88	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3290xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3433xxxxxx	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.2	N/A	0.6	2700.0	83.0	10000.0	10/25/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P3547xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3548xxxxxx	Residential	Fluorescent	Ceiling Mount	2400.0	35.91	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3637xxxxxx	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	69.2	N/A	0.6	2700.0	83.0	10000.0	10/25/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P3760xxxxxx	Residential	Fluorescent	Ceiling Mount	2500.0	37.32	74.1	N/A	0.56	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3761xxxxxx	Residential	Fluorescent	Ceiling Mount	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3762xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3764xxxxxx	Residential	Fluorescent	Ceiling Mount	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3765xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3883xxxxxx	Residential	Fluorescent	Porch Light	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/2/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3910xxxxxx	Residential	Fluorescent	Ceiling Mount	1708.0	23.9	71.4	N/A	0.54	2700.0	82.0	10000.0	10/29/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3911xxxxxx	Residential	Fluorescent	Ceiling Mount	3416.0	47.8	71.4	N/A	0.54	2700.0	82.0	10000.0	10/29/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P3914xxxxxx	Residential	Fluorescent	Decorative Pendant	1600.0	23.94	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P4440xxxxxx	Residential	Fluorescent	Chandelier	2400.0	35.91	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Progress Lighting	Progress Lighting	P4441xxxxx	Residential	Fluorescent	Chandelier	4000.0	59.85	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P4627xxxxx	Residential	Fluorescent	Chandelier	7200.0	107.73	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P5096xxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5108xxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5113xxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	66.8	N/A	0.5	2700.0	82.0	10000.0	5/25/2012		xxxxxx can be any combination of numbers and letters to denote finish
Progress Lighting	Progress Lighting	P5145xxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5150xxxxx	Residential	Fluorescent	Decorative Pendant	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5151xxxxx	Residential	Fluorescent	Bath Vanity	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	11/9/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5530xxxxx	Residential	Fluorescent	Porch Light	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/2/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5748-xxxxWB	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P5816-xxxxWB	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P5843-xxxxWB	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P5862xxxxx	Residential	Fluorescent	Porch Light	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/2/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5863xxxxx	Residential	Fluorescent	Porch Light	800.0	11.97	67.0	N/A	0.5	2700.0	82.0	10000.0	10/2/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5864xxxxx	Residential	Fluorescent	Porch Light	1250.0	18.66	74.1	N/A	0.56	2700.0	82.0	10000.0	10/2/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5874xxxxx	Residential	Fluorescent	Porch Light	1708.0	23.9	71.4	N/A	0.54	2700.0	82.0	10000.0	10/29/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5875xxxxx	Residential	Fluorescent	Porch Light	1708.0	23.9	71.4	N/A	0.54	2700.0	82.0	10000.0	10/29/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P5881-xxxxWB	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P5985xxxxx	Residential	Fluorescent	Porch Light	1708.0	23.9	71.4	N/A	0.54	2700.0	82.0	10000.0	10/29/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7044-xxxxEBWB	Residential	Fluorescent	Wall Sconces	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	10/4/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7171xxxxx	Residential	Fluorescent	Wall Sconces	1729.0	26.4	65.4	N/A	0.603	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7176xxxxx	Residential	Fluorescent	Wall Sconces	1637.0	23.0	71.2	N/A	0.842	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7230-15EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7231-15EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7232-15EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.9	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7265-30EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Progress Lighting	Progress Lighting	P7266-30EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7267-30EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.6	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7268-30EB	Residential	Fluorescent	Ceiling Mount, Other	N/A	N/A	N/A	N/A	0.5	N/A	N/A	N/A	10/8/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7312xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7315xxxxxx	Residential	Fluorescent	Ceiling Mount	1729.0	26.4	65.4	N/A	0.603	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7316xxxxxx	Residential	Fluorescent	Ceiling Mount	2609.0	39.7	65.7	N/A	0.515	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7319xxxxxx	Residential	Fluorescent	Close to Ceiling Mount	4520.0	65.3	69.2	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7320xxxxxx	Residential	Fluorescent	Close to Ceiling Mount	5880.0	84.6	69.5	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7322xxxxxx	Residential	Fluorescent	Decorative Pendant	4520.0	65.3	69.2	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7323xxxxxx	Residential	Fluorescent	Decorative Pendant	5880.0	84.6	69.5	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7324xxxxxx	Residential	Fluorescent	Ceiling Mount	1729.0	26.4	65.4	N/A	0.603	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7325xxxxxx	Residential	Fluorescent	Ceiling Mount	2609.0	39.7	65.7	N/A	0.515	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7326xxxxxx	Residential	Fluorescent	Ceiling Mount	3458.0	52.8	65.4	N/A	0.603	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7327xxxxxx	Residential	Fluorescent	Close to Ceiling Mount	1729.0	26.4	65.4	N/A	0.603	2700.0	81.7	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7328xxxxxx	Residential	Fluorescent	Close to Ceiling Mount	4520.0	65.3	69.2	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7329xxxxxx	Residential	Fluorescent	Close to Ceiling Mount	5880.0	84.6	69.5	N/A	0.554	2700.0	80.0	10000.0	10/25/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7337-xxxxEBWB	Residential	Fluorescent	Ceiling Mount	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7338-xxxxEBWB	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7339-xxxxEBWB	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7340-xxxxWB	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	7/13/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P7364xxxxxx	Residential	Fluorescent	Ceiling Mount	1600.0	23.94	67.0	N/A	0.5	2700.0	82.0	10000.0	10/8/2012		xxxxxx can be any combination of numbers and letters.
Progress Lighting	Progress Lighting	P7372xxxxxx	Residential	Fluorescent	Ceiling Mount	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	10/25/2012		Variable X can be added or dropped from catalog number
Progress Lighting	Progress Lighting	P8071-28/30KS TR2	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Progress Lighting	Progress Lighting	P8071-28/35KS TR2	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Progress Lighting	Progress Lighting	P8071-28/40KS TR2	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Progress Lighting	Progress Lighting	P8071-28/50KS TR2	Both	Solid State	Downlight Recessed	714.7	13.565	N/A	52.69	0.961	3000.0	85.0	60000.0	1/25/2012	Dimmable	
Quorum International	Oxygen Lighting	2-5898-XX	Residential	Fluorescent	Wall Sconces	900.0	13.83	71.0	N/A	0.6	2700.0	82.0	10000.0	5/24/2012		XX = Availabe Finish Options
Quorum International	Quorum International	2-5176-XX	Residential	Fluorescent	Bath Vanity	1431.0	21.0	67.0	N/A	0.6	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	2-5177-XX	Residential	Fluorescent	Bath Vanity	2442.0	29.0	84.0	N/A	0.6	3000.0	N/A	10000.0	9/28/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Quorum International	Quorum International	2-5178-XX	Residential	Fluorescent	Bath Vanity	2824.0	33.0	87.0	N/A	0.6	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	80024-1-6	Residential	Fluorescent	Ceiling Mount	973.0	15.0	65.0	N/A	0.6	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	82025-2-6	Residential	Fluorescent	Ceiling Mount	1838.0	17.0	65.0	N/A	0.5	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	82049-2-6	Residential	Fluorescent	Ceiling Mount	3520.0	32.0	65.0	N/A	0.9	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	82049-4-6	Residential	Fluorescent	Ceiling Mount	6362.0	32.0	65.0	N/A	0.5	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	82148-2-6	Residential	Fluorescent	Ceiling Mount	3520.0	32.0	65.0	N/A	0.9	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	87449-4-65	Residential	Fluorescent	Ceiling Mount	6362.0	32.0	65.0	N/A	0.5	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	87748-3-65	Residential	Fluorescent	Ceiling Mount	5772.0	32.0	65.0	N/A	0.5	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	89248-2-6	Residential	Fluorescent	Ceiling Mount	3520.0	32.0	65.0	N/A	0.9	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	89248-4-6	Residential	Fluorescent	Ceiling Mount	6362.0	32.0	65.0	N/A	0.5	3000.0	N/A	10000.0	9/14/2012		
Quorum International	Quorum International	89348-2-6	Residential	Fluorescent	Ceiling Mount	3520.0	32.0	65.0	N/A	0.9	3000.0	N/A	10000.0	9/14/2012		
Rayo Industries	Rayo Industries	ES-2514XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
Rayo Industries	Rayo Industries	ES-3606XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
Rayo Industries	Rayo Industries	ES-3606XXXXY YYYYYY "XXXX" means a finishes which may be any alphanumeric character or symbol or blank; "YYYYYY" means a switch which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
Rayo Industries	Rayo Industries	ES-5880XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
Rayo Industries	Rayo Industries	ES-58801XXXX "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Ceiling Mount, Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	1/11/2012		
Rayo Industries	Rayo Industries	PL-3357XXXXE S "XXXX" means a finishes which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/21/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Rayo Industries	Rayo Industries	PL-3359XXXXE S "XXXX" means a finishes a which may be any alphanumeric character or symbol or blank.	Residential	Fluorescent	Bath Vanity, Wall Sconces, Other (Wall Lamp)	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/21/2012		
RONA Inc.	UBERHAUS	43855051	Residential	Fluorescent	Ceiling mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	3/30/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	R6105	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0013013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0013013 A	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0013018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0013018 A	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0015013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0015018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0016013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0016018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0019013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0019018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0023013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0023018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0025013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0025018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0026013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0026018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0029013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0029018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0033013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0033018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0035013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0035018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0036013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0036018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0039013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0039018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0043013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0043018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0045013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0045018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0046013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0046018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0049013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0049018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0053013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0053018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0055013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0055018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0056013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0056018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0059013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0059018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00612013	Residential	Fluorescent	Chandelier	10800.0	156.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00612018	Residential	Fluorescent	Chandelier	15000.0	216.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0062013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0062018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0063013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0063018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0065013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0065018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0066013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0066018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0069013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0069018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00712013	Residential	Fluorescent	Chandelier	10800.0	156.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00712018	Residential	Fluorescent	Chandelier	15000.0	216.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0072013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0072018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0073013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0073018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0075013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0075018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0076013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0076018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0079013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0079018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00815013	Residential	Fluorescent	Chandelier	13500.0	195.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH00815018	Residential	Fluorescent	Chandelier	15000.0	216.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0083013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0083018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0085013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0085018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0086013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0086018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0089013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0089018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0093013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0093018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0095013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0095018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0103013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0103018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0104013	Residential	Fluorescent	Chandelier	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0104018	Residential	Fluorescent	Chandelier	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0105013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0105018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0106013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0106018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0109013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0109018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0113013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0113018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0115013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0115018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0116013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0116018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0119013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0119018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0125013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0125018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0126013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0126018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0132013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0132018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0133013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0133013 A	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0133018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0133018 A	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0134013	Residential	Fluorescent	Chandelier	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0134018	Residential	Fluorescent	Chandelier	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0135013	Residential	Fluorescent	Chandelier	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0135018	Residential	Fluorescent	Chandelier	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0136013	Residential	Fluorescent	Chandelier	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0136018	Residential	Fluorescent	Chandelier	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0139013	Residential	Fluorescent	Chandelier	8100.0	117.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESCH0139018	Residential	Fluorescent	Chandelier	11250.0	162.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0001013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0011013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0021013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0031013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0041013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0051013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0061013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0061018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0061023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0071013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0071018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0071023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0081013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0081018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0081023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0092013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0092018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0092023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0102013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0102018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0102023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0111013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0111018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0111023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0122013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0122018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0122023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0132013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0132018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0132023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0141013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0141018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0141023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0152013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0152018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0373023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0381013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0381018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0381023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0392013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0392018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0392023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0403013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0403018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0403023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0414013	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0414018	Residential	Fluorescent	Ceiling mount	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0414023	Residential	Fluorescent	Ceiling mount	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0421013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0421018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0421023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0432013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0432018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0432023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0443013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0443018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0443023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0452013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0452018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0452023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0461013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0461018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0461023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0472013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0472018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0472023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0483013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0483018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0483023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0491013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0491018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0491023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0502013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0502018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0774013	Residential	Fluorescent	Ceiling Mount	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0774018	Residential	Fluorescent	Ceiling mount	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0774023	Residential	Fluorescent	Ceiling mount	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0781013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0781018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0781023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0792013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0792018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESFM0792023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0011013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0011018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0011023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0021013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0021018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0021023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0031013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0031018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0031023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0041013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0041018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0041023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0051013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0051018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0051023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0061013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0061018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0061023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0071013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0071018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0071023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0081013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0081018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0081023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0091013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0091018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0091023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0101013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0101018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0101023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		









ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0481013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0481018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0481023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0491013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0491018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0491023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0501013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0501018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0501023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0511013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0511018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0511023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0521013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0521018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0521023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0533013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0533018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESMP0533023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0191013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0191018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0191023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0193013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0193018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0193023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0201013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0201018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0201023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0203013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0203018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0203023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0211013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0211018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0211023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0213013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0213018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0213023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0222013	Residential	Fluorescent	Chandelier	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0222018	Residential	Fluorescent	Chandelier	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESPD0222023	Residential	Fluorescent	Chandelier	3200.0	26.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0693013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0693018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0693023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0761013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0761018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESSF0761023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0011013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0011018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0012013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0012018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0013013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0013018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0014013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0014018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0015013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0015018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0016013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0016018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0021013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0021018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0022013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0022018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0023013	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0023018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0024013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0024018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0025013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0025018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0026013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0026018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0031013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0031018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0032013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0032018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0033013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0033018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0034013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0034018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd	RESVL0035013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		

















ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd.	RESVL0393013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	RESVL0393018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	RESVL0394013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	RESVL0394018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	1RP220XX-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4012XX-G	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4021XX-G	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4022WH-G	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4022XX-G	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4036XX-G	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43147GXX-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43201XX-G13-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43205XX-G13-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43205XX-G213-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43205XX-G218-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	43205XX-G223-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4321XX-G18-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4321XX-G213-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4321XX-G218-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Royal Pacific Ltd.	Royal Pacific Ltd.	4324XX-G18-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4324XX-G213-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4324XX-G218-ES	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4401XX-G23-ES	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4402XX-G18-ES	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4403XX-G18-ES	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44179XX-G18-ES	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44179XX-G23-ES	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44182XX-G18-ES	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44186XX-G18-ES	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44187XX-G218-ES	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	44189XX-G13-ES	Residential	Fluorescent	Ceiling Mount;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4501XX-G18-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	45187XX-G218-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	45187XX-G223-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4601XX-G218-ES	Residential	Fluorescent	Decorative Pendant	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	47133XX-G213-ES	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	47135XX-G213-ES	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4901XX-G13-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4901XX-G213-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4901XX-G313-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	4901XX-G413-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	49114XX-G218-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	49115XX-G213-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	49115XX-G218-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Royal Pacific Ltd.	Royal Pacific Ltd.	49115XX-G223-ES	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
SATCO/NUVO	NUVO	60-1901	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1902	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1903	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-1904	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1905	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-1906	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1907	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1907	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1908	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1911	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-1912	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1913	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1914	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-1915	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1921	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1922	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1923	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-1924	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1925	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-1926	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1927	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1928	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1931	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1932	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1933	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-1934	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-1935	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2201	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2202	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2203	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2204	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2205	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2206	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2207	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/13/2012		
SATCO/NUVO	NUVO	60-2208	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/13/2012		
SATCO/NUVO	NUVO	60-2209	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/13/2012		
SATCO/NUVO	NUVO	60-2400	Residential	Fluorescent	Chandelier	9600.0	156.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2402	Residential	Fluorescent	Chandelier	3600.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2403	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2404	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2405	Residential	Fluorescent	Chandelier	2400.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2406	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2407	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2407	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2408	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2409	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2411	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2412	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2413	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2414	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2415	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2416	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2417	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2418	Residential	Fluorescent	Chandelier	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2419	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2421	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2422	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2423	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2424	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2425	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2426	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2427	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2428	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2429	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2431	Residential	Fluorescent	Chandelier	4800.0	72.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2432	Residential	Fluorescent	Chandelier	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2433	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-2434	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2435	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2436	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2437	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2438	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2439	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2441	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2442	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2443	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2444	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2445	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2448	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2449	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2451	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2452	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2453	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2454	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2455	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2456	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2457	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2458	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2459	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2461	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2462	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2463	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2464	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2465	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2466	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2467	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2468	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2469	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2471	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2472	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2473	Residential	Fluorescent	Chandelier	4800.0	72.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2474	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2475	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2476	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2477	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2478	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2479	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2481	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2482	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2483	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2485	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2486	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2487	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2488	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2489	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2491	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2492	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2493	Residential	Fluorescent	Chandelier	4800.0	72.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2501	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2502	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2503	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2504	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2506	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-2512	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2513	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2516	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2517	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2518	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2519	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2521	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2523	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2524	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2526	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-2527	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2528	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2529	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2541	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2542	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2543	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2544	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2545	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2546	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2547	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2548	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2551	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2552	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2553	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2554	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-2556	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2557	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2558	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-2559	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2561	Residential	Fluorescent	Chandelier	4800.0	72.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-2562	Residential	Fluorescent	Chandelier	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2563	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2564	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2565	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2566	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2567	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2568	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2569	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2571	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2621	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2622	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2623	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2624	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2625	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2627	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2628	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2629	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2631	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2632	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2633	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2634	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2635	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2636	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2637	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2651	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2652	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-2653	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2654	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2655	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-2656	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-2889	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2892	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-2941	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2942	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2943	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2944	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2945	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2946	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-2947	Residential	Fluorescent	Ceiling Mount	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-2948	Residential	Fluorescent	Ceiling Mount	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-2949	Residential	Fluorescent	Ceiling Mount	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3101	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3102	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3103	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3104	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3105	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3106	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3107	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3108	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3109	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3111	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3112	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3113	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3114	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3114	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3115	Residential	Fluorescent	Wall Sconces	5600.0	91.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/10/2012		
SATCO/NUVO	NUVO	60-3121	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3122	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3123	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3124	Residential	Fluorescent	Wall Sconces	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3125	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3126	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3127	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3128	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3129	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3131	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3132	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3135	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3136	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3137	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3180	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3181	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3182	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3183	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3184	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3185	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3186	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3187	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3188	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3189	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3195	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3196	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3197	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-3199	Residential	Fluorescent	Chandelier	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3201	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3202	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3203	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3204	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3205	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3206	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3207	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3208	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3209	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3211	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3212	Residential	Fluorescent	Wall Sconces	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3213	Residential	Fluorescent	Wall Sconces	5600.0	91.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/10/2012		
SATCO/NUVO	NUVO	60-3290	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3291	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3292	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3293	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3294	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3295	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3296	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3297	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3298	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3299	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3305	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3306	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3307	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3309	Residential	Fluorescent	Chandelier	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3311	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3312	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3313	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3314	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3315	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3316	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3317	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3318	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3319	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3321	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3322	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3323	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3324	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3325	Residential	Fluorescent	Wall Sconces	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3327	Residential	Fluorescent	Wall Sconces	5600.0	91.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/10/2012		
SATCO/NUVO	NUVO	60-3331	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3332	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3333	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3334	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3335	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3336	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3337	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3338	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3339	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3341	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3342	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3343	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3344	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3345	Residential	Fluorescent	Wall Sconces	5600.0	91.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/10/2012		
SATCO/NUVO	NUVO	60-3351	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-3352	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3353	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3354	Residential	Fluorescent	Wall Sconces	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3355	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3356	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3357	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3358	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3359	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3361	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3362	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3364	Residential	Fluorescent	Chandelier	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3365	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3366	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3367	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3801	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3802	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3803	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3804	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3805	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3806	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3807	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3808	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3809	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3811	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3812	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3813	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3821	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3822	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3823	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3824	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3825	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3826	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3827	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3828	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3829	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3831	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3832	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3833	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3841	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3842	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3843	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3844	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3845	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3846	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3847	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3848	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3849	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3851	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3852	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3861	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3862	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-3863	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3864	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3865	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3866	Residential	Fluorescent	Chandelier	5600.0	91.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-3867	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3868	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-3869	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3870	Residential	Fluorescent	Wall Sconces	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-3871	Residential	Fluorescent	Chandelier	3600.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3872	Residential	Fluorescent	Chandelier	3600.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3873	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3874	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3875	Residential	Fluorescent	Chandelier	3600.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-3903	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-3904	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-3905	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3906	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3907	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3923	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-3924	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-3925	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3926	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3927	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3928	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-3941	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3942	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3943	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3944	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3945	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3946	Residential	Fluorescent	Porch Light	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-3951	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3952	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3953	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3954	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3955	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3956	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3957	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-3958	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-401	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-402	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-403	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-4032	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4033	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4034	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4035	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4036	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4037	Residential	Fluorescent	Ceiling Mount	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/6/2012		
SATCO/NUVO	NUVO	60-4038	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-4039	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-404	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-4041	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4042	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4043	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-4044	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4045	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4046	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4047	Residential	Fluorescent	Chandelier	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4048	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-4049	Residential	Fluorescent	Ceiling Mount	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/10/2012		
SATCO/NUVO	NUVO	60-405	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-4051	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-406	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-450	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-451	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-460	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-461	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-462	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-463	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-464	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-465	Residential	Fluorescent	Chandelier	2400.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-466	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-467	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-468	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-469	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-490	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-491	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-492	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-493	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-494	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-495	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-496	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-497	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-4981	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4982	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4983	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4991	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4992	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4993	Residential	Fluorescent	Porch Light	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4997	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4998	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-4999	Residential	Fluorescent	Decorative Pendant	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	10/10/2012		
SATCO/NUVO	NUVO	60-500	Residential	Fluorescent	Chandelier	4800.0	78.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-501	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-502	Residential	Fluorescent	Ceiling Mount	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-503	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-504	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-505	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-5051	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5052	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5053	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5053	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-5054	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5055	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-5056	Residential	Fluorescent	Chandelier	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5056	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5057	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5058	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5059	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-506	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5061	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5062	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5063	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5064	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-507	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-508	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-509	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5151	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-5152	Residential	Fluorescent	Wall Sconces	1600.0	26.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5153	Residential	Fluorescent	Wall Sconces	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-5154	Residential	Fluorescent	Wall Sconces	3200.0	52.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5155	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-5156	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5157	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5158	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5159	Residential	Fluorescent	Chandelier	7200.0	117.0	66.0	N/A	0.6	2700.0	82.0	10000.0	4/5/2012		
SATCO/NUVO	NUVO	60-5161	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5162	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5163	Residential	Fluorescent	Chandelier	4000.0	65.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-5164	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-561	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-564	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-565	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-566	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-567	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-568	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-569	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-572	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-573	Residential	Fluorescent	Ceiling Mount	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	6/12/2012		
SATCO/NUVO	NUVO	60-900	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-901	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-902	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-903	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-904	Residential	Fluorescent	Wrapped Lens	5560.0	60.9	78.0	N/A	0.6	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-905	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-906	Residential	Fluorescent	Wrapped Lens	2460.0	34.0	65.0	N/A	0.5	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-907	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-908	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-909	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-910	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-911	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-912	Residential	Fluorescent	Wrapped Lens	5560.0	60.9	78.0	N/A	0.6	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-913	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-914	Residential	Fluorescent	Wrapped Lens	2460.0	34.0	65.0	N/A	0.5	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-915	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-916	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	7/19/2012		
SATCO/NUVO	NUVO	60-917	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-918	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-919	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-920	Residential	Fluorescent	Wrapped Lens	5560.0	60.9	78.0	N/A	0.6	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-921	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-922	Residential	Fluorescent	Wrapped Lens	2460.0	34.0	65.0	N/A	0.5	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-923	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-924	Residential	Fluorescent	Ceiling Mount	1200.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-925	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-926	Residential	Fluorescent	Ceiling Mount	1200.0	54.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-927	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-928	Residential	Fluorescent	Wrapped Lens	5560.0	60.9	78.0	N/A	0.6	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-929	Residential	Fluorescent	Wrapped Lens	8340.0	91.0	78.0	N/A	0.5	3000.0	N/A	10000.0	6/14/2012		
SATCO/NUVO	NUVO	60-930	Residential	Fluorescent	Wrapped Lens	2460.0	34.0	65.0	N/A	0.5	3000.0	N/A	N/A	6/26/2012		
SATCO/NUVO	NUVO	60-931	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-933	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-934	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-936	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-937	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
SATCO/NUVO	NUVO	60-938	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-939	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	NUVO	60-940	Residential	Fluorescent	Wall Sconces	2400.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-941	Residential	Fluorescent	Wall Sconces	2400.0	36.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-944	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-945	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-946	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-947	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-948	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	60-949	Residential	Fluorescent	Wall Sconces	1200.0	18.0	68.0	N/A	0.6	2700.0	81.0	10000.0	6/15/2012		
SATCO/NUVO	NUVO	TH355	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH356	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH357	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH358	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH361	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH362	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH363	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH364	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH365	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH366	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH367	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TH368	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TK381	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	NUVO	TK382	Residential	Fluorescent	Accent Light Line-voltage	476.0	13.72	N/A	35.0	0.5	2700.0	82.0	10000.0	11/14/2012		
SATCO/NUVO	Patriot Lighting	348-8622	Residential	Fluorescent	Chandelier	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	Patriot Lighting	348-8620	Residential	Fluorescent	Chandelier	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	Patriot Lighting	348-8624	Residential	Fluorescent	Wall Sconces	800.0	13.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	Patriot Lighting	348-8626	Residential	Fluorescent	Ceiling Mount	2400.0	39.0	66.0	N/A	0.6	2700.0	82.0	10000.0	5/4/2012		
SATCO/NUVO	SATCO PRODUCTS	90-2615	Residential	Fluorescent	Ceiling Mount	800.0	13.27	68.0	N/A	0.6	2700.0	81.0	10000.0	7/30/2012		
SATCO/NUVO	SATCO PRODUCTS	90-2616	Residential	Fluorescent	Ceiling Mount	800.0	13.27	68.0	N/A	0.6	2700.0	81.0	10000.0	7/30/2012		
SATCO/NUVO	SATCO PRODUCTS	90-2631	Residential	Fluorescent	Ceiling Mount	1200.0	17.46	72.0	N/A	0.5	2700.0	83.0	10000.0	7/30/2012		
SATCO/NUVO	SATCO PRODUCTS	90-2632	Residential	Fluorescent	Ceiling Mount	1200.0	17.46	72.0	N/A	0.5	2700.0	83.0	10000.0	7/30/2012		
SAVENERGY INC.	SavEnergy Inc.	SD6	Commercial	Solid State	Down-light Recessed	700.34	10.11	N/A	69.27	0.9491	3000.0	85.9	35000.0	6/22/2012		
SAVENERGY INC.	SavEnergy Inc.	SD8	Commercial	Solid State	Down-light Recessed	682.09	10.04	N/A	67.94	0.9507	3000.0	86.0	35000.0	6/22/2012		
Scott Lamp Company	Scott Architectural Lighting	S3120-2C26E	residential	Fluorescent	Wall Sconces	2940.0	42.28	69.5	N/A	0.554	2700.0	80.0	10000.0	10/18/2012		
Sea Gull Lighting Products LLC	Traverse	14600S-15 TRV6 WW MTL 120V CV WH	Residential	Solid State	Downlight Solid State Retrofit	750.0	14.362	N/A	58.32	0.783	3000.0	80.2	35000.0	3/29/2012	Dimmable	
Sea Gull Lighting Products LLC	Traverse	14601S-15 TRV4 WW MTL 120V CV WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	3000.0	81.9	35000.0	2/24/2012	Dimmable	
Sea Gull Lighting Products LLC	Traverse	14601S-15 TRV4 WW MTL 120V CV WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	3000.0	81.9	35000.0	8/29/2012	Dimmable	
Sea Gull Lighting Products LLC	Traverse	14602S-15 TRV4 W27 MTL 120V CV WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	2700.0	81.9	35000.0	8/29/2012	Dimmable	
Sea Gull Lighting Products LLC	Traverse	14603S-15 TRV6 W27 MTL 120V CV WH	Residential	Solid State	Downlight Solid State Retrofit	700.0	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Sea Gull Lighting Products LLC	Traverse	14604S-15 TRV6 NW MTL 120 CV WH	Both	Solid State	Downlight Solid State Retrofit	750.0	13.295	N/A	54.03	0.792	4000.0	80.9	35000.0	8/10/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sea Gull Lighting Products LLC	Traverse	14607S-15 TRV4 NW MTL 120V CV WH	Both	Solid State	Downlight Solid State Retrofit	542.7	9.53	N/A	56.95	0.965	4000.0	81.9	35000.0	8/29/2012	Dimmable	
Shanghai Meetime Lighting Co., Ltd.	Meetime	S9051E15-xx-xx	Both	Solid State	Downlight Recessed	685.0 lm	13.28 W	N/A	51.47 lm/W	0.92	2700.0	83.0	35000.0	8/15/2012	Dimmable	S9051E15-xx-xx , the preceding xx (xx=27,30,40) represents different CCT 2700K, 3000K, 4000K, the following xx (xx=MW, AB) represents different finish.
Shanghai Meetime Lighting Co., Ltd.	Meetime	S9051E21-xx-xx	Both	Solid State	Downlight Recessed	1061.7 lm	19.03 W	N/A	57.16 lm/W	0.966	2700.0	85.0	50000.0	8/15/2012	Dimmable	S9051E21-xx-xx , the preceding xx (xx=27,30,40) represents different CCT 2700K, 3000K, 4000K, the following xx (xx=MW, AB) represents different finish.
Shanghai Meetime Lighting Co., Ltd.	Meetime	S9051N15-xx-xx	Both	Solid State	Downlight Recessed	682.3 lm	13.30 W	N/A	51.27 lm/W	0.917	2700.0	83.0	35000.0	8/15/2012	Dimmable	S9051N15-xx-xx , the preceding xx (xx=27,30,40) represents different CCT 2700K, 3000K, 4000K, the following xx (xx=MW, AB) represents different finish.
Shanghai Meetime Lighting Co., Ltd.	Meetime	S9051N21-xx-xx	Both	Solid State	Downlight Recessed	1074.7 lm	18.58 W	N/A	58.01 lm/W	0.948	2700.0	83.0	50000.0	8/15/2012	Dimmable	S9051N21-xx-xx , the preceding xx (xx=27,30,40) represents different CCT 2700K, 3000K, 4000K, the following xx (xx=MW, AB) represents different finish.
Shenzhen Jiawei Photovoltaic Lighting Co., Ltd.	Utilitech	DLS02-627D-WH-F1	Residential	Solid State	Downlight Solid State Retrofit	704.3	12.53	N/A	56.2	0.885	2700.0	83.0	50000.0	7/19/2012	Dimmable	
Shenzhen Jiffa Electrical Co., Ltd.	Patriot Lighting	C12453	Residential	Fluorescent	Ceiling mount	1830.26	25.84	70.82	N/A	0.548	2700.0	82.0	10000.0	11/29/2011		Provided with Photo-Electric Switch
Shenzhen Jiffa Electrical Co., Ltd.	Patriot Lighting	C13633P	Residential	Fluorescent	Ceiling mount	1830.26	25.84	70.82	N/A	0.548	2700.0	82.0	10000.0	11/29/2011		Not Provided with Photo-Electric Switch
Shenzhen OKT Electronics & Technology Co.,Ltd.	OKT	DD-13D180-#	Both	Solid State	Downlight Solid State Retrofit	966.6	12.9	N/A	74.8	0.963	2700.0	83.1	36000.0	9/12/2012	Dimmable	Where * denotes color temperature, 27 identifies "2700K", 30 identifies "3000K", 40 identifies "4000K", 50 identifies "5000K". And # denotes trim color W identifies "White trim", P identifies "Platinum trim", N identifies "Brushed nickel trim", B identifies "Black trim"
SmartRay, Inc.	SmartRay	SR1NNRD613W	Residential	Solid State	Downlight Solid State Retrofit	656.07	12.56	N/A	52.99	0.912	3000.0	82.0	35000.0	4/18/2012		
SmartRay, Inc.	SmartRay	SR2NNRD613W	Residential	Solid State	Downlight Solid State Retrofit	643.94	12.29	N/A	52.41	0.964	3000.0	82.0	25000.0	4/18/2012		B0881A-GU24: GU24 base
Standard Products, Inc.	FlexLED	61507: LED/ DL6/14.3W/30K/ 35M/RETRO/ E26/D/FLEX	Residential	Solid State	Downlight Solid State Retrofit	750.0	13.295	N/A	54.03	0.792	3000.0	80.9	35000.0	3/29/2012	Dimmable	
Standard Products, Inc.	FlexLED	61560: LED/ DL4/9.5W/30K/ 35M/RETRO/ E26/D/FLEX	Both	Solid State	Downlight Solid State Retrofit	525.0	9.53	N/A	56.95	0.965	3000.0	81.9	25000.0	2/24/2012	Dimmable	
Standard Products, Inc.	FlexLED	61807: LED/ DL4/9.5W/27K/ 35M/RETRO/ E26/D/FLEX	Both	Solid State	Downlight Solid State Retrofit	475.0	9.53	N/A	56.95	0.965	2700.0	81.9	25000.0	2/24/2012	Dimmable	
Standard Products, Inc.	FlexLED	61808: LED/ DL6/14.3W/27K/ 35M/RETRO/ E26/D/FLEX	Residential	Solid State	Downlight Solid State Retrofit	700.0	13.295	N/A	54.03	0.792	2700.0	80.9	35000.0	3/29/2012	Dimmable	
Standard Products, Inc.	Standard Products	61071	Both	Solid State	Downlight Solid State retrofit	626.47	13.7	N/A	45.91	0.95	3000.0	80.7	35000.0	5/21/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Star Mount Enterprise Limited	Star Mount	FMF0250	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/29/2012		
Sunpark Electronics Corporation	Sunpark	1009PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	1010PG-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	1011PG-126-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1650.0	26.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	1012PG-126-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1650.0	26.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	1014PG-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	1015PG-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	1015PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	1019PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	1132PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-0102PG-118	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-0103PG-118	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-0515PG-226	Residential	Fluorescent	Bath Vanity	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-0615PG-226	Residential	Fluorescent	Bath Vanity	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4001-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4011PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4021-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4041PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4081PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4082PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4091PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	3-4098PG-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sunpark Electronics Corporation	Sunpark	4475-113-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	900.0	13.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4475-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4475-313-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	2700.0	39.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4475-413-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	3600.0	52.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4476-113-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	900.0	13.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4476-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4476-313-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	2700.0	39.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4476-413-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	3600.0	52.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4478-113-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	900.0	13.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4478-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4478-313-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	2700.0	39.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4478-413-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	3600.0	52.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	4479-226-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Bath Vanity	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	BH1PG-118	Residential	Fluorescent	Wall Sconce	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	C163-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC010-118-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC012-PD-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1650.0	26.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC012-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1650.0	26.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC014PG-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	DC014PG-218-PD-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC014PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sunpark Electronics Corporation	Sunpark	DC016PG-218-PD-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC016PG-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC018PG-226-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC018PG-318-PD-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	3645.0	54.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC018PG-318-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	3645.0	54.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC024PG-226-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	DC050PG-226-PD-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	3300.0	52.0	76.64	N/A	0.567	2700.0	81.4	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	LP051-218-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Ceiling Mount	2430.0	36.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	MDF021PG-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF025PG-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF030-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF032-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF033PG-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF035PG-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF036PG-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	MDF039-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sunpark Electronics Corporation	Sunpark	P035-1-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	P052-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	P055-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	P117-1-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	P118-1-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	P120-1-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Chandelier	1215.0	18.0	74.68	N/A	0.575	2700.0	82.0	10000.0	7/5/2012		
Sunpark Electronics Corporation	Sunpark	W104-213-XX ("XX" stands for fixture color finish)	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sunpark Electronics Corporation	Sunpark	W260-213	Residential	Fluorescent	Wall Sconce	1800.0	26.0	69.37	N/A	0.582	2700.0	81.9	10000.0	7/3/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1000-GU118-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1000-GU123-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1003-GU123-XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1003-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1004-GU213-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1004-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1004-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1005-GU213-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1005-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1005-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1006-GU213-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1006-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1006-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1007-GU213-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1007-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1007-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1010-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	1010-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU113-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU118-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU213-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU218-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2001-GU223-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU113-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU118-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU213-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU218-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2002-GU223-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2003-GU113-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2003-GU118-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2003-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2003-GU213-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2008-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	2012-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3000-GU223-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU113-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU118-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU123-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU213-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU218-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU223-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU313-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU318-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU323-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU413-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU418-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3001-GU423-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3002-GU313-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3002-GU318-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3002-GU323-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	3002-GU413-XX	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	4002-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	4003-GU213-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	4003-GU218-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	4003-GU223-XX	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5000-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5000-GU123-XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5002-GU113-XX	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5002-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5002-GU123-XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5003-GU213-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5003-GU218-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5003-GU223-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5004-GU118-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5004-GU123-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5004-GU213-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5005-GU213-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5005-GU218-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5005-GU223-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5006-GU113-XX	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5006-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5006-GU123-XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5007-GU113-XX	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5007-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5007-GU123-XX	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5008-GU113-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5008-GU118-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5008-GU123-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5008-GU213-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5010-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5013-GU118-XX	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Sun & Stars Lighting, Inc.	Sun & Stars Lighting	5015-GU213-XX	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Tach Lighting & Electronics Ltd.	TACH	RRDL-5x3W	Residential	Solid State	Downlight Solid State Retrofit	628.18	14.7	N/A	43.46	0.976	3500.0	81.0	25000.0	9/30/2011		
Technical Consumer Products, Inc. (TCP)	TCP	11826BSGU	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	11826PBGU	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	11826WHGU	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	11830WH	Residential	Fluorescent	Ceiling Mount	2000.0	30.0	66.7	N/A	0.507	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	11930PB	Residential	Fluorescent	Ceiling Mount	2000.0	30.0	66.7	N/A	0.507	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	14840BS	Residential	Fluorescent	Ceiling Mount	2800.0	40.0	70.0	N/A	0.531	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51013BPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51013WPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51018BPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51018WPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51023BPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51023WPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51027BPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51027WPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51032BPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	51032WPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52013BPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52013BSPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52013WPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52018BPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Technical Consumer Products, Inc. (TCP)	TCP	52018BSPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52018WPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52023BPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52023BSPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	52023WPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	55813BPCGU	Residential	Fluorescent	Outdoor Globe	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	55813WPCGU	Residential	Fluorescent	Outdoor Globe	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	55818BPCGU	Residential	Fluorescent	Outdoor Globe	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	55818WPCGU	Residential	Fluorescent	Outdoor Globe	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56309BPCGU	Residential	Fluorescent	Porch Light	550.0	9.0	69.6	N/A	0.609	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56309WPCGU	Residential	Fluorescent	Porch Light	550.0	9.0	69.6	N/A	0.609	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56313BPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56313WPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56318BPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56318WPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56323BPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56323WPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56327BPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56327WPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56332BPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Technical Consumer Products, Inc. (TCP)	TCP	56332WPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56409BPCGU	Residential	Fluorescent	Porch Light	550.0	9.0	61.1	N/A	0.609	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56409WPCGU	Residential	Fluorescent	Porch Light	550.0	9.0	61.1	N/A	0.609	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56413BPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56413WPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56418BPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56418WPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56423BPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56423WPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56427BPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56427WPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56432BPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	56432WPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57013BPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57013WPCGU	Residential	Fluorescent	Porch Light	900.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57018BPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57018WPCGU	Residential	Fluorescent	Porch Light	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57023BPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57023WPCGU	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57027BPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Technical Consumer Products, Inc. (TCP)	TCP	57027WPCGU	Residential	Fluorescent	Porch Light	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	57032BPCGU	Residential	Fluorescent	Porch Light	2200.0	32.0	68.8	N/A	0.593	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	CL13	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.627	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	CL134PACK	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.627	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	CL13B	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.627	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	CL13B4PACK	Residential	Fluorescent	Ceiling Mount	900.0	13.0	69.2	N/A	0.627	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X1841KG UWALLBS	Residential	Fluorescent	Wall Sconces	1100.0	18.0	73.0	N/A	0.6	4100.0	84.0	10000.0	9/28/2011		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X18GUFL CLBS	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X18GUFL CLWH	Residential	Fluorescent	Ceiling Mount	1200.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X23GUFL CLBS	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X23GUFL CLWH	Residential	Fluorescent	Ceiling Mount	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X23GUWA LLBS	Residential	Fluorescent	Wall Sconces	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X23GUWA LLWH	Residential	Fluorescent	Wall Sconces	1600.0	23.0	69.6	N/A	0.566	2700.0	81.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X27GUFL CLBS	Residential	Fluorescent	Ceiling Mount	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES1X27GUFL CLWH	Residential	Fluorescent	Ceiling Mount	1850.0	27.0	68.5	N/A	0.551	2700.0	82.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES2X18GUPE NDBS	Residential	Fluorescent	Ceiling Mount	2400.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES2X18GUPE NDWH	Residential	Fluorescent	Ceiling Mount	2400.0	18.0	66.7	N/A	0.547	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES3X13GUBA THBS	Residential	Fluorescent	Bath Vanity	2700.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	DES4X13GUBA THSBS	Residential	Fluorescent	Bath Vanity	3200.0	13.0	69.2	N/A	0.578	2700.0	83.0	10000.0	4/30/2012		
Technical Consumer Products, Inc. (TCP)	TCP	LED12DR627K	Residential	Solid State	Downlight Recessed	650.0	12.0	N/A	60.0	0.879	2700.0	82.0	36000.0	11/21/2012	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Technical Consumer Products, Inc. (TCP)	TCP	LED12DR630K	Residential	Solid State	Downlight Recessed	650.0	12.0	N/A	63.3	0.879	3000.0	83.0	36000.0	11/21/2012	Dimmable	
Technical Consumer Products, Inc. (TCP)	TCP	LED14DR627K	Residential	Solid State	Downlight Recessed	750.0	14.0	N/A	56.0	0.888	2700.0	82.0	36000.0	11/21/2012	Dimmable	
Technical Consumer Products, Inc. (TCP)	TCP	RL12DR6527K	Residential	Solid State	Downlight Recessed	650.0	12.0	N/A	60.0	0.879	2700.0	82.0	36000.0	11/21/2012	Dimmable	
Technical Consumer Products, Inc. (TCP)	TCP	RL12DR6527K2	Residential	Solid State	Downlight Recessed	650.0	12.0	N/A	60.0	0.879	2700.0	82.0	36000.0	11/21/2012	Dimmable	
The Lighting Quotient	fraqtir	S301-R02J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		2ft unit 350mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R02K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		2ft unit 700mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R03J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		3ft unit 350mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R03K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		3ft unit 700mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R04J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		4ft unit 350mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R04K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		4ft unit 700mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R05J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		5ft unit 350mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R05K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		5ft unit 700mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R06J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		6ft unit 350mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S301-R06K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		6ft unit 700mA drive current, non-dimming, remote driver
The Lighting Quotient	fraqtir	S305-R02J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		2ft unit 350mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R02K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		2ft unit 700mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R03J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		3ft unit 350mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R03K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		3ft unit 700mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R04J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		4ft unit 350mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R04K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		4ft unit 700mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R05J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		5ft unit 350mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R05K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		5ft unit 700mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R06J-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		6ft unit 350mA drive current, non-dimming
The Lighting Quotient	fraqtir	S305-R06K-S-00-1-00-0-30-00	Both	Solid State	Cove Mount	2711.0	54.0	N/A	50.2037037037037	0.993	3000.0	86.0	N/A	1/31/2012		6ft unit 700mA drive current, non-dimming
Tons Lightology Inc.	Tons	LGB-358	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	255.06	8.595	N/A	29.52	0.94	3000.0	81.0	35000.0	10/12/2011	Dimmable	
Tons Lightology Inc.	Tons	LGB-560	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	452.78	12.36	N/A	36.65	0.94	3000.0	81.0	35000.0	10/12/2011	Dimmable	



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Tons Lightology Inc.	Tons	LGB-810	Commercial	Solid State	Under Cabinet Shelf Mounted Task Light	638.25	17.67	N/A	35.97	0.94	3000.0	81.0	35000.0	10/12/2011	Dimmable	
Top China Production Ltd.	Hampton Bay	FM376/12ES	Residential	Fluorescent	Ceiling Mount	975.86	24.67	39.54	N/A	0.615	2700.0	82.0	10000.0	8/14/2012		
Top China Production Ltd.	Hampton Bay	FM376/12BN/ES	Residential	Fluorescent	Ceiling Mount	866.48	21.8	39.73	N/A	0.586	2700.0	82.0	10000.0	8/3/2012		
T-Opto	T-Opto	TFLX-ST	Both	Solid state	Downlight Solid State Retrofit	681.4	10.91	N/A	62.4	0.937	2700.0	80.8	50000.0	8/10/2012	Dimmable	All models identical with only exception being the base
Treasure Best Limited	TORCH	JL2342;JL2342A;JL2342-GU24;JL2342A-GU24;JL2342-30;JL2342A-30;JL2342-GU24-30;JL2342A-GU24-30;JL2342-35;JL2342A-35;JL2342-GU24-35;JL2342A-GU24-35;JL2342-40;JL2342A-40;JL2342-GU24-40;JL2342A-GU24-40	Residential	Solid State	Downlight Solid State retrofit	354.98	8.09	N/A	43.9	0.813	2700.0	84.7	35000.0	12/29/2011	Dimmable	
Treasure Best Limited	TORCH	JL2450;JL2450A;JL2450-GU24;JL2450A-GU24;JL2450-30;JL2450A-30;JL2450-GU24-30;JL2450A-GU24-30;JL2450-35;JL2450A-35;JL2450-GU24-35;JL2450A-GU24-35;JL2450-40;JL2450A-40;JL2450-GU24-40;JL2450A-GU24-40	Residential	Solid State	Downlight Solid State retrofit	352.41	8.07	N/A	43.69	0.814	2700.0	84.4	35000.0	12/29/2011	Dimmable	
Treasure Best Limited	TORCH	JL2526;JL2526A;JL2526-GU24;JL2526A-GU24;JL2526-30;JL2526A-30;JL2526-GU24-30;JL2526A-GU24-30;JL2526-35;JL2526A-35;JL2526-GU24-35;JL2526A-GU24-35;JL2526-40;JL2526A-40;JL2526-GU24-40;JL2526A-GU24-40	Residential	Solid State	Downlight Solid State retrofit	714.85	16.49	N/A	43.36	0.943	2700.0	86.6	35000.0	12/28/2011	Dimmable	
Treasure Best Limited	TORCH	JL2684;JL2684A;JL2684-GU24;JL2684A-GU24;JL2684-30;JL2684A-30;JL2684-GU24-30;JL2684A-GU24-30;JL2684-35;JL2684A-35;JL2684-GU24-35;JL2684A-GU24-35;JL2684-40;JL2684A-40;JL2684-GU24-40;JL2684A-GU24-40	Residential	Solid State	Downlight Solid State retrofit	710.67	16.27	N/A	43.69	0.948	2700.0	87.2	35000.0	12/28/2011	Dimmable	

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing, etc)	Notes
UPEC Electronics Corp.	UPEC Electronics	UE-MILDA01M#T-S1FAA	Residential	Solid State	Downlight Solid State Retrofit	599.9	10.1	N/A	59.6	0.865	2700.0	84.0	25000.0	8/12/2011		UE-MILDA01MWT-S1FAAC, UE-MILDA01MWT-S1FAAB ---3000K UE-MILDA01MVT-S1FAAC, UE-MILDA01MVT-S1FAAB --- 2700K UE-MILDA01MNT-S1FAAC, UE-MILDA01MNT-S1FAAB --- 4000K
UPEC Electronics Corp.	UPEC Electronics	UE-MILDA02M#T-S1FAA	Residential	Solid State	Downlight Solid State Retrofit	696.5	14.4	N/A	48.5	0.879	2700.0	84.0	25000.0	8/12/2011		UE-MILDA02MWT-S1FAAC, UE-MILDA02MWT-S1FAAB ---3000K UE-MILDA02MVT-S1FAAC, UE-MILDA02MVT-S1FAAB --- 2700K UE-MILDA02MNT-S1FAAC, UE-MILDA02MNT-S1FAAB --- 4000K
UPEC Electronics Corp.	UPEC Electronics	UE-MILDA03S#T-S1FB@	Residential	Solid State	Downlight Solid State Retrofit	790.65	14.02	N/A	56.39	0.871	2700.0	91.0	25000.0	10/21/2011		UE-MILDA03SWT-S1FBF, UE-MILDA03SWT-S1FBK ---3000K UE-MILDA03SVT-S1FBF, UE-MILDA03SVT-S1FBK --- 2700K UE-MILDA03SNT-S1FBF, UE-MILDA03SNT-S1FBK --- 4000K
UPEC Electronics Corp.	UPEC Electronics	UE-MILDA04S#T-S1FB@	Residential	Solid State	Downlight Solid State Retrofit	432.01	10.26	N/A	42.11	0.857	2700.0	89.0	25000.0	10/21/2011		UE-MILDA04SWT-S1FBF, UE-MILDA04SWT-S1FBK ---3000K UE-MILDA04SVT-S1FBF, UE-MILDA04SVT-S1FBK --- 2700K UE-MILDA04SNT-S1FBF, UE-MILDA04SNT-S1FBK --- 4000K
U S LED LTD	USLED	LRT65-1-30-14-120-6-W	Both	Solid State	Downlight Solid State Retrofit	857.0	14.41	N/A	59.5	0.957	3000.0	82.0	36000.0	2/20/2012	Dimmable	
U S LED LTD	USLED	LRT65-1-40-14-120-6-W	Both	Solid State	Downlight Solid State Retrofit	864.0	14.02	N/A	61.5	0.957	4000.0	83.0	36000.0	2/20/2012	Dimmable	
U S LED LTD	USLED	LRT65-1-50-14-120-6-W	Both	Solid State	Downlight Solid State Retrofit	907.0	14.39	N/A	63.1	0.957	5000.0	80.0	36000.0	2/20/2012	Dimmable	
Vantage Engineering Limited	PORTFOLIO	VEL-02251102-PIR-BK;VEL-03091103CA-PIR-BZ;VEL-1005-7W-PIR;VEL-2867M D-7W-PIR;VEL-5069-MD-PIR	Residential	Halogen	Other (Motion-Activated Wall Lantern)	N/A	100.0	N/A	N/A	N/A	N/A	N/A	N/A	5/29/2012		
Vantage Engineering Limited	PORTFOLIO	VEL-8041MD-BK	Residential	Halogen	Other	N/A	100.0	N/A	N/A	N/A	N/A	N/A	N/A	8/2/2012		Motion-Activated Wall Lantern
Vantage Engineering Limited	PORTFOLIO	VEL-8041MD-BK-TWIN	Residential	Halogen	Other	N/A	100.0	N/A	N/A	N/A	N/A	N/A	N/A	8/2/2012		Motion-Activated Wall Lantern
Vantage Engineering Limited	PORTFOLIO	VEL-8041MD-BN	Residential	Halogen	Other	N/A	100.0	N/A	N/A	N/A	N/A	N/A	N/A	8/2/2012		Motion-Activated Wall Lantern
Vantage Engineering Limited	PORTFOLIO	VEL-8041MD-PB	Residential	Halogen	Other	N/A	100.0	N/A	N/A	N/A	N/A	N/A	N/A	8/2/2012		Motion-Activated Wall Lantern

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
WAC Lighting	N/A	HR-2LD-ET*09X-Y-ZZ	Residential	Solid State	Downlight Solid State Retrofit	610.0	14.0	N/A	43.0	0.9	2700.0	83.0	36000.0	10/24/2012	Dimmable	** suffix 1 and 7 refer to the shape of panel: round, square, respectively, X' refer to the beam angle F = 53Å°, N = 30Å°, S = 16.5Å°, Y' refer to the CCT:27 = 2700 K, W = 3000 K, 35 = 3500 K, C = 4000 K Z' indicate color of the panel
WAC Lighting	N/A	HR-3LD-ET*18F-Y-ZZ	Residential	Solid State	Downlight Solid State Retrofit	896.0	21.0	N/A	42.0	0.9	2700.0	82.0	36000.0	10/24/2012	Dimmable	** suffix 1 and 7 refer to the shape of panel: round with 44Å° beam angle, square 84Å° beam angle, respectively, Y' refer to the CCT:27 = 2700 K, W = 3000 K, 35 = 3500 K, C = 4000 K, Z' indicate color of the panel
WAC Lighting	WAC Lighting	HR-LED4q-xy-zC	Both	Solid State	Downlight Recessed	554.0	10.05	N/A	55.0	0.9	3000.0	80.0	60000.0	5/17/2012	Dimmable	q--18 for spackle trim, 51 for open reflector, 21 for step baffle x--N for new construction, R for remodel y--IC for insulation contact z--RO for round, SQ for Square W--Warm White C--Cool White
WAC Lighting	WAC Lighting	HR-LED4q-xy-zW	Both	Solid State	Downlight Recessed	554.0	10.05	N/A	55.0	0.9	3000.0	80.0	60000.0	5/17/2012	Dimmable	q--18 for spackle trim, 51 for open reflector, 21 for step baffle x--N for new construction, R for remodel y--IC for insulation contact z--RO for round, SQ for Square W--Warm White C--Cool White
Wave Lighting	Wave Lighting	10xx-Gxx-xxx	Residential	Fluorescent	Porch Light	1800.0	27.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	156FM-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	157FM-2EXX-XXXX	Residential	Fluorescent	Ceiling Mount	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	157FM-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	15xFM-xxxx-xx-xxx	Residential	Fluorescent	Ceiling Mount	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	164FMX-2EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	164FMX-EXX-XXXX	Residential	Fluorescent	Ceiling Mount	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	164FMx-xxxx-xxxxx	Residential	Fluorescent	Ceiling Mount, Wall Sconces	1200.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	165FMx-xxxx-xxxxx	Residential	Fluorescent	Ceiling Mount, Wall Sconces	1200.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	204SX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	204VX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	208SX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Wave Lighting	Wave Lighting	20xx-xx-xxx-xxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	20xxx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	214VC-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	21xx-xx-xxx-xxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	220SX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	221SX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	22xxx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	230xxx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	231xxx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	240SX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	240VX-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	240xx-Gxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	260xx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	261xx-xxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	66.7	N/A	0.6	2700.0	82.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	40x-Gxx-xxx	Residential	Fluorescent	Porch Light	1800.0	27.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	60x-Gxx-xxx	Residential	Fluorescent	Porch Light	1800.0	27.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	785-EXX-XXXX	Residential	Fluorescent	Porch Light	1027.0	14.0	73.0	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	785-Gxx-xxxx	Residential	Fluorescent	Porch Light	1800.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S75XX-EXX-XXXX	Residential	Fluorescent	Porch Light	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S75xx-Gxx-xxxx	Residential	Fluorescent	Porch Light	1600.0	23.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S75xx-x-Gxx-xxxx	Residential	Fluorescent	Porch Light	3200.0	46.0	69.6	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S771WF-E2XX-XXXX	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S771WF-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S771WF-xGxx-xxxx	Residential	Fluorescent	Wall Sconces	1800.0	27.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S7XWF-2EXX-XXXX	Residential	Fluorescent	Wall Sconces	2400.0	36.0	65.6	N/A	0.6	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S7XWF-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S7xWF-xGxx-xxxx	Residential	Fluorescent	Wall Sconces	1800.0	27.0	69.2	N/A	0.6	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Wave Lighting	Wave Lighting	S7XXWF-2EXX-XXXX	Residential	Fluorescent	Wall Sconces	3150.0	45.31	69.5	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S7XXWF-EXX-XXXX	Residential	Fluorescent	Wall Sconces	1547.0	21.8	71.0	N/A	0.53	2700.0	81.0	10000.0	9/28/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	S7xxWF-xGxx-xxxxx	Residential	Fluorescent	Ceiling Mount	1800.0	36.0	66.7	N/A	0.5	2700.0	83.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Wave Lighting	Wave Lighting	SxxX-Gxx-xxxxx	Residential	Fluorescent	Porch Light	1800.0	27.0	69.2	N/A	0.6	2700.0	81.0	10000.0	3/30/2012		Variable X can be added or dropped from catalog number
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1001GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1002GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1002GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1002GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-213	Residential	Fluorescent	Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-218	Residential	Fluorescent	Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-223	Residential	Fluorescent	Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1003GU-XX-226	Residential	Fluorescent	Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1004GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1004GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1004GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1005GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1005GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1009GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1009GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1010GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1013GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1014GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1016GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1019GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1022GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	1027GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1028GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1036GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1038GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1038GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1040GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1048GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1048GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1048GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1049GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1049GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1049GU-XX-126	Residential	Fluorescent	Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1051GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1051GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1060GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1064GU-XX-113	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1064GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1064GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1065GU-XX-113	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1065GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1065GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1066GU-XX-113	Residential	Fluorescent	Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1066GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1066GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1067GU-XX-113	Residential	Fluorescent	Ceiling Mount;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1067GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1067GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1067GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1067GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1068GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1070GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1070GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1070GU-XX-213	Residential	Fluorescent	Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1070GU-XX-218	Residential	Fluorescent	Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1070GU-XX-223	Residential	Fluorescent	Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1071GU-XX-118	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1071GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	1115GU-XX-123	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1115GU-XX-213	Residential	Fluorescent	Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1115GU-XX-218	Residential	Fluorescent	Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1115GU-XX-223	Residential	Fluorescent	Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1115GU-XX-226	Residential	Fluorescent	Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1117GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1117GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1117GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1117GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	1117GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2001GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-213-11	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-213-13	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-218-13	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2002GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2004GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2004GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2004GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2004GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2006GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2006GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2009GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2010GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2014GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2014GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2014GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2014GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2014GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2017GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2017GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2017GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2017GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2017GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2023GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2028GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2029GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2029GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2029GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2030GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2030GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2031GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2031GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2032GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2032GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2032GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2033GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2034GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2036GU-XX-226	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2042GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2043GU-XX-318-F1	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2043GU-XX-318-F2	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2043GU-XX-318-F4	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2050GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2050GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2050GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2050GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2050GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2051GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-126	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2057GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2058GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2058GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2058GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2058GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2058GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2059GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2059GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2059GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2059GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2059GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2060GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2060GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2060GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2060GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2060GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2061GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2061GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2061GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2061GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2061GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2062GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2062GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2062GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2062GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2062GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2063GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2063GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2063GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2063GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2063GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2064GU-XX-118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2064GU-XX-123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2064GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2064GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2064GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2071GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2071GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2071GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2072GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2072GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2072GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2073GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2073GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2073GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2074GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2074GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	2074GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount,Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2308GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2308GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2308GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2309GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2309GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2309GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2310GU-XX-213	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2310GU-XX-218	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	2310GU-XX-223	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3001GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3001GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3001GU-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-113	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3016GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-113	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3017GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3018GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3021GU-XX-113	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3021GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3021GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3021GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces;Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3024GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3024GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	3024GU-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3025GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3025GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3025GU-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3032GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3066GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3069GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3069GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3074GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3076GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3079GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3081GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3082GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-126	Residential	Fluorescent	Bath Vanity;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3083GU-XX-226	Residential	Fluorescent	Bath Vanity;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3084GU-XX-118	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3084GU-XX-123	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3084GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3084GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3084GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3087GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3095GU-XX-113	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3095GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3095GU-XX-313	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3095GU-XX-413	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-213	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-218	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-313	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-318	Residential	Fluorescent	Bath Vanity;Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-323	Residential	Fluorescent	Bath Vanity;Wall Sconces	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-413	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-418	Residential	Fluorescent	Bath Vanity;Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3096GU-XX-423	Residential	Fluorescent	Bath Vanity;Wall Sconces	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		





ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-313	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-318	Residential	Fluorescent	Bath Vanity;Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-323	Residential	Fluorescent	Bath Vanity;Wall Sconces	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-413	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-418	Residential	Fluorescent	Bath Vanity;Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3113GU-XX-423	Residential	Fluorescent	Bath Vanity;Wall Sconces	6400.0	92.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3114GU-XX-223	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3115GU-XX-313	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3115GU-XX-413	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3116GU-XX-313	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	3116GU-XX-413	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	4302GU-XX-218	Residential	Fluorescent	Decorative Pendant	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	4304GU-XX-118	Residential	Fluorescent	Decorative Pendant	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7001GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7002GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7003GU-XX-113	Residential	Fluorescent	Ceiling Mount;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7003GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7003GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7004GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	7004GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7004GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7004GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7004GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7005GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7005GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7005GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7005GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7005GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7006GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7006GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7006GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7006GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7006GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7007GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7007GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7007GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7007GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7007GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7008GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7008GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7009GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7009GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7010GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7010GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7014GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7015GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7016GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7016GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7016GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7016GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7016GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7017GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7017GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7017GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7017GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7017GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7021GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7021GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7031GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7031GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7031GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Xing Nan Lighting Co., Ltd.	Xing Nan	7031GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-118	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-123	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-126	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1650.0	26.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-213	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-218	Residential	Fluorescent	Ceiling Mount;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-223	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Xing Nan Lighting Co., Ltd.	Xing Nan	7033GU-XX-226	Residential	Fluorescent	Ceiling Mount;Wall Sconces	3300.0	52.0	76.64	N/A	0.562	2700.0	81.4	10000.0	2/23/2012		
Yellow Energy	Biltmore	B770GU123-BZ-27K	Residential	Flourescent	Ceiling Mount	1600.0	23.0	72.3	N/A	0.568	2700.0	82.0	10000.0	11/17/2011		
Yellow Energy	Biltmore	B770GU123-XX-27K	Residential	Flourescent	Ceiling Mount	1600.0	23.0	72.3	N/A	0.568	2700.0	82.0	10000.0	11/17/2011		
Yellow Energy	Biltmore	B771GU218-BZ-27K	Residential	Flourescent	Ceiling Mount	2500.0	36.0	74.1	N/A	0.56	2700.0	82.0	10000.0	11/17/2011		
Yellow Energy	Biltmore	B771GU218-NI-27K	Residential	Flourescent	Ceiling Mount	2500.0	36.0	74.1	N/A	0.56	2700.0	82.0	10000.0	11/17/2011		
Yellow Energy	Biltmore Lighting	10311-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10311-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10311-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10311-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10311-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10311-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10313-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10313-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10313-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10315-ES-3013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10315-ES-3018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10315-ES-3023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10370-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10371-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	10372-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1096-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1096-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1096-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1097-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1097-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1097-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1291-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1291-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1291-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1292-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1292-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1292-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	17112-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	17118-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	17124-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	17136-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		



ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	17148-ES	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1738-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1738-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	1738-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2801-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2801-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2802-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2802-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2803-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2803-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2804-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2804-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2805-ES-5013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2805-ES-5018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2806-ES-6013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	2806-ES-6018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3256-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3256-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3256-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3258-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3258-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3258-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	325-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	325-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	325-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	326-ES-1013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	326-ES-1018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	326-ES-1023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	351-4301-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	351-4301-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	351-4301-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	3632-ES	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5551-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5551-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5552-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5552-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5553-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5553-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5554-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5554-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5555-ES-5013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5555-ES-5018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5556-ES-6013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	5556-ES-6018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	57700-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57700-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57700-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57701-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57701-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57701-ES-2023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57702-ES-3013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57702-ES-3018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	57702-ES-3023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58800-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58801-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58801-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58801-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58802-ES-3013	Residential	Fluorescent	Ceiling Mount	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58802-ES-3018	Residential	Fluorescent	Ceiling mount	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	58802-ES-3023	Residential	Fluorescent	Ceiling mount	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	6020-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	6020-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	9307-ES-1013	Residential	Fluorescent	Ceiling Mount	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	9307-ES-1018	Residential	Fluorescent	Ceiling mount	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	9307-ES-1023	Residential	Fluorescent	Ceiling mount	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B101GU118-XX-27K	Residential	Fluorescent	Ceiling Mount,Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B105GU118-XX-27K	Residential	Fluorescent	Bath Vanity,Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B108GU123-XX-27K	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B1153-XX	Residential	Fluorescent	Bath Vanity,Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B1154-XX	Residential	Fluorescent	Bath Vanity,Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B117GU218-XX-27K	Residential	Fluorescent	Bath Vanity,Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B131GU218-XX-27K	Residential	Fluorescent	Bath Vanity,Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B140GU123-XX-27K	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B141GU118-XX-27K	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B142GU218-XX-27K	Residential	Fluorescent	Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B14GU118-XX-27K	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B151-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B151-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B151GU118-XX-27K	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B152-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B152-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B153-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B153-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B154-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B154-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	B155-ES-5013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B155-ES-5018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B156-ES-6013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B156-ES-6018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B161GU118-XX-27K	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B19009-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B19009-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B19009-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B225-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B225-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B225-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B241GU318-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B243GU318-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B244GU318-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B255GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B257GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B283GU313-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B284GU413-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B311GU113-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B311GU118-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B312GU213-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B313GU313-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B314GU413-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B33GU118-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B34GU113-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B351-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B351-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B352-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B352-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B353-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B353-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B353GU313-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	B354-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B354-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B354GU413-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B355-ES-5013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B355-ES-5018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B356-ES-6013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B356-ES-6018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B35GU118-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B36GU213-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B376GU218-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B381GU218-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B382GU123-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B389GU218-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B404-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B404-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B404-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B434GU118-XX-27K	Residential	Fluorescent	Decorative Pendant	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B44GU113-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B45GU118-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B46GU213-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B48GU123-XX-27K	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B49GU123-XX-27K	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B609GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B611GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B6160-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B6160-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B6160-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B61GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B63GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	B66GU223-XX-27K	Residential	Fluorescent	Bath Vanity;Wall Sconces	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B690-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B690-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B691-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B691-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B691-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B692-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B692-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B693-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B693-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B694-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B694-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B695-ES-5013	Residential	Fluorescent	Bath Vanity, Wall Sconces	4500.0	65.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B695-ES-5018	Residential	Fluorescent	Bath Vanity, Wall Sconces	6250.0	90.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B696-ES-6013	Residential	Fluorescent	Bath Vanity, Wall Sconces	5400.0	78.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B696-ES-6018	Residential	Fluorescent	Bath Vanity, Wall Sconces	7500.0	108.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B705GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B708GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B708GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B714GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B716GU213-XX-27K	Residential	Fluorescent	Ceiling Mount;Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	B723GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B728GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B728GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B83GU123-XX-27K	Residential	Fluorescent	Wall Sconces	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B85GU118-XX-27K	Residential	Fluorescent	Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B912GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B914GU218-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Yellow Energy	Biltmore Lighting	B916GU223-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B92GU123-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B96-ES-1013	Residential	Fluorescent	Bath Vanity, Wall Sconces	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B96-ES-1018	Residential	Fluorescent	Bath Vanity, Wall Sconces	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B97-ES-2013	Residential	Fluorescent	Bath Vanity, Wall Sconces	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B97-ES-2018	Residential	Fluorescent	Bath Vanity, Wall Sconces	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B97GU118-XX-27K	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	B98-ES-3013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B98-ES-3018	Residential	Fluorescent	Bath Vanity, Wall Sconces	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B99-ES-4013	Residential	Fluorescent	Bath Vanity, Wall Sconces	3600.0	52.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	B99-ES-4018	Residential	Fluorescent	Bath Vanity, Wall Sconces	5000.0	72.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	BP42-232;W24E-120V	Residential	Fluorescent	Linear Strip	4065.0	64.0	79.61	N/A	0.613	4100.0	83.0	10000.0	7/2/2012		
Yellow Energy	Biltmore Lighting	BR11-D13-41K	Residential	Fluorescent	Ceiling Mount, Residential Portable Desk Task Light	1360.0	26.0	65.45	N/A	0.574	4100.0	80.9	10000.0	7/2/2012		
Yellow Energy	Biltmore Lighting	BXX-SCHL-GU113	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	2/22/2012		
Yellow Energy	Biltmore Lighting	BXX-SCHL-GU118	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	BXX-SCHL-GU123	Residential	Fluorescent	Ceiling Mount;Close to Ceiling Mount;Ceiling Fan Light Kit	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	2/23/2012		
Yellow Energy	Biltmore Lighting	E48AL-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	E48AL-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	E48AL-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	E62ALAB-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	E62ALAB-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	E62ALAB-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F2199-ES-2013	Residential	Fluorescent	Ceiling Mount	1800.0	26.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F2199-ES-2018	Residential	Fluorescent	Ceiling mount	2500.0	36.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F2199-ES-2023	Residential	Fluorescent	Ceiling mount	3200.0	46.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F7678-ES-3013	Residential	Fluorescent	Chandelier	2700.0	39.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F7678-ES-3018	Residential	Fluorescent	Chandelier	3750.0	54.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	F7678-ES-3023	Residential	Fluorescent	Chandelier	4800.0	69.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	LS17851-ES-1013	Residential	Fluorescent	Chandelier	900.0	13.0	70.97	N/A	0.615	2700.0	82.3	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	LS17851-ES-1018	Residential	Fluorescent	Chandelier	1250.0	18.0	74.09	N/A	0.56	2700.0	81.9	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	LS17851-ES-1023	Residential	Fluorescent	Chandelier	1600.0	23.0	72.32	N/A	0.568	2700.0	82.1	10000.0	9/11/2012		
Yellow Energy	Biltmore Lighting	W44E-120V	Residential	Fluorescent	Linear Strip	8130.0	128.0	79.61	N/A	0.613	4100.0	83.0	10000.0	7/2/2012		

ENERGY STAR Partner	Brand	Model Number	Intended for Commercial Use, Residential Use or Both?	Lighting Technology Used	Fixture Type	Light Output	Total Input Power (Watts)	Source Efficacy	Luminaire Efficacy	Power Factor	Correlated Color Temperature (Kelvin)	Color Rendering Index (CRI)	Light Source Life (Hours)	Date Qualified	Special Features (Dimming, Motion Sensing etc)	Notes
Zumtobel Lighting, Inc. USA	Zumtobel Lighting, Inc.	BR4XLEDXXWK35XSXD1	Both	Solid State	Downlight Recessed	1463.0	26.2	N/A	55.8	0.988	3500.0	83.0	36000.0	2/6/2012	Dimmable	X Can be D or W, XX Can be any value à ¢ 25. xSx can be any combination of N,M,W -S- 4,5
Zumtobel Lighting, Inc. USA	Zumtobel Lighting, Inc.	BR6XLEDXXWK35XSXD1	Both	Solid State	Downlight Recessed	1597.0	26.52	N/A	60.2	0.988	3500.0	83.0	36000.0	2/6/2012	Dimmable	X Can be D or W, XX Can be any value à ¢ 25. xSx can be any combination of N,M,W -S- 4,5
Zumtobel Lighting, Inc. USA	Zumtobel Lighting, Inc.	BS4XLEDXXWK35XSXD1	Both	Solid State	Downlight Recessed	1562.0	24.7	N/A	63.2	0.974	3500.0	83.0	36000.0	2/6/2012	Dimmable	X Can be D or W, XX Can be any value à ¢ 25. xSx can be any combination of N,M,W -S- 4,5
Zumtobel Lighting, Inc. USA	Zumtobel Lighting, Inc.	BS6XLEDXXWK35XSXD1	Both	Solid State	Downlight Recessed	1408.0	25.55	N/A	55.1	0.977	3500.0	82.0	36000.0	2/6/2012	Dimmable	X Can be D or W, XX Can be any value à ¢ 25. xSx can be any combination of N,M,W -S- 4,5

## Key Efficiency Criteria

Qualified models meet all ENERGY STAR requirements as listed in the Version 1.1 ENERGY STAR Program Requirements for Luminaires.

Performance Characteristic	Minimum Requirements
<b>Light Output</b>	<p>Non-directional luminaires (those listed with a "Source Efficacy" value in column J): <math>\geq 800</math> lumens, or <math>\geq 450</math> lumens for fixtures with three sources or more.</p> <p>Directional fixtures: <math>\geq 125</math> lumens/foot for undercabinet, 200 lumens/foot for cove mount, 345 or 575 for downlights (depending on aperture size), 200 lumens per head for accent lights, 300 lumens for outdoor post-mounted luminaires.</p>
<b>Source Efficacy (non-directional luminaires)</b>	<p><math>\geq 65</math> lm/W  <math>\geq 70</math> lm/W after September 2013</p>
<b>Luminaire Efficacy (directional luminaires)</b>	<p>Dependent on fixture type/application starting at <math>\geq 29</math> lm/W</p>
<b>Power Factor</b>	<p>Residential: <math>\geq 0.5</math>  Commercial: <math>\geq 0.9</math></p> <p>Solid state residential with input power greater than 5 watts: <math>\geq 0.7</math></p>
<b>Correlated Color Temperature</b>	<p>Lamps shipped with luminaires shall have one of the following nominal correlated color temperatures (CCT): 2700K, 3000K, 3500K, 4000/4100K, 5000K (commercial only)</p>
<b>Color Rendering Index</b>	<p>Ra <math>\geq 80</math></p>
<b>Light Source Life</b>	<p>Fluorescent and HID: <math>\geq 10,000</math> hours  Halogen incandescent: <math>\geq 2,500</math> hours  Solid state (LED): <math>\geq 25,000</math> residential or <math>\geq 35,000</math> commercial</p>



## Definitions for Column Headers

Performance Characteristic	Definitions
<b>Light Output</b>	The amount of light emitted by the light source or light fixture. Non directional fixtures (with removable light sources i.e. GU24 base bulbs) are measured at the light source and do not account for light lost from the fixture, while other fixtures meant to put light on a specific application (e.g. recessed downlights, under cabinet lights, accent lights, cove lights) are measured at the fixture level, only counting the light that escapes the fixture.
<b>Source Efficacy</b>	The quotient of the total light source/lamp luminous flux (lumens) emitted over the total lamp power input (Watts). It is expressed in lm/W. For ENERGY STAR qualified fixtures this applies to light fixtures that are residential only, considered "non-directional" and have been measured at the light source level.
<b>Luminaire Efficacy</b>	The quotient of the total luminous flux (lumens) emitted by the fixture over the total power input (Watts). It is expressed in lumens per watt (lm/W). For ENERGY STAR qualified fixtures this applies to light fixtures that are considered directional and are measured at the fixture level. This includes the following residential grade directional fixture types: line-voltage track lights, ceiling fan light kits, undercabinet and cove lighting, downlights, recessed, pendant or surface mounted and includes retrofit kits for existing recessed cans. This also includes the following LIMITED commercial fixture types: Accent lights such as line-voltage track lights, under cabinet task lights, portable desk task lights, downlights, recessed, pendant or surface-mounts BUT EXCLUDES typical commercial and industrial fixtures such as recessed troffers or linear forms (e.g. linear fluorescent pendants) typically used in office spaces.
<b>Power Factor</b>	Ratio of real power flowing to the lamp to the apparent power in the circuit. A lamp with a lower power factor will draw more current than a lamp with a higher power factor of the same wattage.

## Definitions for Column Headers

<b>Correlated Color Temperature</b>	A description of the "color" of a light source measured on the Kelvin (K) scale. CFLs are available in a range of color temperatures. Lower values (2700-3000K) mean the white light has a warmer (red-yellow) tone, while higher kelvin (4100-6500K) mean the white light has a cooler (bluer) tone.
<b>Color Rendering Index</b>	Measure of the degree of color shift objects undergo when illuminated by the light source as compared with the color of those same objects when illuminated by a reference source of comparable color temperature.
<b>Light Source Life</b>	The expected useful life of the light source. Measured differently depending on the technology of the light source. For example, LED lighting expected useful life is based on the estimated point at which only 70% of the original light output remains, while for older technologies, like fluorescent and halogen, estimated useful life is based on the measured median sample life.