Basic Specifications – Engines February 2010

General specifications:

Certification: NFPA 1906 (with limited exceptions)

Striping: per draft FS handbook supplement (based on R-5 requirements)

Color:

Transmission: Automatic

Panel location: Rear

Hose Reel: One - for all engine types except Type 4

Foam proportioner: Automatic-regulating injection on discharge side of pump

Green

Type		<u>Tank</u>	Body	<u>Pump</u>	<u>Foam</u>	
3	Mo226/346	600 gal	Crew cab utility body	PTO single stage pump	25 gal	4x2 or 4x4, SCBA seats w/cylinder storage, chainsaw storage bracket
				Options		ns
3	328/348	800 gal	Single cab utility body	PTO single stage pump	25 gal	4x2 or 4x4, chainsaw storage bracket
4	428/448	800 gal	Crew cab utility body	Auxiliary, turbo diesel	25 gal	4x2 or 4x4
6	643U	300 gal	Crew cab utility body	Auxiliary, turbo diesel	12 gal	Steel utility body
6	643P	300 gal	Crew cab platform body	Auxiliary, turbo diesel	12 gal	BB4 pump
7*	n/a	50 gal	n/a	Auxiliary, gas powered	5 gal**	Foam proportioner, side panel
7*	n/a	125 gal		Auxiliary, gas powered	5 gal**	Foam proportioner, side panel

n/a

^{*} Slip-on unit only

^{**} if equipped with foam system