


- NOTES
- FOR ADDITIONAL NOTES SEE DWG. 10425-20
 - CHAIN SHALL BE HIGH STRENGTH GRADE 80 ALLOY STEEL CHAIN HANG 5/8" Ø 20' LONG, GALV. IN FULL MANUFACTURER'S PINT PROTECTION
 - FOR WALK REPLACEMENT NUTS, SEE 10425-20
 - WALK STOP SHALL BE AN ANTI-SLIP CASSETT INTERSTOP AS MANUFACTURED BY COTY. MANUFACTURER'S INSTALLATION INSTRUCTIONS SHALL BE FOLLOWED.
 - SECTION SHALL BE CONSTRUCTED WITHIN THREE (3) WEEKS OF THE DATE OF THE CONTRACT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS.



- NO. 10
- FILTER FABRIC SHALL BE PLACED PRIOR TO THE START OF WEIR CONSTRUCTION.
 - STEEL NUTS SHALL BE MIN. 1/2" DIAM. & 6" LONG.
 - WALK STOP SHALL BE PLACED AT 4' INTERVALS MAX.
 - WALK STOP SHALL BE PLACED PRIOR TO THE START OF WEIR CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS.
 - WALK STOP SHALL BE PLACED PRIOR TO THE START OF WEIR CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS.

NO.	DESCRIPTION	QTY.	UNIT	REMARKS
1	STEEL NUTS	10	EA	MIN. 1/2" DIAM. & 6" LONG
2	WALK STOP	1	EA	MIN. 1/2" DIAM. & 6" LONG
3	FILTER FABRIC	1	EA	MIN. 1/2" DIAM. & 6" LONG
4	WALK STOP	1	EA	MIN. 1/2" DIAM. & 6" LONG
5	FILTER FABRIC	1	EA	MIN. 1/2" DIAM. & 6" LONG