FIPS 140-2 Validation Certificate



The National Institute of Standards and Technology of the United States of America





The Communications Security
Establishment of the Government
of Canada

Certificate No. 1036

The National Institute of Standards and Technology, as the United States FIPS 140-2 Cryptographic Module Validation Authority; and the Communications Security Establishment, as the Canadian FIPS 140-2 Cryptographic Module Validation Authority; hereby validate the FIPS 140-2 testing results of the Cryptographic Module identified as:

Cisco 1841 Integrated Services Routers with AIM-VPN/BPII-Plus and Cisco 2801 Integrated Services Routers with AIM-VPN/EPII-Plus by Cisco Systems, Inc. (When operated in FIPS mode)

in accordance with the Derived Test Requirements for FIPS 140-2, Security Requirements for Cryptographic Modules. FIPS 140-2 specifies the security requirements that are to be satisfied by a cryptographic module utilized within a security system protecting *Sensitive Information* (United States) or *Protected Information* (Canada) within computer and telecommunications systems (including voice systems).

Products which use the above identified cryptographic module may be labeled as complying with the requirements of FIPS 140-2 so long as the product, throughout its life cycle, continues to use the validated version of the cryptographic module as specified in this certificate. The validation report contains additional details concerning test results. No reliability test has been performed and no warranty of the products by both agencies is either expressed or implied.

This certificate includes details on the scope of conformance and validation authority signatures on the reverse.

FIPS 140-2 provides four increasing, qualitative levels of security: Level 1, Level 2, Level 3, and Level 4. These levels are intended to cover the wide range and potential applications and environments in which cryptographic modules may be employed. The security requirements cover eleven areas related to the secure design and implementation of a cryptographic module. The scope of conformance achieved by the cryptographic modules as tested in the product identified as:

Cisco 1841 Integrated Services Routers with AIM-VPN/BPII-Plus and Cisco 2801 Integrated Services Routers with AIM-VPN/EPII-Plus by Cisco Systems, Inc.

(Hardware Versions: 1841 and 2801; AIM-VPN/BPII-Plus Version: 1.0, Board Version: C1; AIM-VPN/EPII-Plus Version: 1.0, Board Version: D0; Firmware Version: 12.4(15)T3; Hardware)

and tested by the Cryptographic Module Testing accredited laboraris as follows:		Atlan Laboratories, NVLAP Lab Code 200492-0 y: CRYPTIK Version 7.0	
Cryptographic Module Specification:	Level 2	Cryptographic Module Ports and Interfaces:	Level 2
Roles, Services, and Authentication:	Level 2	Finite State Model:	Level 2
Physical Security:	Level 2	Cryptographic Key Management:	Level 2
(Multi-Chip Standalone) EMI/EMC:	Level 2	Self-Tests:	Level 2
Design Assurance:	Level 2	Mitigation of Other Attacks:	Level N/A
Operational Environment:	Level N/A	tested in the following configuration(s): N/A	
The following FIPS approved Cryptographic Algorithms are used:		AES (Certs. #100, #181 and #795); HMAC (Certs. #27, #38 and #436); RNG (Certs. #80 and #456); RSA (Certs. #379 and #383); SHS (Certs. #267, #401	

The cryptographic module also contains the following non-FIPS approved algorithms: Diffie-Hellman (key agreement; key establishment methodology provides 80 or 96 bits of encryption strength); RSA (key wrapping; key establishment methodology provides between 80 and 112 bits of encryption strength); MD5; HMAC-MD5; RC4; DES

and #794); Triple-DES (Certs. #213, #283 and #683)

Overall Level Achieved: 2

Signed on behalf of the Government of the United States	Signed on behalf of the Government of Canada	
	Signature:	
Dated: October 14, 2008	Dated: October 3, 2,008	
Chief, Computer Security Division National Institute of Standards and Technology	Director, Industry Program Group Communications Security Establishment Canada	