


DOZER TRACKS CREATE TRACK
IMPRINTS PARALLEL TO THE
SLOPE CONTOUR.

NOTE:

PERFORM VERTICAL TRACKING ON SLOPES TO TEMPORARILY STABILIZE SOIL. PROVIDE EQUIPMENT WITH A TRACK UNDERCARRIAGE CAPABLE OF PRODUCING LINEAR SOIL IMPRESSIONS MEASURING AT LEAST 12" IN LENGTH BY 2" TO 4" IN WIDTH BY 1/2" TO 2" IN DEPTH. DO NOT EXCEED 12" BETWEEN TRACK CLEATS. INSTALL CONTINUOUS LINEAR TRACK IMPRESSIONS WHERE THE MINIMUM 12" IN LENGTH IS PERPENDICULAR TO THE DIRECTION OF WATER FLOW.

©2007  Texas Department
of Transportation
Dallas District Standard
TEMPORARY EROSION,
SEDIMENT AND WATER
POLLUTION CONTROL MEASURES
VERTICAL TRACKING
FOR EROSION CONTROL

FED. RD. DIV. NO.	PROJECT NUMBER		SHEET NUMBER
18			00
STATE	DISTRICT	COUNTY	
TEXAS	DALLAS		
CONTROL	SECTION	JOB	HIGHWAY NUMBER