

**Price**

- ~\$27,000.00 (without the KG-250X)

Capabilities

- Concurrent voice, video, and data over multiple transmission paths to include built in cellular (3G/4G), built in WiFi or Ethernet connection to Public Internet or Satellite terminal

Physical specifications

- Kit: Width: 14.7", Depth: 8.9", Height: 3.3" H
- 9.2lbs / 4.1kg (no KG-250X); 12 lbs / 5.4kg (with KG-250X)
- Carbon fiber structure
- IP65 Ingress protection; MIL-STD 810G compliant

Power specifications

- Global AC charging / supports vehicle power supply
- 10-36V DC Input range
- 2 hour internal battery power for all components & PoE on both red and black enclaves

Environmental specifications

- Operating temperature: -10°C to +55°C
- Storage temperature: -20°C to +70°C

Network Interfaces*Classified Enclave*

- 6 ethernet interfaces, including 4 PoE
- VIK interface for end-user persona mobility
- FXS port for two-wire telephone support
- USB interface for expansion

Unclassified Enclave

- 4 Ethernet connections, including 1 PoE
- Internal connection to ViaSat KG-250X CT (FE 0/2)
- Includes Cisco 5915 ESR and CradlePoint IBR600 3G/4G/Wi-Fi router
- WiFi 802.11 in client or server mode with Full Security
- AT&T, Verizon, Sprint and International modem variants

Encryption Support

- Supports Suite-B algorithms for CSfC applications

Ordering Information

Klas Telecom Sales at 202-813-0004
sales@klastelecom.com

**Price**

~\$13,500 - \$15,000 (Unrugged, Semi, and Full-Ruggedized)

Capabilities

- Concurrent voice, video, and data per security domain
- Multi-domain capability permits both unclassified and classified access
- Special Modes: Stealth Mode / Optional night vision mode setting

Physical specifications

- Case: Width: 10.68" , Depth: 9.69" , Height: 6.82" , Weight: 8.1 lbs
- Laptop: Width: 13.46" , Depth: 9.64" , Height: 1.85" , Weight: 7.4 lbs
- 19 lbs (case, laptop, peripherals)
- Intel® Core™ Ivy Bridge 3rd Generation vPro™ i7 Processor
- Splash resistant keyboard, sealed ports and connectors
- 2 Smart card readers (For Class Token & CaC), Push-2-Talk Headset
- 14" HD Widescreen, sunlight readable LCD
- M-SATA SSD as the main storage, Two DDRIII 1600 MHz SODIMM 16GB
- L-3 Com Talon II Encryptor (KOV-26B) NSA Type 1 Certification
- Cisco ASA 5505 Firewall/VPN Appliance (JITC Approved 9.1.5 Firmware)

Power specifications

- AC power input: 100V-240V, 50Hz-60Hz
- Standard Battery : 9-cell 7800 mAh (Optional hot-swappable second battery pack 6-cell 5200 mAh)

Network Interfaces

- Embedded RG-45 / External Wifi, RG-45 & 4G connection via KOV-26B

Environmental Specifications

- Drop, Shock, and Dust/Water Resistant (MIL-STD-810G, Method 514.6)
- Operating temperature: 32F to 140F
- -- 5% to 95% relative humidity (RH)

Ordering Instructions

Contact 727-545-8510 or giovanni.suarez@niacorp.com