



**U.S. Army Corps
of Engineers**
Northwestern Division

Lower Missouri River Navigation Charts

Rulo, Nebraska to St. Louis, Missouri

FEB 2014



Requests for maps or information should be addressed to:

Additional marine mapping products can be found at:

Additional marine mapping products can be found at:

U.S. Army Engineer District, Kansas City

ATTN: Geospatial Data Section
601 East 12th Street
Kansas City, MO 64106
816-389-3669

<http://www.nwk.usace.army.mil/Missions/CivilWorks/Navigation.aspx>

U.S. Army Topographic Engineering Center

7701 Telegraph Road
Alexandria, VA 22315-3864
703-428-6816

<http://www.agc.army.mil/Missions/Echarts.aspx>

NOAA (National Oceanic and Atmospheric Administration)

14th Street & Constitution Avenue, N.W.
Room 6217
Washington, D.C. 20230
202-482-6090

<http://www.noaa.gov>

COAST GUARD UNIT

Commander
Eighth Coast Guard District
Hale Boggs Federal Building
500 Poydras Street
New Orleans, Louisiana 70130
Commander 504-671-2020

U.S. Coast Guard, Cutters' Cheyenne & Gasconade
Foot of Arsenal St.
Bldg. 17
St. Louis, MO 63108
Call Sign - Coast Guard Cutter Cheyenne or Gasconade

SECTOR UPPER MISSISSIPPI RIVER (08-37390)
1222 SPRUCE ST, SUITE 7.103
ST LOUIS, MO 63103
Primary Phone: 314-269-2500
Emergency Phone: 866-360-3386
Fax Number: 314-269-2734
URL: <http://www.uscg.mil/d8/sectUMR>
Quick Link <http://homeport.uscg.mil/umr>

USCG Navigation Center (NAVCEN)
7323 Telegraph Rd.
Alexandria, VA 22315
703-313-5900
<http://www.navcen.uscg.gov>
703-313-5900 (24 Hour Line)

US ARMY CORPS OF ENGINEERS

Kansas City District Office
601 E. 12th Street
Kansas City, Missouri 64106-2896
Telephone: 816-389-3486

Missouri River Area Office
790 E. 224 Highway
Napoleon, Missouri 64074-7001
Telephone: 816-240-8131

Gasconade Harbor Facility
P.O. Box 410
Hermann, MO 65041
Telephone: 573-294-6411

Glasgow Project Office
P.O. Box 76
Glasgow, Missouri 65254
Telephone: 660-338-2278/3139

REPORT OIL AND CHEMICAL SPILLS ANY TIME TO THE NATIONAL RESPONSE CENTER AT:
(TOLL FREE) 1-800-424-8802, (DIRECT) 202-267-2675, (ONLINE) <http://www.nrc.uscg.mil>

**NAVIGATION CHARTS
MISSOURI RIVER
KANSAS CITY DISTRICT
RULO, NEBRASKA TO ST. LOUIS, MISSOURI**

U.S. ARMY ENGINEER DISTRICT, KANSAS CITY
RICHARD BOLLING FEDERAL BLDG.
601 EAST 12TH ST.
KANSAS CITY, MISSOURI 64106

Points of Contact	Inside Front Cover
Table of Contents	
General Notes	
Legal Disclaimer & Metadata	Sheet A
Navigation Information	Sheet B
Regulations	
Rivers and Harbors Act - 1917	Sheet C-F
Rivers and Harbors Act - 1899	Sheet G-H
USCG Aids to Navigation	Sheet I
Legend	Sheet J
Map Index of Navigation Charts	Index Charts No. 1-3
Tabular Index of Navigation Charts	Sheet K
Navigation Charts	Charts No. 1-94
Appendices	
Vertical Clearances Table	Appendix A-1
Commercial River Terminals	Appendix B-1
Stage Gauge Information Table	Appendix C-1

The data herein, including but not limited to geographic data, tabular data, analytical data, electronic data structures or files, are provided "as is" without warranty of any kind, either expressed or implied, or statutory, including, but not limited to, the implied warranties or merchantability and fitness for a particular purpose. The entire risk as to the quality and performance of the data is assumed by the user. No guarantee of accuracy is granted, nor is any responsibility for reliance thereon assumed. In no event shall the U.S. Army Corps of Engineers, Kansas City District, Geospatial Data Section be liable for direct, indirect, incidental, consequential or special damages of any kind, including, but not limited to, loss of anticipated profits or benefits arising out of use of or reliance on the data. The Geospatial Data Section does not accept liability for any damages or misrepresentation caused by inaccuracies in the data or as a result of changes to the data caused by system transfers or other transformations or conversions, nor is there responsibility assumed to maintain the data in any manner or form.

These data have been developed from the best available sources. Although efforts have been made to ensure that the data are accurate and reliable, errors and variable conditions originating from physical sources used to develop the data may be reflected in the data supplied. Users must be aware of these conditions and bear responsibility for the appropriate use of the information with respect to possible errors, scale, resolution, rectification, positional accuracy, development methodology, time period, environmental and climatic conditions and other circumstances specific to these data. The user is responsible for understanding the accuracy limitations of the data provided herein. The burden for determining fitness for use lies entirely with the user. The user should refer to the accompanying metadata notes for a description of the data and data development procedures. Although these data have been processed successfully on computers at the Spatial Data Section, no guarantee, expressed or implied, is made by Spatial Data Section regarding the use of these data on any other system, nor does the act of distribution constitute or imply any such warranty. Distribution of these data is intended for information purposes and should not be considered authoritative for navigational, engineering, legal and other site-specific uses.

GENERAL

These navigation charts were generated from field surveys conducted by the U.S. Army Corps of Engineers offices and from aerial photography taken. Information presented on these charts can change and, therefore, anyone navigating on the Missouri River must exercise caution and acknowledge the ever-present hazards of this natural resource. Mariners are urged to submit any condition found to differ from those shown on the charts to <https://ienc-report.usace.army.mil/>, or call 816-389-3669.

PROCUREMENT OF NAVIGATION CHARTS

Navigation charts for the Federal navigation projects on the Western Rivers of the United States are available for purchase from the US Army Corps of Engineers. Navigation charts for the Missouri River can be procured from the following sources:

732 North Capitol Street NW
Washington, DC 20401-0001
202-512-1800

A list of locations for the purchase of navigation charts for other Corps' projects can be obtained from the following internet address:

<http://bookstore.gpo.gov>

Electronic navigation charts can be obtained from:

<http://www.agc.army.mil/echarts/inlandnav>

NAVIGATION NOTICES

Notices to Navigation Interests (Navigation Notice), containing data on channel conditions, location of dredges, etc., are issued by the Corps of Engineers as occasions warrant. Distribution of the Navigation Notices for the Missouri River is by e-mail. Requests to be placed on the distribution list for the Missouri River need to contact:

U.S Army Corps of Engineers, Northwestern Division

Kansas City District

601 East 12th St.

Kansas City, Missouri 64106

MILE POINTS


River mileage, as shown along the navigation project's sailing line, is measured from the mouth of the Missouri River and continues upstream to Rulo, Nebraska, river mile 498.4. The miles points do not represent actual distance along the sailing line. Generally, the mile points approximate a mile between the points; however, in areas where the alignment of the navigation channel has changed during its existence, the distance between mile points would tend to be greater or less than 1-mile in distance.

MISSOURI RIVER

AUTHORIZED PROJECT

The Corps of Engineers has the responsibility under Congressional authorization for the construction, operation and maintenance of the Missouri River for navigation, flood reduction and related purposes, including flow regulation and bank protection. The navigation project extends from Sioux City, Iowa to the mouth, a distance of 735 miles. The completed project provides a continuous navigation channel 9' deep and 300' wide, which is designed to flow along the concave side of the bends and through the crossing between bends. The Corps support of navigation is normally from latter March to latter November at Sioux City, and from the first of April to the first of December at the mouth. Ice conditions and low water may preclude navigation the rest of the year. Specific minimum flow rates are required during the navigation season to provide adequate depths and width. To meet this, insufficient natural flows are augmented by releases from upstream reservoirs. A flow of 30,000 to 35,000 cubic feet per second is generally maintained at Sioux City and Omaha, and 35,000 to 40,000 cubic feet per second at Kansas City. During the navigation season, river stages vary from a range of about one foot at Sioux City to around 15 feet at Hermann, Mo., and the velocity of the flow varies from 4 to 5 miles per hour.

CORPS OF ENGINEERS JURISDICTIONS



BUOYS

Buoys that are used to mark channels on the Missouri River system conform to the standard lateral system of buoyage on the Western Rivers of the United States. All buoys are equipped with reflectors; buoys on the left descending side of the channel reflect red; buoys on the right descending side of the channel reflect green. Due to practical limitations of positioning and maintaining floating buoys in precise geographical locations, buoy position shown on these navigation charts are approximate positions only, if shown. Prevailing river conditions alter the actual locations of the buoys. They may be carried off position by currents, high stages, accumulation of drift, ice, sunk by collision or other causes. When carried off position, destroyed or removed to prevent loss, buoys are re-established at the earliest opportunity by the U.S. Coast Guard.

GAUGES

River gauges provide current river stage conditions. See gauge table for data specific to individual gauges.

WATER SURFACE ELEVATIONS

All water surface elevations referenced on these charts are referenced to the North American Vertical Datum of 1988 (NAVD88) unless otherwise noted in the gauge table. The project depths refer to data collected during summer 2013.

VERTICAL CLEARANCES

Vertical clearances under bridges and overhead cables are shown on the respective charts as well as in the vertical clearance table. The source for the clearances is the U.S Coast Guard Light List Volume 5 for the Mississippi River System (<http://www.navcen.uscg.gov/>) and field verification surveys accomplished in Fall 2012. The project depths as well as the overhead clearances reference the Construction Reference Plane (CRP), which is defined as the stage or elevation at which the river's discharge is exceeded 75 percent of the time during the normal navigation season from April 1 to December 1.

PERMITS

In the administration of laws, enacted by Congress for the protection and preservation of navigation and the navigable waters of the United States, the U.S. Army Corps of Engineers exercises jurisdiction over the Missouri River and several of its tributary streams and wetlands. Anyone wishing to undertake a project in, under, over or adjacent to water (including wetlands) of the United States need to inquire at the appropriate Corps of Engineers District regarding permit requirements. Inquiries for such work or structures should be addressed to:

Kansas City District Regulatory Office
601 East 12th Street
Kansas City, MO 64106-2896
Telephone: 816-389-3990
Fax: 816-389-2032

REGULATIONS
PREScribed BY THE SECRETARY OF THE ARMY FOR
OHIO RIVER, MISSISSIPPI RIVER ABOVE CAIRO, IL., AND
THEIR TRIBUTARIES; USE, ADMINISTRATION
AND NAVIGATION

(The following are excerpts)

THE LAW

Section 7 of the River and Harbor Act of August 8, 1917, provides as follows:

“That it shall be the duty of the Secretary of War to prescribe such regulations for the use, administration, and navigation of the navigable waters of the United States as in his judgment the public necessity may require for the protection of life and property, or of operations of the United States in channel improvement, covering all matters not specifically delegated by law to some other executive department. Such regulations shall be posted, in conspicuous and appropriate places, for the information of the public; and every person and every corporation which shall violate such regulations shall be deemed guilty of a misdemeanor, and on conviction thereof in any district court of the United States within whose territorial jurisdiction such offense may have been committed, shall be punished by a fine not exceeding \$500, or by imprisonment (in the case of a natural person) not exceeding six months, in the discretion of the court.”

In pursuance of the law above quoted, the following regulations were prescribed to govern the use, administration, and navigation of the Ohio River, Mississippi River above Cairo, Illinois, and their tributaries.

THE REGULATIONS

Sec. 207.300 Ohio River, Mississippi River above Cairo, Ill., and their tributaries; use, administration, and navigation.

(a) *Authority of Lockmasters.*

The lockmaster shall be charged with the immediate control and management of the lock, and of the area set aside as the lock area, including the lock approach channels. He/she shall see that all laws, rules, and regulations for the use of the lock and lock area are duly complied with, to which end he/she is authorized to give all necessary orders and directions in accordance therewith, both to employees of the government and to any and every person

within the limits of the lock and lock area, whether navigating the lock or not. No one shall cause any movement of any vessel, boat, or other floating thing in the lock or approaches except by or under the direction of the lockmaster or his/her assistants. In the event of an emergency, the lockmaster may depart from these regulations as he deems necessary. The lockmasters shall also be charged with the control and management of federally constructed mooring facilities.

(b) *Safety rules for vessels using navigation locks.*

The following safety rules are hereby prescribed for vessels in the locking process, including the act of approaching or departing a lock:

- (1) *Tows with flammable or hazardous cargo barges, loaded or empty.*
 - (i) Stripping barges or transferring cargo is prohibited.
 - (ii) All hatches on barges used to transport flammable or hazardous materials shall be closed and latched, except those barges carrying a gas-free certificate.
 - (iii) Spark-proof protective rubbing fenders (“possums”) shall be used.
- (2) *All vessels.*
 - (i) Leaking vessels may be excluded from locks until they have been repaired to the satisfaction of the lockmaster.
 - (ii) Smoking, open flames, and chipping or other spark-producing activities are prohibited on deck during the locking cycle.
 - (iii) Painting will not be permitted in the lock chamber during the locking cycle.
 - (iv) Tow speeds shall be reduced to a rate of travel such that the tow can be stopped by checking should mechanical difficulties develop. Pilots should check with the individual lockmasters concerning prevailing conditions. It is also recommended that pilots check their ability to reverse their engines prior to beginning an approach. Engines shall not be turned off in the lock until the tow has stopped and been made fast.

- (v) U.S. Coast Guard regulations require all vessels to have on board life saving devices for prevention of drowning. All crew members of vessels required to carry work vests (life jackets) shall wear them during a lockage, except those persons in an area enclosed with a handrail or other device which would reasonably preclude the possibility of falling overboard. All deckhands handling lines during locking procedure shall wear a life jacket. Vessels not required by Coast Guard regulations to have work vests aboard shall have at least the prescribed life saving devices, located for ready access and use if needed. The lockmaster may refuse lockage to any vessel which fails to conform to the above.

(c) *Reporting of navigation incidents.*

In furtherance of increased safety on waterways the following safety rules are hereby prescribed for all navigation interests:

- (1) Any incident resulting in uncontrolled barges shall immediately be reported to the nearest lock. The report shall include information as to the number of loose barges, their cargo, and the time and location where they broke loose. The lockmaster or locks shall be kept informed of the progress being made in bringing the barges under control so that he can initiate whatever actions may be warranted.
- (2) Whenever barges are temporarily moored at other than commercial terminals or established fleeting areas, and their breaking away could endanger a lock, the nearest lock shall be so notified, preferably the downstream lock.
- (3) Sunken or sinking barges shall be reported to the nearest lock both downstream and upstream of the location in order that other traffic passing those points may be advised of the hazards.
- (4) In the event of an oil spill, notify the nearest lock downstream, specifying the time and location of the incident, type of oil, amount of spill, and what recovery or controlling measures are being employed.

- (5) Any other activity on the waterways that could conceivably endanger navigation or a navigation structure shall be reported to the nearest lock.
- (6) Whenever it is necessary to report an incident involving uncontrolled, sunken or sinking barges, the cargo in the barges shall be accurately identified.
- (d) *Precedence at locks.*
- (1) The vessel arriving first at a lock shall normally be first to lock through, but precedence shall be given to vessels belonging to the United States. Licensed commercial passenger vessels operating on a published schedule or regularly operating in the "for hire" trade shall have precedence over cargo tows and like craft. Commercial cargo tows shall have precedence over recreational craft, except as described in paragraph (f) of this section.
- (2) Arrival posts or markers may be established ashore above and/or below the locks. Vessels arriving at or opposite such posts or markers will be considered as having arrived at the locks within the meaning of this paragraph. Precedence may be established visually or by radio communication. The lockmaster may prescribe such departure from the normal order of precedence as in his judgment is warranted to achieve best lock utilization.
- (e) *Unnecessary delay at locks.*
- Masters and pilots must use every precaution to prevent unnecessary delay in entering or leaving locks. Vessels failing to enter locks with reasonable promptness when signaled to do so shall lose their turn. Rearranging or switching of barges in the locks or in approaches is prohibited unless approved or directed by the lockmaster. This is not meant to curtail "jackknifing" or set-overs where normally practiced.
- (f) *Lockage of recreational craft.*
- In order to fully utilize the capacity of the lock, the lockage of recreational craft shall be expedited by locking them through with commercial craft, *provided That both parties agree to joint use of the chamber.* When recreational craft are locked simultaneously with commercial tows, the lockmaster will direct, whenever practicable, that the recreational craft enter the lock and depart while the tow is secured in the lock. Recreational craft will not be locked through with vessels carrying volatile cargoes or other substances likely to emit toxic or explosive vapors. If the lockage of recreational craft cannot be accomplished within the time required for three other lockages, a separate lockage of recreational craft shall be made. Recreational craft operators are advised that many locks have a pull chain located at each end of the lock which signals the lockmaster that lockage is desired. Furthermore, many Mississippi River locks utilize a strobe light

at the lock to signal recreational type vessels that the lock is ready for entry. Such lights are used exclusively to signal recreational craft.

- (g) *Simultaneous lockage of tows with dangerous cargoes.*
- Simultaneous lockage of other tows with tows carrying dangerous cargoes or containing flammable vapors normally will only be permitted when there is agreement between the lockmaster and both vessel masters that the simultaneous lockage can be executed safely. He shall make a separate decision each time such action seems safe and appropriate, provided:
- (1) The first vessel or tow in and the last vessel or tow out are secured before the other enters or leaves.
- (2) Any vessel or tow carrying dangerous cargoes is not leaking.
- (3) All masters involved have agreed to the joint use of the lock chamber.
- (h) *Stations while awaiting a lockage.*
- Vessels awaiting their turn to lock shall remain sufficiently clear of the structure to allow unobstructed departure for the vessel leaving the lock. However, to the extent practicable under the prevailing conditions, vessels and tows shall position themselves so as to minimize approach time when signaled to do so.
- (i) *Stations while awaiting access through navigable pass.*
- When navigable dams are up or are in the process of being raised or lowered, vessels desiring to use the pass shall wait outside the limits of the approach points unless authorized otherwise by the lockmaster.
- (j) *Signals.*
- Signals from vessels shall ordinarily be by whistle; signals from locks to vessels shall be by whistle, another sound device, or visual means. When a whistle is used, long blasts of the whistle shall not exceed 10 seconds and short blasts of the whistle shall not exceed 3 seconds. Where a lock is not provided with a sound or visual signal installation, the lockmaster will indicate by voice or by the wave of a hand when the vessel may enter or leave the lock. Vessels must approach the locks with caution and shall not enter nor leave the lock until signaled to do so by the lockmaster. The following lockage signals are prescribed:
- (1) *Sound signals by means of a whistle.* These signals apply at either a single lock or twin locks.
- (i) Vessels desiring lockage shall on approaching a lock give the following signals at a distance of not more than one mile from the lock:
- (a) If a single lockage only is required: One long blast of the whistle followed by one short blast.
- (b) If a double lockage is required: One long blast of the whistle followed by two short blasts.

- (ii) When the lock is ready for entrance, the lock will give the following signals:
- (a) One long blast of the whistle indicates permission to enter the lock chamber in the case of a single lock or to enter the landward chamber in the case of twin locks.
- (b) Two long blasts of the whistle indicates permission to enter the riverward chamber in the case of twin locks.
- (iii) Permission to leave the locks will be indicated by the following signals given by the lock:
- (a) One short blast of the whistle indicates permission to leave the lock chamber in the case of a single lock or to leave the landward chamber in the case of twin locks.
- (b) Two short blasts of the whistle indicates permission to leave the riverward chamber in the case of twin locks.
- (iv) Four or more short blasts of the lock whistle delivered in rapid succession will be used as a means of attracting attention, to indicate caution, and to signal danger. This signal will be used to attract the attention of the captain and crews of vessels using or approaching the lock or navigating in its vicinity and to indicate that something unusual involving danger or requiring special caution is happening or is about to take place. When this signal is given by the lock, the captains and crews of vessels in the vicinity shall immediately become on the alert to determine the reason for the signal and shall take the necessary steps to cope with the situation.
- (2) *Lock signal lights.* At locks where density of traffic or other local conditions make it advisable, the sound signals from the lock will be supplemented by signal lights. Flashing lights (showing a one-second flash followed by a two-second eclipse) will be located on or near each end of the land wall to control use of a single lock or of the landward lock of double locks. In addition, at double locks, interrupted flashing lights (showing a one-second flash, a one-second eclipse and a one-second flash, followed by a three-second eclipse) will be located on or near each end of the intermediate wall to control use of the riverward lock. Navigation will be governed as follows:
- (i) *Red light.* Lock cannot be made ready immediately. Vessel shall stand clear.
- (ii) *Amber light.* Lock is being made ready. Vessel may approach but under full control.
- (iii) *Green light.* Lock is ready for entrance.
- (iv) *Green and amber.* Lock is ready for entrance but gates cannot be recessed completely. Vessel may enter under full control and with extreme caution.

- (3) *Radio communications.* VHF-FM radios, operating in the FCC authorized Maritime Band, have been installed at all operational locks (except those on the Kentucky River and Lock 3, Green River). Radio contact may be made by any vessel desiring passage. Commercial tows are especially requested to make contact at least one half hour before arrival in order that the pilot may be informed of current river and traffic conditions that may affect the safe passage of his tow. All locks monitor 156.8 MHz (Ch. 16) and 156.65 MHz (Ch. 13) and can work 156.65 MHz (Ch. 13) and 156.7 MHz (Ch. 14) Ch. 16 is the authorized call, reply and distress frequency, and locks are not permitted to work on this frequency except in an emergency involving the risk of immediate loss of life or property. Vessels may call and work Ch. 13, without switching, but are cautioned that vessel to lock traffic must not interrupt or delay Bridge to Bridge traffic which has priority at all times.
- (k) *Rafts.*
Rafts to be locked through shall be moored in such manner as not to obstruct the entrance of the lock, and if to be locked in sections, shall be brought to the lock as directed by the lockmaster. After passing the lock the sections shall be reassembled at such distance beyond the lock as not to interfere with other vessels.
- (l) *Entrance to and exit from locks.* In case two or more boats or tows are to enter for the same lockage, their order of entry shall be determined by the lockmaster. Except as directed by the lockmaster, no boat shall pass another in the lock. In no case will boats be permitted to enter or leave the locks until directed to do so by the lockmaster. The sides of all craft passing through any lock shall be free from projections of any kind which might injure the lock walls. All vessels shall be provided with suitable fenders, and shall be used to protect the lock and guide walls until it has cleared the lock and guide walls.
- (m) *Mooring*
(1) *At locks.*
(i) All vessels when in the locks shall be moored as directed by the lockmaster. Vessels shall be moored with bow and stern lines leading in opposite directions to prevent the vessel from "running" in the lock. All vessels will have one additional line available on the head of the tow for emergency use. The pilothouse shall be attended by qualified personnel during the entire locking procedure. When the vessel is securely moored, the pilot shall not cause movement of the propellers except in emergency or unless directed by the lockmaster. Tying to lock ladders is strictly prohibited.
- (ii) Mooring of unattended or non-propelled vessels or small craft at the upper or lower channel approaches will not be permitted within 1200 feet of the lock.
- (2) *Outside of locks.*
(i) No vessel or other craft shall regularly or permanently moor in any reach of a navigation channel. The approximate centerline of such channels are marked as the sailing line on Corps of Engineers' navigation charts. Nor shall any floating craft, except in an emergency, moor in any narrow or hazardous section of the waterway. Furthermore, all vessels or other craft are prohibited from regularly or permanently mooring in any section of navigable waterways which are congested with commercial facilities or traffic unless it is moored at facilities approved by the Secretary of the Army or his authorized representative. The limits of the congested areas shall be marked on Corps of Engineers' navigation charts. However, the District Engineer may authorize in writing exceptions to any of the above if, in his judgment, such mooring would not adversely affect navigation and anchorage.
(ii) No vessel or other craft shall be moored to railroad tracks, to riverbanks in the vicinity of railroad tracks when such mooring threatens the safety of equipment using such tracks, to telephone poles or power poles, or to bridges or similar structures used by the public.
(iii) Except in case of great emergency, no vessel or craft shall anchor over revetted banks of the river, and no floating plant other than launches and similar small craft shall land against banks protected by revetment except at regular commercial landings. In all cases, every precaution to avoid damage to the revetment works shall be exercised. The construction of log rafts along matted or paved banks or the tying up and landing of log rafts against such banks shall be performed in such a manner as to cause no damage to the mattress work or bank paving. Generally, mattress work extends out into the river 600 feet from the low water line.
(iv) Any vessel utilizing a federally constructed mooring facility (e.g., cells, buoys, anchor rings) at the points designated on the current issue of the Corps' navigation charts shall advise the lockmaster at the nearest lock from that point by the most expeditious means.
- (n) *Draft of vessels.*
No vessel shall attempt to enter a lock unless its draft is at least three inches less than the least depth of water over the guard sills, or over the gate sills if there be no guard sills. Information concerning controlling depth over sills can be obtained from the lockmaster at each lock or by inquiry at the office of the district engineer of the district in which the lock is located.
- (o) *Handling machinery.*
No one but employees of the United States shall move any lock machinery except as directed by the lockmaster. Tampering or meddling with the machinery or other parts of the lock is strictly forbidden.
- (p) *Refuse in locks.*
Placing or discharging refuse of any description into the lock, on lock walls or esplanade, canal or canal bank is prohibited.
- (q) *Damage to locks or other work.*
To avoid damage to plant and structures connected with the construction or repair of locks and dams, vessels passing structures in the process of construction or repair shall reduce their speed and navigate with special caution while in the vicinity of such work. The restrictions and admonitions contained in these regulations shall not affect the liability of the owners and operators of floating craft for any damage to locks or other structures caused by the operation of such craft.
- (r) *Trespass of lock property.*
Trespass on locks or dams or other U.S. property pertaining to the locks or dams is strictly prohibited except in those areas specifically permitted. Parties committing any injury to the locks or dams or to any part thereof will be responsible therefor. Any person committing a willful injury to any U.S. property will be prosecuted. No fishing will be permitted from lock walls, guide walls, or guard walls of any lock or from any dam, except in areas designated and posted by the responsible District Engineer as fishing areas. Personnel from commercial and recreational craft will be allowed on the lock structure for legitimate business reasons; e.g., crew changes, emergency phone calls, etc.
- (s) *Restricted areas at locks and dams.*
All waters immediately above and below each dam, as posted by the respective District Engineers, are hereby designated as restricted areas. No vessel or other floating craft shall enter any such restricted area at any time. The limits of the restricted areas at each dam will be determined by the responsible District Engineer and marked by signs and/or flashing red lights installed in conspicuous and appropriate places.
- (t) [Reserved]
- (u) *Operations during high water and floods in designated vulnerable areas.*

Vessels operating on these waters during periods when river stages exceed the level of "ordinary high water", as designated on Corps of Engineers' navigation charts, shall exercise reasonable care to minimize the effects of their bow waves and propeller washes on river banks; submerged or partially submerged structures or habitations; terrestrial growth such as trees and bushes; and man-made amenities that may be present. Vessels shall operate carefully when passing close to levees and other flood protection works, and shall observe minimum distances from banks which may be prescribed from time to time in Notices to Navigation Interests. Pilots should exercise particular care not to direct propeller wash at river banks, levees, revetments, structures or other appurtenances subject to damage from wave action.

(v) *Navigation lights for use at all locks.*

- (1) At locks at all fixed dams and at locks at all movable dams when the dams are up so that there is no navigable pass through the dam, the following navigation lights will be displayed during hours of darkness:
 - (i) Three green lights visible through an arc of 360 deg. arranged in a vertical line on the upstream end of the river (guard) wall unless the intermediate wall extends farther upstream. In the latter case, the lights will be placed on the upstream end of the intermediate wall.
 - (ii) Two green lights visible through an arc of 360 deg. arranged in a vertical line on the downstream end of the river (guard) wall unless the intermediate wall extends farther downstream. In the latter case, the lights will be placed on the downstream end of the intermediate wall.
 - (iii) A single red light, visible through an arc of 360 deg. on each end (upstream and downstream) of the land (guide) wall.
- (2) At movable dams when the dam has been lowered or partly lowered so that there is an unobstructed navigable pass through the dam, the navigation lights indicated in the following paragraphs will be displayed during hours of darkness until lock walls and weir piers are awash.
 - (i) Three red lights visible through an arc of 360 deg. arranged in a vertical line on the upstream end of the river (guard) wall.
 - (ii) Two red lights visible through an arc of 360 deg. arranged in a vertical line on the downstream end of the river (guard) wall.
 - (iii) A single red light visible through an arc of 360 deg. on each end (upstream and downstream) of the land (guide) wall.
- (3) After lock walls and weir piers are awash they will be marked as prescribed in paragraph (x) of this section.

- (4) If one or more bear traps or weirs are open or partially open, and may cause a set in current conditions at the upper approach to the locks, this fact will be indicated by displaying a white circular disk 5 feet in diameter, on or near the light support on the upstream end of the land (guide) wall during the hours of daylight, and will be indicated during hours of darkness by displaying a white (amber) light vertically under and 5 feet below the red light on the upstream end of the land (guide) wall.
- (5) At Locks No. 1 and 2, Green River, when the locks are not in operation because of high river stages, a single red light visible through an arc of 360 deg. will be displayed on each end (upstream and downstream) of the lock river (guard) wall at which time the lights referred to above will not be visible.

(w) [No longer applicable]

(x) *Buoys at movable dams.*

- (1) Whenever the river (guard) wall of the lock and any portion of the dam are awash, and until covered by a depth of water equal to the project depth, the limits of the navigable pass through the dam will be marked by buoys located at the upstream and downstream ends of the river (guard) wall, and by a single buoy over the end or ends of the portion or portions of the dam adjacent to the navigable pass over which project depth is not available. A red nun-type buoy will be used for such structures located on the left-hand side (facing downstream) of the river and a black can-type buoy for such structures located on the right-hand side. Buoys will be lighted, if practicable.
- (2) Where powerhouses or other substantial structures projecting considerably above the level of the lock wall are located on the river (guard) wall, a single red light located on top of one of these structures may be used instead of river wall buoys prescribed above until these structures are awash, after which they will be marked by a buoy of appropriate type and color (red nun or black can buoy) until covered by a depth of water equal to the project depth. Buoys will be lighted, if practicable.

- (y) *Vessels to carry regulations.* A copy of these regulations shall be kept at all times on board each vessel regularly engaged in navigating the rivers to which these regulations apply. Copies may be obtained from any lock office or District Engineer's office on request. Masters of such vessels are encouraged to have on board copies of the current edition of appropriate navigation charts.

NOTE: These regulations are those in effect 31 July 1975.

ACT OF MARCH 3, 1899
[As Amended Through P.L. 106-580, Dec. 29, 2000]
(Commonly Known as THE "RIVERS AND HARBORS APPROPRIATION ACT OF 1899")
(Sections 15, 16, 19 & 20)

CHAP. 425.—An Act Making appropriations for the construction, repair, and preservation of certain public works on rivers and harbors, and for other purposes.

* * * * *

SECTION 15

That it shall not be lawful to tie up or anchor vessels or other craft in navigable channels in such a manner as to prevent or obstruct the passage of other vessels or craft; or to sink, or permit or cause to be sunk, vessels or other craft in navigable channels; or to float loose timber and logs, or to float what is known as sack rafts of timber and logs in streams or channels actually navigated by steamboats in such manners as to obstruct, impede, or endanger navigation. And whenever a vessel, raft, or other craft is wrecked and sunk in a navigable channel, it shall be the duty of the owner, lessee, or operator of such sunken craft to immediately mark it with a buoy or beacon during the day and a lighted lantern at night, and to maintain such marks until the sunken craft is removed or abandoned, and the neglect or failure of the said owner, lessee, or operator so to do shall be unlawful; and it shall be the duty of the owner, lessee, or operator of such sunken craft to commence the immediate removal of the same, and prosecute such removal diligently, and failure to do so shall be considered as an abandonment of such craft and subject the same to removal by the United States as hereinafter provided for. (33 U.S.C. 409)

SECTION 16

That every person and every corporation that shall violate, or that shall knowingly aid, abet, authorize, or instigate a violation of the provisions of sections 13, 14, 15, 19, and 20 of this Act shall be guilty of a misdemeanor, and on conviction thereof shall be punished by a fine of up to \$25,000 per day, or by imprisonment (in the case of a natural person) for not less than thirty days nor more than one year, or by both such fine and imprisonment, in the discretion of the court; one-half of said fine to be paid to the person or persons giving information which shall lead to conviction. And any and every master, pilot, and engineer, or person or persons acting in such capacity, respectively, on board of any boat or vessel who shall knowingly engage in towing any scow, boat, or vessel loaded with any material specified in section thirteen of this Act to any point or place of deposit or discharge in any harbor or navigable water, elsewhere than within the limits defined and permitted by the Secretary of War, or who shall willfully injure or destroy any work of the United States contemplated in section fourteen of this Act, or who shall willfully obstruct the channel of any waterway in the manner contemplated in section fifteen of this Act, shall be deemed guilty of a violation of this Act, and shall upon conviction be punished as hereinbefore provided in this section, and shall also have his license revoked or suspended for a term to be fixed by the judge before whom tried and convicted. And any boat, vessel, scow, raft, or other craft used or employed in violating any of the provisions of sections 13, 14, 15, 19, and 20 of this Act shall be liable for the pecuniary penalties specified in this section, and in addition thereto for the amount of the damages done by said boat, vessel, scow, raft, or other craft, which latter sum shall be placed to the credit of the appropriation for the improvement of the harbor or waterway in which the damage occurred, and said boat, vessel, scow, raft, or other craft may be proceeded against summarily by way of libel in any district court of the United States having jurisdiction thereof. (33 U.S.C. 411, 412)

SECTION 19

(a) That whenever the navigation of any river, lake, harbor, sound, bay, canal, or other navigable waters of the United States shall be obstructed or endangered by any sunken vessel, boat, water craft, raft, or other similar obstruction, and such obstruction has existed for a longer period than thirty days, or whenever the abandonment of such obstruction can be legally established in a less space of time, the sunken vessel, boat, water craft, raft, or other obstruction shall be subject to be broken up, removed, sold, or otherwise disposed of by the Secretary of War at his discretion, without liability for any damage to the owners of the same: *Provided*, That in his discretion, the Secretary of War may cause reasonable notice of such obstruction of not less than thirty days, unless the legal abandonment of the obstruction can be established in a less time, to be given by publication, addressed "To whom it may concern," in a newspaper published nearest to the locality of the obstruction, requiring the removal thereof: *And provided also*, That the Secretary of War may, in his discretion, at or after the time of giving such notice, cause sealed proposals to be solicited by public advertisement, giving reasonable notice of not less than ten days, for the removal of such obstruction as soon as possible after the expiration of the above specified thirty days' notice, in case it has not in the meantime been so removed, these proposals and contracts, at his discretion, to be conditioned that such vessel, boat, water craft, raft, or other obstruction, and all cargo and property contained therein, shall become the property of the contractor, and the contract shall be awarded to the bidder making the proposition most advantageous to the United States: *Provided*, That such bidder shall give satisfactory security to execute the work: *Provided further*, That any money received from the sale of any such wreck, or from any contractor for the removal of wrecks, under this paragraph shall be covered into the Treasury of the United States.

(b) The owner, lessee, or operator of such vessel, boat, watercraft, raft, or other obstruction as described in this section shall be liable to the United States for the cost of removal or destruction and disposal as described which exceeds the costs recovered under subsection (a). Any amount recovered from the owner, lessee, or operator of such vessel pursuant to this subsection to recover costs in excess of the proceeds from the sale or disposition of such vessel shall be deposited in the general fund of the Treasury of the United States. (33 U.S.C. 414)

SECTION 20

(a) That under emergency, in the case of any vessel, boat, water craft, or raft, or other similar obstruction, sinking or grounding, or being unnecessarily delayed in any Government canal or lock, or in any navigable waters mentioned in section nineteen, in such manner as to stop, seriously interfere with, or specially endanger navigation, in the opinion of the Secretary of War, or any agent of the United States to whom the Secretary may delegate proper authority, the Secretary of War or any such agent shall have the right to take immediate possession of such boat, vessel, or other water craft, or raft, so far as to remove or to destroy it and to clear immediately the canal, lock, or navigable waters aforesaid of the obstruction thereby caused, using his best judgment to prevent any unnecessary injury; and no one shall interfere with or prevent such removal or destruction: *Provided*, That the officer or agent charged with the removal or destruction of an obstruction under this section may in his discretion give notice in writing to the owners of any such obstruction requiring them to remove it: *And provided further*, That the actual expense, including administrative expenses, of removing any such obstruction as aforesaid shall be a charge against such craft and cargo; and if the owners thereof fail or refuse to reimburse the United States for such expense within thirty days after notification, then the officer or agent aforesaid may sell the craft or cargo, or any part thereof that may not have been destroyed in removal, and the proceeds of such sale shall be covered into the Treasury of the United States.

(c) The owner, lessee, or operator of such vessel, boat, watercraft, raft, or other obstruction as described in this section shall be liable to the United States for the actual cost, including administrative costs, of removal or destruction and disposal as described which exceeds the costs recovered under subsection (a). Any amount recovered from the owner, lessee, or operator of such vessel pursuant to this subsection to recover costs in excess of the proceeds from the sale or disposition of such vessel shall be deposited in the general fund of the Treasury of the United States. (33 U.S.C. 415)


Boating & Safety on the Missouri River

This chart contains numerous safety tips and guidelines for boaters and other water recreationalists. Please use caution when boating on the river and keep safety in mind at all times.

When Lewis and Clark traveled the river in 1804 they left no trace of their passage. We hope that all river users will respect the environment and "Leave no trace".

Before putting a boat on the Missouri River you should become familiar with the system of aids to navigation established by the U.S. Coast Guard. These aids to navigation (signs, markers, and buoys) mark a 300' wide by 9' deep navigation channel maintained by the U.S. Army Corps of Engineers.

By constricting the majority of the river's flow between sets of rock dikes located on both sides of the river, the navigation channel generally maintains a minimal depth of 9'. The dikes extend nearly perpendicular into the river and may have a downstream "L-head" on the end. The dikes are often submerged just under the surface of the water and can be a significant hazard to watercraft.




Aids to Navigation




Mile Marker Boards are useful navigation aids that help you locate your position on these navigation charts. Mile markers indicate the distance upstream from the mouth of the river (river mile 0), at the confluence of the Missouri and Mississippi Rivers. The boards are attached to beacons (see below) on the river banks and indicate distances in miles. The U.S. Army Corps of Engineers places additional black and white mile boards on trees or posts located along the banks.


Beacons are permanently fixed to a post or other structure along the bank. Lighted beacons are called lights and unlighted beacons are called day beacons or day boards. Because the navigable channel of the river swings back and forth from bank to bank as the river bends, the beacons indicate where to cross or where to stay to the bank. Beacons are located at the beginning and end of each bend and crossing.



Passing Beacon is found at the start and finish of a bend and indicates that you should stay on that side of the river until you reach a crossing beacon.



Crossing Beacon is found at the start and end of a crossing and indicates that you should cross the river and aim for the crossing beacon on the opposite shore.



Buoys are floating aids attached to the riverbed by concrete sinkers with chain or rope. Buoys are maintained by the U.S. Coast Guard during the navigation season, 1 April through 10 November.

Navigation buoys, looking downstream green "can" buoys mark the right descending channel and red "nun" buoys mark the left descending channel. Keep your boat between the green and red buoys and give them wide berth. Buoys are not always present and may be carried off position by high water, collisions, drift in the riverbed or other causes.

River Hazards

The Missouri River is deep in some areas, but other locations may have rock dikes, sandbars and shallow spots. Snags and floating debris also present hazards that may be difficult to see until you are right on top of them. Varying river levels can expose or submerge hazards within a short period of time.

As you travel the river, look for water areas with boils or ripples. This indicates sandbars, dikes or possible hazards close to the surface. Maps and charts may not necessarily show the location of sandbars because they shift with the flow of the river. At locations where the river narrows, or where there are obstacles in the river, tongues of relative glassy water form inverted "V's" downstream of the obstruction.

Rock dikes are numerous. There is a possibility of submerged dikes that create a hazard for boaters. The location of these dikes are indicated on these navigation charts. Mile markers (white with black numbers) make it easy to track your location. These are placed on the bank you should be favoring. Navigation Markers are provided whenever the channel crosses from one side to another. A rule of thumb is to stay toward the outside of every bend and the dikes should give you no trouble.

Boating and Alcohol

The combination of boating and alcohol can prove to be deadly. Alcohol impairs judgment and reaction time and decreases your body's ability to defend itself from hypothermia.

Alcohol greatly increases the risk of dehydration.

Bring along plenty of drinking water. The rule of thumb is one gallon of water per twenty-four hour period per person.

Planning Your Trip

First time Missouri River boaters should become informed of the hazards and challenges associated with boating in swift current.

When you plan your trip, note the area names and public lands along your route on the map. Then use the information on SHEET L to contact the agency and secure detailed maps, information and regulations.

Boaters should prepare a trip plan and inform another person of their travel plans including their destination and estimated time of arrival.

Take a boat safety course and get a free boat safety check from the Coast Guard Auxiliary or U.S. Power Squadron.

Inspect your boat to make sure you have all of the required boat safety equipment.

Planning Your Trip (cont'd)

Fuel is scarce on the lower Missouri River. Locate fuel sources before you begin your trip and plan accordingly. Upstream boaters should expect a 15-80 percent reduction in speed and corresponding increase in fuel consumption due to the 4-7 mph current of the river.

Swimming

Swimming and tubing on the Missouri is extremely dangerous and is strongly discouraged. A fast river current (normally 4-7 mph) can quickly exhaust even the strongest swimmer. Inner tubes should never be used on the river. There's no way to control them in the current and they pose problems with boats and tugs especially on holidays and weekends when recreational traffic peaks.

Never swim in floodwaters, the main river channel, around structures like wing dikes or around moored barges. Strong hidden currents, drop-offs, and hidden obstacles make these areas extremely hazardous to swimmers. Swimmers and waders should always wear a life jacket.

Equipment

"Life jackets float ... you don't". Life jackets (also referred to as Personal Floatation Devices or PFDs) do save lives and are the most important piece of safety equipment in your boat. Make sure you follow the boating rules for your state regarding life jackets. Be sure they fit snugly to avoid the PFD coming off if you should accidentally fall in the water. Frayed or damaged PFD's should be replaced. Smaller children should wear PFD's made for them. The U.S. Coast Guard label affixed to the PFD will aid in selecting the appropriate type and size.

Boats must be equipped with appropriate emergency equipment (i.e., first aid kit, oars and paddles, anchor, sound device, fire extinguisher, navigation lights, and 100 feet of line or rope).

If your boat capsizes, do not attempt to swim to shore. Stay with the craft until the boat can be safely beached. Remember, hypothermia is a possibility during most of the year. Life jackets help to minimize loss of body heat.

Avoid sunburn, wear a wide brimmed hat, long sleeved shirt, long trousers and use sunscreen. Sunscreen alone is not sufficient for long exposure to the sun.

Always carry a change of clothing in a waterproof container. Dry clothes could save your life by preventing hypothermia if the clothes you are wearing become wet. It does not have to be "cold" for hypothermia to strike.

Respect Private Property

Most land along the lower Missouri is privately owned. You'll see by looking at the green shading on the map that public lands are very limited. Camping should be done only if you know who's land you are on and have the landowners permission.

Be especially careful not to moor to drainage structures or to trees that might damage or imperil private levees.

Boating & Barges

It is not necessary to get off the river because a barge is approaching. You should move toward the off channel shore (the inside of a bend) and be alert for rock dikes which are located there. Move as far away from the barge as possible and position the bow of your boat perpendicular to the wake. Never turn your boat broadside to the wake created by barges and tugs, they can easily swamp a small boat. Remember, barges have the right-of-way.

Pilots of towboats have a blind spot in front of their vessels and it could take a barge and tow up to 1 ½ miles to stop. These barges also create extreme turbulence up to ½ mile behind the tow. The strong wake may lift your boat onto the rocks, dikes or other hazards. Hydraulics generated by barges can suck under objects including smaller craft so it's best to give them a wide berth. Playing games with this kind of vessel can result in serious injury or even death.

Permits are required for regattas and special events on the river. The U.S. Coast Guard (314-269-2332) or Missouri Water Patrol (573-751-3333) should be contacted to obtain these permits.

Stewardship & Endangered Species

Human disturbance can disrupt bird nesting, fish spawning, and other wildlife activities. Avoid dragging your boat across gravel bars or through spawning areas. Launch and land only on designated sites. Keep pets under control.

Minimize campfire impacts and dispose of all waste properly. Pack out all of your trash and pick up litter left by others.

If artifacts or fossils are found, leave them in place and undisturbed. Photograph or sketch rock art, but do not touch.

Check your boat and clean for zebra mussels before taking it from the Missouri River to any other body of water. Signs at launch ramps will provide further instruction.

Mooring & Anchoring

Never set an anchor in the fast flowing river channel. Current can pull you under and debris (e.g. logs) floating under the surface can hook your line and draw you under in an instant. It can also be difficult to unhook the anchor from submerged obstacles you can't see. Be sure you can quickly cut or detach the anchor line on your boat if you need to.

If you do anchor in the river, pick your anchorage carefully out of the channel and current. Remember to use a bowline and keep your bow into the wind or current. This will minimize the risk of being swamped by water coming over the transom or back of the boat. The anchor line should be at least seven times as long as the depth of the water in which the boat is moored.

Never attempt to moor to stationary objects such as dikes and moored barges and never approach these objects from upstream. Swift water flowing over, under, and around these objects creates very strong turbulence and undertow currents that may overturn your boat and pull you under.

When stopping, make every attempt to turn your boat upstream into the current and cut the throttle to an idle. The throttle setting will vary with the speed of the current.

Always land your boat facing upstream and pull in parallel to the riverbank. If you try landing facing downstream or perpendicular to the bank, the current will pivot the boat to position the bow upstream and parallel to the bank. A two-point tie off should be used to keep the prop out of the rock and prevent its contact with the bank.

Camping

Camping at designated camping sites only, is the rule for most public lands. Contact the managing agency for regulations. If you choose to camp elsewhere along the river, you should have permission of the private land owner in advance.

Watch for biting insects, poisonous plants and snakes. They can ruin a trip. Have a first-aid kit on board.

Weather

Monitor the local weather forecast before you begin your journey and throughout your trip. In the Midwest, storms may emerge abruptly. These storms are often accompanied by strong winds that can easily capsize a small craft. Lightning, heavy rain or hail can turn a pleasant trip into disaster. Watch the sky and be aware of your surroundings for signs of inclement weather. Carry foul weather gear for unexpected storms.

High winds create very hazardous conditions and it is best to exit the river as soon as possible. Facing downstream in a crosswind can be dangerous. Always keep your boat straight into or away from the wind (parallel with the wind) as you head toward the shore.

Carry a portable radio or weather radio and tune it to the National Weather Service for up-to-date forecasts.

Beware of travel on a rising river which often results in large quantities of floating debris that can cause serious boat damage.

Emergencies

Emergency numbers for each county are listed on the following sheet, SHEET L, and county boundaries are designated on the charts. The county sheriff's office will contact the proper authorities to deal with the emergency.

File a float plan - let a reliable person know where you are going, when and where you plan on departing and arriving, your route and other pertinent information that will enable someone to find you. We never plan on accidents but they do happen. Filing and adhering to a float plan will help if emergency personnel need to locate you.

Administer first aid to accident victims immediately and then call or send for help.

Boaters are advised to carry a marine radio and cell phone or satellite phone for emergency communication with the local Sheriff's office or other emergency response agencies and be familiar with these phone numbers. Cell coverage may not be 100% in rural areas.

Help Stop Zebra Mussels

The zebra mussel poses a multibillion-dollar threat to North America's industrial, agricultural, and municipal water supplies. First discovered in 1988 in the Great Lakes, this invader has spread throughout the Mississippi and Ohio River basins in just 10 years. Public assistance in reporting zebra mussel sightings at new locations is essential in preventing its spread.

Zebra mussels look like small clams with a yellowish or brownish "D" shaped shell. They usually have alternating dark and light stripes. Zebra mussels are relatively small, with adults ranging from 1/4 to 1 1/2 inches long. Zebra mussels usually grow in clusters. They are the only freshwater mollusk that can firmly attach to objects. They are commonly found on rocks, dock pilings, boat hulls, and water intake pipes.

Zebra mussel juveniles, called veligers, are microscopic and invisible to the naked eye. You can prevent the spread of zebra mussels by routinely decontaminating your boat and equipment by power washing with water heated to 140- degrees Fahrenheit or by allowing everything to completely dry before using in another body of water. Drain water from your motor, live well, bilge and transom wells before leaving the recreation area. Empty bait buckets in land based receptacles and do not take bait from one body of water to another.

If you find a zebra mussel, note the date and precise location where the mussel was found. Take the mussel with you and store in rubbing alcohol. Immediately contact the nearest state wildlife department.

For more information please visit these websites:

www.100thmeridian.org
www.protectyourwaters.net
www.anstaskforce.gov



Emergency Numbers**Missouri County Sheriff's Department**

Andrew County...816-324-4114
 Atchison County...660-744-6308
 Boone County...573-875-1111
 Buchanan County...816-271-5555
 Callaway County...573-642-7291
 Carroll County...660-542-2828
 Chariton County...660-288-3277
 Clay County...816-792-7614
 Cole County...573-634-9160
 Cooper County...660-882-2771
 Franklin County...636-583-2560
 Gasconade County...573-486-3880
 Holt County...660-446-3305
 Howard County...660-248-2477
 Jackson County...816-524-4302
 Lafayette County...660-259-3622
 Moniteau County...573-796-2525
 Montgomery County...573-564-3378
 Osage County...573-897-3107
 Platte County...816-858-2424
 Ray County...816-776-2000
 Saline County...660-886-5511
 St. Charles County...636-949-0809
 St. Louis County...314-615-4724
 Warren County...636-456-4332

Kansas County Sheriff's Department

Atchison County...913-367-8202
 Doniphan County...785-985-3711
 Leavenworth County...913-682-5724
 Wyandotte County...913-573-2861

Nebraska County Sheriff's Department

Nemaha County...402-274-3139
 Otoe County...402-873-6691
 Richardson County...402-245-2479

Illinois County Sheriff's Department

Madison County...618-692-4433
 St. Clair County...618-277-3505

Iowa County Sheriff's Department

Fremont County...712-374-2673

Additional Information Links...

Kansas Department of Wildlife and Parks: www.kdwp.state.ks.us
 Missouri Department of Conservation: www.mdc.mo.gov
 Missouri Department of Natural Resources: www.dnr.mo.gov
 Missouri River Communities Network: www.moriver.org
 Missouri State Parks: www.mostateparks.com
 Missouri Water Patrol: www.mswp.dps.mo.gov
 Nebraska Game and Parks Commission: www.ngpc.state.ne.us
 State of Illinois: www.enjoyillinois.com
 State of Kansas: www.accesskansas.org or www.travelks.com
 State of Missouri: www.missouritourism.com
 State of Nebraska: www.visitnebraska.org or www.state.ne.us
 U.S. Coast Guard: www.uscg.mil
 U.S. Geological Survey Missouri River Information: infolink.cr.usgs.gov
 Zebra Mussels and other Aquatic Nuisance Species: www.anstaskforce.gov



U.S. AIDS TO NAVIGATION SYSTEM on the Western River System AS SEEN ENTERING FROM SEAWARD



PREFERRED CHANNEL TO STARBOARD
TOPMOST BAND GREEN
FI (2+1) G

PREFERRED CHANNEL TO PORT
TOPMOST BAND RED
FI (2+1) R

Diagrams showing various buoy shapes: JG (green top band), JR (red top band), and combinations of green and red bands.

DAYBOARDS HAVING NO LATERAL SIGNIFICANCE
MAY BE LETTERED WHITE LIGHT ONLY

NB

MOORING BUOY
WHITE WITH BLUE BAND
MAY SHOW WHITE REFLECTOR OR LIGHT

PORT SIDE OR RIGHT DESCENDING BANK
GREEN OR WHITE LIGHTS

STARBOARD SIDE OR LEFT DESCENDING BANK
RED OR WHITE LIGHTS

FLASHING ISO IS0

FLASHING (2) ISO IS0

Diagrams showing various buoys: LIGHT, LIGHTED BUOY, CAN, LIGHT, LIGHTED BUOY, NUN, PASSING DAYBEACON, CROSSING DAYBEACON.

Labels: SG, CNG, TR, CNR.

MILE BOARD 176.9, MILE BOARD 123.5

TYPICAL INFORMATION AND REGULATORY MARKS
INFORMATION AND REGULATORY MARKERS
WHEN LIGHTED, INFORMATION AND REGULATORY MARKS
MAY DISPLAY ANY LIGHT RHYTHM EXCEPT QUICK FLASHING, Mo(a) AND FLASHING (2)

NW WHITE LIGHT ONLY

Diagrams showing regulatory marks: SWIM AREA, BOAT EXCLUSION AREA, ROCK, DANGER, CONTROLLED AREA, SLOW NO WAKE.

Diagrams showing information buoys: MULLET LAKE, BLACK RIVER, INFORMATION, BUOY USED TO DISPLAY REGULATORY MARKERS, MAY SHOW WHITE LIGHT MAY BE LETTERED.

STATE WATERS

Diagrams showing obstruction buoys: 3, 2.

INLAND (STATE) WATERS OBSTRUCTION MARK
MAY SHOW WHITE REFLECTOR OR QUICK FLASHING WHITE LIGHT

Diagrams showing black-striped white buoys.

Used to indicate an obstruction to navigation, extends from the nearest shore to the buoy. This means "do not pass between the buoy and the nearest shore." This aid is replacing the red and white striped buoy within the USWMS, but cannot be used until all red and white striped buoys on a waterway have been replaced.


SPECIAL MARKS - MAY BE LETTERED

Diagrams showing special marks: UNLIGHTED, LIGHTED, NY, B.

SHAPE: OPTIONAL—BUT SELECTED TO BE APPROPRIATE FOR THE POSITION OF THE MARK IN RELATION TO THE NAVIGABLE WATERWAY AND THE DIRECTION OF BUOYAGE.

YELLOW LIGHT ONLY
FIXED FLASHING

<p>BRIDGES/OVERHEAD FEATURES</p> <p>Bridge</p> <p>Pier Support</p> <p>Cable-Overhead</p> <p>Pipeline-Overhead</p>	<p>COMMERCIAL</p> <p>Dock/Pier</p> <p>Conveyor</p> <p>Mooring Facility</p> <p>Dolphin</p>	<p>HYDRAULIC STRUCTURES</p> <p>Flow Control Structures</p> <p>Levee/ Flood Wall</p>	<p>NAVIGATIONAL AIDS</p> <p>River Mile</p> <p>Light- Green, Private</p> <p>Light- Red, Private</p> <p>Light- White, Private</p> <p>Light- Green</p> <p>Light- Red</p> <p>Light- White</p> <p>Daymark- NG Nun Buoy Green</p> <p>Daymark- NR Nun Buoy Red</p> <p>Daymark- SG Square Daymark Junction Aid</p> <p>Daymark- TR Triangle Daymark Red</p>	<p>TRANSPORTATION</p> <p>Railroad</p> <p>Road</p> <p>Sailing Line Primary</p> <p>Flow Arrow</p> <p>Pedestrian Trails</p> <p>Airport</p> <p>Authorized Channel Area</p>
<p>SUBMERGED CROSSING</p> <p>Cable-Submerged</p> <p>Pipeline-Submerged</p>	<p>SMALL CRAFT</p> <p>Boat Ramp</p> <p>Fuel Location</p>	<p>HYDRAULICS</p> <p>Gauge - USGS</p>		<p>Highway Marker Labels</p> <p>Interstate Highway</p> <p>Interstate Business Loop</p> <p>U.S. Route Highway</p> <p>State Route Highway</p>
<p>OBSTRUCTIONS</p> <p>Marine Obstruction</p> <p>Wreck</p> <p>Hazard Area</p>	<p>CULTURAL</p> <p>Coast Guard Station</p> <p>USACE Building</p> <p>Tower</p> <p>Grid Line</p> <p>County Boundary</p> <p>State Boundary</p>	<p>HYDROLOGY</p> <p>Match Line</p> <p>River/ Stream</p> <p>Lakes</p> <p>Rivers</p>		
<p>UTILITY</p> <p>Water Intake</p> <p>Water Outfall</p>	<p>Built Up Areas</p> <p>Casino Boats</p> <p>Land- Public Land</p>	<p>TOPOGRAPHY</p> <p>Bedrock Outcrop</p> <p>Land</p>		



* Clearance above 2010 CRP Elevation is NAVD88

CHART NO.	RIVER MILE	FEATURES / LOCALITY
1	497.5 - 502.6	Rulo NE
2	492.0 - 497.6	Big Nemaha River
3	486.8 - 492.0	White Cloud KS
4	481.5 - 486.8	Iowa Point Bend
5	474.5 - 481.5	Wolf Creek Bend
6	469.9 - 475.3	Wolf Creek Quarry Dock
7	465.2 - 471.1	Charleston Bend
8	459.8 - 465.5	Nodaway Island
9	453.6 - 460.1	Worthwine Island
10	448.7 - 453.7	St. Joseph MO
11	443.1 - 448.8	Elwood KS
12	437.7 - 443.9	Palermo Bend
13	432.2 - 437.8	Scholz Quarry Dock
14	427.0 - 432.3	Doniphan Bend
15	420.9 - 427.1	Atchison KS
16	416.1 - 421.0	Bean Lake Bend
17	410.9 - 416.0	Oak Mills Quarry Dock
18	405.6 - 410.9	Iatan Bend, Middle
19	399.7 - 407.0	Weston MO
20	395.2 - 400.6	Leavenworth KS
21	390.2 - 395.2	Lansing KS
22	383.9 - 390.3	Smoot Grain Co. Dock
23	379.3 - 384.7	Parkville MO
24	373.1 - 379.7	Kansas City KS
25	367.2 - 373.6	North Kansas City MO
26	362.4 - 369.9	Kansas City MO
27	357.5 - 363.6	River Front Park, Kansas City MO
28	353.0 - 359.2	Sugar Creek MO
29	348.4 - 353.4	River Bend MO
30	342.7 - 348.4	Missouri City MO
31	337.9 - 343.0	Little Blue River
32	332.5 - 337.8	Sibley MO
33	326.6 - 332.5	Napoleon MO
34	321.0 - 326.8	Wellington MO
35	315.6 - 321.0	Lexington MO
36	310.5 - 315.6	Crooked River
37	305.6 - 310.4	Tabo Bend
38	300.1 - 305.6	Baltimore Bend
39	294.4 - 300.2	Baltimore Island Chute
40	288.8 - 295.0	Waverly MO
41	283.6 - 289.7	Bowdry Drain
42	276.9 - 283.9	Cranberry Bend
43	270.8 - 277.0	Malta Bend
44	265.2 - 272.1	Grand Pass
45	260.1 - 265.2	Miami MO
46	253.2 - 260.1	Dewitt MO
47	248.4 - 253.9	Grand River

CHART NO.	RIVER MILE	FEATURES / LOCALITY
48	243.4 - 248.5	Franklin Woods Quarry and Dock
49	238.7 - 243.5	Chariton River
50	233.2 - 238.8	Gilliam Bend
51	224.7 - 233.5	Glasgow MO
52	220.1 - 225.1	Richland Creek
53	213.1 - 220.6	Lisbon Chute
54	207.4 - 213.3	Arrow Rock MO
55	202.5 - 207.6	Lamine River
56	197.8 - 202.5	Lamine River Bend
57	192.7 - 197.7	Boonville MO
58	188.0 - 192.7	Franklin Island Reach
59	182.6 - 188.0	Rocheport MO
60	177.5 - 182.8	Hunts Quarry and Dock
61	172.9 - 177.6	Lupus MO
62	166.0 - 173.3	Perche Creek
63	161.1 - 168.0	Sandy Hook Quarry Dock
64	154.8 - 161.7	Marion Quarry Dock
65	150.3 - 155.2	Busch Landing
66	144.4 - 150.3	Cedar Creek
67	139.7 - 144.4	Jefferson City MO
68	135.0 - 139.7	Moreau River
69	130.1 - 135.0	Osage River
70	125.0 - 130.1	Loose Creek
71	120.1 - 125.0	St. Auberts Island
72	114.9 - 120.1	Chamois MO
73	110.1 - 114.9	Tate Island
74	105.0 - 110.1	Boatright Chute
75	100.0 - 105.0	Gasconade River
76	95.3 - 100.0	Hermann MO
77	89.8 - 95.3	Little Berger Creek
78	85.1 - 89.8	Berheimer Bend
79	79.6 - 85.1	New Haven MO
80	74.3 - 79.6	Boeuf Creek
81	68.9 - 74.4	St. John's Creek
82	64.1 - 68.8	Washington MO
83	59.2 - 64.1	Boles Bend
84	54.4 - 59.2	Labadie Creek
85	48.9 - 54.3	Wildwood MO
86	43.7 - 49.2	Howell Island
87	38.3 - 43.7	Chesterfield MO
88	32.4 - 38.5	Maryland Heights MO
89	27.3 - 32.4	St. Charles MO
90	21.2 - 27.2	Bridgeton MO
91	16.2 - 21.8	Florissant MO
92	9.9 - 16.5	Pelican Island
93	5.1 - 9.9	Coldwater Creek
94	0.0 - 5.2	St. Louis MO

CHART NO.	RIVER MILE	FEATURE
2	497.8	Rulo Park
3	488.1	White Cloud
5	477.0	Payne Landing
8	462.2	Nodaway Island
10	450.4	French Bottom
11	447.8	Elwood Access
13	437.2	Jentell Brees
15	422.9	Independence Park
20	397.5	Riverfront Park
26	367.5	Kaw Point
27	363.1	KC Riverfront Park
29	352.6	La Benite
31	341.2	Cooley Lake
32	337.2	Fort Osage Park
33	328.6	Corps of Engineers (Open 7:30 to 4:00 weekdays)
35	316.4	Lexington Riverfront Park
40	293.1	Waverly Access
45	262.8	Miami
49	239.1	Dalton Bottoms
51	226.1	Stump Island
57	195.2	Franklin Island
60	179.6	Katfish Katy's
62	170.5	Providence Access Ramp
62	170.2	Cooper's Landing (Fee)
64	159.8	Hartsburg
64	158.0	Marion
67	144.0	Noren
68	138.4	Moreau 50
69	130.0	Bonnots Mill
71	124.7	Mokane
72	117.9	Chamois
73	114.2	Portland Access
75	104.3	Gasconade Park
76	97.7	Hermann Riverfront Park
79	81.4	New Haven
82	68.3	Washington City
84	56.3	Klondike Access
86	48.6	Weldon Spring
89	29.0	Frontier Park
89	27.5	Blanchette Landing
92	10.4	Souix Passage Park
94	3.6	Columbia Bottom
94	0.0	Lewis and Clark Park Ramp






INDEX CHART NO. 1

INDEX CHART NO. 3







REVISED FEB 2014





CHART NO. 1
River Mile 497.5 to 502.6



① **Burlington Northern Railroad Bridge**

River Mile: **498.1**

CLEARANCES: Horizontal, channel spans, 365.0 feet;
vertical, 71.2 feet above zero on W.B. gage at this mile.

CRP Stage at Rulo, Ne: 9.2

CRP Elevation: 846.7

CRP Clearance: 62.7

② **New Rulo Highway Bridge**


River Mile: **498**

CLEARANCES: Horizontal 400 feet;
vertical 52.08 feet above 2% flowline elevation of 856.3 feet.

CRP Stage at Rulo, Ne: 9.2

CRP Elevation: 846.7

CRP Clearance: 62.7





REVISED FEB 2014





CHART NO. 2
River Mile 492 to 497.6





REVISED FEB 2014






CHART NO. 4
River Mile 481.5 to 486.8





REVISED FEB 2014






CHART NO. 6
River Mile 469.9 to 475.3





REVISED FEB 2014






CHART NO. 8

River Mile 459.8 to 465.5





REVISED FEB 2014




CHART NO. 10

River Mile 448.7 to 453.7



REVISED FEB 2014


SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 11

River Mile 443.1 to 448.8



① **Union Pacific Railroad Drawbridge**

River Mile: **448.2**

CLEARANCES: Horizontal, two draw openings, each 200.0 feet; vertical, closed, 31.5 feet above zero on gage at this bridge. CALL SIGN: KTD 403, channels 14 and 16.

CRP Stage at St. Joseph, Mo: 8.5

CRP Elevation: 796.985

CRP Clearance: 23.915

② **Missouri Route 36 Bridge**


River Mile: **447.9**

CLEARANCES: Horizontal, 415.5 feet; vertical, 69.7 feet above gage at St. Joseph.

CRP Stage at St. Joseph, Mo: 8.5

CRP Elevation: 796.971

CRP Clearance: 64.629







REVISED FEB 2014





CHART NO. 13

River Mile 432.2 to 437.8





REVISED FEB 2014





CHART NO. 15

River Mile 420.9 to 427.1



① **Atchison Railroad Drawbridge**


River Mile: **422.6**
 CLEARANCES: Horizontal, left descending drawspan, 155.0 feet, right descending drawspan, 156.5 feet; vertical, closed, 37.5 feet above zero on this gage. CALL SIGN: KTD 426, channels 14 and 16.



CRP Elevation: 774.108
 CRP Clearance: 22.092


② **Amelia Earhart Memorial Bridge**

River Mile: **422.45**
 CLEARANCES: Horizontal 410.0 feet; vertical, 52 feet above 2% flowline elevation of 784 feet.

CRP Elevation: 773.92
 CRP Clearance: 67.38









REVISED FEB 2014





CHART NO. 18

River Mile 405.6 to 410.9



REVISED FEB 2014


SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 19

River Mile 399.7 to 407



REVISED FEB 2014





CHART NO. 20
River Mile 395.2 to 400.6




① **Leavenworth Highway Bridge**


River Mile: **397.6**


CLEARANCES: Horizontal, both channel span, 400.0 feet;
vertical, 71.2 feet above zero on gage at Railway Bridge.

CRP Elevation: 748.578

CRP Clearance: 68.122







REVISED FEB 2014





CHART NO. 23

River Mile 379.3 to 384.7

CHANNEL SPAN



① I-435 Highway Bridge


River Mile: 383.3

CLEARANCES: Horizontal, 415.0 feet;

vertical, 84.39 feet for mid-365 feet of channel span, above zero on Kansas City W.B. gage at mile 366.1.

CRP Elevation: 732.538

CRP Clearance: 73.262



REVISED FEB 2014





CHART NO. 24

River Mile 373.1 to 379.7




① **I-635 Highway Bridge**

River Mile: **374.1**

CLEARANCES: Horizontal, 412.0 feet;
vertical, 73.9 feet above zero on Kansas City W.B. gage at mile 366.1.

CRP Elevation: 722.872

CRP Clearance: 80.328



REVISED FEB 2014





CHART NO. 25

River Mile 367.2 to 373.6



① **Fairfax Dual Bridge**


River Mile: **372.6**

CLEARANCES: Horizontal, channel spans, left, 463.0 feet, right, 406.0 feet; vertical, 73.0 feet above zero on W.B. Gage at Kansas City.

CRP Stage at Kansas City, Mo: 10

CRP Elevation: 721.703

CRP Clearance: 74.597



REVISED FEB 2014





CHART NO. 26

River Mile 362.4 to 369.9




① **Broadway Avenue Highway Bridge**

River Mile: **366.2**

CLEARANCES: Horizontal, channel span, 500.0 feet;
vertical, 86.2 feet above zero on W.B. gage at Kansas City.

CRP Stage at Kansas City, Mo: 10
CRP Elevation: 716.7
CRP Clearance: 88.7



② **Hannibal Railroad Drawbridge (swing)**

River Mile: **366.1**

CLEARANCES: Horizontal, two draw openings, each 200.0 feet;
vertical, closed, 56.0 feet above zero on W.B. gage at this bridge (Kansas City Gage).
CALL SIGN: KQU 500, channels 14 and 16.

CRP Stage at Kansas City, Mo: 10
CRP Elevation: 716.622
CRP Clearance: 48.078


③ **A.S.B. Highway and Railroad Drawbridge**

River Mile: **365.6**

CLEARANCES: Horizontal, channel span, 395.0 feet; vertical, lift up, 98.8 feet,
lift down, 49.7 feet above zero on Kansas City gage.

Contact Hannibal Railroad Bridge on channels 14 or 16 to open A.S.B. Bridge.

CRP Stage at Kansas City, Mo: 10
CRP Elevation: 716.29
CRP Clearance: 39.81





④ **Heart of America Bridge**

River Mile: **365.5**

CLEARANCES: Horizontal, 350.0 feet;
vertical, 52.0 feet above 2% flowline elevation 733.1 feet MSL.

CRP Stage at Kansas City, Mo: 10
CRP Elevation: 716.224
CRP Clearance: 76.176





⑤ **Christopher S. Bond Bridge**


River Mile: **364.8**


CLEARANCES; Horizontal, channel span, 454.0 feet, vertical, 79.5 feet, above zero on W.B. gauge at Kansas City.

CRP Stage at Kansas City, Mo: 10

CRP Elevation: 715.76

CRP Clearance: 72.74





① **Chouteau Bridge**

River Mile: **362.3**
 CLEARANCES: Horizontal, 423.8 feet;
 vertical, 52.9 feet at 2 percent flowline, 76.7 feet at zero on the Kansas City Gauge.

CRP Stage at Kansas City, Mo: 10
 CRP Elevation: 714.1
 CRP Clearance: 70.3

② **I-435 Bridge**


River Mile: **360.3**
 CLEARANCES (Main span): Horizontal, 400.0 feet; vertical, 74.8 feet for mid-300.0 feet of span.
 CLEARANCES (Auxiliary span): Horizontal, 300.0 feet; vertical, 73.6 feet for mid-200.0 feet of span.
 Clearances all above zero on Kansas City W.B. gage.


CRP Stage at Kansas City, Mo: 10
 CRP Elevation: 712.77
 CRP Clearance: 70.43


③ **Harry S Truman Railroad Drawbridge**

River Mile: **359.3**
 CLEARANCES: Horizontal, 403.0 feet; vertical, open, 84.7 feet, closed, 51.3 feet,
 above zero on W.B. gage at Kansas City.
 CALL SIGN: KVV 575, channels 13 and 16.

CRP Stage at Kansas City, Mo: 10
 CRP Elevation: 712.107
 CRP Clearance: 41.293







REVISED FEB 2014





CHART NO. 29


River Mile 348.4 to 353.4





① Liberty Bend Bridge


River Mile: **352.7**
CLEARANCES: Horizontal, 407.0 feet;
vertical, 70.6 feet above zero on gage at this bridge.

CRP Elevation: 707.742
CRP Clearance: 70.558










① **Atchison Topeka and Santa Fe Railroad Bridge**

River Mile: **336.2**

CLEARANCES: Horizontal, channel spans, 383.0 feet;
vertical, 88.5 feet above zero on W.B. gage at this mile.


CRP Elevation: 694.702


CRP Clearance: 78.998




Fire Creek Daybeacon

US Army Corps of Engineers
Corps of Engineers Ramp
(Open 7:30 to 4:00 weekdays)







REVISED FEB 2014





CHART NO. 35

River Mile 315.6 to 321







① **Lexington Bridge**



River Mile: **314.9**


CLEARANCES: Horizontal, 465.3 feet;
vertical, 48.8 feet above 2% flowline elevation 686.0 feet.



CRP Elevation: 675.416


CRP Clearance: 67.684











① **Waverly Bridge**

River Mile: **293.2**

CLEARANCES: Horizontal, channel spans, 400.0 feet;
vertical, right span, 73.0 feet, left span, 57.6 feet, above zero on W.B. gauge at this bridge.

CRP Stage at Waverly, Mo: 11.1

CRP Elevation: 657.228

CRP Clearance: 65.372



REVISED FEB 2014




CHART NO. 41
River Mile 283.6 to 289.7





REVISED FEB 2014




CHART NO. 43

River Mile 270.8 to 277



REVISED FEB 2014



SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 44

River Mile 265.2 to 272.1





① **Miami Bridge**

River Mile: **262.6**


CLEARANCES: Horizontal, right span, 404.0 feet;
vertical, right span, 78.8 feet above zero on gage at this bridge.

CRP Elevation: 629.828

CRP Clearance: 73.472







REVISED FEB 2014








CHART NO. 48

River Mile 243.4 to 248.5







REVISED FEB 2014


SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 51

River Mile 224.7 to 233.5



① Glasgow Railroad Bridge


River Mile: **226.31**
CLEARANCES: Horizontal, center main channel span, 328.0 feet, left span, 170.0 feet, right span, 298.0 feet; vertical, 74.4 feet above zero on W.B. gage at this mile.


CRP Stage at Glasgow, Mo: 12.8
CRP Elevation: 599.295
CRP Clearance: 62.305


② Glasgow Highway Bridge


River Mile: **226.3**
CLEARANCES: Horizontal, center main channel span, 330.0 feet, left span, 170.0 feet, right span, 302.0 feet; vertical, 78.8 feet above zero on W.B. at this mile.


CRP Stage at Glasgow, Mo: 12.8
CRP Elevation: 599.295
CRP Clearance: 66.105











REVISED FEB 2014






CHART NO. 55
River Mile 202.5 to 207.6





REVISED FEB 2014





CHART NO. 57

River Mile 192.7 to 197.7



① **M-K-T Railroad Drawbridge**

River Mile: **197.1**

CLEARANCES: Horizontal, channel spans, 400.0 feet; vertical, open, 75.3 feet, closed, 45.3 feet above zero on W.B. gage at this bridge. No radiotelephone. Bridge maintained in open position.

CRP Stage at Boonville, Mo: 8.1

CRP Elevation: 573.595

CRP Clearance: 67.105

② **Boonville Highway Bridge**


River Mile: **196.6**


CLEARANCES: Horizontal, both channel spans 417.0 feet; vertical clearance left span 59.5 feet above 2 percent flowline elevation 587.5 feet m.s.l., vertical clearance right span 59.9 feet above 2 percent flowline elevation.

CRP Stage at Boonville, Mo: 8.1

CRP Elevation: 573.217

CRP Clearance: 76.183





REVISED FEB 2014






CHART NO. 58

River Mile 188 to 192.7






① **Rocheport Highway Bridge**

River Mile: **185**


CLEARANCES: Horizontal, both spans, 533.0 feet;
vertical, 73.0 feet above zero on W.B. gage at Boonville.

CRP Elevation: 564.538

CRP Clearance: 67.662







REVISED FEB 2014


SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 62

River Mile 166 to 173.3



REVISED FEB 2014









CHART NO. 63


River Mile 161.1 to 168











① **Jefferson City Dual Bridge**


River Mile: **143.9**

CLEARANCES: Horizontal, both bridges, right span, 400.0 feet; vertical, both bridges, right span, 86.4 feet above zero on W.B. gage at this bridge.

CRP Stage at Jefferson City, Mo: 8.2

CRP Elevation: 528.465

CRP Clearance: 78.135



REVISED FEB 2014






CHART NO. 68

River Mile 135 to 139.7





REVISED FEB 2014






CHART NO. 70

River Mile 125 to 130.1





REVISED FEB 2014







CHART NO. 72
River Mile 114.9 to 120.1







REVISED FEB 2014







CHART NO. 75
River Mile 100 to 105





① **Christopher S. Bond Bridge**


River Mile: **97.9**


CLEARANCES: Horizontal, channel spans, 452.0 feet;
vertical, 52.0 feet above 2% flowline elevation 505.2 feet MSL.

CRP Stage at Hermann, Mo: 7.1

CRP Elevation: 488.608

CRP Clearance: 70.892







REVISED FEB 2014





CHART NO. 79
River Mile 79.6 to 85.1



REVISED FEB 2014


SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



CHART NO. 80

River Mile 74.3 to 79.6



REVISED FEB 2014






CHART NO. 81

River Mile 68.9 to 74.4

CHART NO. 80

CHART NO. 82





① **Washington Bridge**


River Mile: **67.6**


CLEARANCES: Horizontal, left span, 462.0 feet, right span, 463.0 feet;
vertical, left span, 74.7 feet, right span, 83.1 feet above zero on W.B. gage at this bridge.

CRP Stage at Washington, Mo: 3.3

CRP Elevation: 460.603

CRP Clearance: 83.697





Labaddie Daybeacon

Schulenberg Daybeacon

Augusto Bluff Daybeacon


Matson Daybeacon

CHART NO. 83


CHART NO. 85


CHART NO. 84

REVISED FEB 2014



River Mile 54.4 to 59.2





REVISED FEB 2014





CHART NO. 86

River Mile 43.7 to 49.2




① **Daniel Boone Bridge (Dual)**

River Mile: **44**

CLEARANCES: Horizontal, 447.0 feet;
vertical, 52.0 feet above 2% flowline elevation 455.2 feet MSL.

CRP Elevation: 438.139

CRP Clearance: 76.861



REVISED FEB 2014






CHART NO. 87

River Mile 38.3 to 43.7








① **Veterans Memorial Bridge**

River Mile: **32.6**
CLEARANCES: Horizontal, 602.0 feet;
vertical, 62.2 feet above 2% flowline elevation 444.7 feet.

CRP Elevation: 426.401
CRP Clearance: 83.499







① **I-70 Dual Bridges**


River Mile: **29.6**

CLEARANCES: Horizontal, 417.0 feet, both bridges;
vertical, 81.5 feet above zero on St. Charles W.B. gage at mile 28.2.

CRP Elevation: 424.602

CRP Clearance: 74.998





① **Wabash Railroad Bridge**


River Mile: **27.1**
 CLEARANCES: Horizontal, center span, 600.0 feet, right span, 408.0 feet; vertical, 81.0 feet above zero on W.B. gage at St. Charles.


CRP Stage at St. Charles, Mo: 10.1
 CRP Elevation: 422.954
 CRP Clearance: 71.246

② **Discovery Bridge**

River Mile: **27**
 CLEARANCES: Horizontal 617.0 feet; vertical, 70.4 feet above standard low water.

CRP Stage at St. Charles, Mo: 10.1
 CRP Elevation: 422.879
 CRP Clearance: 70.721





Charbonnier Daybeacon

Black Walnut Daybeacon

Mullanphy Daybeacon

Sunset Park

Florissant

Consolidated North County Levee

Mullanphy Bend

St. Charles County

St. Louis County

Missouri

21

20

19


18

17

Leuke Hauling

CHART NO. 90

CHART NO. 92



REVISED FEB 2014






CHART NO. 92

River Mile 9.9 to 16.5





① **Burlington Northern Bridge**


River Mile: **8.2**
CLEARANCES: Horizontal, channel spans, 430.0 feet;
vertical, 76.8 feet above zero at Lewis Bridge.


CRP Elevation: 407.236
CRP Clearance: 68.554

② **Lewis Bridge (U.S. Hwy 67)**

River Mile: **8.1**
CLEARANCES: Horizontal, 431.0 feet;
vertical, 55.5 feet above 2% flowline elevation 422.2 feet.

CRP Elevation: 407.152
CRP Clearance: 77.648





REVISED FEB 2014

SCALE : 1" = 2000'

1,000 0 1,000 2,000 3,000 Feet



Extent of Lower Missouri River Navigation Chart Coverage. See Mississippi River Navigation Charts for Continuation.

CHART NO. 94

River Mile 0 to 5.2

Bridge Name	River Mile	Light List Vertical Clearance	Light List Horizontal Clearance	Light List Horizontal Clearance Left Descending Bank	Light List Horizontal Clearance Right Descending Bank	Light List Vertical Lift	2 Percent Flowline Clearance	Gauge Clearance	Gauge Reference	Low Steel Elevation	Standard Low Water Clearance	Reference Elevation
Lewis Bridge (U.S. Hwy 67)	8.2	55.50	431.0			NA	55.5			484.6**		422.2
Burlington Northern Bridge	8.2	76.80	430.0			NA		76.8	Zero at Lewis Bridge	475.6**		413.6
Discovery Bridge	27.0	70.40	617.0			NA				493.7**	70.4	
Wabash Railroad Bridge	27.1	81.00	600.0			NA		81.0	Zero at St. Charles Westbound	494.3**		413.6
I-70 Dual Bridges	29.6	81.50	417.0			NA		81.5	Zero at St. Charles Westbound	499.7**		413.6
Veterans Memorial Bridge	32.6	62.20	602.0			NA	62.2			510.0**		444.7
Daniel Boone Dual Bridge	43.9	52.00	447.0			NA	52.0			515.2**		455.2
Washington Bridge	67.5	74.70		462.0	463.0	NA		74.7	Zero at this bridge (Washington Bridge)	544.5**		457.2
Hermann Highway Bridge	97.9	52.00	452.0			NA	52.0			559.4**		505.2
Jefferson City Dual Bridge	143.9	86.40		400.0	400.0	NA		86.4	Zero at this bridge (Jefferson Bridge)	606.5**		520.1
Rocheport Highway Bridge	185.0	73.00	533.0			NA		73.0	Zero at Boonville Bridge	632.1**		565.4
Boonville Highway Bridge	196.6	59.50		417.0	417.0	NA	59.5			649.3**		587.5
M-K-T Railroad Drawbridge	197.1	45.30		400.0	400.0	20.0		45.3	Zero at MKT RR Bridge (Boonville Gauge)	640.6**		565.4
Glasgow Railroad Bridge	226.3	74.40	328.0	170.0	298.0	NA		74.4	Zero at Gauge at this mile (Glasgow Gauge)	665.3**		586.5
Glasgow Highway Bridge	226.3	78.80	330.0	170.0	302.0	NA		78.8	Zero at Gauge at this mile (Glasgow Gauge)	665.3**		586.5
Miami Bridge	262.6	78.80			404.0	NA		78.8	Zero at Miami Bridge	703.2**		621.4
Waverly Bridge	293.2	73.00	400.0			NA		73.0	Zero at this bridge (Waverly Bridge)	722.3**		
Lexington Bridge	314.9	48.80	465.3			NA	48.8			742.8**		686.0
Atchison Topeka and Santa Fe Railroad Bridge	336.2	88.50	383.0			NA		88.5	Zero at Gauge at this mile	773.4**		683.9
Liberty Bend Bridge	352.7	70.60	407.0			NA		70.6	Zero at Liberty Bridge	778.0**		
Harry S Truman Railroad Drawbridge	359.4	51.30	403.0			33.4		51.3	Zero at Kansas City	753.1**		706.4
I-435 Bridge	360.3	74.80	400.0		300.0	NA		74.8	Zero at Kansas City	781.1**		706.4
Chouteau Bridge	362.4	76.70	423.8			NA	52.9	76.7	Zero at Kansas City	784.1**		706.4
Christopher S. Bond Bridge	364.8	79.50	454.0			NA		79.5	Zero at Kansas City	788.2**		706.4
Heart of America Bridge	365.5	52.00	350.0			NA	52.0			787.2**		733.1
A.S.B. Highway and Railroad Drawbridge	365.6	49.70	395.0			49.1		49.7	Zero at Kansas City	755.8**		706.4
Hannibal Railroad Drawbridge (Swing)	366.1	56.00		200.0	200.0	NA		56.0	Zero at this bridge (Kansas City)	764.4**		706.4
Broadway Avenue Highway Bridge	366.2	86.20	500.0			NA		86.2	Zero at Kansas City	805.1**		706.4
Fairfax Dual Bridge	372.6	73.00		463.0	406.0	NA		73.0	Zero at Kansas City	796.0**		706.4
I-635 Highway Bridge	374.1	73.90	412.0			NA		73.9	Zero at Kansas City	802.9**		706.4
I-435 Highway Bridge	383.3	84.39	415.0			NA		84.4	Zero at Kansas City	805.5**		706.4
Leavenworth Highway Bridge	397.6	71.20	400.0			NA		71.2	Zero at Railway Bridge	816.4**		742.2
Amelia Earhart Memorial Bridge	422.5	52.0*	410.0*			NA	52.0			839.82*		784.0
Atchison Railroad Drawbridge	422.6	37.50		155.0	156.5	NA		37.5	Zero at this bridge (Atchison)	795.9**		762.2
Missouri Route 36 Bridge	447.9	69.70	415.5			NA		69.7	Zero at St. Joseph	861.3**		788.2
Union Pacific Railroad Drawbridge (closed)	448.2	31.50		200.0		NA		31.5	Zero at this bridge (St. Joseph)	820.6**		788.2
Rulo Highway Bridge	498.0	52.08*	400.0*			NA	52.1			909.25*		856.3
Burlington Northern Railroad Bridge	498.1	71.20	365.0			NA		71.2	Zero at Gauge at this mile	909.2**		837.2

* Data from permit Drawings approved by the USCG.

** Low Steel values from 2012 survey

Missouri River Commercial Terminals and Facilities Kansas City District								
<u>Terminal</u>	<u>Facility</u>	<u>Town</u>	<u>River Mile</u>	<u>Bank</u>	<u>Contact</u>	<u>Address</u>	<u>Zip Code</u>	<u>Phone</u>
Central Stone Co., Fort Belle Quarry Dock	Receipt of sand/shipment of stone	Ft. Bellefontaine, MO	7.8	Right	Randy Barke	14201 Lewis and Clark Road	63034	(314) 830-9000
Central Stone Co., North Quarry Docks	Receipt of sand/ shipment of stone	Ft. Bellefontaine, MO	8.5	Right	Randy Barke	14200 Lewis and Clark Road	63034	(314) 830-9000
Leuke Hauling, Riverview Quarry Florissant Dock	Receipt of sand	Florissant, MO	16.8	Right	Brian Hachmeister	3009 Douglas Rd	63034	(314) 837-1700
LaFarge/ St. Charles Sand Co.	Sand unloading	St. Charles, MO	27.8	Right	Dave Viehmann	14582 Missouri Bottom Rd, Bridgeton, MO	63044	(314) 739-0169
LaFarge/ St. Charles Sand Co.	Sand unloading	St. Charles, MO	28.1	Right	Dave Viehmann	14581 Missouri Bottom Rd, Bridgeton, MO	63044	(314) 739-0169
City of St. Charles, Excursion Dock	Dock	St. Charles, MO	28.8	Left	Scott Sharp	200 N Second Street, St. Charles, MO	63301	(636) 949-3549
LaFarge Corp., St Charles, Dock	Receipt of sand	St. Charles, MO	31.5	Left	David Viehmann	14580 Missouri Bottom Rd, Bridgeton, MO	63044	(314) 393-9452
LaFarge/ St. Charles Sand Co.	Sand unloading	Gumbo, MO	43.9	Right	Dave Viehmann	14580 Missouri Bottom Rd, Bridgeton, MO	63044	(314) 739-0169
Washington Sand Co.	Sand and gravel unloading	Washington, MO	65.4	Right	Allen Korman	2 Kingsland Dr. Washington, MO	63090	(636) 239- 6638
Hermann Sand and Gravel, Inc.	Sand unloading	Hermann, MO	96.9	Left	Steven W. Engemann	114 Hermann Sand Plant at HW 19, Hermann, MO	65041	(573) 486-2913
Hermann Sand and Gravel, Inc.	Load out ramp	Hermann, MO	97.1	Left	Steven W. Engemann	114 Hermann Sand Plant at HW 19, Hermann, MO	65041	(573) 486-2913
U.S. Army Corps of Engineers	Dock, Harbor, & Boatyard	Gasconade, MO	104.4	Right	Owner	Gasconade, MO	65036	(573) 294-6411
Capital Sand Co.	Sand and gravel unloading	Jefferson City, MO	143.2	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
Jefferson City River Terminal	Loading and unloading dock	Jefferson City, MO	143.3	Left	Ray Bohlken	700 Mokane Road, Jefferson City, MO	65022	(573) 634-4880
Hermann Sand and Gravel, Inc.	Sand unloading	Jefferson City, MO	146.6	Left	Steven W. Engemann	114 Hermann Sand Plant at HW 19, Hermann, MO	65041	(573) 486-2913
Capital Sand Co.	Sand and gravel unloading	Huntsdale, MO	181.6	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
Capital Sand Co.	Sand and gravel unloading	Rocheport, MO	186.3	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
Capital Sand Co.	Sand and gravel unloading	Boonville, MO	197.0	Right	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
Skyline Materials	Rock loading	Glasgow, MO	219.0	Left	Bo Parks	821 County Rd 317 Glasgow, MO	65254	(660) 338-2798
Capital Sand Co.	Sand and gravel unloading	Glasgow, MO	226.2	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
U.S. Army Corps of Engineers	Loading platform	Glasgow, MO	226.4	Left	Owner	P.O. Box 76 Glasgow, MO	65254	(660) 338-2278
Brunswick River Terminal, Inc.	Bulk fertilizer unloading	DeWitt, MO	256.3	Left	Bill Jackson	P.O. Box 38, Brunswick, MO	65236	(660) 549-3351
Capital Sand Co.	Sand unloading	Carrolton, MO	286.9	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
Capital Sand Co.	Sand unloading	Lexington, MO	317.1	Left	Ray Bohlken	P.O. Box 104990, Jefferson City, MO	65110	(573) 634-3020
MFA INC.	Grain Loading dock	Lexington, MO	318.2	Right	Owner	2350 Monroe ST. P.O. BOX 308 Lexington, MO	64067	(660) 259-2261
U.S. Army Corps of Engineers	Government materials dock	Napoleon, MO	328.6	Right	Owner	790 E. 224 Highway Napoleon, MO	64074	(816) 240-8131
LaFarge Corp.	Cement loading dock	Sugar Creek, MO	354.8	Right	Terry VanWinkle	4201 N. River Road, Sugar Creek, MO	64054	(816) 257-5178
Holliday Sand and Gravel Co.	Sand and gravel unloading dock	Randolph, MO	360.1	Left	Travis Cope	7801 NE Birmingham Road, Randolph, MO	64161	(816) 454-5250
Brenntag Midsouth	Asphalt unloading dock	Kansas City, MO	360.6	Left	Brian Bridgeman	6301 NE Birmingham Road, Kansas City, MO	64117	(816) 454-8244
Bartlett and Company, Inc. (KCT)	Grain Loading Dock	Randolph, MO	361.0	Left	Rodney Schlatter	5801 NE Birmingham Road, K.C. MO	64116	(816) 452-3122
Bartlett and Company, Inc. (RiverRail)	Grain elevator	Kansas City, KS	367.7	Right	Rodney Schlatter	1310 Fairfax Trafficway	66115	(816) 452-3122
Holliday Sand and Gravel Co.	Sand and gravel unloading dock	Riverside, MO	371.8	Left	Ken Millsap	3501 Zeke Rd., Riverside, MO	64150	(816) 741-6466
Intercon	Loading and unloading dock	Riverside, MO	375.5	Left	Intercon	P.O. Box 9055, Kansas City, MO	64168	(816) 741-0700
Massman Construction Co.	Materials/ rock loading dock	Parkville, MO	385.0	Left	Mark Dickerson	8901 State Line, K.C., MO	64114	(816) 523-1000
Ergon Wolcott	Asphalt unloading	Kansas City, KS	386.4	Right	Owner	10520 Wolcott Dr., Kansas City, KS	66109	(913) 299-4335
U.S. Coast Guard (Leavenworth)	Government materials dock	Leavenworth, KS	397.3	Right	U.S. Coast Guard	P.O. Box 350, Leavenworth, KS	66048	(319) 524-7511
Holliday Sand and Gravel Co.	Sand and gravel unloading dock	St. Joseph, MO	447.6	Left	Doris Stobauch	P.O. Box 3211 Station A, St. Joseph, MO	64503	(816) 232-7771
St. Joseph Regional Port Authority	General Cargo Dock	St. Joseph, MO	448.0	Left	Brad Lau	3003 Frederick Ave, St. Joseph, MO	64506	(816) 364-4110
White Cloud Grain	Grain & fertilizer loading dock	White Cloud, KS	488.0	Right	Joe Kramer	604 Nemaha St., Seneca, KS	66538	(785) 336-2148

<u>Gauge Name</u>	<u>River Mile</u>	<u>Gauge Zero</u>	<u>Gauge Datum</u>	<u>Gauge Website</u>	<u>Gauge Code</u>	<u>X Coordinate</u>	<u>Y Coordinate</u>	<u>CRP Stage*</u>
St. Charles	28.00	413.47	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=sclm7	SCLM7	-90.472	38.786	10.1
Washington	67.60	457.27	NAVD88	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=whgm7	WHGM7	-91.014	38.611	3.3
Hermann	97.90	481.56	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=hrnm7	HRNM7	-91.439	38.710	7.1
Gasconade	104.80	484.80	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=gscm7	GSCM7	-91.556	38.675	
Chamois	117.40	502.50	Other	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=cmsm7	CMSM7	-91.762	38.683	
Jefferson City	143.90	520.18	NAVD88	http://water.weather.gov/ahps2/hydrograph.php?wfo=lsx&gage=jffm7	JFFM7	-92.180	38.587	8.2
Boonville	197.10	565.42	Other	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=bozm7	BOZM7	-92.754	38.978	8.1
Glasgow	226.30	586.49	Other	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=glzm7	GLZM7	-92.849	39.222	12.8
Miami	262.60	621.35	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=miam7	MIAM7	-93.225	39.328	
Waverly	293.20	646.00	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=vvym7	WVYM7	-93.515	39.214	11.1
Napoleon	328.60	680.24	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=napm7	NAPM7	-94.061	39.200	7.2
Sibley	336.20	683.92	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=sbem7	SBEM7	-94.180	39.179	
Kansas City	366.10	706.40	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=kcdm7	KCDM7	-94.588	39.112	10.0
Leavenworth	397.40	742.65	NAVD88	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=levk1	LEVK1	-94.909	39.327	
Atchison	422.50	762.20	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=atck1	ATCK1	-95.114	39.560	
St. Joseph	448.10	789.27	NAVD88	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=sjsm7	SJSM7	-94.858	39.753	8.5
Rulo	498.00	837.23	NGVD 29	http://water.weather.gov/ahps2/hydrograph.php?wfo=eax&gage=ruln1	RULN1	-95.422	40.054	9.2

*CRP Stage at gauge reflects 2010 CRP Values