

Summary of Columbia River Flood Control, 1-Mar

WY 2009

Project >>	MCDB	ARDB	LIB	DCDB	HGH	GCL	BRN	DWR
Project Limits								
Maximum Elevation, ft	2475.0	1446.0	2459.0	1892.0	3560.0	1290.0	2077.0	1600.0
Minimum Elevation, ft	2320.0	1378.0	2287.0	1794.2	3336.0	1208.0	1976.0	1445.0
Usable Storage, kaf	12053.3	7361.6	4979.5	1398.6	2981.0	5185.3	975.3	2015.7
Usable Storage, ksfd	6076.9	3711.5	2510.5	705.1	1502.9	2614.3	491.7	1016.3

Feb. 28 Project Conditions							
Elevation, ft (MSL)	2412.0	1411.9	2406.1	1812.2	3514.1	1282.3	2053.9
Draft, kaf	6092.9	3843.3	2175.1	1218.6	985.0	614.6	296.8
Usable Stor. less Draft, kaf	5960.5	3256.6	2804.4	180.0	1996.0	4570.7	678.5

1-Mar Water Supply Forecast									
Project >>	MCDB	ARDB	LIB	DCDB	HGH	GCL	BRN	DWR	TDI
Apr-Jul, kaf	-	-	-	-	-	-	3350	2461	-
Apr-Jul %-Normal	2	-	-	-	-	-	53.1%	91.7%	-
Apr-Jul Change	1	-	-	-	-	-	-670	-219	-
Apr-Aug, kaf	10582	21340	5295	1866	-	53100	-	-	74800
Apr-Aug %-Normal	2	91.3%	94.2%	83.6%	91.4%	-	88.1%	-	80.4%
Apr-Aug Change	1	-147	-706	-140	-78	-	-1500	-	-4900
May-Sep, kaf	-	-	-	-	1697	-	-	-	-
May-Sep %-Normal	2	-	-	-	-	92.5%	-	-	-
May-Sep Change	1	-	-	-	-	-167	-	-	-

System Flood Control Requirements, Drafts									
Project >>	MCDB	ARDB	LIB VarQ	DCDB	HGH VarQ	GCL	BRN	DWR Sys	DWR Loc
Jan. 31, kaf	1662	1703	1421	857	366	0	0	1118	1124
	2771	2570	1000	1215	509	0	249	1156	1170
	-	-	800	1136	-	-	-	-	-
	3060	2716	739	1136	467	537	35	1057	923
	3060	2716	698	1136	502	537	18	1142	782
	3060	2716	657	1136	538	660	-47	1012	-

System Flood Control Requirements, Elevations									
	Jan. 31, ft	Feb. 28, ft	Mar. 15, ft	Mar. 31, ft	Apr. 15, ft	Apr. 30, ft			
	-	1430.5	2426.2	1839.3	3544.1	1290.0	2077.0	1528.5	1528.0
	-	1423.2	2436.4	1812.5	3537.5	1290.0	2058.1	1525.6	1524.5
	-	-	2441.1	1812.5	-	-	-	-	-
	-	1421.9	2442.6	1818.9	3539.5	1283.3	2074.6	1532.9	1542.7
	-	1421.9	2443.5	1818.9	3537.9	1283.3	2075.8	1526.7	1552.6
	-	1421.9	2444.4	1818.9	3536.2	1281.7	2080.0	1536.3	-

Flood Control Summary at The Dalles, Oregon				
Apr-Aug, kaf	74800			
Apr-Aug %-Normal	80.4%	Upstream Storage Adjustment, kaf, Chart #2 (3) =		17849
Apr-Aug Change, kaf (1)	-4900	Initial Controlled Flow, ICF, kcfs, Chart #1 (3) =		279.2
May-Aug, kaf	63410	Estimated Unregulated Peak Discharge, kcfs, Chart #1-A (3) =		447.0

Notes: 1 Change in official forecast from the previous month.

2 Normal Runoff Volumes based on 71-Year, 1929-1999, averages for MCDB, ARDB, LIB, DCDB, DWR as reported in the *2000 Level Modified Streamflow Report*, 2004. Normal Runoff Volumes based on 30-Year, 1971-2000, averages for HGH, GCL, BRN, and TDA as determined by the Northwest River Forecast Center.

³ See Charts 1 and 2 of Columbia River Treaty I, Northwestern Division, Corps of Engineers.

Questions? Contact Ken Soderlind, 503-808-3950; or Patti Low, 503-808-3958.

Summary of Columbia River Flood Control, 1-Mar

WY 2009

Maximum Flood Control Shift from DWR to GCL												Maximum Flood Control Shift from BRN to GCL							
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
	GCL	GCL	GCL	DWR	DWR	DWR	DWR / GCL	DWR	DWR	GCL	GCL	GCL	BRN	BRN / GCL	BRN	BRN	GCL	GCL	
	Non-Shifted FC Draft	Maximum Draft Limit	Maximum Shift Potential	FC Draft		FC Shift		Shifted FC		Shifted FC		Maximum Shift Potential remaining	FC Shift		Shifted FC Draft		Shifted FC		
				System	Local	Potential	Allowable	Draft	Elevation	Draft (w/DWR Shift)	Elevation (w/DWR Shift)		Potential	Allowable FC Shift	Draft	Elevation	Draft (w/DWR+BRN Shift)	Elevation (w/DWR+BRN Shift)	
Notes	-	a	2-1	-	-	4-5	Min 3,6	4-7	-	1+7	-	2-10	-	Min 12,13	13-14	-	10+14	-	
Units	kaf	kaf	kaf	kaf	kaf	kaf	kaf	kaf	ft	kaf	ft	kaf	ft	kaf	kaf	kaf	kaf	ft	
Jan. 31	0	2745	2745	1118	1124	0	0	1124	1528.0	0	1290.0	2745	0	0	0	2077.0	0	1290.0	
Feb. 28	0	2745	2745	1156	1170	0	0	1170	1524.5	0	1290.0	2745	0	0	249	2058.1	0	1290.0	
Mar. 31	537	3556	3019	1057	923	134	134	923	1542.7	671	1281.6	2885	0	0	35	2074.6	671	1281.6	
Apr. 15	537	2287	1750	1142	782	360	360	782	1552.6	897	1278.6	1390	0	0	18	2075.8	897	1278.6	
Apr. 30 b	660	660	0	1139	-	0	0	1139	1526.9	660	1281.7	0	0	0	0	2077.0	660	1281.7	

Notes: Under certain conditions the required flood control space at DWR and BRN may be shifted to GCL prior to 30-April. The shifted rule curve shown above represents the maximum allowable flood control shift(s) for the current water year based on the current month's flood control requirements for each project and evacuation limitations at GCL; however, the actual volume shifted to GCL on any date is ultimately determined by the Bureau of Reclamation. The shift of volume for DWR to GCL has priority over the shift of volume from BRN to GCL in cases when GCL cannot accept the total combined volume.

a The potential flood control shift to GCL is limited to the operation at GCL above elevation 1252.3 ft (2744 kaf draft) at the end of February and elevation 1225.0 ft (4355 kaf draft) at end of March and 15-Apr, and also limited by the GCL maximum draft rate limit. All projects are to be at their non-shifted flood control requirements at the end of Apr.

b No shift is allowed, all projects to be back to their non-shifted flood control requirement by 30-April.

Questions? Contact Ken Soderlind, 503-808-3950; or Patti Low, 503-808-3958.