

RURAL AREA

2'-0'' (Min.)

Roadway

ROAD CLOSED

DETOUR

| |Sidewalk-


URBAN AREA

NOTES:

RIGHT

LANE CLOSED AHEAD

- 1. Mount signs that are wider than 3 feet or larger than 10 square feet on double posts.
- 2. All lumber dimensions are nominal.
- 3. The Contractor may submit alternate details for portable signs. Ensure sign mounts hold the sign face in a vertical plane. Portable signs may be mounted lower than fixed signs when approved by the CO. Ensure all portable sign supports meet the requirements of NCHRP Report 350 for crashworthiness.
- 4. When parking is permitted within 200 feet of the sign, mount the sign a minimum of 7 feet above the pavement surface.
- 5. When approved by the CO and the Utility Company, utility poles may be used for sign mounting.
- 6. For posts 4-inch x 6-inch and greater, see the Breakaway Support Detail. If breakaway design cannot be used due to post spacing, place the sign outside the clearzone or shield with a barrier. Do not place holes in posts of non-breakaway signs.



BREAKAWAY SUPPORT DETAIL

(FIXED SIGNS 4" X 6" AND GREATER POSTS)

POST SIZE TABLE MAXIMUM SIGN AREA HOLE (Sq. Ft.) POST SIZE DIAMETER 2 Post | 3 Post | 4 Post 1 Post 4" x 4" 4' None Required 10 20 4" x 6" 70 1.5 35 50 50 75 100 6" x 6' 5' 125 165 6" x 8' 85

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION EASTERN FEDERAL LANDS HIGHWAY DIVISION

U.S. CUSTOMARY DETAIL

CONSTRUCTION TRAFFIC CONTROL SIGN MOUNTING

NO SCALE

DETAIL APPROVED FOR USE	DETAIL
OVED : MAY 2011 SED: JANUARY 2016	E635-01

FIXED ROADWAY SIGNS