


- NOTE:**
- See Detail ET 619-1 for reinforcing steel size and grade.
 - See Details ET 619-1 and 2 for cattle guard wing details. Fabricate end units to accommodate selected cattle guard wing.
 - Minimum soil bearing 4,000 lb/ft². Place units in fine aggregate bed 3 inch thick over hand leveled soil compacted to not less than 95% density.
 - Chamfer exposed concrete edges 3/4" unless otherwise shown. Give all concrete surfaces a Class 1 finish.
 - Approved alternate designs may be used.

PRECAST CATTLE GUARD					
REINFORCING STEEL AND CONCRETE					
UNIT	No. of BARS	BAR MARK	LENGTH	MASS LB	CONCRETE CUYD
6'-0" END	7	B3	85"	33.1	1.89
	10	B2	74"	41.2	
	8	B1	17"	7.6	
	6	B4	26"	8.7	
6'-0" INTERIOR	18	B6	70"	70.1	1.90
	6	B5	36"	12.0	
	8	B3	85"	37.9	
	10	B2	68"	37.9	
8'-0" INTERIOR	12	B4	26"	17.4	2.34
	18	B6	70"	70.1	
	8	B5	36"	16.0	
	10	B2	92"	51.2	
8'-0" END	20	B6	70"	77.9	2.32
	8	B5	36"	16.0	
	7	B3	85"	33.1	
	10	B2	98"	54.6	
8'-0" END	8	B1	17"	7.6	2.32
	6	B4	26"	8.7	
8'-0" END	20	B6	70"	77.9	2.32
	6	B5	36"	12.0	



U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION
EASTERN FEDERAL LANDS HIGHWAY DIVISION

U.S. CUSTOMARY DETAIL

**CATTLE GUARD
PRECAST FOUNDATION**

STANDARD APPROVED FOR USE 6/2005
REVISED: 6/2008 3/2016

DETAIL
ET 619-3