

75 minimum

all around (typ.)

THREE POST SIGNS

Backfill material

all around (typ.)

FOUR POST SIGNS


NOTE:

1. Traffic barrier protection is required for all posts larger than 150 x 200 mm when located within the clear zone or if the post is vulnerable to being struck when placed outside the clear zone.

STATE

PROJECT

- 2. H₁ thru H₄ indicate overall post length. Select post lengths to fit field conditions.
- 3. D is the minimum post embedment depth for average soil conditions. See Wood Post Selection Table below.
- 4. Z is the height from ground line to mid-height of sign at the longest post.
- 5. For the purpose of post selection X and Y are as follows:Single sign, or back to back signs: X and Y are the overall dimensions of the signs.
- Multiple sign installations: X and Y are the dimensions of a rectangle enclosing all the signs.
- 6. Dimensions without units are millimeters.



TYPICAL MOUNTING FOR SIGNS WITHOUT ANGLES

WOOD POST SELECTION TABLE								
POST	NUMBER OF POSTS					Notch		
SIZE	1	2	3	4	D	depth and hole		
(mm)	Prod	duct of	X-Y-Z ('m3)	(m)	diameter		
100 x 100	2.2	4.3	6.6	18.7	0.9	-		
100 x 150	5.0	10.8	15.3	20.3	1.2	45 mm		
150 x 150	6.6	13.3	19.9	26.6	1.2	45 mm		
150 x 200	8.4	23.8	35.8	47.6	1.2	65 mm		
150 x 250	10.8	33.0	49.6	66.1	1.5	-		
200 x 250	16.1	45.1	67.5	90.0	1.5	_		
200 x 300	21.7	64.7	97.0	129.4	1.8	-		

Values shown are the maximum permitted. If the product of XYZ exceeds the limit for the largest post, use steel post installation.

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION WESTERN FEDERAL LANDS HIGHWAY DIVISION

METRIC DETAIL

PERMANENT SIGN INSTALLATION WOOD POSTS

NO SCALE

DETAIL APPROVED FOR USE 10/2009 DETAIL MW633-7