

400 Seventh St., S.W. Washington, D.C. 20590

DOT-E 10552 (NINTH REVISION)

EXPIRATION CATE: September 30, 2005

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. <u>GRANTEE</u>: Hasa, Incorporated Saugus, California

(See Appendix A to this document for a list of additional grantees and expiration dates)

2. PURPOSE AND LIMITATION:

- a. This exemption authorizes tank cars containing chlorine to remain standing with unloading connections attached when no product is being transferred. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
- b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
- 3. <u>REGULATORY SYSTEM AFFECTED</u>: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR \$ 172.302(c) and \$ 174.67(i) and (j).
- 5. <u>BASIS</u>: This exemption is based on the application of Hasa, Incorporated dated October 1, 2003 submitted in accordance with § 107.109.

6. <u>HAZARDOUS MATERIALS (49 CFR § 172.101)</u>:

OCT 31 2003

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Chlorine	2.3	UN1017	N/A

7. <u>SAFETY CONTROL MEASURES</u>:

- a. The facility operator must designate an employee responsible for on-site monitoring of the transfer facility in the absence of the unloader. The designated employee must be made familiar with the nature and properties of the product contained in the tank car, procedures to be followed in the event of an emergency; and, in the event of an emergency, have the ability and authority to take necessary corrective actions.
- b. When a signaling system is used (including a monitoring system or a sensing device), the system must be capable of alerting the designated employee in the event of an emergency and providing immediate notification of any malfunction. (For recommendations on the selection, installation and maintenance of signaling systems see NFPA 72 Installation, Maintenance and Use of Protective Signaling Systems.)
- c. In the absence of the unloader:
 - (i) the tank car and facility shutoff valves must be secured in the closed position;
 - (ii) no product may be transferred; and
 - (iii) the requirements of 49 CFR 174.67(a)(2) and (3) apply.
- d. The transfer facility shutoff valve must be located as close as practicable to the point of connection between the transfer system and the tank car and in a manner that will minimize the release of product in the event of hose rupture or separation. The facility operator must take appropriate steps to prevent rupture

of transfer hoses due to product expansion (i.e., liquid expansion chambers or hoses with an increased minimum burst pressure rating.)

- e. The facility operator must have on file, at each location using this exemption, a current copy of the Chlorine Institute's Pamphlets 6, 57 and 66 for information on employee training and safety, emergency measures and recommended procedures for the installation of piping systems and emergency shut off facilities.
- f. The facility operator must establish and maintain liaison with fire, police and other appropriate public officials to learn the responsibilities and resources of each governmental agency that may be called upon to respond to an emergency involving the tank car and transfer facility and acquaint the officials with the facility's capabilities and procedures in the event of an emergency.

8. <u>SPECIAL PROVISIONS:</u>

- a. Any manually operated switch providing access to the track on which the equipment is located must be lined against movement to that track and locked with an effective locking device operable only by a representative of the facility.
- b. The facility operator must install a bi-directional derail in an effective location (at least 50 feet when possible) from the end of the equipment to be protected by the caution sign. The person performing the unloading operation must lock the device in the derailing position with an effective locking device operable only by a representative of the facility.
- c. The facility operator must have written safety procedures on file at each location that uses this exemption. The facility operator must instruct each employee performing any function under this exemption on the contents of these procedures and ensure compliance with them. The written procedures must contain at least the following:

Continuation of DOT-E 10552 (9th Rev.) OCT 31 2003, Page 4

- (1) A physical description of the facility including the address and hours of operation.
- A drawing of the transfer facility showing natural and manmade barriers, locations of protective equipment (i.e., derail and caution sign), locations of emergency equipment and locations of signaling equipment.
- (3) Procedures for monitoring the transfer facility [see paragraphs 7(a) and (b)].
- (4) Information on the contents of the tank car including:
 - (a) chemical or common name of the product
 - (b) health and physical hazards involved in handling the product
 - (c) emergency and first aid procedures
- (5) Procedures for securing the transfer facility and protective equipment including derail, switch locks, tank car brakes, caution sign and wheel blocks.
- (6) Equipment available for employee safety and procedures for using the equipment.
- (7) Procedures and limitations for movement of tank cars in the vicinity of the transfer facility.
- (8) Testing and maintenance of system components including signalling systems.
- (9) Training requirements for designated employees responsible for monitoring the transfer facility.

Continuation of DOT-E 10552 (9th Rev.) OCT 31 2003 Page 5

- (10) Procedural steps in the event of an emergency, including names and phone numbers of key personnel and public agencies to contact.
- (11) Procedures for reviewing incidents to determine whether the written procedures require revision or modification to prevent future occurrences and amending those procedures when the review necessitates changes.
- d. The marking requirements of § 172.302(c) are waived.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Rail freight.
- 10. $\underline{\text{MODAL REQUIREMENTS}}$: None as a requirement of this exemption.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - O All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - c Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by § 172.700 through § 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. <u>REPORTING REQUIREMENTS</u>: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as

Continuation of DOT-E 10552 (9th Rev.) OCT 31 2003 Page 6

practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:

Robert A. McGuire

OCT 3 1 2003

Associate Administrator for

Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials safety Eomepage at http://hazmat.dot.gov/exemptions Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: sdc

AUG _ 5 2005

The following are hereby granted party status to this exemption based on their application(s) submitted in accordance with § 107.107 or § 107.109, as appropriate:

Company Name City/State	Application	Issue	Expiration
	Date	Date	Date
Hasa, Inc.	Oct 01,	Oct 31,	Sep 30,
Eloy, CA	2003	2003	2005
Hasa, Inc.	Oct 01,	Oct 31,	Sep 30,
Pittsburg, CA	2003	2003	2005
Hasa, Inc.	Oct 01,	Oct 31,	Sep 30,
Saugus, CA	2003	2003	2005
Velsicol Chemical Corp. Chattanooga, TN	May 23, 2005	AUG 5 2005	T1 21

Associate Administrator for

Hazardous Materials Safety