



U.S. Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

MAY 16 1994

DOT-E 11239

EXPIRATION DATE: April 30, 1996.

(FOR RENEWAL, SEE 49 CFR SECTION 107.105.)

1. GRANTEE: CO.ME.F Carpentaria s.r.l., Tradata, Italy
(U.S. Agent: ABS Industrial Verification, Inc.,
Houston, TX).
2. PURPOSE AND LIMITATIONS: This exemption authorizes the
manufacture, marking and sale of non-DOT specification IMO
Type 5 portable tanks which conform with DOT Specification
51 except all openings are not grouped in one location to be
used for the transportation in commerce of Division 2.1 and
Division 2.2 materials. This exemption provides no relief
from any regulation other than as specifically stated
herein.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-
180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR Sections
173.315(a), 178.245-1(b).
5. BASIS: This exemption is based on CO.ME.F Carpentaria
s.r.l.'s application dated March 9, 1994, submitted in
accordance with 49 CFR 107.103 and the public proceeding
thereon.

MAY 16 1994

Continuation of DOT-E 11239

Page 2

6. HAZARDOUS MATERIALS (49 CFR 172.101):

Hazardous materials description/proper shipping name	Hazard Class/ Division	Identification number	Packing Group
Dichlorodifluoromethane	2.2	UN1028	NA
Chlorodifluorobromomethane	2.2	UN1974	NA
Dichlorofluoromethane	2.2	UN1029	NA
Chlorodifluoromethane	2.2	UN1018	NA
Dichlorotetrafluoroethane	2.2	UN1958	NA
Chloropentafluoroethane	2.2	UN1020	NA
Chlorotetrafluoroethane	2.2	UN1021	NA
Chlorotrifluoroethane	2.2	UN1983	NA
1,1,1,2-Tetrafluoroethane	2.2	UN3159	NA
Chlorodifluoroethane	2.1	UN2517	NA
Difluoroethane	2.1	UN1030	NA
Dichlorodifluoromethane and Difluoroethane azeotropic mixture with approximately 74 percent dichlorodifluoromethane	2.2	UN2602	NA

7. PACKAGING(S) and SAFETY CONTROL MEASURES

- a. PACKAGING - Packaging prescribed is a non-DOT specification steel portable tank, mounted in an ISO frame, that complies with DOT Specification 51, including ASME "U" stamp, except that the fill and discharge openings are located on the bottom of the tank. The tanks are constructed in accordance with CO.ME.F Carpentaria s.r.l. drawings numbers 919.7, 919.8, 919.10, 919.11, other drawings, technical specifications, and calculations on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA) and in compliance with the following:

(1) Code - Tanks must comply with DOT Specification 51 in all respects except that the fill and discharge openings are located on the bottom of the tank.

(2) Material - SA-612 carbon steel.

MAY 16 1994

Continuation of DOT-E 11239

Page 3

- (3) Water Capacity (US Gallons) - 4623.
- (4) Insulation - None. Tank provided with sunshield.
- (5) Baffles - None.
- (6) Tank Size (inches) -

(Outside Diameter)	X	(Length)	X	(Thickness)
80.7		230.7		0.59

Head Thickness - 0.55 (min. after forming)

Weld Joint Efficiency - 1

Corrosion Allowance - 0.0

- (7) Design pressure - 277 psig

Note: Design pressure means "Maximum allowable working pressure (MAWP)" as used in the ASME Code.

- (8) Test pressure - 415.5 psig

(9) Openings - Two (2) openings for 2 inch diameter pressure relief devices on top of the tank; one (1) opening for a 16.5 inch diameter manway on the front head; one (1) opening for a 2 inch diameter vapor phase valve and one (1) opening for a 3 inch diameter liquid phase valve on the bottom of the tank.

NOTE: Each bottom outlet valve must be provided with a shear section that meets the requirements of 49 CFR 178.337-12.

- (10) Tank surface area (square feet) - 424

(11) Pressure relief devices - Two (2) 2 inch diameter spring loaded safety relief valve set at 304.4 psig.

- (12) Total relief device capacity - 1,284,218 SCFH

(13) G-loadings - Vertical down - 2, vertical up - 2, longitudinal - 2, transverse - 2.

- (14) Maximum gross weight (pounds) - 74,960

- (15) Maximum commodity weight (pounds) - 57,540

- (16) Tare weight (pounds) - 17,420

MAY 16 1994

Continuation of DOT-E 11239

Page 4

- (17) Design temperature - -40°F to 131°F
- (18) Design specific gravity - 1.4
- b. TESTING - Each tank must (i) be initially tested as required for DOT Specification 51 portable tanks in 49 CFR 178.245; and (ii) reinspected and retested once every five years in accordance with 49 CFR 173.32(e) as prescribed for DOT Specification 51 portable tanks.
- c. MARKING - Each portable tank must be plainly marked on both sides near the middle, in letters and numerals at least two inches high on a contrasting background, "DOT-E 11239". Additionally, "DOT-E 11239" must be stamped on the metal manufacturer's data plate on the line which reads "U.S. DOT Specification No.".
- d. Each tank must be visually inspected prior to shipment to ensure that it has not been damaged during loading.
- e. No product may be shipped that has a venting requirement exceeding 1,284,218 SCFH. The venting capacity required for each product must be determined by the flow formulas contained in the Compressed Gas Association (CGA) Pamphlet S-1.2.

8. SPECIAL PROVISIONS:

- a. Offerors for transportation of the hazardous materials specified in this exemption may use the packaging described in this exemption for the transportation of such hazardous materials so long as no modifications or changes are made to the packages, all terms of this exemption are complied with, and a copy of the current exemption is maintained at each facility from which such offering occurs.
- b. Each packaging manufactured under the authority of this exemption must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated for a specific manufacturing facility.
- c. A copy of this exemption, in its current status, must be maintained at each manufacturing facility at which this packaging is manufactured and must be made available to a DOT representative upon request.

MAY 16 1994


Continuation of DOT-E 11239

Page 5

- d. Shippers using the packaging covered by this exemption must comply with all provisions of this exemption, and all other applicable requirements contained in 49 CFR Parts 171-180.
- e. A test report documenting a satisfactory ISO prototype test for each tank design must be on file with the OHMEA prior to the first shipment.
- f. Hydrostatic test certificates for each tank must be maintained by the manufacturer or owner and made available upon request to any representative of the Department of Transportation.
- g. The tank must be filled by weight in accordance with the provisions of 49 CFR 173.315.
9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, and cargo vessel.
10. MODAL REQUIREMENTS:
- a. A copy of this exemption must be carried aboard each motor vehicle and cargo vessel used to transport packages covered by this exemption.
- b. Rear end protection for the motor vehicle must meet the requirements of 49 CFR 178.340-8(b) and 393.86.
- c. Each portable tank must be secured to the motor vehicle in conformance with the requirements of 49 CFR 393.100 through 393.106.
- d. Portable tanks may not be transported in container-on-flat car (COFC) or trailer-on-flat car (TOFC) service except under conditions approved by the Associate Administrator for Safety, Federal Railroad Administration.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Hazardous Materials Transportation Act:
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
 - o Registration required by 49 CFR 107.601 et seq., when applicable.
- No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect unless a regulation has been amended making the exemption no longer necessary.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (49 CFR 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued at Washington, D.C.



Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

MAY 16 1994

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Dist: USCG, FHWA, FRA.