

U.S. Department of Transportation

Research and Special Programs Administration 400 Seventh Street, S.W. Washington, D.C. 20590

DOT-E 12534

EXPIRATION DATE: November 30, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. <u>GRANTEE</u>: MODcol Corporation Sunnyvale, California

2. PURPOSE AND LIMITATIONS:

- a. This exemption authorizes the manufacture, marking, sale and use of a non-DOT specification combination packaging for the transportation in commerce of the materials authorized by this exemption. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
- b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with use not associated with transportation in commerce.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. <u>REGULATIONS FROM WHICH EXEMPTED</u>: 49 CFR § 173.202(b) in that a non-DOT specification combination packaging is not authorized, except as specified herein.
- 5. <u>BASIS</u>: This exemption is based on the application of MODcol Corporation dated July 24, 2000, submitted in accordance with § 107.105 and the public proceeding thereon.
- 6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Material Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Methanol	3	UN1230	ΙΙ
Acetonitrile	3	UN1648	II
Hexanes	3	UN1208	II

7. SAFETY CONTROL MEASURES:

- a. <u>PACKAGING</u> Packaging prescribed is a non-DOT specification combination package consisting of a non-DOT specification plywood or fiberboard box as an outer packaging and a non-DOT specification "Flanged Chromatography Column" (flanged column) as an inner packaging. The flanged column is fabricated from type 316 stainless steel which is closed by a bolted flange on each end. Design pressure of the flanged column must be at least 2000 psig. Packaging must conform to drawings and specifications of MODcol Corporation on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA).
- b. <u>TESTING</u> Each flanged column must be leak tested at 2,000 psig at time of fabrication.

c. OPERATIONAL CONTROLS:

- (1) The volume of the flanged column may not exceed 5 liters.
- (2) Internal pressure during transportation may not exceed 20 psig.

8. SPECIAL PROVISIONS:

- a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.
- b. A person who is not a holder of this exemption, but receives a package covered by this exemption, may reoffer it for transportation provided no modification or change is made to the package or its contents and it is offered for transportation in conformance with this exemption and the HMR.
- c. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

- d. Each packaging manufactured under the authority of this exemption must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by the OHMEA for a specific manufacturing facility.
- e. A current copy of this exemption must be maintained at each facility where the package is manufactured under this exemption. It must be made available to a DOT representative upon request.
- f. <u>MARKING</u> Each flanged column and outer plywood or fiberboard box must be plainly and durably marked "DOT-E 12534" as specified in § 172.301(c).
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel and cargo aircraft only.
- 10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each cargo vessel, aircraft or motor vehicle used to transport packages covered by this exemption. The shipper must furnish a current copy of this exemption to the air carrier before or at the time the shipment is tendered.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
 - o Registration required by § 107.601 et seg., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when this exemption has expired or is otherwise no longer in effect.

Continuation of DOT-E 12534

Page 4

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued in Washington, D.C.

Robert A. McGuire

Associate Administrator for Hazardous Materials Safety

DEC 20 2000

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W., Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

PO: PTOlson