

## **Principal Particulars**

MAIN DIMENSIONS		
Length, Over All	207.9 m	682.1 ft
Length, Between Perp.	190.4 m	624.7 ft
Beam	28.5 m	93.5 ft
Depth	23.6 m	77.4 ft
Design Draft	7.0 m	23.0 ft
Dwt. at Design Draft	10,178 MT	
Cb at Design Draft	0.63	
HULL PROPORTIONS		
L/B	6.7	
B/T	4.1	
B/D	1.2	
L/D	8.1	

	•				
CARGO	Wt/Unit	Full Load	Full Load	<u>PROPULSION</u>	
		Quantity	Weight	Suggested Engine	2xMAN 12V51/60DF
53' Containers	22	104	2,288		2xWartsila 12V50DF
53' Trailers	20	151	3,020	Speed at design draft	23.7 knots
Cassettes	3.56	52	185	Operating Power	21,600 kW *
Total ‡		714 TEU	5,493 MT	MCR	24,000 kW
Reefer Outlets	50			RPM	514
FULL LOAD CONDITION	<u>N</u>			RANGE & CONSUMPTION	
Cargo Weight	5,493	3 MT		M/E Fuel Consumption†	102.4 MT/Day
Consumables (98%)	2,675	MT		M/E & D/G Fuel (no reefers)	106.4 MT/Day
Ballast	1,890	) MT		Range (MGO)	~10,000 nm
Constant	120	) MT		Range (LNG)	4,000 nm
Lightship	14,447	7 MT			
Displacement	24,625	MT	•	TANK CAPACITIES	
Estimated GM	1.0	) m		Marine Gas Oil	2,700 m <sup>3</sup>
				LNG (if provided)	2,100 m <sup>3</sup>
				Fresh Water	380 m <sup>3</sup>
				Ballast Water	TBD m <sup>3</sup>
					Mad

_egend:
---------

53' Trailer 53' Container

## Notes:

† Fuel Consumption is based on MGO at the operating power.

LNG propulsion is an option and will require added storage tanks

require added storage tanks.

‡ Count assumes 2.8TEU/53'

Trailer/Container


\* Operating power is at design speed and draft with 15% sea margin






AMERICAN MARINE HIGHWAY
DESIGN CONCEPT

YPE	Medium 24kt	2010-083-050-03	
LASS	RoRo	Sheet 1 of 2	Rev







CNC

U.S. Maritime Administration

AMERICAN MARINE HIGHWAY **DESIGN CONCEPT** 

TYPE	Medium 24kt
CLASS	RoRo

2010-083-050-03 Rev. -

Sheet 2 of 2