

Full-Scale Test of Thermally-Induced Reflective Cracking: 5-Year Research at The FAA NAPTF

Hao Yin, Ph.D., P.E. Gemini Technologies, Inc.

Donald Barbagallo, P.E. (retired)FAA Airport Technology R&D Branch

Date: Aug 6, 2014

Outline

- > Research needs
- Project overview (2009-2014)
	- > Preliminary study
	- > Temperature Effect Simulation System
	- Phase I, II, III tests
- > Lessons learned
	- Advanced computational mechanics
	- > Instrumentation
	- > Material characterization
	- Construction

Research Needs

AC 150/5320-6D AC 150/5320-6E

$$
P = f(X_1, X_2, X_3, ...)
$$

Kansas City Int'l Airport

2011 Rehabilitation

- 1. Removal (milling) 4" P-501 PCC
- 2. Crack seal with P-604
- 3. Placement of 4" P-401 HMA overlay
	- P-603 tack coat
	- Two 2-in lifts
- 4. Closure for HMA cure
- 5. Removal of FOD and debris
- 6. Open for traffic

2013 Distress Survey

Project Overview

Evaluation of Tensile Stresses

Evaluation of Shear Stresses

Temperature Effect Simulation System (TESS)

Phase I Test

In May 2012, the test began with ^a sinusoidal displacement waveform with ^a 0.015-in. joint opening. Two loading rates, one cycle per ⁶⁰⁰ and ³⁰⁰ sec, were used, respectively. Later on, ^a ramp loading with ^a displacement rate of 0.10 mil/sec was applied to propagate the crack through the top 0.5-in. overlay.

- Failure was fracture Mode I.
- Although the higher loading rate did not result in higher strain level, the loading rate had ^a substantial influence on the crack propagation, especially when the crack reached the upper portion of the overlay.
- \triangleright Since the test protocol did not allow the overlay to relax, ^a significant joint closing force was generated and accumulated at the overlay bottom.

Phase II Test

Phase II test began on January 24, 2013. ^A maximum horizontal displacement (joint opening) of 0.012 in., ^a loading time of ¹⁵⁰ sec, and ^a rest period of ⁶⁰⁰ sec were used. After ⁴⁸⁶⁹ cycles, the test concluded on March 8, 2013.

Phase II Test Findings

- \triangleright "1 inch per year" was quite conservative
fer thermally induced reflective erecting for thermally-induced reflective cracking.
- > Two overlay strips exhibited almost identical performance.
- \triangleright Inclusion of a rest period at the end of each loading cycle allowed sufficient time for the overlay to relax.
- > Once bottom-up reflection cracks reached ^a critical length, the crack evolution became very aggressive.

Phase III Test

Phase III test began on June 3, 2014. The test employed the same test protocol as Phase II test. After ⁶³⁵⁰ cycles, the test concluded on July 30, 2014.

Phase III Test Findings

- \triangleright The strain relieving interlayer enhanced the reflective cracking resistance of an HMA overlay. The effectiveness of strain relieving interlayer was more pronounced at an early stage of crack propagation and slowly diminished as the crack length increased.
- Inclusion of a 1-in.-thick interlayer between existing
Concrete alabe and the everlay extended everleve concrete slabs and the overlay extended overlay service life up to 15%. The intact interlayer had prevented spalling and moisture infiltration at the joint and therefore prolonged the structural integrity of the pavement.
- > To realistically characterize the development of bottom-up reflection cracks, both mixed-mode fracture and crack channeling should be considered.

Lessons Learned

- Advanced computational mechanics
	- > Optimization of test parameters
	- > Facilitation of instrumentation
- > Instrumentation
	- **≻ Crack initiation**
	- > Crack propagation
- > Material characterization
	- > Support of construction
	- Assistance to test protocol
- Construction challenges

Optimization of Test Parameters

Optimization of Test Parameters

Facilitation of Instrumentation

Facilitation of Instrumentation

Crack Initiation

Crack Initiation

Crack Propagation

Support of Construction

Support of Construction

Assistance to Test Protocol

Construction Challenges

- \blacktriangleright Prior to the overlay construction, the existing pavement surface should be thoroughly cleaned to remove all dirt and dust.
- \triangleright For thin HMA lift, segregation should be carefully detected and eliminated so that design volumetrics can be achieved.
- \blacktriangleright Between lifts, time was cautiously balanced to allow for the application of ^a tack coat, placement of instrumentation sensors, and an adequate mix temperature to achieve the desired density.
- \triangleright Controlling and maintaining an adequate mix temperature are critical for interlayer HMA. There were unexplained spikes and dips in the temperature ranges that might have contributed to the tearing appearance in the surface of interlayer. However, after compaction, the interlayer was smooth and stable.
- \triangleright ^A further lesson learned was to cover the embedded sensors with material close to the lift thickness (i.e., 1-in.) and then use the screed of the paver to strike off the excess HMA to the proper depth and grade. As ^a result, instrumentation damage could be reduced to ^a minimum.

- Ryan Rutter, Murphy Flynn, Charles Ishee, FAA Airport Technology R&D Branch
- Aponte Renaldo, David Traverzo, and Jeffrey Stein, SRA International, Inc.
- Jamie Sabitsky, Advanced Fluid Systems, Inc.
- \triangleright Chris Decker, Roy D. McQueen & Associates, Ltd.