

May 28, 2015



U.S. Department  
of Transportation

East Building, PHH-30  
1200 New Jersey Avenue S.E.  
Washington, D.C. 20590

**Pipeline and Hazardous  
Materials Safety Administration**

DOT-SP 9462  
(NINTH REVISION)

EXPIRATION DATE: April 30, 2019

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Aztec Metal Fabrication  
Odessa, Texas
2. PURPOSE AND LIMITATIONS:
  - a. This special permit authorizes the manufacture, mark, sale and use of non-DOT specification portable tanks manifolded together within a frame and securely mounted on a truck chassis for the transportation of Class 3 and Class 8 hazardous materials described in paragraph 6 below. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.242 and § 173.243 in that a non-DOT specification packaging is authorized.
5. BASIS: This special permit is based on the application of Aztec Metal Fabricating dated May 6, 2015, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

| <b>Hazardous Materials Description</b>  |                               |                              |                           |
|---|-------------------------------|------------------------------|---------------------------|
| <b>Proper Shipping Name</b>   | <b>Hazard Class/ Division</b> | <b>Identification Number</b> | <b>Packing Group</b>      |
| Class 3 liquids having a vapor pressure less than 16 psia at 130°F/Flammable liquids, n.o.s.                  | 3                             | UN1993                       | II or III                 |
| Class 8 liquids which are corrosive to skin only and which are compatible with the tank and its appurtenances | 8                             | Various                      | II or III                 |
| Flammable liquids, corrosive, n.o.s.  | 3, 8                          | UN2924                       | II or III, as appropriate |

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Packaging prescribed is a group of three (3), four (4), or six (6), 60 gallon capacity, non-DOT specification portable tanks manifolded together within a frame, having top and bottom openings, designed and constructed in accordance with Aztec Metal Fabricating drawings dated December 20, 1982 and August 18, 1983 on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA) and in conformance with the following:

- (1) Tanks manufactured before October 1, 1996 must conform to DOT specification 57 in all respects except the metal certification plate required by § 178.251-7 must not be marked DOT specification 57.
- (2) A capacity of less than 110 gallons is authorized.
- (3) The use of sight glasses is authorized. Each sight glass must have shut off valves, top and bottom and be provided with adequate protection to prevent accidental breakage.

**May 28, 2015**

(4) No new construction of tanks manufactured in conformance with DOT Specification 57 is permitted after October 1, 1996.

(5) Tanks manufactured after October 1, 1996 must meet the requirements for UN Standard 31A Intermediate bulk container (IBC) in all respects except for specification marking, water capacity, and that the use of sight glasses is authorized. Each sight glass must have shut-off valves, top and bottom and be provided with adequate protection to prevent accidental breakage. After the drop test is performed as described in § 178.810(c), a manifolded unit must also be subjected to a drop flat on a side, flat on the top, and on a corner, whichever is considered to be the most vulnerable part. The same or different container may be used for each drop.

b. TESTING -

(1) A test report documenting a satisfactory prototype test for the tank assembly design of six tanks must be on file with the OHMSPA prior to the first shipment.

(2) Hydrostatic test certificates for each tank must be maintained by the manufacturer or owner and made available upon request to any representative of the Department of Transportation.

(3) Each tank must be visually inspected prior to each trip to insure that it has not been damaged on the previous trip.

(4) Each DOT specification 57 portable tank must be reinspected and retested once every two and one-half years in accordance with § 180.605 as prescribed for DOT specification 57 portable tanks at a minimum pressure of 10 psig.

(5) Each UN31A intermediate bulk container must be reinspected and retested once every two and one-half years in accordance with 49 CFR 180.352(b) as prescribed for UN31A intermediate bulk containers except that hydrostatic testing at a minimum pressure of 10 psig must be conducted instead of leakproofness testing.

(6) The prototype test on this tank assembly design will serve to qualify smaller tank assembly designs made of the same material and thickness, by the same fabrication technique, and with identical supports and equivalent closures and other appurtenances. A drawing showing the arrangement of the smaller tank assembly design must be on file with the OHMSPA prior to the first shipment.

c. OPERATIONAL CONTROLS -

(1) Each tank must be filled so as not to be liquid full at less than or equal to 130°F.

(2) Sight glasses shut off valves must be closed during transportation.

(3) Tanks are only authorized when manifolded together within a frame. The number of tanks within a group may not exceed six and may not exceed sixty (60) gallons capacity each.

(4) Marking and placarding requirements specified for cargo tanks in 49 CFR Part 172, Subpart D and Subpart F, must be met. Also each manifolded unit must be plainly marked on both sides near the middle, in letters at least two inches high on a contrasting background, "DOT-SP 9462".

(5) Each filling overflow line must be fitted with a shut off valve on the top of the tank which must be secured during transportation.

(6) Each bottom discharge valve must be secured during transportation.

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modifications or

**May 28, 2015**

changes are made to the package and it is offered for transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by the Office of Hazardous Materials Special Permits and Approvals for a specific manufacturing facility.

e. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle.
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each motor vehicle used to transport packages covered by this special permit.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
  - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
  - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
  - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special

**May 28, 2015**

permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notice of certain hazardous materials incidents, and 171.16 Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Dr. Magdy El-Sibaie  
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at [http://hazmat.dot.gov/sp\\_app/special\\_permits/spec\\_perm\\_index.htm](http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm) Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: ae