

February 26, 2014



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue S.E.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 9530
(SIXTH REVISION)

EXPIRATION DATE: January 31, 2018

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: National Refrigerants, Inc.
Philadelphia, PA
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of certain Division 2.1 and 2.2 gases in non-DOT specification IMO Type 5 portable tanks. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. No party status will be granted to this special permit.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.315, in that a non-DOT specification portable tank is not authorized, except as specified herein.
5. BASIS: This special permit is based on the application of National Refrigerants, Inc. dated December 9, 2013, submitted in accordance with § 107.109.

February 26, 2014

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
1-Chloro-1, 1-difluoroethanes, or Refrigerant gas R 142b	2.1	UN2517	N/A
Chlorodifluorobromomethane, or Refrigerant gas R 12B1	2.2	UN1974	N/A
Chlorodifluoromethane and chloropentafluoroethane mixture, or Refrigerant gas R 502 with fixed boiling pint, with approximately 49 percent chlorodifluoromethane	2.2	UN1973	N/A
Chlorodifluoromethane, or Refrigerant gas R 22	2.2	UN1018	N/A
Dichlorodifluoromethane and difluoroethane azeotropic mixture or Refrigerant gas R 500 with approximately 74 percent dichlorodifluoromethane	2.2	UN2602	N/A
Dichlorodifluoromethane, or Refrigerant gas R 12	2.2	UN1028	N/A
1,2-Dichloro-1,1,2,2-tetrafluoroethane, or Refrigerant gas R 114	2.2	UN1958	N/A
1,1-Difluoroethane, or Refrigerant gas R 152a	2.1	UN1030	N/A
Dimethyl ether	2.1	UN1033	N/A
1,1,1,2-tetrafluoroethane, or Refrigerant gas R 134a	2.2	UN3159	N/A

February 26, 20147. SAFETY CONTROL MEASURES:

a. PACKAGING - Prescribed packaging is a non-DOT specification portable tank, mounted in an ISO frame, designed and constructed in accordance with ANF -Industrie drawing nos. 46050.990.015 Rev. A dated June 11, 1985, and 46050.191.009 Rev. B dated June 3, 1985, other drawings, technical specifications and calculations on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA) and in conformance with the following:

- (1) Code - Conforms with DOT Specification 51 except that tanks are not ASME Code "U" stamped and have bottom outlets; IMO Type 5.
- (2) Insulation - None. Tanks are equipped with a sun shield.
- (3) Water capacity (U.S. Gallons): 4,438.
- (4) Material: French standard NFA 36 205, designation A 52 FP, Yield strength: 48,575 psi; Tensile strength: 73,950 psi.
- (5) Tank Size (outside dia.) X (length) X (thick.)

(inches)	78.74	233.27	0.677(min.)
----------	-------	--------	-------------

Head Thickness: 0.618 (min.)
 Weld Joint Efficiency: 1.0
 Corrosion Allowance: 0.0
 Number of Baffles: 2
- (6) Design Pressure (PSIG): 315.
Note: Design pressure means "maximum allowable working pressure (MAWP)" as used in the ASME Code.
- (7) Test Pressure, Minimum (PSIG): 473.
- (8) Openings: Two (2) 7.5 inch diameter opening for the pressure relief devices on the top; one (1) 24.4 inch diameter opening for the manhole on the head; one (1) 8.3 inch diameter opening for the liquid phase valve and one (1) 6.5 inch diameter opening for the vapor phase valve on the bottom. NOTE: Each bottom outlet valve must be provided with a shear section that meets the requirements of ' 178.337-10(f).

February 26, 2014

- (9) Tank surface area (square feet): 441.
- (10) Pressure Relief Devices: Two (2) 2 inch diameter spring loaded safety relief valves set at 315 psig. Total relief device capacity is 1,437,117 SCFH.
- (11) G-Loadings: Vertical down 2: Vertical up 2: Longitudinal 2: and Transverse 2.
- (12) Maximum Gross Weight (pounds): 67,196.
- (13) Maximum Commodity Weight (pounds): 49,868.
- (14) Tare Weight (pounds): 17,328.
- (15) Design Specific Gravity: 1.35.
- (16) Design Temperature Range (EF): -40 to 122.

b. TESTING -

- (1) Each tank must be (i) visually inspected prior to each trip to insure that it has not been damaged on the previous trip; and (ii) retested and reinspected once every five years in accordance with § 180.605 as prescribed for DOT Specification 51 portable tanks.
- (2) Hydrostatic test certificates for each tank must be maintained by the owner or manufacturer at its principal business office and be made available to any representative of the DOT upon request.
- (3) A test report documenting a satisfactory ISO prototype test for this tank design must be on file with the OHMSPA prior to the first shipment.

c. OPERATIONAL CONTROLS -

- (1) Each portable tank must be plainly marked on both sides near the middle, in letters at least two inches high on a contrasting background, "DOT-SP 9530".
- (2) No product may be shipped that has venting requirements exceeding 1,437,117 SCFH. The venting capacity required for each product must be determined by the flow formulas contained in Compressed Gas Association (CGA) pamphlet S-1.2.

February 26, 2014

- (3) The tank must be filled by weight in accordance with the provisions of § 173.315.
- (4) "DOT-SP 9530" must be stamped on the metal manufacturer's data plate on the line which reads "U.S. DOT Specification No."
- (5) For each portable tank, the manufacturer must prepare a certificate which must be signed by a responsible official of the manufacturer and an independent inspection agency certifying that the portable tank is designed and constructed in accordance with the ASME Code and this special permit. The certificate for the first portable tank fabricated must be submitted to the OHMSPA prior to the initial shipment.
- (6) The construction of all portable tanks authorized by this special permit started after January 1, 1986, must be in full conformance with the ASME Code including the "U" stamp.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package and it is reoffered for transportation in conformance with this special permit and the HMR.

b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

c. Transportation of Division 2.1 (flammable gases) are not authorized aboard cargo vessel unless specifically authorized in the Hazardous Materials Table (§ 172.101).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, and cargo vessel.

10. MODAL REQUIREMENTS:

a. A current copy of this special permit must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this special permit.

February 26, 2014

- b. Portable tanks may not be transported in container-on-flat car (COFC) or trailer-on-flat car (TOFC) service except under conditions approved by the Associate Administrator for Safety, Federal Railroad Administration.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

February 26, 2014

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notice of certain hazardous materials incidents, and 171.16 Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Dr. Magdy El-Sibaie
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: dl