

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

B NH

Name of Operator: ENVOY Mobil Pipeline Co.		
OP ID No. ⁽¹⁾ 12628	Unit ID No. ⁽¹⁾ 3944	
H.Q. Address:	System/Unit Name & Address: ⁽¹⁾	
800 Bell Houston, TX 77002	Corsicana Area PO Box 618 Corsicana, Texas 75151	
Co. Official: Gary Pruessing	Activity Record ID#: 118626	
Phone No.: 713-656-5056	Phone No.: 903-654-5345	
Fax No.: 713-656-9579	Fax No.: 903-654-5302	
Emergency Phone No.: 800-537-5200	Emergency Phone No.: 800-537-5200	
Persons Interviewed	Titles	Phone No.
Thad Massengale	Pipeline Advisor	713-656-2258
Larry "Doc" Hawthorne	Field Regulatory Specialist	903-654-5345
Denny Wedgeworth	Corrosion Technician	903-236-8141
PHMSA Representative(s) ⁽¹⁾ Jim Arnold		
Inspection Date(s) ⁽¹⁾ 09/17-21/07		
Company System Maps (copies for Region Files): Adequate		
Unit Description: 159 MILES OF 20" CRUDE (#1) CORSICANA TO THE TEXAS/ARKANSAS STATE LINE. THE 20" LINE IS NO LONGER IDLED. THE LINE WAS REACTIVATED IN MARCH 2006 TRANSPORTING HEAVY CANADIAN CRUDE FROM ILLINOIS TO BEAUMONT TEXAS. NO POTENTIAL VIOLATIONS OBSERVED DURING THIS AUDIT.		
<i>Jim Arnold</i> 11/8/07		
Portion of Unit Inspected ⁽¹⁾		
INSPECTED FIELD RECORDS OF THE FOLLOWING SYSTEM. 159 MILES OF 20" CRUDE (#1) FROM CORSICANA TEXAS TO THE TEXAS/ARKANSAS STATE LINE. FIELD INSPECTION CONSISTED OF MAINLINE VALVES, OVER PRESSURE PROTECTION EQUIPMENT, RECTIFIERS, EXPOSED PIPE, AND ROW CONDITIONS. LOCATIONS INSPECTED WERE MLV MP14.97, 20" GATE VALVE. MLV MP 21.39, 20" GATE VALVE & RECTIFIER. MLV MP 27.49, 20" GATE VALVE. MLV MP 41.07, 20" GATE VALVE & RECTIFIER. MLV MP 56.90, 20" GATE VALVE & RECTIFIER. MLV MP 66.64, 20" GATE VALVE. MLV MP 71.46, 20" GATE VALVE. MLV MP 78.77, 20" GATE VALVE. MLV MP 82.75 & 82.85 @ QUITMAN PUMP STATION (IDLE). MLV MP 159.27, 20" GATE VALVE. MLV MP 134.65, 20" GATE VALVE. MLV MP 127.88, 20" GATE VALVE. EXPOSED PIPE @ MP 124.0. MLV MP 98.51 & 98.46 @ WINNSBORO PUMP STATION (IDLE), 20" GATE VALVES. MLV MP 22.24, 20" GATE VALVE. MLV MP 15.08, 20" GATE VALVE. MLV MP 11.03, 20" GATE VALVE. MLV MP 00.01 & 00.02, 20" GATE VALVES @ THE CORSICANA STATION. MLV MP 30.06 & 30.18, 20" GATE VALVES @ THE FAIRFIELD STATION. MLV MP 42.60, 20" GATE VALVE. MLV MP 55.04, 55.38 & 57.96, 20" GATE VALVES @ CARTER RANCH. MLV MP 62.31 & 62.41, 20" GATE VALVES @ GRAPELAND STATION. MLV MP 99.5, 20" GATE VALVE. MLV MP 108.5, 20" GATE VALVE. MLV MP 108.11, 20" GATE VALVE.		

For hazardous liquid operator inspections, the attached evaluation form should be used in conjunction with 49 CFR 195 during PHMSA

¹ Information not required if included on page 1.

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

inspections. Refer to the Hub Joint O&M team inspection schedule to identify inter-regional operators. For those operators, procedures do not have to be evaluated for content unless: 1) new or amended regulations have been placed in force after the team inspection, or 2) procedures have changed since the team inspection. Items in the procedures sections of this form identified with "*" reflect applicable and more restrictive new or amended regulations that became effective between 03/02/02 and 03/02/07.

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

CONVERSION TO SERVICE		S	U	N/A	N/C
.5	* Has a written procedure been developed addressing all applicable requirements and followed? Amt 195-86 pub 06/09/06 eff 07/10/06.	X			

Comments:
No conversion of service in this unit.

SUBPART B - REPORTING PROCEDURES		S	U	N/A	N/C
.402(a) .402(c) (2)	.50 Accident report criteria, as detailed under 195.50. In general, 5 gallons or more, death or personal injury necessitating hospitalization , or total estimated property damage including clean-up and product lost equaling \$50,000 or more. Note: A release of less than 5 gals may still require reporting. See (195.50(b) and 195.52(a)(4)).				X
	.52 Telephonically reporting accidents to NRC (800) 424-8802				X
	.54(a) Accident Report - file as soon as practicable, but no later than 30 days after discovery				X
	.54(b) Supplemental report - required within 30 days of information change/addition				X
	.55 Safety-related conditions (SRC) - criteria				X
	.56(a) SRC Report is required to be filed within five (5) working days of the determination and within ten (10) working days after discovery				X
	.56(b) SCR Report requirements, including corrective actions (taken and planned)				X

Comments:
Team O&M inspection 04/2007

SUBPART C - PASSAGE OF INTERNAL INSPECTION DEVICE PROCEDURES		S	U	N/A	N/C
.402(c)/ .422	.120(a) Each new pipeline or each section of a pipeline which pipe or components has been replaced must be designed and constructed to accommodate the passage of instrumented internal inspection devices that are applicable to this section				X

Comments:
Team O&M inspection 04/2007

SUBPART D – WELDING, NDT, and REPAIR /REMOVAL PROCEDURES		S	U	N/A	N/C
Compliance with welding requirements for pipe replaced or repaired in the course of pipeline maintenance is required by §195.422 and §195.200.					
*	Welding must be performed by qualified welders using qualified welding procedures.				X
.402(c)/ .422	.214(a) Are welding procedures qualified in accordance with Sec. 5 of API 1104 or Section IX of ASME Boiler & Pressure Code? Amdt. 195-81 pub. 6/14/04, eff. 7/14/04.				X
	Welding procedures must be qualified by destructive testing.				X
	.214(b) Each welding procedure must be recorded in detail including results of qualifying tests.				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

SUBPART D – WELDING, NDT, and REPAIR /REMOVAL PROCEDURES		S	U	N/A	N/C	
*	.222(a)	Welders must be qualified in accordance with Section 6 of API Standard 1104 (19th Ed., 1999) or Section IX of the ASME Boiler and Pressure Vessel Code (2004 Ed. Including addenda through July 1, 2005), except that a welder qualified under an earlier edition than listed in §195.3 may weld, but may not requalify under that earlier edition. Amdt 195-81 pub. 6/14/04, eff. 7/14/04.; Amdt 195-81 corr. Pub. 9/09/04; Amt 195-86 pub 06/09/06 eff 07/10/06.				X
*	.222(b)	Welders may not weld with a particular welding process unless, within the preceding 6 calendar months, the welder has--(1) Engaged in welding with that process; and (2) Had one weld tested and found acceptable under Section 9 of API 1104. Amdt 195-78 pub. 9/11/03, eff. 10/14/03.				X
Alert Notice 3/13/87		In the welding of repair sleeves and fittings, do the operator's procedures give consideration to the use of low hydrogen welding rods, cooling rate of the weld, metallurgy of the materials being welded (weldability carbon equivalent) and proper support of the pipe in the ditch?				
.402(c)/ .422	.226(a)	Arc burns must be repaired.				X
	.226(b)	Do arc burn repair procedures require verification of the removal of the metallurgical notch by nondestructive testing? (Ammon. Persulfate). Pipe must be removed for non-repairable notches.				X
	.226(c)	The ground wire may not be welded to the pipe/fitting being welded.				X
		Nondestructive Testing Procedures				
*	.228 /234	Do procedures require welds to be nondestructively tested to ensure their acceptability according to Section 9 of API 1104 (19th) and as per §195.228(b) and per the requirements of §195.234 in regard to the number of welds to be tested? Amdt 195-81 pub. 6/14/04, eff. 7/14/04.				X
	.234(b)	Nondestructive testing of welds must be performed:				
		1. In accordance with written procedures for NDT				X
		2. By qualified personnel				X
		3. By a process that will indicate any defects that may affect the integrity of the weld				X
	.266	Records of the total number of girth welds and the number nondestructively tested, including the number rejected and the disposition of each rejected weld, must be maintained.				X
		Repair or Removal of Weld Defect Procedures				
	.230	Welds that are unacceptable (Section 9 API 1104) must be removed and/or repaired. See .228 and .230 for exceptions.				X

Comments:
Team O&M inspection 04/2007

SUBPART E - PRESSURE TESTING PROCEDURES		S	U	N/A	N/C	
.402(c)/ .422	.302(a)	Pipelines, and each pipeline segment that has been relocated, replaced, or otherwise changed, must be pressure tested without leakage (see .302(b), (c), and .305(b) for exceptions).				X
	.302(b)	Except for lines converted under §195.5 , certain lines listed under this section may be operated without having been pressure tested per Subpart E.				X
	.302(c)	Have/are the below listed pipelines (excluding converted lines and lines covered under the risk assessment option in §195.303) being pressure tested per subpart E; or, was the MOP established prior to 12/7/98, using the prescribed pressure in 195.406(a)(5) [80% of the 4 hour documented test pressure, or 80% of the 4 hour documented operating pressure] ?				
		- Interstate liquid lines constructed before 01/08/71 (excluding HVL onshore or low stress lines).				X
		- Interstate liquid offshore gathering lines constructed before 08-01-77 (excluding low stress lines)				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

SUBPART E - PRESSURE TESTING PROCEDURES			S	U	N/A	N/C
		- Intrastate liquid lines constructed before 10/21/85 (excluding HVL onshore or low stress lines).				X
		- Carbon dioxide lines constructed before 07/12/91 (excluding rural production field distribution or low stress lines).			X	
.304		Test pressure must be maintained for at least 4 continuous hours at a pressure equal to 125 percent, or more, of the MOP. If not visually inspected during the test, at least an additional 4 hours at 110 percent of MOP is required.				X
.305(a)		All pipe, all attached fittings, including components must be pressure tested in accordance with §195.302.				X
.305(b)		A component, other than pipe, that is the only item being replaced or added to the pipeline system need not be hydrostatically tested under paragraph (a) of this section if the manufacturer certifies that either: (1) The component was hydrostatically tested at the factory; or (2) The component was manufactured under a quality control system that ensures each component is at least equal in strength to a prototype that was hydrostatically tested at the factory.				X
.306		Appropriate test medium				X
.308		Pipe associated with tie-ins must be pressure tested.				X
.310(a)		Test records must be retained for useful life of the facility.				X
.310(b)		Does the record required by paragraph (a) of this section include:				
.310(b)(1)		Pressure recording charts.				X
.310(b)(2)		Test instrument calibration data.				X
.310(b)(3)		Name of the operator, person responsible, test company used, if any.				X
.310(b)(4)		Date and time of the test.				X
.310(b)(5)		Minimum test pressure.				X
.310(b)(6)		Test medium.				X
.310(b)(7)		Description of the facility tested and the test apparatus.				X
.310(b)(8)		Explanation of any pressure discontinuities, including test failures, that appear on the pressure recording charts.				X
.310(b)(9)		Where elevation differences in the test section exceed 100 feet , a profile of the elevation over entire length of the test section must be included				X
*	.310(b)(10)	Temperature of the test medium or pipe during the test period. Amdt 195-78 pub. 9/11/03, eff. 10/14/03.				X

Comments:
 Team O&M inspection 04/2007
 NA = Mobil Pipeline does not operate CO2 pipelines.

SUBPART F - OPERATIONS & MAINTENANCE PROCEDURES			S	U	N/A	N/C
.402(a)	.402	a. Has the operator prepared a manual for normal operations & maintenance activities & handling abnormal operations & emergencies?				X
		b. Procedures for reviewing the manual at intervals not exceeding 15 months, but at least each calendar year?				X
		c. Appropriate parts must be kept at locations where O&M activities are conducted.				X

Comments:

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

Comments:
 Team O&M inspection 04/2007

MAINTENANCE & NORMAL OPERATION PROCEDURES			S	U	N/A	N/C
.402(a)	.402(c)	Written procedures must be followed to provide safety during maintenance and normal operations. Does the operator have procedures for:				
	.402(c)(4)	Has the operator determined which pipeline facilities are located in areas that would require an immediate response by the operator to prevent hazards to the public if the facilities failed or malfunctioned?				X
	.402(c)(5)	Analyzing pipeline accidents to determine their causes?				X
	.402(c)(6)	Minimizing the potential for hazards identified under paragraph (c)(4) and minimizing the possibility of recurrence of accidents analyzed under paragraph (c)(5)?				X
	.402(c)(7)	Starting up and shutting down any part of the pipeline system in a manner designed to assure operation within limits prescribed by §195.406 , considering the hazardous liquid or carbon dioxide in transportation, variations in the altitude along the pipeline, and pressure monitoring and control devices?				X
	.402(c)(8)	In the case of a pipeline that is not equipped to fail safe monitoring from an attended location pipeline pressure during startup until steady state pressure and flow conditions are reached and during shut-in to assure operation within limits prescribed by §195.406 ?				X
	.402(c)(9)	In the case of facilities not equipped to fail safe that are identified under §195.402(c)(4) or that control receipt and delivery of hazardous liquid, detecting abnormal operating conditions by monitoring pressure, temperature, flow or other appropriate operational data and transmitting this data to an attended location?				X
	.402(c)(10)	Abandoning pipeline facilities, including safe disconnection from an operating pipeline system, purging of combustibles, and sealing abandoned environmental hazards				X
		Reporting abandoned pipeline facilities offshore, or onshore crossing commercially navigable waterways per §195.59.				X
	.402(c)(11)	Minimizing the likelihood of accidental ignition of vapors in areas near facilities identified under paragraph (c)(4) of this section where the potential exists for the presence of flammable liquids or gases?				X
	.402(c)(12)	Establishing and maintaining liaison with fire, police, and other appropriate public officials to learn the responsibility and resources of each hazardous liquid pipeline emergency.				X
	.402(c)(13)	Periodically reviewing the work done by operator's personnel to determine the effectiveness of the procedures used in normal operation and maintenance and taking corrective action where deficiencies are found?				X
	.402(c)(14)	Taking adequate precautions in excavated trenches to protect personnel from hazards of unsafe accumulations of vapor or gas, making available when needed at the excavation site, emergency rescue equipment, including a breathing apparatus and, a rescue harness and line.				X

Comments:
 Team O&M inspection 04/2007

ABNORMAL OPERATION PROCEDURES (CONTROL CENTER FUNCTION)			S	U	N/A	N/C
.402(a)	.402(d)	The O&M manual must contain written procedures to provide safety when operating design limits have been exceeded. Does the operator have procedures for:				
	.402(d)(1)	Responding to, investigating, and correcting the cause of:				
		i. Unintended closure of valves or shutdowns?				X
		ii. An increase or decrease in pressure or flow rate outside normal operating limits?				X
		iii. Loss of communications?				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

ABNORMAL OPERATION PROCEDURES (CONTROL CENTER FUNCTION)			S	U	N/A	N/C
.402(d)	(2)	iv. The operation of any safety device?				X
		v. Any other malfunction of a component, deviation from normal operation, or personnel error which could cause a hazard to persons or property?				X
		Checking variations from normal operation after abnormal operations have ended at sufficient critical locations in the system to determine continued integrity and safe operations?				X
	(3)	Correcting variations from normal operation of pressure and flow equipment controls?				X
	(4)	Does operating personnel notify responsible operator personnel where notice of an abnormal operation is received?				X
(5)	Periodically reviewing the response of operating personnel to determine the effectiveness of the procedures and taking corrective action where deficiencies are found?				X	

Comments:
Team O&M inspection 04/2007

EMERGENCY PROCEDURES			S	U	N/A	N/C
.402(a)	.402(e)	The O&M manual must include written procedures to provide safety when an emergency condition occurs. Does the operator have procedures for:				
	(1)	Receiving, identifying, and classifying notices of events which need immediate response by the operator or fire, police, or other, and notifying appropriate operator's personnel for corrective action?				X
	(2)	Making a prompt and effective response to a notice of each type of emergency, fire, explosion, accidental release of hazardous liquid, operational failure, natural disaster affecting the pipeline?				X
	(3)	Making personnel, equipment, instruments, tools, and materials available at the scene of an emergency?				X
	(4)	Taking action; such as emergency shutdown or pressure reduction, to minimize release of liquid at a failure site?				X
	(5)	Controlling the release of liquid at the failure site?				X
	(6)	Minimizing the public exposure and accidental ignition, evacuation, and halting traffic on roads, railroads, etc.?				X
	(7)	Notifying fire, police, and others of hazardous liquid emergencies and preplanned responses including HVLs?				X
	(8)	Determining extent and coverage of vapor cloud and hazardous areas of HVLs by using appropriate instruments?				X
	(9)	Post accident review of employees activities to determine if procedures were effective and corrective action was taken?				X

Comments:
Team O&M inspection 04/2007

EMERGENCY RESPONSE TRAINING PROCEDURES (CONTROL CENTER & FIELD)			S	U	N/A	N/C
.402(a)	.403(a)	Each operator shall establish and conduct a written continuing training program to instruct operating and maintenance personnel to:				
	(1)	Carry out the emergency response procedures established under §195.402.				X
	(2)	Know the characteristics and hazards of liquids or carbon dioxide transported, including in the case of HVL, flammability, of mixtures with air, odorless vapors, and water reactions.				X
	(3)	Recognize conditions that are likely to cause emergencies; predict the consequences of malfunction or failures and take appropriate actions.				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

EMERGENCY RESPONSE TRAINING PROCEDURES (CONTROL CENTER & FIELD)			S	U	N/A	N/C
*	.403(a)(4)	Take steps necessary to control any accidental release of hazardous liquid or carbon dioxide and to minimize the potential for fire, explosion, toxicity, or environmental damage.				X
	.403(a)(5)	Learn the potential causes, types, sizes, and consequences of fire and the appropriate use of portable fire extinguishers and other on-site fire control equipment, involving, where feasible, a simulated pipeline emergency condition. Amdt 195-78 pub. 9/11/03, eff. 10/14/03.				X
	.402(f)	Instructions to enable O&M personnel to recognize and report potential safety related conditions.				X
	.403(b)	At intervals not exceeding 15 months, but at least once each calendar year:				
	.403(b)(1)	Review with personnel their performance in meeting the objectives of the emergency response training program				X
	.403(b)(2)	Make appropriate changes to the emergency response training program				X
	.403(c)	Require and verify that supervisors maintain a thorough knowledge of the emergency response procedures for which they are responsible.				X

Comments:
Team O&M inspection 04/2007

MAPS and RECORDS PROCEDURES			S	U	N/A	N/C
.402(a)	.402(c)(1)	Making construction records, maps, and operating history available as necessary for safe operation and maintenance.				X
	.404(a)	Each operator shall maintain current maps and records of its pipeline system that include at least the following information:				
	.404(a)(1)	Location and identification of the following facilities:				
		i. Breakout tanks				X
		ii. Pump stations				X
		iii. Scraper and sphere facilities				X
		iv. Pipeline valves				X
		v. Facilities to which §195.402(c)(9) applies				X
		vi. Rights-of-way				X
		vii. Safety devices to which §195.428 applies				X
	.404(a)(2)	All crossings of public roads, railroads, rivers, buried utilities and foreign pipelines.				X
	.404(a)(3)	The maximum operating pressure of each pipeline.				X
	.404(a)(4)	The diameter, grade, type, and nominal wall thickness of all pipe.				X
	.404(b)	Each operator shall maintain for at least 3 years daily operating records for the following:				
	.404(b)(1)	The discharge pressure at each pump station.				X
	.404(b)(2)	Any emergency or abnormal operation to which the procedures under §195.402 apply.				X
.404(c)	Each operator shall maintain the following records for the periods specified:					
.404(c)(1)	The date, location, and description of each repair made on the pipe and maintain it for the life of the pipe .				X	
.404(c)(2)	The date, location, and description of each repair made to parts of the pipeline system other than the pipe and maintain it for at least 1 year .				X	
.404(c)(3)	Each inspection and test required by Subpart F shall be maintained for at least 2 years, or until the next inspection or test is performed, whichever is longer .				X	

Comments:

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

Comments:
 Team O&M inspection 04/2007

MAXIMUM OPERATING PRESSURE PROCEDURES (MOP) - ALL SYSTEMS			S	U	N/A	N/C
.402(a)	.406(a)	Except for surge pressures and other variations from normal operations, the MOP may not exceed any of the following:				
	* .406(a)(1)	The internal design pressure of the pipe determined by §195.106. Amt 195-86 pub 06/09/06 eff 07/10/06.				X
	.406(a)(2)	The design pressure of any other component on the pipeline.				X
	.406(a)(3)	80% of the test pressure (Subpart E).				X
	.406(a)(4)	80% of the factory test pressure or of the prototype test pressure for any individual component.				X
	.406(a)(5)	80% of the test pressure or the highest operating pressure for a minimum of 4 hours for a pipeline that has not been tested under Subpart E.				X
	.406(b)	The pipeline may not be operated at a pressure that exceeds 110% of the MOP during surges or other variations from normal operations:				X
		Adequate controls and protective equipment must be installed to prevent the pressure from exceeding 110% of the MOP.				X

Comments:
 Team O&M inspection 04/2007

COMMUNICATION PROCEDURES (CONTROL CENTER)			S	U	N/A	N/C
.402(a)	.408(a)	Operator must have a communication system to provide for the transmission of information needed for the safe operation of its pipeline system.				X
	.408(b)	Does the communication system required by paragraph (a) include means for:				
	.408(b)(1)	Monitoring operational data as required by §195.402(c)(9).				X
	.408(b)(2)	Receiving notices from operator personnel, the public, and others about abnormal or emergency conditions and initiating corrective actions.				X
	.408(b)(3)	Conducting two-way vocal communication between a control center and the scene of abnormal operations and emergencies.				X
	.408(b)(4)	Providing communication with fire, police, and other appropriate public officials during emergency conditions, including a natural disaster.				X

Comments:
 Team O&M inspection 04/2007

LINE MARKER PROCEDURES			S	U	N/A	N/C
.402(a)	.410(a)	Line markers must be placed over each buried pipeline in accordance with the following:				
	.410(a)(1)	Located at each public road crossing, railroad crossing, and sufficient number along the remainder of each buried line so that its location is accurately known				X
	.410(a)(2)	Must have the correct characteristics and information				X
	.410(c)	Must be placed where pipelines are aboveground in areas that are accessible to the public				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

Comments:
Team O&M inspection 04/2007

INSPECTION RIGHTS-of-WAY & CROSSINGS UNDER NAVIGABLE WATER PROCEDURES			S	U	N/A	N/C
.402(a)	.412(a)	Operator must inspect the right-of-way at intervals not exceeding 3 weeks , but at least 26 times each calendar year				X
	.412(b)	Operator must inspect each crossing under a navigable waterway to determine the crossing condition at intervals not exceeding 5 years .				X

Comments:
Team O&M inspection 04/2007

UNDERWATER INSPECTION PROCEDURES of OFFSHORE PIPELINES			S	U	N/A	N/C
* .402(a)	.413(a)	Procedure to identify its pipelines in the Gulf of Mexico and its inlets in waters less than 15 feet (4.6 meters) that are at risk of being an exposed underwater pipeline or a hazard to navigation. Gathering lines of 4 ½ inches (114mm) nominal outside diameter or smaller are exempt. (Procedures must be in effect August 10, 2005.) Amdt 195-82 pub. 8/10/04, eff. 9/09/04.				X
*	.413(b)	Each operator shall conduct appropriate periodic underwater inspections of its pipelines in the Gulf of Mexico and its inlets in waters less than 15 feet (4.6 meters) deep as measured from mean low water based on the identified risk. Amdt 195-82 pub. 8/10/04, eff. 9/09/04.				X
*	.413(c)	When the operator discovers that a pipeline it operates is exposed on the seabed or constitutes a hazard to navigation, does the operator: Amdt 195-82 pub. 8/10/04, eff. 9/09/04.				
*	.413(c)(1)	Promptly, but no later than 24 hours after discovery, notify the NRC by phone.				X
*	.413(c)(2)	Promptly, but not later than 7 days after discovery, mark the location of the pipeline in accordance with 33 CFR Part 64 at each end of the pipeline segment and at intervals of not over 500 yards long , except that a pipeline segment less than 200 yards long need only be marked at the center. Amdt 195-82 pub. 8/10/04, eff. 9/09/04.				X
*	.413(c)(3)	Within 6 months after discovery, or not later than November 1 of the following year if the 6 month period is after November 1 of that year the discovery is made, place the pipeline so that the top of the pipe is 36 inches below the seabed for normal excavation or 18 inches for rock excavation. Amdt 195-82 pub. 8/10/04, eff. 9/09/04.				X
	.57	Offshore pipeline condition reports - must be filed within 60 days after the inspections				X

Comments:
Team O&M inspection 04/2007

VALVE MAINTENANCE PROCEDURES			S	U	N/A	N/C
.402(a)	.420(a)	Operator must maintain each valve that is necessary for the safe operation of its pipeline system in good working order at all times.				X
	.420(b)	Operator must inspect each mainline valve to determine that it is functioning properly at intervals not exceeding 7½ months , but at least twice each calendar year.				X
	.420(c)	Operator must provide protection for each valve from unauthorized operation and from vandalism.				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

Comments:
Team O&M inspection 04/2007

PIPELINE REPAIR PROCEDURES			S	U	N/A	N/C
.402(a)	.422(a)	Operator must, in repairing its pipeline systems, insure that the repairs are made in a safe manner and are made so as to prevent damage to persons and property.				X
	.422(b)	No operator may use any pipe, valve, or fitting, for replacement in repairing pipeline facilities, unless it is designed and constructed as required by this part.				X

X
Comments:
Team O&M inspection 04/2007

PIPE MOVEMENT PROCEDURES			S	U	N/A	N/C
.402(a)	.424(a)	When moving any pipeline, the operator must reduce the pressure for the line segment involved to 50% of the MOP .				X
	.424(b)	For HVL lines joined by welding, the operator must:				
	.424(b)(1)	Move the line when it does not contain HVL , unless impractical.				X
	.424(b)(2)	Have procedures under §195.402 containing precautions to protect the public.				X
	.424(b)(3)	Reduce the pressure for the line segment involved to the lower of 50% of the MOP or the lowest practical level that will maintain the HVL in a liquid state. (Minimum = V.P. + 50 psig)				X
	.424(c)	For HVL lines not joined by welding, the operator must:				
	.424(c)(1)	Move the line when it does not contain HVL , unless impractical.				X
	.424(c)(2)	Have procedures under §195.402 containing precautions to protect the public.				X
	.424(c)(3)	Isolate the line to prevent flow of the HVL .				X

Comments:
Team O&M inspection 04/2007

SCRAPER and SPHERE FACILITY PROCEDURES			S	U	N/A	N/C
.402(a)	.426	Operator must have a relief device capable of safely relieving the pressure in the barrel before insertion or removal of scrapers or spheres.				X
		Operator must have a suitable device to indicate that pressure has been relieved, or a means to prevent insertion.				X

Comments:
Team O&M inspection 04/2007

OVERPRESSURE SAFETY DEVICE PROCEDURES			S	U	N/A	N/C

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked

If an item is marked U, N/A, or N/C, an explanation must be included in this report.

OVERPRESSURE SAFETY DEVICE PROCEDURES			S	U	N/A	N/C
.402(a)	.428(a)	Operator must inspect and test each pressure limiting device, relief valve, pressure regulator, or other items of pressure control equipment to determine that it is functioning properly, in good mechanical condition, has adequate capacity, and is reliable.				X
		Operator must inspect and test overpressure safety devices at the following intervals:				
		1. Non-HVL pipelines at intervals not to exceed 15 months , but at least once each calendar year.				X
	2. HVL pipelines at intervals not to exceed 7½ months , but at least twice each calendar year.				X	
	.428(b)	Operator must inspect and test relief valves on HVL breakout tanks at intervals not exceeding 5 years .				X
*	.428(c)	Aboveground breakout tanks that are constructed or significantly altered according to API Standard 2510 after October 2, 2000, must have an overfill protection system installed according to section 5.1.2 of API Standard 2510. Amt 195-86 pub 06/09/06 eff 07/10/06. Tanks over 600 gallons (2271 liters) constructed or significantly altered after October 2, 2000, must have overfill protection according to API Recommended Practice 2350 unless operator noted in procedures manual (§195.402) why compliance with API RP 2350 is not necessary for the safety of a particular breakout tank.				X
	.428(d)	After October 2, 2000, the requirements of paragraphs (a) and (b) of this section for inspection and testing of pressure control equipment apply to the inspection and testing of overfill protection systems.				X

Comments:

Team O&M inspection 04/2007

FIREFIGHTING EQUIPMENT PROCEDURES			S	U	N/A	N/C
.402(a)	.430	Operator must maintain adequate firefighting equipment at each pump station and breakout tank areas.				X
		The equipment must be:				
		a. In proper operating condition at all times.				X
		b. Plainly marked so that its identity as firefighting equipment is clear.				X
		c. Located so that it is easily accessible during a fire.				X

Comments:

Team O&M inspection 04/2007

BREAKOUT TANK PROCEDURES			S	U	N/A	N/C
.402(a)	.432(a)	Inspection of in-service breakout tanks. (annually/ 15mo) includes anhydrous ammonia and any other breakout tank that is not inspected per 432 (b) & (c) ;				X
	.432(b)	Each operator shall inspect the physical integrity of in-service atmospheric and low-pressure steel aboveground breakout tanks according to section 6 of API Standard 653 . However, if structural conditions prevent access to the tank bottom, the bottom integrity may be assessed according to a plan included in the operations and maintenance manual under §195.402(c)(3) . -Owner/operator visual, external condition inspection interval n.t.e. one month. (more frequent inspections may be needed based on conditions at particular sites) -External inspection, visual, by an Authorized Inspector at least every five years or at the quarter corrosion rate life of the shell, which ever is less. -External ultrasonic thickness measurement of the shell based on the corrosion rate. If the corrosion rate is not known, the maximum interval shall be five years.				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

BREAKOUT TANK PROCEDURES			S	U	N/A	N/C
*	.432(c)	Each operator shall inspect the physical integrity of in-service steel aboveground breakout tanks built to API Standard 2510 according to section 6 of API 510 . Amt 195-86 pub 06/09/06 eff 07/10/06.				X
	.432(d)	The intervals of inspection specified by documents referenced in paragraphs (b) and (c) of this section begin on May 3, 1999 , or on the operator's last recorded date of the inspection, whichever is earlier. -Based on thickness of the tank bottom and the corrosion rate but n.t.e. 20 years. Note: For Break-out tank unit inspection, refer to Breakout Tank Form				X

Comments:
Team O&M inspection 04/2007

SIGN PROCEDURES			S	U	N/A	N/C
.402(a)	.434	Operator must maintain signs visible to the public around each pumping station and breakout tank area.				X
*		Signs must contain the name of the operator and a telephone number (including area code) where the operator can be reached at all times. Amdt 195-78 pub. 9/11/03, eff. 10/14/03.				X

Comments:
Team O&M inspection 04/2007

SECURITY of FACILITY PROCEDURES			S	U	N/A	N/C
.402(a)	.436	Operator must provide protection for each pumping station and breakout tank area and other exposed facilities from vandalism and unauthorized entry.				X

Comments:
Team O&M inspection 04/2007

SMOKING OR OPEN FLAME PROCEDURES			S	U	N/A	N/C
.402(a)	.438	Operator must prohibit smoking and open flames in each pump station and breakout tank area where there is the possibility of the presence of hazardous liquids or flammable vapors.				X

Comments:
Team O&M inspection 04/2007

PUBLIC EDUCATION PROCEDURES			S	U	N/A	N/C
.402(a)	.440	Public Awareness Program in accordance with API RP 1162 [HQ clearinghouse review after June 20, 2006] Amdt 195-83 pub. 5/19/05, eff. 06/20/05.				X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

Comments:
Team O&M inspection 04/2007

DAMAGE PREVENTION PROGRAM PROCEDURES			S	U	N/A	N/C
.402(a)	.442(a)	Is there a written program in place to prevent damage by excavation activities applicable to the operator's pipelines?				X
	.442(b)	Does the operator participate in a qualified One-Call program?				X
	.442(c)(1)	Include the identity, on a current basis, of persons who normally engage in excavation activities in the area in which the pipeline is located.				X
	.442(c)(2)	Provide for notification to the public in the vicinity of the pipeline and actual notification to the persons identified in paragraph (c)(1) of this section of the following, as often as needed to make them aware of the damage prevention program:				
		i. The program's existence and purpose.				X
		ii. How to learn the location of underground pipelines before excavation activities are begun.				X
	.442(c)(3)	Provide a means of receiving and recording notification of planned excavation activities.				X
	.442(c)(4)	If the operator has buried pipelines in the area of excavation activity, provide for actual notification of persons who give notice of their intent to excavate of the type of temporary marking to be provided and how to identify the markings.				X
	.442(c)(5)	Provide for temporary marking of buried pipelines in the area of excavation activity before, as far as practical, the activity begins.				X
	.442(c)(6)	Provide as follows for inspection of pipelines that an operator has reason to believe could be damaged by excavation activities:				
		i. The inspection must be done as frequently as necessary during and after the activities to verify the integrity of the pipeline.				X
		ii. In the case of blasting, any inspection must include leakage surveys.				X

Comments:
Team O&M inspection 04/2007

CPM/LEAK DETECTION PROCEDURES			S	U	N/A	N/C
.402(a) *	.444	If a CPM system is installed, does the operator's procedures for the Computational Pipeline Monitoring (CPM) leak detection system comply with API 1130 in operating, maintaining, testing, record keeping, and dispatching training? Amt 195-86 pub 06/09/06 eff 07/10/06.				X

Comments:
Team O&M inspection 04/2007

PIPELINE INTEGRITY MANAGEMENT IN HIGH CONSEQUENCE AREAS PROCEDURES			S	U	N/A	N/C
.452	This form does not cover Liquid Pipeline Integrity Management Programs					

SUBPART G - OPERATOR QUALIFICATION PROCEDURES			S	U	N/A	N/C
.501 - .509	Refer to Operator Qualification Inspection Forms and Protocols (OPS web page)					

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

SUBPART H - CORROSION CONTROL PROCEDURES		S	U	N/A	N/C
.402(a)	.555	Do procedures require that supervisors maintain a thorough knowledge of that portion of the corrosion control procedures for which they are responsible for insuring compliance?			X
	.557	Except bottoms of aboveground breakout tanks, each buried or submerged pipeline must have an external coating for external corrosion control if the pipeline is :			
		a) Constructed, relocated, replaced, or otherwise changed after the applicable dates : 3/31/70 - interstate pipelines excluding low stress 7/31/77 -interstate offshore gathering excluding low stress 10/20/85-intrastate pipeline excluding low stress 7/11/91- carbon dioxide pipelines 8/10/94 - low stress pipelines NOTE: This does not include the movement of pipe under 195.424 .			X
		b) Converted under 195.5 and 1) Has an external coating that substantially meets 195.559 before the pipeline is placed in service or;			X
		2) Is a segment that is relocated, replaced, or substantially altered?			X
	.559	Coating Materials; Coating material for external corrosion control must: a. Be designed to mitigate corrosion of the buried or submerged pipeline; b. Have sufficient adhesion to the metal surface to prevent under film migration of moisture; c. Be sufficiently ductile to resist cracking; d. Have enough strength to resist damage due to handling and soil stress; e. Support any supplemental cathodic protection; and f. If the coating is an insulating type, have low moisture absorption and provide high electrical resistance.			X
	.561	a. All external pipe coatings required under 195.557 must be inspected just prior to lowering the pipe in the ditch or submerging the pipe.			X
		b. All coating damage discovered must be repaired.			X
	.563	a. Is cathodic protection applied to pipelines that have been subjected to the conditions listed in 195.557(a) within one (1) year?			X
		b. Each buried or submerged pipeline converted under 195.5 must have cathodic protection if the pipeline-			
		1) Has cathodic protection that substantially meets 195.571 before the pipeline is placed in service, or			X
		2) Is a segment that is relocated, replaced, or substantially altered?			X
		c. All other buried or submerged pipelines that have an effective external coating must have cathodic protection.			X
		d. Bare pipelines, breakout tank areas, and buried pumping station piping must have cathodic protection in places where previous editions of this part required cathodic protection as a result of electrical inspections.			X
		e. Unprotected pipe must have cathodic protection if required by 195.573(b) .			X
	.567	Test leads installation and maintenance.			X
	.569	Examination of Exposed Portions of Buried Pipelines.			X
*	.571	Cathodic protection must comply with one or more of the applicable criteria and other considerations for cathodic protection contained in paragraphs 6.2 and 6.3 of NACE Standard RP0169-2002 (incorporated by reference). Amt 195-86 pub 06/09/06 eff 07/10/06.			X
	.573	a. (1) Pipe to soil monitoring (annually / 15months).			X
		Separately protected short sections of bare ineffectively coated pipelines (every 3 years not to exceed 39 months).			X
*		(2) Before 12/29/2003 or not more than 2 years after cathodic protection installed, whichever comes later, identify the circumstances in which a close-interval survey or comparable technology is practicable and necessary to accomplish the objectives of paragraph 10.1.1.3 of NACE RP0169-2002 . Amt 195-86 pub 06/09/06 eff 07/10/06.			X

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

SUBPART H - CORROSION CONTROL PROCEDURES		S	U	N/A	N/C
	b. Unprotected buried or submerged pipe must be evaluated and cathodically protected in areas in which active corrosion is found as follows;				
	1) Determine areas of active corrosion by electrical survey (closely spaced pipe-to-soil survey), or where electrical survey is impractical, by other means that include review of analysis of leak repair and inspection records, corrosion monitoring records, exposed pipe inspection records, and the pipe environment			X	
	2) Before 12/29/2003 - at least once every 5 years not to exceed 63 months. Beginning 12/29/2003 - at least once every 3 years not to exceed 39 months.			X	
	c. Rectifiers, Reverse Current Switches, Diodes, Interference Bonds whose failure would jeopardize structural protection - at least 6 times each year, intervals not to exceed 2½ mos.				X
	d. Inspect each cathodic protection system used to control corrosion on the bottom of an aboveground breakout tank to ensure that operation and maintenance of the system are in accordance with API Recommended Practice 651. (Not required if it is noted in the corrosion control procedures why compliance with all or certain operation and maintenance provisions of API Recommended Practice 651 is not necessary for the safety of the tank.)				X
	e. Any deficiencies identified in corrosion control must be corrected as required by 195.401(b) .				X
.575	Are there adequate provisions for electrical isolations?				X
.577	a. For pipelines exposed to stray currents, is there a program to minimize the detrimental effects.				X
	b. Design & install CP systems to minimize effects on adjacent metallic structures.				X
.579	a. For pipelines that transport any hazardous liquid or carbon dioxide that would corrode the pipe, are corrosive effects investigated and adequate steps taken.				X
	b. Internal Corrosion - Inhibitors - do procedures show that they are to be used in conjunction with coupons or other monitoring equipment to determine the effectiveness of the inhibitors in mitigating internal corrosion.				X
	Coupons or other monitoring equipment must be examined at least 2 times each year, not to exceed 7 ½ months.				X
	c. Whenever pipe is removed from a pipeline, the internal surface of the pipe must be inspected for evidence of corrosion as well as the adjacent pipe.				X
.581	Are pipelines protected against Atmospheric Corrosion using required coating material? (See exception to this statement).				X
.583	Atmospheric corrosion monitoring -				
	ONSHORE - At least once every 3 years but at intervals not exceeding 39 months.				X
	OFFSHORE - At least once each year, but at intervals not exceeding 15 months.				X
.585	a. Are procedures in place and are they followed to either reduce the MOP , or repair/replace pipe if general corrosion has reduced the wall thickness?				X
	b. Are procedures in place and are they followed to either reduce the MOP , or repair/replace if localized corrosion has reduced the wall thickness?				X
.587	Are applicable methods used in determining the strength of corroded pipe (ASME B-31G, RSTRENG)?				X
.589	Corrosion Control Records Retention (Some are required for 5 yrs ; Some are for the service life).				X

Comments:
Team O&M inspection 04/2007
NA = ExxonMobil does not have any converted lines or separately protected short sections of bare pipe.

PART 195 - FIELD REVIEW		S	U	N/A	N/C
.262	Pumping Stations	X			
.262	Station Safety Devices	X			

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

PART 195 - FIELD REVIEW		S	U	N/A	N/C
.308	Pre-pressure Testing Pipe - Marking and Inventory	X			
.403	Supervisor Knowledge of Emergency Response Procedures	X			
.410	Right-of-Way Markers	X			
.412	ROW/Crossing Under Navigable Waters	X			
.420	Valve Maintenance	X			
.420	Valve Protection from Unauthorized Operation and Vandalism	X			
.426	Scraper and Sphere Facilities and Launchers	X			
.428	Pressure Limiting Devices	X			
.428	Relief Valves - Location - Pressure Settings - Maintenance	X			
.428	Pressure Controllers	X			
.430	Fire Fighting Equipment	X			
.432	Breakout Tanks			X	
.434	Signs - Pumping Stations - Breakout Tanks	X			
.436	Security - Pumping Stations - Breakout Tanks	X			
.438	No Smoking Signs	X			
.501-.509	Operator Qualification - Use PHMSA Form 15 Operator Qualification Field Inspection Protocol Form	X			
.571	Cathodic Protection (test station readings, other locations to ensure adequate CP levels)	X			
.573	Rectifiers, Reverse Current Switches, Diodes, Interference Bonds	X			
.575	Electrical Isolation; shorted casings	X			
.583	Exposed pipeline components (splash zones, water spans, soil/air interface, thermal insulation, disbonded coatings, supports, deck penetrations, etc.)	X			

PART 195 - PERFORMANCE AND RECORDS REVIEW		S	U	N/A	N/C
CONVERSION TO SERVICE					
.5(a)(2)	All aboveground segments of the pipeline, and appropriately selected underground segments must be visually inspected for physical defects and operating conditions which reasonably could be expected to impair the strength or tightness of the pipeline.			X	
.5(c)	Pipeline Records (Life of System)			X	
	Pipeline Investigations			X	
	Pipeline Testing			X	
	Pipeline Repairs			X	
	Pipeline Replacements			X	
	Pipeline Alterations			X	
REPORTING					
.49	Annual Report (DOT form RSPA F7000-1.1 Beginning no later than June 15, 2005)	X			
.52	Telephonic Reports to NRC (800-424-8802)	X			
.54(a)	Written Accident Reports (DOT Form 7000-1)	X			
.54 (b)	Supplemental Accident Reports (DOT Form 7000-1)	X			

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

PART 195 - PERFORMANCE AND RECORDS REVIEW		S	U	N/A	N/C
.56	Safety Related Conditions	X			
.57	Offshore Pipeline Condition Reports	X			
.59	Abandoned Underwater Facility Reports	X			
CONSTRUCTION					
.204	Construction Inspector Training/Qualification	X			
.214(b)	Test Results to Qualify Welding Procedures	X			
.222	Welder Qualification	X			
.234(b)	Nondestructive Technician Qualification	X			
.589	Cathodic Protection	X			
.266	Construction Records	X			
.266(a)	Total Number of Girth Welds	X			
	Number of Welds Inspected by NDT	X			
	Number of Welds Rejected	X			
	Disposition of each Weld Rejected	X			
.266(b)	Amount, Location, Cover of each Size of Pipe Installed	X			
.266(c)	Location of each Crossing with another Pipeline	X			
.266(d)	Location of each buried Utility Crossing	X			
.266(e)	Location of Overhead Crossings	X			
.266(f)	Location of each Valve and Test Station	X			
PRESSURE TESTING					
.310	Pipeline Test Record	X			
.305(b)	Manufacturer Testing of Components	X			
.308	Records of Pre-tested Pipe	X			
OPERATION & MAINTENANCE					
.402(a)	Annual Review of O&M Manual (1 per yr/15 months)	X			
.402(c)(4)	Determination of Areas requiring immediate response for Failures or Malfunctions	X			
.402(c)(10)	Abandonment of Facilities	X			
.402(c)(12)	Establishment/Maintaining liaison with Fire, Police, and other Public Officials	X			
.402(c)(13)	Periodic review of personnel work – effectiveness of normal O&M procedures	X			
.402(d)(1)	Response to Abnormal Pipeline Operations	X			
.402(d)(5)	Periodic review of personnel work – effectiveness of abnormal operation procedures	X			
.402(e)(1)	Notices which require immediate response	X			
.402(e)(7)	Notifications to Fire, Police, and other Public Officials of an Emergency	X			
.402(e)(9)	Post Accident Reviews	X			
.403(a)	Emergency Response Personnel Training Program	X			
.403(b)	Review of Personnel Perform., Emergency Response Program Changes (1 per yr/15 months)	X			

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
If an item is marked U, N/A, or N/C, an explanation must be included in this report.

PART 195 - PERFORMANCE AND RECORDS REVIEW		S	U	N/A	N/C
.403(c)	Verification of Supervisor Knowledge - Emergency Response Procedures	X			
.404(a)(1)	Maps or Records of Pipeline System	X			
.404(a)(2)	Maps/Records of Crossings of Roads, Railroads, Rivers, Utilities and Pipelines	X			
.404(a)(3)	MOP of each Pipeline	X			
.404(a)(4)	Pipeline Specifications	X			
.404(b)(1)	Pump Station Daily Discharge Pressure (maintain for at least 3yrs)	X			
.404(b)(2)	Abnormal Operations (§195.402) (maintain for at least 3yrs)	X			
.404(c)(1)	Pipe Repairs (maintain for useful pipe life)	X			
.404(c)(2)	Repairs to Parts of the System other than pipe (maintain for at least 1 yr)	X			
.404(c)(3)	Required inspection and test records (maintain 2 yrs or next test/inspection)	X			
.406(a)	Establishing the MOP	X			
.408(b)(2)	Filing and disposition of notices of abnormal or emergency conditions.	X			
.412(a)	Inspection of the ROW	X			
.412(b)	Inspection of Underwater Crossings of Navigable Waterways	X			
.413(b)	Gulf of Mexico/inlets: Periodic underwater inspections based on the identified risk	X			
.420(b)	Inspection of Mainline Valves	X			
.428(a)	Insp. of Overpress. Safety Devices (1 per yr/15 months non-HVL; 2 per yr/7½ months HVL)	X			
.428(b)	Inspection of Relief Devices on HVL Tanks (intervals NTE 5 yrs).			X	
.428(d)	Inspection of Overfill Systems (1 per yr/15 months non-HVL; 2 per yr/7½ months HVL)	X			
.430	Inspection of Fire Fighting Equipment	X			
.432	Inspection of Breakout Tanks (1 per yr/15 months or per API 510 or 653).	X			
.440	Public Education/Awareness Program	X			
DAMAGE PREVENTION PROGRAM					
.442(c)(1)	List of Current Excavators	X			
.442(c)(2)	Notification of Public/Excavators	X			
.442(c)(3)	Notifications of planned excavations. (One -Call Records)	X			
CORROSION CONTROL					
.555	Supervisors maintain thorough knowledge of corrosion procedures.	X			
.589(c)/.567	Test Lead Maintenance, frequent enough intervals	X			
.589(c)/.569	Inspection of Exposed Buried Pipelines (External Corrosion)	X			
.589(c)/.573(a)(1)	External Corrosion Control, Protected Pipelines Annual CP tests (1 per yr/15 months)	X			
.589(c)/.573(a)(2)	Close Interval surveys (meeting the circumstances determined by the operator)	X			
.589(c)/.573(b)	External Corrosion Control, Unprotected Pipeline Surveys, CP active corrosion areas (1 per 3 cal yr/39 months)	X			
.589(c)/.573(c)	Interference Bonds, reverse current switches, diodes, rectifiers	X			
.589(c)/.573(d)	External Corrosion Control - Bottom of Breakout Tanks	X			
.589(c)/.573(e)	Corrective actions as required by .401(b) and, if IMP pipeline, 195.452(h).	X			

STANDARD INSPECTION REPORT OF A LIQUID PIPELINE CARRIER

Unless otherwise noted, all code references are to 49CFR Part 195. S – Satisfactory U – Unsatisfactory N/A – Not Applicable N/C – Not Checked
 If an item is marked U, N/A, or N/C, an explanation must be included in this report.

PART 195 - PERFORMANCE AND RECORDS REVIEW		S	U	N/A	N/C
.589(c).575	Electrical isolation inspection and testing	X			
.589(c).577	Testing for Interference Currents	X			
.589(c).579(a)	Corrosive effect investigation	X			
.589(c).579(b)	Examination of Coupons/Other Types of Internal Corrosion Monitoring Equipment (2 per yr/7 ½ months)	X			
.589(c).579(c)	Inspection of Removed Pipe for Internal Corrosion	X			
.589(c).583(a)	Atmos. Corr. Monitoring (1 per 3 cal yr/39 months onshore; 1 per yr/15 months offshore)	X			
.589(c).585(a)	General Corrosion – Reduce MOP or repair ; ASME B31G or RSTRENG	X			
.589(c).585(b)	Localized Corrosion Pitting – replace, repair, reduce MOP	X			
.589(a)&(b)	Cathodic Protection (Maps showing anode location, test stations, CP systems, protected pipelines, etc.)	X			

Comments:
 NA = Operator has no conversion of service pipe & no atmospheric pressure or HVL breakout tanks in this unit.

Recent PHMSA Advisory Bulletins (Last 2 years)

Leave this list with the operator.

<u>Number</u>	<u>Date</u>	<u>Subject</u>
ADB-05-02	April 6, 2005	Pipeline Safety: Strapping Table Calibration for Pipeline Breakout Tank Operators
ADB-05-03	May 23, 2005	Pipeline Safety: Planning for Coordination of Emergency Response to Pipeline Emergencies
ADB-05-04	July 29, 2005	Integrity Management Notifications for Gas Transmission Lines
ADB-05-05	August 10, 2005	Pipeline Safety Advisory Bulletin - Inspecting and Testing Pilot-Operated Pressure Relief Valves
ADB-05-06	August 11, 2005	ADB-05-06 - Pipeline Safety - Countermeasures to Prevent Human Fatigue in the Control Room
ADB-05-07	September 7, 2005	Pipeline Safety Advisory - Potential for damage to Natural Gas Distribution Pipeline Facilities Caused by the Passage of Hurricane Katrina
ADB-05-08	September 7, 2005	Pipeline Safety Advisory - Potential for damage to Pipeline Facilities Caused by the Passage of Hurricane Katrina
ADB-06-01	January 17, 2006	Pipeline Safety: Notice to Operators of Natural Gas and Hazardous Liquid Pipelines To Integrate Operator Qualification Regulations into Excavation Activities
ADB-06-02	June 16, 2006	Submission of Public Awareness Programs for Review
ADB-06-03	November 22, 2006	Pipeline Safety-Notice to Operators of Natural Gas and Hazardous Liquid Pipelines to Accurately Locate and Mark Underground Pipelines Before Construction-Related Excavation Activities Commence Near the Pipelines
ADB-06-04	December 28, 2006	Pipeline Safety: Lessons Learned From a Security Breach at a Liquefied Natural Gas Facility

For more PHMSA Advisory Bulletins, go to <http://ops.dot.gov/regs/advice.htm>

IOCS Inspection Summary

Activity ID: 118626

Handwritten initials/signature

Activity ID	Type	From / To Dates	Status:	Result:	AFO / Total Days:
118626	I01 UNIT INSPECTION	02/15/2007 - 09/21/2007	INC		5.50 5.50

OPS Representative:
ARNOLD, JIM

JIM

Comments:

THIS UNIT NOW HAS 267.0 MILES OF DOT LINE FROM THE TEXAS/ARKANSAS STATE LINE UNDER JURISDICTION OF THE CORSICANA TEAM. THIS UNIT WILL BE MERGED INTO UNIT # 9744 WHICH HAS ONLY 99.0 MILES OF JURISDICTIONAL PIPE GIVING THIS UNIT A TOTAL OF 366.0 MILES OF PIPELINE RUNNING FROM THE TEXAS/ARKANSAS STATE LINE TO THE SUN TERMINAL IN BEAUMONT TEXAS.

Portion Inspected:

INSPECTED FIELD RECORDS OF THE FOLLOWING SYSTEM. 159 MILES OF 20" CRUDE (#1) FROM CORSICANA TEXAS TO THE TEXAS/ARKANSAS STATE LINE. FIELD INSPECTION CONSISTED OF MAINLINE VALVES, OVER PRESSURE PROTECTION EQUIPMENT, RECTIFIERS, EXPOSED PIPE, AND ROW CONDITIONS. LOCATIONS INSPECTED WERE MLV MP 14.97, 20" GATE VALVE. MLV MP 21.39, 20" GATE VALVE & RECTIFIER. MLV MP 27.49, 20" GATE VALVE. MLV MP 41.07, 20" GATE VALVE & RECTIFIER. MLV MP 56.90, 20" GATE VALVE & RECTIFIER. MLV MP 66.64, 20" GATE VALVE. MLV MP 71.46, 20" GATE VALVE. MLV MP 78.77, 20" GATE VALVE. MLV MP 82.75 & 82.85 @ QUITMAN PUMP STATION (IDLE). MLV MP 159.27, 20" GATE VALVE. MLV MP 134.65, 20" GATE VALVE. MLV MP 127.88, 20" GATE VALVE. EXPOSED PIPE @ MP 124.0. MLV MP 98.51 & 98.46 @ WINNSBORO PUMP STATION (IDLE), 20" GATE VALVES. MLV MP 22.24, 20" GATE VALVE. MLV MP 15.08, 20" GATE VALVE. MLV MP 11.03, 20" GATE VALVE. MLV MP 00.01 & 00.02, 20" GATE VALVES @ THE CORSICANA STATION. MLV MP 30.06 & 30.18, 20" GATE VALVES @ THE FAIRFIELD STATION. MLV MP 42.60, 20" GATE VALVE. MLV MP 55.04, 55.38 & 57.96, 20" GATE VALVES @ CARTER RANCH. MLV MP 62.31 & 62.41, 20" GATE VALVES @ GRAPELAND STATION. MLV MP 99.5, 20" GATE VALVE. MLV MP 108.5, 20" GATE VALVE. MLV MP 108.11, 20" GATE VALVE.

RANK / YEAR
17 2007

Assignments:

Name	Region	Task(s)	From / To Dates	AFO/Total Days
ARNOLD, JIM	SW	INSPECTION	09/17/2007 09/21/2007	5.00 5.00
STANDARD INSPECTION OF EXXONMOBILE PIPELINE.				
ARNOLD, JIM	SW	INSPECTION	02/15/2007 02/15/2007	.50 .50
SCHEDULING STANDARD INSPECTION DATES				

Operator Name and Address

12628 EXXONMOBIL PIPELINE CO
800 BELL STREET
P.O. BOX 2220
HOUSTON, TX 77002-7002
TUDOR, MIKE
PRESIDENT

Jim Arnold 11/8/07

Phone: 713/656-5056 Fax: 713/656-9579

IOCS Inspection Summary

Activity ID: 118626

Unit Name and Address

3944 CORSICANA AREA - IDLE
P. O. BOX 618
CORSICANA, TX 75151-5151

Region

SW

Insp Plan

ONSHORE

Jurisdiction:

FEDERAL

Pipeline Type

1 INTERSTATE LIQUID

A01

Emergency Phone: 214/742-3106

Records: CORSICANA

Location:

CORSICANA, TX

Pipeline Description:

159 MILES OF 20" CRUDE (#1) CORSICANA TO THE TEXAS/ARKANSAS STATE LINE. THE 20" LINE IS NO LONGER IDLED. THE LINE WAS REACTIVATED IN MARCH 2006 TRANSPORTING HEAVY CANADIAN CRUDE FROM ILLINOIS TO BEAUMONT TEXAS.

Comments:

REMOVED THE 188 MILES OF 16" AND THE 104 MI OF 12" FROM THIS INSPECTION UNIT. IT IS NOW UNDER INSPECTION UNIT 65634 (SEE UNIT #65634 FOR ADDITIONAL INFORMATION). EFFECTIVE AUGUST 1, 2005, SUNOCO PIPELINE L.P. ACQUIRED FROM MOBIL PIPELINE COMPANY 187 MILES OF 16" PIPE AND 104 MILES OF 12" PIPE. VALIDATE THE INFORMATION IN IOCS.

Summary:

EXXONMOBIL PIPELINE SEEMS TO BE MAKING A REASONABLE EFFORT TO OPERATE IN COMPLIANCE WITH THE CODE. NO INCREASE IN INSPECTION FREQUENCY RECOMMENDED. NO POTENTIAL VIOLATIONS OBSERVED DURING THIS AUDIT.

Findings:

ALL MLV SITES WERE SECURED WITH EITHER A PIPE FENCE OR A 8' CHAIN LINK FENCE. A REVIEW OF JURISDICTIONAL PIPE IN THIS UNIT REVEALED 267 MILES TOTAL. THE BEAUMONT UNIT # 9744 (99 MILES) SHOULD BE MERGED INTO THE CORSICANA AREA UNIT # 3944 AND COULD BE INSPECTED IN A WEEK. THE CORSICANA TEAM WOULD TAKE OVER AT GROVETON STATION AND CONTINUE TO THE ARKANSAS/TEXAS LINE WITH ABOUT 366 TOTAL MILES TO BE INSPECTED. FOUND AN INCORRECT LINE MARKER AT MP 21.39 (CORRECTED DURING INSPECTION). VALVE INDICATOR AT MLV MP 56.90 WAS BROKEN (CORRECTED DURING INSPECTION). EXPOSED PIPE AT MP 124.0 SHOWED IN NEED OF ATTENTION AND SHOULD BE BRACED BETTER. OPERATOR ASSURED DOT THIS WOULD BE CORRECTED.