



Engineer Research and
Development Center

GenCade Applications

Ashley Frey

Research Civil Engineer, Co-PI of the Inlet
Engineering Toolbox work unit of CIRP



**US Army Corps
of Engineers®**



Documentation

- Long Island, NY
- Onslow Bay, NC
- St. Johns County, FL
- Sargent Beach, TX
- Matagorda Peninsula, TX



Beaufort Inlet, NC




BUILDING STRONG®



Innovative solutions for a safer, better world

Point Lookout, NY – Study Area



BUILD




GenCade



world

Point Lookout, NY – Model Setup

Modified Wave input to account for shoaling and sheltering



ERDC

Innovative solutions for a safer, better world

Point Lookout, NY - Results

1994 Shoreline Comparison




BUILDING STRONG®

Point Lookout, NY - Results

Modeling Results

Existing



Results of Alternatives

- a) No action is not feasible for the SDR Project requirements
 - I. Two additional groins had greatest effect on shoreline position, with little difference between the full length and shortened groins
 - II. Four groins show greater shoreline accretion across Hempstead Beach, providing long-term stability for the erosion hotspot
 - III. Terminal groin extension provides additional sand retention
 - IV. Reoccurring nourishments are critical to project success
- b) Long-term stability of shoreline at erosional hotspot can be mitigated with frequent nourishments. Structures spanning the erosional area were modeled and found to increase accretion at the shoreline, suggesting structures will best mitigate shoreline control.
- c) GenCade was successful in evaluating long-term effects to the shoreline for the 50-year planning period

Onslow Bay, NC – Problem Statement

Use GenCade to

- Improve understanding of the regional sediment system
- Provide information for a sediment budget



Bogue Banks near Bogue Inlet



Fort Fisher Revetment



North weir jetty at Masonboro Inlet




BUILDING STRONG®

ERDC

Innovative solutions for a safer, better world

Onslow Bay, NC - Overview






BUILDING STRONG®

Innovative solutions for a safer, better world

Onslow Bay - Procedure

Inputs:


Grid spacing = 300 ft
 Shorelines: 1997 and 2004
 1980-1999 WIS wave data
 Grain size = 0.17mm
 Berm height = 4.5 ft (MHW)
 Closure depth = 26.5 ft (MHW)
 Q parameters: $K1=0.6$; $K2=0.4$
 Validation period: 1997-2004
 with composite wave data.



U.S. Survey Feet
0 10000



Secondary - East Grid Setup




Beaufort Inlet 1997 initial shoal volume estimated by subtracting yearly shoal volume change calculated by Olsen (2006) from the volume of the 2004 survey

Used USACE published beach fill volumes



Used yearly maintenance dredging records and split volumes into East and West bypassing bars

Beach Location	Date	Added Berm width (ft)
Fort Macon	2002	37.0
Pine Knoll Shores	2002	40.0
Indian Beach	2002	57.0
Emerald Isle (phase 2)	2003	51.0

	Outer channel dredging (cy)	From west byp. bar (70%, cy)	From east byp. bar (30%, cy)
1997	267,655	187,359	80,297
1998	2,240,267	1,568,187	672,080
1999	1,040,919	728,643	312,276
2000	1,701,659	1,191,161	510,498
2001	834,645	584,252	250,394
2002	861,074	602,752	258,322
2003	1,144,987	801,491	343,496
2004	813,119	569,183	243,936
Yearly average:	1,113,041	779,128	333,912



Representation of Beaufort Inlet in GenCade




- Estimated ebb shoal volume in 1900: 58.4 Mcy
- Estimated ebb shoal volume in 2004: 37.4 Mcy
- Channel depth in 1900 was 15 ft (MLW); dredged to 47 ft since 1994.
- Yearly average maintenance dredging 1 Mcy; all disposed offshore until 1997.



Primary Grid Setup

- Almost no data on this stretch of coast
- 7 Inlets all at equilibrium
- Includes 3 beach fills on Bogue Banks
- Gated BC at Masonboro north jetty
- Dredging of Rich Inlet



Beach Location	Date	Added Berm width (ft)
Pine Knoll Shores	2002	40.0
Indian Beach	2002	57.0
Emerald Isle (Phase 2)	2003	51.0


Inlet	Date	Volume Dredged, cy
Rich Inlet	1999	200,000
	2002	250,000
	2003	90,000

Secondary - West Grid Setup

Inlet	Date	Volume dredged cy
Carolina Beach Inlet	1997	50,500
Carolina Beach Inlet	1998	1,525,500
Masonboro Inlet	1998	1,672,200
Carolina Beach Inlet	1999	188,000
Rich Inlet	1999	200,000
Carolina Beach Inlet	2000	188,000
Carolina Beach Inlet	2001	1,188,000
Carolina Beach Inlet	2002	188,000
Rich Inlet	2002	250,000
Masonboro Inlet	2002	1,302,500
Carolina Beach Inlet	2003	188,000
Rich Inlet	2003	90,000
Carolina Beach Inlet	2004	1,392,700



Location	Date	Added Berm Width (ft)
Kure Beach	1997	159.68
Kure Beach	1998	58.06
Wrightsville Beach	1998	95.34
Masonboro Island	1998	40.33
Carolina Beach	1998	94.52
Figure Eight Island	1999	38.71
Figure Eight Island	1999	38.71
Carolina Beach	2001	78.47
Figure Eight Island	2002	48.44
Figure Eight Island	2002	48.44
Wrightsville Beach	2002	67.97
Figure Eight Island	2003	17.42
Kure Beach	2004	9.19
Carolina Beach	2004	53.36

- 4 inlets
- Masonboro with north weir jetty
- Dredging of Rich, Masonboro and Carolina Beach Inlets
- Includes Fort Fisher revetment and Carolina Beach seawall





Rich Inlet
Mason Inlet
Masonboro Inlet
Carolina Beach Inlet
Carolina Beach seawall
Ft. Fisher revetment

Results: Secondary-East Grid



	Skill Score	Secondary-East Grid
Final Shoreline		
	BSS	0.63
	RMSE (ft)	16.5
	Bias (ft)	40.5
Shoreline Change	R ²	0.83


Results: Primary Grid



	Skill Score	Primary grid
Final Shoreline		
	BSS	0.37
	RMSE (ft)	-6.64
	Bias (ft)	55.6
Shoreline Change	R ²	0.70

Innovative solutions for a safer, better world

Results: Secondary-West Grid



	Skill Score	Secondary-West Grid
Final Shoreline		
	BSS	0.71
	RMSE (ft)	6.6
	Bias (ft)	67.0
Shoreline Change	R ²	0.84




BUILDING STRONG®



Innovative solutions for a safer, better world

Mean Transport, 1980-1999



Onslow Bay, NC - Summary

- Goodness of fit of the calculated shoreline (1997-2004) ranges from 0.37 to 0.71 (Brier Skills Score) with correlation coefficients (R^2) ranging from 0.70 to 0.84.
- Results from the 20 year simulation indicate a gross mean sand transport on the order of 1,000,000 cy/yr consistently across all of Onslow Bay. The net transport is generally small, less than 200,000 cy/yr, and directed to the northeast from New River Inlet to Beaufort Inlet and to the southwest for the southern half of the bay.
- Results indicate Beaufort Inlet is a convergent nodal point, meaning the net sand transport is into the inlet shoals (or into the bay) on both sides of the inlet. Hence, dredging of the shoal should have minimal net impact to adjacent beach.



St. Johns County, FL – Problem Statement

What is the optimal dredging volume and interval, and beach placement volume and interval that will supply adequate sand to maintain two Shore Protection Projects in St. Johns County?



GenCade used to help answer:

What is the volumetric limit (cubic yards of sediment) that can be mined regularly from the ebb shoal in its present condition which does not cause a significant long-term effect on the morphology and volumetric recovery of the shoal?

How much sediment and what nourishment interval is required to maintain present volume of the active and planned Shore Protection Projects?



St. Johns County, FL – GenCade Grid Setup



Input:

- 1986, 1999 Shorelines
- Waves
- Dredging/Placement Information
- Structures

Model Calibration Also Dependent On:

- Equilibrium Shoal Volumes
- Inlet Bypassing Rates & Locations
- Regional Contour
- Interpolation of Waves Between Gage Stationing





BUILDING STRONG®



Innovative solutions for a safer, better world

St. Johns County, FL – Ebb-Tidal Delta Volume Change



BUILDING STRONG®

Innovative solutions for a safer, better world



St. Johns County, FL - Results Plotted on SMS Grid



BUILDING STRONG®

Innovative solutions for a safer, better world

St. Johns County, FL – Volumetric Results




BUILDING STRONG®


Innovative solutions for a safer, better world

St. Johns County, FL - Summary

- The performance and estimate of certainty in GenCade as a sediment management planning tool is relative to the accuracy of the calibration. Furthermore, extensive analysis of measured data must be performed to properly inform the model on realistic bounds in a 3-dimensional morphologic environment.
- Though not all 3-dimensional morphologic processes are represented in the model, most general inferences about sediment transport and bypassing within the coastal zone can be applied to calculating future sediment budgets with GenCade.
- The benefits of coordinating and modifying dredging intervals can be explored simultaneously with varying beach fill volumes and intervals.
- The greatest benefit lies in determining optimal mobilization periods and coordinating regional efforts to save in mobilization and demobilization costs for dredging and beach fill placement.



Overview – Sargent Beach and Matagorda Peninsula, TX




BUILDING STRONG®



Innovative solutions for a safer, better world

Calibration – Sargent Beach and Matagorda Peninsula



GenCade Input

- 1995 and 2000 shorelines
- Waves (WIS 73060, 73058, 73055, 73053)
- Sargent Beach revetment
- Mitchell's Cut and Mouth of the Colorado River




BUILDING STRONG®



Innovative solutions for a safer, better world

Sargent Beach and Matagorda Peninsula: Net Transport





BUILDING STRONG®



Innovative solutions for a safer, better world

Sargent Beach and Matagorda Peninsula: 1995-2000 Measured Shoreline Change



BUILDING STRONG®

Innovative solutions for a safer, better world

Sargent Beach - Problem Statement

- Sargent Beach – fastest eroding beach in Texas

Determine feasibility of structural solutions to reduce erosion

- protect the beach habitat
- protect Gulf Intracoastal Waterway

Refined problem statement in Phase 2

- segmented breakwaters
- adaptive and scalable plan
- minimal downdrift impacts
- multiple layouts to accommodate incremental funding




BUILDING STRONG®

ERDC

Innovative solutions for a safer, better world

Sargent Beach Alternatives



Sargent Beach alternatives use shorter grid than calibration

Breakwater alternatives required shorter grid due to computational time

Alt 0: No Action

Alt 1: 3,000,000 cubic yard beach fill

Alt 2: Single Groin

Alt 3: Groin Field

Alt 4: Breakwaters

Phase 1: 10 Breakwaters;
220 ft Breakwaters;
330 ft Gaps

Phase 2: 15 Breakwaters

Final Phase: 81 Breakwaters




BUILDING STRONG®

ERDC



Innovative solutions for a safer, better world

Sargent Beach Alternatives

Alt 0:
No Action



- About 6 miles of shoreline recedes to revetment after 5 years
- Gross transport about 400,000 cy/yr over entire domain




BUILDING STRONG®



Innovative solutions for a safer, better world

Sargent Beach Alternatives


Alt 1



Alt 1: 3 million cubic yard beach fill over 10 miles

Placement density of 57 cy/linear foot

Added berm width of 100 ft



Beach fill does not increase beach width

Additional nourishments required to protect the beach (not cost effective)




BUILDING STRONG®



Innovative solutions for a safer, better world

Sargent Beach Alternatives




Alt 2: Single Groin East of Mitchell's Cut plus Beach Fill

Beach Fill identical to Alt 1

Unrealistically long groin to demonstrate maximum trapping capacity

Alt 2a: Single Groin Only



Groin does not have impact on shoreline change northeast of 57+000 ft

Northeast of 57+000 ft, Alt 2 is identical to Alt 1 and Alt 2a is identical to Alt 0




BUILDING STRONG®



Innovative solutions for a safer, better world

Sargent Beach Alternatives




Alt 3: Groin Field plus Beach Fill

Beach fill identical to Alt 1

Includes 28 groins of 600 ft spaced 1800 ft apart

Alt 3a: Groin Field Only



Groin field has little effect on shoreline in front of revetment

Groin protects shoreline at northern end of revetment, but recedes to almost same location as Alt 0 along most of the revetment




BUILDING STRONG®



Innovative solutions for a safer, better world



Sargent Beach Alternatives



Alt 4: 10 breakwaters placed at 350 ft offshore

Breakwater length = 220 ft


Gap size = 330 ft



BUILDING STRONG®

Innovative solutions for a safer, better world



Sargent Beach Alternatives



Alt 4, Phase 2: 15 breakwaters placed at 350 ft offshore

Breakwater length = 220 ft

Gap size = 330 ft




BUILDING STRONG®



Innovative solutions for a safer, better world



Sargent Beach Alternatives



Alt 4, Phase 3: 81 breakwaters placed at 350 ft offshore

Breakwater length = 220 ft

Gap size = 330 ft



Sargent Beach, TX - Summary

The best structural alternative at Sargent Beach is breakwaters

Multiple offshore distances and depths were tested with the breakwaters at Sargent Beach

Several phases were simulated for selected Sargent Beach breakwater setup

Mitigation beach fill necessary southwest of Mitchell's Cut for Sargent Beach breakwaters



BUILDING STRONG®

ERDC

Innovative solutions for a safer, better world

Matagorda Peninsula - Problem Statement

- Matagorda Peninsula – breached by ephemeral inlets in past

Determine feasibility of structural solutions to reduce erosion

- protect beach habitat
- reduce storm damage
- reduce sediment impoundment along the MCR east jetty

Refined problem statement in Phase 2

- groin field between 3 Mile Cut and MCR
- project goal to widen beach by 200 ft
- design so project does not impact 3 Mile Cut




BUILDING STRONG®

ERDC

Innovative solutions for a safer, better world

Matagorda Peninsula Alternatives



- Grid extends from 3.3 miles southwest of Mitchell's Cut to southwest of MCR
- 28 miles long
- Smaller cell size between 3 Mile Cut and MCR
- 5 and 16 year long simulations




BUILDING STRONG®



Innovative solutions for a safer, better world

Matagorda Peninsula Alternatives



Alt 1: Alignment, 300 ft long,
800 ft spacing





BUILDING STRONG®

ERDC

Innovative solutions for a safer, better world

Matagorda Peninsula Alternatives



No beach fills
115,000 cy/yr of bypassing
around MCR
 $P = 0.3$




BUILDING STRONG®




Innovative solutions for a safer, better world

Matagorda Peninsula Alternatives

After 5 Years



After 16 Years





Based on preliminary simulations, Alt 5 was selected as the design alternative
Additional variations of Alt 5 were simulated



BUILDING STRONG®

Innovative solutions for a safer, better world

Matagorda Peninsula – Alt 5



Matagorda Peninsula – Alt 5 Comparison



P = 0.3 for final design

Compare No Action to
Alt 5 (no beach fill or bypassing)


After 5 years, greatest accretion to
northeast of first groin (less than 100 ft)

After 16 years, about 200 ft of accretion
northeast of first groin

After 16 years, almost 300 ft of shoreline
advance northeast of MCR




Matagorda Peninsula – Alt 5



- Bypassing between 0 and 200,000 cu/yr may provide best result

- With 200,000 cu/yr of bypassing, erosion occurs with and without beach fills
- All cases result in accretion northeast of first groin



Matagorda Peninsula - Summary

Shifting the groin field to the southwest significantly improved the results

Of the groin configurations modeled at Matagorda Peninsula, three groins of 800 ft spaced 1600 ft apart produced the best results

The rate of bypassing and the construction of a beach fill affects the shoreline change in the area



BUILDING STRONG®



Innovative solutions for a safer, better world