

NIJ
DEDORT

Special

Test Results for Forensic Media Preparation Tool: Voom HardCopy II (Model XLHCPL-2PD Version 1-11)

National Institute of Justice Website

U.S. Department of Justice Office of Justice Programs

810 Seventh Street N.W. Washington, DC 20531

Eric H. Holder, Jr.
Attorney General

Laurie O. Robinson

Acting Assistant Attorney General

Kristina Rose

Acting Director, National Institute of Justice

This and other publications and products of the National Institute of Justice can be found at:

National Institute of Justice

National Institute of Justice Website

Office of Justice Programs

Innovation • Partnerships • Safer Neighborhoods
Office of Justice Programs Website



JAN. 10

Test Results for Forensic Media Preparation Tool: Voom HardCopy II (Model XLHCPL-2PD Version 1-11)



Kristina Rose

Acting Director, National Institute of Justice

This report was prepared for the National Institute of Justice, U.S. Department of Justice, by the Office of Law Enforcement Standards of the National Institute of Standards and Technology under Interagency Agreement 2003–IJ–R–029.

The National Institute of Justice is a component of the Office of Justice Programs, which also includes the Bureau of Justice Assistance, the Bureau of Justice Statistics, the Office of Juvenile Justice and Delinquency Prevention, and the Office for Victims of Crime.

Test Results for Forensic Media Preparation Tool: Voom HardCopy II (Model XLHCPL-2PD Version 1-11)



This page intentionally left blank.

Contents

1.	Resu	ılts Summary	. 2
2.		Case Selection	
3.	Test	Materials.	. 3
	3.1	Support Software	. 3
	3.2	Test Drive Creation	. 3
	3.3	Test Drive Analysis	. 3
	3.4	Test Drives	. 4
4.	Test	Results	. 4
	4.1	Test Results Report Key	. 4
	4.2	Test Details	. 5
	4.2.1	I FMP-01-ATA28	. 5
	4.2.2	2 FMP-01-ATA48	. 7
	4.2.3	3 FMP-01-SATA28	. 8
	4.2.4	4 FMP-01-SATA48	. 9
	4.2.5	5 FMP-03-DCO	10
	4.2.6	5 FMP-03-DCO+HPA	11
	4.2.7	7 FMP-03-HPA	12

This page intentionally left blank.

Introduction

The Computer Forensics Tool Testing (CFTT) program is a joint project of the National Institute of Justice (NIJ), the research and development organization of the U.S. Department of Justice (DOJ), and the National Institute of Standards and Technology's (NIST's) Office of Law Enforcement Standards and Information Technology Laboratory. CFTT is supported by other organizations, including the Federal Bureau of Investigation, the U.S. Department of Defense Cyber Crime Center, U.S. Internal Revenue Service Criminal Investigation Division Electronic Crimes Program, and the U.S. Department of Homeland Security's Bureau of Immigration and Customs Enforcement, U.S. Customs and Border Protection, and U.S. Secret Service. The objective of the CFTT program is to provide measurable assurance to practitioners, researchers, and other applicable users that the tools used in computer forensics investigations provide accurate results. Accomplishing this requires the development of specifications and test methods for computer forensics tools and subsequent testing of specific tools against those specifications.

Test results provide the information necessary for developers to improve tools, users to make informed choices, and the legal community and others to understand the tools' capabilities. The CFTT approach to testing computer forensic tools is based on well-recognized methodologies for conformance and quality testing. The specifications and test methods are posted on the CFTT Web site for review and comment by the computer forensics community.

This document reports the results from testing Voom Hardcopy II, against the *Forensic Media Preparation Tool Test Assertions and Test Plan Version 1.0*, available at the CFTT Web site.

Test results for other devices and software packages using the CFTT tool methodology can be found on NIJ's computer forensics tool testing Web page.

Test Results for Forensic Media Preparation Tool

Tool Tested: Voom HardCopy II

Version: 1–11
Serial No. A001256
Run Environments: Custom

Supplier: Voom Technologies, Inc.

110 St. Croix Trail South Lakeland, Minnesota 55043

Tel: 651–998–1618

651–436–4030 (fax)

Email: <u>Voom Technologies email address</u>
WWW: <u>Voom Technologies Website</u>

1. Results Summary

In all the test cases run against Voom HardCopy II Version 1–11, all visible sectors were successfully overwritten. For the test cases that used destination drives containing an HPA or DCO, the tool behaved as designed by the vendor. It removed any HPA or DCO and overwrote the sectors with zeros.

2. Test Case Selection

Voom HardCopy II was tested for its ability to overwrite sectors. The test cases selected were limited to only those test cases defined by *Forensic Media Preparation Tool Test Assertions and Test Plan Version 1.0* and applicable to features supported by this tool.

Since Voom HardCopy II does not support a secure erase mode those tests were omitted; All selected test cases were *WRITE* tests (cases FMP–01 and FMP–03).

Three hidden sector test cases (FMP–03) were included among the cases selected. They were included to measure the tool behavior in conjunction with hidden sectors.

The following cases were used in testing Voom HardCopy II:

- FMP-01-ATA28
- FMP-01-ATA48
- FMP-01-SATA28
- FMP-01-SATA48
- FMP-03-DCO
- FMP-03-DCO+HPA

• FMP-03-HPA

The following source interfaces were tested: ATA28, ATA48, SATA28, SATA48.

3. Test Materials

3.1 Support Software

Several programs were used in the setup and analysis of the test drives. These include **hdat2** (download from: hdat2 download page, **dsumm** (download from: CFTT Project Website) and the **diskwipe** program from **FS-TST Release 2.0** (download from: CFTT fs-tst20.zip download page).

The **hdat2** program is used to create, remove and document hidden areas on a drive.

The **diskwipe** program initializes the hard drive with known content.

The **dsumm** program analyzes the content of a hard drive. It produces a summary of disk contents in terms of counts for each byte value present on the drive. For example, if a drive can contain 10GB (19531250 sectors of 512 bytes per sector) and the drive is wiped with zero bytes, then **dsumm** reports 10,000,000,000 zero bytes. The program also prints the first sector found with printable ASCII content.

3.2 Test Drive Creation

The following steps are used to setup a test drive:

- 1. The drive is initially filled with known content by the **diskwipe** program. The **diskwipe** program writes the sector address to each sector in both C/H/S and LBA format. The remainder of the bytes in each sector is set to a constant fill value unique for each drive. The fill value is noted in the **diskwipe** tool log file.
- 2. The **dsumm** program is run to capture and analyze the drive content. Each sector has unique content after the drive setup is complete.
- 3. If the destination drive is intended for a hidden area test (FMP–03), an HPA, a DCO or both are created.
- 4. The drive size after creation of a hidden area is recorded.

3.3 Test Drive Analysis

The following steps are used to analyze a test drive after it has been wiped by the tool under test:

1. The size of the drive is recorded. This determines if the tool changes the size of a hidden area.

- 2. Any hidden areas still present on the drive are removed.
- 3. The **dsumm** program is run to determine the final content of the drive.

3.4 Test Drives

The following hard drives were used in testing. The column labeled **Test Case** identifies the test case. The column labeled **Sectors** is the size of the drive with no DCO or HPA. The column labeled **Model** is the model of the drive as returned by the ATA IDENTIFY DEVICE command. The column labeled **Serial** # is the serial number as returned by the ATA IDENTIFY DEVICE command.

Test Case	Sectors	Model	Serial #
FMP-01-ATA28	156301488	WDC WD800BB-75CAA0	WD-WMA8E2108916
FMP-01-ATA48	488397168	WDC WD2500JB-00GVC0	WD-WCAL78188039
FMP-01-SATA28	234441648	WDC WD1200JD-00GBB0	WD-WMAES2049679
FMP-01-SATA48	312581808	ST9160310AS	5SV092JK
FMP-03-DCO	78140160	FUJITSU MHW2040BH	K10XT7B278AP
FMP-03-DCO+HPA	490234752	Maxtor 7Y250P0	Y63FSHTE
FMP-03-HPA	312581808	WDC WD1600JB-00GVC0	WD-WMAL94865344

For FMP-03 test cases the layout of visible and hidden sectors is as follows. The column labeled Test Case identifies the test case. The column labeled Size is the number of visible sectors presented to the device for the test case. The column labeled **Hidden** is the size in sectors of the hidden area.

Test Case	Size	Total	Hidden (DCO+HPA)
FMP-03-DCO	7814016	78140160	70326144
FMP-03-DCO+HPA	465234752	490234752	25000000 (10000000+15000000)
FMP-03-HPA	46887271	312581808	265694537

4. Test Results

The main item of interest for interpreting the test results is determining the conformance of the tool under test with the test assertions. Conformance with each assertion tested by a given test case is evaluated by examining the Log Highlights box of the test report summary.

4.1 Test Results Report Key

A summary of the actual test results is presented in this report. The following table presents a description of each section of the test report summary.

Heading	Description	
First Line:	Test case ID, name, and version of tool tested.	
Case Summary:	Test case summary from Forensic Media Preparation Tool Test	
	Assertions and Test Plan Version 1.0.	

4

Heading	Description	
Assertions:	The test assertions applicable to the test case, selected from	
	Forensic Media Preparation Tool Test Assertions and Test Plan	
	Version 1.0.	
Tester Name:	Name or initials of person executing test procedure.	
Analysis Host:	Host used to setup test drive and analyze final drive state.	
Test Host:	Host computer executing the test.	
Test Date:	Time and date that test was started.	
Test Drive:	Drive erased by the tool under test.	
Source Setup:	Report of the native drive size, the size of any hidden areas, the	
	apparent size of the drive (as reported by an ATA IDENTIFY	
	DEVICE command) and an analysis of initial drive contents.	
Log Highlights:	Report of the state of the drive after executing the tool under test,	
	including the apparent drive size, size of hidden area and analysis	
	of drive contents. The ASCII content of the first nonbinary-zero	
	sector is reported.	
Results:	Expected and actual results for each assertion tested.	
Analysis:	Whether or not the expected results were achieved.	

4.2 Test Details

4.2.1 FMP-01-ATA28

Test Case FMP-01-ATA28 Voom HardCopy II Version 1-11			
Case Summary:	FMP-01. Overwrite visible sectors using WRITE commands.		
Assertions:	FMP-CA-01 All visible sectors shall be overwritten with the specified		
	benign data.		
Tester Name:	csr		
Analysis	frank		
host:			
Test host:	none		
Test date:	Mon Jul 27 16:54:04 2009		
Test drive:	56-IDE		
Source Setup:	<pre>Initial setup size: 156301488 from total of 156301488 (with 0 hidden) IDE disk: Model (WDC WD800BB-75CAA0) serial # (WD-WMA8E2108916)</pre>		
	Sector 0 is first sector with printable text		
	======= Start text ========		
	00000/000/01 00000000000000000000000000		
	\(VVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVV		
	\(VVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVV		
	VVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVV		
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
			VVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVVV
	======= End text Sector 0 =======		
	9 <new line=""> characters inserted for readability</new>		
Totals for all sectors			
	summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	156301488 00 156301488 20 () 312602976 2F (/)		
	1092738319 30 (0) 445157427 31 (1) 274740905 32 (2)		

Test Case FMP-	-01-ATA28 Voom HardCopy II Version 1-11	
	274642393 33 (3) 272159917 34 (4) 225709546 36 (6) 215483146 37 (7) 215483135 39 (9) 75907021680 56 (V) Totals for non-ASCII sectors summary format: <count> <hex value=""> <(a 80026361856 bytes, 156301488 sectors, 1 156301488 sectors have printable text</hex></count>	215483143 38 (8) ctual character if printable)>
Log Highlights:	Size after tool runs: 156301488 from total of 156301488 (with 0 hidden) Analysis of tool result Totals for all sectors summary format: <count> <hex value=""> <(actual character if printable)> 80026361856 00 Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)> 80026361856 00 80026361856 bytes, 156301488 sectors, 1 distinct values seen No sectors have printable text</hex></count></hex></count>	
Results:	Assertion & Expected Result	Actual Result
	FMP-CA-01 Visible sectors overwritten	as expected
Analysis:	Expected results achieved	

4.2.2 FMP-01-ATA48

Test Case FMP-	01-ATA48 Voom HardCopy II Version 1-11		
Case Summary:	FMP-01. Overwrite visible sectors using WRITE commands.		
Assertions:	FMP-CA-01 All visible sectors shall be overwritten with the specified		
	benign data.		
Tester Name:	Csr		
Analysis	Frank		
host:			
Test host:	None		
Test date:	Thu Jul 30 16:38:39 2009		
Test drive:	29-IDE		
Source Setup:	Initial setup size: 488397168 from total of 488397168 (with 0 hidden) IDE disk: Model (WDC WD2500JB-00GVC0) serial # (WD-WCAL78188039) Sector 0 is first sector with printable text ===================================		
	00000/000/01 00000000000))))))))))))))))		
	Totals for all sectors summary format: <count> <hex value=""> <(actual character if printable)> 488397168 00 488397168 20 () 237361023648 29 ()) 976794336 2F (/) 2735169210 30 (0) 1278997882 31 (1) 1192805876 32 (2) 933260747 33 (3) 905775911 34 (4) 805865997 35 (5) 749775664 36 (6) 718765480 37 (7) 716559080 38 (8) 707761849 39 (9) Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)> 250059350016 bytes, 488397168 sectors, 14 distinct values seen 488397168 sectors have printable text</hex></count></hex></count>		
Log Highlights:	Size after tool runs: 488397168 from total of 488397168 (with 0 hidden) Analysis of tool result Totals for all sectors summary format: <count> <hex value=""> <(actual character if printable)> 250059350016 00 Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)> 250059350016 00 250059350016 bytes, 488397168 sectors, 1 distinct values seen No sectors have printable text</hex></count></hex></count>		
Dag. 1 + 4	Described & Research Described Descr		
Results:	Assertion & Expected Result Actual Result		
	FMP-CA-01 Visible sectors overwritten as expected		
Analysis:	Expected results achieved		

4.2.3 FMP-01-SATA28

Test Case FMP-0	1-SATA28 Voom HardCopy II Version 1-11		
Case Summary:	FMP-01. Overwrite visible sectors using		
Assertions:	FMP-CA-01 All visible sectors shall be overwritten with the specified benign data.		
Tester Name:	Csr		
Analysis host:	Frank		
Test host:	None		
Test date:	Thu Jul 30 08:57:27 2009		
Test drive:	1C-SATA		
Source Setup:	Initial setup size: 234441648 from tota IDE disk: Model (WDC WD1200JD-00GBB0) se		
	Sector 0 is first sector with printable text		
	======== Start text =======		
	00000/000/01 000000000000		
	====== End text Sector 0 ======		
	1 <new line=""> character inserted for read</new>	dability	
	Totals for all sectors summary format: <count> <hex value=""> <(a. 234441648 00 113938640928 1C 468883296 2F (/) 1461085523 30 (0) 497617498 32 (2) 407041791 33 (3) 376075228 35 (5) 347651457 36 (6) 332765657 38 (8) 332658242 39 (9) Totals for non-ASCII sectors summary format: <count> <hex value=""> <(a. 120034123776 bytes, 234441648 sectors, 234441648 sectors have printable text</hex></count></hex></count>	234441648 20 () 678339301 31 (1) 391715334 34 (4) 332766225 37 (7) ctual character if printable)>	
Log Highlights:	Size after tool runs: 234441648 from total of 234441648 (with 0 hidden) Analysis of tool result Totals for all sectors summary format: <count> <hex value=""> <(actual character if printable)> 120034123776 00 Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)> 120034123776 00 120034123776 bytes, 234441648 sectors, 1 distinct values seen No sectors have printable text</hex></count></hex></count>		
Results:	Assertion & Expected Result FMP-CA-01 Visible sectors overwritten	Actual Result as expected	
Analysis:	Expected results achieved		
111141 Y 0 1 0 .	Impededa resures acintevea		

4.2.4 FMP-01-SATA48

Test Case FMP-01-SATA48 Voom HardCopy II Version 1-11			
Case Summary:	FMP-01. Overwrite visible sectors using WRITE commands.		
Assertions:	FMP-CA-01 All visible sectors shall be overwritten with t	the specified	
	benign data.		
Tester Name:	Csr		
Analysis	Frank		
host:			
Test host:	None		
Test date:	Tue Jul 28 15:50:27 2009		
Test drive:	21-LAP		
Source Setup:	Initial setup size: 312581808 from total of 312581808 (wi IDE disk: Model (ST9160310AS) serial # (5SV092JK) Sector 0 is first sector with printable text	th 0 hidden)	
	======== Start text ========		
	00000/000/01 0000000000000!!!!!!!!!!!!!!	1111	
	111111111111111111111111111111111111111		
	====== End text Sector 0 =======		
	9 <new line=""> characters inserted for readability</new>		
	Totals for all sectors		
	summary format: <count> <hex value=""> <(actual character if 312581808 00 312581808 20 () 151914758688 21 (625163616 2F (/) 1850492169 30 (0) 906528227 31 (696435016 32 (2) 541016511 33 (3) 522787395 34 (</hex></count>	(!) (1)	
	514450557 35 (5) 478352540 36 (6) 458495114 37 (
	458481159 38 (8) 449761088 39 (9)	· ,	
	Totals for non-ASCII sectors		
	summary format: <count> <hex value=""> <(actual character if</hex></count>	printable)>	
	160041885696 bytes, 312581808 sectors, 14 distinct values 312581808 sectors have printable text	s seen	
Log Highlights:	Size after tool runs: 312581808 from total of 312581808 (Analysis of tool result Totals for all sectors	(with 0 hidden)	
	summary format: <count> <hex value=""> <(actual character if</hex></count>	printable)>	
	160041885696 00	1	
	Totals for non-ASCII sectors		
	summary format: <count> <hex value=""> <(actual character if printable)> 160041885696 00</hex></count>		
	160041885696 bytes, 312581808 sectors, 1 distinct values	seen	
	No sectors have printable text		
Dec 11			
Results:	Assertion & Expected Result Actual Result		
	FMP-CA-01 Visible sectors overwritten as expected		
Analysis:	Expected results achieved		

4.2.5 FMP-03-DCO

Test Case FMI	P-03-DCO Voom HardCopy II Version 1-11				
Case	FMP-03. Overwrite hidden sectors using	WRITE commands.			
Summary:					
Assertions:	FMP-CA-01 All visible sectors shall be data. FMP-AO-01 If there is a hidden area pre	sent and the tool supports			
	overwriting sectors contained in a hidden in the hidden area shall be overwritten FMP-AO-02 A hidden area may optionally be a second or the second of the se	with the specified benign data.			
Tester Name:	Csr	<u>, </u>			
Analysis host:	Frank				
Test host:	None				
Test date:	Mon Aug 3 11:16:26 2009				
Test drive:	24-LAP				
Source Setup:	Initial setup size: 7814016 from total of IDE disk: Model (FUJITSU MHW2040BH) ser				
	Sector 0 is first sector with printable ====================================	text			
	00000/000/01 0000000000000s\$				
	\$	\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$			
	\$	\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$\$			
	\$				
	\$				
	15628032 2F (/) 70255912 30 (0) 14411539 32 (2) 12727549 33 (3) 10812309 35 (5) 9905387 36 (6)	3797611776 24 (\$) 15793560 31 (1) 12384049 34 (4) 9216849 37 (7)			
	8259015 38 (8) 8142183 39 (9) Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)></hex></count>				
	4000776192 bytes, 7814016 sectors, 14 distinct values seen 7814016 sectors have printable text				
Log Highlights:	Size after tool runs: 78140160 from total Analysis of tool result Totals for all sectors				
	summary format: <count> <hex value=""> <(actual character if printable)> 40007761920 00 Totals for non-ASCII sectors</hex></count>				
	summary format: <count> <hex value=""> <(a 40007761920 00</hex></count>	-			
	40007761920 bytes, 78140160 sectors, 1 No sectors have printable text	distinct values seen			
Results:	Assertion & Expected Result	Actual Result			
	FMP-CA-01 Visible sectors overwritten	as expected			
	FMP-AO-01 Hidden sectors overwritten	as expected			
	FMP-AO-02 Hidden area final state is	removed			
Analysis:	Expected results achieved				

4.2.6 FMP-03-DCO+HPA

Test Case FMP	-03-DCO+HPA Voom HardCopy II Version 1-1	.1	
Case	FMP-03. Overwrite hidden sectors using N		
Summary:			
Assertions:	FMP-CA-01 All visible sectors shall be	overwritten with the specified benign	
	data.		
	FMP-AO-01 If there is a hidden area present and the tool supports		
	overwriting sectors contained in a hidden area, then all sectors contained		
	in the hidden area shall be overwritten with the specified benign data.		
	FMP-AO-02 A hidden area may optionally be removed from the storage device.		
Tester	csr		
Name:			
Analysis	frank		
host:			
Test host:	none		
Test date:	Wed Aug 5 13:43:20 2009		
Test drive:	2A-IDE		
Source	Size with DCO: 480234752 245.88 GB (10000000 sectors in DCO)		
Setup:	Size with HPA: 465234752 238.20 GB (1500		
	Initial setup size: 465234752 from total		
	IDE disk: Model (Maxtor 7Y250P0) serial		
	IDD disk: Model (Maxeol /125010) Selial	(100101111)	
	Sector 0 is first sector with printable	text	
	======================================	CCAC	
	00000/000/01 000000000000*********	*****	

	========= End text Sector 0 =========		
	9 <new line=""> characters inserted for readability</new>		
	Totals for all sectors		
	summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	480234752 00 480234752 20 () 233394089472 2A (*)		
	960469504 2F (/) 2688406892 30 (0) 1262709725 31 (1)		
	1176182573 32 (2) 913616218 33 (3) 886219489 34 (4)		
	794684344 35 (5) 739530848 36 (6) 709039708 37 (7)		
	699165650 38 (8) 695609097 39 (9)		
	Totals for non-ASCII sectors		
	summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	045000102004		
	245880193024 bytes, 480234752 sectors, 14 distinct values seen		
	480234752 sectors have printable text		
Log	Size after tool runs: 490234752 from to	tal of 490234752 (with 0 hidden)	
Highlights:	Analysis of tool result		
	Totals for all sectors		
	summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	251000193024 00		
	Totals for non-ASCII sectors		
	Totals for non-ASCII sectors summary format: <count> <hex value=""> <(ac</hex></count>	ctual character if printable)>	
		ctual character if printable)>	
	summary format: <count> <hex value=""> <(ac 251000193024 00</hex></count>	-	
	<pre>summary format: <count> <hex value=""> <(ac</hex></count></pre>	-	
	summary format: <count> <hex value=""> <(ac 251000193024 00</hex></count>	-	
	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors,</hex></count>	-	
	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors,</hex></count>	-	
Results:	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors,</hex></count>	-	
Results:	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors, No sectors have printable text</hex></count>	1 distinct values seen	
Results:	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors, No sectors have printable text Assertion & Expected Result</hex></count>	1 distinct values seen Actual Result	
Results:	summary format: <count> <hex value=""> <(ac 251000193024 00 251000193024 bytes, 490234752 sectors, No sectors have printable text Assertion & Expected Result FMP-CA-01 Visible sectors overwritten</hex></count>	1 distinct values seen Actual Result as expected	

11

4.2.7 FMP-03-HPA

Test Case FM	P-03-HPA Voom HardCopy II Version 1-11		
Case Summary:	FMP-03. Overwrite hidden sectors using	WRITE commands.	
Assertions:	FMP-CA-01 All visible sectors shall be overwritten with the specified benign data.		
	FMP-AO-01 If there is a hidden area present and the tool supports overwriting sectors contained in a hidden area, then all sectors contained in the hidden area shall be overwritten with the specified benign data.		
	FMP-AO-02 A hidden area may optionally be removed from the storage device.		
Tester Name:	csr		
Analysis host:	frank		
Test host:	none		
Test date:	Tue Aug 4 13:35:18 2009		
Test drive:	53-IDE		
Source Setup:	IDE disk: Model (WDC WD1600JB-00GVC0) s		
	Sector 0 is first sector with printable	text	
	00000/000/01 00000000000ssssssssssssssss		
	\$		
	\$		
	\$		
	SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS		
	Totals for all sectors		
	summary format: <count> <hex value=""> <(a 312581808 00 312581808 20 () 1850492169 30 (0) 906528227 31 (1)</hex></count>	625163616 2F (/) 696435016 32 (2)	
	541016511 33 (3) 522787395 34 (4) 514450557 35 (5) 478352540 36 (6) 458495114 37 (7) 458481159 38 (8) 449761088 39 (9) 151914758688 53 (S)		
	Totals for non-ASCII sectors summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	160041885696 bytes, 312581808 sectors, 14 distinct values seen 312581808 sectors have printable text		
Log	Size after tool runs: 312581808 from total of 312581808 (with 0 hidden) Analysis of tool result		
Highlights:	Totals for all sectors summary format: <count> <hex value=""> <(actual character if printable)></hex></count>		
	160041885696 00 Totals for non-ASCII sectors		
	summary format: <count> <hex value=""> <(actual character if printable)> 160041885696 00</hex></count>		
	160041885696 bytes, 312581808 sectors, 1 distinct values seen No sectors have printable text		
Dogul+ - :	Decembing & Remontal Page 31	Partial Paralle	
Results:	Assertion & Expected Result	Actual Result	
	FMP-CA-01 Visible sectors overwritten FMP-AO-01 Hidden sectors overwritten	as expected as expected	
	FMP-AO-02 Hidden area final state is	removed	
Analysis:	Expected results achieved	25	

This page intentionally left blank.

About the National Institute of Justice

NIJ is the research, development, and evaluation agency of the U.S. Department of Justice. NIJ's mission is to advance scientific research, development, and evaluation to enhance the administration of justice and public safety. NIJ's principal authorities are derived from the Omnibus Crime Control and Safe Streets Act of 1968, as amended (see 42 U.S.C. §§ 3721–3723).

The NIJ Director is appointed by the President and confirmed by the Senate. The Director establishes the Institute's objectives, guided by the priorities of the Office of Justice Programs, the U.S. Department of Justice, and the needs of the field. The Institute actively solicits the views of criminal justice and other professionals and researchers to inform its search for the knowledge and tools to guide policy and practice.

Strategic Goals

NIJ has seven strategic goals grouped into three categories:

Creating relevant knowledge and tools

- 1. Partner with State and local practitioners and policymakers to identify social science research and technology needs.
- 2. Create scientific, relevant, and reliable knowledge—with a particular emphasis on terrorism, violent crime, drugs and crime, cost-effectiveness, and community-based efforts—to enhance the administration of justice and public safety.
- 3. Develop affordable and effective tools and technologies to enhance the administration of justice and public safety.

Dissemination

- 4. Disseminate relevant knowledge and information to practitioners and policymakers in an understandable, timely, and concise manner.
- 5. Act as an honest broker to identify the information, tools, and technologies that respond to the needs of stakeholders.

Agency management

- 6. Practice fairness and openness in the research and development process.
- 7. Ensure professionalism, excellence, accountability, cost-effectiveness, and integrity in the management and conduct of NIJ activities and programs.

Program Areas

In addressing these strategic challenges, the Institute is involved in the following program areas: crime control and prevention, including policing; drugs and crime; justice systems and offender behavior, including corrections; violence and victimization; communications and information technologies; critical incident response; investigative and forensic sciences, including DNA; less-than-lethal technologies; officer protection; education and training technologies; testing and standards; technology assistance to law enforcement and corrections agencies; field testing of promising programs; and international crime control.

In addition to sponsoring research and development and technology assistance, NIJ evaluates programs, policies, and technologies. NIJ communicates its research and evaluation findings through conferences and print and electronic media.

To find out more about the National Institute of Justice, please visit:

National Institute of Justice Website

or contact:

National Criminal Justice Reference Service P.O. Box 6000 Rockville, MD 20849–6000 800–851–3420 National Criminal Justice Reference Service Website