Unique Payload Services

Remote environmental sensing is only part of the GOES-R mission. The satellites will also provide unique capabilities to relay data directly to users to meet critical needs.

Data Collection System (DCS)



Remote Automated Weather Stations transmitting to GOES

DCS is a satellite relay system used to collect information from Earth-based data collection platforms that transmit in-situ environmental sensor data from more than 20,000 platforms across the hemisphere.

GOES Rebroadcast (GRB)


GRB is the primary space relay of Level 1b products, replacing the GVAR (GOES VARiable) service. GRB will provide full resolution, calibrated, navigated, near real-time direct broadcast data.

High Rate Information Transmission/Emergency Managers Weather Information Network (HRIT/EMWIN)

EMWIN is a direct service that provides users with weather forecasts, warnings, graphics and other information directly from the National Weather Service (NWS) in near real-time. HRIT service is a new high data rate (400 Kpbs) version of today's LRIT (Low Rate Information Transmission), broadcasting GOES-R satellite imagery and selected products to remotely-located user terminals.

Search and Rescue Satellite Aided Tracking (SARSAT)

The SARSAT system detects and locates mariners, aviators and other recreational users in distress. GOES-R will continue the legacy function of the SARSAT system on board NOAA's GOES satellites. This system uses a network of satellites to



Emergency Beacons


quickly detect and locate signals from emergency beacons onboard aircraft, vessels and from handheld personal locator beacons. The GOES-R SARSAT transponder will operate with a lower uplink power than the current system (32 bBm), enabling GOES-R to detect weaker beacon signals.

System Architecture

Ground support is critical to the GOES-R mission. The GOES-R ground system will operate the satellites, receive data from the spacecraft and generate and distribute real-time GOES-R data products. The ground system will operate from two primary locations: the NOAA Satellite Operations Facility (NSOF) in Suitland, Md., and the Wallops Command and Data Acquisition Center (WCDAS) at Wallops, Va. A third facility in Fairmont, W. Va. will serve as the Consolidated Backup in case of a systems or communications failure at either or both NSOF and WCDAS.



The GOES-R Series Program is a collaborative effort between NOAA and NASA to develop, deploy and operate the satellites. The GOES-R series is a four-satellite program (GOES-R, S, T and U) that will extend the availability of the operational GOES satellite system through 2036. Once operational, GOES-R will be known as GOES-16.



GOES fleet in the GOES-R era

nesdis.goesr@noaa.gov www.goes-r.gov www.facebook.com/GOESRsatellite






Why GOES-R?


- Improved hurricane track and intensity forecasts
- Increased thunderstorm and tornado warning lead time
- Improved aviation flight route planning
- Improved air quality warnings and alerts
- Better data for long-term climate variability studies
- Improved solar flare warnings for communications and navigation disruptions
- More accurate monitoring of energetic particles responsible for radiation hazards to humans and spacecraft
- Better monitoring of space weather to improve geomagnetic storm forecasting






Visual and Infrared Imagery

Lightning Mapping





Solar Imaging Space Weather Monitoring


GOES-R Instruments: Earth, Solar and Space Weather

Advanced Baseline Imager (ABI)

ABI is the primary instrument on board GOES-R for imaging Earth's weather, climate, oceans and the environment. ABI will view the Earth with 16 spectral bands (compared to five on current GOES) and will provide three times



more spectral information, four times the spatial resolution and more than five times faster coverage than the current system.



Geostationary Lightning Mapper (GLM)



GLM will be the first-ever operational lightning mapper flown from geostationary orbit. GLM maps total lightning (in-cloud and cloud-to-ground) activity continuously day and night over the Americas and adjacent ocean regions. Research and testing has demonstrated GLM's potential for improvement in tornado warning lead time and false alarm rate reduction.

Space Environment In-Situ Suite (SEISS)

SEISS is an array of sensors that will monitor proton, electron and heavy ion fluxes at geosynchronous orbit. Information provided by SEISS will be used for assessing radiation hazards to astronauts and satellites and to warn of high flux events, mitigating damage to radio communication.

Magnetometer

The Magnetometer will provide measurements of the space environment magnetic field that controls charged particle dynamics in the outer region of the magnetosphere. These particles can be dangerous to spacecraft and human spaceflight. The geomagnetic field measurements will provide alerts and warnings to satellite operators and power utilities.

Extreme Ultraviolet and X-Ray Irradiance Sensors (EXIS)



EXIS detects and monitors solar irradiance in the upper atmosphere. The X-Ray Sensor monitors solar flares that can disrupt communications and degrade navigational accuracy, affecting satellites, astronauts, high latitude airline passengers and power grid performance.

The Extreme Ultraviolet Sensor monitors solar variations that directly affect satellite drag/tracking and ionospheric changes, which impact communications and navigation operations.

Solar Ultraviolet Imager (SUVI)

SUVI is a telescope that observes and characterizes coronal holes, solar flares, and coronal mass ejection source regions. SUVI data enables improved forecasting of space weather and early warnings of possible impacts to the Earth environment,

including disruption of power utilities and communication and navigation systems as well as possible damage to orbiting satellites and the International Space Station.

