

9.9.5 Pasta Manufacturing

9.9.5.1 General¹⁻²

Although pasta products were first introduced in Italy in the 13th century, efficient manufacturing equipment and high-quality ingredients have been available only since the 20th century. Prior to the industrial revolution, most pasta products were made by hand in small shops. Today, most pasta is manufactured by continuous, high capacity extruders, which operate on the auger extrusion principle in which kneading and extrusion are performed in a single operation. The manufacture of pasta includes dry macaroni, noodle, and spaghetti production.

9.9.5.2 Process Description¹⁻²

Pasta products are produced by mixing milled wheat, water, eggs (for egg noodles or egg spaghetti), and sometimes optional ingredients. These ingredients are typically added to a continuous, high capacity auger extruder, which can be equipped with a variety of dies that determine the shape of the pasta. The pasta is then dried and packaged for market.

Raw Materials —

Pasta products contain milled wheat, water, and occasionally eggs and/or optional ingredients. Pasta manufacturers typically use milled durum wheat (semolina, durum granulars, and durum flour) in pasta production, although farina and flour from common wheat are occasionally used. Most pasta manufacturers prefer semolina, which consists of fine particles of uniform size and produces the highest quality pasta product. The water used in pasta production should be pure, free from off-flavors, and suitable for drinking. Also, since pasta is produced below pasteurization temperatures, water should be used of low bacterial count. Eggs (fresh eggs, frozen eggs, dry eggs, egg yolks, or dried egg solids) are added to pasta to make egg noodles or egg spaghetti and to improve the nutritional quality and richness of the pasta. Small amounts of optional ingredients, such as salt, celery, garlic, and bay leaves, may also be added to pasta to enhance flavor. Disodium phosphate may be used to shorten cooking time. Other ingredients, such as gum gluten, glyceryl monostearate, and egg whites, may also be added. All optional ingredients must be clearly labeled on the package.

Wheat Milling —

Durum wheat is milled into semolina, durum granular, or durum flour using roll mills. Semolina milling is unique in that the objective is to prepare granular middlings with a minimum of flour production. Grain milling is discussed in AP-42 Section 9.9.1, Grain Elevators and Processes. After the wheat is milled, it is mixed with water, eggs, and any other optional ingredients.

Mixing —

In the mixing operation, water is added to the milled wheat in a mixing trough to produce dough with a moisture content of approximately 31 percent. Eggs and any optional ingredients may also be added. Most modern pasta presses are equipped with a vacuum chamber to remove air bubbles from the pasta before extruding. If the air is not removed prior to extruding, small bubbles

will form in the pasta which diminish the mechanical strength and give the finished product a white, chalky appearance.

Extruding —

After the dough is mixed, it is transferred to the extruder. The extrusion auger not only forces the dough through the die, but it also kneads the dough into a homogeneous mass, controls the rate of production, and influences the overall quality of the finished product. Although construction and dimension of extrusion augers vary by equipment manufacturers, most modern presses have sharp-edged augers that have a uniform pitch over their entire length. The auger fits into a grooved extrusion barrel, which helps the dough move forward and reduces friction between the auger and the inside of the barrel. Extrusion barrels are equipped with a water cooling jacket to dissipate the heat generated during the extrusion process. The cooling jacket also helps to maintain a constant extrusion temperature, which should be approximately 51°C (124°F). If the dough is too hot (above 74°C [165°F]), the pasta will be damaged.

Uniform flow rate of the dough through the extruder is also important. Variances in the flow rate of the dough through the die cause the pasta to be extruded at different rates. Products of nonuniform size must be discarded or reprocessed, which adds to the unit cost of the product. The inside surface of the die also influences the product appearance. Until recently, most dies were made of bronze, which was relatively soft and required repair or periodic replacement. Recently, dies have been improved by fitting the extruding surface of the die with Teflon® inserts to extend the life of the dies and improve the quality of the pasta.

Drying —

Drying is the most difficult and critical step to control in the pasta production process. The objective of drying is to lower the moisture content of the pasta from approximately 31 percent to 12 to 13 percent so that the finished product will be hard, retain its shape, and store without spoiling. Most pasta drying operations use a preliminary drier immediately after extrusion to prevent the pasta from sticking together. Predrying hardens the outside surface of the pasta while keeping the inside soft and plastic. A final drier is then used to remove most of the moisture from the product.

Drying temperature and relative humidity increments are important factors in drying. Since the outside surface of the pasta dries more rapidly than the inside, moisture gradients develop across the surface to the interior of the pasta. If dried too quickly, the pasta will crack, giving the product a poor appearance and very low mechanical strength. Cracking can occur during the drying process or as long as several weeks after the product has left the drier. If the pasta is dried too slowly, it tends to spoil or become moldy during the drying process. Therefore, it is essential that the drying cycle be tailored to meet the requirements of each type of product. If the drying cycle has been successful, the pasta will be firm but also flexible enough so that it can bend to a considerable degree before breaking.

Packaging —

Packaging keeps the product free from contamination, protects the pasta from damage during shipment and storage, and displays the product favorably. The principal packaging material for noodles is the cellophane bag, which provides moisture-proof protection for the product and is used easily on automatic packaging machines, but is difficult to stack on grocery shelves. Many manufacturers utilize boxes instead of bags to package pasta because boxes are easy to stack, provide good protection for fragile pasta products, and offer the opportunity to print advertising that is easier to read than on bags.

9.9.5.3 Emissions and Controls

Air emissions may arise from a variety of sources in pasta manufacturing. Particulate matter (PM) emissions result mainly from solids handling and mixing. For pasta manufacturing, PM emissions occur during the wheat milling process, as the raw ingredients are mixed, and possibly during packaging. Emission sources associated with wheat milling include grain receiving, precleaning/handling, cleaning house, milling, and bulk loading. Applicable emission factors for these processes are presented in AP-42 Section 9.9.1, Grain Elevators and Processes. There are no data for PM emissions from mixing of ingredients or packaging for pasta production.

Volatile organic compound (VOC) emissions may potentially occur at almost any stage in the production of pasta, but most usually are associated with thermal processing steps, such as pasta extruding or drying. No information is available on any VOC emissions due to the heat generated during pasta extrusion or drying.

Control of PM emissions from pasta manufacturing is similar to that discussed in AP-42 Section 9.9.1, Grain Elevators and Processes. Because of the operational similarities, emission control methods used in grain milling and processing plants are similar to those in grain elevators. Cyclones or fabric filters are often used to control emissions from the grain handling operations (e. g., unloading, legs, cleaners, etc.) and also from other processing operations. Fabric filters are used extensively in flour mills. However, certain operations within milling operations are not amenable to the use of these devices and alternatives are needed. Wet scrubbers, for example, may be applied where the effluent gas stream has a high moisture content.

References for Section 9.9.5

1. D. E. Walsh and K. A. Gilles, "Pasta Technology", *Elements Of Food Technology*, N. W. Desrosier, Editor, AVI Publishing Company, Inc., 1977.
2. *1992 Census Of Manufactures: Miscellaneous Food And Kindred Products*, Preliminary Report Industry Series, U. S. Department of Commerce, Bureau of Census, Issued August 1994.